



(86) Date de dépôt PCT/PCT Filing Date: 2016/04/06

(87) Date publication PCT/PCT Publication Date: 2016/10/27

(45) Date de délivrance/Issue Date: 2022/08/23

(85) Entrée phase nationale/National Entry: 2017/10/19

(86) N° demande PCT/PCT Application No.: US 2016/026128

(87) N° publication PCT/PCT Publication No.: 2016/171903

(30) Priorités/Priorities: 2015/04/21 (US62/150,572);
2016/03/21 (US15/075,271)

(51) Cl.Int./Int.Cl. *A22B 5/16* (2006.01),
A22C 25/08 (2006.01), *A22C 25/12* (2006.01),
A22C 25/17 (2006.01), *A23N 7/00* (2006.01)


(72) Inventeurs/Inventors:
BERGMAN, MATTHEW A., US;
CATE, STEPHEN H., US;
GROSS, JOSEPH A., US;
HART, COLIN R., US;
JOHNSON, WILLIAM A., US;
ROHE, RYAN J., US

(73) Propriétaire/Owner:
MAREL MEAT PROCESSING INC., US

(74) Agent: MARKS & CLERK

(54) Titre : DISPOSITIF DE PELAGE AUTOMATIQUE

(54) Title: AUTOMATIC SKINNING DEVICE



(57) Abrégé/Abstract:

An automatic skinning mechanism having an inlet conveyor, a take away conveyor, a skinning mechanism and a hold down mechanism that removes pressure from a food product as the skinning mechanism begins skinning food product.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(10) International Publication Number
WO 2016/171903 A1

(43) International Publication Date
27 October 2016 (27.10.2016)

(51) International Patent Classification:

A22B 5/16 (2006.01) A22C 25/08 (2006.01)
A22C 25/17 (2006.01) A22C 25/12 (2006.01)

(21) International Application Number:

PCT/US2016/026128

(22) International Filing Date:

6 April 2016 (06.04.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/150,572 21 April 2015 (21.04.2015) US
15/075,271 21 March 2016 (21.03.2016) US

(71) Applicant: **MAREL MEAT PROCESSING INC.**
[US/US]; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US).

(72) Inventors: **BERGMAN, Matthew A.**; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US). **CATE, Stephen H.**; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US). **GROSS, Joseph A.**; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US). **HART, Colin R.**; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US). **JOHNSON, William A.**; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US). **ROHE, Ryan J.**; 2425 Hubbell Avenue, Des Moines, Iowa 50317 (US).

(74) Agents: **ZARLEY, Timothy J.** et al.; Zarley Law Firm, P.L.C., Capital Square, 400 Locust Street, Suite 200, Des Moines, Iowa 50309-2350 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH,

[Continued on next page]

(54) Title: AUTOMATIC SKINNING DEVICE




FIG. 1

(57) Abstract: An automatic skinning mechanism having an inlet conveyor, a take away conveyor, a skinning mechanism and a hold down mechanism that removes pressure from a food product as the skinning mechanism begins skinning food product.

WO 2016/171903 A1

GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT,
LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,

SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

TITLE: AUTOMATIC SKINNING DEVICE

BACKGROUND OF THE INVENTION

This invention is directed toward a device for removing skin from food products and
5 more particularly to a device for removing skin from delicate food products such as fish.

In the meat processing industry it is desirable to remove the skin from meat parts such
as fish fillets. Today this is done by using a knife or one of several conveyor fed skinning
machines. Removing skin with a knife may cause lacerations or repetitive motion injuries.
Also, skinning with a knife typically results in poor yields. Alternatively skinning machines
10 often require feeding fish fillets tail first for good results. This requires turning fish either
manually or automatically to accommodate tail first skinning which can result in damage to
fish fillets. It is desirable that the fillets be fed head first in some cases to match the rest of the
production line. Furthermore, it is desirable to have a machine that can easily or automatically
be adjusted to accommodate demands for different skin thicknesses and/or product
15 appearances.

Skinning machines fed with a conveying system normally require some type of
opening bite at the skinning mechanism to start the meat product. To do this, most
manufacturers take a thicker cut at the start of the skinning action by moving the skinning
mechanism out and/or in and/or up and down. The other method used is to rotate the skinning
20 mechanism around the product pulling roller and pinch the leading edge of the product. In all
cases a hold-down mechanism is used to keep the product in place, during the skinning.
Typical hold-down devices include individual rubber (nitrile) rollers, conveyor belts over the
infeed conveyor and skinning mechanism or delrin rollers only over the skinning mechanism.
Each of these methods can be disadvantageous. First, they may not provide even pressure
25 over products that have varying shapes front to back or side to side. Second, these devices
may cause damage and yield loss due to their aggressive nature. Particularly with fish such as
salmon, constant pressure causes gapping or separation of the meat fibers. In fact, once the
skinning has begun, holding down on the product is not necessary or desirable in some cases.

Therefore, an objective of the present invention is to provide a method and apparatus
30 that can skin meat products such as fish fillets either head first or tail first with minimal skin
patches.

Another objective of the present invention is to provide a hold-down system that

provides sufficient pressure over the varying thicknesses of a single piece of product.

A still further objective of the present invention is to provide linking the skinning mechanism with the hold-down device to reduce adjustments.

5 A further objective of the present invention is to provide a skinning mechanism and a hold-down device where the hold-down device follows the position of the skinning mechanism as it moves in and out of its opening bite and/or height adjustments.

Another objective of the present invention is to remove all hold down pressure on the food product to ensure that damage to the product via hold down force is eliminated.

10 Yet another objective of the present invention is to adapt this method to either a dual lane or single lane skinning device.

Also, an objective other the present invention is to be easily and/or automatically adjusted for different skinning thicknesses or product requirements.

15 Finally, it is an objective of the present invention to use this method to eliminate skinning with a knife and the undesirable impact that knife skinning has on workers.

These and other objectives will be apparent to one of ordinary skill based upon the following written description and drawings.

SUMMARY OF THE INVENTION

20 An automatic skinning device having an inlet conveyor, a hold down mechanism, a skinning mechanism, and a take away conveyor. The hold down mechanism is linked to the skinning mechanism such that the hold down mechanism follows the movement of the skinning mechanism during the opening bite and/or height adjustments and then removes pressure from a food product once the skinning of the food product begins.

25 The hold down mechanism includes at least one disc having a plurality of deformable curved spokes that extend from a central opening to an outer perimeter. The hold down mechanism provides a consistent pressure to a food product without the presence of a gap between the hold down mechanism and the food product.

30 Accordingly, in one aspect there is provided an automatic skinning device, comprising: an infeed conveyor and a takeaway conveyor; a skinning mechanism positioned between the infeed conveyor and the takeaway conveyor; and a hold down mechanism positioned above at least a portion of the infeed conveyor and the skinning mechanism, wherein the hold down mechanism is linked to the skinning mechanism such that the hold

down mechanism is configured to follow the position of the skinning mechanism as the skinning mechanism moves position, and wherein the hold down mechanism is configured to remove pressure from a food product as the skinning mechanism begins skinning the food product.

- 5 In another aspect, there is provided a method of skinning a food product, comprising the steps of: placing the food product on an infeed conveyor such that a head portion of the food product is ahead of a tail portion; transporting the food product toward a skinning mechanism; and skinning the food product with the skinning mechanism, providing consistent pressure to the food product having various thickness without gaps with a hold
10 down mechanism, and raising the hold mechanism to remove all pressure from the food product when the skinning mechanism moves from an open bite position to a skinning position.

BRIEF DESCRIPTION OF THE DRAWINGS

- 15 Fig. 1 is a side sectional view of an automatic skinning device;
Fig. 2 is a perspective view of an automatic skinning device;
Fig. 3 is a side sectional view of an automatic skinning device; and
Fig. 4 is an end view of an automatic skinning device.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to the Figures, an automatic skinning device 10 includes an infeed conveyor 12, a hold down mechanism 14, a skinning mechanism 16, and an exit or take-away conveyor 18. The infeed conveyor 12 has a continuous belt 20 mounted about
5 rollers/pulleys 22

The skinning mechanism 16 has a shoe 28 with an arcuate surface that receives a tooth roll 30. A blade holder 32 is connected to the top of the shoe 28 and the blade holder 32 with an edge adjacent the outer circumference of the tooth roll 30.

Moveably positioned above a portion of the skinning mechanism is the hold down
10 mechanism 14. The hold down mechanism 14 includes one, and preferably a plurality of discs 36, mounted to a rotatable shaft 38. The number of discs 36 used is determined by the width of a food product 40. The discs 36 preferably are made of a polymer material that has a diameter that varies based upon the type of food product 40. Each disc 36 has a
15 continuous outer perimeter 42 and a plurality of arcuate spokes 44 that extend between the outer perimeter 42 and a central opening 46 of the disc 36. The discs 36 are closely spaced and/or engage one another such that when engaged by a food product 40 the discs deform to provide a consistent pressure to the food product 40 of varying thickness without gaps.

The rotatable shaft 38 is mounted to a support arm 48 that preferably extends upwardly and rearwardly of the discs 36 and then curves downwardly toward a
20 connecting end 50. The connecting end 50 is pivotally connected to a plate 52 that is attached to the skinning mechanism 16. A pneumatic piston 54 is connected to and extends between the support arm 48 and plate 52.

Positioned adjacent the infeed conveyor 12, upstream of the hold down mechanism 14 and the skinning mechanism 16 is a sensor 56 that detects the presence of a food product
25 40. The sensor 56 is connected to a computer 58 that is also connected to a source of pressurized air 60 that extends or contracts piston 54.

Downstream of the skinning mechanism 16 and positioned to receive a skinned food product 40 is the exit or take-away conveyor 18. The take-away conveyor 18 has a continuous belt 62 mounted about rollers or pulleys 64.

30 In operation, the food product 40 is placed on the infeed conveyor 12 with the head portion ahead of the tail portion. As the infeed conveyor 12 transports the food product 40

toward the skinning mechanism 16, the food product 40 engages the hold down mechanism 14 which exerts a consistent pressure against the food product 40 without the presence of a gap between the hold down mechanism 14 and the food product 40. The hold down mechanism 14 and the skinning mechanism 16 are linked by a support arm 48 and a plate 52. As a result, 5 the hold down mechanism 14 follows the position of the skinning mechanism 16 as the skinning mechanism 16 moves in and out of its opening bite.

Once the skinning mechanism 16 begins skinning the food product 40, the open bite moves from open to skinning position and the hold down mechanism 14 is raised removing all hold-down pressure from the food product 40 to ensure that damage to the food product is 10 eliminated. To move the skinning mechanism and the hold down mechanism 14, a signal is sent from sensor 56 to computer 58. The computer 58 calculates when skinning begins based upon the speed of conveyor 12 and the distance of the sensor 56 from the skinning mechanism 16. The timing of the movement and opening bite can be altered to maximize yield based on a variable profile of a leading edge of the food product. This can be done either manually by an 15 operator or electronically using electronic means of measurements. The computer 58 sends a signal actuating pressurized air to activate piston 54. The piston 54 retracts which causes support arm 48 to rotate upwardly in relation to plate 52 at connection end 50.

The food product 40 is engaged by the tooth roll 30 and the blade 34 separates the skin from the meat or lean portion. The skin falls below the skinning device to a hopper or 20 conveyor while the lean portion is transported to the take away conveyor 18 for further processing. Once the food product 40 passes sensor 56 the computer activates cylinder 54 lowering the hold down mechanism 16. While a single lane device has been shown, two or more lanes are contemplated as well.

Thus, a skinning device has been disclosed that at the very least meets all the stated 25 objectives.

What is claimed is:

1. An automatic skinning device, comprising:
an infeed conveyor and a takeaway conveyor;
a skinning mechanism positioned between the infeed conveyor and the takeaway conveyor; and
a hold down mechanism positioned above at least a portion of the infeed conveyor and the skinning mechanism,
wherein the hold down mechanism is linked to the skinning mechanism such that the hold down mechanism is configured to follow the position of the skinning mechanism as the skinning mechanism moves position, and
wherein the hold down mechanism is configured to remove pressure from a food product as the skinning mechanism begins skinning the food product.
2. The skinning device of claim 1 wherein the hold down mechanism is configured to exert a consistent pressure against the food product without the presence of a gap between the hold down mechanism and the food product.
3. The skinning device of claim 1 or 2 wherein the hold down mechanism comprises at least one disc having a deformable curved spoke that extends from a central opening of the disc to an outer perimeter of the disc.
4. The skinning device of any one of claims 1 to 3 further comprising a sensor mounted adjacent the infeed conveyor that detects the presence of the food product and sends a signal to a computer that activates movement of the hold down mechanism and an opening bite of the skinning mechanism.
5. The skinning device of claim 4 wherein timing of the opening bite is adjusted manually.

6. A method of skinning a food product, comprising the steps of:
placing the food product on an infeed conveyor such that a head portion of the food product is ahead of a tail portion;
transporting the food product toward a skinning mechanism; and
skinning the food product with the skinning mechanism, providing consistent pressure to the food product having various thickness without gaps with a hold down mechanism, and
raising the hold mechanism to remove all pressure from the food product when the skinning mechanism moves from an open bite position to a skinning position.
7. The method of claim 6, further comprising the step of calculating when skinning begins based upon the speed of the conveyor and the distance of a sensor from the skinning mechanism.

1 / 4




FIG. 1

2/4




FIG. 2

3/4




FIG. 3

4 / 4




FIG. 4

