




(22) **Date de dépôt/Filing Date:** 2013/11/29
(41) **Mise à la disp. pub./Open to Public Insp.:** 2015/05/29
(45) **Date de délivrance/Issue Date:** 2016/04/05

(51) **Cl.Int./Int.Cl.** *E03F 5/14* (2006.01),
C02F 1/40 (2006.01), *E03F 5/16* (2006.01)
(72) **Inventeurs/Inventors:**
BIRD, ANDREW, CA;
POUPORE, TIMOTHY JAMES HENDRIE, CA;
ARMSTRONG, STEVE, CA;
WILSON, MICHAEL F., CA
(73) **Propriétaire/Owner:**
CANPLAS INDUSTRIES LTD., CA
(74) **Agent:** PIASETZKI NENNIGER KVAS LLP

(54) **Titre :** ENSEMBLE DE CHICANE D'ENTREE POUR UN INTERCEPTEUR EN LIGNE
(54) **Title:** INLET BAFFLE ASSEMBLY FOR AN IN-LINE INTERCEPTOR



(57) **Abrégé/Abstract:**

There is an inlet baffle assembly for use in an in-line interceptor for separating FOG from wastewater and a method of cleaning the inlet baffle assembly without the need for removal from the interceptor. The inlet baffle assembly has an inlet baffle for the grease

(57) Abrégé(suite)/Abstract(continued):

collecting chamber of an in-line interceptor. The inlet baffle defines a flow channel through which influent enters the collecting chamber. The inlet baffle has a moveable section which is moveable between an open and a closed position. The inlet baffle assembly also has a flow control element associated with the inlet baffle to control the rate of flow of influent entering the flow channel when the moveable section is in the closed position. The flow control element is positioned to be accessible for cleaning when the moveable section is in the open position. After cleaning, the moveable section is moved into the closed position in order to facilitate fluid flowing through the inlet baffle assembly into the grease collecting chamber.

ABSTRACT OF THE DISCLOSURE

There is an inlet baffle assembly for use in an in-line interceptor for separating FOG from wastewater and a method of cleaning the inlet baffle assembly without the need for removal from the interceptor. The inlet baffle assembly has an inlet baffle for the grease collecting chamber of an in-line interceptor. The inlet baffle defines a flow channel through which influent enters the collecting chamber. The inlet baffle has a moveable section which is moveable between an open and a closed position. The inlet baffle assembly also has a flow control element associated with the inlet baffle to control the rate of flow of influent entering the flow channel when the moveable section is in the closed position. The flow control element is positioned to be accessible for cleaning when the moveable section is in the open position. After cleaning, the moveable section is moved into the closed position in order to facilitate fluid flowing through the inlet baffle assembly into the grease collecting chamber.

CANADA

PATENT APPLICATION

PIASETZKI NENNIGER KVAS LLP

File No.: CAN368/JTN

Title:

INLET BAFFLE ASSEMBLY FOR AN IN-LINE INTERCEPTOR

Inventor(s):

Andrew Bird

Timothy James Hendrie Poupore

Steve Armstrong

Michael F. Wilson

Title: INLET BAFFLE ASSEMBLY FOR AN IN-LINE INTERCEPTOR**FIELD OF THE INVENTION**

This invention relates generally to the field of wastewater
5 management and in particular to grease interceptors of the type which are
used on wastewater outflows from, for example, commercial food
establishments. Grease interceptors are typically used to prevent fats, oils
and grease ("FOG") from entering the sanitary sewage system. In
particular, this invention relates to an inlet baffle assembly for use in such
10 a grease interceptor.

BACKGROUND OF THE INVENTION

In many food preparation facilities, such as commercial kitchens
and restaurants, the sink is a major source of various types of food waste.
15 In the course of normal operation, liquid food wastes containing FOG are
inadvertently or intentionally introduced to the drainage system and, in
other cases, a mechanical chopper such as a garborator is used to shred
the food waste as it leaves the sink and enters the wastewater system.
Many food preparation establishments, such as commercial restaurants
20 and the like, have multiple sinks for such food waste disposal.

In the majority of jurisdictions, the disposal from commercial
kitchens of FOG and FOG laden debris into the sanitary sewage system
is prohibited. There are a number of reasons why this is so, including the
ability of those types of materials to clog or plug sanitary sewage systems
25 and the difficulty of adequately treating such materials in a sewage
treatment facility. Therefore, many jurisdictions require that these
materials be removed from the wastewater stream before permitting the
wastewater stream to be added to the sanitary sewer system.

As a result, devices known as grease interceptors have been
30 developed. These grease interceptors are connected to the wastewater
effluent stream from the food preparation kitchen or other facility and are

integrated with the building drain before entering the municipal system. The interceptor may commonly be located internally within the kitchen or externally adjacent to the building. The grease interceptors may take a number of forms, but typically consist of an in-line container which is
5 mounted on, at or below grade within the wastewater discharge system downstream of all of the discharging appliances and the like. The container includes features that are configured to allow fats, oils and grease to float to the surface of the container where they can be physically or mechanically removed for controlled disposal. In this way
10 these wastes are removed from the wastewater before the wastewater enters the sanitary sewer system.

Some examples of grease interceptors include the following:

United States Patent No. 2,003,140 issued May 28, 1935;
United States Patent No. 2,414,949 issued Jan. 28, 1947;
15 United States Patent No. 5,271,853 issued Dec. 21, 1993;
United States Patent No. 5,505,860 issued Apr. 9, 1996;
United States Patent No. 5,714,069 issued Feb. 3, 1998;
United States Patent No. 6,951,615 issued Oct. 4, 2005;
United States Patent No. 7,296,694 issued Nov. 20, 2007;
20 United States Patent No. 7,300,588 issued Nov. 27, 2007;
United States Patent No. 7,427,356 issued Sep. 23, 2008;
United States Patent No. 7,452,472 issued Nov. 18, 2008;
United States Patent No. 7,481,321 issued Jan. 27, 2009;
Canadian Patent No. 2,299,134 issued September 1, 2009;
25 Canadian Patent No. 2,672,865 issued July 31, 2012; and
Canadian Patent Application No. 2,769,800, published August 28,
2013.

While these different inventions all have various features and benefits, consistent challenges facing these interceptors, particularly for
30 larger interceptors, include: efficiently separating FOG from wastewater, controlling the rate of flow into the tank and clearing blockages within the

system. Some more developed solutions employ flow control devices to manage the flow rate of fluid entering the interceptors, but those devices are often at risk of being blocked by foreign object debris. Removable baffles have been used to attempt to allow cleaning within an interceptor, 5 but these prior art removable baffles often do not provide access to fluid channels within inlet assemblies which may contain blockages. In addition, these prior art removable baffles are not always accessible or are obstructed by external objects or elements within the operational environment. What is desired is a way to control the flow rate and type of 10 flow of fluid through a grease interceptor to effectively separate FOG from wastewater without excessively turbulent flow. What is also desired is a way to provide for the separation of FOG using a grease interceptor within which key functional elements can be cleaned, accessed and unblocked more easily.

15

SUMMARY OF THE INVENTION

The present invention is directed to an inlet baffle assembly for an inline interceptor. In particular, the inlet baffle assembly may be placed in a grease collecting chamber of an in-line wastewater grease interceptor. 20 The inlet baffle assembly should preferably allow for the efficient separation of FOG from wastewater. The inlet baffle assembly according to the present invention may also preferably control the rate of flow into the grease collecting chamber to try to achieve desirable flow rates which permit efficient FOG separation. The inlet baffle assembly may also 25 preferably provide a mechanism for clearing blockages within the upstream system without the need for any independent means of access in the unit or the associated drainage system. The inlet baffle assembly may also preferably accommodate the provision of alternate orifice plates so as to manage a range of flow rates as determined by the manufacturer.

30

In one preferred embodiment of the present invention there may be provided an inlet baffle assembly for use in an in-line interceptor used to

separate fats, oil and grease from wastewater. The interceptor may have a wastewater inlet opening through which influent will pass, an outflow opening and a grease collecting chamber hydraulically located between said inflow opening and said outflow opening. The inlet baffle assembly
5 may also have an inlet baffle sized and shaped to fit into the grease collecting chamber. The inlet baffle defines a flow channel connected to the inflow opening through which influent enters the grease collecting chamber. The inlet baffle may have a moveable section being moveable between an open position and a closed position. The inlet baffle assembly
10 may also have a flow control orifice associated with said inlet baffle to control the rate of influent flow entering the flow channel when the moveable section is in the closed position. The flow control element may be positioned so as to be accessible for cleaning and inspection when the moveable section is in the open position. The flow control element may
15 be used to limit the flow rate into the chamber to a flow rate that encourages good FOG separation, for example, by avoiding turbulent flow through the chamber.

In another embodiment of the present invention there is a method of cleaning an inlet baffle assembly in an in-line interceptor. The
20 interceptor may be an inflow opening through which influent will pass, an outflow opening and a grease collecting chamber hydraulically located between said inflow opening and said outflow opening. The method includes the step of providing an inlet baffle assembly within the in-line interceptor, where the inlet baffle assembly may include: (a) an inlet baffle
25 defining a flow channel connected to the inflow opening through which influent flows into the grease collecting chamber, the inlet baffle having a moveable section being moveable between an open position and a closed position and (b) a flow control orifice associated with said inlet baffle to limit the rate of flow of wastewater through the flow channel when the
30 moveable section is in the closed position. The method may also include moving the moveable section into the open position, cleaning the inlet

baffle assembly while the moveable section is in the open position and moving the moveable section into the closed position in order to facilitate fluid flowing through the inlet baffle assembly into the grease collecting chamber.

5

BRIEF DESCRIPTION OF THE DRAWINGS

Reference will now be made, by way of example only, to preferred embodiments of the inventions and in which:

10 Figure 1 is a first perspective view from an upstream direction of an embodiment of an inlet baffle assembly in a closed position;

Figure 2 is a second perspective view from a downstream direction of an embodiment of the inlet baffle assembly of Figure 1;

Figure 3 is an exploded perspective view of an embodiment of the inlet baffle assembly of Figure 1;

15 Figure 4 is a perspective view of an embodiment of a fixed section of the inlet baffle assembly;

Figure 5 is a first perspective view of an embodiment of a moveable section of the inlet baffle assembly;

20 Figure 6 is a second perspective view of the embodiment of the moveable section of the inlet baffle assembly of Fig. 5;

Figure 7 is a side perspective view of an embodiment of a link arm of the inlet baffle assembly;

Figure 8 is a side perspective view of an embodiment of a flow control component of the inlet baffle assembly;

25 Figure 9 is a side perspective view of an embodiment of an actuator component of the inlet baffle assembly;

Figure 10 is a first perspective view of an inlet baffle assembly in an open position viewed from downstream;

30 Figure 11 is a second perspective view of the inlet baffle assembly of Fig. 10 in an open position, viewed from upstream;

Figure 12 is a side perspective view of an embodiment of the inlet

baffle assembly in a closed position;

Figure 13 is a side perspective view of an embodiment of the inlet baffle assembly in an open position;

Figure 14 is a top perspective view of an embodiment of the inlet
5 baffle assembly in a closed position;

Figure 15 is a top perspective view of an embodiment of the inlet baffle assembly in an open position;

Figure 16 is a cross-sectional side perspective view of an embodiment of the inlet baffle assembly in a closed position;

10 Figure 17 is a cross-sectional side perspective view of an embodiment of the inlet baffle assembly in an open position; and

Figure 18 is a cross-sectional side plan view of an in-line interceptor.

15 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

An embodiment of an inlet baffle assembly 20 is shown in Fig. 1-17. The inlet baffle assembly 20 is designed to be used in an in-line interceptor 22 such as is depicted generally in Fig. 18. Referring to Fig. 18, an in-line interceptor or grease interceptor 22 is used to separate fats,
20 oil and grease from wastewater which originates from food preparation kitchens or other facilities. The interceptor 22 has an inflow opening 25 through which influent will pass during operation of the interceptor 22. The interceptor 22 also includes outflow opening 26 and a grease collecting chamber 28 hydraulically located between said inflow opening 25 and
25 said outflow opening 26. A bulkhead fitting 24 is shown connected to the inflow opening 25.

Referring to Fig. 1, the inlet baffle assembly 20 includes an inlet baffle 30 sized and shaped to fit into the grease collecting chamber 28 (Fig. 18). The inlet baffle 30 defines a flow channel to direct the flow of
30 influent into the collecting chamber. The inlet baffle is affixed within the chamber to permit it to do this, for example by being removably affixed to

the bulkhead fitting. It will be understood that other means of affixing the inlet baffle in place are also comprehended.

In the embodiment shown in Fig. 1, the flow channel provides a fluid passageway between a baffle opening 32 and an open bottom 50 of the inlet baffle 30. When the inlet baffle 30 is connected to the inflow opening 25 (Fig. 18) of the interceptor 22 (Fig. 18), the flow channel allows influent to pass through the inlet opening 25 and ultimately enter the grease collecting chamber 28. The influent enters the inlet baffle 30 through the inflow opening 25 into the baffle opening 32, through the flow channel and exits the open bottom 50 into the grease collecting chamber. Influent passing through the inflow opening 25 may include wastewater containing FOG and other debris.

The inlet baffle 30 has a nominally fixed section 34 and a moveable section 36. Although the fixed section 34 is described as being 'fixed', it need not be permanently connected to inflow opening 25 (Fig. 18), so long as the moveable section 36 and fixed section 34 are moveable relative to one another. For example, the nominally fixed section 34 may be detachably connected, as described above, to the inflow opening 25 (Fig. 18). Preferably, the moveable section 36 is an elongate moving baffle half and the fixed section 34 is an elongate moving baffle half. However, the moveable section 36 and the fixed section 34 may take various forms and relative portions other than two halves, so long as the moveable section 36 is able to move in such a way that the interior of the inlet baffle is accessible for cleaning and inspection as described below. The relative movement of the moveable section 36 and the fixed section 34 allows the moveable section 36 to move between a closed position as shown in Figs. 12, 14 and 16 and an open position as shown in Figs. 13, 15 and 17. When the moveable section 36 is moved into the closed position relative to the fixed section 34, the flow channel is established which allows influent to flow, most preferably, in a controlled manner into the grease collecting chamber. As shown, for example, in Figs. 12 and 13,

the moveable section 36 may be operationally moved in its relative orientation away from the fixed section 34 and into the open position. The fixed section 34 may be affixed, such as by being clamped, retained in a retaining slot or groove, or attached with fasteners or the like, to the bulkhead fitting 24 of the in-line interceptor 22. The fixed section may provide an attachment point for the moveable section 36.

Preferably, fixed section 34 and the moveable section 36 are sized and shaped to ultimately produce laminar flow of influent through the grease collecting chamber when the moveable section 36 is in a closed position. A laminar flow is preferred to optimize the separation of solids, FOG and wastewater as the fluid passes through the chamber from the inlet side to the outlet side. The flow through the inlet baffle 30 may be partially controlled by the shapes of each of the fixed section 34 and the moveable section 36. As shown in Fig. 2, the moveable section 36 includes a generally cylindrical upper section 84 and flat sections 88 at the base. The upper section 84 has a rounded top 82. The fixed section 34 has a unitary flat section 86 as shown in Fig. 3. The assembly 34 when in the closed position seeks to do the following: initially turbulently mix the influent so as to entrain air via the opening 40 (Fig. 6) this air being drawn in through the opening 40 under negative pressure created by flow as it accelerates through the flow control orifice 58 (Fig. 8) and into turbulence. On passing through the flow control orifice, influent continues downward through the inlet baffle assembly being initially influenced by the more cylindrical form of the upper portion 84 and then transitioning to the more linear form enclosed by the flat areas 88 and 86 (Fig. 3). During this transition the flow area increases to slow the flow speed and the smooth baffle shape and reduced flow speed help re-establish laminar flow. Other shapes are comprehended for the baffles provided that laminar flow is re-established after the turbulent air mixing and entraining section above.

Referring to Figs. 8 and 17, the inlet baffle 30 includes a flow

control element 38 associated with the inlet baffle 30 to control the rate of flow of influent entering the flow channel when the moveable section 36 is in the closed position. Preferably, the flow control element 38 further comprises a flow control orifice 58. Alternate shapes and designs for flow control element 38 may be used so long as the rate of fluid flow into the system can be adequately controlled. For example, the flow control element may take the form of a flow control plate.

Referring to Fig. 17, the flow control element 38 is positioned to be accessible for cleaning and inspection when the moveable section 36 is in the open position. Preferably, the flow control element 38 is fixed to the moveable section 36 of the inlet baffle 30 so that the flow control element 38 moves away from the fixed section 34 of the inlet baffle 30 when the moveable section 36 is moved from the closed position to the open position, permitting access to the upstream side of the flow control element 38 and internal surfaces of the inlet baffle assembly 20 for cleaning. It will be understood that material which can block the opening in the flow control element will generally originate upstream. Thus, if, for example, an upstream sink has poor drainage, the sink user can simply go to the inline waste interceptor, open it, pull up the inlet baffle actuator as described herein, and get access to the flow control element 38, for prompt cleaning.

The orifice 58 can be provided in a range of different sizes, where the specific size is appropriate for a specific design inlet flow and/or to comply with regulatory requirements. When the moveable section 36 is moved to an open position, obstructions within the upstream baffle retainer 100 (Fig. 17) and the inlet baffle 30, including at the flow control element 38, may be cleared passively, through the flow of released, back-up wastewater, or actively, by physical cleaning by an operator. As shown in Figs. 1 and 5, the inlet baffle assembly 20 includes an integrated air intake 40 to facilitate entrainment of air into the influent flow. Air entrainment is desirable to allow buoyant bubbles of air to adhere to

droplets of oil, thereby causing them to rise or separate more quickly when in the chamber. Thus, the initial part of the flow through the inlet opening, through the flow control element and then down the baffle past the air intake 40 is most preferably somewhat turbulent to encourage
5 mixing of air into the influent as described above.

In the embodiment of Fig. 1, the integrated air intake 40 is illustrated by a single opening and is preferably located above the operational static water level of the interceptor 28 positioned generally in the upper portion of the moveable section 36. The integrated air intake 40
10 may take a variety of different forms (such as one or more openings) and need not be located within the moveable section 36 provided that the air intake 40 allows air to enter the influent flow from outside the inlet baffle assembly 20 and most preferably in a way that lets the air combine with a turbulent influent. For example, the inlet interceptor 22 may be a closed
15 compartment having a lid 90 (Fig. 18) and having an atmospherically balanced and vented environment from which air may be entrained into the air intake 40. In other words, air is mixed with the influent air, and then allowed to bubble up and resupply the air space above the fluid level in the chamber. The integrated air intake 40 is preferably located on an
20 upper portion of the inlet baffle 30 to ensure that the air intake 40 generally lies above the fluid level in the interceptor 22. Although in the embodiment shown, the air intake 40 is shown as a single linear detail, the air intake 40 may also include a different arrangement or number of holes which may have a variety of different shapes or sizes. Furthermore,
25 the air intake 40 may also be placed on a different component of the inlet baffle 30, such as the fixed section 34, or on both the fixed section 34 and the moveable section 36, so long as the air intake 40 provides a mechanism for introducing air into the influent liquid in a turbulent portion of flow to assist in the formation of bubbles to aid hydromechanical
30 separation of the FOG from the influent.

As shown in Fig. 10, the hinge pins 60 and 62 (Fig. 2) are

integrated to fixed section 34. The pins 60, 62 are moveably connected to opposed receiving details 44 on moveable section 36. The hinge details 44 define a rotational axis 52 which is adjacent the open bottom 50. An actuator assembly 46 is connected between the fixed section 34 and the moveable section 36 of the inlet baffle 30. When actuated, the actuator assembly 46 moves the moveable section 36 between the open position and the closed position. Preferably, the actuator assembly 46 is manually operable and is comprised of link arms 48 and an actuator component 54 which are operatively connected between the fixed section 34 and moveable section 36 of the inlet baffle assembly 30. The actuator component 54 may be in the form of a pull handle. The link arms 48 include slots 66 which interface with pins 68 on the moveable section 36 and slots 72 which interface to pins 64 on the fixed section 34. The fixed section 34 includes extension features 80 (Fig. 4) which each extend perpendicularly from the unitary flat section 86 of the fixed section 34. Each extension feature 80 includes one of each pair of pivot points 64 and 70.

As shown in Fig. 9, the handle 54 includes a connecting element 92 on each side of the handle 54. Each connecting element 92 has an elongate slot 74 which interfaces with pivots 64 and 70 on the fixed section 34. As shown in Fig. 10, at the base of each connecting element 92 is a pivot 76 which interfaces to a corresponding pivot hole 98 in each of the link arms 48. The link arms 48 allow the moveable section 36 to rotate about axis 52 and tilt away from the fixed section 34 to an open position, opening the inlet baffle 30 and exposing the upstream face of the flow control element 38 and allowing obstructions to be cleared as previously described.

As shown in Fig. 2, the hinged attachment 44 includes a pair of hinge pins 60, 62, on opposite sides of each of the fixed section 34 and the moveable section 36, which also allow the moveable section 34 to pivot away from the inflow opening 100 (Fig. 17). As shown, the hinged

attachment is placed at the bottom of the baffle assembly. This permits the top to open when the baffles are hinged apart. While this is the most preferred form of the present invention, other hinged positions and configurations are also comprehended. All that is required is an actuator component which is clear of the influent and retained fluids, and which can open the moveable baffle to permit the visual inspection and then cleaning of the flow control element as needed.

As shown in Fig. 3, the actuator component 54 provides a mechanism for manoeuvring the link arms 48 and causes the inlet baffle to move between the open position and the closed position as the actuator component 54 is raised and lowered, respectively. The actuator component 54 includes catch hooks 78 which interface with pins 68 to lock the moveable section 36 into the closed position to allow the assembly to stay closed against the force of any inlet fluid flow. The pins 68 also provide extension limits within slots 66 (Fig. 3) to control the maximum degree of openness. Although pivoting displacement provides good results, other forms of displacement are also comprehended. For example, the moveable section could be translated straight up on guides, or straight out. As well the moveable section could be completely detachable rather than being pivotally attached. All that is required is that the upstream side of the flow control element is exposed for ease of cleaning.

In operation, the interior of the inlet baffle assembly 20 can be cleaned by moving the moveable section 36 into the open position as shown in Figs. 13, 15 and 17 and by cleaning the inlet baffle assembly 20 while the moveable section 36 is in the open position. After being cleaned, the moveable section 36 is moved back into the closed position as shown in Figs. 12, 14 and 16 in order to facilitate fluid flowing through the inlet baffle assembly 20 into the grease collecting chamber 28. The actuator 54 is moved in a vertical plane to move the moveable section 36 between the open position and the closed position. The actuator assembly 46 may be

actuated by manually operating the handle 54. The flow control element 38 moves away from the baffle retainer component 100 (Fig. 17) when the moveable section 36 is moved into the open position, allowing backed-up wastewater and debris to flow into the grease collection chamber 28
5 which may be cleared using a pump for removal, for example.

The operation of the actuator assembly 46 can be understood with reference to Figs. 12 and 13. To open the inlet baffle, an operator pulls the actuator component 54 either by hand or with an implement so that the catch hooks 78 are lifted from the pins 68. When lifted, the actuator
10 component 54 moves upwards vertically. The motion of the handle 54 upwards causes the pivot 76 and pivot hole 98 to move upwards which in turn results in the upper end of the link arms 48 moving away from the fixed section 34. The moveable section 36 thereby moves apart at the top from the fixed section 34. The interaction between the elongate slots 74
15 and the pins 64 and 70 on the fixed section 34 restrict the relative motion of the actuator component 54 in a vertical direction. The pins 64 and 68 move within the slots 72 and 66, respectively of the link arms 48 as the actuator component 54 is lifted. As shown in Fig. 17, in the open position, the moveable section 36 exposes the upstream face of the flow control
20 element 38 from its position pressed against the inlet baffle retainer component 100. Once cleaned, the inlet baffle may be closed by the operator pushing down on the actuator component 54, either by hand or using an implement which draws the moveable section 36 and fixed section 34 together until the catch hooks 78 are locked into place on the
25 pins 68. The mechanism will stop when fully closed. An implement may be desirable to actuate the actuator assembly 46 when the inlet baffle assembly 20 is installed at greater than arm's length from the point of access of the operator. Detail 101 (Fig. 16) provides an attachment feature integrated with pull handle 54.

30 The inlet baffle assembly 20 may be constructed from a broad range of materials including but not limited to moulded or formed plastic.

In the claims, the word “comprising” is used in its inclusive sense and does not exclude other elements being present. The indefinite article “a” before a claim feature does not exclude more than one of the feature being present.

5 It will be appreciated that the foregoing description is intended by way of example only and that many variations and modifications to the invention are comprehended without departing from the scope of the claims which are attached. Some of these variations are discussed above and others will be apparent to those skilled in the art. For example, while
10 the preferred form of the invention is moulded plastic, metal or other materials could also be used. However, plastic is preferred for its low cost, and ease of manufacture among other reasons.

**THE EMBODIMENTS OF THE INVENTION IN WHICH AN EXCLUSIVE
PROPERTY OR PRIVILEGE IS CLAIMED ARE DEFINED AS
FOLLOWS:**

- 5 1. An inlet baffle assembly for use in an in-line interceptor used to
separate fats, oil and grease from wastewater, said interceptor having a
wastewater inflow opening through which influent will pass, an outflow
opening and a grease collecting chamber hydraulically located between
said inflow opening and said outflow opening, said inlet baffle assembly
10 comprising:
- an inlet baffle assembly sized and shaped to fit within said grease
collecting chamber, the inlet baffle assembly defining a flow channel
connected to the inflow opening through which influent enters the grease
collecting chamber, the inlet baffle assembly having a moveable section
15 being moveable between an open position and a closed position; and
- a flow control element associated with said inlet baffle assembly to
control the rate and flow characteristics of influent entering the flow
channel when the moveable section is in the closed position, said flow
control element being positioned to be accessible for cleaning and
20 inspection when the moveable section is in the open position.
2. The inlet baffle assembly of claim 1 further comprising an
integrated air intake to facilitate entrainment of air into said influent flow.
- 25 3. The inlet baffle assembly of claim 1 in which the inlet baffle further
comprises a nominally fixed section connected to the inflow opening and
the moveable section being associated with the fixed section, in such a
manner as to allow the moveable section to be operationally moved in its
relative orientation away from the fixed section.
- 30 4. The inlet baffle assembly of claim 3 further comprising a hinge

detail operationally related to said moveable section and said fixed section.

- 5 5. The inlet baffle assembly of claim 3 in which the inlet baffle further comprises an open bottom.
- 10 6. The inlet baffle assembly of claim 5 further comprising a hinge detail integrated attachment connected to said moveable section and said fixed section, the hinge detail being pivoted around a rotational axis and in which the rotational axis of the hinged attachment is adjacent the open bottom.
- 15 7. The inlet baffle assembly of claim 3 further comprising an actuator connected between the fixed section and the moveable section of the inlet baffle wherein the actuator moves the moveable section between the open position and the closed position.
- 20 8. The inlet baffle assembly of claim 7 in which the actuator is manually operable and is comprised of link arms and an actuator component which are operatively connected between the fixed and moveable sections of the inlet baffle.
- 25 9. The inlet baffle assembly of claim 3 in which the flow control element further comprises a flow control plate including an orifice.
- 30 10. The inlet baffle assembly of claim 3 in which the flow control element further comprises a flow control plate fixed to the moveable section of the inlet baffle so that the flow control plate moves away from the fixed section of the inlet baffle when the moveable section is moved from the closed position to the open position to permit access to an inflow opening, the flow control element and internal surfaces of the inlet baffle

assembly for cleaning.

11. The inlet baffle assembly of claim 3 in which the fixed section of the inlet baffle further comprises an elongate fixed baffle half and the
5 moveable section of the inlet baffle further comprises an elongate moving baffle half and said flow channel is formed between them.
12. The inlet baffle assembly of claim 11 further comprising the elongate fixed baffle half and the elongate moveable baffle half being
10 sized and shaped to produce a laminar flow of influent with reduced velocity into the grease collecting chamber.
13. The inlet baffle assembly of any one of claim 1 to 12 further comprising the inlet baffle and the flow control element being formed from
15 a plastic material.
14. The inlet baffle assembly of claim 8 further including a removeable handle extension to facilitate manual actuation of said handle in a below-grade in-line interceptor.
20
15. The inlet baffle assembly of claim 1 further including guide tables which locate said assembly within said in-line interceptor.
16. The inlet baffle assembly of claim 15 wherein said guide tabs are
25 sized and shaped to be received in vertical guide slots on said in-line interceptor.
17. The inlet baffle assembly of claim 1 wherein said flow control element includes both a flow restricting orifice and a flow deflector to
30 direct flow within said baffle.

18. A method of cleaning an inlet baffle assembly in an in-line interceptor, said interceptor having an inflow opening through which influent will pass, an outflow opening and a grease collecting chamber hydraulically located between said inflow opening and said outflow opening, the method comprising:

5 providing an inlet baffle assembly within the in-line interceptor, the inlet baffle assembly comprising: (a) an inlet baffle assembly defining a flow channel connected to the inflow opening through which influent flows into the grease collecting chamber, the inlet baffle assembly having a
10 moveable section being moveable between an open position and a closed position and (b) a flow control element associated with said inlet baffle to manage the rate of flow of wastewater through the flow channel when the moveable section is in the closed position;

moving the moveable section into the open position;

15 cleaning the inlet baffle assembly while the moveable section is in the open position; and

moving the moveable section into the closed position in order to facilitate fluid flowing through the inlet baffle assembly into the grease collecting chamber.

20

19. The method of claim 18 in which the inlet baffle further comprises a fixed section connected to the inflow opening, wherein the moveable section is moveably connected to the fixed section and wherein the inlet baffle assembly further comprises an actuator connected between the
25 fixed section and the moveable section of the inlet baffle, and the method further comprising actuating the actuator to move the moveable section between the open position and the closed position.

20. The method of claim 19 in which the actuator is further comprised
30 of link arms and a handle and the method further comprising manually operating the handle to move the moveable section between the open

position and the closed position.

21. The method of claim 19 in which the flow control element further comprises a flow control plate and the method further comprising moving
5 the flow control plate away from the fixed section of the inlet baffle assembly when the moveable section is moved into the open position.

22. The method of claim 18 in which cleaning the inlet baffle assembly while the moveable section is in the open position further comprises
10 allowing backed-up wastewater and debris to flow into the grease collection chamber when the moveable section is in the open position.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 8




Fig. 7





Fig. 9






Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18

