




US 20100284633A1

(19) **United States**(12) **Patent Application Publication**
Dytchkowskyj et al.(10) **Pub. No.: US 2010/0284633 A1**(43) **Pub. Date: Nov. 11, 2010**(54) **DISCRETE POUCH HAVING A CLOSURE
SYSTEM SECURED THERETO**(22) Filed: **May 7, 2009****Publication Classification**(75) Inventors: **David Z. Dytchkowskyj**, Appleton,
WI (US); **Lawrence D. Mikulsky**,
De Pere, WI (US); **Scott R. Grasse**,
Hortonville, WI (US); **Daniel J.**
Moran, Appleton, WI (US); **Peter**
T. Hunnicutt, Greenville, WI (US)(51) **Int. Cl.**
B65D 33/16 (2006.01)
B65D 30/08 (2006.01)
B65D 30/20 (2006.01)(52) **U.S. Cl. 383/64; 383/116; 383/120**(57) **ABSTRACT**Correspondence Address:
WILHELM LAW SERVICE, S.C.
100 W LAWRENCE ST, THIRD FLOOR
APPLETON, WI 54911

A discrete pouch is disclosed having a closure system transversely secured across an open end thereof. The discrete pouch includes first and second major surfaces joined together by a pair of sides. The discrete pouch also has a closed bottom, an open top, and a closure system secured to the second major surface adjacent to the open top. The discrete pouch is designed to have the open top sealed after it is filled with products and the closure system is capable of being opened and closed multiple times.

(73) Assignee: **CMD Corporation**, Appleton, WI
(US)(21) Appl. No.: **12/387,781**




FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 4




FIG. 5




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

FIG. 17






FIG. 18

FIG. 19






FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28

DISCRETE POUCH HAVING A CLOSURE SYSTEM SECURED THERETO

FIELD OF THE INVENTION

[0001] This invention relates to a discrete pouch having a closure system secured thereto. The closure system is secured in a transverse direction which is perpendicular to the machine direction in which the discrete pouch is advancing.

BACKGROUND OF THE INVENTION

[0002] Today, it is commonplace to find a variety of flexible pouches which include a closure system, such as a zipper, that can be opened and closed multiple times by the ultimate consumer. These reclosable pouches are used to enclose and/or hold a wide variety of items, articles or products in solid, semi-solid or liquid form. One or more items, articles or products can be manufactured or assembled and then be packaged in these pouches. The pouches and the enclosed items, articles or products can then be shipped to wholesalers, distributors and retailers for sale to the general public. The ultimate consumers can purchase the items, articles or products packaged in these pouches at grocery stores, mass merchandise stores, home improvement stores, garden supply stores, feed stores, etc. Examples of some items, articles and products that can be enclosed in such pouches include but are not limited to: food items in solid form such as fruit, vegetables, meats, candy, cookies, snacks, etc. and food items in liquid form such as non-carbonated juices, milk, sauces, etc; personal items such as medicine, cough drops, tobacco, cosmetics, toys, office supplies, etc; household items such as plastic knives, forks and spoons, cups, rubber bands, tacks, screws, hooks, laundry detergent, soap, etc; lawn and garden items such as grass seed, fertilizer, flower seeds, pet food, animal bedding material such as wood chips, etc., and various other items such as medical instruments, dental instruments, hardware, computer parts, sporting goods, etc.

[0003] The closure system used on such pouches can vary in design. A common closure system is in the form of a zipper having a track with an opening/closing mechanism and a slide member movably attached to the opening/closing mechanism. The slide member is designed to be manually moved back and forth along the track such that the pouch can be opened or closed multiple times. This ability to open and close the pouch multiple times, permits the ultimate consumer to remove only a portion of the items, articles or products enclosed therein at any one time. Alternatively, a consumer can insert or refill the pouch if desired. The pouch can be closed or resealed to keep the remaining items, articles or products together. If the pouch is constructed from an air tight material or a fluid or liquid tight material, it may also be able to keep the items, articles or products enclosed therein fresh. This is especially important for many food items which are not all consumed at one time.

[0004] Up until now, such reclosable pouches have been constructed using two basic methods. In the first method, which involves a two step process, a pouch without a closure system is manufactured in a first machine. The pouch includes a first major surface, an oppositely aligned second major surface, a pair of sides joining the first and second major surfaces together, a closed end and an open end. The pouch is then removed from the first machine and transported to a second machine. At the second machine, the pouch is reoriented such that its open end is aligned parallel to the

machine direction. A closure system is then secured to the open end in the machine direction. This method tends to be cumbersome and limits the pouches from being manufactured at high speeds.

[0005] The second method for manufacturing reclosable pouches involves an in-line process using a single machine. The closure system is first secured to a continuous flat strip of material. After the closure system is in place, the material is folded upon itself to form a tubular member. The tubular member is then intermittently sealed and transversely slit adjacent to the closure system to form discrete pouches. Although the second method is somewhat more efficient than the first method, it suffers from a major design flaw. That design flaw is that the closure system does not extend outward from the top end of the finished pouch. This makes it difficult for the ultimate consumer to locate and maneuver the slide member along the track when he or she desires to open and/or close the pouch.

[0006] Now a discrete pouch having a closure system secured thereto has been invented. Each discrete pouch is constructed before the closure system is applied. The closure system is secured to each of the discrete pouches in a cross direction, perpendicular to the machine direction. The closure system is applied while each pouch advances in the machine direction. This allows a higher quality pouch to be manufactured as well as permitting the closure system to extend outward from the top end of the pouch. The finished, discrete pouches that are produced are aesthetically pleasing to the consumer and can be manufactured at a lower cost.

SUMMARY OF THE INVENTION

[0007] Briefly, this invention relates to a discrete pouch having first and second major surfaces. The first major surface has a transverse edge with a predetermined pattern formed therein. The transverse edge has a pair of opposite ends. The second major surface is aligned opposite to the first major surface and also has a transverse edge with the predetermined pattern formed therein. The predetermined pattern formed in the first and second major surfaces has a contiguous boundary. The second major surface also has an inner surface. A pair of sides joins the first and second major surfaces together. The pair of sides can be secured to the first and second major surfaces by at least one longitudinal bond to form a tubular structure. Each of the discrete pouches also includes a seal which extends transversely across the tubular structure to form a closed bottom. Lastly, each of the discrete pouches includes a closure system. The closure system includes a track having a first leg and a second leg, with each leg having an outer surface. The outer surface of the first leg is secured to the inner surface of the second major surface adjacent to the transverse edge. The first and second legs are joined together by an opening/closing mechanism which includes a member capable of being manually moved back and forth such that the opening/closing mechanism can be sequentially opened and closed. The pair of opposite ends of the first major surface is secured to the outer surface of the second leg to form an open top located adjacent to the transverse edge of the first major surface. The open top is aligned opposite to the seal and is spaced apart therefrom.

[0008] The general object of this invention is to provide a discrete pouch having a closure system secured thereto. A more specific object of this invention is to provide a discrete pouch having a closure system transversely secured across an open end of the discrete pouch.

[0009] Another object of this invention is to provide a discrete pouch wherein the closure system is attached after the discrete pouch is constructed.

[0010] A further object of this invention is to provide a discrete pouch having a closure system which is economical to manufacture.

[0011] Still another object of this invention is to provide a discrete pouch having a closure system which can be manufactured at high speeds.

[0012] Still further, an object of this invention is to provide a discrete pouch having a closure system transversely secured across an open end thereof, wherein the closure system can be opened and closed multiple times.

[0013] Other objects and advantages of the present invention will become more apparent to those skilled in the art in view of the following description and the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] FIG. 1 is a perspective view of a machine capable of producing discrete, reclosable pouches.

[0015] FIG. 2 is a perspective view of a discrete pouch having a closure system that can be manually moved back and forth to open and close the discrete pouch multiple times.

[0016] FIG. 3 is a side view of a closure system which includes a track having first and second legs, the first and second legs being joined together by a thin membrane, an opening/closing mechanism joined to the first and second legs, and a slide member capable of being manually moved back and forth along the opening/closing mechanism.

[0017] FIG. 4 is an end view of the closure system shown in FIG. 3, taken along line 3-3 but without the slide member, and showing the opening/closing mechanism in a closed position and with the first and second legs being joined together by a thin membrane.

[0018] FIG. 5 is an end view of the closure system shown in FIG. 3 when the opening/closing mechanism is in an open position and with the first and second legs being joined together by a thin membrane.

[0019] FIG. 6 is a perspective view of the slide member shown in FIG. 3 which can be manually moved back and forth along the opening/closing mechanism so as to sequentially open and close the closure system.

[0020] FIG. 7 is a perspective view of a web of material being unwound from a supply roll and having a predetermined pattern punched therein.

[0021] FIG. 8 is a top view of the punched web of material depicting six fold lines where it will be folded to partially form a pair of gussets.

[0022] FIG. 9 is a top view of the punched web of material shown in FIG. 7 after it has been folded in half upon itself and folded to form gussets at both sides.

[0023] FIG. 10 is a perspective view of the continuous folded structure shown in FIG. 9.

[0024] FIG. 11 is a cross sectional view taken along line 11-11 of FIG. 10 showing the folds and gussets.

[0025] FIG. 12 is a perspective view of a continuous tubular structure once the web of material is bonded together.

[0026] FIG. 13 is an enlarged view of a portion of FIG. 12 showing a gusset.

[0027] FIG. 14 is an end view of the tubular structure shown in FIG. 12 after four bonds have been formed.

[0028] FIG. 15 is an end view of an alternative embodiment of a tubular structure having a single longitudinal bond.

[0029] FIG. 16 is a perspective view of the continuous tubular structure with a transverse seal formed therein.

[0030] FIG. 17 is an enlarged view of a portion of FIG. 16 showing one end of the transverse seal.

[0031] FIG. 18 is a perspective view of the continuous tubular structure with a crease and a stomp seal formed therein.

[0032] FIG. 19 is an enlarged view of a portion of FIG. 18 showing the crease and the stomp seal.

[0033] FIG. 20 is a perspective view of the continuous tubular structure after being subjected to another punch.

[0034] FIG. 21 is an enlarged view of a portion of FIG. 20 showing the punched section.

[0035] FIG. 22 is a perspective view of a discrete pouch after it has been slit or cut from the continuous web.

[0036] FIG. 23 is a perspective view of a rearward portion of the machine.

[0037] FIG. 24 is a perspective view of the discrete article shown in FIG. 22 after the lip has been folded back upon itself.

[0038] FIG. 25 is an enlarged view of a portion of FIG. 24 showing the lip being folded back and exposing the inside of the second major surface.

[0039] FIG. 26 is a perspective view of the discrete article shown in FIG. 24 after a closure system has been secured to the inner surface of the second major surface.

[0040] FIG. 27 is a perspective view of the discrete pouch shown in FIG. 26 after the lip is folded back and its ends are sealed.

[0041] FIG. 28 is a perspective view of a discrete pouch having a closure system secured to its second major surface and having its sides manipulated to form an enlarged opening adjacent to the open top.

DETAILED DESCRIPTION OF THE INVENTION

[0042] Referring to FIGS. 1 and 2, a machine 10 and a discrete pouch 12, respectively, are shown. The machine 10 is capable of manufacturing a plurality of the discrete pouches 12 in a cost effective and efficient manner. By "discrete" pouch it is meant a distinct thing. The discrete pouches 12 can be formed or constructed from one or more different materials. The kinds of material used to construct the discrete pouch 12 can vary. The discrete pouch 12 can be constructed from a variety of different material including but not limited to: a plastic material, a thermoplastic material, a cloth material, a film material, a polyolefin such as polyethylene or polypropylene, a low density polyethylene, a high density polyethylene, a low density polypropylene, a high density polypropylene, a polyester, a nylon material, a rayon material, a woven fabric, a non-woven fabric, cotton, paper, paper laminate, hemp, canvas, a woven polypropylene, a woven polyethylene, a mono-layered film, a multilayer film, a corn starched material, a compostable material, etc. The discrete pouches 12 can also be formed from a combination of two or more similar or different materials. The discrete pouches 12 can further be formed or constructed from any of the new green materials now being manufactured that are environmentally friendly. Desirably, the discrete pouches 12 are formed or constructed from a thermoplastic material. More desirably, the discrete pouches 12 are formed or constructed from polyethylene, polypropylene or a combination thereof.

[0043] Furthermore, the discrete pouches 12 can be formed from a laminate consisting of two or more layers. The various layers of the laminate can be identical, similar or be different

in composition from an adjacent layer. At least one of the layers of the laminate can be constructed so as to prevent air from passing therethrough. Alternatively, at least one of the layers of the laminate can be constructed so as to prevent a fluid or a liquid from passing therethrough.

[0044] The discrete pouches **12** can be formed or constructed from a continuous sheet of material or from two or more individual pieces of material. Desirably, the discrete pouches **12** are formed or constructed from a continuous single web of material. The thickness of the web used to form or construct each of the discrete pouches **12** can vary.

[0045] Referring to FIG. 2, each of the discrete pouches **12** has a first major surface **14** and an oppositely aligned second major surface **16**. For example, the first major surface **14** can represent the front of the discrete pouch **12** and the second major surface can represent the back of the discrete pouch **12**. The discrete pouch **12** also has a pair of sides **18** and **20** which join the first and second major surfaces, **14** and **16** respectively, together. The pair of sides **18** and **20** can vary in size and configuration. One or both of the pair of sides **18** and **20** can be configured as a single fold, as a strip of material having a predetermined width, be shaped as a gusset or have some other desired shape. In FIG. 2, each of the sides **18** and **20** contain a gusset **22**. By “gusset” it is meant a triangular insert or profile, as in the seam of a garment, for added strength or expansion. The discrete pouch **12** further has a closed bottom **24** and an open top **26**. The open top **26** should extend across at least 50% of a face width w_1 of the finished discrete pouch **12**. Desirably, the open top **26** will extend across at least 75% of the face width w_1 of the finished discrete pouch **12**. More desirably, the open top **26** will extend across at least 90% of the face width w_1 of the finished discrete pouch **12**. Even more desirably, the open top **26** will extend across at least 95% of the face width w_1 of the finished discrete pouch **12**.

[0046] A closure system **28** can be secured at or adjacent to the open top **26** so that the discrete pouch **12** can be sequentially opened or closed. Those skilled in the art sometimes refer to the discrete pouches **12** as “reclosable pouches”. The closure system **28** can be constructed in various shapes and designs. Desirably, the closure system **28** is a zipper. Those skilled in packaging will be familiar with various zipper designs.

[0047] Referring now to FIGS. 3-6, the closure system **28** will be described and is depicted as a zipper. However, various other closure systems are known to those skilled in the packaging art and can be used as well. Examples of a closure system that includes a zipper are taught in U.S. Pat. Nos. 4,909,017; 5,638,586; 6,805,485; 6,931,820; 6,986,237; 6,991,372 and 7,211,036; and 7,249,400.

[0048] It should be understood that the closure system **28** can vary in construction, profile and configuration. In addition, the closure system **28** does not have to include a zipper although many reclosable pouches do utilize a zipper.

[0049] The closure system **28** can be constructed from a single material or from two or more similar or different materials. Desirably, the closure system **28** is constructed from a single material. The closure system **28** can include various components. For purposes of discussion only, the closure system **28** includes at least three components. The closure system **28** includes a track **30** having a first leg **32** and a second leg **34**. The first leg **32** has an inner surface **36** and an outer surface **38**. The outer surface **38** can contain a heat activated substance which enables the outer surface **38** to bond to another material. For example, the heat activated

substance can be an additive, a sealant which assist in forming a thermal bond, a fiber having a low melt temperature, a film having a low melt temperature, an adhesive, etc.

[0050] The second leg **34** also has an inner surface **40** and an outer surface **42**. Like the outer surface **38** of the first leg **32**, the outer surface **42** of the second leg **34** can contain a heat activated substance as described above which enables the outer surface **42** to bond to another material.

[0051] Referring to FIGS. 4 and 5, the first and second legs, **32** and **34** respectively, can be folded upon themselves or they can be joined together by other means known to those skilled in the art. Optionally, a thin membrane **44** can join the first leg **32** to the second leg **34**. The thin membrane **44** can be integral with the first and second legs, **32** and **34** respectively. When the thin membrane **44** is present, it is usually situated away from either end of the first and second legs, **32** and **34** respectively. The thin membrane **44** functions as a breakable seal that must be broken, ruptured or severed before the contents of the discrete pouch **12** can be removed. The thin membrane **44** can be scored such that it has a cut which extends partially through its thickness such that it can be easily broken or separated. Alternatively, the thin membrane **44** can have an area or line of weakness or reduced thickness, be notched to facilitate breakability, or be treated in some fashion to make it susceptible to be easily broken. With the design depicted in FIGS. 4 and 5, as one pulls apart the upper portions of the first and second legs, **32** and **34** respectively, the thin membrane **44** is easily broken.

[0052] The thin membrane **44** can be formed from the same material used to construct the closure system **28**. Alternatively, the thin membrane **44** can be constructed of one or more materials such that an air tight or a liquid tight seal is created. The thin membrane **44** will serve as a physical barrier to prevent contaminants from contacting the items, articles or products contained within the discrete pouch **12** until the thin membrane **44** is broken. The thin membrane **44** can also serve as a tamper resistance seal to alert the ultimate consumer that no one has removed any items, articles or products from the discrete pouch **12** if the thin membrane **44** is not broken.

[0053] It should be understood that the thin membrane **44** is an optional feature and does not have to be present if it is not needed.

[0054] Referring again to FIGS. 3-5, the closure system **28** also includes an opening/closing mechanism **46** having a first part **48** and a second part **50**. In FIG. 4, the opening/closing mechanism **46** is closed, and in FIG. 5, the opening/closing mechanism **46** is opened. The first part **48** is connected to the upper end of the first leg **32** and the second part **50** is connected to the upper end of the second leg **34**. The opening/closing mechanism **46** is constructed such that the first part **48** is sized and configured to engage with and temporarily lock to the second part **50**. The two parts **48** and **50** can be formed from the same material or from a different material. As best shown in FIGS. 4 and 5, the first part **48** has a generally C-shaped cross-section with a finger which extends upward and inward from the C-shaped cross-section. The second part **50** is generally hook shaped with a finger extending upward and inward from the hook shaped cross-section. The hook shaped cross-section of the second part **50** is sized and configured to engage with and temporarily lock to the first part **48** when the two parts **48** and **50** are pressed together. When so engaged, see FIG. 4, the pair of upward and inwardly extending fingers will approach and/or abut one another. When the first and second parts, **48** and **50** respectively, of the opening/

closing mechanism 46 are separated from one another and moved away from one another, the opening/closing mechanism 46 will be in an open position, see FIG. 5.

[0055] It should be understood that opening the opening/closing mechanism 46 will not necessarily break the thin membrane 44. In order to break the thin membrane 44, when it is present, one must forcibly pull the first part 48 away from the second part 50 such that the first and second legs, 32 and 34 respectively, will move apart and cause the thin membrane 44 to break. It should also be noted that once the thin membrane 44 is broken, it will remain broken and cannot be resealed.

[0056] It should also be understood that the opening/closing mechanism 46, depicted in FIGS. 4 and 5, is but one embodiment. Those skilled in the packaging art will know of other ways to modify or alter the design of the opening/closing mechanism 46 while still providing for a similar function.

[0057] Referring now to FIGS. 3 and 6, the closure system 28 further includes a member 52. The member 52 can be a slidable member that is sized and configured to allow a person to pinch or grasp the member 52 between the tips of his or her thumb and forefinger on either hand. As best depicted in FIG. 6, the member 52 has a top wall 54 and first and second sidewalls, 56 and 58 respectively, which extend downwardly from the top wall 54. The top wall 54 can have a relatively smooth upper surface or be scored. The top wall 54 can be flat or contoured. The first and second sidewalls, 56 and 58 respectively, are aligned opposite to one another and each can be flat, contoured. Desirably, each side wall 56 and 58 has a concave profile. The concave profile is sized to easily receive the tips of a person thumb and forefinger and allows the member 52 to be moved back and forth without escaping from the person's grip. Each of the first and second sidewalls, 56 and 58 respectively, has an inwardly directed flange, 60 and 62 respectively. The two inwardly directed flanges 60 and 62 face one another but do not touch. The two inwardly directed flanges 60 and 62 are sized and configured such that one will contact the outer surface 38 of the first leg 32 while the other flange contacts the outer surface 42 of the second leg 34. The member 52 also has a tongue 64, see FIG. 6, formed at one end thereof which extends downwardly from the inner surface of the top wall 54. The tongue 64 is located between the first and second sidewalls, 56 and 58 respectively, but is spaced from the inner surfaces of the first and second sidewalls, 56 and 58 respectively. The tongue 64 is also distally spaced away from the flanges 60 and 62.

[0058] The member 52 is constructed and designed to interact with the opening/closing mechanism 46 so as to cause the opening/closing mechanism 46 to open when the member 52 is slid or moved in a first direction and to subsequently cause the opening/closing mechanism 46 to close when the member 52 is slid or moved in a second opposite direction. The member 52 is capable of being manually moved back and forth along the opening/closing mechanism 46 such that the opening/closing mechanism 46 can be opened and closed. This is accomplished by having the tongue 64 engage with opening/closing mechanism 46 such that it can cause the two parts 48 and 50 to separate from one another. As the member 52 is moved in an opposite second direction, the first and second flanges, 60 and 62 will urge or force the two parts 48 and 50 of the opening/closing mechanism 46 to contact one another and engage. This allows the two parts 48 and 50 to seal close the discrete pouch 12.

[0059] The member 52 can be formed or constructed from the same material as was used to construct the remainder of the closure system 28 or it can be formed or constructed from a different material. Desirably, the member 52 is constructed from a different material. More desirably, the member 52 is formed from a hard plastic. The material from which the member 52 is formed or constructed can include a color additive so that the member 52 is more visible to the ultimate consumer who will use the discrete pouch 12.

[0060] Referring again to FIG. 2, when the discrete pouch 12 is filled with items, articles or products and is offered for sale by a retailer, it will usually have the opening/closing mechanism 46 in a closed position. In this position, the member 52 will be situated at one end of the track 30. As the member 52 is moved or slid in a first direction away from the side 18 and towards the opposite side 20, the opening/closing mechanism 46 will be forced open by the tongue 64. With the first and second parts, 48 and 50 respectively, of the opening/closing mechanism 46 spaced apart from one another, the ultimate consumer can pull the first major surface 14 away from the second major surface 16 and this will cause the thin membrane 44, when present, to sever or break. The ultimate consumer will now have access to the items, articles or products contained in the discrete pouch 12. As the member 52 is moved or slid in an opposite second direction, back toward the side 18, the member 52 will urge or force the first and second parts, 48 and 50 respectively, of the opening/closing mechanism 46 to again engage, via the flanges 60 and 62, and close the closure system 28. The closure system 28 can be moved back and forth multiple times such that the discrete pouch 12 can be opened and closed multiple times. Once the discrete pouch 12 is empty of its items, articles or products, it can be discarded. Alternatively, the discrete pouch 12 can be refilled with some other items and continue to serve as a useful discrete pouch 12.

[0061] Referring now to FIGS. 1 and 7, the machine 10 is capable of forming or constructing the discrete pouch 12 in a single in-line process and securing the closure system 28 in a transverse direction as the discrete pouch 12 advances in the machine direction (MD). The transverse direction at which the closure system 28 is secured is aligned perpendicular to the machine direction (MD). The machine 10 has an unwind station 66 which is capable of unwinding a web of material 68 from a supply roll 70. The supply roll 70 is a cylindrical roll of a particular material 68 from which the discrete pouches 12 will be manufactured. The supply roll 70 can vary in diameter and width. Desirably, the supply roll 70 has a diameter of less than about 4 feet and a width of less than about 6 feet. More desirably, the supply roll 70 has a diameter of less than about 3 feet and a width of less than about 3 feet. The supply roll 70 can be a roll of thermoplastic or polyolefin material. However, as mentioned above, the material 68 wound on the supply roll 70 can be also any kind of material known to those in the packaging art that is currently used to construct flexible pouches.

[0062] The web of material 68 can be unwound from the supply roll 70 in either the clockwise or counterclockwise direction. In FIG. 1, the web of material 68 is unwound in the counter clockwise direction and the forward end of the web of material 68 is advanced through the machine 10 in a machine direction (MD). The machine direction (MD) extends from right to left in FIG. 1.

[0063] Referring again to FIG. 7, as the web of material 68 is unwound from the supply roll 70 it will become a planar

web. The web of material **68** is relatively flat and has a first surface **72** and an oppositely aligned second surface **74**. For example, the first surface **72** can be the upper surface and the second surface **74** can be the lower surface. The first surface **72** can be folded so as to be either the interior or exterior surface of the finished discrete pouch **12**. The machine **10** and the process of forming the discrete pouches **12** will be explained with the first or upper surface **72** being folded down and under itself such that the first surface **72** will become the exterior surface of the finished discrete pouches **12**. As this occurs, the second or lower surface **74** will become the interior surface of the finished discrete pouches **12**. The surface of the web of material **68** that forms the exterior surface of the discrete pouches **12** can be printed to display words, numbers, symbols, graphics, photos, etc. The first surface **72** can also be partially or fully colored. One or more colors can be present on the first surface **72** and each of the colors can vary to suit one's particular printed image. Additionally, the first or exterior surface **72** can be treated, contain an additive, a sealant or some other substance to give it a glossy aesthetic appearance. To the contrary, the second surface **74** of the web of material **68** is usually void of any printing, coloring or coating. However, the second surface **74** may contain a sealant, if desired. The reason that the second surface **74** is void of any printing, coloring or coating is that the second surface **74** will eventually form the interior surface of the discrete pouches **12** and a portion of the second or interior surface **74** will need to be bonded to another interior portion of the web of material **68**. The absence of any printing, coating or coloring will facilitate bonding. Those skilled in the art will recognize that, especially for plastic and thermoplastic material, the absence of any printing, coloring or coating is usually a requirement in order to be able to form a good bond. This is especially true if heat and pressure are being used to form the bond.

[0064] The web of material **68** advancing through the machine **10** also has a first side edge **76** and an opposite, second side edge **78**. The web of material **68** has a width w extending perpendicular between the first and second side edges, **76** and **78** respectively. The width w can vary. Desirably, the width w is less than about 4 feet. More desirably, the width w is less than about 3.5 feet. More desirably, the width w is less than about 3 feet.

[0065] Referring again to FIG. 1, the relatively flat web of material **68** is advanced to a first dancer **80** having a draw nip (not shown). The first dancer **80** can be a horizontal dancer or any other form of dancer. The first dancer **80** is capable of continuously adjusting the advancement of the web of material **68** such that the material **68** can make a transition from continuous motion, as it leaves the supply roll **70**, to intermittent motion. Those skilled in art of manufacturing machines will be familiar with the function and operation of the dancer **80**. The dancer **80** can contain a plurality of vertically movable, cylindrical rolls around which the web of material **68** flows in a serpentine fashion. The cylindrical rolls are capable of constantly changing their vertical position with respect to one another such that the incoming material **68** can make the transition from a continuous motion to an intermittent motion.

[0066] Still referring to FIG. 1, located downstream from the first dancer **80** and from the unwind station **66**, as the web of material **68** moves in the machine direction (MD), is a punch station **82**. The punch station **82** is capable of punching a predetermined pattern **84** through the web **66**. Alternatively, the predetermined pattern **84** can be cut using equipment

other than a punch. The punch station **82** can include one or more punch units **86** each capable of punching the particular pattern **84** through the web of material **68**. In FIG. 1, two punch units **86, 86** are depicted. Each of the punch units **86, 86** can be identical or different. For example, each of the punch units **86, 86** can punch a portion of the overall predetermined pattern **84**. Alternatively, the first of the punch units **86** can punch out the entire pattern **84** and the second or subsequent punch unit(s) **86** can provide a trim punch to make sure the predetermined pattern **84** is crisp, sharp and registered correctly in the advancing web of material **68**.

[0067] Referring again to FIG. 7, the predetermined pattern **84** is repeated at a predetermined dimension b through the web of material **68**. The dimension b is measured parallel to the machine direction (MD) of the web of material **68**. The dimension b can vary depending upon the size of the discrete pouches **12** one desires to manufacture. The predetermined pattern **84** can also vary in configuration. A configuration **88** illustrates but one of an infinite variety of configurations that one can punch in the web of material **68**. As illustrated, the configuration **88** includes a pair of spaced apart, approximately C-shaped configurations **88, 88** formed across the width w of the web of material **68**. Even though a pair of approximately C-shaped configurations **88, 88** is shown, it should be understood that the predetermined pattern **84** can consist of one or more configurations, each having a desired profile.

[0068] It should be understood that when two or more configurations are present, that one configuration can be different from another configuration.

[0069] Each of the pair of approximately C-shaped configurations **88, 88** will form an upper end of one of the gussets **22** in the finished discrete pouches **12**. The gussets **22, 22** are formed at the sides **18** and **20** of each of the discrete pouches **12**. If the design of the discrete pouches **12** does not include gussets **22, 22** then the predetermined pattern **84** would not have to be punched out of the web of material **68**.

[0070] Still referring to FIG. 7, each of the pair of approximately C-shaped configurations **88, 88** is aligned along a common centerline $a-a$. Each of the centerlines $a-a$ is aligned perpendicular to the machine direction (MD). Of the pair of approximately C-shaped configurations **88, 88** located along each of the centerlines $a-a$, one of the approximately C-shaped configurations **88, 88** is spaced apart from the first side edge **76** by a dimension c . The dimension c can vary. Desirably, the dimension c is less than about 1 inch so as to reduce trim waste. The other approximately C-shaped configuration **88** is spaced apart from the second side edge **78** by a dimension d . The dimension d can vary. Desirably, the dimension d is several inches. In FIG. 7, the dimension d is greater than the dimension c . Furthermore, the pair of configuration **88, 88** is separated by a distance e . The dimension e can vary. Desirably, the dimension e is usually several inches in length. The dimension e will range from between about 90% to about 99% of a face width w_1 , of each of the finished, discrete pouches **12**. Desirably, the dimension e will range from between about 95% to about 99% of the face width w_1 of each of the finished, discrete pouches **12**. By "face width" it is meant the width w_1 measured perpendicular between the sides **18** and **20** of the first major surface **14** of each of the finished, discrete pouches **12**. The face width w_1 is usually less than half of the width w of the web of material **68**.

[0071] Each of the pair of approximately C-shaped configurations **88, 88** has a base member **90** with two spaced apart legs **92** and **94**. The legs **92** and **94** extend outward from the ends of the base member **90** in the machine direction (MD). The base member **90** has a dimension or length f measured parallel to the centerline a-a. The dimension f can vary but is usually several inches in length. For example, for a discrete pouch **12** having a face width w_1 of about 16 inches, the dimension f of the base member **90** can range from between about 4 inches to about 10 inches. More desirably, for a discrete pouch **12** having a face width w_1 of about 16 inches, the dimension f of the base member **90** can range from between about 6 inches to about 9 inches. The two legs **92** and **94** are aligned approximately parallel to one another and approximately parallel to the machine direction (MD). The two legs **92** and **94** can be aligned perpendicular to the base member **90** or be oriented at an angle thereto. Desirably, the two legs **92** and **94** are aligned perpendicular to the base member **90**. The dimension of each leg **92** and **94** can vary. Desirably, each leg **92** and **94** has the same dimension. Each of the two legs **92** and **94** extend outward from an end of the base member **90** in a downstream fashion. The overall size of base member **90** and each of the two spaced apart legs **92** and **94** can vary but will be sized to correspond to a particular size discrete pouch **12**. For example, the overall size of each of the pair of approximately C-shaped configurations **88, 88** can become larger as the size of the discrete pouches **12** get larger.

[0072] In FIG. 7, the dimension or length f of the base member **90** is sized such that it can be folded half way along the length f to form a pair of gussets **22, 22**. Each of the gussets **22, 22** will have a width equal to or less than about half of the dimension f .

[0073] One will also notice that a pair of small apertures or holes **96, 96** are punched through the web of material **68** adjacent to the base member **90** of each of the pair of configurations **88, 88**. These apertures **96, 96** are optional and can vary in size and shape. Desirably, the apertures **96, 96** are circular in shape and having a diameter of at least about 0.1 inches. Desirably, each aperture **96** has a minimum dimension which ranges from between about 0.1 inches to about 1.5 inches. The presence of the pair of apertures **96, 96** makes it easier to form bonds between various portions of the interior surface of the discrete pouches **12**. This is especially true at those areas where the gussets **22, 22** are located. This will be explained in greater detail below when discussing the process.

[0074] Returning to FIG. 1, the web of material **68** is advanced downstream from the punch station **82** to a second dancer **98**. The second dancer **98** can be equipped with a draw nip (not shown). The second dancer **98** can also be a vertical dancer like the first dancer **80** or it can be any other kind of dancer. The second dancer **98** can be identical to the first dancer **80**. The second dancer **98** is capable of continuously adjusting the advancement of the web of material **68** such that the web **68** can make a transition from the intermittent motion that it has as it leaves the punch station **82**, back to a continuous motion.

[0075] Still referring to FIG. 1, located downstream of the second dancer **98** and downstream of the punch station **82** is a folding station **100**. The folding station **100** is capable of folding the web of material **68** upon itself such that the first surface **72** forms the exterior of the finished, discrete pouches **12**, and the second surface **74** forms the interior of the finished, discrete pouches **12**. The folding station **100** can

include various stationary or movable components such as bars, plates, moveable fingers, etc. which can fold the web of material **68** into a desired configuration. Such folding machines are well known to those skilled in the art.

[0076] Referring to FIGS. 8-11, the web of material **68** is shown with six fold lines **102, 104, 106, 108, 110** and **112** shown as dashed lines. Each of the fold lines **102, 104, 106, 108, 110** and **112** are aligned parallel to one another and also are aligned parallel to the machine direction (MD) of the advancing web of material **68**. Desirably, the six fold lines **102, 104, 106, 108, 110** and **112** are aligned parallel to the first and/or second side edges, **76** and **78** respectively. The web of material **68** is folded at the three fold lines **102, 104** and **106** to form a gusset **22** at the side **18**, see FIG. 2. The web of material **68** is also folded at the three fold lines **108, 110** and **112** to form a gusset **22** at the opposite side **20**, see FIG. 2. In addition, the web of material **68** is folded in half upon itself at fold lines **108** and **112** to form a folded web **114**, see FIGS. 9-11.

[0077] Once the web of material **68** is folded upon itself, the predetermined pattern **84**, which can consist of one or more cuts, is present in both the first and second major surfaces, **14** and **16** respectively. The predetermined pattern **84** formed in the first and second major surfaces, **14** and **16** respectively, has a contiguous boundary.

[0078] Referring again to FIG. 1 the folded web **114** is then advanced through a third dancer **116**. The third dancer **116** does not include a draw nip. The third dancer **116** can be a horizontal dancer or any other form of dancer. Desirably, the third dancer **116** is a horizontal dancer. The third dancer **116** is capable of adjusting the advancement of the folded web **114** such that the folded web **114** can make a transition from continuous motion, as it leaves the folding station **100**, back to an intermittent motion. Located downstream of the third dancer **116** is a draw mechanism **118** which includes a pair of draw rolls (not shown) having a nip formed therebetween. The draw mechanism **118** functions to advance the folded web **112** into a bonding station **120**.

[0079] Referring again to FIG. 1, the bonding station **120** is located downstream from the folding station **100** and from the third dancer **116**. The bonding station **120** can include one or more bonding units **122**. Two spaced apart bonding units **122** are depicted. Each bonding unit **122** is aligned parallel to the machine direction (MD).

[0080] Referring now to FIGS. 12-14, each of the bonding units **122** is capable of forming one or more spaced apart bonds **124** in the overlapped material. Four longitudinal bonds **124** are depicted adjacent to the fold lines **102, 106, 108** and **112**. Each of the four bonds **124, 124, 124** and **124** can be continuous or intermittent. Desirably, each of the four bonds **124, 124, 124** and **124** is a continuous bond. To facilitate a good bond, the second surface **74** should not be printed, colored, coated or contain any substance which could interfere with establishing a good strong bond. Once the four bonds **124, 124, 124** and **124** are formed, a continuous tubular structure **126** is formed. The four bonds **124, 124, 124** and **124** can be located approximate each of the four corners of the tubular structure **126**. In the tubular structure **126**, two of the bonds **124, 124** are formed adjacent to the side **18** and the remaining two bonds **124, 124** are formed adjacent to the side **20** of the finished, discrete pouch **12**. Each of the bonds **124, 124, 124** and **124** can be formed by using heat, pressure, heat and pressure, ultrasonics, adhesive, glue, a co-adhesive, double sided tape, etc. In addition, each of the bonds **124, 124,**

124 and **124** could be created by using a chemical bonding agent. A combination of heat, pressure and/or a chemical bonding agent can also be utilized. Desirably, each of the four bonds **124**, **124**, **124** and **124** are formed by using a combination of heat and pressure. The four bonds **124**, **124**, **124** and **124** secure a portion of the second surface **74** to another portion of the second surface **74**. The apertures **96**, **96** which were punched in the web of material **68** provide a means by which a portion of the second surface **74** can be secured to another portion of the second surface **74** in the vicinity of each of the gussets **22**, **22**. At each of the folded sides **18** and **20** where the gussets **22**, **22** are located, there are four layers of material. The apertures **96**, **96** permit the first major surface **14** to be directly bonded to the second major surface **16**, see FIG. 2. Those skilled in the bonding art will know of the kind of equipment needed in order to form the bonds **124**, **124**, **124** and **124**.

[0081] Referring to FIG. 15, an alternative embodiment is depicted showing a continuous tubular structure **126'** wherein a single bond **124** is formed at or adjacent to the fold line **102**. The bond **124** is formed only at the side **18** of the finished discrete pouch **12**.

[0082] Referring again to FIG. 1, when a thermal bond is utilized, a certain amount of heat will be generated which will be retained by the surrounding material. Depending upon the material from which the pouch **12** is constructed, it may be advantageous to cool the material in which the bonds **124**, **124**, **124** and **124** have been formed so as to prevent the material from becoming deformed or damaged or to give the material a textured pattern. This is especially true when the material is a polyolefin, such as polyethylene or polypropylene. If too much heat is present or if the heat is maintained for an extended period of time from the bonding step, the material could melt and through holes could develop in the tubular structure **126** or **126'**. This is detrimental to the finished pouch **12** and must be avoided. One way to dissipate or remove the heat that may be present from the bonding step is to advance the continuous tubular web **126** or **126'** downstream to a cooling station **128**. In FIG. 1, the cooling station **128** includes a pair of spaced apart cooling units **130**, **130** which are coaxially aligned with the bonding units **122**, **122**. The cooling units **130**, **130** are aligned parallel with the machine direction (MD). The cooling units **130**, **130** are spaced apart approximately the same distance as the bonding units **122**, **122** so that they can cool the same region of the material of the folded web **114** that was heated by the bonding units **122**, **122**.

[0083] It should be understood that if the bonding station **120** does not generate any heat or does not generate a sufficient amount of heat that needs to be removed, then the cooling station **128** would not be needed.

[0084] Referring again to FIG. 1, a draw unit **132** is shown located downstream of both the cooling station **128** and the bonding station **120**. The draw unit **132** includes a pair of draw rolls (not shown) with a nip formed therebetween. The draw unit **132** functions to advance the tubular structure **126** or **126'** through a sealing station **134**. Those skilled in the art will recognize that the draw unit **132** could possibly be located downstream of the sealing station **134**, if desired. For some applications, it may be possible to eliminate the draw unit **132** completely. However, as indicated in FIG. 1, the draw unit **132** functions to advance the tubular structure **126** or **126'** in an intermittent fashion.

[0085] Referring now to FIGS. 1, 16 and 17, the sealing station **134** is located downstream from the bonding station

120. The sealing station **134** is capable of forming one or more seals **136**, see FIGS. 16 and 17 in the tubular structure **126** or **126'**. The size, shape and location of the seals **136** can vary. Desirably, one of the seals **136** will extend transversely across the continuous tubular structure **126** or **126'**. The seals **136** can be formed adjacent to and upstream of each pair of the configurations **88**, **88**. The sealing station **134** can include one or more sealing units arranged downstream from one another. In FIG. 1, three sealing units **138**, **140** and **142** are depicted. The three sealing units **138**, **140** and **142** can apply heat, a combination of heat and pressure, or some other sealing process to form one or more of the seals **136** in the tubular structure **126** or **126'**. The temperature of the three sealing units **138**, **140** and **142** can range from between about 100° Fahrenheit (F) to about 600° F. Desirably, the temperature of the sealing units **138**, **140** and **142** can range from between about 200° F. to about 500° F. More desirably, the temperature of the sealing units **138**, **140** and **142** is at least about 300° F.

[0086] Referring to FIGS. 16 and 17, a particular configuration for the seal **136** will be taught. However, it should be recognized that this invention is not limited to this particular seal **136** configuration.

[0087] The first sealing unit **138** can form an approximately K-shaped seal **144** or a portion of an approximately K-shaped seal **144** transversely across the tubular structure **126** or **126'**. The actual construction of the approximately K-shaped seal **144** includes an elongated segment **146** and two shorter segments **148** and **150**. The elongated segment **146** and the two shorter segments **148** and **150** can all vary in shape but desirably they are either linear or curvilinear. Most desirably, they are all linear. The elongated segment **146** spans transversely across a portion of or across the entire face width w_1 of the tubular structure **126** or **126'**. Desirably, the elongated segment **146** spans completely across the face width w_1 and is aligned perpendicular to the machine direction (MD). The elongated segment **146** can vary in width and depth but should form a sufficiently strong seal capable of permanently sealing the first major surface **14** to the second major surface **16**, see FIG. 2. The two shorter segments **148** and **150** are angled outward from the elongated segment **146** to form an approximately K-shape seal **144**. The two shorter segments **148** and **150** are shown angling upstream from the elongated segment **146** such that they extend away from the closed bottom **24**. The exact angle θ that each of the shorter segments **148** and **150** are arranged relative to the elongated segment **146** can vary. The angle θ can range from between about 5 degrees to about 75 degrees. Desirably, the angle θ is less than about 60 degrees. More desirably, the angle θ is less than about 45 degrees. Each of the two shorter segments **148** and **150** intersect with one of the sides **18** and **20**.

[0088] It should be understood that the discrete pouches **12** can be designed to have only a single seal that is either linear or arcuate in configuration. In fact, the seal **136** can be of any desired geometrical shape. The approximately K-shaped seal **144** produces a much stronger seal and is advantageous when the discrete pouches **12** are large, for example when the discrete pouches have a face width w_1 of 16 inches or more, and a height of 18 inches or more. Discrete pouches **12** size to retain pet food and having a total weight of 10 pounds or more represent a good example of when the approximately K-shaped seal **144** can be advantageously employed.

[0089] Referring again to FIG. 1, all three of the sealing units **138**, **140** and **142** can be utilized to form the approximately K-shaped seal **144**. This can be accomplished by have

each of the three sealing units **138**, **140** and **142** form a portion of the approximately K-shaped seal **144**. Alternatively, the sealing unit **138** can form the complete approximately K-shaped seal **144** and the sealing units **140** and **142** can create a deeper and more pronounced seal **144**. Desirably, all three of the sealing units **138**, **140** and **142** form a portion of the approximately K-shaped seal **144** such that after the three sealing units **138**, **140** and **142**, the approximately K-shaped seal **144** is completely formed.

[0090] Referring again to FIGS. **1**, **18** and **19**, a crease and stomp seal unit **152** is located downstream of the sealing units **138**, **140** and **142**. The crease and stomp seal unit **152** is capable of forming a crease **154**, see FIG. **18**, transversely across the tubular structure **126** or **126'**. Simultaneously or sequentially, the crease and stomp seal unit **152** is capable of forming a stomp seal **156** onto the approximately K-shaped seal **144**. The stomp seal **156** forms two small notches **158** and **160** approximate the location where each of the shorter segments **148** and **150** intersect with the elongated linear seal **146**. The purpose of the stomp seal **156** is to crimp the first and second major surfaces **14** and **16** so as to prevent products housed in the discrete pouch **12** from escaping or leaking out. This is important when a liquid or a small granular product is stored in the discrete pouch **12**. The stomp seal **156** functions to reinforce the two lower corners of the finished discrete pouch **12**. The stomp seal **156** may not be required in all applications. For example, if large items or articles are to be stored in the discrete pouches **12**, one may not need to reinforce the corners of the discrete pouches **12** because such items or articles cannot escape or leak out.

[0091] Referring again to FIG. **1**, two cooling units **162** and **164** are located downstream of the crease and stomp seal unit **152** and also downstream of the sealing units **138**, **140** and **142**. The cooling unit **164** is located downstream of the cooling unit **162**. The cooling units **162** and **164** function to cool the approximately K-shaped seal **144** and the stomp seal **156** formed in the tubular structure **126** or **126'**. It should be noted that the cooling units **162** and **164** can be eliminated if they are not needed. When present, the cooling units **162** and **164** can reduce the temperature of the material where the seals **144** and **152** were formed down to less than about 100° F., and desirably, down to around room temperature.

[0092] The sealing station **134** can be viewed as including the three sealing units **138**, **140** and **142**, the crease and stomp seal apparatus **152**, and the two cooling units **162** and **164**.

[0093] Referring again to FIG. **1**, a punch unit **166** is located downstream of the cooling units **162** and **164** and the crease and stomp unit **152**. The punch unit **166** can include a pair of punches **168** and **170** spaced apart from one another. The pair of punches **168** and **170** can be aligned opposite to one another so that they can punch opposite sides of the tubular structure **126** or **126'**.

[0094] Referring now to FIGS. **20** and **21**, the pair of punches **168** and **170** can form a pair of notches **172** and **174** in the tubular structure **126** or **126'**. The notch **172** is formed adjacent to the side **18** and the notch **174** is formed adjacent to the side **20**. The size and shape of each of the notches **172** and **174** can vary. Desirably, both notches **172** and **174** are of the same size and configuration. As depicted, the two notches **172** and **174** have a rectangular configuration but could have some other configuration, if desired.

[0095] Referring again to FIG. **1**, the tubular structure **126** or **126'** is advanced past a slitting station **176**. The slitting station **176** is located downstream of the punch unit **166** and

downstream of the sealing station **134**. The slitting station **176** can be a servo cut-off knife, a rotary knife, or any other kind of cutting apparatus known to those skilled in the art.

[0096] Referring now to FIG. **22**, the slitting station **176** is capable of forming a slit or cut **178** transversely across the continuous tubular structure **126** or **126'**. The slit or cut **178** occurs at the locations, depicted in FIG. **22**, which is at or adjacent to the elongated linear seal **146**. The slitting station **176** slits, cuts or severs the continuous tubular structure **126** or **126'** into a plurality of the discrete articles **180**. A multiplicity of discrete articles **180** can be formed from the tubular structure **126** or **126'**. Since the machine **10** is an in-line manufacturing process, the speed at which the discrete articles **180** can be manufactured is rather high.

[0097] Referring again to FIG. **1**, a rearward portion **182** of the machine **10** is shown. This rearward portion **182** can be assembled in-line with one or more of the upstream portions **82**, **100**, **122** and **134** of the machine **10** as shown. Alternatively, the rearward portion **182** can be a standalone segment which is separated from the remainder of the machine **10**. Desirably, the rearward portion **182** is in-line and attached to the upstream portion **134** of the machine **10**. The rearward portion **182** includes a first station **184** which is capable of receiving and advancing each of the discrete articles **180** in the machine direction (MD). The first station **184** can be operated at a speed that is equal to or different from the speed of the upstream sealing station **134**. Desirably, the first station **184** is operated at a speed that is faster than the speed of the sealing station **134**. By running the first station **184** at a faster speed than the sealing station **134**, one can be assured that the discrete articles **180** are moved away from the advancing continuous tubular structure **126** or **126'** which is being slit at the slitting station **176**.

[0098] Referring now to FIG. **23**, the first station **184** includes a stationary plate **186** which serves as an entry point for the discrete articles **180**. The stationary plate **186** is relatively flat and is aligned horizontally so as to provide support for each of the discrete articles **180**. Positioned in axially alignment and downstream of the stationary plate **186** is a first continuous belt **188** that rotates around a plurality of spaced apart rollers **190**. The exact number of rollers **190** can vary depending upon the length of the continuous belt **188** and the path of the continuous belt **188**. The first continuous belt **188** can run along the entire first station **184**, as shown, or it could extend along the greater length of the rearward portion **182** of the machine **10**. Desirably, the first continuous belt **188** will run along the length of the first station **184**. The first continuous belt **188** is shown moving in a counter clockwise direction since the machine direction (MD) is from right to left. The first continuous belt **188** will serve as a movable platform for each of the discrete articles **180** as they advance through the first station **184**.

[0099] The first continuous belt **188** can have a width that is equal to or greater than the face width w_1 of each of the discrete pouches **12**, see FIG. **2**. Desirably, the width of the first conveyor belt **188** is wider than the face width w_1 of each of the discrete pouches **12**. More desirably, the width of the first conveyor belt **188** is at least 4 inches wider than the face width w_1 of each of the discrete pouches **12**. The first continuous belt **188** functions to support the lower surface of each of the discrete articles **180** as they advance through the first station **184**.

[0100] Still referring to FIG. **23**, the first station **184** also includes first upper belts **192** which are continuous and are

movable around a plurality of spaced apart rollers **194**. Three first upper belts **192** are depicted in FIG. 23. It should be understood that one, two, three or more of the first upper belts **192** can be utilized depending upon the face width w_1 of the finished discrete pouch **12**. Each of the first upper belts **192** can have a width ranging from between about 1 inch to about 6 inches. Desirably, each of the first upper belts **192** has a width ranging from between about 1.5 inches to about 3 inches. Each of the first upper belts **192** is spaced apart from an adjacent belt **192** and the first upper belts **192** can be aligned parallel to one another. The first upper belts **192** rotate in a clockwise direction.

[0101] The number of rollers **194** around which the first upper belts **192** rotate can vary depending upon the size and configuration of the first upper belts **192**. The first upper belts **192** cooperates with the first continuous belt **188** to form a nip **196** therebetween through which each of the discrete articles **180** can be advanced. The speed of the first upper belts **192** can be adjusted to match the speed of the continuous belt **188**.

[0102] Referring back to FIG. 22, each of the discrete articles **180** can be advanced through the rearward portion **182** of the machine **10** with its K-shaped seal **144** serving as the leading edge. In this orientation, the sides **18** and **20** are aligned parallel or approximately parallel to the machine direction (MD). In other words, the closed bottom **24** of each finished discrete pouch **12**, see FIG. 2, will lead the discrete article **180** through the machine **10**. It is important in attaching the closure system **28** to each of the discrete articles **180** that the sides **18** and **20** are aligned parallel or approximately parallel to the machine direction (MD). Alternatively, each of the discrete articles **180** can be advanced through the rearward portion **182** of the machine **10** with the open top **26**, see FIG. 2, or the unsealed end being the leading edge. This is a very unique aspect of the machine **10**. Up until now, applicants do not know of any machine that has the ability to feed a discrete article **180**, in the machine direction (MD), through the machine **10** with either the closed end **24** or the open end **26** serving as the lead.

[0103] Referring now to FIGS. 1, 2 and 24-25, the first station **184** also includes a number of fingers **198**, which are capable of lifting and folding a portion of the first major surface **14** upon itself to form a lip **200**. The number of fingers **198** can vary. The fingers **198** can be spaced apart from one another and can be aligned parallel to one another. There should be a sufficient number of fingers **198** to extend across the face width w_1 of the discrete pouch **12**. Desirably, there are at least two spaced apart fingers **198** which extend across the face width w_1 of the discrete pouch **12**. More desirably, there are at least three spaced apart fingers **198** which extend across the face width w_1 of the discrete pouch **12**. Even more desirably, there are at least four spaced apart fingers **198** which extend across the face width w_1 of the discrete pouch **12**.

[0104] It should be understood by those skilled in the art that the fingers **198** could be replaced by some other mechanism that can accomplish the same function. For example, the fingers **198** could be replaced by one or more vacuum bars, rotary brushes, static pinners, etc., or by some combination thereof.

[0105] In FIGS. 24 and 25, the lip **200** is shown being aligned approximately perpendicular to the machine direction (MD). The lip **200** has a length l , measured parallel to the machine direction (MD), which ranges from between about 0.25 inches to about 4 inches. Desirably, the length l of the lip

200 ranges from between about 0.5 inches to about 3 inches. More desirably, the length l of the lip **200** ranges from between about 0.75 inches to about 2 inches. As the material which forms the lip **200** is folded, a first surface **202** of the lip **200** faces upward and is exposed. The exposed first surface **202** is a portion of the interior of the first major surface **14**. The exposed first surface **202** should not contain any printing, coloring or coating thereon. The lip **200** is distally spaced from a transverse edge **204** of the second major surface **16** which forms the discrete article **180**. The second major surface **16** also has an inner surface **206** which is located adjacent to the transverse edge **204**. The inner surface **206** faces upward and is exposed. The exposed inner surface **206** also should not contain any printing, coloring or coating thereon. Furthermore, as the lip **200** is formed, the inside surfaces **208**, **208** of each of the gussets **22**, **22** face upward and are exposed. These surfaces **208**, **208** also should not contain any printing, coloring or coating thereon.

[0106] Referring again to FIGS. 1 and 23, the first station **184** further includes second upper belts **210** which are continuous and are movable around a plurality of spaced apart rollers **212**. Like the first upper belts **192**, the second upper belts **210** can be aligned parallel to one another and be spaced apart from one another. Three of the second upper belts **210** are depicted in FIGS. 1 and 23. However, the exact number of the second upper belts **210** that are utilized can vary. One, two, three or more of the second upper belts **210** can be present. The face width w_1 of the finished discrete pouches **12** will partially determine how many of the second upper belts **210** are needed. The second upper belts **210** move in a clockwise direction.

[0107] The number of rollers **212** needed can vary depending on the size and configuration of the second upper belts **210**. The second upper belts **210** cooperate with the continuous belt **188** to form a nip **214** through which each of the discrete articles **180** can be advanced after leaving the fingers **198**. The second upper belts **210** can be similar or identical to the first upper belts **192**. The second upper belts **210** are located downstream of the fingers **198**. Each of the second upper belts **210** can have a width ranging from between about 1 inch to about 6 inches. Desirably, the width of each of the second upper belts **210** ranges from between about 1.5 inches to about 3 inches. The speed of the second upper belts **210** can be adjusted to match the speed of the continuous belt **188**. Desirably, the first upper belts **192**, the second upper belts **210** and the continuous belt **188** all move at the same speed.

[0108] Referring again to FIG. 23, the first station **184** also has a vacuum section **216** located beneath the first station **184**. The vacuum section **216** can extend throughout the entire length of the first station **184**. The vacuum section **216** includes one or more vacuum boxes **218** and one or more vacuum plenums **220** located below the vacuum boxes **218**. The size and shape of the two vacuum boxes **218**, **218** and the two vacuum plenums **220**, **220** can vary. The vacuum section **216** functions to hold the second major surface **16** of each of the discrete articles **180** securely against the continuous first conveyor belt **188** as the lip **200** is folded upon itself. The vacuum section **216** also functions to hold each of the discrete articles **180** such that the sides **18** and **20** are aligned parallel to the machine direction (MD). This allows the lip **200** to be folded perpendicular to the sides **18** and **20** such that the length l of the lip **200** remains constant. In other words, the lip **200** will not be skewed relative to the machine direction (MD).

[0109] Referring now to FIGS. 1, 23 and 26, the rearward portion 182 of the machine 10 also includes a second station 222 located downstream from the first station 184. The second station 222 is capable of positioning and attaching a closure system 28 transversely across the exposed inner surface 206 of the second major surface 16, adjacent to the transverse edge 204. The second station 222 is also capable of cutting the strip material which forms the closure system 28 to a desired length l_1 so that it has a length l_1 equal to the face width w_1 of the finished discrete pouch 12. The closure system 28 is secured in place as each of the discrete articles 180 advances in the machine direction (MD) at a predetermined speed. Alternatively, each of the discrete articles 180 can be temporarily halted as the closure system 28 is attached, although this will slow down the production process. Desirably, the closure system 28 is attached to each of the discrete articles 180 as each of the discrete articles 180 is intermittently moved through the rearward portion 182 of the machine 10. The second station 222 can be a commercially available unit from Illinois Tool Works Inc. of Glenview, Ill. The unit from Illinois Tool Works Inc. is designed to secure a zipper to an edge of a tubular structure or to a side of a discrete pouch but it can be modified to work with the present machine 10. U.S. Pat. Nos. 4,878,987; 4,909,017; 5,557,907 are just a few that teach securing a closure system, for example a zipper, onto a bag material. Those skilled in the art will be familiar with other closure systems and apparatuses which could be utilized with the present machine 10 with slight modifications.

[0110] Referring to FIGS. 3, 4 and 26, one way of securing or attaching the closure system 28 to each of the discrete articles 180 is to seal or bond the outer surface 38 of the second leg 34 of each of the closure systems 28 to the inner surface 206 of the second major surface 16, see FIG. 26. Desirably, the closure system 28 is initially in the form of a continuous strip of material that can be advanced across the face width w_1 of the discrete article 180 and then be cut to the required length l_1 . Alternatively, the strip of material can first be secured or attached to the inner surface 206 before it is cut to the desired length l_1 . The closure system 28 can be a typical zipper or any variation thereof. The closure system 28 can be secured or attached by using heat, pressure, heat and pressure, an ultrasonic bond, by using an adhesive, by using a co-adhesive, by using double sided tape, by using a combination of any of the above or by using some other bonding method known to those skilled in the bonding art. The closure system 28 could also be mechanically attached to the inner surface 206. Desirably, the closure system 28 is secured to the inner surface 206 by using heat and pressure. The amount of heat and pressure utilized will depend upon the materials from which the second major surface 16 and the closure system 28 are constructed of, the thickness of each material, the melting temperature of each material, etc.

[0111] When the closure system 28 is in the form of a zipper, it can be secured to the inner surface 206 of the second major surface 16 while the opening/closing mechanism 46 is in either the closed position, see FIG. 4, or in the open position, see FIG. 5. Desirably, the closure system 28 is secured to the inner surface 206 of the second major surface 16 while the opening/closing mechanism 46 is in the closed position. The slide member 52 can be positioned on the track 30 before, during or after the closure system 28 is secured to the inner surface 206 of the second major surface 16.

[0112] It should be recognized that the closure system 28 can be temporarily secured to the inner surface 206 or be permanently attached to the inner surface 206. If the closure system 28 is temporarily attached, then a second securement step will be needed to permanently attach the closure system 28 to the inner surface 206. Desirably, the closure system 28 will be permanently attached to the inner surface 206 in one step.

[0113] The location of the securement of the closure system 28 to the inner surface 206 and whether the securement is continuous or intermittent along the length of the closure system 28 can vary. For example, the securement can be a plurality of spot bonds, a continuous linear seal, an intermittent linear seal, etc. Desirably, the bond or securement will extend along essentially the entire inner surface 206 of the second major surface 16. More desirably, the securement of the closure system 28 to the inner surface 206 will be in the form of a continuous bond which extends along the entire length l_1 of the closure system 28.

[0114] It is to be understood that the length l_1 of the closure system 28 should be essentially equal to the face width w_1 of the discrete pouch 12. However, the length l_1 of the closure system 28 could be slightly less than the face width w_1 of the discrete pouch 12. For example, the length l_1 of the closure system 28 could be slightly less than the face width w_1 because of the material that was punched out of the continuous web of material 68. Desirably, the closure system 28 should 30310 be bonded or secured along its entire length l_1 . Alternatively, the closure system 28 could be bonded or secured along essentially most of its length l_1 .

[0115] It should be noted that the closure system 28 can be permanently secured to the inner surface 206 of the second major surface 16 at the second station 222. Alternatively, the closure system 28 can be temporarily secured to the inner surface 206 of the second major surface 16 at the second station 222 and then be permanently secured using additional sealing units. The use of additional sealing units is shown in FIG. 23.

[0116] Referring again to FIGS. 1 and 23, the rearward portion 182 of the machine 10 includes a second conveyor belt 224 that rotates around a plurality of spaced apart rollers 226. The exact number of rollers 226 can vary depending upon the length of the second conveyor belt 224 and the travel path of the second continuous belt 224. The second conveyor belt 224 forms a continuous loop. The second conveyor belt 224 can be similar to the first conveyor belt 188. The second conveyor belt 224 extends downstream from the second station 222 to the end of the rearward portion 182. The second conveyor belt 224 is shown rotating in a counter clockwise direction and functions as a moving horizontal support for the discrete articles 180 as they advance through the remainder of the rearward portion 182.

[0117] Still referring to FIGS. 1 and 23, the rearward portion 182 also includes an optional sealing unit 228 located downstream of the second station 222. The sealing unit 228 is designed to permanently seal or bond the closure system 28 to the inner surface 206 of the second major surface 16 adjacent to the trailing end 204. The sealing unit 228 will not be needed if the second station 222 can form the permanent bond. When the sealing unit 228 is present, it can bond the closure system 28 to the inner surface 206 from the top, from the bottom or from both the top and the bottom. Desirably, the closure system 28 is bonded from both sides to the inner surface 206

in order to obtain a secure bond that extends completely along the entire length l_1 of the closure system 28.

[0118] It should also be understood that the seal or bond can be formed between the closure system 28 and the inner surface 206 of the second major surface 16 using different kinds of bonding equipment known to those skilled in the art.

[0119] Still referring to FIGS. 1, 5, 23 and 27, the rearward portion 182 of the machine 10 further includes a third station 230 located downstream from said second station 222 and downstream of the sealing unit 228 when it is present. The third station 230 includes an unfolding and seal unit 232, a sealing unit 234, and a cooling unit 236. The unfolding and seal unit 232 is capable of unfolding the lip 200 back to its initial unfolded orientation. In this orientation, the exposed first surface 202 is no longer exposed but instead now lies over and covers a major portion of the closure system 28. The unfolding and seal unit 232 is also capable of forming a pair of seals 238 and 240 at the opposite ends, 242 and 244, respectively, of the lip 200. The pair of seals 238 and 240 secure portions of the first surface 202 of the lip 200 to the closure system 28. In particular, the seals 238 and 240 secure portions of the first surface 202 of the lip 200 to the outer surface 42 of the second leg 34, see FIG. 5. The size of the pair of seals 238 and 240 can vary. The opposite ends 242 and 244 of the lip 200 can be sealed or bonded using any of the bonding techniques taught above. A hot seal or bond can be obtained by using heat or heat and pressure works fine. One can also use ultrasonics, an adhesive or a double sided tape to form the seals 238 and 240.

[0120] The opposite ends 242 and 244 of the lip 200 can be bonded or sealed to the closure system 28 from the top, from the bottom or from both the top and the bottom. Desirably, the opposite ends 242 and 244 are bonded or sealed to the closure system 28 from both sides in order to form a more secure seal.

[0121] The sealing unit 234 can apply additional heat or heat and pressure onto the seals 238 and 240 to insure that they are permanently formed. The sealing unit 234 is optional if the unfolding and seal unit 232 is capable of forming permanent seals 238 and 240. After the seals 238 and 240 are formed, the discrete articles 180 are subjected to the cooling unit 236. The cooling unit 236 cools the material which forms the discrete pouches 12 and the seals 238 and 240 down to or towards room temperature. Once the discrete articles 180 have been cooled, the discrete pouches 12 are finished.

[0122] Referring now to FIG. 28, the discrete pouch 12 is shown after its sides 18 and 20 have been manipulated, such as being squeezed towards one another, so as to form an enlarged opening 256 adjacent to the open end 26. One will notice that the first major surface 14 of the discrete pouch 12 is not bonded to the closure system 28 along its entire length. Instead, the first major surface 14 is bonded only at the opposite ends 242 and 244 to the closure system 28. The distance between the pair of ends 242 and 244 is left unbounded and open. The reason for this is that the discrete pouches 12 can be quickly and rapidly filled with items, articles or products at a manufacturing site. Usually for a liquid product or for small granular products, the products can be dispensed into an empty pouch 12 via an injection or hopper system. Alternatively, the discrete pouches 12 can be manually filled, if desired. At the filling location, each of the discrete pouches 12 can be manipulated such that the enlarged opening 256 appears and items, articles or products can easily and quickly be inserted into the discrete pouch 12. After the discrete pouches 12 have been filled with items, articles or products,

the manufacturer will then flatten the open end 26 of each of the discrete pouches 12 and bond or seal the inner surface 40 of the second leg 34 to the inside surface 202 of the first major surface 14. This action will cause the open end 26 of the discrete pouch 12 to be sealed shut. The bond or seal can be formed using heat, pressure, heat and pressure, ultrasonics, an adhesive, a co-adhesive, a mechanical connector, double sided tape, etc. Once the discrete pouches 12 are filled and sealed, the filled pouches 12 can be shipped to a warehouse, distributor, retailer, etc. for sale or distribution to the ultimate consumer.

[0123] Referring again to FIGS. 1 and 23, the rearward portion 182 of the machine 10 also includes a removal mechanism 246. The removal mechanism 246 can take on many different forms. By way of example and not as a limitation, the removal mechanism 246 is depicted to include a first belt drive 248 and a second belt drive 250. The first belt drive 248 is positioned vertically above the second belt drive 250. The first and second belt drives, 248 and 250 respectively, cooperate to form a nip 252 therebetween. The first belt drive 248 can rotate in a clockwise direction while the second belt drive 250 can rotate in a counter clock wise direction. The first and second belt drives, 248 and 250 respectively, can include one or more continuous belts movably positioned around two or more spaced apart rollers. The discrete pouches 12 are conveyed from the machine 10 via the nip 252. The speed of the first and second belt drives, 248 and 250 respectively, can be adjusted to be equal to or be greater than the speed at which the discrete articles 180 are advanced through the machine 10. Desirably, the speed of the removal mechanism 246 is greater than the speed of the rearward portion 182 of the machine 10. This increase in speed allows the discrete pouches 12 to be removed continuously without interfering with the advancing discrete pouches 12 leaving the rearward portion 182 of the machine 10. After leaving the nip 252, the discrete pouches 12 can be directed away to be packaged and shipped. In FIG. 1, a slant stacker 254 is shown for moving the finished discrete pouches 12 away from the machine 10. Other means known to those skilled in the art can also be used. Such other means include but are not limited to: a movable conveyor belt, being manually conveyed away; being manually stacked and packaged into boxes for shipment; and being directed to an automated stacker or magazine which will stack and assembly the discrete pouches 12 into packages and route then to storage or to a shipment facility.

Method

[0124] A method of securing a closure system 28 onto a discrete pouch 12 is also taught. Each of the discrete pouches 12 has a first major surface 14, an oppositely aligned second major surface 16, a pair of sides 18 and 20 joining the first and second major surfaces, 14 and 16 respectively, together, a closed bottom 24 and an open top 26. Each of the discrete pouches 12 can be constructed from a plastic material, from a thermoplastic material, or from some other kind of material. The method comprises the steps of advancing one or more of the discrete pouches 12 through a first station 184 of the machine 10. The discrete pouches 12 are aligned in a machine direction (MD) with the closed bottom 24 leading each of the discrete pouches 12 through the machine 10. The discrete pouches 12 can be advanced using a first continuous conveyor belt 188. A vacuum source 216 can be utilized which will hold each of the discrete pouches 12 secure to the conveyor belt 188 and prevent the discrete pouches 12 from becoming

skewed. As the discrete pouches **12** are routed through the machine **10**, the first major surface **14** of each discrete pouch **12** will face upward. The first station **184** is capable of lifting and folding a portion of the first major surface **14** upon itself to form a lip **200** having a first surface **202** which is exposed. The second major surface **16** of each of the discrete pouches **12** has an inner surface **206** and a transverse edge **204** located adjacent to the open end **26**. The transverse edge **204** is distally spaced apart from the lip **200** such that a portion of the inner surface **206** is exposed. Desirably, at least about 2 inches of the inner surface **206** is exposed.

[0125] The method also includes routing each of the discrete pouches **12** downstream from the first station **184** to a second station **222**. The second station **222** is capable of positioning and attaching a closure system **28** transversely across the exposed inner surface **206**. The closure system including a track **30** having a first leg **32** and a second leg **34** each having an outer surface **38** and **42** respectively. The outer surface **38** of the first leg **32** is secured to the exposed inner surface **206** adjacent to the transverse edge **204**. The first and second legs, **32** and **34** respectively, are joined together by an opening/closing mechanism **46**. A member **52**, such as a slide member, is movably attached to the opening/closing mechanism **46**. The member **52** is capable of being manually moved back and forth along the opening/closing mechanism **46** such that the opening/closing mechanism **46** can be opened and closed.

[0126] The method further includes routing each of the discrete pouches **12** downstream from the second station **222** to a third station **230**. The discrete pouches **12** can be routed to the third station **230** on a second continuous conveyor belt **224**. The third station **230** is capable of unfolding the lip **200** and securing opposite ends **242** and **244** of the lip **200** to the outer surface **42** of the second leg **34**.

[0127] After exiting the third station **230**, the pair of sides **18** and **20** of each of the discrete pouches **12** can be manipulated, such as by being squeezed towards one another, to create an enlarged opening **256** located between the first major surface **14** and the outer surface **42** of the second leg **34**. This enlarged opening **256** enables items, articles or products to be easily and quickly inserted into the discrete pouch **12**. After the discrete pouch **12** has been filled with items, articles or products, the open end **26** is flattened and the outer surface **42** of the second leg **34** is bonded or sealed to the inside surface **202** of the first major surface **14**. The bond or seal can be formed using any of the bonding techniques taught above. Desirable, heat and pressure is used to form the bond. The filled discrete pouches **12** are then ready to be shipped to the ultimate consumer.

[0128] A more specific method for securing a closure system **28** onto a discrete pouch **12** is also disclosed. As in the method described above, each of the discrete pouches **12** has a first major surface **14**, an oppositely aligned second major surface **16**, a pair of sides **18** and **20** joining the first and second major surfaces, **14** and **16** respectively, together, a closed bottom **24** and an open top **26**. The more specific method comprises the steps of unwinding a web of material **68** from a supply roll **70** and advancing the web of material **68** to a punch station **82**. The web of material **68** has a first surface **72** and an oppositely aligned second surface **74**, first and second sides, **76** and **78** respectively, and a width dimension **w** extending between the first and second sides, **76** and **78** respectively. At the punching station **82** a predetermined pattern **84** is punched completely through the web of material **68**.

The predetermined pattern **84** can be an approximately C-shaped configuration. Desirably, the predetermined pattern **84** is a pair of spaced apart C-shaped configurations. The punched web of material **68** is then longitudinally folded upon itself such that the first major surface **14** is exposed. The punched web of material **68** can be folded at one or more locations so as to form gussets **22**, **22** adjacent to each of the sides **18** and **20** of the finished discrete pouches **12**. Desirably, six longitudinal fold lines **102**, **104**, **106**, **108**, **110** and **112** are present so that a gusset **22** is formed adjacent to each of the sides **18** and **20**.

[0129] The method also includes bonding the first and second major surfaces, **14** and **16** respectively, together along a single longitudinal line **102** to form a continuous tubular structure **126'**. The bond **124** can be formed using any of the techniques described above. Desirably, heat and pressure is used to form the bond **124**. Alternatively, a continuous tubular structure **126** can be formed that includes four bonds **124**, with each bond **124** being located at each corner of the tubular structure **126**. A transverse seal **136** is then formed across the continuous tubular structure **126** or **126'** at select locations. The transverse seal **136** is aligned adjacent to the predetermined pattern **84** and perpendicular to the machine direction (MD). The transverse seal **136** can be formed by heating the tubular structure **126** or **126'** to a temperature ranging from between about 100° F. to 600° F. and pressing the first and second major surfaces, **14** and **16** respectively, together. Desirably, the temperature will range from between about 200° F. to 500° F. The transverse seal **136** can have a width of at least about 0.1 inches. The distance that the transverse seal **136** is spaced away from the predetermined pattern **84** can vary. Desirably, the transverse seal **136** is spaced within 2 inches of the predetermined pattern **84**. More desirably, the transverse seal **136** is spaced within 1 inch of the predetermined pattern **84**. Even more desirably, the transverse seal **136** is spaced within 0.5 inches of the predetermined pattern **84**.

[0130] The method further includes transversely slitting at **178** the continuous tubular structure **126** or **126'** adjacent to the transverse seal **136** to form discrete articles **180**. The slitting can be accomplished by making a slit or cut **178** in the transverse seal **136**. Each of the discrete articles **180** or pouches **12** is then advanced through a first station **184** of the machine **10** in a machine direction (MD) with the closed bottom **24** leading the discrete article **180** through the machine **10** and with the first major surface **14** facing upward. The first station **184** is capable of lifting and folding a portion of the first major surface **14** upon itself to form a lip **200** having a first surface **202** which is exposed. The second major surface **16** has an inner surface **206** and a transverse edge **204** located adjacent to the open end **26**. The transverse edge **204** is distally spaced apart from the lip **200** such that a portion of the inner surface **206** is exposed. The discrete articles are then routed downstream from the first station **184** to a second station **222**. The second station **222** is capable of positioning and attaching a closure system **28** transversely across the exposed inner surface **206**. The closure system **28** includes a track **30** having a first leg **32** and a second leg **34** each having an outer surface, **38** and **42** respectively. The outer surface **38** of the first leg **32** is secured to the exposed inner surface **206** adjacent to the transverse edge **204**. The first and second legs, **32** and **34** respectively, are joined together by an opening/closing mechanism **46**. A member **52**, such as a slid member, is capable of being manually moved back and forth along the

opening/closing mechanism 46 such that the opening/closing mechanism 46 can be opened and closed.

[0131] Lastly, the method includes routing the discrete articles 180 downstream from the second station 222 to a third station 230. The third station 230 is capable of unfolding the lip 200 and securing opposite ends 242 and 244 of the lip 200 to the outer surface 42 of the second leg 34 to form the discrete pouches 12.

[0132] After each of the discrete pouches 12 has the closure system 28 attached thereto, it can be shipped to a manufacturer where the discrete pouches 12 can be filled and sealed. At the manufacturer, the sides 18 and 20 of each of the discrete pouches 12 can be manipulated. For example the sides 18 and 20 and/or the first and second major surfaces, 14 and 16 respectively, can be squeezed, pulled or somehow flexed towards one another, so as to form an enlarged opening 256 adjacent to the open end 26. Since the first major surface 14 of the discrete pouch 12 is bonded to the closure system 28 only at the opposite ends 242 and 244, the enlarged opening 256 will easily be formed. The enlarged opening 256 permits each of the discrete pouches 12 to be quickly and rapidly filled with items, articles or products. Usually for a liquid product or for small granular products, the products can be dispensed into an empty pouch 12 via an injection or hopper system. Alternatively, the discrete pouches 12 can be manually filled, if desired.

[0133] After the discrete pouches 12 have been filled with items, articles or products, the manufacturer will then flatten the open end 26 of each of the discrete pouches 12 and bond or seal the inner surface 40 of the second leg 34 to the inside surface 202 of the first major surface 14. This action will cause the open end 26 of the discrete pouch 12 to be sealed shut. The bond or seal can be formed using heat, pressure, heat and pressure, ultrasonics, an adhesive, a co-adhesive, a mechanical connector, double sided tape, etc. Once the discrete pouches 12 are filled and sealed, the filled pouches 12 can be shipped to a warehouse, distributor, retailer, etc. for sale or distribution to the ultimate consumer.

Article

[0134] The finished discrete pouches 12 shown in FIGS. 2-22 and 24-28 will now be described. Each of the discrete pouches 12 can be formed from various materials, described above. Desirably, each of the discrete pouches 12 can be formed from a single, identical material. It should be noted that the closure system 28 can be formed from a different material from the material used to construct the remainder of the discrete pouch 12. Furthermore, each of the discrete pouches 12 can be formed from a laminate having at least two layers. When a laminate is used, at least one of the layers of the laminate can be constructed so as to prevent air, a liquid or a fluid, or a combination thereof, from passing therethrough.

[0135] Each of the discrete pouches 12 includes a first major surface 14 having a transverse edge with a predetermined pattern 84 formed therein. The predetermined pattern 84 can be cut out of or be punched out of the material that will form the first and second major surfaces 14 and 16 respectively, as well as the pair of sides 18 and 20. The transverse edge of the first major surface 14 has a pair of opposite ends 242 and 244, see FIG. 27. Each of the discrete pouches 12 also has a second major surface 16 aligned opposite to the first major surface 14. The second major surface 16 has a transverse edge 204, see FIG. 24, with the predetermined pattern 84 formed therein. The predetermined pattern 84 formed in

both of the first and second major surfaces, 14 and 16 respectively, has a contiguous boundary, see FIG. 9. The base 90 and the legs 92 and 94 form the contiguous boundary. In addition, the transverse edges of the first and second major surfaces, 14 and 16 respectively, can be contiguous with one another. The second major surface 16 also has an inner surface 206, see FIG. 24.

[0136] Each of the discrete pouches 12 also has a pair of sides 18 and 20 joined to the first and second major surfaces, 14 and 16 respectively, by at least one longitudinal bond 124, see FIG. 15, to form a tubular structure 126'. Desirably, four, spaced apart longitudinal bonds 124, 124, 124 and 124 are present approximate each corner of a tubular structure 126, see FIG. 14. Desirably, heat and pressure is used to form the longitudinal bond(s) 124. Each of the sides 18 and 20 can be constructed to contain a gusset 22 or some other expandable structure.

[0137] Each of the discrete pouches 12 further includes a seal 136 which extends transversely across the tubular structure 126 or 126' to form a closed bottom 24, see FIG. 16.

[0138] Lastly, each of the discrete pouches 12 includes a closure system 28. The closure system 28 can vary such that it includes a closure system having a slide mechanism, a press-to-close closure system, a cohesive closure system, a closure system using Velcro®, etc. Referring to the closure system shown in FIGS. 3-6, the closure system 28 includes a track 30 having a first leg 32 and a second leg 34. Each of the legs 32 and 34 has an outer surface 38 and 42 respectively. The outer surface 38 of the first leg 32 is secured to the inner surface 206 of the second major surface 16 adjacent to the transverse edge 204, see FIG. 24. The first and second legs, 32 and 34 respectively, are joined together by an opening/closing mechanism 46 which includes a member 52 capable of being manually moved back and forth such that the opening/closing mechanism 46 can be sequentially opened and closed. The pair of opposite ends 242 and 244 of the first major surface 14 is secured to the outer surface 42 of the second leg 34 to form an open top 26 located adjacent to the transverse edge of the first major surface 14, see FIG. 28. The open top 26 is aligned opposite to the seal 136 and is spaced apart therefrom. The open top 26 is located horizontally between the pair of opposite ends 242 and 244.

[0139] It should be understood that the open top 26 of each of the discrete pouches 12 is designed to be sealed after each of the discrete pouches 12 is filled with items, articles or products.

[0140] While the invention has been described in conjunction with several specific embodiments, it is to be understood that many alternatives, modifications and variations will be apparent to those skilled in the art in light of the foregoing description. Accordingly, this invention is intended to embrace all such alternatives, modifications and variations which fall within the spirit and scope of the appended claims.

We claim:

1. A discrete pouch comprising:

- a) a first major surface having a transverse edge with a predetermined pattern formed therein, said transverse edge having a pair of opposite ends;
- b) a second major surface aligned opposite to said first major surface, said second major surface having a transverse edge with said predetermined pattern formed therein, said predetermined pattern in said first and second major surfaces having a contiguous boundary, and said second major surface having an inner surface;

- c) a pair of sides joined to said first and second major surfaces to form a tubular structure;
 - d) a seal extending transversely across said tubular structure to form a closed bottom; and
 - e) a closure system including a track having a first leg and a second leg, each leg having an outer surface, said outer surface of said first leg being secured to said inner surface of said second major surface adjacent to said transverse edge, said first and second legs being joined together by an opening/closing mechanism which includes a member capable of being manually moved back and forth such that said opening/closing mechanism can be sequentially opened and closed, and said pair of opposite ends of said first major surface being secured to said outer surface of said second leg to form an open top located adjacent to said transverse edge of said first major surface, said open top being aligned opposite to said seal and being spaced apart therefrom.
2. The discrete pouch of claim 1 wherein each of said pair of sides contains a gusset.
3. The discrete pouch of claim 1 wherein said seal is a K-shaped seal.
4. The discrete pouch of claim 3 wherein said K-shaped seal includes an elongated segment that extends between said pair of sides and two spaced apart shorter segments that angle outward from said elongated segment, and each of said shorter segments intersects with one of said pair of sides.
5. The discrete pouch of claim 4 wherein said two shorter segments extend away from said closed bottom.
6. The discrete pouch of claim 1 wherein said discrete pouch is formed from a laminate having at least two layers and at least one of said layers can prevent a liquid from passing therethrough.
7. The discrete pouch of claim 1 wherein said pair of sides is joined to said first and second major surfaces by four, spaced apart longitudinal bonds to form said tubular structure.
8. The discrete pouch of claim 1 wherein said discrete pouch is formed from a thermoplastic material and said predetermined pattern is cut from said first and second major surfaces.
9. The discrete pouch of claim 1 wherein said predetermined pattern comprises a pair of spaced apart, approximately C-shaped configurations, and each of said pair of approximately C-shaped configurations has a base member with two legs extending outward from said base member.
10. A discrete pouch comprising:
- a) a first major surface having a transverse edge with a predetermined pattern formed therein, said transverse edge having a pair of opposite ends;
 - b) a second major surface aligned opposite to said first major surface, said second major surface having a transverse edge with said predetermined pattern formed therein, said predetermined pattern in said first and second major surfaces having a contiguous boundary, and said second major surface having an inner surface;
 - c) a pair of sides joined to said first and second major surfaces by at least one longitudinal bond to form a tubular structure, each of said pair of sides containing a gusset, and said first and second major surfaces and said pair of sides being formed from an identical material;
 - d) a seal extending transversely across said tubular structure to form a closed bottom; and
 - e) a closure system including a track having a first leg and a second leg, each leg having an outer surface, said outer surface of said first leg being secured to said inner surface of said second major surface adjacent to said transverse edge, said first and second legs being joined together by an opening/closing mechanism which includes a member capable of being manually moved back and forth such that said opening/closing mechanism can be sequentially opened and closed, and said pair of opposite ends of said first major surface being secured to said outer surface of said second leg to form an open top located adjacent to said transverse edge of said first major surface, said open top being aligned opposite to said seal and being spaced apart therefrom.
11. The discrete pouch of claim 10 wherein said at least one longitudinal bond and said seal are formed using heat and pressure.
12. The discrete pouch of claim 10 wherein said first and second major surfaces and said pair of sides are formed from a laminate having at least two layers, and at least one of said layers can prevent air from passing therethrough.
13. The discrete pouch of claim 10 wherein said seal is K-shaped and includes an elongated segment that extends between said pair of sides and two spaced apart shorter segments that angle outward from said elongated segment, and each of said shorter segments intersects with one of said pair of sides.
14. The discrete pouch of claim 10 wherein said closure system is a zipper.
15. The discrete pouch of claim 10 wherein said open top of said closure system is designed to be sealed after said discrete pouch is filled with articles.
16. A discrete pouch comprising:
- a) a first major surface having a transverse edge with a predetermined pattern formed therein, said transverse edge having a pair of opposite ends;
 - b) a second major surface aligned opposite to said first major surface, said second major surface having a transverse edge with said predetermined pattern formed therein, said transverse edges of said first and second major surfaces being contiguous, said predetermined pattern being cut into both said first and second major surfaces and having a contiguous boundary, and said second major surface having an inner surface;
 - c) a pair of sides joined to said first and second major surfaces by at least one longitudinal bond to form a tubular structure, and each of said pair of sides containing a gusset;
 - d) a seal extending transversely across said tubular structure to form a closed bottom; and
 - e) a closure system including a track having a first leg and a second leg, each leg having an outer surface, said outer surface of said first leg being secured to said inner surface of said second major surface adjacent to said transverse edge, said first and second legs being joined together by an opening/closing mechanism which includes a member capable of being manually moved back and forth such that said opening/closing mechanism can be sequentially opened and closed, and said pair of opposite ends of said first major surface being secured to said outer surface of said second leg to form an open top located adjacent to said transverse edge of said first major surface, said open top being aligned opposite to said seal and being spaced apart therefrom.

17. The discrete pouch of claim **16** wherein said open top is located between said pair of opposite ends of said first major surface.

18. The discrete pouch of claim **17** wherein said first major surface has a width and said open top extends across at least 75% of said width.

19. The discrete pouch of claim **16** wherein said closure system is a zipper.

20. The discrete pouch of claim **16** wherein said open top of said closure system is designed to be sealed after said discrete pouch is filled with articles.

* * * * *