



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

published in accordance with Art. 158(3) EPC

Note: Bibliography reflects the latest situation

(15) Correction information:

Corrected version no 1 (W1 A1)
INID code(s) 54

(51) Int Cl.:

C22C 14/00 ^(1974.07) **C23G 1/12** ^(1968.09)

(48) Corrigendum issued on:

26.04.2006 Bulletin 2006/17

(86) International application number:

PCT/JP2003/007297

(43) Date of publication:

25.05.2005 Bulletin 2005/21

(87) International publication number:

WO 2003/104506 (18.12.2003 Gazette 2003/51)

(21) Application number: **03736120.1**

(22) Date of filing: **09.06.2003**

(84) Designated Contracting States:

**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR**

(72) Inventor: **TAKAHASHI, Wataru,**
Sumitomo Metal Industries, Ltd.
Osaka-shi, Osaka 541-0041 (JP)

(30) Priority: **11.06.2002 JP 2002169441**

(74) Representative: **Simons, Amanda Louise**
J.A. Kemp & Co.,
14 South Square,
Gray's Inn
London WC1R 5JJ (GB)

(71) Applicant: **SUMITOMO METAL INDUSTRIES, LTD.**
Osaka-shi,
Osaka 541-0041 (JP)

(54) **BETA TYPE TITANIUM ALLOY AND PROCESS FOR PRODUCING THE SAME**

(57) The present invention provides a β type titanium alloy **characterized by** consisting of, by mass %, V: 15 to 25%, Al: 2.5 to 5%, Sn: 0.5 to 4%, O (Oxygen): not more than 0.20%, H: not more than 0.03%, Fe: not more than 0.40%, C: not more than 0.05% and N: not more than 0.02%, and the balance Ti and impurities.

The present invention also provides a method of manufacturing a β type titanium alloy **characterized by** comprising the following steps (a) to (c):

(a) Preparing a β type titanium alloy consisting of, by mass %, V: 15 to 25%, Al: 2.5 to 5%, Sn: 0.5 to 4%, O (Oxygen): not more than 0.20%, H: not more than 0.03%, Fe: not more than 0.40%, C: not more than 0.05% and N: not more than 0.02%, and the balance Ti and impurities.

(b) Pickling the β type titanium alloy in an aqueous solution including 3 to 40 mass % of HF, and

(c) Further pickling the β type titanium alloy in an aqueous solution including 3 to 6 mass % of HF and 5 to 20 mass % of HNO_3 .

Fig. 1

