







FIG. 2

## SYSTEM AND METHOD FOR PRODUCING AN ORGANIC BASED FERTILIZER AND USABLE WATER FROM ANIMAL WASTE

### CROSS-REFERENCE TO RELATED APPLICATION

**[0001]** This application claims the benefit of provisional application 61/156,375 filed in the United States Patent and Trademark Office on Feb. 27, 2009, the complete disclosure of which is incorporated herein by reference and priority to which is claimed pursuant to 35 U.S.C. section 120.

### BACKGROUND OF THE INVENTION

**[0002]** 1. Field of the Invention

**[0003]** The present invention relates to a method of producing an organic based fertilizer and, in particular, to a method of producing an organic based fertilizer from animal waste in a closed loop system that conserves water.

**[0004]** 2. Description of the Related Art

**[0005]** In modern agricultural practice, it has become usual to employ an agricultural operation as an intensive feeding operation for raising hundreds or even thousands of livestock, for example swine and bovine animals, at a single location. Consequently, large amounts of animal waste are produced at such locations. The disposal of this waste in a hygienic and inoffensive manner is problematic.

**[0006]** More particularly, it has been suggested that hogs produce more than four times as much waste as humans. It has, for example, been planned to initiate a hog farm containing 2,000,000 hogs, which will produce an amount of waste equivalent to that produced by the city of Los Angeles. The current pig population of North Carolina is four times that number. Accidents in North Carolina, in which millions of gallons of hog excreta were released into the countryside, have drawn attention to the problems involved in the disposal of such waste. Applications for permits to construct large hog farms have been denied because of concerns about odours and waste disposal.

**[0007]** Animal waste, including hog waste, has traditionally been disposed of by spreading it over agricultural land as a liquid fertilizer. For sufficiently large cropped land bases this method of disposal can be performed safely. However, in areas of high population density or where multiple farms are closely clustered, and the land base is therefore relatively small, problems arise. For example, excess nutrients cannot be absorbed by crops and leach into ground water and surface water.

**[0008]** When land application is prevented, for example, because the ground is frozen or saturated with water and/or nutrients, the waste must be stored, usually in large pits, with consequential costs and environmental risk.

**[0009]** As an alternative to land disposal, it is also common practice to compost the waste. For this purpose, the waste is separated into solid waste and liquid waste through the use of inclined screens, sometimes followed by the use of belt or filter presses. These methods produce an output containing about 30% solid material at best. This is then mixed with a bulking material to facilitate aeration and an appropriate C:N ratio, and deposited in windrows for stabilization, over a period of about 45 to 60 days, by composting. This process may not ensure that pathogens in the waste are killed and the windrows are often odorous and may attract birds, rodents

and vermin. The liquid, approximately 90% of the total waste still has to be dealt with through land application.

**[0010]** The challenges involved in the treatment of animal waste include the destruction of pathogens, the controlled extraction of ammonium and other plant nutrients, and the disposal of organic matter.

**[0011]** It is known, from U.S. Pat. No. 4,093,544, issued Jun. 6, 1978, to David S. Ross, the full disclosure of which is incorporated herein by reference, to remove ammonium from wastewater by firstly increasing the pH value of the wastewater, then desorbing ammonium by vacuum and subsequently absorbing the desorbed ammonium in liquid having a pH value and temperature substantially less than that of the original wastewater.

**[0012]** It is further known from U.S. Pat. No. 5,914,040, issued Jun. 22, 1999, to Yvette Pescher et al., the full disclosure of which is also incorporated herein by reference, to purify a medium containing organic waste, for example animal waste, by subjecting the medium to treatment with an oxidizing agent, treatment with a flocculating agent, and treatment with at least one polyelectrolyte. The effluent thus obtained is filtered to provide a filtration cake and a filtrate.

**[0013]** It is still further known from U.S. Pat. No. 6,916,426, issued Jul. 12, 2005, to Van Slyke et al., the full disclosure of which is also incorporated herein by reference, that the extraction of nitrogen, potassium, and phosphorus from animal waste is substantially enhanced if the animal waste is treated promptly after production of the waste by the animals. More particularly, it is known that potassium is present in animal waste material in the form of an insoluble potassium urate, and a substantial amount of the potassium in animal waste material can be extracted in a solid form, as potassium urate, before microbial action breaks down the potassium urate to leave potassium and ammonium in solution. Extracted urates are then available for inclusion in a fertilizer. When the fertilizer is used on land, the microbes in the soil break down these urates, releasing the potassium and ammonia, but at a rate less than that at which these nutrients would be released in the soil if dissolved in water.

**[0014]** It is yet still further known from U.S. Pat. No. 7,232,036, issued Jun. 19, 2007, to Van Slyke et al., the full disclosure of which is also incorporated herein by reference, that solid waste may be rapidly separated from liquid waste using an inclined conveyor belt system.

### SUMMARY OF THE INVENTION

**[0015]** It is an object of the present invention to provide an improved system and method for producing an organic based fertilizer.

**[0016]** It is a particular object of the present invention to provide a system and method for producing an organic based fertilizer and usable water from swine and bovine waste collected on an agricultural operation.

**[0017]** In one embodiment of the system and method disclosed herein animal waste is collected at least once daily from a barn or other animal enclosure on an agricultural operation. Preferably solid waste is separated from liquid waste in the barn. The solid waste is directed to a bio-mass fuelled dryer. The dried solid waste may be used as a bio-mass fuel for the system, or supplemented with concentrated by-products of the treatment of the liquid waste and other nutrients, as required, to produce a commercially viable organic based fertilizer. If the solid waste is used as a bio-mass fuel for the system the resulting ash may be added as a supplement to

the solid waste prior to pelletizing the solid waste into a fertilizer. If the solid waste is not burned as a fuel for the system other suitable bio-mass fuel may be used.

[0018] The liquid waste is treated with chemicals for coagulation and flocculation to assist the settling of any particulates remaining in the liquid waste. The particulates are then collected and may be added as a supplement to the solid waste prior to pelletizing the solid waste into a fertilizer. After heating and pH adjustments, the liquid waste is passed against a gas transfer membrane to remove ammonia from the liquid waste. Once the ammonia passes through the membrane it is exposed to sulfuric acid to produce ammonium sulfate which may also be added as a supplement to the solid waste prior to pelletizing the solid waste into a fertilizer. The remaining liquid waste is passed through a direct contact distillation membrane to filter water in the liquid waste from the total dissolved solids in the liquid waste. The total dissolved solids may also be added as an additional supplement to the solid waste prior to pelletizing the solid waste into a fertilizer.

[0019] The water filtrate is treated with pH adjustments, cooling, and UV sterilization to produce water which is usable for both barn washing and animal drinking. This may significantly reduce fresh water consumption by over 50%.

[0020] In preferred embodiments the system operates continuously and is designed to process collected animal waste in 24 hours. The system collects a majority of the solid waste and, after any losses from using some the solid waste as a bio-mass fuel, the collected solid waste is pelletized into fertilizer. This produces a commercially viable fertilizer which may be sold to help offset operational costs, i.e nutrient imbalances on other agricultural operations may be rectified by transporting the dry pelletized fertilizers off-site. The resulting water filtrate may be diverted for irrigation at points dictated by the economics of the agricultural operator or recycled back to the barn for animal washing or drinking.

[0021] The system and method disclosed herein provide the advantage of reducing odours by rapidly separating the solid waste from the liquid waste in either the barn or a treatment building connected to, or adjacent, the barn or another enclosure housing livestock. This reduces the contact between urease found in the solid waste and urea found in the liquid waste thereby minimizing release of gases which are harmful to humans, animals, and the environment. Odours and greenhouse gases are also reduced by minimizing anaerobic activity which occurs in longer term storage methods common to other treatment systems currently in use. Agricultural operation can therefore exist closer to urban areas thereby reducing the cost of transporting the livestock to market.

[0022] Furthermore, water consumption may be significantly reduced on the agricultural operation through the recycling of water filtrate to the barn or another installation on the agricultural operation. Large scale agricultural operations will also not require disposal acreage for the storage and disposal of liquid manure slurries now used in the production of fertilizer.

[0023] Additional advantages of the system and method disclosed herein will be apparent to a person skilled in the art.

#### BRIEF DESCRIPTION OF DRAWINGS

[0024] The invention will be more readily understood from the following description of preferred embodiments thereof given, by way of example only, with reference to the accompanying drawings, in which:

[0025] FIG. 1 is a schematic diagram showing a first embodiment of an improved system and method for producing an organic based fertilizer and usable water from animal waste collected with in-barn conveyors on an agricultural operation; and

[0026] FIG. 2 is a schematic diagram showing a second embodiment of an improved system and method for producing an organic based fertilizer and usable water from animal waste collected by scraping or flushing on an agricultural operation.

#### DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0027] Referring to the drawings and first to FIG. 1 this is a schematic diagram showing a first embodiment of an improved system and method for producing an organic based fertilizer and usable water from animal waste collected on an agricultural operation. In this example, animal waste is collected in a barn 100 but in other embodiments animal waste may be collected anywhere on the agricultural operation. Preferably the animal waste is removed from the barn 100 using a conveyor system 190 similar to the type disclosed in U.S. Pat. No. 7,232,036, issued Jun. 19, 2007, to Van Slyke et al., the full disclosure of which is incorporated herein by reference. This allows for the rapid separation of solid wastes from liquid wastes.

[0028] In the example shown in FIG. 1, the conveyor system 190 disclosed by Van Slyke et al. is used to rapidly separate solid waste 102 from liquid waste 104 in the barn 100. The solid waste 102 is collected in a solid waste storage tank 106 and the liquid waste 104 is directed to a liquid waste storage tank 108. The solid waste 102 is directed from the solid waste storage tank to a dryer 110. Some of the dried solid waste may be used as a bio-mass fuel to power the system. However, in this example, a majority of the solid waste 102 is pelletized into a fertilizer while other available bio-mass fuels are used to power the system by fuelling the burners of dryer and heaters disclosed herein.

[0029] The liquid waste 104 is agitated in the liquid waste storage tank 108 to avoid settlement of any particulates in the liquid waste 104. The liquid waste 104 is then treated with a first polymer 112 as it is directed to a first clarifier 114. The first polymer 112 is a standard coagulating and/or flocculating agent readily available from chemical supply companies. For example, the first polymer 112 may be a polyacrylamide or polyamine. The purpose of the first polymer 112 is to accumulate suspended particulates in the liquid waste 104 so they can be more easily settled in the first clarifier 114. Sludge 116 from the first clarifier 114 is directed to a sludge storage tank 118 from which it is then directed through a first heater 120 to a filter press 122. Filter cake 124 from the filter press 122 is dried in the dryer 110 and used to supplement the solid waste material being pelletized into a fertilizer. In this example, the filter press 122 should be capable of producing a filter cake with a solid matter content of at least 30%. Filtrate 126 from the filter press 122 may be re-introduced into the first clarifier 114 for further processing.

[0030] Supernatant 128 from the first clarifier 114 may be released for irrigation as will be discussed in greater detail below. However, in this example, most of the supernatant 128 is treated with lime 130 (to increase pH) and a second polymer 132 as it is directed to a second clarifier 134. The second polymer 132 is a standard coagulating and/or flocculating agent readily available from chemical supply companies. For

example, the second polymer **132** may be a polyacrylamide or polyamine. Lime sludge **135** from the second clarifier **134** is directed to the sludge storage tank **118** from which it is directed to the first heater **120** and filter press **122**. As disclosed above, filter cake **124** from the filter press **122** is used to supplement the solid waste material being pelletized into a fertilizer. Filtrate **126** from the filter press **122** may be re-introduced into the first clarifier **114** for further processing.

[0031] Alternatively, the first clarifier **114** may be bypassed or even removed from the system all together. Liquid waste **104** from the liquid waste storage tank **108** would then be treated with lime **130** and the second polymer **132** as it is directed to the second clarifier **134**. This would occur in situations where supernatant **128** from the first clarifier **114** will not be released for irrigation. In other embodiments, the clarifiers **114** and **134** may be provided with a skimmer for collecting any floating materials in the liquid waste which will not settle in the clarifiers **114** and **134**, for example, spilled feed or diarrhea which comprises undigested feed. The collected floating materials are directed to the sludge storage tank **118** for further processing. Other means to collect floating materials may also be employed such as dissolved air flotation or charged air flotation.

[0032] Supernatant **136** from the second clarifier **134** is passed through a second heater **138** before being passed through an ammonia extractor **140**. In some cases, the supernatant **136** may be subject to filtration prior to being passed through the ammonia extractor **140**, particularly; if the supernatant **136** contains solid particulates. The solid particulates would then be returned to the sludge storage tank **118** for further treatment. In this example, the ammonia extractor **140** includes a series of gas transfer membranes **142a**, **142b** and **142c** which allow the ammonia gas to transfer and make contact with sulfuric acid **150** on the other side of the membranes and combine to make ammonium sulfate **146** and an aqueous solution **148**. In other embodiments other methods of ammonia extraction may be used and other ammonium salts, such as ammonium nitrate, may be produced. The ammonium salts may be used to supplement the solid waste material being pelletized into a fertilizer. The aqueous solution **148** may be released for irrigation as will be discussed in greater detail below. However, in this example, most the aqueous solution **148** is treated with sulfuric acid **150** for pH normalization and both the aqueous solution **148** and ammonium sulfate **146** are passed through a third heater **152**.

[0033] After being heated the aqueous solution **148** is passed through Direct Contact Distillation Membranes **154a** and **154b**, or any other system such as a nanotube filtering system, that allows drinking water to pass through the membrane. Such systems typically heat a solution causing water vapour from the warm side to pass through the membrane and condense with a colder solution on the cold side. An example of a suitable Direct Contact Distillation Membrane is disclosed in United States Patent Application Publication Number 2006/0076294 A1 which was filed by Sirkar et al. on Jul. 26, 2006 and the full disclosure of which is incorporated herein by reference. The Direct Contact Distillation Membranes **154a** and **154b** separate the aqueous solution **148** into concentrated dissolved solids or concentrate **156** and a drinking water filtrate **158**. The concentrate **156** is used to supplement the solid waste material being pelletized into a fertilizer. The drinking water filtrate **158** is exposed to UV light in a sterilizer **160** and passed through a cooler **162** prior to being recycled back as return water **164** into the barn **100** for wash-

ing or drinking. It is desirable for the return water **164** to have less than 3,000 ppm total dissolved solids.

[0034] Referring back to the solid waste **102**, the dryer **110** lowers the moisture level of the solid waste **102**, filter cake **124**, and concentrate **156** to a suitable level to pelletize. Dryer exhaust of warm moist air and dust is directed to a dust collector **166** which separates the dust for return to the solid wastes for pelletizing while directing the air stream to a bio-filter **168** to further condense moisture and reduce odours before being released as air **170**. Condensate **172** from the bio-filter may be re-introduced into the second clarifier **134** for further treatment.

[0035] If any of the dried solid waste is used as a bio-mass fuel to power the system, the ash **174** may also be used to supplement the solid waste material being pelletized into a fertilizer. Likewise ash from any bio-mass fuel may be used to supplement the solid waste material being pelletized into a fertilizer. Other foreign supplements **176** may also be used to supplement the solid waste material being pelletized into a better balanced fertilizer for the market. The supplemented dried solid waste is pelletized and cooled in a pelletizer **178**. The pelletized fertilizer may be kept in an on-site storage **180**.

[0036] Referring now to FIG. 2, this is a schematic diagram showing a second embodiment of an improved system and method for producing an organic based fertilizer and usable water from animal waste collected on an agricultural operation. In FIG. 2 like components have been given like reference numerals as in FIG. 1 with the expectation that the reference numerals are in the 200 series as opposed to the 100 series, i.e. the barn is given reference numeral **100** in FIG. 1 and reference numeral **200** in FIG. 2. Similarly the dryer has been given reference numeral **110** in FIG. 1 and reference numeral **210** in FIG. 2.

[0037] In the example shown in FIG. 2, animal waste is collected by scraping or flushing the gutters of a barn **200**. This results in slurry **201** of solid waste and liquid waste which may contain bedding or stringy components. The slurry **201** is passed through a chopper pump **203** to promote homogeneity. The collected slurry **201** is stored and agitated in a slurry storage tank **205** to avoid the settlement of any particulates. The slurry is then passed through a heater **207** and treated with a polymer **209** as it is directed to a filter press **222**. The polymer **209** is a standard coagulating and/or flocculating agent readily available from chemical supply companies. For example, the polymer **209** may be a polyacrylamide or polyamine. The purpose of the purpose of the polymer is to accumulate suspended particulates in the slurry **205** so they can be more easily processed by the filter press **222**.

[0038] Filter cake **224** from the filter press **222** is directed to a dryer **210** and is treated in a manner substantially similar as described above for the solid waste **102** in the first embodiment of the system and method disclosed herein.

[0039] The filtrate **226** from the filter press **222** is directed to a first clarifier **214** or alternatively re-introduced into the slurry storage tank **205** to assist filter press operation or returned to the barn **200** as a replacement for flushing volumes. If the filtrate is directed to the first clarifier **214** it is treated in a substantially similar manner as described above for the liquid waste **104** in the first embodiment of the system and method disclosed herein.

[0040] In both embodiments disclosed herein the supernatant **128** or **228** may be released from the system for irrigation through an outlet port **182** or **282** after passing through the

first clarifier **114** or **214**. This results in a liquid fertilizer with low suspended solids and a nitrogen content that is desirable for some crops. The aqueous solution **148** or **248** may also be released for irrigation after passing through the ammonia extractor **140** or **240**. Heat levels of the aqueous solution **148** or **248** can be altered by varying the position of an outlet port **184** or **284** to a point after the third heater **152** or **252**. This also results in a liquid fertilizer with low suspended solids and a nitrogen content that is desirable for some crops.

**[0041]** The system disclosed herein accordingly provides a multistep substantially closed loop system that provides flexibility to an operator of an agricultural operation. Nutrients from solid waste may be packaged in a form that may be easily transported and sold. However, the system also allows for varied uses of liquid wastes as well.

**[0042]** If the operator desires irrigation water with all dissolved nutrients and minimal suspended solids then the supernatant **128** or **228** is drawn off after passing through the first clarifier **114** or **214**.

**[0043]** If the operator desires irrigation water with ammonia and some dissolved nutrients withdrawn then the aqueous solution **148** or **248** is drawn off after pH normalization with sulfuric acid **150** or **250**. In this situation the dosages of the sulfuric acid **150** or **250** as well as the lime **130** or **230** and the second polymer **132** or **232** may be varied to meet the operator's pH requirements. This would provide a liquid fertilizer by-product of ammonium sulfate which may be used by the operator or sold off-set operational costs.

**[0044]** If the operator desires drinking and washing water for animals the filtrate **158** or **258** from the Direct Contact Distillation Membranes should have acceptable pathogen levels. However, as a precaution, further sterilization of the filtrate **158** or **258** is done using UV light in the sterilizer **160** or **260**. Also, since animals prefer cool drinking water the filtrate **158** or **258** is also passed through the cooler **162** or **262** prior to being return to the barn **100** or **200** as return water **164** or **264**.

**[0045]** In the embodiment of FIG. 1, by-products of the treatment of the liquid waste **104** are re-introduced into the system during the treatment of the solid waste **102** in order to preserve nutrients and avoid other disposal methods.

**[0046]** It will be understood by a person skilled in the art that many of the details provided above are by way of example only, and are not intended to limit the scope of the invention which is to be determined with reference to following claims.

1. (canceled)
2. (canceled)
3. (canceled)
4. (canceled)
5. (canceled)
6. (canceled)
7. (canceled)
8. (canceled)

9. A method of producing an organic based fertilizer and usable water from animal waste, the method comprising the steps of:

- (a) collecting the animal waste;
- (b) clarifying the animal waste and thereby producing a supernatant and a sludge;
- (c) pressing the sludge into a filter cake;

(d) extracting ammonia from the supernatant to produce an ammonium salt and an aqueous solution;

(e) filtering the aqueous solution to produce a concentrate and the usable water;

(f) forming the filter cake into the organic based fertilizer.

**10.** The method as claimed in claim **9** further including the step of treating the animal waste with a coagulating agent or a flocculating agent prior to clarifying the animal waste.

**11.** The method as claimed in claim **9** further including the step of using the concentrate to supplement the filter cake being formed into the organic based fertilizer.

**12.** The method as claimed in claim **9** further including the step of using the ammonium salt to supplement the filter cake being formed into the organic based fertilizer.

**13.** The method as claimed in claim **9** further including the step of using a portion of the supernatant as a liquid fertilizer.

**14.** The method as claimed in claim **9** further including the step of using a portion of the aqueous solution as a liquid fertilizer.

**15.** The method as claimed in claim **9** further including the step of sterilizing the water filtrate prior to using the water filtrate as drinking and washing water.

**16.** A method of producing an organic based fertilizer and usable water from animal waste, the method comprising the steps of:

- (a) collecting a slurry of animal waste;
- (b) treating the slurry with a chemical selected from the group consisting of a coagulating agent and a flocculating agent;
- (c) pressing the slurry into a filter cake and a filtrate;
- (d) clarifying the filtrate to produce a supernatant and a sludge;
- (e) pressing the sludge into further filter cake;
- (f) extracting ammonia from the supernatant to produce an ammonium salt and an aqueous solution;
- (g) filtering the aqueous solution to produce a concentrate and the usable water;
- (h) forming the filter cake into the organic based fertilizer.

**17.** A system for producing an organic based fertilizer and usable water from animal waste, the system comprising:

- a waste storage tank for storing animal waste;
- a clarifier for separating the animal waste into a supernatant and a sludge;
- a filter press for pressing the sludge into a filter cake;
- an ammonium extractor for extracting ammonium from the supernatant to produce an ammonium salt and an aqueous solution;
- a filter for filtering the aqueous solution to produce a concentrate and the usable water; and
- a pelletizer for pelletizing the filter cake into the organic based fertilizer.

**18.** The system as claimed in claim **17** further including a conveyor for separating the animal waste into liquid waste and solid waste wherein the waste storage tank is a liquid waste storage tank.

**19.** The system as claimed in claim **18** further including a solid waste storage tank for storing the solid waste.

**20.** The system as claimed in claim **17** further including a sterilizer for sterilizing the usable water.

\* \* \* \* \*