

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
15 February 2007 (15.02.2007)

PCT

(10) International Publication Number
WO 2007/016996 A1(51) International Patent Classification:
C07C 2/14 (2006.01) C07C 2/30 (2006.01)

Riyadh (SA). ALI, Talal [LB/SA]; Saudi Basic Industries Corporation, P.O. Box 5101, 11422 Riyadh (SA).

(21) International Application Number:
PCT/EP2006/005646

(74) Agents: WINKLER, Andreas et al.; Boehmert & Boehmert, Hollerallee 32, 28209 Bremen (DE).

(22) International Filing Date: 13 June 2006 (13.06.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
05016527.3 29 July 2005 (29.07.2005) EP

(71) Applicants (for all designated States except US): LINDE AG PATENT- UND LIZENZABTEILUNG [DE/DE]; Abraham-Lincoln-Str. 21, 65189 Wiesbaden (DE). SAUDI BASIC INDUSTRIES CORPORATION [SA/SA]; P.O. Box 5101, 11422 Riyadh (SA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): FRITZ, Peter [DE/DE]; Truderinger Strasse 21, 82008 Unterhaching (DE). BÖLT, Heinz [DE/DE]; Schießtättstraße 12b, 82515 Wolfratshausen (DE). HOFFMANN, Karl-Heinz [DE/DE]; Erikstrasse 11, 82110 Germering (DE). KÖHLER, Markus [DE/DE]; Schönstr. 73, 81543 München (DE). ZANDER, Hans-Jörg [DE/DE]; Ludwigshöher Strasse 42, 81479 München (DE). MOSA, Fuad [SA/SA]; Saudi Basic Industries Corporation, P.O. Box 5101, 11422

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.



WO 2007/016996 A1

(54) Title: METHOD FOR PREPARING LINEAR ALPHA-OLEFINS WITH IMPROVED HEAT REMOVAL

(57) Abstract: The present invention relates to a method for preparing linear alpha-olefins by oligomerizing of ethylene in the presence of a first organic solvent and a homogenous catalyst in a reactor, characterized in that the reactor overhead is cooled by means of a refrigerant.

Method for preparing linear alpha-olefins with improved heat removal

The present invention relates to a method for preparing linear alpha-olefins (LAO) by oligomerizing of ethylene in the presence of a first organic solvent and a homogenous catalyst in a reactor.

The oligomerization of ethylene using an organometallic catalyst is widely known in the art. The oligomerization is highly exothermic so that reaction heat has to be removed from the reactor to prevent a runaway.

DE 43 38 414 C1 discloses a method for the preparation of linear alpha-olefins, wherein polymer grade ethylene is re-circulated to remove the reaction heat. Therefore, ethylene feed (having an ethylene content of approximately 100% with minor amounts of impurities) is introduced into the reactor at a lower temperature, and non-oligomerized monomeric ethylene is removed at a higher temperature, cooled down and re-introduced into the reactor.

It was found that only about 3% of the ethylene feed is used in the oligomerization process, wherein the remainder is utilized as cooling media. Ethylene is quite expensive.

Additionally, it was found that for sufficient heat removal the ethylene cooling cycle gas flow rate has to be sufficiently high resulting in increased demands for equipment, piping, power consumption, etc.

According to the state of the art, a typical overhead temperature of a reactor for the oligomerization of ethylene to produce linear alpha-olefins is about 50°C, whereas the bottom temperature of the reactor is about 60 to about 100°C. In this case, the cooling of the overhead is usually achieved by means of cooling water, preferably utilizing a condenser. Based on these conditions and the application of toluene as suitable solvent, a small amount of toluene is evaporized at reactor bottoms, flows upwards to the reactor overhead, is partly condensed and serves as internal

reflux. This internal cycle contributes to the heat removal from the reactor only with a very small percentage.

It is therefore an object of the present invention to provide a method for preparing linear alpha-olefins by oligomerizing of ethylene which method overcomes the disadvantages of the prior art. Especially, a method shall be provided showing an improved heat removal from the reactor, together with a significant reduction of cooling cycle gas flow rate, resulting in savings for equipment, piping, power consumption, etc..

This object is achieved in that the reactor overhead temperature is cooled by means of a refrigerant.

Preferably, the temperature in the reactor overhead is held at about 15 to about 20°C, preferably by a condenser.

More preferably, the refrigerant is propylene.

Additionally, the method may be carried out in the presence of at least one cooling medium added to the reactor and condensing at the top of the reactor and re-evaporating at reactor bottoms.

Preferably, the cooling medium is selected so that it substantially remains within the reactor while operating the method.

In one also preferred embodiment, the cooling medium is selected from an inert second organic solvent having a boiling point of at least about 120°C at atmospheric pressure.

The first organic solvent may be toluene.

Preferably, the catalyst comprises a zirconium salt of organic acids and at least one organoaluminum compound.

It is proposed that the zirconium salt has the formula $ZrCl_{4-m}X_m$, wherein $X = OCOR$ or OSO_3R' with R and R' being independently alkyl, alkene or phenyl, and wherein $0 < m < 4$.

The at least one aluminum compound may be $Al(C_2H_5)_3$, $Al_2Cl_3(C_2H_5)_3$, $AlCl(C_2H_5)_2$ or mixtures thereof.

Finally, the bottom temperature of the oligomerization reactor is between about 60 to about 100°C.

Surprisingly, it was found that cooling of the reactor overhead by means of a refrigerant, preferably by a reduction of the reactor overhead temperature to about 15 to about 20°C significantly increases the internal cooling cycle. Additionally, the high ethylene feed being so far essential for heat removal, can be reduced, and thus the cooling cycle gas flow rate can be significantly reduced. This further results in savings for equipment, piping, power consumption, etc..

In a preferred embodiment, an appropriate cooling medium can be further introduced into the LAO reactor providing a further improved removal of the heat generated due to the exothermic oligomerization process. The cooling medium which is to be introduced into the reactor, preferably injected, is selected so that the cooling medium may easily condensate at the top of the reactor, but may be also easily re-evaporated at reactor bottoms. Further, the boiling point at atmospheric pressure of the cooling medium is preferably selected in that it satisfactorily avoids the discharge of the cooling medium from the reactor.

According to the inventive method a direct internal cooling may be achieved.

The method of the present invention is now illustrated in detail.

Catalyst dissolved in a suitable solvent, such as toluene, is fed to an oligomerization reactor. Additionally, ethylene is supplied to the reactor, and a cooling medium may be also provided for introduction therein. The cooling medium is selected so that it may easily condensate at the top of the reactor, but may be also easily re-evaporated at reactor bottoms. In the reactor, ethylene is oligomerized to obtain linear alpha-olefins. Especially, the oligomerization of ethylene is conducted in the reactor, when the feed of ethylene bubbles through the mixture of solvent and catalyst. The products of the oligomerization remain dissolved in the solvent. The temperature of the reactor bottom is about 60 to about 100°C.

The temperature of the reactor overhead is held at about 15 to about 20°C, preferably by application of a refrigerant, preferably utilizing a condenser. In this matter, the internal cooling cycle within the reactor is significantly increased. From the reactor, a mixture of ethylene and light alpha-olefins may be removed via the reactor overhead and may be collected in a separator. The liquid obtained, comprising solvent and alpha-olefins, may be re-circulated into the reactor. The part from the separator remaining gaseous may be further cooled in a cooling device to a temperature of about 5°C and is then transferred into a second separator. In the cooling device the cooling is adjusted so that olefins heavier than ethylene are liquefied. The linear alpha-olefins obtained may then be further processed as is known in the art. Non-consumed ethylene may be, in admixture with a fresh feed thereof, again introduced into the reactor. A liquid mixture comprising solvent, catalyst and linear alpha-olefins may be discharged from the reactor via a line above the reactor bottom and may be further processed as known in the art.

The features disclosed in the foregoing description, in the drawing or in the claims may, both separately and in any combination thereof, be material for realizing the invention in diverse forms thereof.

Claims

1. Method for preparing linear alpha-olefins by oligomerizing of ethylene in the presence of a first organic solvent and a homogenous catalyst in a reactor, characterized in that the reactor overhead is cooled by means of a refrigerant.
2. Method according to claim 1, wherein the temperature in the reactor overhead is held at about 15 to about 20°C, preferably by a condenser.
3. Method according to claim 2, wherein the refrigerant is propylene.
4. Method according to any of the preceding claims, wherein the method is carried out in the presence of at least one cooling medium added to the reactor and condensing at the top of the reactor and re-evaporating at reactor bottoms.
5. Method according to claim 4, wherein the cooling medium is selected so that it substantially remains within the reactor while operating the method.
6. Method according to claim 4 or 5, wherein the cooling medium is selected from an inert second organic solvent having a boiling point of at least about 120°C at atmospheric pressure.
7. Method according to any of the preceding claims, wherein the first organic solvent is toluene.
8. Method according to any of the preceding claims, wherein the catalyst comprises a zirconium salt of organic acids and at least one organoaluminum compound.

9. Method according to claim 8, wherein the zirconium salt has the formula $ZrCl_{4-m}X_m$, wherein $X = OCOR$ or OSO_3R' with R and R' being independently alkyl, alkene or phenyl, and wherein $0 < m < 4$.
10. Method according to claim 9, wherein the at least one aluminum compound is $Al(C_2H_5)_3$, $Al_2Cl_3(C_2H_5)_3$, $AlCl(C_2H_5)_2$ or mixtures thereof.
11. Method according to any of the preceding claims, wherein the bottom temperature of the oligomerization reactor is between about 60 to about 100°C.

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2006/005646

A. CLASSIFICATION OF SUBJECT MATTER
INV. C07C2/14 C07C2/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2004/029012 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V; ARNOLDY, PETER; DE BOE) 8 April 2004 (2004-04-08) page 1, line 1 – line 8 page 4, line 3 – page 5, line 18 claims 1-3	1-7,11
Y	-----	8-10
X	DE 43 38 414 C1 (LINDE AG, 65189 WIESBADEN, DE) 16 March 1995 (1995-03-16) cited in the application column 1, line 47 – column 3, line 41	1-11
Y	-----	8-10

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

26 September 2006

Date of mailing of the international search report

09/10/2006

Name and mailing address of the ISA/
European Patent Office, P.B. 5818 Patentlaan 2
NL – 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

O'Sullivan, Paul

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No
PCT/EP2006/005646

Patent document cited in search report	Publication date		Patent family member(s)	Publication date
WO 2004029012	A	08-04-2004	AU 2003271645 A1	19-04-2004
			CA 2499887 A1	08-04-2004
			CN 1735576 A	15-02-2006
			EP 1546069 A1	29-06-2005
			JP 2006500411 T	05-01-2006
			ZA 200502082 A	12-09-2005
DE 4338414	C1	16-03-1995	CN 1107828 A	06-09-1995