

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
28 December 2006 (28.12.2006)

PCT

(10) International Publication Number  
**WO 2006/136902 A1**

(51) International Patent Classification:  
**H04Q 7/38** (2006.01) **H04Q 7/32** (2006.01)

(74) Agents: **TEAGUE, Brian, J.** et al.; Alston & Bird LLP,  
Bank of America Plaza, 101 South Tryon Street, Suite  
4000, Charlotte, NC 28280-4000 (US).

(21) International Application Number:  
PCT/IB2006/001606

(22) International Filing Date: 1 June 2006 (01.06.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
11/157,613 21 June 2005 (21.06.2005) US

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **OOMMEN, Paul**  
[IN/US]; 8723 Stonecrest Drive, Irving, TX 75063 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,

[Continued on next page]

(54) Title: SYSTEM, TERMINAL, NETWORK ENTITY, METHOD, AND COMPUTER PROGRAM FOR SYSTEM SELECTION IN A MULTI-MODE COMMUNICATION SYSTEM



(57) Abstract: A terminal, network entity, system, method and computer program product enable communications to be established with an available system that is on a priority list and that has a desired service available. Communications may be established automatically with the system that is highest on the priority list and that has the desired service available. Alternatively, all of the systems that are on the priority list and that have the desired service available may be displayed to a user, such that the user may select one of the displayed systems and communications may be established with the selected system.

WO 2006/136902 A1



RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

**Published:**

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

SYSTEM, TERMINAL, NETWORK ENTITY, METHOD, AND COMPUTER  
PROGRAM PRODUCT FOR SYSTEM SELECTION IN A MULTI-MODE  
COMMUNICATION SYSTEM

FIELD OF THE INVENTION

Embodiments of the invention generally relate to wireless networks, and more particularly to system selection in a multi-mode wireless communication system.

5

BACKGROUND OF THE INVENTION

Wireless communication systems and networks are used in connection with many applications and devices, including for example, portable communication devices (PCDs) (e.g., cellular telephones), portable digital assistants (PDAs),  
10 laptop computers, or any suitable device that is capable of communicating with a wireless network. One significant benefit that wireless communications networks provide to a user of portable communication devices is to allow the user mobility to travel within and between networks.

Many different modes or types of wireless communications systems have  
15 been developed. These modes include GSM (Global Systems for Mobile Communication) (which may include WCDMA (Wideband Code Division Multiple Access)), CDMA (Code Division Multiple Access), WLAN (Wireless Local Area Network, based on the IEEE 802.11 standard), UMTS (Universal Mobile Telecommunications System), WiMAX (based on the IEEE 802.16  
20 standard), and the like. Different modes of communication may be provided in different geographic areas or by different communication service providers in the same geographic area. Multi-mode PCDs, which are capable of communicating over two or more different modes of networks, are becoming more common.

Because such multi-mode PCDs enable users to communicate with different types of systems, users may therefore be able to communicate in many different geographic areas.

When a user travels to a new geographic area with a PCD, the PCD will typically establish communication with one of the available systems in the new geographic area. Two or more different communication systems with which the PCD may communicate may be available in the new geographic area. As such, the PCD may select one of the communications systems and establish communication with the selected system. The PCD will typically use a predefined method for determining which communication system to select. Typically, each different mode of communication may use a different method for determining which communication system to select. Such methods may use a priority list, such as the Preferred Roaming List (PRL) used in CDMA systems, that is stored in the PCD. The priority list may be arranged by geographic area, and typically comprises a list of systems with which the PCD may establish communications depending on availability of each system. As the PCD enters a new geographic area, the PCD will typically attempt to establish communications with the first system on the priority list. If the first system on the priority list is not available, the PCD will typically attempt to establish communications with the second system on the priority list. The PCD will typically cycle through the priority list, attempting to establish communications with each successive system on the priority list, until the PCD is able to establish communications with one of the systems on the priority list. The systems that are contained in a priority list may vary based on the particular geographic area, the communication service provider for a particular PCD, and the reciprocal agreements between the communication provider for the particular PCD and other communication providers (e.g., roaming agreements). The priority list is typically stored in each PCD, and may be updated via the over-the-air service provision (OTASP). Each method of determining which communication system to select typically has a goal of ensuring basic voice service for the PCD.

When a user of a multi-mode PCD travels to a new geographic area, the multi-mode PCD may be able to establish communications with a number of

different systems corresponding to each different mode. For example, the user may have a PCD capable of communicating using GSM, CDMA, and UMTS. There may be several available GSM systems, several available CDMA systems, and several available UMTS systems in the area. Currently, the user would typically need to select which mode the user would prefer to use to establish communications. The PCD would then use the corresponding method of determining with which system to establish communication within the selected mode. There is a proposal to establish what may be termed a mode priority list. The mode priority list may be used by the PCD as an alternative to allowing the user to select the desired mode. The mode priority list may comprise a list of modes that the PCD is capable of using to communicate. The mode priority list would typically indicate the order in which the modes should be used by the PCD to attempt to establish communication. As the PCD attempts to establish communication within one particular mode, the PCD would typically use that mode's method of determining which system to select (e.g., the priority list). In the example multi-mode PCD described above, the mode priority list may indicate that communication should be attempted with CDMA first, then GSM, and finally UMTS. Typically, the PCD would first attempt to establish communications with the systems on the CDMA priority list (i.e., the PRL). If the PCD is unable to establish communications with any of the systems on the CDMA priority list, the PCD would then typically attempt to establish communications with the systems on the GSM priority list, as GSM is the next mode in the mode priority list. If the PCD is unable to establish communications with any of the systems on the GSM priority list, the PCD would then typically attempt to establish communications with the systems on the UMTS priority list, as UMTS is the next mode in the mode priority list. If the PCD is unable to establish communications with any of the systems on the UMTS priority list, the PCD would then typically attempt again with the CDMA priority list. Even under this proposed new method of determining which communication system to select, the goal would typically still be to ensure basic voice service for the PCD.

While basic voice service may be important to PCD users, many other services may be desired by users and provided by many, but not all,

communication service providers. Examples of such services include but are not limited to instant messaging (IM), push-to-talk (PTT), multimedia messaging service (MMS), device management, voice over internet protocol (VoIP), and other voice and data services. When a user travels to a new geographic area, the user may desire to continue using a service, such as MMS, that the user was using in the previous geographic area. As such, the user would prefer that the PCD establish communications with a system that is capable of providing the desired service. However, current methods for determining which communication system to select do not consider the availability of desired services.

10

#### BRIEF SUMMARY OF THE INVENTION

A terminal, network entity, system, method and computer program product are therefore provided in which communications may be established with an available system that is on a priority list and that has the desired service available. Communications may be established automatically with the system that is highest on the priority list and that has the desired service available. Alternatively, all of the systems that are on the priority list and that have the desired service available may be displayed to a user, such that the user may select one of the displayed systems and communications may be established with the selected system.

20 In this regard, a terminal for providing flexible system selection in a multi-mode communication system comprises a processor capable of receiving signals from at least two communication systems and establishing communication with one of the communication systems based on respective availability information for at least one desired service from each of the communication systems. The desired service may be selected from the group comprising instant messaging, push-to-talk, multimedia messaging service, device management, and voice over internet protocol (VoIP).

In one exemplary embodiment, the processor receives the respective availability information from the communication systems. In an alternative embodiment, the processor receives respective geographic information from the communication systems, and the processor is further capable of determining the

30

respective availability information for the desired service based on the geographic information.

The terminal may further comprise a storage element capable of accessing at least one system priority list. The system priority list may define respective  
5 geographic information for the communication systems, such that the processor is further capable of determining the respective availability information for the desired service based on the geographic information defined in the system priority list.

In one embodiment, the may comprise a storage element capable of  
10 accessing the desired service and accessing at least one system priority list. The system priority list may define the respective availability information for the at least one desired service. Alternatively, the processor may be further capable of establishing communication with the communication system that has a highest priority on the system priority list and has the desired service available. In another  
15 alternative embodiment, the processor may be further capable of receiving a user communication system selection from among all communication systems that are on the system priority list and that have the desired service available, and then establishing communication with the communication system selected by the user.

In addition to the terminal for providing flexible system selection in a  
20 multi-mode communication system as described above, other aspects of the present invention are directed to corresponding network entities, systems, methods and computer program products for providing flexible system selection in a multi-mode communication system.

## 25 BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING(S)

Having thus described the invention in general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

**FIG. 1** is a schematic block diagram of one type of system that would  
30 benefit from embodiments of the invention;

**FIG. 2** is a schematic block diagram of an entity capable of operating as a mobile station, terminal, and/or network entity, in accordance with embodiments of the invention;

**FIG. 3** is a schematic block diagram more particularly illustrating a mobile station or access terminal in accordance with one embodiment of the invention;

5 and

**FIG. 4** is a flowchart illustrating system selection in a multi-mode communication system, in accordance with one embodiment of the invention.

10 DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth

15 herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout.

Referring to FIG. 1, an illustration of one type of system that would benefit from embodiments of the present invention is provided. The system can include

20 one or more access terminals (AT) 10 (also termed terminals or mobile stations), each having an antenna 11 for transmitting signals to and for receiving signals from one or more base transceiver stations (BTS's) 14 (also termed base stations), two of which are shown in FIG. 1 (shown as including a source BTS 14a and a target BTS 14b). The BTS is a part of one or more cellular or mobile networks

25 that each includes elements required to operate the network. The user of the AT 10 may be executing a service such as IM, PTT, or MMS such that the AT is communicating with the source access network 12a. If the user is traveling away from source AN and toward the target access network 12b, the communication with the AT 10 must be handed off from the source AN to the target AN. The

30 service being executed by the AT typically must be available from the target AN if the AT is to continue executing the service.

A BTS acts as the interface between a network and an access terminal, in that the BTS converts digital data into radio signals and converts radio signals into digital data. Each BTS generally has an associated radio tower or antenna and communicates with various access terminals using radio links. In particular, BTSs  
5 communicate with various access terminals through the modulation and transmission of sets of forward signals, while BTSs receive and demodulate sets of reverse signals from various access terminals that are engaged in a wireless network activity (e.g., a telephone call, Web browsing session, etc.).

BTSs connect to one or more base station controllers (BSCs) 16 (e.g., using  
10 un-channelized T1 facilities or direct cables, although this is not required), two of which are shown in FIG. 1 (shown as including a source BSC 16a and a target BSC 16b). The connection between a BTS and a BSC may use, for example, un-channelized T1 facilities or direct cables. BSCs are used to interface (aggregate) all radio frequency (RF) traffic arriving from the antennas of the BTSs, and to  
15 provide this traffic to a mobile switching center 18 (MSC) two of which are shown in FIG. 1 (shown as including a source MSC 18a and a target MSC 18b). As known in the art, BSCs are generally responsible for managing the radio resources for one or more BTSs. For example, BSCs may handle radio-channel setup, frequency hopping, and handovers. Moreover, the MSC is responsible for  
20 providing the interface between the radio access network 12 (RAN), which includes BTSs 14, BSCs 16, and packet control functions 22 (PCFs) (including a source PCF 22a and a target PCF 22b), and a public switched telephone network 20 (PSTN) (including a source PSTN 20a and a target PSTN 20b). In particular, MSC 18 controls the signaling required to establish calls, and allocates RF  
25 resources to BSCs and PCFs. In operation, the MSC is capable of routing calls, data or the like to and from mobile stations when those mobile stations are making and receiving calls, data or the like. The MSC can also provide a connection to landline trunks when mobile stations are involved in a call.

PCFs are used to route IP packet data between access terminals (when  
30 within range of one of BTSs) and a packet data service node 24 (PDSN). A PDSN, in turn, may be used to provide access to one or more IP networks 28, such as, for example, the Internet, intranets, applications servers, or corporate virtual private

networks (VPNs). In this manner, a PDSN acts as an access gateway. A PDSN generally also acts as a client for an Authentication, Authorization, and Accounting (AAA) server 26. As known in the art, an AAA server may be used to authenticate and authorize access terminals before access is granted to an IP network. Once  
5 access is authorized, an access terminal may communicate with a content server 30, which may be capable of providing information and/or services to the access terminal.

Although not every element of every possible network is shown and described herein, it should be appreciated that the access terminal 10 may be  
10 coupled to one or more of any of a number of different networks using one or more of any of a number of different modes (also referred to herein as protocols). In this regard, access terminal(s) can be capable of supporting communication in accordance with any one or more of a number of first-generation (1G), second-generation (2G), 2.5G and/or third-generation (3G) mobile communication  
15 protocols or the like. More particularly, one or more mobile stations may be coupled to one or more networks capable of supporting communication in accordance with 2G wireless communication protocols IS-136 (TDMA), GSM, and IS-95 (CDMA). Also, for example, one or more of the network(s) can be capable of supporting communication in accordance with 2.5G wireless communication  
20 protocols GPRS, Enhanced Data GSM Environment (EDGE), or the like. In addition, for example, one or more of the network(s) can be capable of supporting communication in accordance with 3G wireless communication protocols such as Universal Mobile Telephone System (UMTS) network employing Wideband Code Division Multiple Access (WCDMA) radio access technology. Additionally, one  
25 ore more network(s) may be capable of supporting wide area network (WAN) communications, such as WLAN (IEEE 802.11) or WiMAX (802.16). Some narrow-band AMPS (NAMPS), as well as TACS, network(s) may also benefit from embodiments of the present invention, as should dual or higher mode mobile stations (e.g., digital/analog or TDMA/CDMA/analog phones).

30 Referring now to FIG. 2, a block diagram of an entity capable of operating as a mobile station, terminal, and/or network entity is shown in accordance with one embodiment of the invention. The entity capable of operating as a mobile

station, terminal, and/or network entity includes various means for performing one or more functions in accordance with exemplary embodiments of the present invention, including those more particularly shown and described herein. It should be understood, however, that one or more of the entities may include alternative  
5 means for performing one or more like functions, without departing from the spirit and scope of the present invention. More particularly, for example, as shown in FIG. 2, the entity can generally include a processor 38 connected to a memory 40. The memory can comprise volatile and/or non-volatile memory, and typically stores content, data or the like. For example, the memory typically stores content  
10 transmitted from, and/or received by, the entity. Also for example, the memory typically stores client applications, instructions or the like for the processor to perform steps associated with operation of the entity in accordance with embodiments of the present invention. As explained below, for example, the memory can store client application(s) including a configuration utility, content  
15 manager and/or display manager. In this regard, when executed, the configuration utility may function to configure a source of content to receive or otherwise provide content. The content manager, when executed, may function to manage the receipt of content from the source, and/or the use of content received from the source. And the display manager may function to manage presentation of content  
20 received from the source. As described herein, the client application(s) each comprise software operated by the respective entities. It should be understood, however, that any one or more of the client applications described herein can alternatively comprise firmware or hardware, without departing from the spirit and scope of the present invention.

25 In addition to the memory 40, the processor 38 can also be connected to at least one interface or other means for displaying, transmitting and/or receiving data, content or the like. In this regard, the interface(s) can include at least one communication interface 42 or other means for transmitting and/or receiving data, content or the like, as well as at least one user interface that can include a display  
30 44 and/or a user input interface 46. The user input interface, in turn, can comprise any of a number of devices allowing the entity to receive data from a user, such as a keypad, a touch display, a joystick or other input device.

Reference is now made to FIG. 3, which illustrates one type of access terminal or mobile station 10, a mobile telephone, which would benefit from embodiments of the present invention. It should be understood, however, that the mobile terminal illustrated and hereinafter described is merely illustrative of one type of mobile station that would benefit from the present invention and, therefore, should not be taken to limit the scope of the present invention. While several embodiments of the mobile station are illustrated and will be hereinafter described for purposes of example, other types of access terminals or mobile stations, such as portable digital assistants (PDAs), pagers, laptop computers, mobile gaming devices, and other types of electronic systems, can readily employ the present invention.

The terminal 10 includes various means for performing one or more functions in accordance with exemplary embodiments of the present invention, including those more particularly shown and described herein. It should be understood, however, that the terminal may include alternative means for performing one or more like functions, without departing from the spirit and scope of the present invention. More particularly, for example, as shown in FIG. 3, in addition to an antenna 14, the mobile station 10 can include a transmitter 48, receiver 50, and controller 52 or other processor that provides signals to and receives signals from the transmitter and receiver, respectively. These signals include signaling information in accordance with the air interface standard of the applicable cellular system, and also user speech and/or user generated data. In this regard, the mobile station can be capable of operating with one or more air interface standards, communication protocols, modulation types, and access types. More particularly, the mobile station can be capable of operating in accordance with any of a number of first generation (1G), second generation (2G), 2.5G and/or third-generation (3G) communication protocols or the like. For example, the mobile station may be capable of operating in accordance with 2G wireless communication protocols IS-136 (TDMA), GSM, and IS-95 (CDMA). Also, for example, the mobile station may be capable of operating in accordance with 2.5G wireless communication protocols GPRS, EDGE, or the like. Further, for example, the mobile station may be capable of operating in accordance with 3G

wireless communication protocols such as UMTS network employing WCDMA radio access technology. Additionally, the mobile station may be capable of operating in accordance with wide area network (WAN) communication protocols, such as WLAN (IEEE 802.11) or WiMAX (802.16). Some NAMPS, as well as  
5 TACS, mobile stations may also benefit from the teaching of this invention, as should dual or higher mode phones (e.g., digital/analog or TDMA/CDMA/analog phones).

It is understood that the controller 52 includes the circuitry required for implementing the audio and logic functions of the mobile station 10. For example,  
10 the controller may be comprised of a digital signal processor device, a microprocessor device, and various analog-to-digital converters, digital-to-analog converters, and other support circuits. The control and signal processing functions of the mobile station are allocated between these devices according to their respective capabilities. The controller can additionally include an internal voice  
15 coder (VC) 52a, and may include an internal data modem (DM) 52b. Further, the controller may include the functionality to operate one or more client software programs such as those indicated above, which may be stored in memory (described below).

The mobile station 10 also comprises a user interface including a  
20 conventional earphone or speaker 54, a ringer 56, a microphone 58, a display 60, and a user input interface, all of which are coupled to the controller 52. Although not shown, the mobile station can include a battery for powering the various circuits that are required to operate the mobile station, as well as optionally providing mechanical vibration as a detectable output. The user input interface,  
25 which allows the mobile station to receive data, can comprise any of a number of devices allowing the mobile station to receive data, such as a keypad 52, a touch display (not shown), a joystick (not shown) or other input device. In embodiments including a keypad, the keypad includes the conventional numeric (0-9) and related keys (#, \*), and other keys used for operating the mobile station.

30 The mobile station 10 can also include one or more means for sharing and/or obtaining data. For example, the mobile station can include a short-range radio frequency (RF) transceiver or interrogator 64 so that data can be shared with

and/or obtained from electronic devices in accordance with RF techniques. The mobile station can additionally, or alternatively, include other short-range transceivers, such as, for example an infrared (IR) transceiver 66, and/or a Bluetooth (BT) transceiver 68 operating using Bluetooth brand wireless technology developed by the Bluetooth Special Interest Group. The mobile station can therefore additionally or alternatively be capable of transmitting data to and/or receiving data from electronic devices in accordance with such techniques.

The mobile station 10 can further include memory, such as a subscriber identity module (SIM) 70, a removable user identity module (R-UIM), a smart card, or the like, which typically stores information elements related to a mobile subscriber. In addition to the SIM, the mobile station can include other removable and/or fixed memory. In this regard, the mobile station can include volatile memory 72, such as volatile Random Access Memory (RAM) including a cache area for the temporary storage of data. The mobile station can also include other non-volatile memory 74, which can be embedded and/or may be removable. The non-volatile memory can additionally or alternatively comprise an EEPROM, flash memory or the like. The memories can store any of a number of software applications, instructions, pieces of information, and data, used by the mobile station to implement the functions of the mobile station.

As will be appreciated, a number of the entities of the system of FIG. 1 can be configured in any of a number of different architectures to perform any of a number of functions. For example, the entities of the system of FIG. 1 can be configured in a centralized client-server architecture, decentralized architecture and/or proxy architecture. Additionally or alternatively, for example, the entities of the system of FIG. 1 can be configured in an architecture given in the Scalable Network Application Package (SNAP) (formerly Sega Network Application Package) provided by Nokia Corporation for applications such as in the context of gaming.

Referring now to FIG. 4, a flowchart illustrating system selection in a multi-mode communication system is presented, in accordance with one exemplary embodiment of the invention. In the embodiment illustrated in FIG. 4, communication may be established with an available system that is on a priority

list and that has the desired service available. The desired service is typically some telecommunication feature, other than standard voice communication, to which the user has subscribed with a communication service provider. Examples of such services include but are not limited to instant messaging (IM), push-to-talk (PTT),  
5 multimedia messaging service (MMS), device management, voice over internet protocol (VoIP), and other voice and data services. Communications may be established automatically with the system that is highest on the priority list and that has the desired service available. In this regard, a system is considered to be highest on the priority list in instances in which the system has the greatest priority,  
10 i.e., has a priority greater than that of any other system on the priority list. A terminal, such as access terminal 10 of FIG. 1, may receive signals from at least two communication systems. See block 70. The communication systems may be operating in accordance with different communication protocols or modes. For example, the terminal may receive a signal from one system operating in  
15 accordance with the GSM protocol (e.g., one mode) and may receive a signal from another system operating in accordance with the CDMA protocol (e.g., another mode).

The terminal may then retrieve the desired service. See block 72. The desired service is typically stored in memory in the terminal, such as in the  
20 subscriber identity module 60 of FIG. 3. The flowchart of FIG. 4 illustrates establishing communication by a terminal capable of communicating via X different modes and having a priority list comprising Y systems for each of the X modes (the value of Y may vary for each of the X modes). As shown in block 74, X is set to 1 and Y is set to 1, so that the availability of the desired service can be  
25 determined (as discussed below) for the first system in the priority list for the first mode. The terminal may have a mode priority list stored in memory, as well as a system priority list for each of the modes which the terminal is capable of using to communicate. As discussed above, the mode priority list may comprise a list of modes that the terminal is capable of using, in the order in which the modes should  
30 be used by the terminal to attempt to establish communication. The mode priority list may be retrieved from memory (see block 76), and the system priority list for the first mode in the mode priority list may be retrieved from memory (see block

78). If the terminal is receiving a signal from the first system in the first mode, such that the terminal is capable of establishing communication with that system, the terminal would typically determine if the desired service is available from that system. See block 80. The terminal may receive information from the system  
5 regarding the availability of the desired service. For example, the system may include information regarding the service(s) supported by the system in a broadcast message transmitted by the system, such as by using a bit map technique to embed service availability information in the broadcast message. Alternatively, the availability of services may be defined by the system priority list that may have  
10 been provisioned over the air to the terminal and stored in memory. Alternatively, the terminal may receive geographic information from the system, typically embedded in a broadcast message, such that the terminal may determine the availability information for the desired service based on the geographic information. The terminal would typically use a stored reference table containing  
15 information as to which services are available in which geographic area. Alternatively, the terminal could access a reference table stored by a network entity, such as a proxy server or the like. In one exemplary embodiment, the geographic information may be defined by the system priority list that is stored in memory such that the terminal may determine the availability information for the  
20 desired service based on the geographic information defined by the priority list.

If the terminal determines in block 82 that the desired service is available from the first system in the priority list of the first mode, then the terminal may establish communication with that system. See block 84. The terminal may automatically establish communication with the first system on the system priority  
25 list that the terminal determines has the desired service available. Alternatively, the terminal may determine all of the systems that are available for communication and that have the desired service available, and may display a list of all such services to the user. The user may then select a system from the list, and the terminal may establish communication with the selected system.

30 If the terminal determines in block 82 that the first system in the priority list of the first mode does not have the desired service available, the terminal determines if there are other systems in the priority list for the first mode that have

not been checked for availability of the desired service. See block 86. If not all systems in the priority list of the first mode have been checked for availability of the desired service, the terminal would typically increment  $Y$  to  $Y + 1$  in block 88, such that the second (i.e., the  $Y + 1$ ) system in the priority list of the first mode may be checked in block 80 for availability of the desired service. Blocks 80 through 88 would typically continue to be executed until a system is determined to have the desired service available or until all systems in the priority list of the first mode have been checked for availability of the desired service. If all systems in the priority list of the first mode have been checked for availability of the desired service, the terminal would typically determine if all modes in the mode priority list have been checked. See block 90. If not all modes in the mode priority list have been checked, as determined in block 90, then the terminal would typically increment  $X$  to  $X + 1$  in block 92. The terminal may then retrieve the priority list for the second (i.e., the  $X + 1$ ) mode. See block 78. The terminal would then typically continue to execute blocks 80 through 88 until a system is determined to have the desired service available or until all systems in the priority list of the second mode have been checked for availability of the desired service. Blocks 78 through 92 would typically continue to be executed by the terminal until a system is determined to have the desired service available or until all systems in the priority lists of all modes have been checked for availability of the desired service.

If all systems in the priority lists of all modes have been checked for availability of the desired service and the desired service is not available, the terminal may reset  $X$  and  $Y$  to 1, and continue to execute blocks 74 through 92 until a system is determined to have the desired service available and the terminal establishes communication with such a system. Alternatively, the terminal may disregard availability of the desired service and establish communication, using the mode priority list and the system priority lists for each mode, with an available system capable of basic voice service. The determination of whether to continue searching for a system having availability of the desired service or to instead establish communication with an available system capable of basic voice service may be predefined in the terminal, or the user may be allowed to select between the two alternatives.

While FIG. 4 illustrates an embodiment of the invention in which the terminal determines the availability of one desired service and uses that availability to determine which system to establish communications with, other embodiments of the invention may enable the terminal to determine the availability of more than one desired service and use that availability information. For example, the user may subscribe to PTT and MMS services and may desire to connect with systems that have both services available. Such an embodiment would typically function similarly to the embodiment illustrated in FIG. 4, however in block 72 the terminal would typically retrieve all of the desired services and in block 80 the terminal would check for availability of all of the desired services. The terminal may establish communications with a system that has availability of all the desired services. Alternatively, if the terminal cannot identify a system that has availability of all the desired services, the terminal may use a prioritized list of desired services and establish communication with the system that has availability of the highest service on the prioritized list. In another alternative, the available services may be displayed to the user and the user may select which available service the user would prefer to use. The terminal would then typically establish communication with the system having the highest priority that has availability of the user selected service.

According to one exemplary aspect of the present invention, the functions performed by one or more of the entities of the system, such as the terminal 10, may be performed by various means, such as hardware and/or firmware, including those described above, alone and/or under control of a computer program product. The computer program product for performing one or more functions of exemplary embodiments of the present invention includes a computer-readable storage medium, such as the non-volatile storage medium, and software including computer-readable program code portions, such as a series of computer instructions, embodied in the computer-readable storage medium.

In this regard, FIG. 4 is a flowchart of a system, method and program product according to exemplary embodiments of the present invention. It will be understood that each block or step of the flowcharts, and combinations of blocks in the flowcharts, can be implemented by various means, such as hardware, firmware,

and/or software including one or more computer program instructions. As will be appreciated, any such computer program instructions may be loaded onto a computer or other programmable apparatus (i.e., hardware) to produce a machine, such that the instructions which execute on the computer or other programmable apparatus create means for implementing the functions specified in the flowcharts block(s) or step(s). These computer program instructions may also be stored in a computer-readable memory that can direct a computer or other programmable apparatus to function in a particular manner, such that the instructions stored in the computer-readable memory produce an article of manufacture including instruction means which implement the function specified in the flowcharts block(s) or step(s). The computer program instructions may also be loaded onto a computer or other programmable apparatus to cause a series of operational steps to be performed on the computer or other programmable apparatus to produce a computer-implemented process such that the instructions which execute on the computer or other programmable apparatus provide steps for implementing the functions specified in the flowcharts block(s) or step(s).

Accordingly, blocks or steps of the flowcharts support combinations of means for performing the specified functions, combinations of steps for performing the specified functions and program instruction means for performing the specified functions. It will also be understood that one or more blocks or steps of the flowcharts, and combinations of blocks or steps in the flowcharts, can be implemented by special purpose hardware-based computer systems which perform the specified functions or steps, or combinations of special purpose hardware and computer instructions.

Many modifications and other embodiments of the invention will come to mind to one skilled in the art to which this invention pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed and that modifications and other embodiments are intended to be included within the scope of the appended claims. For example, while the terminal is described to store various data, information or the like, the data, information or the like could, instead, be stored by a network entity, such as a

proxy server, that is accessible by the terminal. Although specific terms are employed herein, they are used in a generic and descriptive sense only and not for purposes of limitation.

## WHAT IS CLAIMED IS:

1. A terminal for flexible system selection, the terminal comprising:  
a processor capable of receiving signals from at least two communication  
systems and establishing communication with one of the at least two  
5 communication systems based on respective availability information for at least  
one desired service from each of the at least two communication systems.
2. The terminal of claim 1, wherein the at least one desired service is  
selected from the group comprising instant messaging, push-to-talk, multimedia  
10 messaging service, device management, and voice over internet protocol.
3. The terminal of claim 1, wherein the processor receives the  
respective availability information from the at least two communication systems.
- 15 4. The terminal of claim 1, wherein the processor receives respective  
geographic information from the at least two communication systems, and wherein  
the processor is further capable of determining the respective availability  
information for the at least one desired service based on the geographic  
information.  
20
5. The terminal of claim 1, further comprising a storage element  
capable of accessing at least one system priority list, wherein the at least one  
system priority list defines respective geographic information for the at least two  
communication systems, and wherein the processor is further capable of  
25 determining the respective availability information for the at least one desired  
service based on the geographic information defined in the at least one system  
priority list.
6. The terminal of claim 1, further comprising a storage element  
30 capable of accessing the at least one desired service and accessing at least one  
system priority list, wherein the at least one system priority list defines the  
respective availability information for the at least one desired service.

7. The terminal of claim 1, further comprising a storage element capable of accessing the at least one desired service and accessing at least one system priority list, wherein the processor is further capable of establishing  
5 communication with the at least one communication system that has a highest priority on the system priority list and has the desired service available.

8. The terminal of claim 1, further comprising a storage element capable of accessing the at least one desired service and accessing at least one  
10 system priority list, wherein the processor is further capable of receiving a user communication system selection from among all communication systems that are on the system priority list and that have the desired service available, and wherein the processor is further capable of establishing communication with the communication system selected by the user.

15 9. A network entity for flexible system selection, the network entity comprising:  
a processor capable of directing transmission of a signal independent of a transmission from a terminal, wherein the signal is capable of being received by a  
20 terminal, wherein the signal comprises availability information for at least one desired service, wherein the processor is capable of receiving a communication request from the terminal based on the availability information.

10. The network entity of claim 9, wherein the at least one desired  
25 service is selected from the group comprising instant messaging, push-to-talk, multimedia messaging service, device management, and voice over internet protocol.

11. The network entity of claim 9, wherein the processor is further  
30 capable of receiving the communication request from the terminal based on a system priority list accessible by the terminal and the availability information.

12. A system for flexible system selection, the system comprising:  
at least two network entities capable of transmitting signals; and  
a terminal capable of receiving the signals from the at least two network  
entities and establishing communication with one of the at least two network  
5 entities based on respective availability information for at least one desired service.

13. The system of claim 12, wherein the at least one desired service is  
selected from the group comprising instant messaging, push-to-talk, multimedia  
messaging service, device management, and voice over internet protocol.  
10

14. The system of claim 12, wherein the terminal receives the  
respective availability information from the at least two network entities.

15. The system of claim 12, wherein the terminal receives respective  
15 geographic information from the at least two network entities, and wherein the  
terminal is further capable of determining the respective availability information  
for the at least one desired service based on the geographic information.

16. The system of claim 12, wherein the terminal is further capable of  
20 accessing at least one system priority list, wherein the at least one system priority  
list defines respective geographic information for the at least two communication  
systems, and wherein the terminal is further capable of determining the respective  
availability information for the at least one desired service based on the geographic  
information defined in the at least one system priority list.  
25

17. The system of claim 12, wherein the terminal is further capable of  
accessing the at least one desired service and accessing at least one system priority  
list, wherein the at least one system priority list defines the respective availability  
information for the at least one desired service.  
30

18. The system of claim 12, wherein the terminal is further capable of  
accessing the at least one desired service and accessing at least one system priority

list, wherein the terminal is further capable of establishing communication with the at least one network entity that has a highest priority on the system priority list and has the desired service available.

5           19.     The system of claim 12, wherein the terminal is further capable of accessing the at least one desired service and accessing at least one system priority list, wherein the terminal is further capable of receiving a user network entity selection from among all network entities that are on the system priority list and that have the desired service available, and wherein the terminal is further capable  
10 of establishing communication with the network entity selected by the user.

          20.     A method for flexible system selection, the method comprising:  
          receiving signals from at least two communication systems; and  
          establishing communication with one of the at least two communication  
15 systems based on respective availability information for at least one desired service from each of the at least two communication systems.

          21.     The method of claim 20, wherein the at least one desired service is selected from the group comprising instant messaging, push-to-talk, multimedia  
20 messaging service, device management, and voice over internet protocol.

          22.     The method of claim 20, further comprising:  
          receiving the respective availability information from the at least two  
communication systems.

25           23.     The method of claim 20, further comprising:  
          receiving respective geographic information from the at least two  
communication systems; and  
          determining the respective availability information for the at least one  
30 desired service based on the geographic information.

24. The method of claim 20, further comprising:  
accessing at least one system priority list, wherein the at least one system  
priority list defines respective geographic information for the at least two  
communication systems; and
- 5 determining the respective availability information for the at least one  
desired service based on the geographic information defined in the at least one  
system priority list.
25. The method of claim 20, further comprising:  
10 accessing the at least one desired service; and  
accessing at least one system priority list, wherein the at least one system  
priority list defines the respective availability information for the at least one  
desired service.
- 15 26. The method of claim 20, further comprising:  
accessing the at least one desired service;  
accessing at least one system priority list; and  
establishing communication with the at least one communication system  
that has a highest priority on the system priority list and has the desired service  
20 available.
27. The method of claim 20, further comprising:  
accessing the at least one desired service;  
accessing at least one system priority list;  
25 receiving a user communication system selection from among all  
communication systems that are on the system priority list and that have the  
desired service available; and  
establishing communication with the communication system selected by  
the user.
- 30 28. A computer program product for flexible system selection, the  
computer program product comprising at least one computer-readable storage

medium having computer-readable program code portions stored therein, the computer-readable program code portions comprising:

a first executable portion capable of receiving signals from at least two communication systems; and

5 a second executable portion capable of establishing communication with one of the at least two communication systems based on respective availability information for at least one desired service from each of the at least two communication systems.

10 29. The computer program product of claim 28, wherein the at least one desired service is selected from the group comprising instant messaging, push-to-talk, multimedia messaging service, device management, and voice over internet protocol.

15 30. The computer program product of claim 28, further comprising:  
a third executable portion capable of receiving the respective availability information from the at least two communication systems.

20 31. The computer program product of claim 28, further comprising:  
a third executable portion capable of receiving respective geographic information from the at least two communication systems; and  
a fourth executable portion capable of determining the respective availability information for the at least one desired service based on the geographic information.

25 32. The computer program product of claim 28, further comprising:  
a third executable portion capable of accessing at least one system priority list, wherein the at least one system priority list defines respective geographic information for the at least two communication systems; and  
30 a fourth executable portion capable of determining the respective availability information for the at least one desired service based on the geographic information defined in the at least one system priority list.

33. The computer program product of claim 28, further comprising:  
a third executable portion capable of accessing the at least one desired  
service; and  
5 a fourth executable portion capable of accessing at least one system priority  
list, wherein the at least one system priority list defines the respective availability  
information for the at least one desired service.

34. The computer program product of claim 28, further comprising:  
10 a third executable portion capable of accessing the at least one desired  
service;  
a fourth executable portion capable of accessing at least one system priority  
list; and  
a fifth executable portion capable of establishing communication with the  
15 at least one communication system that has a highest priority on the system priority  
list and has the desired service available.

35. The computer program product of claim 28, further comprising:  
a third executable portion capable of accessing the at least one desired  
20 service;  
a fourth executable portion capable of accessing at least one system priority  
list;  
a fifth executable portion capable of receiving a user communication  
system selection from among all communication systems that are on the system  
25 priority list and that have the desired service available; and  
a sixth executable portion capable of establishing communication with the  
communication system selected by the user.







FIG. 1.

2/3

FIG. 2.FIG. 3.

3/3

**FIG. 4.**

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB2006/001606

## A. CLASSIFICATION OF SUBJECT MATTER

IPC: see extra sheet

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC: H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages                                                  | Relevant to claim No.                                    |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| X         | US 20040192313 A1 (MARCIA JEAN OTTING),<br>30 Sept 2004 (30.09.2004), [0008],[0009],[0012],<br>fig.2&3                              | 1,3,6-9,<br>11-12,14,<br>17-20,22,<br>25-28,30,<br>33-35 |
| Y         | [0021]-[0033],[0038],abstract                                                                                                       | 2,4-5,10,13,<br>15-16,21,<br>23-24,29,<br>31-32          |
|           | --                                                                                                                                  |                                                          |
| X         | US 20020177466 A1 (PASI LAURILA ET AL.),<br>28 November 2002 (28.11.2002), [0008]-[0020],<br>[0038],[0054],claims 2;5-6,figs 1B & 5 | 1-3;6-14;17-<br>22;25-30;33-<br>35                       |
| Y         |                                                                                                                                     | 4-5;15-16;23<br>-24;31-32                                |
|           | --                                                                                                                                  |                                                          |

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 November 2006

Date of mailing of the international search report

08-11-2006

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Elisabet Åselius /itw  
Telephone No. +46 8 782 25 00

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB2006/001606

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages                                                                                                       | Relevant to claim No.                 |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|
| X         | WO 2004056136 A2 (MOTOROLA INC., A CORPORATION),<br>1 July 2004 (01.07.2004), page 1, line 5 - line 28;<br>page 3, line 16 - page 4, line 24; page 9,<br>line 3 - line 12, figures 1,3&4 | 1,3-9,11-12,<br>14-20,22-28,<br>30-35 |
| Y         | --                                                                                                                                                                                       | 2,10,13,21,<br>29                     |
| P,X       | US 20050266844 A1 (MURALI NARASIMHA),<br>1 December 2005 (01.12.2005), [0002][0005],claims<br>1-28                                                                                       | 1-35                                  |
| P,X       | US 20050243870 A1 (DAN ANTHONY BALOGH ET AL.),<br>3 November 2005 (03.11.2005), [0006]-[0015]                                                                                            | 1-35                                  |
| P,X       | EP 1622315 A1 (BROADCOM CORPORATION),<br>1 February 2006 (01.02.2006), [0006]-[0010],claims<br>1-10,figs 1-7D,abstract                                                                   | 1-35                                  |
| E         | WO 2006109124 A2 (NOKIA CORPORATION),<br>19 October 2006 (19.10.2006), page 1,<br>line 13 - page 5, line 23, claims 1-31                                                                 | 1-35                                  |
|           | --<br>-----                                                                                                                                                                              |                                       |

INTERNATIONAL SEARCH REPORT

International application No.  
PCT/IB2006/001606

**International patent classification (IPC)**

**H04Q 7/38** (2006.01)

**H04Q 7/32** (2006.01)

**Download your patent documents at [www.prv.se](http://www.prv.se)**

The cited patent documents can be downloaded at [www.prv.se](http://www.prv.se) by following the links:

- In English/Searches and advisory services/Cited documents (service in English) or
- e-tjänster/anförda dokument(service in Swedish).

Use the application number as username.

The password is **QRTFUEQAZW**.

Paper copies can be ordered at a cost of 50 SEK per copy from PRV InterPat (telephone number 08-782 28 85).

Cited literature, if any, will be enclosed in paper form.

## INTERNATIONAL SEARCH REPORT

Information on patent family members

04/10/2006

International application No.

PCT/IB2006/001606

|    |             |    |            |      |             |   |            |
|----|-------------|----|------------|------|-------------|---|------------|
| US | 20040192313 | A1 | 30/09/2004 | WO   | 2004095853  | A | 04/11/2004 |
| US | 20020177466 | A1 | 28/11/2002 | FI   | 20010979    | A | 10/11/2002 |
| WO | 2004056136  | A2 | 01/07/2004 | AU   | 2003294423  | A | 09/07/2004 |
|    |             |    |            | BR   | 0317169     | A | 25/10/2005 |
|    |             |    |            | CN   | 1723721     | A | 18/01/2006 |
|    |             |    |            | MX   | PA05006235  | A | 08/09/2005 |
|    |             |    |            | US   | 6954649     | B | 11/10/2005 |
|    |             |    |            | US   | 20040203893 | A | 14/10/2004 |
| US | 20050266844 | A1 | 01/12/2005 | WO   | 2005117465  | A | 08/12/2005 |
| US | 20050243870 | A1 | 03/11/2005 | NONE |             |   |            |
| EP | 1622315     | A1 | 01/02/2006 | US   | 20060025151 | A | 02/02/2006 |
|    |             |    |            | CN   | 1741485     | A | 01/03/2006 |
|    |             |    |            | CN   | 1819536     | A | 16/08/2006 |
|    |             |    |            | EP   | 1622314     | A | 01/02/2006 |
|    |             |    |            | US   | 20060023675 | A | 02/02/2006 |
|    |             |    |            | US   | 20060025111 | A | 02/02/2006 |
|    |             |    |            | US   | 20060025135 | A | 02/02/2006 |
|    |             |    |            | US   | 20060025148 | A | 02/02/2006 |
|    |             |    |            | US   | 20060025149 | A | 02/02/2006 |
|    |             |    |            | US   | 20060034335 | A | 16/02/2006 |
| WO | 2006109124  | A2 | 19/10/2006 | NONE |             |   |            |