



- (51) International Patent Classification:
G02B 15/177 (2006.01) *G02B 13/00* (2006.01)
- (21) International Application Number:
PCT/CN2016/086000
- (22) International Filing Date:
16 June 2016 (16.06.2016)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
- | | | |
|----------------|--------------------------------|----|
| 201510340158.8 | 17 June 2015 (17.06.2015) | CN |
| 201520421140.6 | 17 June 2015 (17.06.2015) | CN |
| 201510367784.6 | 26 June 2015 (26.06.2015) | CN |
| 201520453994.2 | 26 June 2015 (26.06.2015) | CN |
| 201510622908.0 | | |
| | 25 September 2015 (25.09.2015) | CN |
| 201520757238.9 | | |
| | 25 September 2015 (25.09.2015) | CN |

- (71) Applicant: **ZHEJIANG DAHUA TECHNOLOGY CO., LTD** [CN/CN]; No.1187 Binan Road, Hangzhou, Zhejiang (CN).
- (72) Inventors: **LIU, Kai**; No.1187 Binan Road, Hangzhou, Zhejiang (CN). **WANG, Feng**; No.1187 Binan Road, Hangzhou, Zhejiang (CN). **DING, Hongxing**; No.1187 Binan Road, Hangzhou, Zhejiang (CN). **ZHANG, Xing-**

ming; No.1187 Binan Road, Hangzhou, Zhejiang (CN). **ZHANG, Qian**; No.1187 Binan Road, Hangzhou, Zhejiang (CN).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A ZOOM LENS SYSTEM




FIG. 1

(57) Abstract: A zoom lens system for providing high quality images with higher resolution includes a first lens group (110), an aperture stop (120), and a second lens group (130). The first lens group has a positive or negative refractive power, and includes at least two lens elements having a negative refractive power and at least one lens element having a positive refractive power. The second lens group has a positive refractive power. A distance between a first and second lens group is not fixed.



A ZOOM LENS SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is based upon and claims priority from Chinese Patent Application No. 201510340158.8, filed on June 17, 2015, Chinese Patent Application No. 201520421140.6, filed on June 17, 2015, Chinese Patent Application No. 201510367784.6, filed on June 26, 2015, Chinese Patent Application No. 201520453994.2, filed on June 26, 2015, Chinese Patent Application No. 201510622908.0, filed on September 25, 2015, and Chinese Patent Application No. 201520757238.9, filed on September 25, 2015. Each of the above-referenced applications are expressly incorporated herein by reference to their entireties.

TECHNICAL FIELD

[0002] The present disclosure generally relates to optical imaging devices, more specifically relates to zoom lens systems having at least one optical lens.

BACKGROUND

[0003] Imaging devices, like digital cameras and surveillance TV cameras, conventionally use zoom lens systems to capture images of an object through one or more groups of lens. With increasing usage of Charge Coupled Device (CCD) and Complementary Metal Oxide Semiconductor (CMOS) in imaging devices, zoom lens systems with high resolution and wide field view are needed.

[0004] However, conventional zoom lens systems do not adequately achieve high resolution and wide field view. For zoom lens systems with two lens groups, the resolution in some focal lengths may be sacrificed. For zoom lens system with more

than two lens groups, the manufacturing cost is relatively high due to a mechanism for driving the lens groups.

SUMMARY

[0005] In one aspect of the present disclosure is directed to a zoom lens system and/or a lens including the zoom lens system. The zoom lens system may include a first lens group, an aperture stop, and a second lens group having a positive refractive power. The first lens group may include at least two lens elements having a negative refractive power and at least one lens element having a positive refractive power. The second lens group may include a first lens element having a positive refractive power, a second lens element having a positive refractive power, a first lens component having a negative refractive power, a third lens element having a negative refractive power, a fourth lens element having a positive refractive power, a second lens component having a negative refractive power, a fifth lens element having a positive refractive power, and a sixth lens element having a negative refractive power. In some embodiments, the first lens component may include at least one lens element. In some embodiments, the second lens component may include at least one lens element. In some embodiments, the fifth lens element and the sixth lens element may be affixed to each other. In some embodiments, a distance between the first lens group and the second lens group may vary.

[0006] In some embodiments, the first lens element of the second lens group may be a biconvex lens, and a refractive index of the first lens element may be no less than 1.7.

[0007] In some embodiments, the second lens element of the second lens group may be a biconvex lens, an Abbe number of the second lens element of the second lens

group may be greater than 80, and the second lens element and the first lens component of the second lens group may be affixed to each other.

[0008] In some embodiments, the first lens component of the second lens group may include a biconcave lens having a negative refractive power and a biconvex lens having a positive refractive power, and the biconcave lens and the biconvex lens may be affixed to each other.

[0009] In some embodiments, the third lens element of the second lens group may be a biconcave lens, an Abbe number of the third lens element of the second lens group may be greater than 65, and a refractive index of the third lens element of the second lens group may be less than 1.55.

[0010] In some embodiments, the fourth lens element of the second lens group may be a biconvex lens, and the third lens element and the fourth lens element of the second lens group may be affixed to each other.

[0011] In some embodiments, the second lens component of the second lens group may include a first meniscus lens having a positive refractive power, a second meniscus lens having a negative refractive power, and the first meniscus lens and the second meniscus lens may be affixed to each other.

[0012] In some embodiments, the fifth lens element of the second lens group may be a biconvex lens, and an Abbe number of the fifth lens element may be greater than 80.

[0013] In some embodiments, the sixth lens element of the second lens group may be a biconcave lens, an Abbe number of the sixth lens element of the second lens group may be less than that of the fifth lens element of the second lens group, and a

refractive index of the sixth lens element of the second lens group may be greater than that of the fifth lens element of the second lens group.

[0014] In some embodiments, the first lens group may include a first meniscus lens having a negative refractive power, a biconcave lens having a negative refractive power, a second meniscus lens having a positive refractive power, and the convex surfaces of the first and second meniscus lenses may face against an image plane.

[0015] In some embodiments, the zoom lens system may satisfy $1.85 \leq$

$|f_1|/(f_w \times f_t)^{\frac{1}{2}} \leq 2.25$, f_1 may be a focus length of first lens group, f_w may be a shortest focus length of the zoom lens system, f_t may be a longest focus length of the zoom lens system.

[0016] In some embodiments, the zoom lens system may satisfy $0.8 < f_2/f_w < 1.2$, f_2 may be a focus length of second lens group, wherein f_w may be a shortest focus length of zoom lens system.

[0017] In some embodiments, the zoom lens system may satisfy $0.4 < N_n \times f_w/f_t < 0.55$, wherein N_n may be an average refractive index of the meniscus lens having a negative refractive power and the biconcave lens having a negative refractive power, f_w may be a shortest focus length of zoom lens system, and f_t may be a longest focus length of zoom lens system.

[0018] In another aspect of the present disclosure is directed to a zoom lens system and/or a lens including the zoom lens system. The zoom lens system may include a first lens group, an aperture stop and a second lens group having a positive refractive power. The first lens group may include at least two lens elements of negative refractive power and at least one lens element of a positive refractive power. The second lens

group may include a first lens element having a negative refractive power, a second lens element having a positive refractive power, a third lens element having a positive refractive power, a fourth lens element having a positive refractive power, a fifth lens element having a positive refractive power, and a sixth lens element having a negative refractive power. In some embodiments, the distance between the first lens group and the second lens group may be not fixed.

[0019] In some embodiments, the zoom lens system may satisfy $0.7 < |F_{eff}/F_1| < 1.7$, and $0.3 < |F_{eff}/F_c| < 1.2$, wherein F_{eff} may be an effective focal length of the zoom lens system, F_1 may be an effective focal length of the first lens group, and F_c may be an effective focal length of the second lens group.

[0020] In some embodiments, the first lens group may include a plano-concave lens and two meniscus lenses. The concave surface of the plano-convex lens may face an image plane, the convex surfaces of the two meniscus lenses may face against an image plane, and the two meniscus lenses may be affixed to each other.

[0021] In some embodiments, the first lens element of the second group may be a biconcave lens, the second lens element of the second group may be a biconvex lens, the third lens element of the second group may be a meniscus lens, the fourth lens element of the second group may be a biconvex lens, the fifth lens element of the second group may be a biconvex lens, and the sixth lens element of the second group may be a biconcave lens.

[0022] In some embodiments, the first lens element of the second group and the second lens element of the second group may be affixed to each other, and the fifth

lens element of the second group and the sixth lens element of the second group may be affixed to each other.

[0023] In some embodiments, the first concave surface of one of the two meniscus lens and the second concave surface of the other one of the two meniscus lens may be integrated into a lens component by adhesive, and the lens component may have a positive refractive power

[0024] In some embodiments, the concave surface of the first lens element of the second group and the convex surface of the second lens element of the second group may be integrated into a lens component by adhesive, and the lens component may have a negative refractive power.

[0025] In some embodiments, the convex surface of the fifth lens element of the second group and the concave surface of the sixth lens element may be integrated into a lens component by adhesive, and the lens component may have a positive refractive power.

[0026] In another aspect of the present disclosure is directed to a zoom lens system and/or a lens including the zoom lens system. The zoom lens system may include a first lens group, an aperture stop and a second lens group having a positive refractive power. The first lens group may include at least two lens elements having a negative refractive power, at least two lens elements having a positive refractive power at least one lens component having a positive refractive power, and the at least one lens component may include at least one lens element. The second lens group may include a first lens element having a positive refractive power, a first lens component having a negative refractive power, a second lens element having a positive refractive power,

and a third lens element having a positive refractive power. In some embodiments, the first lens component may include at least one lens element, and the distance between the first lens group and the second lens group may be not fixed

[0027] In some embodiments, the first lens group may include a first meniscus lens having a positive refractive power, a second meniscus lens having a negative refractive power, a biconcave lens having a negative refractive power, a second lens component having a positive refractive power, and a biconvex lens having a positive refractive power, and the convex surfaces of the first and second meniscus lenses may face against an image plane.

[0028] In some embodiments, the second lens component of the first lens group may include a third meniscus lens having a positive refractive power and a fourth meniscus lens having a negative refractive power, and the third meniscus lens and the fourth meniscus lens may be affixed to each other.

[0029] In some embodiments, the first lens component of the second lens group may include a biconcave lens having a negative refractive power and a biconvex lens having a positive refractive power, and the biconcave lens and the biconvex lens may be affixed to each other.

BRIEF DESCRIPTION OF THE DRAWINGS

[0030] The present disclosure is further described in terms of exemplary embodiments. These exemplary embodiments are described in detail with reference to the drawings. These embodiments are non-limiting exemplary embodiments, in which like reference numerals represent similar structures throughout the several views of the drawings, and wherein:

[0031] FIG. 1 is a block diagram illustrating an exemplary zoom lens system according to some embodiments of the present disclosure;

[0032] FIG. 2A is a schematic diagram illustrating an exemplary zoom lens system at long-focus and short-focus according to some embodiments of the present disclosure;

[0033] FIGs. 2B through 2G are schematic diagrams illustrating exemplary zoom lens systems according to some embodiments of the present disclosure;

[0034] FIG. 3 illustrates an exemplary optical imaging device including an exemplary zoom lens system configuration according to some embodiments of the present disclosure;

[0035] FIGs. 4A through 4V illustrate optical simulation of the zoom lens system illustrated in FIG. 2A according to some embodiments of the present disclosure;

[0036] FIG. 5A is a schematic diagram illustrating an exemplary zoom lens system according to some embodiments of the present disclosure;

[0037] FIG. 5B is a schematic diagram illustrating lens surfaces of the zoom lens system illustrated in FIG. 5A according to some embodiments of the present disclosure;

[0038] FIGs. 6A through 6F illustrate optical simulation of the zoom lens system illustrated in FIG. 5A according to some embodiments of the present disclosure;

[0039] FIG. 7 is a schematic diagram illustrating an exemplary zoom lens system according to some embodiments of the present disclosure;

[0040] FIG. 8 illustrate an exemplary zoom lens system configuration of an optical imaging device according to some embodiments of the present disclosure.

DETAILED DESCRIPTION

[0041] In the following detailed description, numerous specific details are set forth by way of examples in order to provide a thorough understanding of the relevant disclosure. However, it should be apparent to those skilled in the art that the present disclosure may be practiced without such details. In other instances, well known methods, procedures, module, systems, devices, and/or drivers have been described at a relatively high-level, without detail, in order to avoid unnecessarily obscuring aspects of the present disclosure.

[0042] The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms "a," "an," and "the" may be intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms "comprise," "comprises," and/or "comprising," "include," "includes," and/or "including," when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

[0043] These and other features, and characteristics of the present disclosure, as well as the methods of operation and functions of the related elements of structure and the combination of parts and economies of manufacture, may become more apparent upon consideration of the following description with reference to the accompanying drawing(s), all of which form a part of this specification. It is to be expressly understood, however, that the drawing(s) are for the purpose of illustration and description only and

are not intended to limit the scope of the present disclosure. It is understood that the drawings are not to scale.

[0044] The terms "lens element", "lens component", and "lens group relating to the detailed description of this application may be described as follows. The term "lens element" herein may be a single transparent material that has two surfaces; both surfaces are curved, or one surface curved and the other is flat. The lens element may be used singly or combined with other lens element(s) in an optical instrument for focusing an object. The term "lens component" herein may be: either a single lens element spaced so far from other adjacent lens element(s) that the spacing cannot be neglected for purposes of computing the optical image forming properties of the lens elements; or two or more lens elements that have their adjacent lens surfaces that are overlapped or so close to each other that the spacing between adjacent lens surfaces of the lens elements can be neglected for purposes of computing the optical image forming properties of the lens elements. In some embodiments, some lens elements may also be lens components. The term "lens group" herein may be defined as a group of two or more lens elements or lens components in optical series along an optical axis.

[0045] The disclosure is directed to a zoom lens system for providing high quality images and/or videos with a higher resolution. For example, FIG. 1 illustrates an exemplary zoom lens system 100 including, in order from an object, a first lens group 110, an aperture stop 120, and a second lens group 130. Zoom lens system 100 may be implemented in an optical imaging device and configured to perform functions disclosed in this application.

[0046] First lens group 110 may include one or more lens elements and/or one or more lens components. The lens element(s) and/or lens components may have a negative or a positive refractive power. In some embodiments, first lens group 110 may include three lens elements. In some embodiments, first lens group 110 may include four lens elements and one lens component. The refractive power of first lens group 110 may be negative or positive.

[0047] Aperture stop 120 may be disposed between first lens group 110 and second lens group 130. Aperture stop 120 may be a hole or an opening through which light travels. More specifically, aperture stop 120 and focal length of zoom lens system may determine the cone angle of a bundle of rays that come to a focus in image plane 350. Aperture stop 120 may determine how collimated the admitted rays are. Aperture stop 120 may also determine how many of the incoming rays are actually admitted and thus how much light reaches image plane 350. The narrower the aperture, the darker the image for a given exposure time. In some embodiments, aperture stop 120 may be narrow, then highly collimated rays are admitted, resulting in a sharp focus at image plane 350. In some embodiments, aperture stop 120 may be wide, then highly uncollimated rays are admitted, resulting in a sharp focus only for rays coming from a certain distance. In some embodiments, the size of the aperture stop 120 may remain unchanged.

[0048] Second lens group 130 may include one or more lens elements and/or lens components. In some embodiments, the lens element(s) and/or lens component(s) may have one or more aspheric lens surfaces. The refractive power of second lens group 130 may be negative or positive. In some embodiments, second lens group 130 may

include at least one lens element. For example, second lens group 130 may include ten lens elements. In some embodiments, second lens group 130 may include at least one lens element and at least one component. For example, second lens group 130 may include six lens elements and two lens components. As another example, second lens group 130 may include three lens elements and one lens component. In some embodiments, the two lens elements closest to an object side may have a positive refractive power. This would help to converge the light rays efficiently. In some embodiments, at least two elements of second lens group 130 may be affixed to each other. In some embodiments, the at least two elements may be disposed closest to image plane 350. In some embodiments, the at least two elements may reduce chromatic aberration of zoom lens system 100 and make zoom lens system 100 more stable. Such configurations of zoom lens system may provide a better imaging quality.

[0049] Refractive power of lens group(s) 110 and/or 130 may be determined based on the lens elements and/or the lens components. For example, the number, arrangement, combination, refractive power of the lens elements and/or the lens components in the lens groups may determine the refractive power of lens group(s) 110 and/or 130. The refractive power of the lens component may be determined based on the lens elements. For example, the number, arrangement, combination, refractive power of lens elements in the lens components may determine the refractive power of lens components.

[0050] The lens element may be a convex lens, a concave lens, or a flat lens. The convex lens may include a biconvex lens (convex on both sides), plano-convex (flat on one side and convex on the other side) lens, concavo-convex lens (meniscus lens,

concave on one side and convex on the other side), etc. The concave lens may include biconcave lens (concave on both sides), plano-concave lens (flat on one side and concave on the other side), convexo-concave lens (meniscus lens, convex on one side and concave on the other side), etc. The lens component may include two or more lens elements. The convex lens may have a positive refractive power and may be used to converge the light rays. The concave lens may have a negative refractive power and may be used to diverge the light rays. The material of the lens elements (e.g., the convex lens, the concave lens and the flat lens) may be plastic, glass, crystal, resin, silica gel, etc. Materials used to manufacture lens may include K9(H-K9L, N-BK7), fused silica, fluoride (e.g., calcium fluoride, barium fluoride, magnesium fluoride, etc.), zinc selenide, silicon, germanium, etc.

[0051] The lens component may include different number and different kinds of lens elements. For example, a meniscus lens and a biconcave lens may be affixed to each other to form a lens component. As another example, a biconvex lens and a biconcave lens may be affixed to each other to form a lens component. The refractive power of a lens component may be negative or positive. It should be noted that the different combinations of lens elements are still within the scope of the current disclosure described above. Zoom lens system 100 may be used in fields of science and technology, military, etc. For example, zoom lens system 100 may be used in fields of safety monitoring system, film or television camera, digital cameras and surveillance TV cameras, projector, telescope, microscope, space exploration, missile test, tracking record of rocket, image detecting elements such as CCD (Charge Coupled Device) and CMOS (Complementary Metal Oxide Semiconductor), etc.

[0052] In some embodiments, two lens groups and one or more lens elements or lens components may be used in zoom lens system 100, which may reduce the cost of the lenses and the mechanisms in zoom lens system 100 and reduce the difficulty in fabricating lenses and assembling lenses. Other objectives, features and advantages of the invention will be further understood from the further technological features disclosed by the embodiments of the invention wherein there are shown and described preferred embodiments of this invention, simply by way of illustration of modes best suited to carry out the invention.

[0053] It should be noted that the above description about zoom lens system 100 is merely an example and should not be understood as the only embodiment. To those skilled in the art, after understanding the basic principles of the connection between different devices, the devices and connection between the devices may be modified or varied without departing from the principles. The modifications and variations are still within the scope of the current disclosure described above. For example, second lens group 130 may include seven lens elements and one lens component. A lens component may include two meniscus lenses.

[0054] FIG. 2A is a schematic diagram illustrating an exemplary zoom lens system at long-focus and short-focus according to some embodiments of the present disclosure. FIGs. 2B through 2G are schematic diagrams illustrating exemplary zoom lens systems according to some embodiments of the present disclosure. As illustrated in FIG. 1, zoom lens system 100 may include a first lens group 110, an aperture stop 120, a second lens group, and other components (not shown). Further referring to FIG. 2A, first lens group 110 may include lens elements 211, 212, and 213. In some embodiments,

first lens group 110 may have a negative refractive power. In some embodiments, lens element 211 may be a meniscus lens having a negative refractive power. Lens element 212 may be a concave lens having a negative refractive power. Preferably, lens element 212 may be a biconcave lens. Lens element 213 may be a meniscus lens having a positive refractive power. Preferably, the convex surfaces of lens elements 211 and 213 may face towards an object (i.e., the opposite direction to image plane 350 illustrated in FIG. 2A).

[0055] First lens group 110 with the above-described arrangement of lens elements, may reduce spherical aberration. First lens group 110 with three lens elements may reduce axis aberration and produce a better imaging quality.

[0056] In some embodiments, second lens group 130 may include six lens elements 231, 232, 235, 236, 239 and 240, and two lens components. The first lens component may include lens elements 233 and 234. The second lens component may include lens elements 237 and 238. In some embodiments, lens elements 231 and 232 may be convex lenses having a positive refractive power. For example, lens elements 231 and 232 may be biconvex lenses. In some embodiments, lens element 233 may be a concave lens having a negative refractive power. For example, lens element 233 may be a biconcave lens. In some embodiments, lens element 234 may be a convex lens having a positive refractive power. For example, lens element 234 may be a biconvex lens. In some embodiments, lens element 235 may be a concave lens having a negative refractive power. For example, lens element 235 may be a biconcave lens. In some embodiments, lens element 236 may be a convex lens having a positive refractive power. For example, lens element 236 may be a biconvex lens. In some embodiments,

lens element 237 may be a convex lens having a positive refractive power. In some embodiments, lens element 238 may be a concave lens having a negative refractive power. For example, lens elements 237 and 238 may be meniscus lenses. In some embodiments, lens element 239 may be a convex lens having a positive refractive power. For example, lens element 239 may be a biconvex lens. In some embodiments, lens element 240 may be a concave lens having a negative refractive power. For example, lens element 240 may be a biconcave lens. In some embodiments, lens elements 239 and 240 may be rigidly affixed together to reduce chromatic aberration of the zoom lens system, make the zoom lens system more stable, and provide a better imaging quality.

[0057] In some embodiments, lens element 240 may be a plano-concave lens. As illustrated in FIG. 2B, lens element 241 in second lens group 130 may be a plano-concave lens having a negative refractive power.

[0058] In some embodiments, lens element 240 may be a meniscus lens. As illustrated in FIG. 2C, lens element 242 in second lens group 130 may be a meniscus lens having a negative refractive power.

[0059] In some embodiments, first lens component may include a biconcave lens. As illustrated in FIG. 2D, first lens component 243 in second lens group 130 may be a biconcave lens having a negative refractive power.

[0060] In some embodiments, first lens component may include a meniscus lens. As illustrated in FIG. 2E, first lens component 244 in second lens group 130 may be a meniscus lens having a negative refractive power.

[0061] In some embodiments, second lens component may include a meniscus lens. As illustrated in FIG. 2F, second lens component 245 in second lens group 130 may be a meniscus lens having a negative refractive power.

[0062] In some embodiments, second lens component may include a biconcave lens. As illustrated in FIG. 2G, second lens component 246 in second lens group 130 may be a biconcave lens having a negative refractive power.

[0063] Lens element 231 may converge light rays from aperture stop 120 and reduce coma and astigmatism of zoom lens system 100. The higher refractive index of lens element 231 may have a better convergence effect. For example, the refractive index of lens element 231 may be no less than 1.7.

[0064] In some embodiments, lens element 232 and the first component may be affixed to each other by adhesive (or any suitable materials or method). In some embodiments, lens element 232 and lens element 233 may be rigidly affixed together, and the Abbe number of lens element 232 may be greater than 80.

[0065] In some embodiments, lens element 233 and lens element 234 may be affixed to each other by adhesive (or any suitable materials or method). In some embodiments, lens element 235 and lens element 236 may be rigidly affixed together and integrated into one lens component. Preferably, Abbe number of lens element 235 may be greater than 65, and refractive index of lens element 235 may be less than 1.55.

[0066] Lens element 237 and lens element 238 in the second component may be two meniscus lenses. The meniscus lens (e.g., one side is convex and the other side is concave) can reduce spherical aberration. In some embodiments, lens element 237 and lens element 238 may be affixed to each other by adhesive (or any suitable materials or

method). Preferably, the convex surfaces of lens elements 237 and 238 may face towards the object.

[0067] In some embodiments, lens element 239 and lens element 240 may be affixed to each other by adhesive (or any suitable materials or method). For example, Abbe number of lens element 239 may be greater than that of lens element 240, and refractive index of lens element 239 may be less than that of lens element 240. As another example, Abbe number of lens element 239 may be greater than 80.

[0068] In some embodiments, positions of first lens group 110 and second lens group 130 may change in zoom lens system 100. Zooming may be carried out by varying a distance between first lens group 110 and second lens group 130. The distance between first lens 110 group and second lens group 130 may be not fixed.

[0069] Preferably, the following equation (1) is satisfied:

$$1.85 \leq |f_1|/(f_w \times f_t)^{\frac{1}{2}} \leq 2.25, \quad (1)$$

where f_1 represents a focus length of first lens group 110, and f_w represents a shortest focus length of zoom lens system 100, and f_t represents a longest focus length of zoom lens system 100. f_1 within a reasonable range may reduce aberration and produce a better imaging quality.

[0070] Preferably, the following equation (2) is satisfied:

$$0.8 < f_2/f_w < 1.2, \quad (2)$$

where f_2 represents a focus length of second lens group 130. f_2 within a reasonable range may reduce aberration and produce a better imaging quality.

[0071] Preferably, the following equation (3) is satisfied:

$$0.4 < N_n \times f_w/f_t < 0.55, \quad (3)$$

where N_n represents average refractive index of lens elements 211 and 213. N_n within a certain range may limit divergence of light rays and produce a better imaging quality.

[0072] Merely by way of example, zoom lens system 100 may be configured according to parameters of each lens listed in Table 1. R_1 represents radius of curvature of the surface towards the object. R_2 represents radius of curvature of the surface towards image plane 350. T_c represents thickness of an optical center of the lens. N_d represents refraction index of the lens. V_d represents Abbe number of the lens.

TABLE 1

Lens element	$R_1(\text{mm})$	$R_2(\text{mm})$	$T_c(\text{mm})$	N_d	V_d
211	$30 \leq R_1 \leq 100$	$12 \leq R_2 \leq 18$	$0.8 \leq T_c \leq 2$	$1.75 \leq N_d \leq 1.89$	$40 \leq V_d \leq 50$
212	$-45 \leq R_1 \leq -34$	$18 \leq R_2 \leq 30$	$0.8 \leq T_c \leq 2$	$1.6 \leq N_d \leq 1.76$	$50 \leq V_d \leq 62$
213	$25 \leq R_1 \leq 35$	$200 \leq R_2$	$3 \leq T_c \leq 5$	$1.7 \leq N_d \leq 1.95$	$17 \leq V_d \leq 30$
231	$21 \leq R_1 \leq 35$	$-200 \leq R_2 \leq -50$	$1.8 \leq T_c \leq 3.8$	$1.7 \leq N_d \leq 1.95$	$20 \leq V_d \leq 42$
232	$8 \leq R_1 \leq 20$	$-30 \leq R_2 \leq -15$	$3 \leq T_c \leq 5$	$1.4 \leq N_d \leq 1.5$	$70 \leq V_d \leq 96$
233	$-30 \leq R_1 \leq -15$	$8 \leq R_2 \leq 20$	$0.6 \leq T_c \leq 2$	$1.7 \leq N_d \leq 1.95$	$17 \leq V_d \leq 30$
234	$8 \leq R_1 \leq 20$	$-75 \leq R_2 \leq -20$	$2.5 \leq T_c \leq 4.5$	$1.45 \leq N_d \leq 1.65$	$60 \leq V_d \leq 91$
235	$-20 \leq R_1 \leq -8$	$11 \leq R_2 \leq 35$	$0.6 \leq T_c \leq 2$	$1.45 \leq N_d \leq 1.65$	$60 \leq V_d \leq 82$
236	$11 \leq R_1 \leq 35$	$-21 \leq R_2 \leq -14$	$2 \leq T_c \leq 3.5$	$1.7 \leq N_d \leq 1.95$	$17 \leq V_d \leq 30$
237	$15 \leq R_1 \leq 30$	$150 \leq R_2$	$1 \leq T_c \leq 3$	$1.8 \leq N_d \leq 1.92$	$30 \leq V_d \leq 50$
238	$150 \leq R_1$	$6 \leq R_2 \leq 15$	$0.6 \leq T_c \leq 2$	$1.55 \leq N_d \leq 1.75$	$25 \leq V_d \leq 45$
239	$7 \leq R_1 \leq 15$	$-15 \leq R_2 \leq -7$	$2.5 \leq T_c \leq 4.5$	$1.4 \leq N_d \leq 1.5$	$70 \leq V_d \leq 96$
240	$-15 \leq R_1 \leq -7$	$150 \leq R_2$	$0.6 \leq T_c \leq 2$	$1.7 \leq N_d \leq 1.85$	$35 \leq V_d \leq 50$

[0073] In some embodiments, the parameters of each lens may be within a certain range. The certain range satisfying conditions listed in Table 1 may allow zoom lens system 100 to achieve a better imaging quality and a higher resolution.

[0074] In some embodiments, a first distance along the optical axis between the optical centers of lens elements 211 and 212 may be set in a range from 7.5mm to 10.5mm. For example, the distance may be set 10mm. In some embodiments, a second distance along the optical axis between the optical centers of lens elements 212 and 213 may be set in a range from 0.0mm to 4.0mm. For example, the distance may be set 2.4mm. In some embodiments, a third distance along the optical axis between the optical centers of lens elements 231 and 232 may be set in a range from 0.1mm to 0.5mm. For example, the distance may be set 0.1 mm. In some embodiments, three lens elements 232, 233 and 234 may be affixed to each other by adhesive (or any suitable materials or method). A fourth distance along the optical axis between the optical centers of the lens elements 234 and 235 may be set in a range from 0.5mm to 1.5mm. For example, the distance may be set 0.7mm. Two lens elements 235 and 236 may be rigidly affixed to each other and integrated into one lens component. In some embodiments, a fifth distance along the optical axis between the optical centers of lens elements 236 and 237 may be set in a range from 0.1mm to 0.5mm. For example, the distance may be set 0.1mm. Two lens elements 237 and 238 may be rigidly affixed to each other and integrated into one lens component. In some embodiments, a sixth distance along the optical axis between the optical centers of lens elements 238 and 239 may be set in a range from 0.1mm to 1.0mm. For example, the distance may be set

0.3mm. In some embodiments, two lens elements 239 and 240 may be rigidly affixed to each other and integrated into one lens component.

TABLE 2

Lens element	R ₁ (mm)	R ₂ (mm)	T _c (mm)	N _d	V _d
211	61	16	1.5	1.834	37.185
212	-37.55	22.61	1.1	1.697	55.534
213	30.4	-217.9	4.35	1.847	23.791
231	34.28	-95	2	1.883	40.807
232	11.1	-17.557	3.84	1.497	81.61
233	-17.557	11.328	0.7	1.717	29.51
234	11.328	-72.199	2.53	1.497	81.595
235	-15.103	34.055	0.7	1.487	70.42
236	34.055	-17.04	2.17	1.847	23.791
237	22.518	172.6	1.59	1.883	40.807
238	172.6	7.45	0.7	1.575	41.507
239	8.6	-8.6	3.48	1.497	81.61
240	-8.6	234.9	0.7	1.782	37.095

[0075] Zoom lens system 100 with parameters of each lens listed in Table 2 may have optical indexes as following. The total length of optical may be less than or equal to 95.7mm. The focus length may be in the range of 3.7 to 16 mm. The image surface may be 1/1.7". Aperture stop 120 may be in the range of 1.5 to 2.6.

[0076] In some embodiments, the first distance along the optical axis between the optical centers of lens elements 211 and 212 may be set 10mm. The second distance along the optical axis between the optical centers of lens elements 212 and 213 may be 2.4mm. The third distance along the optical axis between the optical centers of lens

elements 231 and 232 may be set 0.1 mm. The fourth distance along the optical axis between the optical centers of lens elements 234 and 235 may be set 0.7mm. The fifth distance along the optical axis between the optical centers of lens elements 236 and 237 may be set 0.1mm. The sixth distance along the optical axis between the optical centers of lens elements 238 and 239 may be set 0.3mm.

[0077] FIG. 3 illustrates an exemplary zoom lens system 100 configuration of an optical imaging device according to some embodiments of the present disclosure. . Zoom lens system 100, in order from the object, a first lens group 110, an aperture stop 120, a second lens group 130, a glass filter (GF) 340 and an image plane (IMA) 350.

[0078] It should be noted that the above description about lens is merely an example, should not be understood as the only embodiment. Obviously, to those skilled in the art, after understanding the basic principles of the connection between different devices, the devices and connection between the devices may be modified or varied without departing from the principles. The modifications and variations are still within the scope of the current disclosure described above. For example, second lens group 130 may have the configurations depicted in FIGs. 2B-2G.

[0079] FIGs. 4A through 4V illustrate optical simulation of the zoom lens system illustrated in FIG. 2A according to some embodiments of the present disclosure. FIGs. 4A and 4B show Modulation Transfer Function (MTF) performances of zoom lens system 100 illustrated in FIG. 2A in short focus and long focus, respectively. As shown in FIGs. 4A and 4B, the MTF curves are smooth, and the average value is greater than 0.64. The MTF curves may indicate that zoom lens system 100 may satisfy the resolution requirement of the imaging of a 12 million pixel and a 4K camera. FIGs. 4C

and 4D show the Modulation Transfer Function (MTF) performance of zoom lens system 100 illustrated in FIG. 2A in short focus and long focus with infrared light, respectively. As shown in FIGs. 4C and 4D, the MTF curves are smooth and the average value is more than 0.55. In some embodiments, the MTF may indicate that zoom lens system may have high resolution and optical performance with infrared light.

[0080] FIGs. 4E-4I are respectively transverse ray fan plots of images at different fields of zoom lens system illustrated in FIG. 2A in short focus (i.e., FIG. 4E at a field being 0mm; FIG. 4F at a field being 2.3mm, FIG. 4G at a field being 3.0mm, FIG. 4H at a field being 3.6mm, and FIG. 4I at a field being 4.4mm). FIGs. 4J-4N are respectively transverse ray fan plots of images at different fields of zoom lens system illustrated in FIG. 2A at long focus (i.e., FIG. 4J at a field being 0mm, FIG. 4K at a field being 2.3mm, FIG. 4L at a field being 3.0mm, FIG. 4M at a field being 3.6mm, and FIG. 4N at a field being 4.4mm). In some embodiments, a coordinate of a horizontal axis refers a position where a light ray passes through aperture stop 120, and a vertical axis refers to a distance between a position where the light ray forming an image on an image plane and a position where a chief ray forming an image on image plane 350. As shown in FIGs. 4E-4N, the aberration curves of the zoom lens system illustrated in FIG. 2A in short focus and long focus close to the horizontal axis. The aberration curves may indicate that the zoom lens system 100 may have a good imaging quality in the range of focus length.

[0081] FIGs. 4O and 4P are spots diagrams of zoom lens system illustrated in FIG. 2A in short focus and long focus, respectively. As shown in FIGs. 4O and 4P, the smaller the spot radius is, the better the image quality is. For example, the pixel size of

4K camera is $1.85\ \mu\text{m}$. The size of spots in FIGs. 4O and 4P are all smaller than the double size of the pixel size, and some of the spots have a size smaller than the pixel size. The sizes of spots may indicate that zoom lens system 100 may have a good imaging quality.

[0082] FIGs. 4Q and 4R are the field curvature diagrams of zoom lens system 100 illustrated in FIG. 2A in short focus and long focus, respectively. In some embodiments, a horizontal axis may refer to a distance from a focal plane, and a vertical axis may refer to the field of view from 0 to a maximum value. Three curves, S or T in FIGs. 4Q and 4R, represent image aberration of the light with the wavelengths of 460 nm, 550 nm and 620 nm, respectively. S represents data of a sagittal ray, and T represents data of a tangential ray. The smaller the value of tangential curvature of field is, the better the image quality is. FIGs. 4S and 4T are the distortion diagrams of the zoom lens system illustrated in FIG. 2A in short focus and long focus, respectively. In some embodiments, a horizontal axis may refer to a distortion of a specific percentage, and a vertical axis may refer to the field of view from 0 to a maximum value being. The closer the distortion curve approaches the vertical axis, the smaller the distortion of the zoom lens system is. As shown in FIGs. 4Q and 4S, as to the zoom lens system in short focus, the tangential curvature of field value is in the range of 0 to 0.015mm, sagittal curvature of field value is in the range of 0 to 0.01mm, and distortion rate is in the range of -27.5% to 0. As shown in FIGs. 4R and 4T, as to the zoom lens system in long focus, the tangential curvature of field value is in the range of 0 to 0.05mm, sagittal curvature of field value is in the range of 0 to 0.05mm, and distortion rate is in the range of -2.3% to 0.

[0083] FIGs. 4U and 4V are the chromatic aberration diagrams of zoom lens system 100 illustrated in FIG. 2A in short focus and long focus, respectively. The closer the chromatic aberration curve approaches the vertical axis, the smaller the aberration of the zoom lens system is. As shown in FIGs. 4U, the chromatic aberration of the zoom lens system in short focus is in the range of -0.02 to +0.02. As shown in FIG. 4V, the chromatic aberration of the zoom lens system in long focus is in the range of -0.05 to +0.05.

[0084] FIG. 5A is a schematic diagram illustrating an exemplary zoom lens system according to some embodiments of the present disclosure. As shown in FIGs. 1 and 5A, zoom lens system 100 may include a first lens group 110, an aperture stop 120, a second lens group, and other components (not shown). In some embodiments, first lens group 110 may have a negative refractive power, and second lens group 130 may have a positive refractive power. In some embodiments, first lens group 110, aperture stop 120, and second lens group 130 may be configured such that the following conditional expressions are satisfied:

$$\mathbf{[0085] \quad } 0.7 < |F_{eff} / F_1| < 1.7, \text{ and } 0.3 < |F_{eff} / F_c| < 1.2, \quad (4)$$

where F_{eff} represents the effective focal length of the zoom lens system, F_1 represents the effective focal length of the first lens group 110, and F_c represents the effective focal length of the second lens group 130.

[0086] In some embodiments, first lens group 110 having a negative refractive power may include one or more lens elements. For example, as illustrated in FIG. 5A, first lens group 110 may include a first lens element 511, a second lens element 512, and a third lens element 513. Second lens group 130 having a positive refractive power

may include one or more lens elements. For example, as illustrated in FIG. 5A, second lens group 130 may include a fourth lens element 531, a fifth lens element 532, a sixth lens element 533, a seventh lens element 534, an eighth lens element 535, and a ninth lens element 536. The lens elements above may be an individual lens having different properties than other lens elements (e.g., shape, size (e.g., height and width, etc.), refractive power, effective focal length, Abbe number of the lens elements, or the like, or any combination thereof).

[0087] The lens elements 511-513 and 531-536 may have different refractive powers. In some embodiments, first lens element 511, second lens element 512, and third lens element 513 may have a negative refractive power, a negative refractive power, and a positive refractive power, respectively. In some embodiments, fourth lens element 531, fifth lens element 532, sixth lens element 533, seventh lens element 534, eighth lens element 535, and ninth lens element 536 may have a negative refractive power, a positive refractive power, a positive refractive power, a positive refractive power, a positive refractive power, and a negative refractive power, respectively.

[0088] The lens elements 511-513 and 531-536 may have different configurations. In some embodiments, first lens element 511 may be a plano-concave lens with a convex surface towards image plane 350, second lens element 512 may be a meniscus lens with a convex surface towards an object (i.e., the opposite direction to image plane 350), and the third lens element 513 may be a meniscus lens with a convex surface towards the object. In some embodiments, fourth lens element 531 may be a biconcave lens, fifth lens element 532 may be a biconvex lens, sixth lens element 533 may be a meniscus lens with a convex surface towards image plane 350, seventh lens element

534 may be a biconvex lens, eighth lens element 535 may be a biconvex lens, ninth lens element 536 may be a biconcave lens. In some other embodiments, the configurations of the lens elements (e.g., in order from the object) may further satisfy conditions listed in Table 3. Table 3 lists radius of curvature R_1 (in mm) of the surface towards the object, radius of curvature R_2 (in mm) of the surface towards image plane 350, Abbe number V_d , refractive index N , and center thickness D (in mm) of a lens. A zoom lens system may be generated based on the lens elements listed in Table 3. In addition, an effective focal length of the zoom lens system may be 8 mm, size of aperture may satisfy $F/2.0$, and total length of the zoom lens system may be 23.5 mm.

TABLE 3

Lens element	R_1	R_2	N	V_d	D
511	$R_1 = \infty$	$5 < R_2 < 10$	$1.5 < N < 1.7$	$50 < V_d < 70$	$0.8 < D < 1.5$
512	$10 < R_1 < 15$	$4 < R_2 < 8$	$1.5 < N < 1.7$	$50 < V_d < 70$	$0.8 < D < 1.5$
513	$4 < R_1 < 8$	$400 < R_2 < 600$	$1.7 < N < 1.9$	$30 < V_d < 50$	$1.3 < D < 1.8$
531	$5 < R_1 < 10$	$5 < R_2 < 10$	$1.7 < N < 1.9$	$20 < V_d < 40$	$0.8 < D < 1.5$
532	$5 < R_1 < 10$	$5 < R_2 < 10$	$1.5 < N < 1.7$	$50 < V_d < 70$	$1.2 < D < 1.9$
533	$90 < R_1 < 150$	$5 < R_2 < 10$	$1.5 < N < 1.7$	$50 < V_d < 70$	$1.2 < D < 1.9$
534	$20 < R_1 < 30$	$20 < R_2 < 30$	$1.5 < N < 1.7$	$50 < V_d < 70$	$1.1 < D < 1.8$
535	$5 < R_1 < 10$	$40 < R_2 < 60$	$1.5 < N < 1.7$	$50 < V_d < 70$	$1.5 < D < 2.2$
536	$40 < R_1 < 60$	$5 < R_2 < 10$	$1.5 < N < 1.7$	$50 < V_d < 70$	$0.8 < D < 1.5$

[0089] In some embodiments, two lens elements may be affixed to each other by an adhesive (or any suitable materials or method). In some embodiments, two lens elements may be rigidly affixed to each other and integrated into one lens component.

For example, first lens element 511 may be affixed to second lens element 512 by an adhesive (e.g., glue, UV-curing adhesive, etc.), and integrated into a first lens component. In some embodiments, first lens element 511 may be a plano-concave lens, and second lens element 512 may be a meniscus lens. The first lens component, including first lens element 511 and second lens element 512 may have a positive refractive power. As another example, fourth lens element 531 and fifth lens element 532 may be affixed to each other and integrated into a second lens component. In some embodiments, fourth lens element 531 may be a biconcave lens, and fifth lens element 532 may be a biconvex lens. The second lens component, including fourth lens element 531 and fifth lens element 532 may have a negative refractive power. As another example, eighth lens element 535 and ninth lens element 536 may be affixed to each other and integrated into a third lens component. In some embodiments, eighth lens element 535 may be a biconvex lens, and ninth lens element 532 may be a biconvex lens. The third lens component, including eighth lens element 535 and ninth lens element 532 may have a positive refractive power.

[0090] FIG. 5B is a schematic diagram illustrating lens surfaces of the zoom lens system illustrated in FIG. 5A according to some embodiments of the present disclosure. Referring to FIGs. 1, and 5A, zoom lens system 100 may include first lens group 110, aperture stop 120, and second lens group 130. In some embodiments, as illustrated in FIG. 5B, zoom lens system 100 may include 15 lens surfaces (arranged from S1 to S15). First lens element 511 may include lens surface S1 and lens surface S2. Second lens element 512 (which may have lens surface S3) and third lens element 513 may be affixed to each other to form the first lens component. Lens surface S4 may be a

surface between the second lens element 512 and the third lens element 513. Lens surface S5 may be a surface of third lens element 513 towards the image plane 350. Fourth lens element 531 (which may have lens surface S6) and fifth lens element 532 may be affixed to each other to form the second lens component. Lens surface S7 may be a surface between fourth lens element 531 and fifth lens element 532. Lens surface S8 may be a surface of fifth lens element 532 towards the image plane 350. Sixth lens element 533 may have lens surface S9 (towards the object) and lens surface S10 (towards the image plane 350). Seventh lens element 534 may have lens surface S11 (towards the object) and lens surface S12 (towards the image plane 350). Eighth lens element 535 (which may have lens surface S13) and ninth lens element 536 may be affixed to form the third lens component. Lens surface S14 may be a surface between eighth lens element 535 and ninth lens element 536. Lens surface S15 may be a surface of the ninth lens element towards the image plane 350.

[0091] Merely by way of example, zoom lens system 100 may be configured according to the parameters listed in Table 4. In addition, an effective focal length of the zoom lens system may be 8 mm, size of aperture may satisfy F/2.0, and total length of the zoom lens system may be 23.5 mm.

TABLE 4

Lens surface	R	D	N _d	V _d
S1	∞	0.97	1.52	64.2
S2	5.439	1.28		
S3	11.325	1.03	1.52	59
S4	4.528	1.58	1.83	37.2

Lens surface	R	D	N _d	V _d
S5	-524.774	1.92		
S6	-5.831	1	1.85	30.1
S7	8.018	1.54	1.62	63.4
S8	-7.145	0.68		
S9	-102.769	1.66	1.57	57.5
S10	-8.831	0.12		
S11	25.07	1.61	1.62	58.2
S12	-25.07	0.11		
S13	7.783	1.81	1.66	54.7
S14	-47.413	1.01	1.58	40.9
S15	5.803	7.1		

[0092] FIGs. 6A through 6F illustrate optical simulation of an exemplary zoom lens system illustrated in FIGs. 5A and 5B according to some embodiments of the present disclosure. FIGs. 6A and 6B show Modulation Transfer Function (MTF) performances of the zoom lens system with visible light and infrared, respectively. The MTF performance may indicate the ability of the zoom lens system to reproduce various levels of details of an image captured by an imaging system implementing the zoom lens system. In FIGs. 6A and 6B, the vertical axis represents degree of contrast (also referred to as modulation), and the horizontal axis may represents spatial frequency (also referred to as resolution, in lp/mm). In some embodiments, the MTF may be used to evaluate imaging quality of a zoom lens system. For example, the MTF curves with

high degree of contrast and a slight slope may represent high-quality images produced by the zoom lens system.

[0093] FIG. 6C illustrates axial aberration of the zoom lens system with visible light. The axial aberration may include spherical aberration and axial chromatic aberration. One or more beams of visible light may be used to determine the axial aberration of the zoom lens system. In some embodiments, visible light with wavelength of 486nm, visible light with wavelength of 588 nm, and visible light with wavelength of 656 nm can be used to determine the axial aberration. In FIG. 6C, the vertical axis represents radius of the visible light (in mm), and the horizontal axis represents axial aberration (in mm).

[0094] FIG. 6D illustrates lateral chromatic aberration of the zoom lens system with visible light. One or more beams of visible light may be used to determine the lateral chromatic aberration of the zoom lens system. In some embodiments, visible light with wavelength of 486nm, visible light with wavelength of 588 nm, and visible light with wavelength of 656 nm can be used to determine the lateral chromatic aberration. As shown in FIG. 6D, the vertical axis represents radius of the visible light beam(s) (in μm), and the horizontal axis represents lateral chromatic aberration (in μm).

[0095] FIG. 6E illustrates field curvature of the zoom lens system. One or more beams of visible light may be used to determine the field curvature of the zoom lens system. In some embodiments, visible light with wavelength of 486nm, visible light with wavelength of 588 nm, and visible light with wavelength of 656 nm can be used to determine the field curvature. In FIG. 6E, the vertical axis represents the scale of field of view (in μm), and the horizontal axis represents field curvature (in mm).

[0096] FIG. 6F illustrates distortion of the zoom lens system. One or more beams of visible light may be used to determine the distortion of the zoom lens system. In some embodiments, visible light with wavelength of 486nm, visible light with wavelength of 588 nm, and visible light with wavelength of 656 nm can be used to determine the distortion. In FIG. 6F, the vertical axis represents the scale of field of view (in μm), and the horizontal axis represents distortion (in percentage).

[0097] FIG. 7 is a schematic diagram of another exemplary zoom lens system 100 according to some embodiments of the present disclosure. Referring again to FIG.1, zoom lens system 100 may include first lens group 110, aperture stop 120, second lens group 130, and other components (not shown). Image plane 350 may be a surface where an image may be captured. For example, a light-sensitive film may be mounted on the image plane 350 for capturing an image. In some embodiments, first lens group 110 may have a positive refractive power, and second lens group 130 may have a positive refractive power.

[0098] In some embodiments, first lens group 110 may include one or more lens elements. In some embodiments, the first lens group 110 may include a first lens element 711, a second lens element 712, a third lens element 713, a fourth lens element 714, a fifth lens element 715, and a sixth lens element 716. In some embodiments, second lens group 130 may include a seventh lens element 731, an eighth lens element 732, a ninth lens element 733, a tenth lens element 734, and a eleventh lens element 735.

[0099] The lens elements 711-716 and 731-735 may have different refractive powers. In some embodiments, first lens element 711, second lens element 712, third

lens element 713, fourth lens element 714, fifth lens element 715, and sixth lens element 716 may have a positive refractive power, a negative refractive power, a negative refractive power, a positive refractive power, a negative refractive power, and a positive refractive power, respectively. In some embodiments, seventh lens element 731, eighth lens element 732, ninth lens element 733, tenth lens element 734, and eleventh lens element 735 may have a positive refractive power, a negative refractive power, a positive refractive power, a positive refractive power, and a positive refractive power, respectively.

[0100] The lens elements 711-716 and 731-735 may have different configurations. In some embodiments, first lens element 711 may be a meniscus lens with a convex surface towards an object (i.e., the opposite direction to image plane 350), second lens element 712 may be a meniscus lens with a convex surface towards the object, third lens element 713 may be a biconcave lens, fourth lens element 714 may be a meniscus lens with a convex surface towards image plane 350, fifth lens element 715 may be a meniscus lens with a convex surface towards image plane 350, and sixth lens element 716 may be a biconvex lens. In some embodiments, seventh lens element 731 may be a meniscus lens with a concave surface towards the object, eighth lens element 732 may be a biconcave lens, ninth lens element 733 may be a biconvex lens, tenth lens element 734 may be a biconvex lens, and eleventh element 735 may be a meniscus lens with a convex surface towards the object. In some embodiments, a gap between two lens elements (or between a lens element and a lens component, or between two lens components) may be fixed by one or more spacers. In some embodiments, a first gap may be present between third lens element 713 and fourth lens element 714, and a

second gap may be present between fifth lens element 715 and sixth lens element 716. In some embodiments, a third gap may be present between seventh lens element 731 and eighth lens element 732, a fourth gap may be present between ninth lens element 733 and tenth lens element 734, and a fifth gap may be present between tenth lens element 734 and eleventh lens element 735.

[0101] In some embodiments, two lens elements may be affixed to each other by adhesive (or any suitable materials or method). In some embodiments, two or more lens elements may be rigidly affixed together and integrated into one lens component. Merely by way of example, fourth lens element 714 and fifth lens element 715 may be affixed to each other (e.g., by glue, UV-curing adhesive, etc.) and integrated into a first lens component. The first lens component may have a positive refractive power. As another example, eighth lens element 732 and ninth lens element 733 may be affixed to each other and integrated into a second lens component. The second lens component may have a negative refractive power.

[0102] FIG. 8 illustrates an exemplary zoom lens system configuration of an optical imaging device 800 according to some embodiments of the present disclosure. The optical imaging device may include a zoom lens system 100, a primary lens barrel 830, a secondary lens barrel 820, one or more spacers (e.g., a first spacer 810, a second spacer 840, a third spacer 850, a fourth spacer 860, a fifth spacer 870, a sixth spacer 880), and/or other components. The spacers 810, 840, 850, 860, 870 and 880 may be used to fix the gaps between the lens elements, and to generate (or maintain) air spaces between the lens elements. For example, spacer 810 may be used to fix the gap between first lens element 711 and second lens element 712; spacer 860 may be used

to fix the gap between third lens element 713 and fourth lens element 714; spacer 870 may be used to fix the gap between fifth lens element 715 and sixth lens element 716; spacer 880 may be used to fix the gap between seventh lens element 731 and eighth lens element 732; spacer 840 may be used to fix the gap between ninth lens element 733 and tenth lens element 734; spacer 850 may be used to fix the gap between tenth lens element 734 and eleventh lens element 735. In some embodiments, secondary lens barrel 820 may house first lens group 110. In some embodiments, secondary lens barrel 820 may be mounted to primary lens barrel 830.

[0103] Having thus described the basic concepts, it may be rather apparent to those skilled in the art after reading this detailed disclosure that the foregoing detailed disclosure is intended to be presented by way of example only and is not limiting. Various alterations, improvements, and modifications may occur and are intended to those skilled in the art, though not expressly stated herein. These alterations, improvements, and modifications are intended to be suggested by this disclosure, and are within the spirit and scope of the exemplary embodiments of this disclosure.

[0104] Moreover, certain terminology has been used to describe embodiments of the present disclosure. For example, the terms "one embodiment," "an embodiment," and/or "some embodiments" mean that a particular feature, structure or characteristic described in connection with the embodiment is included in at least one embodiment of the present disclosure. Therefore, it is emphasized and should be appreciated that two or more references to "an embodiment" or "one embodiment" or "an alternative embodiment" in various portions of this specification are not necessarily all referring to

the same embodiment. Furthermore, the particular features, structures or characteristics may be combined as suitable in one or more embodiments of the present disclosure.

[0105] Further, it will be appreciated by one skilled in the art, aspects of the present disclosure may be illustrated and described herein in any of a number of patentable classes or context including any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof. Accordingly, aspects of the present disclosure may be implemented entirely hardware, entirely software (including firmware, resident software, micro-code, etc.) or combining software and hardware implementation that may all generally be referred to herein as a "block," "module," "engine," "unit," "component," or "system." Furthermore, aspects of the present disclosure may take the form of a computer program product embodied in one or more computer readable media having computer readable program code embodied thereon.

[0106] Furthermore, the recited order of processing elements or sequences, or the use of numbers, letters, or other designations therefore, is not intended to limit the claimed processes and methods to any order except as may be specified in the claims. Although the above disclosure discusses through various examples what is currently considered to be a variety of useful embodiments of the disclosure, it is to be understood that such detail is solely for that purpose, and that the appended claims are not limited to the disclosed embodiments, but, on the contrary, are intended to cover modifications and equivalent arrangements that are within the spirit and scope of the disclosed embodiments.

[0107] Similarly, it should be appreciated that in the foregoing description of embodiments of the present disclosure, various features are sometimes grouped

together in a single embodiment, figure, or description thereof for the purpose of streamlining the disclosure aiding in the understanding of one or more of the various inventive embodiments. This method of disclosure, however, is not to be interpreted as reflecting an intention that the claimed subject matter requires more features than are expressly recited in each claim. Rather, inventive embodiments lie in less than all features of a single foregoing disclosed embodiment.

WHAT WE CLAIMED ARE:

1. A zoom lens system, comprising:

a first lens group including:

at least two lens elements having a negative refractive power; and

at least one lens element having a positive refractive power;

an aperture stop; and

a second lens group having a positive refractive power including:

a first lens element having a positive refractive power;

a second lens element having a positive refractive power;

a first lens component having a negative refractive power;

a third lens element having a negative refractive power;

a fourth lens element having a positive refractive power;

a second lens component having a negative refractive power;

a fifth lens element having a positive refractive power; and

a sixth lens element having a negative refractive power, wherein:

the first lens component includes at least one lens element,

the second lens component includes at least one lens element,

the fifth lens element having a positive refractive power and the sixth lens element having a negative refractive power are affixed to each other, and

a distance between the first lens group and the second lens group is not fixed.

2. The zoom lens system of claim 1, wherein:

the first lens element of the second lens group is a biconvex lens, and
a refractive index of the first lens element is no less than 1.7.

3. The zoom lens system of claim 1, wherein:

the second lens element of the second lens group is a biconvex lens,
an Abbe number of the second lens element of the second lens group is greater than 80, and
the second lens element and the first lens component of the second lens group are affixed to each other.

4. The zoom lens system of claim 1, wherein the first lens component of the second lens group includes:

a biconcave lens having a negative refractive power, and
a biconvex lens having a positive refractive power, the biconcave lens and the biconvex lens being affixed to each other.

5. The zoom lens system of claim 1, wherein:

the third lens element of the second lens group is a biconcave lens,
an Abbe number of the third lens element of the second lens group is greater than 65, and
a refractive index of the third lens element of the second lens group is less than 1.55.

6. The zoom lens system of claim 1, wherein:

the fourth lens element of the second lens group is a biconvex lens, and

the third lens element and the fourth lens element of the second lens group are affixed to each other.

7. The zoom lens system of claim 1, wherein the second lens component of the second lens group includes:

a first meniscus lens having a positive refractive power,

a second meniscus lens having a negative refractive power, and

the first meniscus lens and the second meniscus lens are affixed to each other.

8. The zoom lens system of claim 1, wherein:

the fifth lens element of the second lens group is a biconvex lens, and

an Abbe number of the fifth lens element is greater than 80.

9. The zoom lens system of claim 1, wherein:

the sixth lens element of the second lens group is a biconcave lens,

an Abbe number of the sixth lens element of the second lens group is less than that of the fifth lens element of the second lens group, and

a refractive index of the sixth lens element of the second lens group is greater than that of the fifth lens element of the second lens group.

10. The zoom lens system of claim 1, wherein the first lens group includes:

a first meniscus lens having a negative refractive power,

a biconcave lens having a negative refractive power, and

a second meniscus lens having a positive refractive power, convex surfaces of the first and second meniscus lenses facing against an image plane.

11. The zoom lens system of claim 1, wherein the zoom lens system satisfies $1.85 \leq$

$|f_1|/(f_w \times f_t)^{\frac{1}{2}} \leq 2.25$, f_1 being a focus length of first lens group, f_w being a shortest focus length of the zoom lens system, f_t being a longest focus length of the zoom lens system.

12. The zoom lens system of claim 1, wherein the zoom lens system satisfies $0.8 <$

$f_2/f_w < 1.2$, f_2 being a focus length of second lens group, and f_w being a shortest focus length of zoom lens system.

13. The zoom lens system of claim 10, wherein the zoom lens system satisfies $0.4 < N_n \times$

$f_w/f_t < 0.55$, N_n being an average refractive index of the meniscus lens having a negative refractive power and the biconcave lens having a negative refractive power, f_w being a shortest focus length of zoom lens system, and f_t being a longest focus length of zoom lens system.

14. A lens, comprising the zoom lens system of claim 1.

15. A zoom lens system, comprising:

a first lens group including:

at least two lens elements of negative refractive power; and

at least one lens element of a positive refractive power;

an aperture stop; and

a second lens group having a positive refractive power including:

a first lens element having a negative refractive power;

a second lens element having a positive refractive power;

a third lens element having a positive refractive power;

a fourth lens element having a positive refractive power;

a fifth lens element having a positive refractive power; and

a sixth lens element having a negative refractive power, wherein:

a distance between the first lens group and the second lens group

is not fixed.

16. The zoom lens system of claim 15, wherein the zoom lens system satisfies $0.7 < |F_{eff}/F_1| < 1.7$, and $0.3 < |F_{eff}/F_c| < 1.2$, F_{eff} being an effective focal length of the zoom lens system, F_1 being an effective focal length of the first lens group, and F_c being an effective focal length of the second lens group.

17. The zoom lens system of claim 15, wherein the first lens group includes:

a plano-concave lens, a concave surface of the plano-convex lens facing an image plane,

two meniscus lenses, convex surfaces of the two meniscus lenses facing against an image plane, and

the two meniscus lenses are affixed to each other.

18. The zoom lens system of claim 15, wherein:

the first lens element of the second group is a biconcave lens,

the second lens element of the second group is a biconvex lens,

the third lens element of the second group is a meniscus lens,

the fourth lens element of the second group is a biconvex lens,

the fifth lens element of the second group is a biconvex lens, and

the sixth lens element of the second group is a biconcave lens.

19. The zoom lens system of claim 15, wherein:

the first lens element of the second group and the second lens element of the second group are affixed to each other, and

the fifth lens element of the second group and the sixth lens element of the second group are affixed to each other.

20. The zoom lens system of claim 17, wherein:

a first concave surface of one of the two meniscus lens and a second concave surface of the other one of the two meniscus lens are integrated into a lens component by adhesive, and

the lens component has a positive refractive power.

21. The zoom lens system of claim 19, wherein:

a concave surface of the first lens element of the second group and a convex surface of the second lens element of the second group are integrated into a lens component by adhesive, and

the lens component has a negative refractive power.

22. The zoom lens system of claim 19, wherein:

a convex surface of the fifth lens element of the second group and a concave surface of the sixth lens element are integrated into a lens component by adhesive, and

the lens component has a positive refractive power.

23. A lens, comprising the zoom lens system of claim 15.

24. A zoom lens system, comprising:

a first lens group including:

at least two lens elements having a negative refractive power;

at least two lens elements having a positive refractive power; and

at least one lens component having a positive refractive power, the at least one lens component includes at least one lens element;
an aperture stop; and
a second lens group having a positive refractive power including:
a first lens element having a positive refractive power;
a first lens component having a negative refractive power;
a second lens element having a positive refractive power; and
a third lens element having a positive refractive power, wherein:
the first lens component includes at least one lens element, and
a distance between the first lens group and the second lens group is not fixed.

25. The zoom lens system of claim 24, wherein the first lens group includes:

a first meniscus lens having a positive refractive power;
a second meniscus lens having a negative refractive power;
a biconcave lens having a negative refractive power;
a second lens component having a positive refractive power; and
a biconvex lens having a positive refractive power, convex surfaces of the first and second meniscus lenses facing against an image plane.

26. The zoom lens system of claim 25, the second lens component of the first lens group includes:

a third meniscus lens having a positive refractive power; and

a fourth meniscus lens having a negative refractive power, the third meniscus lens and the fourth meniscus lens being affixed to each other.

27. The zoom lens system of claim 24, the first lens component of the second lens group includes:

a biconcave lens having a negative refractive power; and

a biconvex lens having a positive refractive power, the biconcave lens and the biconvex lens being affixed to each other.

28. A lens, comprising the zoom lens system of claim 24.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 2G




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H




FIG. 4I




FIG. 4J




FIG. 4K




FIG. 4L




FIG. 4M





FIG. 4N



Field of view:	1	2	3	4	5
Centroid radius:	1.482	2.635	3.039	3.138	2.999
Geometry radius:	2.619	11.149	11.803	14.255	15.894

FIG. 4O




FIG. 4P




FIG. 4Q

Field curvature




FIG. 4R




FIG. 4S




FIG. 4T




FIG. 4U




FIG. 4V




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D

Field curvature




FIG. 6E

Distortion




FIG. 6F




FIG. 7




FIG. 8

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2016/086000

A. CLASSIFICATION OF SUBJECT MATTER

G02B 15/177(2006.01)i; G02B 13/00(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G02B13; G02B11; G02B15; G02B9

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

CNABS, CNTXT, VEN:4th, 6th, fourth+, sixth+, eighth, 8th, ninth, 9th, tenth, 10th, negative, positive, meniscus, biconcave, biconvex

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CN 101320125 A (CANON KK) 10 December 2008 (2008-12-10) description, page 13, line 21 to page 15, line 19 and figure 1	1, 2, 8, 10, 14
PX	CN 105182504 A (ZHEJIANG DAHUA TECHNOLOGY CO) 23 December 2015 (2015-12-23) claims 1-11	24-28
A	US 2002126393 A1 (ASAHI SEIMITSU KK) 12 September 2002 (2002-09-12) the whole document	15-23
A	CN 102955233 A (TAMRON KK) 06 March 2013 (2013-03-06) the whole document	15-23
X	JP 2005316052 A (TOCHIGI NIKON CORP ET AL.) 10 November 2005 (2005-11-10) description, paragraphs [0038]-[0043] and figure 5	24, 27, 28
PX	CN 204807791 U (ZHEJIANG DAHUA TECHNOLOGY CO) 25 November 2015 (2015-11-25) claims 1-8, description, paragraphs [0030]-[0043], and figure 1	15-23

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

“&” document member of the same patent family

Date of the actual completion of the international search

23 August 2016

Date of mailing of the international search report

20 September 2016

Name and mailing address of the ISA/CN

STATE INTELLECTUAL PROPERTY OFFICE OF THE
P.R.CHINA
6, Xitucheng Rd., Jimen Bridge, Haidian District, Beijing
100088
China

Facsimile No. (86-10)62019451

Authorized officer

ZHANG, Yu

Telephone No. (86-10)62085762

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2016/086000**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
PX	CN 204964860 U (ZHEJIANG DAHUA TECHNOLOGY CO) 13 January 2016 (2016-01-13) claims 1-11, description, paragraphs [0029]-[0052], and figure 1	24-28
PX	CN 204807794 U (ZHEJIANG DAHUA TECHNOLOGY CO) 25 November 2015 (2015-11-25) claims 1-13, description, paragraphs [0006]-[0048], and figures 1(a)-2	1-14
A	JP 2012242688 A (TAMRON KK) 10 December 2012 (2012-12-10) the whole document	15-23

INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2016/086000

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

- [1] I: Claims 1-14 direct to a zoom lens system or a lens comprising a first lens group having at least two negative lenses and one positive lens, and a second lens group having a positive first lens, a positive second lens, a negative first lens component, a negative third lens, a positive fourth lens, a negative second lens component, a positive fifth lens, and a negative sixth lens.
- [2] II: Claims 15-23 direct to a zoom lens system or a lens comprising a first lens group having at least two negative lenses and one positive lens, and a second lens group having a negative first lens, a positive second lens, a positive third lens, a positive fourth lens, a positive fifth lens, and a negative sixth lens.
- [3] III: Claims 24-28 direct to a zoom lens system or a lens comprising: a first lens group having at least two negative lenses, two positive lenses, and one positive lens component; a second lens group having a positive first lens, a negative first lens component, a positive second lens, and a positive third lens.
- [4] Claims 1-14, 15-23, and 24-28 do not form a single general inventive concept, and do not satisfy the criteria set out in PCT Rule 13.1.

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/CN2016/086000

Patent document cited in search report			Publication date (day/month/year)	Patent family member(s)			Publication date (day/month/year)
CN	101320125	A	10 December 2008	US	7755843	B2	13 July 2010
				EP	2000839	A1	10 December 2008
				JP	2008304765	A	18 December 2008
				CN	101320125	B	22 September 2010
				EP	2000839	B1	28 November 2012
				US	2008304162	A1	11 December 2008
CN	105182504	A	23 December 2015	None			
US	2002126393	A1	12 September 2002	JP	3559526	B2	02 September 2004
				JP	2002207166	A	26 July 2002
				US	6683730	B2	27 January 2004
				GB	0200611	D0	27 February 2002
				GB	2371120	A	17 July 2002
				GB	2371120	B	13 October 2004
				DE	10200841	B4	25 November 2004
				DE	10200841	A1	18 July 2002
CN	102955233	A	06 March 2013	US	9229204	B2	05 January 2016
				US	2013050827	A1	28 February 2013
				JP	2013044964	A	04 March 2013
				CN	102955233	B	17 June 2015
JP	2005316052	A	10 November 2005	None			
CN	204807791	U	25 November 2015	None			
CN	204964860	U	13 January 2016	None			
CN	204807794	U	25 November 2015	None			
JP	2012242688	A	10 December 2012	None			