

(12) **United States Patent**
Hon et al.

(10) **Patent No.:** **US 11,699,776 B2**
(45) **Date of Patent:** **Jul. 11, 2023**

(54) **LIGHT-EMITTING ELEMENT HAVING CONDUCTIVE CONTACT LAYER**

(71) Applicant: **EPISTAR CORPORATION**, Hsinchu (TW)

(72) Inventors: **Schang-Jing Hon**, Hsinchu (TW);
Chao-Hsing Chen, Hsinchu (TW);
Tsun-Kai Ko, Hsinchu (TW);
Chien-Fu Shen, Hsinchu (TW);
Jia-Kuen Wang, Hsinchu (TW);
Hung-Che Chen, Hsinchu (TW)

(73) Assignee: **EPISTAR CORPORATION**, Hsinchu (TW)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 158 days.

(21) Appl. No.: **17/185,551**

(22) Filed: **Feb. 25, 2021**

(65) **Prior Publication Data**

US 2021/0202797 A1 Jul. 1, 2021

Related U.S. Application Data

(63) Continuation of application No. 16/446,059, filed on Jun. 19, 2019, now Pat. No. 10,964,847, which is a (Continued)

(30) **Foreign Application Priority Data**

Jul. 12, 2012 (TW) 101146339

(51) **Int. Cl.**
H01L 33/38 (2010.01)
H01L 33/62 (2010.01)
(Continued)

(52) **U.S. Cl.**
CPC **H01L 33/38** (2013.01); **H01L 33/20** (2013.01); **H01L 33/24** (2013.01); **H01L 33/38** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC H01L 33/38-387; H01L 3/44; H01L 33/44
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,573,537 B1 * 6/2003 Steigerwald H01L 33/405
257/E33.068

8,476,644 B2 7/2013 Illek et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101720513 6/2010
CN 101331622 B 11/2010

(Continued)


Primary Examiner — Wasiul Haider

(74) *Attorney, Agent, or Firm* — Muncy, Geissler, Olds & Lowe, P.C.

(57) **ABSTRACT**

A light-emitting element includes a substrate including a first side, a second side and a third side connecting the first side and the second side; a light-emitting semiconductor stack on the substrate and including a first semiconductor layer, a second semiconductor layer, and a light-emitting layer between the first semiconductor layer and the second semiconductor layer; a first electrode on the first semiconductor layer and including a contact area and a first extension area; a second electrode on the second semiconductor layer; a protection layer on the light-emitting semiconductor stack and including a first through hole exposing the first electrode and a second through hole exposing the second electrode; a first conductive part on the protection layer and electrically connected to the first electrode; and a second conductive part on the protection layer and electrically connected to the second electrode, wherein the second conductive part comprises a projected area on the light-emitting semiconductor stack, the first extension area is located outside the projected area and located between the second conductive part and the third side.

18 Claims, 10 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/279,149, filed on Sep. 28, 2016, now Pat. No. 10,374,130, which is a continuation of application No. 15/050,917, filed on Feb. 23, 2016, now Pat. No. 9,461,208, which is a continuation of application No. 14/827,872, filed on Aug. 17, 2015, now Pat. No. 9,306,123, which is a continuation of application No. 14/718,242, filed on May 21, 2015, now Pat. No. 9,153,738, which is a continuation of application No. 14/098,911, filed on Dec. 6, 2013, now Pat. No. 9,076,946.

9,153,738	B2	10/2015	Hon et al.
9,306,123	B2	4/2016	Hon et al.
2005/0194605	A1	9/2005	Shelton et al.
2009/0065800	A1	3/2009	Wirth et al.
2010/0012963	A1	1/2010	Hwan
2010/0051994	A1	3/2010	Katsuno et al.
2011/0062457	A1	3/2011	Naito et al.
2011/0163346	A1	7/2011	Seo et al.
2011/0297997	A1	12/2011	Izuka et al.
2012/0187424	A1	6/2012	Kim et al.
2012/0241760	A1*	9/2012	Okabe H01L 33/38 257/E33.025
2013/0234192	A1	9/2013	Kim et al.
2013/0248910	A1	9/2013	Kimura et al.
2014/0021441	A1	1/2014	Katsuno et al.
2014/0048825	A1	2/2014	Hsieh et al.
2014/0361327	A1	12/2014	Chae et al.
2015/0255676	A1	9/2015	Hon et al.

(51) **Int. Cl.**

H01L 33/54 (2010.01)
H01L 33/44 (2010.01)
H01L 33/46 (2010.01)
H01L 33/20 (2010.01)
H01L 33/24 (2010.01)

(52) **U.S. Cl.**

CPC *H01L 33/44* (2013.01); *H01L 33/46* (2013.01); *H01L 33/54* (2013.01); *H01L 33/62* (2013.01); *H01L 2224/73265* (2013.01)

FOREIGN PATENT DOCUMENTS

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,592,847 B2 11/2013 Chen et al.
 9,076,946 B2 7/2015 Hon et al.

CN	102738344	10/2012
CN	201170722	9/2014
JP	2008-288548 A	11/2008
TW	201131815 A1	9/2011
TW	201246611 A	11/2012

* cited by examiner




FIG.1A




FIG.1B




FIG.1C




FIG.1D




FIG.1E




FIG.2A




FIG.2B




FIG.3





FIG.4

6

FIG. 5






FIG.6
(PRIOR ART)

LIGHT-EMITTING ELEMENT HAVING CONDUCTIVE CONTACT LAYER

REFERENCE TO RELATED APPLICATION

This application is a continuation application of U.S. patent application Ser. No. 16/446,059, filed on Jun. 19, 2019, which is a continuation application of U.S. patent application Ser. No. 15/279,149, filed on Sep. 28, 2016, which is a continuation application of U.S. patent application Ser. No. 15/050,917, filed on Feb. 23, 2016, which is a continuation application of U.S. patent application Ser. No. 14/827,872, filed on Aug. 17, 2015, now issued, which is a continuation application of U.S. patent application Ser. No. 14/718,242, filed on May 21, 2015, now issued, which is a continuation application of U.S. patent application Ser. No. 14/098,911, filed on Dec. 6, 2013, now issued, which claims the right of priority based on TW application Serial No. 101146339, filed on Dec. 7, 2012, and the contents of which are hereby incorporated by references in their entireties.

TECHNICAL FIELD

The present application relates to a light-emitting element, and particularly to a light-emitting element such as a flip-chip light-emitting diode, which comprises a conductive contact layer.

DESCRIPTION OF BACKGROUND ART

Optoelectronic devices, such as light-emitting diodes, are now widely used for optical display devices, traffic lights, data storage devices, communication devices, lighting devices, and medical devices.

Besides, the light-emitting diode as mentioned above is able to combine with other structures to form a light-emitting device. FIG. 6 schematically shows a conventional light-emitting device. As shown in FIG. 6, a conventional light-emitting device 5 comprises a submount 52 comprising an electrical circuit 54; a solder 56 on the submount 52, wherein the solder is used for stabilizing an LED 51 on the submount 52 and thus renders the LED 51 electrically connected to the electrical circuit 54 of the submount 52, wherein the LED 51 comprises a substrate 53; and an electrical connecting structure 58 used for electrically connecting an electrode 55 of the LED 51 to the electrical circuit 54 of the submount 52; wherein the submount 52 is a lead frame or a large-scale mounting substrate.

SUMMARY OF THE DISCLOSURE

A light-emitting element includes: a substrate including: a first side; a second side opposite to the first side; and a third side connecting the first side and the second side; a light-emitting semiconductor stack formed on the substrate and including: a first semiconductor layer; a second semiconductor layer; and a light-emitting layer between the first semiconductor layer and the second semiconductor layer; a first electrode formed on the first semiconductor layer, extending from the first side to the second side and including a contact area and a first extension area; a second electrode formed on the second semiconductor layer; a protection layer formed on the light-emitting semiconductor stack, including a first through hole exposing the first electrode and a second through hole exposing the second electrode; a first conductive part formed on the protection layer and electrically connected to the first electrode through the first

through hole; and a second conductive part formed on the protection layer and electrically connected to the second electrode through the second through hole, wherein the second conductive part comprises a projected area on the light-emitting semiconductor stack, the extension area is located outside the projected area and located between the second conductive part and the third side.

A backlight module includes: a plurality of light-generating elements, wherein one of the plurality of light-generating element including: a first side; a second side opposite to the first side; and a third side connecting the first side and the second side; a light-emitting semiconductor stack; a first electrode formed on the light-emitting semiconductor stack, extending from the first side to the second side and including a first contact area and a first extension area; a second electrode formed on the light-emitting semiconductor stack and including a second contact area; a protection layer formed on the light-emitting semiconductor stack, comprising a first through hole exposing the first contact area and a second through hole exposing the second contact area; a first conductive part formed on the protection layer and electrically connected to the first electrode through the first contact area; and a second conductive part formed on the protection layer and electrically connected to the second electrode through the second contact area, wherein the second conductive part comprises a projected area on the light-emitting semiconductor stack, the first extension area is located outside the projected area and located between the second conductive part and the third side; and an optical element processing a light generated by the light-generating elements.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a top view of a light-emitting element in accordance with one of the embodiments of the present application;

FIG. 1B is a cross-sectional diagram along the line of A-A' in accordance with the light-emitting element of the present application shown in FIG. 1A;

FIG. 1C is a cross-sectional diagram along the line of B'-B' shown in FIG. 1A in accordance with one of the embodiments of the light-emitting element of the present application;

FIG. 1D is a cross-sectional diagram along the line of B'-B' shown in FIG. 1A in accordance with one of the embodiments of the light-emitting element of the present application;

FIG. 1E is a three dimensional view in accordance with the light-emitting element of the present application shown in FIG. 1A;

FIG. 2A is a top view of a light-emitting element in accordance with one of the embodiments of the present application;

FIG. 2B is a cross-sectional diagram along the line of C-C' in accordance with the light-emitting element of the present application shown in FIG. 2A;

FIG. 3 schematically shows a light-generating element in accordance with one of the embodiments of the present application;

FIG. 4 schematically shows a backlight module in accordance with one of the embodiments of the present application;

FIG. 5 is an exploded view of a light bulb in accordance with one of the embodiments of the present application; and FIG. 6 schematically shows a conventional light-emitting device.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Exemplary embodiments of the present application will be described in detail with reference to the accompanying drawings hereafter. The following embodiments are given by way of illustration to help those skilled in the art fully understand the spirit of the present application. Hence, it should be noted that the present application is not limited to the embodiments herein and can be realized by various forms. Further, the drawings are not precise scale and components may be exaggerated in view of width, height, length, etc. Herein, the similar or identical reference numerals will denote the similar or identical components throughout the drawings.

FIG. 1A is a top view of a light-emitting element in accordance with one of the embodiments of the present application. FIG. 1B is a cross-sectional diagram along the line of A-A' of FIG. 1A. As shown in FIGS. 1A and 1B, a light-emitting element 1 comprises a substrate 10; a light-emitting semiconductor stack 12 on the substrate 10; a first protection layer 11 on the light-emitting semiconductor stack 12; a reflective layer 13 on the first protection layer 11; a barrier layer 15 on the reflective layer 13 and covering and surrounding the reflective layer 13; a second protection layer 17 on the barrier layer 15 and covering and surrounding the first protection layer 11, the reflective layer 13, and the barrier layer 15; and a conductive contact layer 19 on the second protection layer 17. The light-emitting semiconductor stack 12 comprises a first semiconductor layer 122 on the substrate 10; a light-emitting layer 124 on the first semiconductor layer 122; a second semiconductor layer 126 on the light-emitting layer 124. The light-emitting element 1 further comprises multiple first electrodes 121 on the first semiconductor layer 122; and a second electrode 123 on the second semiconductor layer 126, wherein each first electrode 121 comprises a contact area 125 and an extension area 127. In the present embodiment, the multiple first electrodes 121 are physically separated from one another, such as spatially separated from one another, and are electrically connected to one another by a first conductive part 190, so as to reduce a portion of the light-emitting semiconductor stack 12 that needs to be removed. Thus, the light emitting area is increased. The second protection layer 17 has a first through hole 172 and a second through hole 174, wherein the first through hole 172 is above the contact area 125, as shown in FIG. 1B, and the second through hole 174 is above the barrier layer 15, as shown in FIG. 1A.

The conductive contact layer 19 is for receiving an external voltage and for heat dissipation. The conductive contact layer 19 comprises a first conductive part 190 and a second conductive part 191, and the conductive contact layer 19 is composed of one or multiple metal materials. The metal material comprises Cu, Sn, Au, Ni, Ti, Pt, Pb, AuSn alloy, Cu—Sn, Cu—Zn, Cu—Cd, Sn—Pb—Sb, Sn—Pb—Zn, Ni—Sn, Ni—Co, Au alloy, Au—Cu—Ni—Au, and the combinations thereof.

Referring to FIG. 1A, each extension area 127 of the first electrodes 121 extends outwardly from one of the contact areas 125 so the extension areas 127 cover larger area on the first semiconductor layer 122 to improve current spreading. As shown in FIG. 1A, an end of each extension area 127

distant away from the contact areas 125 is under the second conductive part 191, but the present disclosure is not limited to this, and the end of each extension area 127 can also protrude beyond a projected area of the second conductive part 191. Referring to FIG. 1B, the first conductive part 190 is electrically connected to the contact areas 125 of the first electrodes 121 by the first through hole 172, and therefore a current can flow from the first conductive part 190 to the first semiconductor layer 122 through the first electrodes 121, wherein the first semiconductor layer 122 is under the second conductive part 191. The second conductive part 191 is electrically connected to the barrier layer 15 by the second through hole 174, and therefore a current can flow from the second conductive part 191 to the second semiconductor layer 126 through the barrier layer 15, the reflective layer 13, and the second electrode 123. Referring to FIG. 1B, the first conductive part 190 comprises a first width w_1 and the second conductive part 191 comprises a second width w_2 . In the present embodiment, the first width w_1 is smaller than the second width w_2 . A distance d between the first conductive part 190 and the second conductive part 191 is at least about 50 μm . More preferably, the distance d ranges from 70 to 150 μm . A distance smaller than 50 μm leads to a short circuit, for example, prior to a process of soldering the light-emitting element 1 and a base (not shown), a solder paste is applied on the first conductive part 190 and the second conductive part 191 respectively, if the distance d is smaller than 50 μm , the solder pastes on the first conductive part 190 and the second conductive part 191 are easily in contact with each other, and the contact then causes a short circuit; or during a process of an eutectic bonding between the light-emitting element 1 and a base, an inaccurate alignment between the light-emitting element 1 and the base leads to a misalignment between the first conductive part 190 and one of the electrodes on the base, and between the second conductive part 191 and another electrode of the base, and then the misalignment causes a short circuit.

In another embodiment, the first conductive part 190 comprises a first height h_1 defined as a distance between an upper surface of the first conductive part 190 and an upper surface of the substrate 10, and the second conductive part 191 comprises a second height h_2 defined as a distance between an upper surface of the second conductive part 191 and the upper surface of the substrate 10, wherein the first height h_1 is substantially equal to the second height h_2 . As a result, a height difference between the first conductive part 190 and the second conductive part 191, which causes a failure of a connection between a base and the light-emitting element 1, is prevented. Thus, the quality is improved. The first width w_1 of the present embodiment is not limited to smaller than the second width w_2 . The first width w_1 can be larger than or equal to the second width w_2 as well.

In another embodiment, referring to FIG. 1B, the first conductive part 190 comprises a first height balancer 192 filled in the first through hole 172, preferably on the second protection layer 17, and the second conductive part 191 comprises a second height balancer 193 on the second protection layer 17. The first height balancer 192 and the second height balancer 193 can be used for adjusting the height of the first conductive part 190 and the height of the second conductive part 191 respectively, such as used for rendering the height of the first conductive part 190 substantially equal to the height of the second conductive part 191, that is, rendering the first height h_1 substantially equal to the second height h_2 .

In another embodiment, the first height balancer 192 of the first conductive part 190 renders the first height h_1 larger

than the second height h_2 . In the case of soldering process, during the process of soldering the light-emitting element **1** and a base, when the surface area of the upper surface of the second conductive part **191** is larger than the surface area of the upper surface of the first conductive part **190**, the adhesion of second conductive part **191** to the base is stronger than the adhesion of the first conductive part **190** to the base since a contact area between the second conductive part **191** and the solder paste is larger. The adhesion difference causes the substrate **10** to warp during the heating process and thus results in a height difference, which further causes the first conductive part **190** to peel from the base. As a result, when the first height h_1 is larger than the second height h_2 , the first height h_1 can reduce the height difference caused by the warp of the substrate **10**, and thus prevent the first conductive part **190** from peeling from the base. Besides, the height difference between the first height h_1 and the second height h_2 can also alleviate a problem of a height difference of the electrodes on the base or a misalignment of the electrodes, and thus further mitigate a problem of the first conductive part **190** peeling from the base, wherein the height difference of the electrodes is caused by the warp of the substrate **10**, the design of the base or the unevenness of the surface, and the misalignment of the electrodes is resulted from a factor related to the manufacturing process, such as vibration or gas flow. Specifically, the first height h_1 is about 1 to 10 μm larger than the second height h_2 .

The substrate **10** is used for supporting the light-emitting semiconductor stack **12** and other layers or structures thereon. The material of the substrate **10** can be transparent material comprising sapphire, diamond, glass, epoxy, quartz, acrylics, Al_2O_3 , GaAs, ZnO or AlN, wherein sapphire and GaAs can be used for growing a light-emitting semiconductor stack.

The light-emitting semiconductor stack **12** can be directly grown on the substrate **10**, or can be fixed on the substrate **10** by a bonding layer (not shown). The material of the light-emitting semiconductor stack **12** can be semiconductor material comprising one or more elements selected from the group consisting of Ga, Al, In, P, N, Zn, Cd, and Se. The electrical polarity of the first semiconductor layer **122** is different from that of the second semiconductor layer **126**. The light-emitting layer **124** emits light having one or more colors and the structure of light-emitting layer **124** can be single heterostructure (SH), double heterostructure (DH), double-side double heterostructure (DDH), multi-quantum well (MQW) or quantum dots.

The first electrodes **121** and the second electrode **123** are used for conducting a current, and the material of the first electrodes **121** and the second electrode **123** is transparent material or metal material, wherein the transparent material comprises indium tin oxide (ITO), indium oxide (InO), tin oxide (SnO), cadmium tin oxide (CTO), antimony tin oxide (ATO), aluminium zinc oxide (AZO), zinc tin oxide (ZTO), zinc oxide (ZnO), gallium doped zinc oxide (GZO), indium zinc oxide (IZO), AlGaAs, GaN, GaP, GaAs, GaAsP, or diamond-like carbon (DLC), and the metal material includes Cu, Sn, Au, Ni, Pt, Al, Ti, Cr, Pb, Cu—Sn, Cu—Zn, Cu—Cd, Sn—Pb—Sb, Sn—Pb—Zn, Ni—Sn, Ni—Co, Au alloy, Au—Cu—Ni—Au or combinations thereof.

The first protection layer **11** and/or the second protection layer **17** are used for electrically insulating the first conductive part **190** and the second conductive part **191** from the reflective layer **13**, and for preventing the reflective layer **13** from a damage caused by the first conductive part **190** and the second conductive part **191**. The first protection layer **11** and/or the second protection layer **17** are used for securing

the reflective layer **13** and improving the mechanical strength of the light-emitting element **1**. The material of the first protection layer **11** and the second protection layer **17** can be an insulating material comprising polyimide (PI), benzocyclobutene (BCB), prefluorocyclobutane (PFCB), MgO, epoxy, Sub, acrylic resin, cyclic olefin polymers (COC), polymethylmethacrylate (PMMA), polyethylene terephthalate (PET), polycarbonate (PC), polyetherimide, fluorocarbon polymer, glass, Al_2O_3 , SiO_x , TiO_2 , SiN_x or spin-on glass.

The reflective layer **13** reflects the light emitted from the light-emitting semiconductor stack **12**. The material of the reflective layer **13** comprises Cu, Al, Sn, Au, Ag, Ti, Ni, Pt, TiW alloy, Ag—Ti, Ni—Sn, Au alloy, Ni—Ag or Ti—Al.

The barrier layer **15** is used for avoiding an ionic diffusion from the reflective layer **13** and/or for enhancing the adhesion between the reflective layer **13** and the second protection layer **17**. The material of the barrier layer **15** comprises Cu, Al, Sn, Au, Ag, Ti, Ni, Pt, TiW alloy, Ag—Ti alloy, Ni—Cr, Ag—Ti, Ni—Sn, Au alloy, Ni—Ag, or Ti—Al.

FIG. 1C is a cross-sectional diagram along the line of B'-B' shown in FIG. 1A in accordance with another embodiment. Referring to FIG. 1C, the laminated layer structures above the substrate **10** of the light-emitting element **1** can comprise similar profiles, for example, each comprises a side face inclined relative to the substrate **10**. Specifically, as shown in FIG. 1C, the extension area **127** comprises an upper face **1270**, a lower face **1272** opposite to the upper face **1270**, a side face **1274** between the upper face **1270** and the lower face **1272**, and an angle θ between the side face **1274** and the lower face **1272**, wherein the angle θ ranges from about 15 degrees to 70 degrees, more preferably, from about 30 degrees to 45 degrees. Compared with an extension area comprising an angle of 90 degrees between the side face and the lower face, the angle θ of the extension area **127** causes the side face **1274** to have a more gentle slope, and therefore the structures formed on the extension area **127** such as the first protection layer **11**, do not have deficiency in structure such as insufficient of thickness, which is resulted from a steep side face, and the deficiency may further result in instability and a lowering yield of a optoelectronic device. Accordingly, the stability of the light-emitting element **1** is improved. The first conductive part **190** and the second conductive part **191** can each have a concave-convex profile. In another embodiment, as shown in FIG. 1D, each upper face of the first conductive part **190** and the second conductive part **191** is flat since the first conductive part **190** and the second conductive part **191** have the first height balancer **192** on the second protection layer **17** and the second height balancer **193** on the second protection layer **17** respectively. Specifically, the first height balancer **192** is in the first through hole **172** and on part of the second protection layer **17**. The second height balancer **193** is on part of the second protection layer **17** and filled in the second through hole **174**.

FIG. 1E is a three dimensional view in accordance with the light-emitting element **1** of the present application shown in FIG. 1A. As shown in FIG. 1E, the second protection layer **17** is on the substrate **10**, and the first conductive part **190** and the second conductive part **191** are on the second protection layer **17**.

FIG. 2A is a top view of a light-emitting element **2** in accordance with another embodiment of the present application, and FIG. 2B is a cross-sectional diagram along the line of C-C' in accordance with the light-emitting element **2** of the present application shown in FIG. 2A. As shown in FIG. 2A, the first electrode **20** of the light-emitting element

2 has multiple contact areas **202**, multiple extension areas **204** and a connecting area **206** connecting the multiple contact areas **202**. The first conductive part **190** is electrically connected to the contact areas **202** of the first electrode **20** by the first through hole **172**, and therefore a current can flow from the first conductive part **190** to the first semiconductor layer **122** through the first electrode **20**, wherein the first semiconductor layer **122** is under the second conductive part **191**. Besides, the second protection layer **17** electrically insulates the first conductive part **190** from the second semiconductor layer **126**. In the present embodiment, the surface area of the upper surface of the first conductive part **190** can be substantially equal to the surface area of the upper surface of the second conductive part **191**. As a result, during a process of soldering the light-emitting element **2** and a base, a peeling problem of the first conductive part **190** or the second conductive part **191** from the base caused by the adhesion difference to the base is avoided, wherein the adhesion difference is caused by the difference in surface area of the upper surface of the first conductive part **190** and the upper surface of the second conductive part **191**. Accordingly, the quality of the soldering process is improved. More preferably, when the surface area of the upper surface of the first conductive part **190** is substantially equal to the surface area of the upper surface of the second conductive part **191**, the height of the first conductive part **190** is substantially equal to the height of the second conductive part **191**, that is, the first height h_1 is substantially equal to the second height h_2 .

In another embodiment, a ratio of the surface area of the upper surface of the first conductive part **190** to the surface area of the upper surface of the second conductive part **191** ranges from about 0.8 to 1.2, more preferably, from about 0.9 to 1.1. In another embodiment, as shown in FIG. 2B, a first width w_1 of the first conductive part **190** is substantially equal to a second width w_2 of the second conductive part **191**. In another embodiment, a ratio of the first width w_1 to the second width w_2 ranges from about 0.8 to 1.2, more preferably, from about 0.9 to 1.1.

Referring to FIG. 2A, the first conductive part **190** does not cover a part of each contact area **202**, so the part of each contact area **202** and/or the second protection layer **17** on the part of each contact area **202** are exposed. Prior to a process of eutectic bonding between the first conductive part **190** and a base, a solder flux is applied on the surface of the first conductive part **190**. After the eutectic bonding, the solder flux residue needs to be cleaned so as to prevent the following packaging process being affected by the solder flux residue. In the present embodiment, the exposed second protection layer **17** is near the edge of the light-emitting element **2**, and thus a solder flux residue remained between the light-emitting element **2** and the base is easy to clean through the exposed second protection layer **17**. Accordingly, the quality of the following packaging process is improved.

FIG. 3 schematically shows a light-generating element **3** of an embodiment of the present application. The light-generating element **3** comprises a light-emitting element of any one of the embodiments as mentioned above. The light-generating element **3** can be a lighting device, such as a street light, a headlight, or an interior lighting, or can be a traffic light or a backlight of a backlight module of a flat panel display. The light-generating element **3** comprises a light source **31** comprising a light-emitting element of any embodiment as mentioned above, a power supply system **32**

used for providing a current to the light source **31**, and a control element used for controlling the power supply system **32**.

FIG. 4 schematically shows a backlight module **4** of an embodiment of the present application. The backlight module **4** comprises a light-generating element **3** as mentioned above and an optical element **41**. The optical element **41** processes the light generated by the light-generating element **3**, such as diffuses the light generated by the light-generating device **3**. The backlight module **4** is applicable to flat panel displays.

FIG. 5 is an exploded view of a light bulb **6** in accordance with one of the embodiments of the present application. The light bulb **6** comprises a lamp **61**, a lens **62** disposed in the lamp **61**, a lighting module **64** disposed under the lens **62**, a lamp holder **65** comprising a heat sink **66**, wherein the lighting module **64** is used for holding the lighting module **64**, a connecting part **67**, and an electrical connector **68**, wherein the connecting part **67** connects the lamp holder **65** to the electrical connector **68**. The lighting module **64** comprises a carrier **63** and multiple light-emitting elements **60** of any one of the embodiments as mentioned above, wherein the multiple light-emitting elements **60** are on the carrier **63**.

The foregoing description of preferred and other embodiments in the present disclosure is not intended to limit or restrict the scope or applicability of the inventive concepts conceived by the Applicant. In exchange for disclosing the inventive concepts contained herein, the Applicant desires all patent rights afforded by the appended claims. Therefore, it is intended that the appended claims include all modifications and alterations to the full extent that they come within the scope of the following claims or the equivalents thereof.

What is claimed is:

1. A light-emitting element, comprising:
 - a substrate comprising:
 - a first side;
 - a second side opposite to the first side; and
 - a third side connecting the first side and the second side;
 - a light-emitting semiconductor stack formed on the substrate and comprising:
 - a first semiconductor layer;
 - a second semiconductor layer; and
 - a light-emitting layer between the first semiconductor layer and the second semiconductor layer;
 - a first electrode formed on the first semiconductor layer, extending from the first side to the second side and comprising a contact area and a first extension area;
 - a second electrode formed on the second semiconductor layer;
 - a protection layer formed on the light-emitting semiconductor stack, comprising a first through hole exposing the first electrode and a second through hole exposing the second electrode;
 - a first conductive part formed on the protection layer and electrically connected to the first electrode through the first through hole; and
 - a second conductive part formed on the protection layer and electrically connected to the second electrode through the second through hole, wherein the second conductive part comprises a projected area on the light-emitting semiconductor stack, the first extension area is located outside the projected area and located between the second conductive part and the third side,

wherein the first conductive part and the second conductive part each comprises a concave-convex profile.

2. The light-emitting element according to claim 1, wherein the first through hole has a first width and the contact area has a second width, and the first width is smaller than the second width.

3. The light-emitting element according to claim 1, wherein the first electrode comprises a side surface, a lower surface, and an angle between the side surface and the lower surface, and wherein the angle ranges from 15 degrees to 70 degrees.

4. The light-emitting element according to claim 1, further comprising a third electrode formed on the first semiconductor layer and electrically connected to the first conductive part, wherein the third electrode is adjacent to the first electrode and comprises a second extension area extending from the first side to the second side, wherein a shortest distance between the second extension area and the first extension area is larger than a shortest distance between the first extension area and the third side.

5. The light-emitting element according to claim 1, wherein a distance between the first conductive part and the second conductive part is equal to or greater than 50 μm.

6. The light-emitting element according to claim 1, wherein the contact area and the first extension area are in contact with the first semiconductor layer.

7. The light-emitting element according to claim 1, wherein a shortest distance between the second through hole and the third side is larger than a shortest distance between the first extension area and the third side.

8. The light-emitting element according to claim 1, wherein a shortest distance between the first electrode and the first side is larger than a shortest distance between the first electrode and the second side.

9. The light-emitting element according to claim 1, wherein the first conductive part covers the first electrode and the second electrode.

10. A backlight module, comprising:

a plurality of light-generating elements, wherein one of the light-generating elements comprising:

- a first side;
- a second side opposite to the first side;
- a third side connecting the first side and the second side;

a light-emitting semiconductor stack;

a first electrode formed on the light-emitting semiconductor stack, extending from the first side to the second side and comprising a first contact area and a first extension area;

a second electrode formed on the light-emitting semiconductor stack and comprising a second contact area;

a protection layer formed on the light-emitting semiconductor stack, comprising a first through hole

exposing the first contact area and a second through hole exposing the second contact area;

a first conductive part formed on the protection layer and electrically connected to the first electrode through the first contact area; and

a second conductive part formed on the protection layer and electrically connected to the second electrode through the second contact area, wherein the second conductive part comprises a projected area on the light-emitting semiconductor stack, the first extension area is located outside the projected area and located between the second conductive part and the third side; and

an optical element processing a light generated by the light-generating elements,

wherein the first conductive part and the second conductive part each comprises a concave-convex profile.

11. The backlight module according to claim 10, wherein the first through hole has a first width and the contact area has a second width, and the first width is larger than the second width.

12. The backlight module according to claim 10, wherein the one of the light-generating elements further comprises a third electrode formed on the light-emitting semiconductor stack and electrically connected to the first conductive part, wherein the third electrode is adjacent to the first electrode and comprises a second extension area extending from the first side to the second side, wherein a shortest distance between the second extension area and the first extension area is larger than a shortest distance between the first extension area and the third side.

13. The backlight module according to claim 10, wherein a distance between the first conductive part and the second conductive part is equal to or greater than 50 μm.

14. The backlight module according to claim 10, wherein a shortest distance between the second through hole and the third side is larger than a shortest distance between the first extension area and the third side.

15. The backlight module according to claim 10, wherein a shortest distance between the first electrode and the first side is larger than a shortest distance between the first electrode and the second side.

16. The backlight module according to claim 10, wherein the first conductive part covers the first electrode and the second electrode.

17. The backlight module according to claim 10, wherein the optical element diffuses the light generated by the light-generating elements.

18. The backlight module according to claim 10, further comprising a carrier, wherein the light-generating elements are formed on the carrier.

* * * * *