

(43) International Publication Date
12 March 2015 (12.03.2015)

- (51) International Patent Classification:
H01S 3/067 (2006.01) H01S 3/09 (2006.01)
- (21) International Application Number:
PCT/EP2014/069222
- (22) International Filing Date:
9 September 2014 (09.09.2014)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
13306235.6 9 September 2013 (09.09.2013) EP
- (71) Applicant: **ECOLE POLYTECHNIQUE** [FR/FR];
Route de Saclay, F-91128 PALAISEAU Cedex (FR).
- (72) Inventors: **TAJIMA, Toshiki**; 26741 street Portola Park-
way 136, Foothill Ranch, California 92610 (US). **MOUR-
OU, Gérard**; 25 avenue Reille, F-75014 Paris (FR). **NA-
KAJIMA, Kazuhisa**; 3-1-115 Azuma, Tsukuba, Ibaraki
305-0031 (JP).
- (74) Agent: **MILON, Marie-Anne**; 90333, B, Technopôle
Atalante, 16B rue de Jouanet, F-35703 Rennes Cedex 7
(FR).
- (81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments (Rule 48.2(h))

(54) Title: FREE-ELECTRON LASER DRIVEN BY A FIBRE-BASED LASER FEEDING A LASER PLASMA ACCELERATOR




Fig.1

(57) Abstract: The invention concerns a Free Electron Laser-FEL-EUV or Soft-X-Ray light source emitting between 5nm and 15nm comprising : a fiber-based laser (1), encompassing a plurality of amplifying fibres wherein an initial laser pulse is distributed and amplified, and means for grouping together the elementary pulses amplified in the said fibre in order to form an a single amplified global laser pulse (3); a laser plasma accelerator (6) wherein the said global laser pulse (3) generates relativistic electron beams (10), a beam focusing system (12) transporting electron beams (10) from the laser plasma accelerator, an undulator (13) wherein relativistic electron beams (10) generate an electromagnetic beams, and a beam separator system, wherein the said electron beam and the said electromagnetic beam are separated.

FREE-ELECTRON LASER DRIVEN BY A FIBRE-BASED LASER FEEDING A LASER PLASMA
ACCELERATOR

1. Field of the invention

The invention relates to a new embodiment of a Free-Electron Laser ("FEL").

The invention also relates to the use of such a Free-Electron Laser as an Extreme UltraViolet ("EUV") light sources for Extreme UltraViolet lithography.

2. Background of the invention

Background of Free-Electron Lasers ("FEL")

A Free-Electron laser (FEL), is a type of laser that use a relativistic electron beam that moves freely through a magnetic structure, in order to create a beam consisting of coherent electromagnetic radiation that can reach high power. In this type of laser, the free electron beam is the lasing medium. The free-electron laser has the widest frequency range of any laser type, and can be widely tunable, currently ranging in wavelength from microwaves, through terahertz radiation and infrared, to the visible spectrum, ultraviolet, and X-ray.

To create a Free-Electron Laser, a beam of electrons is accelerated to almost the speed of light. The beam passes through the Free-Electron Laser oscillator, a periodic transverse magnetic field produced by an arrangement of magnets with alternating poles within an optical cavity along the beam path. This array of magnets is commonly configured as an undulator, because it forces the electrons in the beam to follow a sinusoidal path. The acceleration of the electrons along this path results in the release of photons (synchrotron radiation). Since the electron motion is in phase with the field of the light already emitted, the fields add together coherently. The wavelength of the light emitted can be readily tuned by adjusting the energy of the electron beam or the magnetic field strength of the undulators.

A free-electron laser requires the use of an electron accelerator, which is very voluminous, requires a high voltage supply, has a very low repetition rate and is expensive.

Background of Extreme Ultraviolet ("EUV") light sources

Extreme UltraViolet ("EUV") with wavelengths below about 50 nm and more specifically around and below 13.5 nm can be used in microlithography processes to enhance the resolution of optical systems that are limited by the diffraction limit of light accompanying miniaturization of semiconductor integrated circuits. This technology called as extreme ultraviolet lithography (EUVL) is capable of providing resolution below 30 nm that had been impossible with conventional optical lithography that utilizes deep ultraviolet (DUV) light sources with wavelengths of 248 nm or 193 nm.

The current technologies for generating high power Extreme UltraViolet radiation at 13.5 nm, referred to as laser produced plasma (LPP), employs the deposition of laser energy into a source element, such as xenon (Xe), tin (Sn) or lithium (Li), creating ionized gas

microplasma at electron temperatures of several tens of electron volts. As these highly excited ions decay, energetic radiation is emitted in all directions of 4π radians.

One particular laser produced plasma (LPP) technique involves irradiating molten tin droplets with one or more pre-pulse(s) followed by a main pulse. In this regard, CO₂ lasers at the wavelength of 10.6 μm provide certain advantages as a drive laser producing main pulses in the laser produced plasma (LPP) process thanks to the ability to produce a relatively high conversion efficiency, i.e., the ratio of output Extreme UltraViolet in-band to drive laser input power.

For Extreme UltraViolet lithography, the 13.5 nm radiation is collected by a mirror (either grazing incidence or normal incidence) and focused to an intermediate focal point where it is relayed to the scanner optics and, ultimately, the wafer.

For example, one apparatus currently being developed with the goal of producing about 100 W at the intermediate location contemplates the use of a pulsed, focused 10 – 12 kW CO₂ drive laser which is synchronized with a droplet generator to sequentially irradiate about 40 k – 100 k tin droplets per second. For this purpose, there is a need to produce a stable stream of droplets at a relatively high repetition rate (e.g. 40 – 100 kHz or more) and deliver the droplets to an irradiation site with high accuracy and good repeatability in terms of timing and position, i.e., with very small jitter, over a relatively long period of time.

The current laser produced plasma (LPP) radiation sources have a serious obstacle on the way to a high volume manufacturing (HVM) source such as small efficiency of the radiation source, a limited set of discrete wavelengths and the mitigation of the plasma debris required for the protection of Extreme UltraViolet optics.

Background of Free Electron Laser used as Extreme UltraViolet light sources

Free-Electron Laser based radiation sources have evident advantages in wavelength tunability, high efficiency and high output power, compared to current laser produced plasma (LPP) radiation sources. The problem of debris mitigation does not exist at all. There is no need to use a multilayer coated reflective collector, of which reflectivity is limited to about 70%, since the radiation is produced in the diffraction limited volume. Hence, there is no problem with the transport of radiation to the exposure system. Harnessing such advantages of Free-Electron Laser based Extreme UltraViolet radiation sources liberated from the debris mitigation and a mechanical targeting system such as a droplet generator, the Free-Electron Laser based Extreme UltraViolet radiation source may have an average output power of 0.5 kW at a repetition rate of at least 250 kHz for meeting the requirements of the light source at 13.5 nm for the next generation lithography.

A proposed Free-Electron Laser based Free-Electron Laser producing a kW-level average output power of Extreme UltraViolet radiation utilizes high-energy electron beams of the order of 1 GeV generated from a radio-frequency (RF)-based linear accelerator that

comprises a high-brightness electron injector typically composed of a photocathode RF gun or thermionic high-voltage DC gun and several buncher cavities for producing electron bunches, a several-stage magnetic bunch compressor system comprising a sequence of RF structure and bending magnets for compressing a bunch length and increasing a peak beam current and a main linac composed of a series of room-temperature or superconducting RF cavities with the accelerating gradient of the order of 10 MV/m and a beam transport system including beam focusing and defocusing electro-quadrupole magnets, lastly followed by undulators with a total length of 30 m, providing alternating magnetic fields to force electrons on a sinusoidal trajectory so that all electrons in a electron bunch emit coherently due to the microbunching process, called as self-amplified spontaneous emission (SASE) Free-Electron Laser. The overall size of a RF linac-driven Free-Electron Laser-based Extreme UltraViolet light source may require a 250 m long facility for a linac-based light source or a 120 m long, 60 m wide area for a recirculator-based light source. The costs for construction and operation of such facility may turn out incredibly so large as to prevent the Free-Electron Laser-based Extreme UltraViolet light sources from industrial realization of the next generation lithography technology.

3. Objective of the invention

The objective of the present invention is to overcome the cited disadvantages of the prior art.

More specifically, an objective of the invention is to provide a new embodiment of Free Electron Laser, more compact and efficient, cheaper and having a higher repetition rate and a higher average power as the prior art Free Electron Lasers.

Another objective of the invention is to provide an efficient Free-Electron Laser-based Extreme UltraViolet light source, usable for industrial lithography technology.

4. Summary of the invention

In order to attain these objectives the present invention provides

A Free Electron Laser source generating an electromagnetic beam presenting a wavelength, called Free Electron Laser wavelength, belonging to the range from 5nm to 15nm, said Free Electron Laser comprising:

a fiber-based laser, comprising a plurality of amplifying fibres wherein an initial laser pulse is distributed and amplified, and means for grouping together the elementary pulses amplified in the said fibre in order to form an a single amplified global laser pulse, and comprising a stretching device able to stretch out in time said initial laser pulse, according to the chirped pulse amplification technique and a grating pulse compressor able to compress in time the said single amplified global laser pulse, according to the chirped pulse amplification technique,

said fiber-laser being tuned using at least one parameter, called fiber-based laser parameter, said at least one fiber-based laser parameter being obtained as a function of

said Free Electron Laser wavelength;

- a laser plasma accelerator wherein, in a bubble regime of said plasma accelerator said global laser pulse generates relativistic electron beams,

said laser plasma accelerator being tuned using at least one parameter, called laser plasma accelerator parameter, said at least one laser plasma accelerator parameter being obtained as a function of said Free Electron Laser wavelength;

- a beam focusing system transporting electron beams from the laser plasma accelerator to an undulator;

- said undulator wherein relativistic electron beams generate an electromagnetic beam, a peak magnetic field and a period of said undulator being previously set,

said undulator being tuned using at least one parameter, called undulator parameter, said at least one undulator parameter being obtained as a function of said Free Electron Laser wavelength;

- a beam separator system, wherein the said electron beam and the said electromagnetic beam are separated.

Thanks to the particular combination of the elements constituting said Free Electron Laser, the Free Electron Laser source, or Free Electron Laser, according to the invention is more compact and efficient, cheaper and has a higher repetition rate and a higher average power as the prior art Free Electron Laser sources.

Such a result can only be obtained because of the particular tuning technique implemented according to the present invention. Indeed, as detailed in the following section 6.5 the tuning of the components of said Free Electron Laser is optimised since at least one parameter of the fiber-based laser (e.g. the average fiber laser power, the required pulse duration, the match spot radius, the peak power, laser energy pulse, etc.), at least one parameter of the laser plasma accelerator (e.g. the electron beam energy, the plasma density, the accelerator length, etc.), and at least one parameter of the undulator (e.g. the Pierce Parameter, the saturation length, the total number of periods, etc.) are all tuned as a function of the Free Electron Laser wavelength, when the peak magnetic field and the period of the undulator have been previously set.

Thus, all the essential components of the Free Electron Laser are tuned in synergy as a function of a same parameter, which corresponds to the Free Electron Laser wavelength. Such a relation between all the major parameters of the FEL is not trivial and requires an inventive step.

Such a synergy between the components constituting said Free Electron Laser is neither disclose nor suggest by the prior art, which does not give any concrete solution for designing and implementing a Free Electron Laser whose wavelength belongs to the range from 5nm to 15nm.

Indeed, considering the disclosure of Wiggins S. M. and al. ("*High Quality electron beams from a laser wakefield accelerator*", Conference on Lasers and Electro-Optics (CLEO) and Quantum Electronics and Laser science Conference (QELS), 2010 pages 1-2 XP031701440), only a classical Laser-Plasma Accelerators towards X-rays combined with a classical undulator are disclosed. Such elements are designed to create an ALPHA-XLWFA line, which could be used for a FEL operation. It has to be noted that such a document discloses only beam transport simulations to illustrate how an FEL laser operating in the VUV using current 100-150MeV electron Beams can be implemented, and disclose only that a compact x-ray FEL should be possible by scaling the LWFA to the gigaelectronvolt range without disclosing any solution to achieve it. Thus, it can be noticed that no full and effective implementation of a FEL with a wavelength range from 5nm to 15nm is disclosed by Wiggins S. M, which underlines that, at the time of the publication of this document, proposing such an effective implementation is tricky and not trivial.

In addition, Wiggins S. M. does not disclose that at least one parameter of the laser plasma accelerator, and at least one parameter of the undulator, are obtained as a function of said Free Electron Laser wavelength.

Even if the one skilled in the art would replace the laser disclosed by Wiggins S. M. by the one disclosed by Tajima T ("*ICAN: The next Laser Powerhouse*", Optics and Photonics news, & May 2013, pages 36-43 XP0055101291), he would not obtain a FEL according to the present invention.

Indeed, the laser disclosed by Tajima, which uses optical fibers (as the one according to the present invention), is not designed such that its major parameters depend all on the Free Electron Laser wavelength. Indeed, no FEL is disclosed by Tajima, who discloses only a use of such fiber-based laser to treat nuclear waste.

Thus the combination of the Alpha-XLWFA beam line of Wiggins S. M. on the one hand with the laser disclosed by Tajima on the other hand would not lead to an effective and usable FEL with a wavelength ranging from 5nm to 15nm, since the laser plasma accelerator and the undulator of Wiggins are tuned for delivering 70-150MeV electron beams, independently from the laser disclosed by Tajima dedicated to treat nuclear waste.

Such a combination can not simply work since a laser able to deliver a gigaelectronvolt is not adapted to be combined with laser plasma accelerator and the undulator of Wiggins tuned for delivering 70-150MeV. Indeed, combining these elements is a tricky issue and no solution about a workable combination is disclosed or suggested.

Thus, such combination of prior art documents can not lead to achieve a concrete and efficient implementation of a FEL with a wavelength ranging from 5nm to 15nm.

Thanks to the particular tuning in synergy of all the elements constituting the FEL according to the invention, concrete compact and efficient FELs are designed (see Table 1 and

Table 2 in the following), which make them usable for industrial lithography. Thus, a great achievement is obtained regarding the prior art, which was aiming to obtain one day such an efficient FEL.

Furthermore, using this chirped pulse amplification technique (CPA), the fiber-based laser can emit pulses of very high energy.

Preferably, said laser plasma accelerator comprises:

- a first gas cell filled with mixed gas, and
- a second gas cell filled with pure helium gas.
- a gas feeding system.

Such a laser plasma accelerator is very efficient, with a very high repetition rate.

Preferably, said laser plasma accelerator comprise means for modifying the length of the said second gas cell.

The wavelength of the electromagnetic beam emitted by the Free Electron Laser source can then be tuned.

Preferably said beam separator system comprises a dipole magnet for bending electron beams and a beam dump.

It has to be noticed that as detailed later the permanent magnet dipole length required for deflecting depends on the electron beam energy E_b , which depends itself on the FEL wavelength as detailed in section 6.5.

Advantageously, said electromagnetic beam is a Extreme UltraViolet beam.

The Free Electron Laser according to this embodiment can provide a Extreme UltraViolet source usable for lithography application. Such a Extreme UltraViolet source is more compact and efficient, cheaper and having a higher repetition rate and a higher average power as the prior art Extreme UltraViolet sources.

According to a preferred embodiment, said Extreme UltraViolet beam wavelength is 13.5 nm.

According to an other possible embodiment, said Extreme UltraViolet beam wavelength is 6.7 nm.

5. Brief description of the drawings

The invention will become more fully understood from the following description of preferred but non-limiting embodiments thereof, described in connection with accompanying drawings, wherein:

- Fig.1 shows a schematic diagram of a Free Electron Laser according to an embodiment of the invention, usable as an Extreme UltraViolet light source.
- Fig. 2 illustrates a schematic diagram of a coherent combining fiber-based drive laser used in the Free Electron Laser of Fig. 1.

- Fig. 3 shows the two-stage gas cell plasma accelerator of the Free Electron Laser of Fig. 1.
- Fig. 4 shows the laser plasma electron accelerator system of the Free Electron Laser of Fig. 1, comprising the gas cell plasma accelerator of Fig. 3.
- 5 - Fig. 5 illustrates schematically electron acceleration mechanism due to laser wakefield.
- Fig. 6 shows a schematic view of a miniature permanent magnet quadrupole (PMQ).
- Fig. 7 shows an example of a beam focusing system comprising four permanent magnet quadrupoles (PMQ) of the type represented by Fig 6.
- Fig. 8 shows schematically a planar undulator made of pure permanent magnets
10 producing a vertical field.
- Fig. 9 shows schematically a hybrid planar undulator made of permanent magnets and ferromagnetic material, e.g., iron or cobalt steel.
- Fig. 10A and 10B show a schematic assembly of the undulator used in the Free Electron Laser of Fig. 1.
- 15 - Fig. 11A, 11B and 11C shows a monolithic beam dump system comprising a permanent magnet dipole separating electron beams from Extreme UltraViolet radiation and a electron beam dump.
- Fig. 12 illustrates a setup of a compact self-amplified spontaneous emission (SASE) Free-Electron Laser system comprising the beam focusing system of Fig. 4, the compact
20 undulator of Fig. 5 and the beam dump system of Fig. 6.
- Fig. 13 illustrates schematically the Extreme UltraViolet light source of Fig. 1, based on a compact Free-Electron Laser driven by a fiber laser-based plasma accelerator according to aspects of an embodiment of the present invention,
- Fig. 14 illustrates how the parameters of each component constituting the Free-Electron
25 Laser of Fig. 1, are obtained as a function of the Free-Electron Laser wavelength according to aspects of an embodiment of the present invention

6. Detailed description of the preferred embodiments of the invention

6.1 General description of a Free-Electron Laser according to an embodiment of the invention

30 With initial reference to Fig. 1, there is shown a schematic diagram of a proposed Free-Electron Laser according to one aspect of an embodiment. As shown in Fig. 1, and described in further detailed below, the proposed Free-Electron Laser may include a drive laser system 1 for generating high energy laser pulses at a high repetition rate of the order of 1 MHz and delivering intense laser pulses 3 compressed through a pulse compressor chamber 2 into a laser
35 plasma accelerator chamber 4. Such a laser-driven Free-Electron Laser can be used as an Extreme UltraViolet light source.

Fibre-type laser

Figure 2 shows an item of drive laser system 1 for producing high-energy laser pulses.

In this drive laser system 1, a low-energy laser pulse 810 is produced by an oscillator 81. This pulse 810 is then stretched out in time, according to the chirped pulse amplification (CPA) technique, by a stretching device 82, comprising a pair of diffraction gratings 821 and 822, having the effect of offsetting in time the various spectral components of the original low-energy pulse 810. The stretched pulse 820 then has a lower peak power and a longer duration of the pulse 810.

This laser pulse 820 is then distributed in a plurality of amplifying fibres 831 forming a first amplifying stage 83 of the fibre-type laser amplifier. The various fibres are separated from one another so as to make it possible to cool them effectively. Each of the amplifying fibres 831 comprises a core made from doped material, and is optically pumped, so as to optically amplify the laser pulse flowing in the fibre. The pulse passing through each of these amplifying fibres 831 is then amplified, and is then itself distributed in a plurality of amplifying fibres 841 forming the second amplification stage 84 of the fibre-type laser amplifier. Once again, the pulse passing through each of these amplifying fibres 841 is amplified and is then itself distributed in a plurality of amplifying fibres 851 forming the third amplification stage 85 of the fibre-type laser amplifier. Thus, in each amplification stage, the pulse is amplified in a plurality of fibres independent of one another and then divided so that pulses of lower power are transmitted to each of the higher-level amplification fibres.

The third and last amplification stage 85 then comprises a very large number of amplifying fibres, for example around 10^6 . Each of the amplifying fibres of this third stage is extended by a transmission fibre having a very low loss level. The transmission fibres are collected together in a cluster 86 so that the pulses emerging from each of the ends of these transmission fibres are emitted in parallel and juxtaposed. These pulses then form a single amplified global pulse 860.

This amplified global pulse 860 is compressed timewise by a compressor 87, located in the pulse compressor chamber 2. This compressor 87 comprises a pair of diffraction gratings 871 and 872, grouping together in time the various spectral components of the pulse. The pulse 3 emerging from this temporal compressor 17 then has a very high energy and very short duration.

Two stages gas cell plasma accelerator with ionization-induced injection

As shown in Fig. 1, the ultrashort intense laser pulse 3 is focused by an off-axis parabolic mirror 5 on the entrance of a two-stage gas cell 6, of which the first cell referred to an injector is filled with a mixed gas, e.g., helium gas mixed with nitrogen, and the second cell referred to as an accelerator is filled with a pure gas, e.g., hydrogen or helium. The gases are fed through a gas flow control system 7 to the two-stage gas cell separately at the different pressures.

As described below, in the injector of the gas cell 6, the said laser pulse 3 excites large-amplitude plasma wakefields, of which an accelerating electric field can trap plasma electrons exclusively out of the inner shell electrons and accelerate them owing to ionization-induced injection. A pre-accelerated electron beam 10 from the injector is further accelerated to the relativistic energy of the order of 1 GeV in the accelerator stage of the gas cell 6, where the laser pulse generates plasma wakefields of the order of 1 GV/cm. A transmitted laser light is directed through a mirror with a beam hole 8 to a recovery box 9 that includes diagnostics and absorbers of the transmitted laser pulses.

This plasma accelerator is particularly advantageous when it is combined with a fiber-based laser, a beam focusing system, an undulator and a beam separator system according to the invention. However, such a laser plasma accelerator comprising a first gas cell filled with mixed gas, and a second gas cell filled with pure helium gas can also be combined with an other type of laser, for producing relativistic electron beams.

Beam focusing system, undulator and separation chamber

The output electron beam 10 from the laser plasma accelerator chamber 4 is transported into an undulator 13 through a beam focusing system 12, installed in a radiation chamber 11. As described below, the electron beam 10 focused by quadrupole magnetic field of the beam focusing system 12 generates the resonantly amplified Extreme UltraViolet radiation 14 due to self-amplified spontaneous emission (SASE) mechanism when passing through the alternating dipole magnetic fields of the undulator 13 that force the electron bunch on a sinusoidal trajectory.

After passing through the undulator 13, the electron bunch is decelerated so strongly that it becomes non-resonant and could not contribute to the amplification of the Extreme UltraViolet radiation, i.e., the onset of saturation. The decelerated electron beam 10 is separated from the Extreme UltraViolet radiation 14 in the dipole magnetic field of the deflection magnet 16 and dumped to a beam dump 17, while the saturated Extreme UltraViolet radiation 14 is extracted from a beam separation chamber 15 and directed to a Extreme UltraViolet lithography scanner/stepper.

6.2. Detailed description of the laser plasma accelerator chamber

Two-stage gas cell

Fig. 3 shows schematically a two-stage gas cell 6 comprising an injector stage 21 and an accelerator stage 24 for efficient electron trapping and acceleration in laser wakefields. As shown in Fig. 4, the two-stage gas cell is set up in a laser plasma accelerator chamber 4 and a compressed laser pulse 3 from the pulse compressor chamber 2 is focused on the entrance of the injector gas cell by an off-axis parabolic mirror 5 with a F-number, e.g., 20.

The injector cell 21 is filled with a mixed gas, e.g., 98% He and 2% N₂, fed through a gas feedthrough 20 from the gas flow control system 7. The accelerator cell 24 is filled with a

pure gas, e.g. H₂ or He, fed through a gas feedthrough 24 from the gas flow control system 7. A length of the accelerator stage is variably adjusted with a bellows structure 25 driven by a motorized actuator 26. Such an adjustment can permit to reuse easily the accelerator stage, using said motorized actuator 26, for different Free-Electron laser wavelengths ranging from 5nm to 15nm. The laser plasma accelerator chamber 4 is pump out by a vacuum pump system 27 to keep an inside pressure of 10^{-3} - 10^{-4} Pa.

Description of the physical process

Fig. 5 illustrates schematically a physical process 100 for the wakefield excitation and electron trapping and acceleration in wakefields, which are generated when an intense laser pulse propagates a neutral mixed gas in the injector 21. In Fig. 5, the evolution of plasma electron density is shown in the upper plot 101 and the excited longitudinal wakefield is shown in the lower plot 102.

As shown in the central part 100 of Fig.5, He and the outer shell electrons up to N⁵⁺ are fully ionized in the leading front of the laser pulse with intensity 1.5×10^{16} W/cm² to produce plasma electrons in the outer region of the laser pulse, of which the boundary is indicated by a thin dotted line 103. Since two inner shell (K-shell) electrons of N⁶⁺ and N⁷⁺ are ionized at the laser intensity higher than 1×10^{19} W/cm², the inner shell electrons are produced only near the peak intensity of the laser pulse 3, of which the intensity profile is indicated by a thick dotted line 108 for the normalized laser field $a_0 = 0.855 \times 10^{-9} I^{1/2} [\text{W/cm}^2] \lambda_L [\mu\text{m}] = 2$ where $I [\text{W/cm}^2]$ is the intensity and $\lambda_L [\mu\text{m}]$ is the laser wavelength. In the upper plot 101, a thick solid curve 109 indicates the evolution of ionization level of nitrogen (the electron number of ionized nitrogen atom) along the propagation axis. A boundary of the plasma region containing the inner shell electrons from ionized N⁶⁺ and N⁷⁺ is indicated by a thin dashed line 104.

Plasma electrons contained in the boundary 103 are blown out by radiation pressure (ponderomotive force) of the laser pulse 3 with the relativistic intensity $a_0 \gg 1$ and form a narrow dense electron sheath surrounding a spherical ion column behind the laser pulse, often referred to as a bubble 105. Such charge separation generates a strong longitudinal electric field 110 of the order of 100 GV/m at a plasma electron density of 10^{18} cm⁻³, which is three orders of magnitude higher than an accelerating field of conventional RF accelerators. In the bubble 105, an electron undergoes a strong focusing force simultaneously. Hence, once electrons 10 are trapped into a bubble, they are efficiently accelerated up to high energy of the order of 1 GeV over a dephasing length of the order of 1 cm, where accelerated electrons outrun a proper accelerating phase.

The said inner shell electrons from ionized N⁶⁺ and N⁷⁺ are located near the bubble center on the propagation axis, where the wake potential is a maximum and the expelling ponderomotive force of the laser pulse is a minimum. Contrary to pre-ionized free electrons,

whose trajectories move along a narrow sheath outside the bubble, the ionized electrons emitted from the inner shell move close to the bubble axis toward the back of the bubble where the wake potential is a minimum, and eventually trapped into the wakefield in condition that electrons gain a sufficient kinetic energy required for trapping, as shown in the electron trajectory 106, while the electron shown in the trajectory 107, ionized earlier and off-axis, slips over the potential well and is not trapped. This mechanism called as ionization-induced injection occurs at the intensity as low as the optical field ionization threshold for the inner shell electrons of impurity gas and significantly increases the trapped charge. As trapping occurs close to the bubble axis, amplitudes of the betatron oscillation after trapping decrease compared to the self-injection from the electron sheath. According to theoretical considerations on the ionization-induced injection, for trapping electrons ionized at the peak of the laser electric field, the minimum laser intensity is given by $1 - \gamma_p^{-1} \leq 0.64 a_0^2$, where γ_p is the Lorentz factor defined as $\gamma_p = (1 - \beta_p^2)^{-1/2}$ and β_p is the phase velocity of the plasma wave. For electrons to be trapped at or in front of the laser envelope, the intensity must be $a_0 \geq 1.7$ for $\gamma_p = 33$. The 1D PIC simulations show that the maximum number of trapped electrons is saturated to be approximately $N_{e\max} \sim 5 \times 10^6 \mu\text{m}^{-2}$ at the mixed gas length $L_{\text{mix}} \approx 1000 \lambda_0$ for the plasma density $n_e = 0.001 n_c$ ($1.7 \times 10^{18} \text{ cm}^{-3}$) with the nitrogen concentration of $\alpha_N = 1\%$, and the laser parameters $a_0 = 2$ and $c\tau_0 \approx 15 \lambda_0$ due to the beam loading effects and initially trapped particle loss from the separatrix in the phase space, where λ_0 is the laser wavelength and n_c is the critical plasma density defined as $n_c = m_e \omega_L^2 / 4\pi e^2 = \pi / (r_e \lambda_L^2) = 1.115 \times 10^{21} [\text{cm}^{-3}] / (\lambda_L [\mu\text{m}])^2$. The number of trapped electrons scales as $N_e [\mu\text{m}^{-2}] \sim 8 \times 10^7 \alpha_N k_p L_{\text{mix}} (n_e / n_c)^{1/2}$ for $\alpha_N k_p L_{\text{mix}} \leq 2$. The energy spread is also proportional to both the mixed gas length and the nitrogen concentration. According to the 2D-PIC simulation for $a_0 = 2$, the energy spread of a trapped electron beam may scale as $\delta E / E = 0.02 [\%] (L_{\text{mix}} / \lambda_L) (n_e / 10^{17} \text{ cm}^{-3})^{-1/2}$, while the transverse normalized emittance is estimated to be $\varepsilon_{n0} \approx 0.5 [\mu\text{m}] a_0^{1/2} (n_e / 10^{17} [\text{cm}^{-3}])^{-1/2}$.

In the bubble (blowout) regime for $a_0 \geq 2$, since an electron-evacuated cavity shape is determined by balancing the Lorentz force of the ion sphere exerted on the electron sheath with the ponderomotive force of the laser pulse, the bubble radius R_b is approximately given as $k_p R_b \approx 2\sqrt{a_0}$, where $k_p = (4\pi r_e n_e)^{1/2}$ is the plasma wavenumber evaluated with the unperturbed on-axis density n_e , and the classical electron radius $r_e = e^2 / m_e c^2 = 2.818 \times 10^{-13} \text{ cm}$ with electron charge e , mass m_e and vacuum light velocity c . The accelerating field E_z is given

by $E_z / E_0 = (1/2)\alpha k_p R_B$, where $E_0 = mc\omega_p / e \approx 96[\text{GV/m}](n_e / 10^{18}[\text{cm}^{-3}])^{1/2}$ and α represents a factor taking into account the beam loading and the difference between the simulation and theoretical estimation. The maximum energy gain limited due to dephasing is given by

$$\Delta\gamma_{\max} = W_{\max} / m_e c^2 \approx (2/3)\alpha\kappa_{\text{self}} a_0 (n_c / n_e),$$

5 where $\kappa_{\text{self}} = (a_0^2 / 8) \{ (1 + a_0^2 / 2)^{1/2} - 1 - \ln[(1 + a_0^2 / 2)^{1/2} + 1] / 2 \}^{-1}$ is a correction factor of the group velocity for a self-guided relativistic laser pulse, of which the relativistic factor related to the group velocity $\beta_g = v_g / c$ is given by $\gamma_g^2 = 1 / (1 - \beta_g^2) \approx \kappa_{\text{self}} (\omega_L^2 / \omega_p^2) = \kappa_{\text{self}} (n_c / n_e) = \kappa_{\text{ch}} \gamma_{g0}^2$, where $\gamma_{g0} = \omega_L / \omega_p$ is the relativistic factor for the linear group velocity for $a_0^2 \ll 1$. The dephasing length L_{dp} for self-guided bubble regime is given by $k_p L_{\text{dp}} \approx (2/3)k_p R_B \gamma_g^2$
 10 $= (4/3)\sqrt{a_0} \kappa_{\text{self}} (n_c / n_e)$. The important parameters of a laser plasma accelerator for reaching a given energy E_b are summarized as follows:

The operating plasma density is determined by

$$n_e = \frac{2}{3} \alpha \kappa_{\text{self}} a_0 \frac{n_c}{\Delta\gamma_{\max}} \approx 1.9 \times 10^{18} [\text{cm}^{-3}] \kappa_{\text{self}} a_0 \left(\frac{1 \mu\text{m}}{\lambda_L} \right)^2 \left(\frac{200 \text{MeV}}{E_b / \alpha} \right).$$

The accelerator length is set to be equal to the dephasing length as

$$15 \quad L_{\text{acc}} = L_{\text{dp}} \approx \sqrt{\frac{3}{2}} \frac{(\Delta\gamma_{\max} / \alpha)^{3/2}}{\pi \kappa_{\text{self}}^{1/2} a_0} \lambda_L \approx \frac{3.1 [\text{mm}]}{\kappa_{\text{self}}^{1/2} a_0} \left(\frac{\lambda_L}{1 \mu\text{m}} \right) \left(\frac{E_b / \alpha}{200 \text{MeV}} \right)^{3/2}$$

The pump depletion length due to pulse front erosion becomes

$$L_{\text{pd}} \approx c \tau_L \frac{n_c}{n_e} = \frac{3}{2} \frac{c \tau_L \Delta\gamma_{\max} / \alpha}{\kappa_{\text{self}} a_0} \approx \frac{5 [\text{mm}]}{\kappa_{\text{self}} a_0} \left(\frac{\tau_L}{30 \text{fs}} \right) \left(\frac{E_b / \alpha}{200 \text{MeV}} \right)$$

The pulse duration required for satisfying a dephasing length longer than a pump depletion length is

$$20 \quad \tau_L \geq 18 [\text{fs}] \kappa_{\text{self}}^{1/2} \left(\frac{\lambda_L}{1 \mu\text{m}} \right) \left(\frac{E_b / \alpha}{200 \text{MeV}} \right)^{1/2}$$

The matched spot radius is given by

$$r_m \approx 3.9 [\mu\text{m}] \frac{R_m}{\sqrt{\kappa_{\text{self}} a_0}} \left(\frac{\lambda_L}{1 \mu\text{m}} \right) \left(\frac{E_b / \alpha}{200 \text{MeV}} \right)^{1/2}$$

where

$$R_m = k_p r_m = \left\{ \frac{\ln(1 + a_0^2 / 2)}{\sqrt{1 + a_0^2 / 2} - 1 - 2 \ln[(\sqrt{1 + a_0^2 / 2} + 1) / 2]} \right\}^{1/2}$$

25 The corresponding matched power is

$$P_L = \frac{k_p^2 r_m^2 a_0^2}{32} P_c \approx 0.312 [\text{TW}] \frac{a_0 R_m^2}{\kappa_{\text{self}}} \left(\frac{E_b / \alpha}{200 \text{MeV}} \right)$$

The required laser pulse energy is given by $U_L = P_L \tau_L$.

Assuming the beam loading efficiency $\eta_b \equiv 1 - E_z^2 / E_M^2$ defined by the fraction of the plasma wave energy absorbed by particles of the bunch with the root mean square (r.m.s) radius σ_b , the beam-loaded field is given by $E_z = \sqrt{1 - \eta_b} E_M = \alpha E_M$, where E_M is an accelerating field without beam loading. Thus a loaded charge is calculated as

$$Q_b \approx \frac{e}{4k_L r_e} \frac{\eta_b k_p^2 \sigma_b^2}{(1 - \eta_b)} \frac{E_z}{E_0} \left(\frac{n_c}{n_e} \right)^{1/2} \approx 76 [\text{pC}] \frac{\eta_b k_p^2 \sigma_b^2}{(1 - \eta_b)} \frac{E_z}{E_0} \left(\frac{n_e}{10^{18} [\text{cm}^{-3}]} \right)^{-1/2}.$$

Using the plasma density n_e , the loaded charge is given by

$$Q_b \approx 55 [\text{pC}] \frac{\eta_b k_p^2 \sigma_b^2}{\kappa_{\text{self}}^{1/2} \sqrt{1 - \eta_b}} \left(\frac{\lambda_L}{1 \mu\text{m}} \right) \left(\frac{E_b / \alpha}{200 \text{ MeV}} \right)^{1/2} \approx 55 [\text{pC}] \frac{1 - \alpha^2}{\alpha^{3/2}} \frac{k_p^2 \sigma_b^2}{\kappa_{\text{self}}^{1/2}} \left(\frac{\lambda_L}{1 \mu\text{m}} \right) \left(\frac{E_b}{200 \text{ MeV}} \right)^{1/2}.$$

A field reduction factor α for accelerating a charge of electrons Q_b up to an energy

$$E_b \quad \text{is obtained from} \quad \alpha^2 + C \alpha^{3/2} - 1 = 0, \quad \text{where} \\ C \equiv (Q_b / 55 \text{ pC}) \kappa_{\text{self}}^{1/2} (k_p^2 \sigma_b^2)^{-1} (1 \mu\text{m} / \lambda_L)^{-1} (E_b / 200 \text{ MeV})^{-1/2}.$$

6.3. Detailed description of the Beam focusing system, undulator and beam separator

Beam focusing system

Beam transport and imaging from the laser plasma accelerator 6 to the undulator 13 is provided by a beam focusing system 12 with short focal length. The field gradient of the two dimensional Halbach-type permanent quadrupole magnet (PMQ) as shown in Fig. 6 is given by $B' = 2B_r(r_i^{-1} - r_o^{-1})$, where B_r is the tip field strength, r_i is the bore radius and r_o is the outer radius of PMQ. With $B_r = 1.45 \text{ T}$ for NdFeB material and $r_i = 2.5 \text{ mm}$, one can obtain the field gradient $B' = 1160 [\text{T/m}](1 - 2.5[\text{mm}]/r_o)$. Fig. 6 illustrates schematically a twelve segments Halbach-type PMQ 31, 32 of a set of the quadrupole magnet 36, including a housing 33, 34 and a bracket 35 for supporting and positioning the PMQ. The quadrupole field is composed of four radially wedges of permanent magnet material 31, e.g., $\text{Nd}_2\text{Fe}_{14}\text{B}$ or SmCO , with a high remanent field, of which the direction of magnetization is indicated by arrows. The outer field closure is formed by eight wedges of permanent magnet material 32. Since the four main wedges are strongly attracted toward of the center of the quadrupole, their mechanical precision and field accuracy can be achieved by the insertion of a nonmagnetic precision cylinder 33 into the center of the PMQ and by the housing case 34 outside the permanent quadrupole magnet (PMQ).

As shown in Fig. 7, the beam focusing system 12 comprises two to four permanent quadrupole magnets (PMQ), e.g. a doublet (FD), a triplet (FDF), or a quadruplet (FFDD) 36-39

installed into a housing chamber 46 with water cooling tubes 44. The longitudinal position of each permanent quadrupole magnet (PMQ) along the electron beam axis is optimized with a computer controlled mover system 40-43, comprising a vacuum linear motion manipulator driven by a stepping motor. Alignment of permanent quadrupole magnets (PMQ) is precisely constrained by a rail system 45.

Undulator

For a Extreme UltraViolet light source based on Free-Electron Laser, a planar undulator comprising alternating dipole magnets 52 is used, e.g., a pure permanent magnet (PPM) undulator with Nd₂Fe₁₄B blocks 50 as shown in Fig. 8 or a hybrid undulator comprising pure permanent magnets 50 and ferromagnetic poles 51 as shown in Fig. 9, e.g. a high saturation cobalt steel such as vanadium permendur or a simple iron. For a hybrid undulator, the thickness of the pole and magnet is optimized in order to maximize the peak field. In Fig. 8 and 9, the arrows represent the direction of magnetization in the magnet blocks, of which a period is λ_u . The minimum distance between the magnet jaws is a gap g . The peak field B_u of the gap is estimated in terms of the gap g and period λ_u according to $B_u = a[T] \exp[b(g/\lambda_u) + c(g/\lambda_u)^2]$ for gap range $0.1 < g/\lambda_u < 1$, where $a = 2.076$ T, $b = -3.24$, $c = 0$ for the pure permanent magnets planar undulator, $a = 3.694$ T, $b = -5.068$, $c = 1.520$ for the hybrid undulator with vanadium permendur, and $a = 3.381$ T, $b = -4.730$, $c = 1.198$ for the hybrid undulator with iron.

As shown in Fig. 10A and 10B, the undulator 13 comprises a rectangular box frame 53, a gap adjusting mechanism 54 and cooling elements 55. The permanent magnet blocks 52 is attached to a thick base plate of the box frame 53 made of aluminium material. The alignment and gap of the undulator are adjusted by controlling the distance between two base plates of the box frame 53 with 4 or 6 adjusting mechanisms 54. Two monolithic water cooling elements 55 fabricated from tubing are connected to each magnet block 52.

Beam separator

As shown in Fig. 11A, 11B and 11C, a decelerated electron beam 10 after saturation is bent by a dipole field of permanent magnet (a beam separator 16) made of NdFeB material and dumped to a beam dump 17 made of copper with a water cooling element 56. The permanent magnet dipole (PMD) 16, e.g., Halbach-type permanent magnet dipole, comprises 8 wedges of the NdFeB material, of which the magnetization direction is shown by the arrows in Fig. 11B. The dipole field B_D of the Halbach-type permanent magnet dipole is given by $B_D = B_r \ln(r_o/r_i)$, where B_r is the tip field strength, r_i is the bore radius and r_o is the outer radius of the PMD. With $B_r = 1.45$ T for NdFeB material, $r_i = 5$ mm and $r_o = 100$ mm, one can obtain the dipole field $B_D = 4.34$ T. The mechanical precision and field accuracy of the

permanent magnet dipole 16 can be achieved by the insertion of a nonmagnetic precision cylinder 57 into the center of the permanent magnet dipole and by the housing case 58 outside the permanent magnet dipole. The electron beam 10 bent by the permanent magnet dipole field 16 is dumped to the copper beam dump 17, while the Extreme UltraViolet radiation 14 is extracted through a narrow Extreme UltraViolet output hole 59 machined in the beam dump 17 at the edge of the permanent magnet dipole bore. The permanent magnet dipole length required for deflecting $d \approx 2r_i$ [mm] is given by $L_{\text{PMD}}[\text{cm}] = 10[(r_i / 3.26 \text{ mm})(E_b / 1 \text{ GeV})]^{1/2}$ for $B_D = 4.34 \text{ T}$ ($r_o / r_i = 20$). Since electrons lose energy by a factor of $1/e \approx 0.37$ over the radiation length $X_0 = 1.44 \text{ cm}$ via electromagnetic cascades in the copper beam dump, almost all electrons with energy 1 GeV lose their energy inside the copper block with length $10X_0 \sim 15 \text{ cm}$ and diameter $7X_0 \sim 10 \text{ cm}$. Both permanent magnet dipole and beam dump are cooled down by the water cooling elements 56.

The Free-Electron Laser device

As shown in Fig. 12, the Free-Electron Laser device comprising the beam focusing system 12, the undulator 13 and the beam separator 16 and beam dump 17 is installed into vacuum chambers 11, 15 with vacuum pumping systems 28, 29 that maintain a pressure of the order of 10^{-4} Pa inside the chamber. The beam dump 17 connected to the beam separator 16 forms a monolithic device.

In self-amplified spontaneous emission (SASE) Free-Electron Laser process, coupling the electron bunch with a copropagating undulator radiation field induces the energy modulation of electrons that yields a current modulation of the bunch due to the dispersion of the undulator dipole fields, called microbunching. It means that the electrons are grouped into small bunches separated by a fixed distance that resonantly coincides with the wavelength of the radiation field. Consequently, the radiation field can be amplified coherently. When lacking an initial resonant radiation field, a seed may build up from spontaneous incoherent emission in the self-amplified spontaneous emission (SASE) process.

Design of Free-Electron Laser based Extreme UltraViolet light source

A design of Free-Electron Laser based Extreme UltraViolet light source is made by the one-dimensional Free-Electron Laser theory as follows. The Free-Electron Laser amplification takes place in the undulator with the undulator period λ_u at the resonant wavelength given by

$$\lambda_x = \frac{\lambda_u}{2\gamma^2} \left(1 + \frac{K^2}{2}\right),$$

where $\gamma = E_b / m_e c^2$ is the relativistic factor of the electron beam energy E_b , and $K_u = 0.934 B_u [\text{T}] \lambda_u [\text{cm}] = \gamma \theta_e$ is the undulator parameter, which is related to the maximum electron deflection angle θ_e .

In the high-gain regime required for the operation of a self-amplified spontaneous emission (SASE) Free-Electron Laser, an important parameter is the Pierce parameter ρ_{FEL} given by

$$\rho_{\text{FEL}} = \frac{1}{2\gamma} \left[\frac{I_b}{I_A} \left(\frac{\lambda_u K_u A_u}{2\pi\sigma_b} \right)^2 \right]^{1/3}$$

where I_b is the beam current, $I_A = 17 \text{ kA}$ is the Alfvén current, σ_b is the root mean square (r.m.s) transverse size of the electron bunch, and the coupling factor is $A_u = 1$ for a helical undulator and $A_u = J_0(\xi) - J_1(\xi)$ for a planar undulator, where $\xi = K_u^2 / [4(1 + K_u^2/2)]$ and J_0 and J_1 are the Bessel functions of the first kind.

Another important dimensionless parameter is the longitudinal velocity spread Λ of the beam normalized by the Pierce parameter:

$$\Lambda^2 = \frac{1}{\rho_{\text{FEL}}^2} \left[\left(\frac{\sigma_\gamma}{\gamma} \right)^2 + \left(\frac{\varepsilon \lambda_u}{4\lambda_x \beta} \right)^2 \right] = \frac{1}{\rho_{\text{FEL}}^2} \left[\left(\frac{\sigma_\gamma}{\gamma} \right)^2 + \left(\frac{\varepsilon_n^2}{2\sigma_b^2(1 + K_u^2/2)} \right)^2 \right],$$

where σ_γ / γ is the relative root mean square (r.m.s.) energy spread, ε is the r.m.s. transverse emittance, $\beta = \sigma_b^2 / \varepsilon$ is the beta function provided by the guiding field (undulator plus external focusing) and ε_n is the normalized emittance defined as $\varepsilon_n \equiv \gamma \varepsilon$ assuming that a beta function is constant along the length of the undulator.

A e -folding gain length L_{gain} over which the power grows exponentially according to $\exp(2s / L_{\text{gain}})$ is given by

$$L_{\text{gain}} = \frac{\lambda_u}{4\pi\sqrt{3}\rho_{\text{FEL}}} (1 + \Lambda^2).$$

In order to minimize the gain length, one needs a large Pierce parameter ρ_{FEL} and a normalized longitudinal velocity spread Λ sufficiently low compared to 1 that means a sufficiently small energy spread σ_γ / γ and ε . This expression applies to moderately small beam size σ_b such that the diffraction parameter $B \gg 1$ where B is defined as

$$B = \frac{16\pi^2 A_u \sigma_b^2}{\lambda_x \lambda_u} \left[\frac{K_u^2 / 2}{\gamma(1 + K_u^2 / 2)} \frac{I_b}{I_A} \right]^{1/2}.$$

A saturation length L_{sat} required to saturate the amplification can be expressed as

$$L_{\text{sat}} = L_{\text{gain}} \ln \left[\left(\frac{\Lambda^2 + 3/2}{\Lambda^2 + 1/6} \right) \frac{P_{\text{sat}}}{P_{\text{in}}} \right],$$

where P_{in} and P_{sat} are an input and a saturated power.

The input P_{in} and saturated power P_{sat} are related to an electron beam power P_b according to

$$P_b = \gamma I_b m_e c^2 = I_b E_b,$$

$$P_{\text{sat}} \cong 1.37 \rho_{\text{FEL}} P_b \exp(-0.82 \Lambda^2),$$

$$P_{\text{in}} \cong 3\sqrt{4\pi} \rho_{\text{FEL}}^2 P_b [N_{\lambda_x} \ln(N_{\lambda_x} / \rho_{\text{FEL}})]^{-1/2},$$

where N_{λ_x} is the number of electrons per wavelength given by $N_{\lambda_x} = I_b \lambda_x / (ec)$.

6.4. Embodiment of a Free-Electron Laser used as an Extreme UltraViolet source at 13.5 nm wavelength

A fiber laser driven Laser Plasma Accelerator (LPA) based Free-Electron Laser produced Extreme UltraViolet radiation source at $\lambda_x = 13.5$ nm wavelength using the undulator with period $\lambda_u = 5$ mm (Case A), 10 mm (Case B), 15 mm (Case C), 20 mm (Case D) and 25 mm (Case E), all cases of which have the gap-period ratio $g / \lambda_u = 0.2$, e.g. $g = 1$ mm (Case A), 2 mm (Case B), 3 mm (Case C), 4 mm (Case D) and 5 mm (Case E), respectively. A hybrid undulator comprising NdFeB materials with grade N52, e.g., VACODYM® 722HR, and ferromagnetic materials such as tempered Co-Fe alloys (vanadium permendur), e.g., VACOFLUX® 50, provide the peak magnetic field $B_u [\text{T}] = 3.694 \exp(-5.068 \times 0.2 + 1.520 \times 0.2^2) = 1.425$. The corresponding undulator parameter becomes $K_u = 0.1331 \lambda_u [\text{mm}] = 0.6655, 1.331, 1.9965, 2.662, 3.3275$ for $\lambda_u [\text{mm}] = 5, 10, 15, 20, 25$.

The electron beam energy E_b required for producing the Extreme UltraViolet radiation at the wavelength $\lambda_x = 13.5$ nm is given by $\gamma = 192.45 \lambda_u^{1/2} (1 + 0.008858 \lambda_u^2)^{1/2}$, i.e., $E_b [\text{MeV}] = 98.45 \lambda_u^{1/2} (1 + 0.008858 \lambda_u^2)^{1/2}$. For Case A to E, $\gamma = 475.6, 835.7, 1290, 1834, 2460$ and $E_b [\text{MeV}] = 243, 427, 659, 937, 1257$.

The Laser Plasma Accelerator (LPA) can provide a high-peak current bunched beam, e.g., $I_A = 50$ kA for electron charge $Q_b = 0.5$ nC and bunch duration $\tau_b \sim 10$ fs. A fiber laser pulse with wavelength $\lambda_L = 1 \mu\text{m}$ after compression is focused on the entrance of gas cell at the normalized laser field $a_0 = 2$ corresponding to the laser intensity $I = 5.5 \times 10^{18} \text{ W cm}^{-2}$. Self-guided propagation of such laser pulse in the gas cell requires the group velocity correction factor $\kappa_{\text{self}} = 1.19$ and the matched spot radius $R_m \equiv k_p r_m = 3.2$. The wakefield reduction factor α due to loaded charge Q_b is calculated from $\alpha^2 + C \alpha^{3/2} - 1 = 0$ for the electron beam radius $k_p \sigma_b = 1$, where the coefficients are $C = 9.0, 6.8, 5.5, 4.6, 4.0$ as $\alpha = 0.223, 0.267, 0.302, 0.335, 0.364$, respectively, for Case A to E.

The important Laser Plasma Accelerator (LPA) parameters are provided as follows:

- (1) The operating plasma density; $n_e [10^{17} \text{ cm}^{-3}] = 8.3, 5.6, 4.2, 3.2, 2.6$
- (2) The accelerator length; $L_{\text{acc}} [\text{mm}] = 18, 32, 51, 74, 102$
- (3) The required pulse duration; $\tau_L [\text{fs}] = 46, 56, 65, 73, 82$

(4) The matched spot radius; $r_m [\mu\text{m}] = 19, 23, 27, 30, 34$

(5) The matched power; $P_L [\text{TW}] = 29, 43, 59, 75, 93$

(6) The required laser pulse energy; $U_L [\text{J}] = 1.34, 2.40, 3.79, 5.52, 7.57$

For the Free-Electron Laser operation, the coupling factor $A_u(\xi)$ are
 $A_u = 0.9527, 0.8696, 0.8083, 0.7711, 0.7486$ with $\xi = 0.09065, 0.2349, 0.3329, 0.3899, 0.4235$ for Case
 A to E, respectively. The root mean square (r.m.s) transverse size of the electron bunch is set to
 $\sigma_b = 25 \mu\text{m}$ in the undulator and is usually much larger than the normalized transverse
 emittance ε_n of the order of $1 \mu\text{m}$ for the Laser Plasma Accelerator (LPA) produced electron
 beam. For the peak current $I_b = 50 \text{ kA}$ with the number of electrons per wavelength
 $N_{\lambda_x} = 1.4 \times 10^7$ and the diffraction parameter $B \gg 1$, the important Free-Electron Laser
 parameters are given as follows according to the one-dimensional Free-Electron Laser theory:

(1) The Pierce parameter; $\rho_{\text{FEL}} [\%] = 1.117, 1.507, 1.597, 1.596, 1.572$

(2) The longitudinal velocity spread; $\Lambda \approx 1$ for setting $\sigma_\gamma / \gamma \approx \rho_{\text{FEL}}$

(3) The e-folding gain length; $L_{\text{gain}} [\text{mm}] = 41, 61, 86, 115, 146$

(4) The saturated power; $P_{\text{sat}} [\text{GW}] \approx 0.6 \rho_{\text{FEL}} P_b = 82, 194, 317, 451, 596$

(5) The input power; $P_{\text{in}} [\text{MW}] \approx 0.94, 3.03, 5.26, 7.48, 9.72$

(6) The saturation length; $L_{\text{sat}} [\text{mm}] = 499, 721, 1016, 1355, 1723$

(7) The total number of periods; $N_u = 100, 72, 68, 68, 69$.

(8) The spectral bandwidth; $\Delta\lambda_x / \lambda_x [\%]: 1/N_u \approx 1.0, 1.4, 1.5, 1.5, 1.5$

(9) The r.m.s. radiation cone angle;

$$\theta_{\text{rms}} [\mu\text{rad}] = \frac{1}{2\gamma} \left(\frac{1 + K_u^2 / 2}{N_u} \right)^{1/2} = 116, 97, 82, 71, 63$$

(10) The average power at the repetition frequency $f_{\text{rep}} [\text{MHz}]$;

$$P_{\text{av}} [\text{kW}]: P_{\text{sat}} \tau_X f_{\text{rep}} = (0.82, 1.94, 3.17, 4.51, 5.96) \times f_{\text{rep}} [\text{MHz}],$$

assuming the radiation duration $\tau_X \approx \tau_b \sim 10 \text{ fs}$.

The repetition rate f_{rep} to be required for generating the average Extreme UltraViolet
 power of $P_{\text{EUV}} = 1 \text{ kW}$ yields $f_{\text{rep}} [\text{MHz}] \approx P_{\text{EUV}} / (P_{\text{sat}} \tau_X) = 1.22, 0.515, 0.315, 0.223, 0.168$. For the
 production of 1 kW Extreme UltraViolet radiation, the average fiber laser power yields
 $P_{\text{Lav}} [\text{MW}] \approx U_L f_{\text{rep}} = 1.63, 1.24, 1.19, 1.22, 1.27$

Consequently, the minimum average laser power takes place for Case C with the
 undulator period 15 mm . The average beam power yields $P_{\text{bav}} [\text{kW}] = Q_b f_{\text{rep}} E_b$
 $\approx 148, 110, 104, 104, 105$. The efficiency of the electron beam acceleration is $\eta_{\text{laser} \rightarrow \text{beam}} [\%]$

$= P_{\text{bay}} / P_{\text{Lav}} \approx 9.1, 8.9, 8.7, 8.5, 8.3$. The efficiency of the production of Extreme UltraViolet radiation yields $\eta_{\text{laser} \rightarrow \text{EUV}} [\%] = 0.061, 0.081, 0.084, 0.082, 0.079$

Said Laser Plasma Accelerator (LPA) and Free-Electron Laser parameters for Case A to E producing the Extreme UltraViolet radiation of 1 kW at 13.5 nm wavelength are summarized as shown in Table 1.

Table 1 Examples of the fiber laser driven Laser Plasma Accelerator (LPA) based Free-Electron Laser Extreme UltraViolet light source at 13.5 nm

Case	A	B	C	D	E
Fiber laser parameters					
Laser wavelength [μm]	1	1	1	1	1
Average laser power [MW]	1.63	1.24	1.19	1.22	1.27
Repetition rate [MHz]	1.22	0.515	0.315	0.223	0.168
Laser energy per pulse [J]	1.34	2.40	3.79	5.52	7.57
Peak power [TW]	29	43	59	75	93
Pulse duration [fs]	46	56	65	73	82
Matched spot radius [μm]	19	23	27	30	34
LPA parameters					
Electron beam energy [MeV]	243	427	659	937	1257
Plasma density [10^{17} cm^{-3}]	8.3	5.6	4.2	3.2	2.6
Accelerator length [mm]	18	32	51	74	102
Charge per bunch [nC]	0.5	0.5	0.5	0.5	0.5
Field reduction factor α	0.223	0.267	0.302	0.325	0.364
Bunch duration [fs]	10	10	10	10	10
Energy spread [%]	~ 1.1	~ 1.5	~ 1.6	~ 1.6	~ 1.6
Normalized emittance [mm mrad]	~ 1	~ 1	~ 1	~ 1	~ 1
Transverse beam size [μm]	25	25	25	25	25
Peak current [kA]	50	50	50	50	50
Average beam power [kW]	148	110	104	104	105
Efficiency of laser to beam [%]	9.1	8.9	8.7	8.5	8.3
FEL parameters					
Undulator period [mm]	5	10	15	20	25
Radiation wavelength [nm]	13.5	13.5	13.5	13.5	13.5
Gap [mm]	1	2	3	4	5
Peak magnetic field [T]	1.425	1.425	1.425	1.425	1.425
Undulator parameter K_u	0.666	1.33	2.00	2.66	3.33

Pierce parameter [%]	1.117	1.507	1.597	1.596	1.572
Gain length [mm]	41	61	86	115	146
Saturation length [mm]	499	721	1016	1355	1723
Number of periods	100	72	68	68	69
Spectral bandwidth [%]	1.0	1.4	1.5	1.5	1.5
r.m.s. Radiation cone angle [μ rad]	116	97	82	71	63
Input power [MW]	0.94	3.03	5.26	7.48	9.72
Saturated power [GW]	82	194	317	451	596
Duration of EUV pulse [fs]	10	10	10	10	10
Average EUV power [kW]	1	1	1	1	1
Efficiency of EUV generation [%]	0.061	0.081	0.084	0.082	0.079

6.4. Embodiment of a Free-Electron Laser used as an Extreme UltraViolet source at 6.7 nm wavelength

A fiber laser driven Laser Plasma Accelerator (LPA) based Free-Electron Laser produced Extreme UltraViolet radiation source at $\lambda_x = 6.7$ nm wavelength using the undulator with period $\lambda_u = 5$ mm (Case A), 10 mm (Case B), 15 mm (Case C), 20 mm (Case D) and 25 mm (Case E), all cases of which have the gap-period ratio $g/\lambda_u = 0.2$, e.g. $g = 1$ mm (Case A), 2 mm (Case B), 3 mm (Case C), 4 mm (Case D) and 5 mm (Case E), respectively. A hybrid undulator comprising NdFeB materials with grade N52, e.g., VACODYM® 722HR, and ferromagnetic materials such as tempered Co-Fe alloys (vanadium permendur), e.g., VACOFLUX® 50, provide the peak magnetic field $B_u[\text{T}] = 3.694 \exp(-5.068 \times 0.2 + 1.520 \times 0.2^2) = 1.425$. The corresponding undulator parameter becomes $K_u = 0.1331\lambda_u[\text{mm}] = 0.6655, 1.331, 1.9965, 2.662, 3.3275$ for $\lambda_u[\text{mm}] = 5, 10, 15, 20, 25$.

The electron beam energy E_b required for producing the Extreme UltraViolet radiation at the wavelength $\lambda_x = 6.7$ is given by $\gamma = 273.18\lambda_u^{1/2}(1 + 0.008858\lambda_u^2)^{1/2}$, i.e., $E_b[\text{MeV}] = 98.45\lambda_u^{1/2}(1 + 0.008858\lambda_u^2)^{1/2}$. For Case A to E, $\gamma = 675.1, 1186, 1830, 2604, 3492$ and $E_b[\text{MeV}] = 345, 606, 935, 1331, 1784$.

The Laser Plasma Accelerator (LPA) can provide a high-peak current bunched beam, e.g., $I_A = 50$ kA for electron charge $Q_b = 0.5$ nC and bunch duration $\tau_b \sim 10$ fs. A fiber laser pulse with wavelength $\lambda_L = 1 \mu\text{m}$ after compression is focused on the entrance of gas cell at the normalized laser field $a_0 = 2$ corresponding to the laser intensity $I = 5.5 \times 10^{18} \text{ Wcm}^{-2}$. Self-guided propagation of such laser pulse in the gas cell requires the group velocity correction factor $\kappa_{\text{self}} = 1.19$ and the matched spot radius $R_m \equiv k_p r_m = 3.2$. The wakefield reduction factor α due to loaded charge Q_b is calculated from $\alpha^2 + C\alpha^{3/2} - 1 = 0$ for the electron beam

radius $k_p \sigma_b = 1$, where the coefficients are $C = 7.55, 5.70, 4.59, 3.84, 3.32$ as $\alpha = 0.249, 0.295, 0.335, 0.369, 0.400$, respectively, for Case A to E.

The important Laser Plasma Accelerator (LPA) parameters are provided as follows:

- (1) The operating plasma density; $n_e [10^{17} \text{ cm}^{-3}] = 6.5, 4.4, 3.2, 2.5, 2.0$
- (2) The accelerator length; $L_{\text{acc}} [\text{mm}] = 26, 47, 74, 109, 150$
- (3) The required pulse duration; $\tau_L [\text{fs}] = 52, 63, 73, 83, 93$
- (4) The matched spot radius; $r_m [\mu\text{m}] = 21, 26, 30, 34, 38$
- (5) The matched power; $P_L [\text{TW}] = 37, 55, 75, 97, 120$
- (6) The required laser pulse energy; $U_L [\text{J}] = 1.92, 3.47, 5.51, 8.06, 11.1$

For the FEL operation, the coupling factor $A_u(\xi)$ are $A_u = 0.9527, 0.8696, 0.8083, 0.7711, 0.7486$ with $\xi = 0.09065, 0.2349, 0.3329, 0.3899, 0.4235$ for Case A to E, respectively. The root mean square (r.m.s) transverse size of the electron bunch is set to $\sigma_b = 25 \mu\text{m}$ in the undulator and is usually much larger than the normalized transverse emittance ε_n of the order of $1 \mu\text{m}$ for the Laser Plasma Accelerator (LPA) produced electron beam. For the peak current $I_b = 50 \text{ kA}$ with the number of electrons per wavelength $N_{\lambda_x} = 7 \times 10^6$ and the diffraction parameter $B \gg 1$, the important Free-Electron Laser parameters are given as follows according to the one-dimensional Free-Electron Laser theory:

- (1) The Pierce parameter; $\rho_{\text{FEL}} [\%] = 0.787, 1.061, 1.125, 1.125, 1.107$
- (2) The longitudinal velocity spread; $\Lambda \approx 1$ for setting $\sigma_\gamma / \gamma \approx \rho_{\text{FEL}}$
- (3) The e-folding gain length; $L_{\text{gain}} [\text{mm}] = 58.4, 86.6, 123, 163, 207$
- (4) The saturated power; $P_{\text{sat}} [\text{GW}] \equiv 0.6 \rho_{\text{FEL}} P_b = 82, 194, 317, 451, 596$
- (5) The input power; $P_{\text{in}} [\text{MW}] \approx 0.94, 3.05, 5.3, 7.5, 9.8$
- (6) The saturation length; $L_{\text{sat}} [\text{mm}] = 709, 1024, 1441, 1923, 2445$
- (7) The total number of periods; $N_u = 142, 102, 96, 96, 98$.
- (8) The spectral bandwidth; $\Delta\lambda_x / \lambda_x [\%] : 1/N_u \approx 0.71, 0.98, 1.04, 1.04, 1.02$
- (9) The r.m.s. radiation cone angle; $\theta_{\text{rms}} [\mu\text{rad}] = 69, 57, 48, 42, 37$
- (10) The average power at the repetition frequency $f_{\text{rep}} [\text{MHz}]$;

$$P_{\text{av}} [\text{kW}] : P_{\text{sat}} \tau_X f_{\text{rep}} = (0.82, 1.94, 3.17, 4.51, 5.96) \times f_{\text{rep}} [\text{MHz}] ,$$

assuming the radiation duration $\tau_X \approx \tau_b \sim 10 \text{ fs}$. The repetition rate f_{rep} to be required for generating the average EUV power of $P_{\text{EUV}} = 1.5 \text{ kW}$ yields $f_{\text{rep}} [\text{MHz}] \approx P_{\text{EUV}} / (P_{\text{sat}} \tau_X) = 1.83, 0.773, 0.473, 0.332, 0.252$. For the production of 1.5 kW EUV radiation, the average fiber laser power yields $P_{\text{Lay}} [\text{MW}] \approx U_L f_{\text{rep}} = 3.52, 2.68, 2.60, 2.68, 2.80$

Consequently, the minimum average laser power takes place for Case C with the undulator period 15 mm. The average beam power yields $P_{bav}[\text{kW}] = Q_b f_{rep} E_b \approx 316, 234, 221, 221, 225$. The efficiency of the electron beam acceleration is $\eta_{laser \rightarrow beam}[\%] = P_{bav} / P_{Lav} \approx 8.97, 8.73, 8.49, 8.26, 8.03$. The efficiency of the production of Extreme UltraViolet radiation yields $\eta_{laser \rightarrow EUV}[\%] = 0.043, 0.056, 0.058, 0.056, 0.054$.

Said Laser Plasma Accelerator (LPA) and Free-Electron Laser parameters for Case A to E producing the Extreme UltraViolet radiation of 1 kW at 6.7 nm wavelength are summarized as shown in Table 2.

Table 2 Examples of the fiber laser driven Laser Plasma Accelerator (LPA) based Free-Electron Laser Extreme UltraViolet light source.

Case	A	B	C	D	E
Fiber laser parameters					
Laser wavelength [μm]	1	1	1	1	1
Average laser power [MW]	3.52	2.68	2.60	2.68	2.80
Repetition rate [MHz]	1.83	0.773	0.473	0.332	0.252
Laser energy per pulse [J]	1.92	3.47	5.51	8.06	11.1
Peak power [TW]	37	55	75	97	120
Pulse duration [fs]	52	63	73	83	93
Matched spot radius [μm]	21	26	30	34	38
LPA parameters					
Electron beam energy [MeV]	345	606	935	1331	1784
Plasma density [10^{17} cm^{-3}]	6.5	4.4	3.2	2.5	2.0
Accelerator length [mm]	26	47	74	109	150
Charge per bunch [nC]	0.5	0.5	0.5	0.5	0.5
Field reduction factor α	0.249	0.295	0.335	0.369	0.400
Bunch duration [fs]	10	10	10	10	10
Energy spread [%]	~ 0.8	~ 1.1	~ 1.1	~ 1.1	~ 1.1
Normalized emittance [mm mrad]	~ 1	~ 1	~ 1	~ 1	~ 1
Transverse beam size [μm]	25	25	25	25	25
Peak current [kA]	50	50	50	50	50
Average beam power [kW]	316	234	221	221	225
Efficiency of laser to beam [%]	9.0	8.7	8.5	8.3	8.0
FEL parameters					
Radiation wavelength [nm]	6.7	6.7	6.7	6.7	6.7

Undulator period [mm]	5	10	15	20	25
Gap [mm]	1	2	3	4	5
Peak magnetic field [T]	1.425	1.425	1.425	1.425	1.425
Undulator parameter K_u	0.666	1.33	2.00	2.66	3.33
Pierce parameter [%]	0.787	1.06	1.125	1.125	1.107
Gain length [mm]	58.4	86.6	123	163	207
Saturation length [mm]	709	1024	1441	1923	2445
Number of periods	142	102	96	96	98
Spectral bandwidth [%]	0.71	0.98	1.04	1.04	1.02
r.m.s. Radiation cone angle [μ rad]	69	57	48	42	37
Input power [MW]	0.94	3.05	5.3	7.5	9.8
Saturated power [GW]	82	194	317	451	596
Duration of EUV pulse [fs]	10	10	10	10	10
Average EUV power [kW]	1.5	1.5	1.5	1.5	1.5
Efficiency of EUV generation [%]	0.043	0.056	0.058	0.056	0.054

6.5 Embodiment of tuning a Free-Electron Laser for the wavelength range from 5 nm to 15 nm

The FEL amplification takes place in the undulator with the undulator period λ_u at the resonant wavelength given by

$$\lambda_x = \frac{\lambda_u}{2\gamma^2} \left(1 + \frac{K_u^2}{2}\right),$$

where $\gamma = E_b / m_e c^2$ is the relativistic factor of the electron beam energy E_b , $K_u = 0.934 B_u [\text{T}] \lambda_u [\text{cm}]$. Setting the peak magnetic field of the undulator to be $B_u = 1.425 \text{ T}$, the corresponding undulator parameter becomes $K_u = 0.1331 \lambda_u [\text{mm}] = 1.9965$ for $\lambda_u = 15 \text{ mm}$ (CASE C). The electron beam energy E_b required for producing the EUV radiation at the wavelength λ_x is given by

$$E_b [\text{MeV}] = 659 \left(\frac{13.5 \text{ nm}}{\lambda_x} \right)^{1/2}$$

The important Laser Plasma Accelerator (LPA) parameters are provided as a function of FEL wavelength λ_x :

(1) The operating plasma density;

$$n_e \approx 4.2 \times 10^{17} [\text{cm}^{-3}] \left(\frac{\lambda_x}{13.5 \text{ nm}} \right)^{1/2}$$

(2) The accelerator length;

$$L_{\text{acc}} \approx 51 [\text{mm}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{3/4}$$

(3) The required pulse duration;

$$\tau_L = 65 [\text{fs}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{1/4}$$

(4) The matched spot radius;

5

$$r_m \approx 27 [\mu\text{m}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{1/4}$$

(5) The required laser peak power;

$$P_L \approx 59 [\text{TW}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{1/2}$$

(6) The required laser pulse energy;

$$U_L = 3.8 [\text{J}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{3/4}$$

10 The important Free-Electron Laser parameters are all given as a function of FEL wavelength λ_X :

(1) The Pierce parameter;

$$\rho_{\text{FEL}} = 1.597 [\%] \left(\frac{\lambda_X}{13.5 \text{ nm}} \right)^{1/2}$$

(2) The longitudinal velocity spread; $\Lambda \approx 1$ for setting $\sigma_\gamma / \gamma \approx \rho_{\text{FEL}}$

15

(3) The e -folding gain length;

$$L_{\text{gain}} = 86 [\text{mm}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{1/2}$$

(4) The saturated power; $P_{\text{sat}} = 317 [\text{GW}]$

(5) The input power; $P_{\text{in}} \approx 5.3 [\text{MW}]$

(6) The saturation length;

20

$$L_{\text{sat}} = 1016 [\text{mm}] \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{1/2}$$

(7) The total number of periods;.

$$N_u = L_{\text{sat}} / \lambda_u = 68 \left(\frac{13.5 \text{ nm}}{\lambda_X} \right)^{1/2}$$

(8) The spectral bandwidth; $\Delta\lambda_X / \lambda_X \sim 1 / N_u \approx 1.5 [\%]$

(9) The r.m.s. radiation cone angle;

$$\theta_{\text{rms}} = \frac{1}{2\gamma} \left(\frac{1 + K_u^2/2}{N_u} \right)^{1/2} = 82 [\mu\text{rad}] \left(\frac{\lambda_x}{13.5\text{nm}} \right)^{1/4}$$

(10) The average power at the repetition frequency f_{rep} [MHz];

$$P_{\text{av}} \sim P_{\text{sat}} \tau_X f_{\text{rep}} = 3.17 [\text{kW}] f_{\text{rep}}$$

for the radiation duration $\tau_X \approx \tau_b \sim 10$ fs.

5 (11) The repetition rate f_{rep} to be required for generating the average Extreme UltraViolet power of $P_{\text{EUV}} = 1$ kW;

$$f_{\text{rep}} \approx P_{\text{EUV}} / (P_{\text{sat}} \tau_X) = 0.315 [\text{MHz}]$$

(12) The average fiber laser power for the production of 1 kW Extreme UltraViolet radiation;

$$P_{L\text{av}} \approx U_L f_{\text{rep}} = 1.19 [\text{MW}] \left(\frac{13.5\text{nm}}{\lambda_x} \right)^{3/4}$$

10 (13) The average electron beam power;

$$P_{b\text{av}} = Q_b f_{\text{rep}} E_b = 104 [\text{kW}] \left(\frac{13.5\text{nm}}{\lambda_x} \right)^{1/2}$$

(14) The efficiency of the electron beam acceleration;

$$\eta_{\text{laser} \rightarrow \text{beam}} = P_{b\text{av}} / P_{L\text{av}} = 8.7 [\%] \left(\frac{\lambda_x}{13.5\text{nm}} \right)^{1/4}$$

(15) The efficiency of the production of Extreme UltraViolet radiation;

$$15 \quad \eta_{\text{laser} \rightarrow \text{EUV}} = P_{\text{EUV}} / P_{L\text{av}} = 0.084 [\%] \left(\frac{\lambda_x}{13.5\text{nm}} \right)^{3/4}$$

For undulator period $\lambda_u = 15$ mm, the average Extreme UltraViolet power of $P_{\text{EUV}} = 1$ kW, the electron beam energy E_b , the operating plasma density n_e , the accelerator length L_{acc} , the required laser peak power P_L , the required laser pulse energy U_L , the Pierce parameter ρ_{FEL} , the saturation length L_{sat} , the average fiber laser power $P_{L\text{av}}$ and the efficiency of the production of Extreme UltraViolet radiation η_{eff} are shown as a function of the radiation wavelength λ_x for the range from 5 nm to 15 nm in Fig. 14, obtained for a given peak magnetic field and a given undulator period, which have been previously set (e.g. $B_u = 1.425$ T and $\lambda_u = 15$ mm.)

Other examples have been given respectively in table 1 and 2 of section 6.4 for other cases A, B, D, E, F related to other examples of undulator period with $B_u = 1.425$ T).

Citation List

Patent Literature

(1) U.S. patent application No. 13/445,195, filed on Apr. 12, 2012, entitled LASER PRODUCED PLASMA EUV LIGHT SOURCE, Pub. No. US 2012/0228526 A1.

(2) U.S. patent No. 4,761,584, Date of patent Aug. 2, 1988, entitled STRONG PERMANENT MAGNET-ASSISTED ELECTROMAGNETIC UNDULATOR.

5 (3) U.S. patent No. 5,019,863, Date of patent May 28, 1991, entitled WEDGED-POLE HYBRID UNDULATOR.

(4) International patent application No. PCT/US2012/050135, filed on 09.08.2012, Pub. No. WO/2013/023053, Pub. Date, 14. 02.2013, ENTITLED COMPACT UNDULATOR SYTEM AND METHODS.

10 Non patent Literature

(1) A. Pak, K. A. Marsh, S. F. Martins, W. Lu, W. B. Mori, and C. Joshi, "Injection and Trapping of Tunnel-Ionized Electrons into Laser-Produced Wakes," Phys. Rev. Lett. 104, 025003 (2010).

15 (2) C. McGuffey, A. G. R. Thomas, W. Schumaker, T. Matsuoka, V. Chvykov, F. J. Dollar, G. Kalintchenko, V. Yanovsky, A. Maksimchuk, K. Krushelnick, V. Y. Bychenkov, I. V. Glazyrin, and A. V. Karpeev, "Ionization Induced Trapping in a Laser Wakefield Accelerator," Phys. Rev. Lett. 104, 025004 (2010).

20 (3) C. Xia, J. Liu, W. Wang, H. Lu, W. Cheng, A. Deng, W. Li, H. Zhang, X. Liang, Y. Leng, X. Lu, C. Wang, J. Wang, K. Nakajima, R. Li, and Z. Xu, "Effects of self-focusing on tunnel-ionization-induced injection in a laser wakefield accelerator," Phys. Plasmas 18, 113101 (2011).

(4) J. S. Liu, C. Q. Xia, W. T. Wang, H. Y. Lu, C. Wang, A. H. Deng, W. T. Li, H. Zhang, X. Y. Liang, Y. X. Leng, X. M. Lu, C. Wang, J. Z. Wang, K. Nakajima, R. X. Li, and Z. Z. Xu, "All-Optical Cascaded Laser Wakefield Accelerator Using Ionization-Induced Injection," Phys. Rev. Lett. 107, 035001 (2011).

25 (5) B. B. Pollock, C. E. Clayton, J. E. Ralph, F. Albert, A. Davidson, L. Divol, C. Filip, S. H. Glenzer, K. Herpoldt, W. Lu, K. A. Marsh, J. Meinecke, W. B. Mori, A. Pak, T. C. Rensink, J. S. Ross, J. Shaw, G. R. Tynan, C. Joshi, and D. H. Froula, "Demonstration of a Narrow Energy Spread, similar to 0.5 GeV Electron Beam from a Two-Stage Laser Wakefield Accelerator," Phys. Rev. Lett. 107, 045001 (2011).

30 (6) M. Chen, E. Esarey, C. B. Schroeder, C. G. R. Geddes, and W. P. Leemans, "Theory of ionization-induced trapping in laser-plasma accelerators," Phys. Plasmas 19, 033101 (2012).

(7) Kazuhisa Nakajima, Haiyang Lu, Xueyan Zhao, Baifei Shen, Ruxin Li and Zhizhan Xu, "100-GeV large scale laser plasma electron acceleration by a multi-PW laser" Chinese Optics Letters 11 (1), 013501-1~15 (2013).

35 (8) J. K. Lim, P. Frigola, G. Travish, J. B. Rosenzweig, S. G. Anderson, W. J. Brown, J. S. Jacob, C. L. Robbins, and A. M. Tremaine, "Adjustable, short focal length permanent-magnet

quadrupole based electron beam final focus system”, PHYSICAL REVIEW SPECIAL TOPICS - ACCELERATORS AND BEAMS 8, 072401-1~17 (2005).

(9) P. Elleaume, J. Chavanne, Bart Faatz, “Design Considerations for a 1 angstrom SASE Undulator”, Nuclear Instruments and Methods in Physics Research A 455, 503-523 (2000).

5 (10) T. Eichner, F. Grüner, S. Becker, M. Fuchs, D. Habs, R. Weingartner, U. Schramm, H. Backe, P. Kunz, and W. Lauth, “Miniature magnetic devices for laser-based, table-top free-electron lasers”, PHYSICAL REVIEW SPECIAL TOPICS - ACCELERATORS AND BEAMS 10, 082401 (2007).

10 (11) C. Pagani, E.L. Saldin, E.A. Schneidmiller, M.V. Yurkov, “Design considerations of 10 kW-scale extreme ultraviolet SASE FEL for lithography”, Nuclear Instruments and Methods in Physics Research A 463, 9–25 (2001).

CLAIMS

1. A Free Electron Laser source generating an electromagnetic beam presenting a wavelength, called Free Electron Laser wavelength λ_x , belonging to the range from 5nm to 15nm, said Free Electron Laser comprising:

5 a fiber-based laser (1), comprising a plurality of amplifying fibres (831, 841, 851) wherein an initial laser pulse is distributed and amplified, and means for grouping together the elementary pulses amplified in the said fibre in order to form an a single amplified global laser pulse (3), and comprising a stretching device (82) able to stretch out in time said initial laser pulse, according to the chirped pulse amplification technique and a grating pulse compressor (87) able to compress in time the said single amplified global laser pulse, according to the chirped pulse amplification technique, said fiber-laser being tuned using at least one parameter, called fiber-based laser parameter, said at least one fiber-based laser parameter being obtained as a function of said Free Electron Laser wavelength λ_x ;

15 - a laser plasma accelerator (6) wherein, in a bubble regime of said plasma accelerator said global laser pulse (3) generates relativistic electron beams (10), said laser plasma accelerator being tuned using at least one parameter, called laser plasma accelerator parameter, said at least one laser plasma accelerator parameter being obtained as a function of said Free Electron Laser wavelength λ_x ;

20 - a beam focusing system (12) transporting electron beams (10) from the laser plasma accelerator to an undulator,
- said undulator (13) wherein relativistic electron beams (10) generate an electromagnetic beam, a peak magnetic field and a period of said undulator being previously set, said undulator being tuned using at least one parameter, called undulator parameter, said at least one undulator parameter being obtained as a function of said Free Electron Laser wavelength λ_x ;

25 - a beam separator system, wherein the said electron beam (10) and the said electromagnetic beam are separated.

2. A Free Electron Laser source according to claim 1 or 2 wherein said laser plasma accelerator (6) comprises:

- 30
- a first gas cell (21) filled with mixed gas, and
 - a second gas cell (24) filled with pure helium gas.
 - a gas feeding system.

3. A Free Electron Laser source according to claim 3 wherein said laser plasma accelerator (6) comprise means for modifying the length of the said second gas cell.

35

4. A Free Electron Laser source according to any of claim 1 to 4 wherein said beam separator system comprises a dipole magnet (16) for bending electron beams (10) and a beam dump.

5. A Free Electron Laser source according to any of claim 1 to 5 wherein said electromagnetic beam is a Extreme UltraViolet beam.

6. A Free Electron Laser source according to claim 6 wherein said Extreme UltraViolet beam wavelength is 13.5 nm.

7. A Free Electron Laser source according to claim 6 wherein said Extreme UltraViolet beam wavelength is 6.7 nm.





Fig.1






Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10A




Fig. 10B




Fig. 11B




Fig. 11C





Fig. 11A






Fig. 13




Fig. 14

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/069222

A. CLASSIFICATION OF SUBJECT MATTER
INV. H01S3/067 H01S3/09
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H01S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, COMPENDEX, INSPEC, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WIGGINS S M ET AL: "High quality electron beams from a laser wakefield accelerator", CONFERENCE ON LASERS AND ELECTRO-OPTICS (CLEO) AND QUANTUM ELECTRONICS AND LASER SCIENCE CONFERENCE (QELS), 2010 : 16 - 21 MAY 2010, SAN JOSE, CA, USA, IEEE, PISCATAWAY, NJ , USA, 16 May 2010 (2010-05-16), pages 1-2, XP031701440, ISBN: 978-1-55752-890-2 1. & 2.; figure 1 the whole document ----- -/--	1-7



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

5 February 2015

Date of mailing of the international search report

13/02/2015

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Bésuelle, Emmanuel

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/069222

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	HAFZ NASR: "Laser-driven electron acceleration research at APRI and future application to compact light sources", JOURNAL OF THE KOREAN PHYSICAL SOCIETY, vol. 56, no. 11, 15 January 2010 (2010-01-15), page 241, XP055101292, ISSN: 0374-4884, DOI: 10.3938/jkps.56.241 fig. 6 the whole document	1-7
Y	----- TOSHIKI TAJIMA ET AL: "ICAN: The Next Laser Powerhouse", OPTICS AND PHOTONICS NEWS, 1 May 2013 (2013-05-01), pages 36-43, XP055101291, DOI: http://dx.doi.org/10.1364/OPN.24.5.000036 p. 41: right col.; p. 39: last par. the whole document	1-7
Y	----- G. Mourou ET AL: "ICAN and 100GeV's Ascent", EuroNNAC, May 2012 Meeting, CERN, 1 May 2012 (2012-05-01), pages 1-60, XP055101548, Retrieved from the Internet: URL: http://indico.cern.ch/event/187383/session/3/contribution/7/material/slides/0.pdf f [retrieved on 2014-02-11]	3
A	Slide 56 the whole document	1,2,4-7
Y	----- G�rard Mourou: "Workshop IZEST 100GeV Ascent", , May 2013 (2013-05), pages 1-18, XP055101549, Retrieved from the Internet: URL: https://gargantua.polytechnique.fr/sia tel-web/linkto/mICYYS74tY [retrieved on 2014-02-11]	3
A	Slide 14 the whole document	1,2,4-7
	----- -/--	

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2014/069222

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	C. MCGUFFEY ET AL: "Ionization Induced Trapping in a Laser Wakefield Accelerator", PHYSICAL REVIEW LETTERS, vol. 104, no. 2, 1 January 2010 (2010-01-01), XP055101503, ISSN: 0031-9007, DOI: 10.1103/PhysRevLett.104.025004 cited in the application	3
A	pages 25004-1 - pages 25004-2 the whole document	1,2,4-7
T	----- PUKHOV A ET AL: "The bubble regime of laser-plasma acceleration: monoenergetic electrons and the scalability; The bubble regime of laser-plasma acceleration", PLASMA PHYSICS AND CONTROLLED FUSION, IOP, BRISTOL, GB, vol. 46, no. 12B, 1 December 2004 (2004-12-01), pages B179-B186, XP020049654, ISSN: 0741-3335, DOI: 10.1088/0741-3335/46/12B/016 the whole document	1-7
A	----- H.-P. SCHLENVOIGT ET AL: "A compact synchrotron radiation source driven by a laser-plasma wakefield accelerator", NATURE PHYSICS, vol. 4, no. 2, 9 December 2007 (2007-12-09), pages 130-133, XP055101295, ISSN: 1745-2473, DOI: 10.1038/nphys811 the whole document	1-7
A	----- H-P SCHLENVOIGT ET AL: "Synchrotron Radiation From Laser-Accelerated Monoenergetic Electrons", IEEE TRANSACTIONS ON PLASMA SCIENCE, IEEE SERVICE CENTER, PISCATAWAY, NJ, US, vol. 36, no. 4, 1 August 2008 (2008-08-01), pages 1773-1781, XP011232933, ISSN: 0093-3813, DOI: 10.1109/TPS.2008.927146 Fig. 1 and related parts of the text, i.a. II. "A.Laser-Plasma-Accelerator" the whole document	1-7
T	----- P. GASIOR: "Can ICAN can CERN into a can?: review study", PROCEEDINGS OF SPIE, vol. 8903, 25 October 2013 (2013-10-25), page 89030N, XP055101289, ISSN: 0277-786X, DOI: 10.1117/12.2035369 the whole document	1-7
	----- -/--	

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/069222

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
T	VIEIRA J F ET AL: "Three-Dimensional Structure of the Laser Wakefield Accelerator in the Blowout Regime", IEEE TRANSACTIONS ON PLASMA SCIENCE, IEEE SERVICE CENTER, PISCATAWAY, NJ, US, vol. 36, no. 4, 1 August 2008 (2008-08-01), pages 1124-1125, XP011232963, ISSN: 0093-3813, DOI: 10.1109/TPS.2008.922930 the whole document	1-7
A	----- YOSHITAMA H ET AL: "PHYSICS OF GASES, PLASMAS, AND ELECTRIC DISCHARGES; Self-Injection and Acceleration of Monoenergetic Electron Beams from Laser Wakefield Accelerators in a Highly Relativistic Regime", CHINESE PHYSICS LETTERS, INSTITUTE OF PHYSICS PUBLISHING, BRISTOL, GB, vol. 25, no. 8, 1 August 2008 (2008-08-01), pages 2938-2941, XP020141951, ISSN: 0256-307X, DOI: 10.1088/0256-307X/25/8/056 the whole document	1-7
A	----- A. PAK ET AL: "Injection and Trapping of Tunnel-Ionized Electrons into Laser-Produced Wakes", PHYSICAL REVIEW LETTERS, vol. 104, no. 2, 1 January 2010 (2010-01-01), XP055101496, ISSN: 0031-9007, DOI: 10.1103/PhysRevLett.104.025003 cited in the application the whole document -----	1-7