

(51) International Patent Classification:
H04W 52/24 (2009.01)

(21) International Application Number:

PCT/EP2010/003790

(22) International Filing Date:

24 June 2010 (24.06.2010)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

09290516.5 30 June 2009 (30.06.2009) EP

(71) Applicant (for all designated States except US): **ALCATEL LUCENT** [FR/FR]; 3, avenue Octave Gréard, F-75007 Paris (FR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BREND, Graham** [GB/GB]; 78 Dovers Park, Bathford, Bath, BA1 7UE Somerset (GB). **SAPIANO, Philip** [GB/GB]; 122 Brook Drive, Corsham, SN13 9AY Wiltshire (GB). **BRADLEY, Nigel** [GB/GB]; 41 North Meadow Road, Cricklade, SN6 6LT Wiltshire (GB). **PUTMAN, Tony** [GB/GB]; Hollyhurst, Brinkworth, Chippenham, SN15 4AQ Wiltshire (GB).(74) Agents: **COCKAYNE, Gillian** et al.; Alcatel-Lucent Telecom Ltd., Unit 18, Core 3, Workzone, Innova Business Park, Electric Avenue, Enfield, EN3 7XU (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: FEMTOCELL ARRANGEMENTS




FIG. 3

(57) **Abstract:** A femtocell arrangement comprises a plurality of femtocells Femto 1 to Femto 13 having coverage distributed over a region, such as, for example, an office. A border femtocell, Femto 3 or Femto 10, of said plurality has coverage at an entrance to the region and is arranged to operate at a higher transmit power level to provide a larger coverage area than that provided by neighboring femtocells. In addition, the border femtocell may be allocated a specific Primary Scrambling Code (PSC) to show its designation as a border femtocell. An approaching user equipment UE 1 or UE 2 tends to attach to the higher transmit power border femtocells. The Femto Gateway managing the connection is aware of the likelihood that an approaching UE will tend to attach to a border femtocell, and this is further confirmed by the use of a specific PSC. Hence, handover is expedited as the most suitable femtocells may be chosen as targets for handover.



-
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

- 1 -

FEMTOCELL ARRANGEMENTS

FIELD OF THE INVENTION

The present invention relates to femtocell arrangements.

BACKGROUND

Femtocells (also referred to as “Femtos” in this specification) are low power,
5 low cost, generally user-deployed base stations that are able to provide exceptional
cellular service in residential or enterprise environments, with a typical coverage
range of tens of meters. They have extensive auto-configuration and self-optimization
capabilities to enable a simple ‘plug and play’ deployment, and are designed to
automatically integrate themselves in an existing macrocellular network. Femtocells
10 typically use the customer’s broadband internet connection (e.g. Digital Subscriber
Line (DSL), cable, etc.) as backhaul.

A typical femtocell architecture is shown in Figure 1, where the ‘Home cell’
shown on the right hand side is a femtocell and is connected to a Home cell, or
Femtocell, Controller/Gateway. In the particular architecture illustrated, elements on
15 the left hand side of the figure are included in a Universal Mobile
Telecommunications System (UMTS) macrocellular network, and include a base
station known as a NodeB, a Radio Network Controller (RNC), Mobile Switching
Centre (MSC), Serving GPRS Support Node (SGSN), and Gateway GPRS Support
Node (GGSN). Usually there is a connection to a public switched telephone network
20 (PSTN).

In UMTS femtocell arrangements, the number of primary scrambling codes
(PSC) which may be allocated to a Femto is limited. The number that can be allocated
is typically between 6 and 16. The selection of a primary scrambling code is typically
auto-configured by the femtocells themselves based on measurements of other
25 primary scrambling codes used in their vicinity. Therefore, in typical femtocell
deployments, these scrambling codes will need to be heavily re-used. With a high
level of PSC re-use, it is likely that a user equipment (UE) served by a macro cell, or a
femtocell, that measures femtocells, will report the same PSC from a number of

- 2 -

different cells. As currently defined in 3rd Generation Partnership Project (3GPP) standards, a UE does not provide the Cell ID in its UE measurement report. Therefore, it is difficult for the target network to use measurements supplied by the UE to automatically determine the actual target cell when performing either macro to Femto, or Femto to Femto Handover procedures.

When handling an incoming handover request from a macro cell, the Home Cell Gateway must be able to determine to which femtocell the UE is handing over. Efficient determination and subsequent reporting of the target cell for a handover procedure is an important requirement in maintaining a high quality of service to the UEs, since any interruption to an on-going session on the UE needs to be minimised. However existing 3GPP standard messages do not provide a mechanism for the source cell to uniquely identify the target cell, as the UE will not report the Cell ID of the target cell in measurement reports to the source cell. The UE is able to report the PSC of the target cell. However, when PSCs are re-used, the Gateway cannot rely on the reported value of the target cell PSC to uniquely identify it. Similarly for Femto to Femto Handovers, the source femtocell also must be able to determine the target femtocell for the handover to complete effectively, but again, the target cell may not be uniquely identified where there is a high level of PSC re-use.

Where the Gateway, or the source Femto, is not able to uniquely determine the target femtocell from the information provided by the UE in the source cell, it makes it difficult for the Gateway or source Femto to decide to which femtocell the Handover Request should be forwarded. This is especially important when considering a typical Enterprise/Office building which is likely to have many femtocells deployed.

One possible approach is for the Femto Gateway to make a guess about the correct target femtocell using the limited information provided as part of the handover request. This solution is likely to lead to an increase in the duration of the handover procedure, which may in turn impact the end user's on-going call, for example, leading to packet loss or even call drop.

- 3 -

Another possible approach is to prepare handover on all Femtos with the same PSC. However it will be appreciated that such an approach is extremely wasteful of resources and may soon become unmanageable as the number of deployed femto base stations and user equipment increases.

5 Enterprise users tend to pay a premium to an operator in return for the provision of a higher quality of service compared to standard users. Hence any degradation to that service is potentially significant as it can negatively impact the enterprise user's perception of the value they are receiving from paying for that premium service.

10 BRIEF SUMMARY

 According to the invention, a femtocell arrangement comprises a plurality of femtocells deployed over a region. A border femtocell at an entrance to the region is configured to operate at a higher transmit power level than neighboring femtocells to provide a larger area coverage than that provided by neighboring femtocells. By
15 operating border femtocells at a higher transmit power than other femtocells in a building, for example, this tends to "attract" UEs as they roam towards the building. This assists with the UEs attaching, and hence attempting to handover, to the border femto cells, rather than to any of the other femtocells that may be installed in the building. As the Femto Gateway is aware that any attachment is likely to be to a
20 border Femto, it facilitates handover by aiding the identification of the target femtocell. The region over which the plurality of femtocells is deployed may be, for example, an office, a building, an outdoor area, or partially outdoors and partially indoors.

 In one embodiment, the border femtocell has an assigned primary scrambling
25 code (PSC) that identifies it as a border femtocell. The special PSC assists the Femto Gateway to make a swift identification as to which femtocell a UE is handing over to, as the number of entrances and hence number of "border" femto cells is likely to be a small number in comparison to the number of other femtocells deployed in such an environment. This has the advantage of minimising the delay in the Femto network
30 when handling an incoming handover request, hence reducing the risk of impacting

- 4 -

the quality of service to the end user. The special PSC may be assigned to a border Femto by the femto management system, based on knowledge of where it is deployed, for example, at the entrance to a building. This contrasts with the approach described previously in which PSCs are autoconfigured and not specially assigned to a specific
5 Femto or specific Femtos.

In one embodiment, the border femtocell has different access control requirements to non-border femtocells. Such a scheme may be useful when considering a typical company office, having femtocells deployed throughout and a border Femto at its entrance. Visitors to a company are not permitted to connect to
10 most of femtocells in the building, which are reserved for internal users only, but are still provided a connection via the border femtocell with wider access permissions.

The invention may be applied to a deployment of femtocells using procedures and information which are compatible with 3GPP R99 compliant UEs and hence does not require a standards change from that currently proposed.

15 BRIEF DESCRIPTION OF THE DRAWINGS

Some embodiments of the present invention will now be described by way of example only, and with reference to the accompanying drawings, in which:

Figure 1 schematically illustrates a typical femtocell base station architecture;

Figure 2 schematically illustrates for explanatory purposes an arrangement not
20 in accordance with the invention;

Figure 3 schematically illustrates a femtocell arrangement in accordance with the invention; and

Figure 4 schematically illustrates messaging associated with the operation of the arrangement shown in Figure 3.

25

DETAILED DESCRIPTION

With reference to Figure 2, which is an illustrative arrangement not in accordance with the invention and provided for the purposes of understanding, an office building has a plurality of femtocells, Femto 1 to Femto 13, deployed within it.

- 5 -

Those Femtos located at the edge of the office radiate outside it. Hence, when a UE approaches the entrance to the office, as shown, it may attempt to attach to any femtocell that meets its handover criteria. For example, the UE 2 may equally attempt to attach to Femto 1, 2, or 3 as it approaches the entrance to the office. Depending on
5 the number of PSCs re-used within the deployment, the Femto Gateway may not be able to make a unique identification of the handover target cell from the information it receives from the UE. Thus, handover may be delayed and adversely affect the operation of the UE.

With reference to Figure 3, in an arrangement in accordance with the
10 invention, a plurality of Femtos 1 to 13 is deployed in an office or other space, such as, for example, a university campus. There are two entrances to the space, shown at the top and bottom boundaries. The Femto 3 having a coverage area that encompasses the top entrance, is arranged to be operated at a higher transmit power than adjacent Femtos 1, 2 and 4, such that its coverage extends more widely. Femto 3 constitutes a
15 border Femto and is allocated a specific PSC, which in this embodiment is PSC #3, to denote its status. At the lower entrance, Femto 10 is similarly arranged to have a wider coverage area than others adjacent to it and is also allocated the same PSC #3 as Femto 3 to denote that it is a border Femto. The PSC #3 is not re-used elsewhere within the office.

20 In Figure 3, the UE 1 is about to enter the office at the bottom entrance and UE 2 at the top. As the UEs 1 and 2 approach the building, they attempt to attach to the border femtocells 10 and 3 respectively in preference to the other deployed cells because border femtocells 10 and 3 have wider coverage than their neighbors. For example, UE 1 will attach to femtocell 10 in preference to femtocell 8 or femtocell 7.
25 This therefore assists the Femto Gateway in identifying which femtocell a UE is attempting to handover to when it receives an incoming Handover Request, since it will most likely be one of the border Femto cells deployed at the entrances to the office or other space. The use of a special PSC then reduces the number of femtocells that the Gateway would consider as the handover target, for example the information
30 provided by UE 1 in its measurement report will include the PSC of the target

- 6 -

femtocell. In this example this should be femtocell 10. Since only the border Femto cells 10 and 3 have the same PSC, the Gateway quickly reduces the number of candidate handover target cells to these two. It then forwards the handover request to both these cells and subsequently the UE will attach to only one. Alternatively, the
5 Gateway may use additional information to make a decision on the most likely border cell and initially forwards the handover request to that candidate.

Figure 4 provides an example of the sequence where the Gateway forwards a request to both border cells, Femtos 3 and 10, of the arrangement shown in Figure 3.

As UE 1 roams towards the building, it sends a measurement report to the
10 Macro Cell RNC (step (a)), indicating that the new cell (in this case Femto 10) is provides a much better quality signal than the existing macro cell. UE1 is “attracted” to Femtocell 10 in preference to other deployed femto cells, since it is transmitting at a higher power.

(b) The macro cell RNC sends a Relocation Required message to the Core
15 Network (CN).

(c) Core Network sends corresponding Relocation Request message to the Femto Gateway, including the PSC of the target Cell (PSC 3).

(d) The Gateway uses the provided measurement information to determine that UE 1 is attempting to handover to one of the border Femto Cells.

20 (e) Gateway forwards the Relocation Request to Femto 10 and Femto 3.

(f) Femto Cell 10 and Femto 3 both respond, followed by acknowledgement and Relocation command back to the macro cell RNC.

(g) Subsequently, UE 1 performs a Handover to Femtocell 10 and prepared resources in Femto 3 are cancelled (h).

25 In a deployment such as that illustrated in Figure 3, the majority of femtocells may only be accessible to UEs that are associated with the company that is based in that office. Therefore, whenever a visitor visits the office it is likely that their UE will not be allowed to access the femtocells deployed there. This can have negative impacts on the “visiting” UE, as it may attempt to handover to Femtos that it is not
30 allowed to access, leading to a degradation in service and potential call drops. A

- 7 -

company can designate the border Femtocells Femto 3 and 10 at the entrances to the building with a different access control requirement from that of other deployed femtocells. Hence “visiting” UEs may be allowed access to the border cells which cover areas within the building most frequently used by visitors. This permits them
5 continuity of service, but also allows the hosting company to maintain restricted access to the other femtocells providing coverage within their office.


The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of
10 the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes that come within the meaning and range of equivalency of the claims are to be embraced within their scope.

- 8 -

CLAIMS

1. A femtocell arrangement comprising a plurality of femtocells deployed over a region and a border femtocell at an entrance to the region being configured to operate at a higher transmit power level than neighboring femtocells to provide a larger area coverage than that provided by neighboring femtocells.
5
2. The arrangement as claimed in claim 1 and wherein the border femtocell has an assigned primary scrambling code (PSC) that identifies it as a border femtocell.
- 10 3. The arrangement as claimed in claim 1 or 2 and wherein the border femtocell has different access control requirements to non-border femtocells.
4. The arrangement as claimed in claim 1, 2 or 3 and including a plurality of entrances to the region, each having associated therewith a border femtocell arranged to operate at a higher transmit power level than neighboring femtocells to provide a larger coverage area than that provided by neighboring femtocells.
15
5. The arrangement as claimed in claim 4 and wherein each of the border femtocells has the same PSC.
20
6. The arrangement as claimed in any preceding claim and wherein the region is an office building.
7. The arrangement as claimed in any preceding claim and wherein, during handover of a user equipment (UE) to a femtocell of the plurality, a handover request from a femto gateway is received by a border femtocell in preference to non-border femtocells.
25

1/4




BS—Base station
 IP—Internet Protocol
 GGSN—Gateway GPRS support node
 GPRS—General packet radio service
 MSC—Mobile switching center

PSTN—Public switched telephone network
 RNC—Radio network controller
 SGSN—Serving GPRS support node
 UMTS—Universal Mobile Telecommunications System

FIG. 1

2/4

**FIG. 2**




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2010/003790

A. CLASSIFICATION OF SUBJECT MATTER

INV. H04W52/24

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

H04W

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPQ-Internal, WPI Data, COMPENDEX, INSPEC, IBM-TDB

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2008/057658 A (MOTOROLA INC [US]; PADFIELD DAVID C [GB]; FOSTER GERARD T [GB]; LOPES) 15 May 2008 (2008-05-15) * abstract page 3, line 8 - page 25, line 11 figures 1-7	1-7
X	US 2007/097939 A1 (NYLANDER TOMAS [SE] ET AL) 3 May 2007 (2007-05-03) * abstract paragraph [0032] - paragraph [0082] figures 1-5	1-7
X	US 2009/097448 A1 (VASUDEVAN SUBRAMANIAN [US] ET AL) 16 April 2009 (2009-04-16) * abstract paragraph [0007] - paragraph [0053] figures 1,2	1-7
	----- -/--	



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 October 2010

Date of mailing of the international search report

04/11/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Körbler, Günther

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2010/003790

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	CHOWDHURY M Z ET AL: "Handover between macrocell and femtocell for UMTS based networks" ADVANCED COMMUNICATION TECHNOLOGY, 2009. ICACT 2009. 11TH INTERNATIONAL CONFERENCE ON, GIRI, PISCATAWAY, NJ, USA, 15 February 2009 (2009-02-15), pages 237-241, XP031446109 ISBN: 978-89-5519-138-7 * abstract section 3.1 section 3.2 section 4 figures 4-7 -----	1-7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2010/003790

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2008057658 A	15-05-2008	GB 2443236 A	30-04-2008
US 2007097939 A1	03-05-2007	NONE	
US 2009097448 A1	16-04-2009	CN 101822101 A	01-09-2010
		EP 2201803 A1	30-06-2010
		KR 20100068427 A	23-06-2010
		WO 2009051642 A1	23-04-2009