

(43) International Publication Date
5 February 2015 (05.02.2015)(51) International Patent Classification:
H04N 5/225 (2006.01)(21) International Application Number:
PCT/IB2014/063393(22) International Filing Date:
24 July 2014 (24.07.2014)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/861,185 1 August 2013 (01.08.2013) US(71) Applicant: COREPHOTONICS LTD. [IL/IL]; 3rd Floor,
25 Habarzel St., Ramat Hachayal, 6971035 Tel-Aviv (IL).(72) Inventors: SHABTAY, Gal; 4 Shmuel Shnitzer St.,
6958313 Tel Aviv (IL). COHEN, Noy; Apt. 20, 30
Shlomo Ben Yossef St., 6912529 Tel Aviv (IL).
GOLDENBERG, Ephraim; 32 Tel Chai St., 7751025
Ashdod (IL). GEVA, Nadav; 3 Vormaiza St., 6264203 Tel
Aviv (IL). GIGUSHINSKI, Oded; 23 Ahi Dakar St.,
4670223 Herzlia (IL).(74) Agent: NATHAN & ASSOCIATES PATENT AGENTS
LTD.; P.O.Box 10178, 6110101 Tel Aviv (IL).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME,
MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ,
OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,
SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM,
ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report (Rule 48.2(g))

(54) Title: THIN MULTI-APERTURE IMAGING SYSTEM WITH AUTO-FOCUS AND METHODS FOR USING SAME




FIG. 5B

(57) Abstract: Dual-aperture digital cameras with auto-focus (AF) and related methods for obtaining a focused and, optionally optically stabilized color image of an object or scene. A dual-aperture camera includes a first sub-camera having a first optics bloc and a color image sensor for providing a color image, a second sub-camera having a second optics bloc and a clear image sensor for providing a luminance image, the first and second sub-cameras having substantially the same field of view, an AF mechanism coupled mechanically at least to the first optics bloc, and a camera controller coupled to the AF mechanism and to the two image sensors and configured to control the AF mechanism, to calculate a scaling difference and a sharpness difference between the color and luminance images, the scaling and sharpness differences being due to the AF mechanism, and to process the color and luminance images into a fused color image using the calculated differences.

THIN MULTI-APERTURE IMAGING SYSTEM WITH AUTO-FOCUS AND METHODS FOR USING SAME

CROSS REFERENCE TO RELATED APPLICATIONS

This application is related to and claims priority from US Provisional Patent Application No. 61/861,185 filed August 1, 2013 and having the same title, which is incorporated herein by reference in its entirety.

5 FIELD

Embodiments disclosed herein relate in general to digital cameras and in particular to thin multi-aperture digital cameras with auto-focus.

10 BACKGROUND

In recent years, mobile devices such as cell-phones, tablets and laptops have become ubiquitous. Most of these devices include one or two compact cameras – a main rear-facing camera (i.e. a camera on the back side of the device, facing away from the user and often used for casual photography) and a secondary front-facing camera (i.e. a camera located on
15 the front side of the device and often used for video conferencing).

Although relatively compact in nature, the design of most of these cameras is very similar to the traditional structure of a digital still camera, i.e. they comprise an optical component (or a train of several optical elements and a main aperture) placed on top of an image sensor. The optical component (also referred to as "optics") refracts the incoming light
20 rays and bends them to create an image of a scene on the sensor. The dimensions of these cameras are largely determined by the size of the sensor and by the height of the optics. These are usually tied together through the focal length ("f") of the lens and its field of view (FOV) – a lens that has to image a certain FOV on a sensor of a certain size has a specific focal length. Keeping the FOV constant, the larger the sensor dimensions (e.g. in an X-Y
25 plane), the larger the focal length and the optics height.

As the dimensions of mobile devices shrink, the compact camera dimensions become more and more a key factor that limits the device thickness. Several approaches have been proposed to reduce the compact camera thickness in order to alleviate this constraint.

Recently, multi-aperture systems have been proposed for this purpose. In such systems, instead of having one aperture with one train of optical elements, the camera is divided into several apertures, each with dedicated optical elements, all apertures sharing a similar field of view. Hereinafter, each such aperture, together with the optics and the sensor area on which the image is formed, is defined as a "sub-camera". Typically, in multi-aperture camera designs, each sub-camera creates a smaller image on the image sensor compared with the image created by a reference single-aperture camera. Therefore, the height of each sub-camera can be smaller than the height of a single-aperture camera, reducing the total height of the camera could be reduced and allowing for slimmer designs of mobile devices.

FIG. 1A and FIG. 1B show a schematic design of a traditional camera and of a dual-aperture camera with two sub-cameras, respectively. A traditional camera **100'** in FIG. 1A includes an image sensor **102** placed on a substrate **104** and a lens **106**. A "camera height" is defined as the height of the camera module, from substrate **104** to the top of lens **106**. A dual-aperture camera **100''** in FIG. 1B includes two sub-cameras, a sub-camera 1 with an image sensor **112a** and a lens **116a** with an optical axis **118a**, and a sub-camera 2 with, an image sensor **112b** and a lens **116b** with an optical axis **118b**. The two sensors are placed on, respectively, substrates **114a** and **114b**. For comparison's sake, it is assumed that the reference single-aperture camera and the dual-aperture camera have the same field of view (FOV) and the sensors have the same pixel size. However, image sensor **102** has a higher resolution (number of pixels) compared with image sensor **112a** or image sensor **112b**, and is therefore larger in size. The potential advantage in camera height of the dual-aperture camera (i.e. the thickness from substrate **114a** to the top of lens **116a** and from substrate **114b** to the top of lens **116b**) may be appreciated.

There are several significant challenges involved in multi-aperture camera designs. First and foremost, the sensor area of each sub-camera is smaller compared with that of a single-aperture camera. If the pixel size in each sub-camera sensor is kept the same as that in the single-aperture camera sensor, the resolution of an image captured by each sub-camera is smaller than that captured by the single-aperture camera. If the resolution of the output image is to be kept the same, the images from the different sub-cameras need to be combined into a higher-resolution image. This is usually done in the digital domain, by a dedicated algorithm. Several methods have been proposed for combining lower-resolution images to produce a higher-resolution image. Some algorithms in such methods require a registration step between the set of low-resolution images, to account for parallax (which is present in a multi-aperture camera system due to the shift in point-of-view between sub-cameras). One such

algorithm is described in co-assigned PCT patent application PCT/IB2014/062180 titled "Dual aperture zoom digital camera", which is incorporated herein by reference in its entirety.

Another challenge relates to the requirement that the camera provides an in-focus image for a wide range of object distances (usually from several centimeters to infinity in compact camera modules). To fulfill this requirement, a single-aperture camera may include an Auto-Focus (AF) mechanism that controls the focus position of the optics, by moving the optical element along the optical axis, thus changing its height above the sensor. In multi-aperture cameras, in order to support an in-focus image for a wide range of object distances, a straightforward approach would be to provide a dedicated AF mechanism in each sub-camera. This approach has several drawbacks including increased size and cost of the camera, higher operating power and more complicated control, as the AF mechanisms of each sub-camera needs to be synchronized, to ensure all of the sub-cameras are focused to the same position.

Another complication that may arise when using an AF mechanism in a multi-aperture camera is connected with the algorithm that combines the lower resolution sub-camera images to produce a higher resolution image. Since an AF mechanism moves the optical element along the optical axis above the sensor, it scales the image that is formed on the sensor to some extent. Slight differences between the focusing positions of different AF mechanisms in each sub-camera may result in different scales applied to the lower resolution sub-camera images. Such differences in scale may degrade the performance of the image registration step in the algorithm. Correcting for the different scale is not trivial, due to the dynamic nature of the scale - the scale applied on the image depends on the focus position of the optics, which in turn changes with object distance. This means that the scale cannot be trivially corrected by calibrating the multi-aperture camera and applying a fixed correction, but rather, the correct scale has to be estimated at each image. Estimating the correct scale to apply from the image is not trivial, in the presence of parallax (where different objects appear at different locations as a function from their distance from the camera) and in the presence of possible occlusions of objects in one aperture but not in the other. There is therefore a need for a method that can accurately estimate and correct differences in scaling on a per-image basis.

As an alternative to using AF, multi-aperture camera designs have been proposed with no AF mechanism at all. Such designs rely on the smaller focal length of each sub-camera to provide increased depth-of-focus (DOF) compared with a corresponding single-aperture camera that supports a larger sensor. Since a larger DOF means that a wider range of object

distances is imaged in-focus onto the sensor, the AF mechanism could be removed. While this approach is advantageous in terms of cost, size and system complexity, the larger DOF that results from the shorter focal length of a multi-aperture camera is often insufficient to support an in-focus image for object distances ranging from a few centimeters to infinity. In these cases, settling for a multi-aperture camera with fixed-focus optics results in poor imaging performance at close object distances.

Between using multiple AF mechanisms and using only fixed-focus optics, there is a need for a multi-aperture camera system that combines the benefits of an AF mechanism without adding additional complexity and cost to the camera system.

SUMMARY

Embodiments disclosed herein provide designs of a multi-aperture camera with an AF mechanism, describe an algorithm that dynamically corrects for scale differences between sub-camera images, and propose a color filter array (CFA) design that may result in higher resolution and sensitivity when combining sub-camera images, compared with standard CFAs.

In various embodiments, there are provided dual-aperture digital cameras with auto-focus (AF) for imaging an object or scene, each such dual-aperture digital camera comprising a first sub-camera that includes a first optics bloc and a color image sensor with a first number of pixels, the first camera operative to provide a color image of the object or scene, a second sub-camera that includes a second optics bloc and a clear image sensor having a second number of pixels, the second sub-camera operative to provide a luminance image of the object or scene, the first and second sub-cameras having substantially the same field of view, an AF mechanism coupled mechanically at least to the first optics bloc, and a camera controller coupled to the AF mechanism and to the two image sensors and configured to control the AF mechanism, to calculate a scaling difference and a sharpness difference between the color and luminance images, the scaling and sharpness differences being due to the AF mechanism, and to process the color and luminance images into a fused color image using the calculated differences.

The first number of pixels and second number of pixels may be equal or different. The first and second images sensors are formed on a single substrate. The first sub-camera may include an infra-red (IR) filter that blocks IR wavelengths from entering the color image sensor and the second sub-camera may be configured to allow at least some IR wavelengths

to enter the clear image sensor. In some embodiments, the color image sensor may include a non-standard color filter array (CFA).

In an embodiment, the AF mechanism may be coupled mechanically to the first optics bloc, and the second optics bloc may have a fixed focus position. In an embodiment, the fixed focus position may be such that a DOF range of the second sub-camera is between infinity and less than about 100 cm. In an embodiment, the AF mechanism may be coupled mechanically to the first and second optics blocs and operative to move them together in a direction common to respective optics bloc optical axes.

In an embodiment, the camera may further comprise an optical image stabilization mechanism coupled mechanically to the first and second optics blocs and in a direction perpendicular to respective optics bloc optical axes to optically stabilize the AF fused color image.

In an embodiment there is provided method for obtaining a focused color image of an object or scene using a dual-aperture camera, comprising the steps of obtaining simultaneously an auto-focused color image and an auto-focused or fixed focus luminance image of the object or scene, wherein the color image has a first resolution, a first effective resolution and a first signal-to-noise ratio (SNR), and wherein the luminance image has a second resolution, a second effective resolution and a second SNR, preprocessing the two images to obtain respective rectified, normalized and scale-adjusted color and luminance images considering scaling and sharpness differences caused by the AF action, performing local registration between the rectified, normalized and scale-adjusted color and luminance images to obtain registered images, and fusing the registered images into a focused fused color image.

In an embodiment, the step of preprocessing to obtain scale-adjusted color and luminance images includes calculating a set of corresponding points in the color and luminance images, extracting a single coordinate from each corresponding point and using the single coordinate to estimate a scaling factor S between the color and luminance images. The extracted coordinate is Y and the scaling factor S may be given by $S = (Y2' * W * Y2) \backslash Y2' * W * Y1$, where $Y1$ is a vector of Y coordinates of points taken from one image, $Y2$ is a vector of Y coordinates of points taken from the other image, and W is a diagonal matrix that holds the absolute values of $Y2$.

In an embodiment, a method may further comprise using scaling factor S to scale one of the images to match the other image, thereby obtaining the registered images.

In an embodiment, a method may further comprise optically stabilizing the obtained

color and luminance images.

BRIEF DESCRIPTION OF THE DRAWINGS

5 Non-limiting examples of embodiments disclosed herein are described below with reference to figures attached hereto that are listed following this paragraph. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein, and should not be considered limiting in any way.

FIG. 1A shows schematically the design of a traditional digital camera;

10 FIG. 1B shows schematically the design of a dual-aperture camera;

FIG. 2 shows schematically an embodiment of a dual-aperture imaging system with auto-focus disclosed herein, in (a) a general isomeric view, and (b) a sectioned isomeric view;

15 FIG. 3 shows an embodiment of an image sensor for the imaging system in FIG. 2, in which one sub-camera has a CFA sensor, while another sub-camera has a clear sensor;

FIG. 4A shows schematically in a flow chart an embodiment of a method disclosed herein;

FIG. 4B shows in a flow chart details of the scale adjustment step in the method shown in FIG. 4A;

20 FIG. 4C shows two images with corresponding points;

FIG. 5A shows schematically another embodiment of a dual-aperture imaging system with a single auto-focus mechanism disclosed herein in a sectioned isomeric view;

Fig. 5B shows schematically in a flow chart an embodiment of a method for auto-focus imaging with the imaging system in FIG. 5A;

25 FIG. 6 shows schematically yet another embodiment of a dual-aperture imaging system numbered with a single auto-focus mechanism in a sectioned isomeric view.

DETAILED DESCRIPTION

30 FIG. 2 shows schematically an embodiment of a dual-aperture imaging system with auto-focus disclosed herein and numbered **200**, in (a) a general isomeric view, and (b) a sectioned isomeric view. In the following description, "imaging system" and "camera" may be used interchangeably. System **200** comprises two sub-cameras, labeled **202** and **204**, each sub-camera having its own optics. Thus, sub-camera **202** includes an optics bloc **206** with an

aperture **208** and an optical lens module **210**, as well as a sensor **212**. Similarly, sub-camera **204** includes an optics bloc **214** with an aperture **216** and an optical lens module **218**, as well as a sensor **220**. The sensors are also referred to henceforth as "sensor 1" (**212**) and "sensor 2" (**220**). Note that the two sensors may be implemented as two distinct areas on the same substrate, and not necessarily as two stand-alone sensors. Each optical lens module may include several lens elements as well as an Infra-Red (IR) filter **222a, b**. In some embodiments, some or all of the lens elements belonging to different apertures may be formed on the same substrate. The two sub-cameras are positioned next to each other, with a small baseline **224** between the two apertures **208** and **216**. Each sub-camera further includes an auto-focus mechanism, respectively **226** and **228**.

The sensors used in each sub-camera may have different color filter arrays (CFAs). In some embodiments, sensor 1 may have one type of CFA, while sensor 2 may have another type of CFA. In some embodiments, sensor 1 may have a CFA and sensor 2 may have a "white" or "clear" filter array (marked by "W") – in which all the pixels absorb the same wide range of wavelengths, e.g. between 400nm and 700nm (instead of each pixel absorbing a smaller portion of the spectrum). A sensor having a color filter array may be referred to henceforth as a "color image sensor", while a sensor with a clear or W filter array is referred to as a "clear image sensor".

FIG. 3 shows a sensor embodiment **300**, where numeral "1" represents sensor 1 (with a CFA) and numeral "2" represents sensor 2 (with a clear "white" filter array). Circles **302a, 302b** mark image circles formed by the optics on the sensors, while a white area **304** marks the substrate on which the sensors are located. Circles **302a, 302b** may be larger than the respective size of the sensor the image is formed on. In some cases, overlap between the two image circles may occur and mechanical light blocking elements (e.g., walls) may be needed to prevent optical cross-talk between the sub-cameras. By using a CFA on sensor 1, sub-camera 1 captures the color information about the scene, while sub-camera 2 captures luminance information about the scene.

The CFA of sensor 1 may be standard or non-standard. As used herein, a "standard CFA" may include a known CFA such as Bayer, RGBE, CYYM, CYGM and different RGBW filters such as RGBW#1, RGBW#2 and RGBW#3. "Non-standard" CFA patterns may exemplarily include repetitions of a 2x2 micro-cell in which the color filter order is RRBB, RBBR or YCCY where Y=Yellow = Green + Red, C = Cyan = Green + Blue; repetition of a 3x3 micro-cell in which the color filter order is GBRRGBBRG (e.g. as in sensor 1 in FIG. 3A); and repetitions of a 6x6 micro-cell in which the color filter order is one

of the following options:

1. Line 1: RBBRRB. Line 2: RWRBWB. Line3: BBRBRR. Line 4: RRBRBB. Line 5: BWBRWR. Line 6: BRRBBR.
2. Line 1: BBGRRG. Line 2: RGRBGB. Line 3: GBRGRB. Line 4: RRGBBG. Line 5: BGBRGR. Line 6: GRBGBR.
3. Line 1: RBBRRB. Line 2: RGRBGB. Line 3: BBRBRR. Line 4: RRBRBB. Line 5: BGBRGR. Line 6: BRRBBR.
4. Line 1: RBRBRB. Line 2: BGBRGR. Line 3: RBRBRB. Line 4: BRBRBR. Line 5: RGRBGB. Line 6: BRBRBR.

10

The CFA pattern of sensor 1, utilizing some of the non-standard CFAs listed above has an advantage over the standard Bayer pattern in that it divides the red, green and blue colors evenly across the sensor pixels. This results in a finer sampling of red and blue colors, while the green color experiences coarser sampling compared with the standard Bayer pattern. However, as the image captured by sensor 2 is used to extract luminance information about the scene (instead of relying on the green channel for that, as is the case when using a Bayer CFA), the green pixels are used only for color information.

In traditional compact camera design, a filter that lets in light in the visible range and blocks light in the IR range is typically placed in the optical path, sometimes as part of a cover glass that protects the sensor. Although the blocking of IR light wastes photons, it allows for a more accurate estimation of the color in the scene, as it reduces color crosstalk from the spectral response of the R, G and B color filters (which may be sensitive to IR light). In an embodiment, clear sensor 2 is made sensitive to IR light by removing the IR filter or by redesigning its spectral response to let in some light in the IR range. The motivation for capturing IR light, in addition to light in the visible range, is to increase the Signal-to-Noise Ratio (SNR) in the image, as many natural and artificial light sources also emit photons in the IR spectrum. Unlike a sensor with a color CFA (i.e. sensor 1), absorption of IR light does not introduce color cross-talk in clear sensor 2 (since the sensor records a panchromatic image of the scene).

Removing the IR filter may have some negative implications on image quality. For example, extending the range of wavelengths that are captured by the camera may lead to longitudinal chromatic aberrations that may degrade the Point Spread Function (PSF), resulting in a blurrier image. To address this issue, in an embodiment, the optics of sub-camera 2 are optimized across both the visible and the IR range, to mitigate the effect of

chromatic aberrations and to result in a more compact PSF compared with standard compact camera optics that use an IR filter. This is unlike the standard optimization process, which considers only wavelengths inside the visible range.

In use, the two sub-cameras share a similar FOV and have substantially equal (limited
5 only by manufacturing tolerances) focal lengths. An image capture process is synchronized, so that the two sub-cameras capture an image of the scene at a particular moment. Due to the small baseline between the two apertures (which could be only a few millimeters, for example 6.5mm or 8.5mm) of the sub-cameras, the output images may show parallax, depending on the object distances in the scene. A digital image processing algorithm
10 combines the two images into one image, in a process called "image fusion". Henceforth, the algorithm performing this process is called "image fusion algorithm". The resulting image may have a higher resolution (in terms of image pixels) and/or a higher "effective resolution" (in terms of the ability to resolve spatial frequencies in the scene, higher "effective resolution" meaning the ability to resolve higher spatial frequencies) and/ or a higher SNR
15 than that of one sub-camera image.

In terms of resolution and exemplarily, if each sub-camera produces a 5 megapixel (2592x1944 pixels) image, the image fusion algorithm may combine the two images to produce one image with 8 megapixel (3264x2448 pixels) resolution. In terms of effective resolution, assuming that an imaged object or scene includes spatial frequencies, the use of a
20 dual-aperture camera having a clear sensor and a color sensor as disclosed herein leads to an overall increase in effective resolution because of the ability of the clear sensor to resolve higher spatial frequencies of the luminance component of the scene, compared with a color sensor. The fusion of the color and clear images as performed in a method disclosed herein (see below) adds information in spatial frequencies which are higher than what could be
25 captured by a color (e.g. Bayer) sub-camera.

In order to generate a higher-resolution or higher effective resolution image, the image fusion algorithm combines the color information from sub-camera 1 with the luminance information from sub-camera 2. Since clear sensor 2 samples the scene at a higher effective spatial sampling rate compared with any color channel or luminance thereof in the
30 color sensor 1, the algorithm synthesizes an image that includes information at higher spatial frequencies compared with the output image from sub-camera 1 alone. The target of the algorithm is to achieve a spatial resolution similar to that obtained from a single-aperture camera with a sensor that has a higher number of pixels. Continuing the example above, the algorithm may combine two 5 megapixel images, one color and one luminance, to produce

one 8 megapixel image with information content similar to that of a single-aperture 8 megapixel color camera.

In addition to improved spatial resolution, the image fusion algorithm uses the luminance information from clear sensor 2 to generate an image with increased SNR, vs. an image from a corresponding single-aperture camera. The fact that the pixels of sensor 2 are not covered by color filters allow each pixel to absorb light in a wider wavelength spectrum, resulting in a significant increase in the light efficiency compared with a color CFA camera. In an embodiment, the fusion of clear image information and color image information then provides a +3dB SNR increase over that of a single aperture digital camera.

As clear sensor 2 is more sensitive than color sensor 1, there may be a need to adjust exposure times or analog gains to match the digital signal levels between the two cameras. This could be achieved by fixing the same exposure times to both sensors and configuring a different analog gain to each sensor, or by fixing the analog gain in both sensors and configuring a different exposure time to each sensor.

FIG. 4A shows schematically, in a flow chart, an embodiment of a method disclosed herein. FIG. 4B shows in a flow chart details of the scale adjustment step in the method shown in FIG. 4A. Two images **400a** and **400b** from respectively sub-cameras 1 and 2 serve as inputs. The two images undergo pre-processing, in respectively step **402a** for the color image of sensor 1 and **402b** for the luminance image of sensor 2. Step **402a** includes digital image signal processing (ISP) in an ISP pipeline. The ISP generates a full color image, with R, G, B values at each image pixel. If the CFA pattern on sensor 1 is non-standard, the ISP includes non-standard demosaicing to interpolate the missing colors at each pixel location. In addition to demosaicing, other standard ISP pipeline algorithms may be applied on the image, e.g., black level correction, defect pixel correction, noise removal, etc, as known in the art. The luminance image from sub-camera 2 is also pre-processed to correct for defects, noise, shading profile, blur and other optical, analog and digital aberrations. Normalization, rectification and scale adjustment are then applied on the two images in step **404**. First, the two images are normalized to have the same mean signal intensity and standard deviation (which is a measure for the image dynamic range). This is done by subtracting the mean from each pixel and dividing each pixel by the standard deviation in each image. Then, the images are rectified by applying two projection matrices, in order to correct for different rotations around the x, y and z axes, to correct for x-y translations of the optical center of the two cameras and to fix lens distortions. The projection matrices parameters are pre-calculated from calibration data, which may be acquired through a calibration step that is applied for

each camera module during camera module assembly. The data may be saved in one-time programmable memory or EEPROM in the camera module. After the rectification step, epipolar lines in both images are more-or-less parallel to the horizontal axis of the image, in case the two sub-cameras are positioned one beside the other along the X-axis, or parallel to the vertical axis of the image, in case the two sub-cameras are positioned one beside the other along the Y axis.

The scale adjustment, done after the rectification step, is described now in more detail with reference to FIGS. 4B. Preprocessed and rectified images **418a** and **418b** (also shown exemplarily in FIG. 4C) from respectively sub-cameras 1 and 2 serve as inputs. In step **420**, corresponding points between the two images are found. In an embodiment, the set of corresponding points is calculated over the entire image. In another embodiment, the set of corresponding points is found for a specific region of interest (ROI) in each image. FIG. 4C, which shows schematically two images A and B of the same scene captured by adjacent cameras (i.e. A captured by sub-camera 1 and A' captured by sub-camera 2) with some parallax – due to the different viewpoint, objects are imaged with some displacement in one image compared with the other, depending on their distance from the cameras. Pairs of features a - a', b- b' and c - c' represent the same "corresponding points" in the two images A and A'. An algorithm is used to find corresponding points between the two images. A set of prominent points are found (e.g. corners) in the two images and then the algorithm finds matches between the points in the two images. Such algorithms are known to the skilled in the art. In step **422**, the Y coordinate only is extracted in order to estimate the scale between the two images. Since the position of the optics, which is controlled by the AF mechanism, may introduce different scales between the two sub-camera images, the proper scale needs to be determined for each captured image (i.e. for each focus position). Assuming the two sub-cameras are positioned adjacent to one another along the X-axis, once corresponding pairs of points are found, a single coordinate is extracted from each point in step **422**. That is, the algorithm considers only their Y coordinate and disregards their X coordinate. The inventors have advantageously realized that while the X coordinate may be affected by parallax, the Y coordinate is largely unaffected by parallax after the rectification step, and therefore the Y coordinates can be used to estimate the scale more robustly. If the two sub-cameras are positioned adjacent along the Y-axis, then once corresponding pairs of point are found, the algorithm considers only their X coordinate and disregards their Y coordinate. Continuing with the assumption of the two sub-cameras being adjacent along the X-axis, the Y coordinates of the corresponding points are used to estimate a scaling factor S between the

images in step **424**. In an exemplary embodiment, the scaling factor estimation is performed using least-squares, in which case S is given by

$$S = (Y2' * W * Y2) \backslash Y2' * W * Y1$$

5

where $Y1$ is a vector of Y coordinates of points taken from one image, $Y2$ is a vector of Y coordinates of points taken from the other image, and W is a diagonal matrix that holds the absolute values of $Y2$. Scaling factor S is then used in step **426** to scale one image in order to match the scale between the two images. In step **426**, point coordinates in each image are multiplied by the same scaling factor S . Finally, in step **428**, the corresponding pairs of scaled points are used to calculate a shift in x and y axes between the two images for each axis. In an embodiment, only a subset of the corresponding points that lie in a certain ROI is used to calculate the shift in x and y . For example, the ROI may be the region used to determine the focus, and may be chosen by the user or the camera software (SW). The estimated shift is applied on one of the images or on both images. The result of the scale adjustment process in FIG. 4B (and in step **404**, FIG. 4A) are scaled images **430**.

15

Returning now to FIG. 4A, local registration and parallax correction to estimate a disparity map are applied to the scaled images in step **406**. The local registration uses scale and shift parameters found in step **404**. Fusion to enhance the resolution and improve SNR in the final image is then performed in step **408**, by combining information from both images, according to the disparity map. The fusion process uses the image from sub-camera 1 as a baseline. The output is a fused image **410**. Post-processing such as tone mapping, gamma correction, contrast enhancement and color correction/enhancement may then be applied to the fused image.

25

Auto-Focus

As mentioned with respect to FIG. 2, a camera system disclosed herein includes an AF mechanism that controls the focus position of the optics. The system shown in FIG. 2 includes two such AF mechanisms. FIG. 5A shows schematically another embodiment of a dual-aperture imaging system numbered **500** with a single auto-focus mechanism in a sectioned isomeric view. System **500** includes in addition to the regular image sensors and optics only one AF mechanism **502**, positioned in a color sub-camera 1. A luminance sub-camera 2 does not have an AF mechanism, being instead a fixed-focus camera, with the focus fixed to a certain object distance. The focus position is such that the DOF range of sub-

30

camera 2 is between infinity and several tens of centimeters, depending on the focal length and optical design. For example, the DOF may be between infinity and 50cm, such that sub-camera 2 would produce sharp images for object distances that lie within this range from the camera. In system **500**, sub-camera 1 can produce an image in which the main object is in focus for a wide range of object distances, so that it appears sharp in a sub-camera 1 image, by changing the focus position of the optics.

Fig. 5B shows schematically in a flow chart an embodiment of a method for image fusion using an imaging system **500** that has AF. Two images **500a** and **500b** from respectively sub-cameras 1 and 2 serve as inputs. A focus position is chosen for sub-camera 1 in step **502**. A check is performed in step **504** to determine whether the distance of an imaged object lies within the DOF of sub-camera 2, by calculating a sharpness metric on the images of sub-cameras 1 and 2, as known in the art. The calculation of the sharpness metric may result in a sharpness difference. If the answer in the check of step **504** is "Yes", the object will appear sharp in the sub-camera 2 image. In such a case, image fusion as described above is applied to the object image obtained by both sub-cameras in step **506** to achieve higher output resolution and better SNR. If the answer to check **504** is "No" (i.e. the object lies closer to the camera, outside the DOF range of sub-camera 2), the object will appear blurry (not sharp) in the sub-camera 2 image. In this case, the image from sub-camera 2 is not used to enhance the resolution, but only to improve the SNR of the image from sub-camera 1. To this end, another algorithm (procedure) similar to the fusion algorithm (procedure) above is applied in step **508**. The image from sub-camera 1 is scaled to the proper output size and a de-noising algorithm that uses information from the sub-camera 2 image is applied. Since in this case high frequencies are lost in the sub-camera 2 image (due to defocus), the algorithm only considers information at low spatial frequencies from the image of sub-camera 2. In order to determine the object distance, the chosen focus position of the AF mechanism of sub-camera 1 is used (after the focusing process has converged).

FIG. 6 shows schematically yet another embodiment of a dual-aperture imaging system numbered **600** with a single AF mechanism in a sectioned isomeric view. Similar to system **500**, system **600** includes in addition to the regular image sensors and optics only one AF mechanism **602**. However, in contrast with AF mechanism **502**, AF mechanism **602** moves the optics of sub-camera 1 and the optics of sub-camera 2 together. The optical elements are mounted on a lens holder **604** with dedicated threads to hold the two lenses, which is moved by the AF mechanism. Since the optics of sub-camera 1 and sub-camera 2 have very similar focal lengths, the mechanical movement brings the image from sub-camera

1 and from sub-camera 2 to focus at the same time. The advantage of this construction over having only one AF mechanism is that both sub-cameras support the same range of object distances, so that the image fusion algorithm can be applied for the entire range. When the AF mechanism chooses the best focus position for the lens, information from both sub-camera images can be taken into account (e.g. to assist in focusing in low-light situations). In low-light, AF sharpness measurements are noisier, due to the lower SNR in the images. Using two images instead of one can help reduce the noise and improve the robustness and accuracy of the AF process (algorithm).

In an embodiment, some or all the optical elements of sub-camera 1 and sub-camera 2, are made on the same die, using wafer-level optics manufacturing techniques or injection molding of glass or plastic materials. In this case, the single AF mechanism moves the optical dies on which the optical elements of the two sub-cameras are fabricated, so that the two optical stacks move together.

In another embodiment, a camera is similar to camera 500 and includes a single AF mechanism placed on sub-camera 1 (with the color CFA). Sub-camera 2 does not have an AF mechanism, but uses instead fixed focus optics with unique characteristics that provide extended depth of focus, which is achieved by means of optical design (e.g., by employing optics with narrower aperture and higher F-number). The optical performance of the optics of sub-camera 2 is designed to support sharp images for object distances between infinity and several cm from the camera – in this case, the fusion algorithm can be applied to enhance output resolution for a wider range of object distances compared with the single AF embodiment described above. There is usually a tradeoff between the DOF of the camera and the minimal achievable PSF size across the DOF range. An algorithm may be used to enhance the sharpness of the image captured by sub-camera 2 before the fusion algorithm is applied to combine the photos. Such an algorithm is known in the art.

To conclude, dual-aperture cameras and methods of use of such cameras disclosed herein have a number of advantages over single aperture cameras, in terms of camera height resolution, effective resolution and SNR. In terms of camera height, in one example, a standard 8Mpix 1/3" camera with a 70 degree diagonal FOV may have a module height of 5.7mm. In comparison, a dual-aperture camera disclosed herein, with two 5Mpix 1/4" image sensors (one color and one clear), each with 70 degrees diagonal field of view may have a module height of 4.5mm. In another example, a standard 8Mpix 1/3" camera with a 76 degree diagonal FOV may have a module height of 5.2mm. In comparison, a dual-aperture camera disclosed herein, with two 5Mpix 1/4" image sensors (one color and one clear), each with a

76 degree diagonal FOV, may have a module height of 4.1 mm.

While this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of the embodiments and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited
5 by the specific embodiments described herein, but only by the scope of the appended claims. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present application.

WHAT IS CLAIMED IS:

1. A dual-aperture digital camera with auto-focus (AF) for imaging an object or scene, comprising:
 - a) a first sub-camera that includes a first optics bloc and a color image sensor with a first number of pixels, the first camera operative to provide a color image of the object or scene;
 - b) a second sub-camera that includes a second optics bloc and a clear image sensor having a second number of pixels, the second sub-camera operative to provide a luminance image of the object or scene, wherein the first and second sub-cameras have substantially the same field of view;
 - c) an AF mechanism coupled mechanically at least to the first optics bloc; and
 - d) a camera controller coupled to the AF mechanism and to the two image sensors and configured to control the AF mechanism, to calculate a scaling difference and a sharpness difference between the color and luminance images, the scaling and sharpness differences being due to the AF mechanism, and to process the color and luminance images into a fused color image using the calculated differences.
2. The camera of claim 1, wherein the AF mechanism is coupled mechanically to the first optics bloc and wherein the second optics bloc has a fixed focus position.
3. The camera of claim 2, wherein the fixed focus position is such that a depth of field range of the second sub-camera is between infinity and less than about 100 cm.
4. The camera of claim 1, wherein the AF mechanism is coupled mechanically to the first and second optics blocs and operative to move them together in a direction common to respective optics bloc optical axes.
5. The camera of claim 4, further comprising an optical image stabilization mechanism coupled mechanically to the first and second optics blocs and operative to move them together in a direction perpendicular to respective optics bloc optical axes to optically stabilize the AF fused color image.
6. The camera of claim 1, wherein the first number of pixels and second number of pixels are equal.

7. The camera of claim 1, wherein the first number of pixels and the second numbers of pixels are different.
8. The camera of claim 1, wherein the first and second images sensors are formed on a single substrate.
9. The camera of claim 1, wherein the first sub-camera includes an infra-red (IR) filter that blocks IR wavelengths from entering the color image sensor and wherein the second sub-camera is configured to allow at least some IR wavelengths to enter the clear image sensor.
10. The camera of claim 1, wherein the color image sensor include a non-standard color filter array (CFA).
11. The camera of claim 10, wherein the non-standard CFA includes a repetition of a 3x3 micro-cell in which the color filter order is GBRRGBBRG.
12. A method for obtaining a focused color image of an object or scene using a dual-aperture camera, comprising the steps of:
 - a) obtaining simultaneously an auto-focused (AF) color image and an auto-focused or fixed focus (FF) luminance image of the object or scene, wherein the color image has a first resolution, a first effective resolution and a first signal-to-noise ratio (SNR), and wherein the luminance image has a second resolution, a second effective resolution and a second SNR;
 - b) non-standard preprocessing the two images to obtain respective rectified, normalized and scale- adjusted color and luminance images considering scaling and sharpness differences caused by the AF action;
 - c) performing local registration between the rectified, normalized and scale-adjusted color and luminance images to obtain registered images; and
 - d) fusing the registered images into a focused fused color image.
13. The method of claim 12, wherein the step of preprocessing to obtain scale-adjusted color and luminance images includes calculating a set of corresponding points in the color and luminance images, extracting a single coordinate from each corresponding point and using the single coordinate to estimate a scaling factor S between the color and luminance images.

14. The method of claim 13, wherein the extracted coordinate is Y and wherein the scaling factor S is given by $S = (Y2' * W * Y2) \backslash Y2' * W * Y1$, wherein Y1 is a vector of Y coordinates of points taken from one image, Y2 is a vector of Y coordinates of points taken from the other image, and W is a diagonal matrix which holds the absolute values of Y2.

15. The method of claim 14, further comprising the step of using scaling factor S to scale one of the images to match the other image, thereby obtaining the registered images.

16. The method of claim 12, further comprising the step of optically stabilizing the obtained color and luminance images.




FIG. 1A





FIG. 1B



300




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C

500




FIG. 5A




FIG. 5B

600




FIG. 6