



US008281561B2

(12) **United States Patent**
Dow et al.

(10) **Patent No.:** **US 8,281,561 B2**
(45) **Date of Patent:** ***Oct. 9, 2012**

(54) **FLEXIBLE DRAPER BELT DRIVE FOR AN AGRICULTURAL HARVESTING MACHINE**

(75) Inventors: **Chad A. Dow**, East Moline, IL (US);
William P. Conrad, Evanston, IL (US);
Jeffrey A. Nelson, Moline, IL (US);
Benjamin M. Lovett, Colona, IL (US);
Amy C. Berg, Milan, IL (US); **Eric D. Taflinger**, Eldridge, IA (US)

(73) Assignee: **Deere & Company**, Moline, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 30 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **12/858,184**

(22) Filed: **Aug. 17, 2010**

(65) **Prior Publication Data**

US 2012/0042617 A1 Feb. 23, 2012

(51) **Int. Cl.**
A01D 43/00 (2006.01)

(52) **U.S. Cl.** 56/181

(58) **Field of Classification Search** 56/181,
56/185, 192, 14.5, 15.8, 208
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,792,691	A *	2/1931	Harris et al.	56/181
5,471,289	A *	11/1995	Sato et al.	399/328
6,202,397	B1 *	3/2001	Watts et al.	56/208
7,600,364	B2 *	10/2009	Lovett et al.	56/181
7,640,720	B1 *	1/2010	Lovett et al.	56/181
7,788,891	B2 *	9/2010	Puryk et al.	56/181
8,065,865	B1 *	11/2011	Dow et al.	56/181

* cited by examiner


Primary Examiner — Alicia Torres

(74) *Attorney, Agent, or Firm* — Taylor IP, P.C.

(57) **ABSTRACT**

An agricultural harvesting machine including a flexible cutterbar and associated draper belts for carrying cut agricultural material to a center location. The belts are guided by a drive rollers and idler rollers. The idler roller for each belt is pivotable about an axis generally at 90 degrees to the axis of the belt and the drive roller for each belt is translatable axially to minimize diagonal stresses caused by flexing of the elongated endless belt.

14 Claims, 4 Drawing Sheets






FIG. 1




Fig. 2






Fig. 3



1

FLEXIBLE DRAPER BELT DRIVE FOR AN AGRICULTURAL HARVESTING MACHINE

FIELD OF THE INVENTION

The present invention relates to agricultural harvesting machines, such as combines, and, more particularly to agricultural harvesting machines including a cutting platform with a belt conveyor.

BACKGROUND OF THE INVENTION

An agricultural harvesting machine such as a combine includes a head and a feeder housing which remove the crop material from the field, gather the crop material and transport the crop material to a separator. In the case of thinner stemmed crops such as soybeans, wheat, etc. which may be cut with a sickle bar carrying a plurality of knives, the head may also be known as a cutting platform. The separator removes the grain crop material from the non-grain crop material. The grain is cleaned and deposited in a grain tank. When the grain tank becomes full, an unloading auger which is positioned alongside the combine during harvesting is moved to the unloading position in which the auger extends approximately perpendicular to the longitudinal axis of the combine. The combine drives alongside a vehicle into which the grain is to be unloaded, such as a semi-trailer, and the unloading auger is actuated to discharge the grain into the vehicle.

A cutting platform may generally be of two types. One type typically has a sheet metal floor with a dual feed auger near the rear of the cutting platform for feeding the crop material longitudinally to the feeder housing. A cutting platform of this type with auger feed is relatively common.

Another type of cutting platform, also known as a draper platform, utilizes a flat, wide belt, referred to as a draper or draper belt to convey crop material. The arrangement and number of belts vary among platforms. One style of draper platform has two or more side belts that convey crop material longitudinally, to the center of the platform, where a center feed belt moves the crop material laterally into the feeder housing. Each belt is wrapped around a pair of rollers, one being a drive roller and the other being an idler roller. An example of this type draper arrangement is disclosed in U.S. Pat. No. 6,202,397, which is assigned to the assignee of the present invention.

An advantage of a draper platform is that larger amounts of crop material can be transported without plugging, etc. For example, with wide platforms approaching 40 feet or even larger, the amount of crop material transported to the feeder housing can be substantial. With an auger feed platform, the crop material may bind between the auger and the back wall of the platform. In contrast, with a draper platform, the crop material is carried on top of the belt with less chance for plugging.

Advanced draper platforms provide a flexible cutting platform that follows the undulations of the field to more effectively collect crop material. The more effective arrangement for a flexible cutterbar assembly is to have a series of pivotally connected float arms where the pivot point of the float arms is as close to the surface of the field as practical. This feature allows greatly reduced draft loads when the agricultural harvester is traversing a field. In addition, it more effectively collects crop material that is close to the ground. While providing superior harvesting, this arrangement provides additional loads on the draper belt that is used to carry the crop material to a center section for processing. This is because the

2

pivot point of the float arm, which journals the rollers for the belt, is not in line with the longitudinal rotational axis of the drive and idler rollers. As a result, the flexing of the rollers during movement through a field causes diagonal stresses on the rollers, which can lead to misalignment.

What is needed in the art, therefore, is an arrangement that minimizes the stress loading on a draper belt used in a flexible cutterbar assembly.

SUMMARY OF THE INVENTION

The invention, in one form, is a flexible draper belt assembly for an agricultural harvesting machine movable in a given direction in which the assembly has at least one endless elongated belt positioned generally laterally with respect to the direction of movement of the agricultural machine. The endless belt extends over an idler roller and a drive roller and one of the rollers is translatable along its rotational axis to alleviate diagonal stresses on the endless elongated belt.

In another form, the invention includes a cutting platform for use with an agricultural harvesting machine having at least one platform section including a frame and a plurality of float arms pivotally coupled with the frame. An endless belt is carried by the plurality of float arms and a cutterbar assembly is also carried by the plurality of float arms. The endless belt and cutterbar assembly are movable in a localized manner across the cutting platform in upwards and downwards directions. The endless belt extends over an idler roller and a drive roller carried by float arms and one of the idler and drive roller is translatable along its axis to alleviate diagonal stresses on the endless belt.

In yet another form, the invention is an agricultural harvesting machine including a feeder housing, a cutting platform attached to the feeder housing with the cutting platform including at least one platform section having a frame. A plurality of float arms are pivotally coupled with the frame and an endless belt is carried by the plurality of float arms, as well as a cutterbar assembly. The cutterbar assembly is movable in a localized manner across the cutting platform in upwards and downwards directions. The endless belt is positioned over idler and driver rollers and one of the idler and drive roller are movable in an axial direction to alleviate diagonal stresses on the belt.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a fragmentary, top view of an agricultural combine including a cutting platform embodying the present invention;

FIG. 2 is a fragmentary, perspective view of the agricultural combine of FIG. 1;

FIG. 3 is a fragmentary, cross section view of the leading edge of the cutting platform shown in FIGS. 1 and 2;

FIG. 4 is a perspective view of driver rollers for a draper platform shown in FIGS. 1-3;

FIG. 5 is fragmentary, sectional view of the mounting for the drive rollers shown in FIG. 4.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, and, more particularly to FIGS. 1, 2, and 3, there is shown an agricultural harvesting machine in the form of a combine 10 including an embodiment of a cutting platform 12 of the present invention. Combine 10 includes a feeder housing 14 which is detachably coupled with cutting platform 12. Feeder housing 14 receives the crop material from cutting platform 12, both grain and

3

non-grain crop material, and transports the crop material to a separator within combine **10** in known manner (not shown). The grain crop material is separated from the non-grain crop material, cleaned and transported to a grain tank. The non-grain crop material is transported to a chopper, blower, etc. in known manner and distributed back to the field.

Cutting platform **12** generally includes a plurality of platform sections **16**, **18** and **20**, a cutterbar assembly **22** and a reel assembly **24**. Each platform section **16**, **18** and **20** generally includes a frame **26**, a plurality of float arms **28** coupled with a respective frame **26** at pivot points **27**, a cutterbar **30** carried by the outboard ends of respective float arms **28**, a plurality of endless belts **32**, and a plurality of belt guides **54**.

As specifically shown in FIG. **3**, cutterbar assembly **22** includes cutterbars **30** carried at the outboard ends of float arms **28** (i.e., at the leading edge of a platform section **16**, **18** or **20**). Each cutterbar **30** includes a plurality of knives **42** carried by a bar (not specifically shown). The bar is formed from a metal which is flexible to an extent allowing a desired degree of flexure across the width of cutting platform **12**. In the embodiment shown, a majority of each cutterbar **30** is carried by a respective first platform section **18** or second platform section **20**, with a lesser extent at the adjacent inboard ends of each cutterbar **30** being carried by center platform section **16**.

A plurality of knife guards **46** are positioned in opposition to knives **42** for providing opposing surfaces for cutting the crop material with knives **42**. A plurality of keepers **48** spaced along cutterbars **30** have a distal end above cutterbars **30** for maintaining cutterbars **30** in place during reciprocating movement.

Float arms **28** are pivoted at their connection locations **27** with a respective frame **26**. A float cylinder (not shown) coupled between a respective frame **26** and float arm **28** may be used for raising or lowering the outboard end of float arm(s) **28** at the leading edge of cutting platform **12**. Each float cylinder may also be placed in a "float" position allowing the connected float arm **28** to generally follow the ground contour during operation. More particularly, each float cylinder is fluidly connected with an accumulator (also not shown) carried by a platform section **16**, **18** or **20**. An accumulator (not shown) allows fluid to flow to and from attached float cylinders such that no pressure build-up occurs. In this manner, the pistons associated with each float cylinder are free to move back and forth longitudinally, thereby allowing float arms **28** to follow the ground contour. When not in a float mode, float cylinders can be actuated to move float arms **28** in an upward or downward direction. In the embodiment shown, each float cylinder may be a hydraulic cylinder, but could possibly be configured as a gas cylinder for a particular application.

Each float arm **28** is also associated with a respective guide **54**. The plurality of guides **54** for each platform section **16**, **18** and **20** carry and are positioned within the loops of a plurality of endless belts **32** described in detail below.

Depending upon the width, reel assembly **24** may include two reels **56**, center reel support arm **58** and a pair of outer reel support arms **60**. Outer reel support arms **60** are pivotally coupled at one end thereof with an outboard end of a respective first platform section **18** or second platform section **20**. Outer reel support arms **60** rotationally carry a respective reel **56** at an opposite end thereof. Each outer reel support arm **60** may be selectively moved up and down using a hydraulic cylinder, and the pair of hydraulic cylinders are typically coupled in parallel so that they move together upon actuation.

Center reel support arm **58** is pivotally coupled at one end thereof with center platform section **16** above the opening

4

leading to feeder housing **14**. Center reel support arm **58** rotationally carries an inboard end of each reel **56** at an opposite end thereof. A hydraulic motor **62** or other suitable mechanical drive rotationally drives each reel **56**. More particularly, hydraulic motor **62** drives a common drive shaft **64** through a chain and sprocket or other suitable arrangement (not shown). The rotational speed of reels **56** can be adjusted by an operator by adjusting the rotational speed of hydraulic motor **62**. Depending upon the width of platform **12**, only one reel may be used. Center reel support arm **58** may be selectively moved up and down using a hydraulic cylinder (not shown).

Referring to FIGS. **4** and **5**, the endless belts **32** extend between drive rollers **70** and idler rollers (not shown). The idler rollers are remote from the drive rollers and, together with the drive rollers **70**, provide the function of journals about which the belt **32** extends for rotation to deliver crop inward towards the center of the work machine. The rollers additionally position the belt **32** axially so that it cooperates with the associated components of the cutterbar assembly **22**. FIG. **2** shows a portion of the belt **32** wrapped around a drive roller **70**. The idler rollers are positioned at the opposite end of the respective belts and, in the illustrated embodiment, provide rotation about an axis for movement of the draper belt **32** but, in addition, have the ability to pivot through a limited arc about an axis that is generally at 90 degrees to the general plane of each draper belt **32**. The idler rollers for the outermost end of the cutting platform additionally provide a tensioning function for both belts on the respective platform sections in a known manner. As herein shown, the agricultural harvesting machine **10** has a total of four laterally extending belts **32**, each of which has a corresponding drive roller **70** and idler roller. It should be apparent, however, to those skilled in the art that there may be more or less belts and still function in accordance with the invention.

As stated previously, the cutterbar assembly **22** has the ability to move in a localized up and down fashion to closely follow the contour of the field being harvested. Because the pivot **27** is significantly lower than rotational axis of the rollers **70** to improve draft loads, this movement causes diagonal stresses in the endless belt **32**.

In accordance with the present invention, the drive rollers **70** are translatable in a fore and aft direction to minimize, if not eliminate, stresses occurring because of flexing of the cutterbar assembly **22**. The drive rollers **70** are journaled within a carriage **72**, having a forward plate **74**, connecting rods **76**, and a rear housing **78**. The drive rollers **70** are appropriately journaled at plate **74** and at housing **78**. As shown particularly in FIG. **5**, housing **78** is connected to a float arm **28** at a pivot connection generally indicated by reference character **77** including a pin **80**, secured to the proximal end of float arm **28** and a slide casting **84** embracing the pin **80**. The slide casting **84** is pivotally connected to the housing **78** through a yoke **82** at a pin **86** such that movement fore and aft along the axis of drive roller **70** is permitted by the pivotal connections at pins **86** and **80**. In addition, sideways movement of the carriage **72** is permitted along pin **80** to aid in the tensioning of the belts **32**. Furthermore the yoke **82** also permits limited pivoting motion about an axis that is generally transverse to the plane of the belts **32**.

The rearward movement is limited by a stop **88** that defines the rearmost axial displacement of the housing **78** and, thus, the roller **70**. The forward end of the carriage **72** in the form of the plate **74** slides on a bar associated with the cutterbar assembly **22** and the stop **88** prevents displacement to the extent that the plate **74** would not be supported by the plate

5

associated with the cutterbar. In addition, forward movement is limited by housing 78 abutting slide casting 84.

As illustrated, a pair of drive rollers 70 are in a common carriage 72 and both connect to housing 78. As particularly shown in FIG. 5, housing 78 connects to a gearbox 90 that drives both pairs of rollers 70 in the common direction to cause crop material to flow towards the center of the work machine. Gearbox 90 has a single input 92, which receives a rotary input from a hydraulic motor 94 shown schematically. Thus, the hydraulic motor 94 drives the rollers 70 to move crop inward toward the center of the work machine.

Rollers 70 have a groove 96 that receives a corresponding rib on the inner facing side of belt 32 so as to position it axially.

In operation, the harvesting machine 10 traverses the field and the float arms 28 move up or down as-needed to closely follow the terrain. In the configuration shown, the pivot for the float arms 28 is below the axis of rotation of the drive and idler rollers. This causes flexure and diagonal stresses in the belts 32. By enabling the drive rollers 70 to translate axially, the diagonal stresses on the belt are alleviated and the possibility of misalignment of the belt is substantially minimized.

The pairing of the drive rollers 70 enables a more efficient utilization of the rotary power source, whether it be in hydraulic form, as illustrated, or another. The pivoting connection enabling the translation of the drive rollers provides a robust and effective system that is relatively insensitive to debris and other operational conditions that would prevent movement of the drive rollers 70.

Having described the preferred embodiment, it will become apparent that various modifications can be made without departing from the scope of the invention as defined in the accompanying claims.

The invention claimed is:

1. A cutting platform for use with an agricultural harvesting machine comprising:

at least one platform section including a frame, a plurality of float arms pivotally coupled with said frame, an endless belt carried by said plurality of float arms, a cutterbar assembly carried by said plurality of float arms, said endless belt and said cutterbar assembly being movable in a localized manner across said cutting platform in upwards and downwards direction, and an idler roller and a drive roller over which said endless belt extends, said idler roller and drive roller being carried by a float arm and, wherein one of said idler and drive roller is translatable along its axis to alleviate diagonal stresses on said endless belt wherein said drive roller translates axially relative to said float arm through a pivoting link connection.

2. The cutting platform as claimed in claim 1, wherein said idler roller is pivotable about an axis at right angles with respect to the plane of said elongated belt.

6

3. The cutting platform as claimed in claim 1, having a pair of elongated belts and associated idler and drive rollers.

4. The cutting platform as claimed in claim 1, having two pairs of drive belts and associated idler and drive rollers, said belts having the drive rollers adjacent drive rollers at the point wherein the adjacent belts meet and said belts are driven from a common drive.

5. The cutting platform as claimed in claim 4, further comprising a gear train to couple the drive rollers together for driving by a single rotary power source.

6. The cutting platform as claimed in claim 5, wherein said rotary power source is a hydraulic drive.

7. The cutting platform as claimed in claim 1, wherein the pivot point for said float arms on said frame is below the plane of the endless belt whereby the diagonal stresses of flexible movement of said belt are alleviated by movement of the drive roller along its axis.

8. The cutting platform as claimed in claim 1 further comprising at least one stop to limit fore and aft movement of said drive roller.

9. An agricultural harvesting machine, comprising:

a feeder housing,

a cutting platform attached to said feeder housing, said cutting platform including at least one platform section having a frame,

a plurality of float arms pivotally coupled with said frame, an endless belt carried by said plurality of float arms, and a cutterbar assembly carried by said plurality of float arms and movable in a localized manner across said cutting platform in upwards and downwards directions,

an idler and driver rollers over which said belt is positioned, one of said idler and drive roller being movable in an axial direction to alleviate diagonal stresses on said belt, wherein said drive roller translates in an axial direction and wherein said drive roller is connected to said float arm with a pivoting link.

10. The agricultural harvesting as claimed in claim 9, wherein said idler roller is pivotable about an axis generally at right angles to the plane of said elongated belt.

11. The agricultural harvesting machine as claimed in claim 9, having a pair of elongated endless belts and associated drive and idler rollers.

12. The agricultural harvesting machine as claimed in claim 11, having two pairs of endless belts adjacent to each other and wherein the drive rollers for adjacent belts are at the end adjacent the junction between the belts.

13. The agricultural harvesting machine of claim 12, further comprising a gear box receiving a common input and providing a rotary output to said adjacent drive rollers.

14. The agricultural harvesting machine of claim 13, wherein the rotary input to said gear box is a hydraulic drive.

* * * * *