

(19) **DANMARK**

(10) **DK/EP 3217821 T3**



(12) **Oversættelse af
europæisk patentskrift**

Patent- og
Varemærkestyrelsen

-
- (51) Int.Cl.: **A 41 D 13/00 (2006.01)** **A 41 D 1/04 (2006.01)** **A 41 D 13/012 (2006.01)**
A 41 H 43/04 (2006.01)
- (45) Oversættelsen bekendtgjort den: **2019-04-15**
- (80) Dato for Den Europæiske Patentmyndigheds bekendtgørelse om meddelelse af patentet: **2019-01-02**
- (86) Europæisk ansøgning nr.: **15802186.5**
- (86) Europæisk indleveringsdag: **2015-11-03**
- (87) Den europæiske ansøgnings publiceringsdag: **2017-09-20**
- (86) International ansøgning nr.: **HR2015000019**
- (87) Internationalt publikationsnr.: **WO2016075501**
- (30) Prioritet: **2014-11-11 WO PCT/HR2014/000040** **2015-03-30 HR HR**
2015-03-30 HR P20150352
- (84) Designerede stater: **AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**
- (73) Patenthaver: **Forko, Michel, Bukovac Gornji 126, 10000 Zagreb, Kroatien**
- (72) Opfinder: **Forko, Michel, Bukovac Gornji 126, 10000 Zagreb, Kroatien**
- (74) Fuldmægtig i Danmark: **Plougmann Vingtoft A/S, Strandvejen 70, 2900 Hellerup, Danmark**
- (54) Benævnelse: **HJÆLPEORGAN TIL AT AFTAGE VÅD SPORTSBEKLÆDNING**
- (56) Fremdragne publikationer:
JP-A- 2002 242 008
US-A1- 2006 143 779
US-A1- 2011 277 212

DESCRIPTION

Technical Field

[0001] The present invention discloses a sportswear takeoff helping means that helps in taking off wet sportswear from the wearer, especially the upper part of the sportswear. The said helping means belongs to a technical field dealing with details of garments that have an additional specific technical function.

Technical Problem

[0002] Nowadays healthy life trends include more and more people in various indoor and outdoor sport activities for which a special garment is designed and worn. A part of the mentioned activities is carried out in the sportswear designed to be extremely skintight for the wearer. During the activities the sportswear becomes wet from sweat as a result of the activity, environmental conditions, or both. Once being wet, it has been observed that the upper sportswear is almost impossible to be taken off over the wearer's head. The assistance of a colleague is needed, otherwise there is a high risk of the sportswear damage. This is particularly important for the garment equipped with high-performance, microfiber, polyester fabric that should move sweat away from the body onto the fabric surface, where it evaporates. However, in rainy conditions or while performing demanding exercises, the sportswear tends to become entirely wet and impossible to be taken off.

[0003] So, the primary technical problem is to construct a simple, reliable and aesthetically acceptable helping means that allows the wet sportswear, in particular the upper sportswear designed to be extremely skintight for the wearer, to be simply taken off over the wearer's head.

[0004] Elderly people have problems with taking off T-shirts or similar garments over the head due to their health conditions regarding the spinal column, joints or limbs. Also the obesity may generate similar inability. Therefore, the solution to the primary technical problem can be easily extended to the above-observed problems. According to the invention, if the wearer is capable of touching the neck, than it is possible to use the takeoff helping means according to the invention.

[0005] The above technical problems are solved with a device basically composed from one or more guides equipped with the corresponding, i.e. compatible, drawstrings attached to the hemline situated in the back of the garment that ends with the handgrip. The said guides are situated preferably on the back part of the upper garment; where the guides start near the hemline and go to the garment top in a continuous way or in one or more continuous segments.

Previous State of the Art

[0006] The technical problem which is solved with the present invention is the construction of a novel takeoff helping means that helps in taking off the wet skintight sportswear over the wearer's head. There are well known solutions in the art which comprise zippers or mechanic / magnetic snaps that allow the sportswear to be unzipped or unfastened along one or more hems which facilitate the takeoff procedure. However, such zippers or snaps are also cumbersome to handle by one person, not to mention that such solutions locally change the user's experience in wearing the skintight sportswear.

[0007] The present invention solves the technical problem by lifting a hemline situated on the sportswear back. That is rather different from the below cited well-known solutions. It is instructive to examine the previous state of the art in the segment; i.e. to search for the garment that is equipped with the means for lifting or taking off a garment, or at least a part of it.

[0008] Probably one of the earliest technical solutions, where a part of the garment is lifted, is mentioned in the US 560,683; inventor E. Brückner. The said document teaches about trousers for bicyclist capable to be drawn up to the knees and retained in this shortened condition. The implemented system is composed of drawstrings and appropriate guides with a lock system.

[0009] Document US 724,758; inventor H. M. Todd, teaches about a skirt or train lifter. The object of the said invention is to provide a device adapted to raise and drop the back and side breadths of women's skirts without the necessity of using hands on the said breadths. The invention consist primarily of a wire frame that is attached to the back of the skirt, provided with the suitable loops through which suitable tapes or cords pass adapted to be tied together or otherwise secured at the waist of the wearer.

[0010] Document US 2,127,763; inventor G. B. Bentz, teaches about improvements in overcoats, topcoats, raincoats, capes and the like. The primary focus of the said invention is to prevent the said garment to be dragged down on the floor or to be stepped upon once left on a chair or similar. The contraction of the garment is achieved by the means of cords, tapes, small chains or similar means, that can be fixed to different positions within the garment, thus effectively producing a lifting hemline.

[0011] Document US 5,299,323; inventor A. Schaefer et al., discloses an adjustment system for forming a repeatedly adjustable hem on a garment. The said document provides an adjustment mechanism comprised of a cord with one end that is attached to the garment inside the hem, while the other end passes through a holding pocket or channel that is secured to the garment inside seam. The advantage of the cited invention is in enabling the garment to be conformed to the person without any tailoring skills.

[0012] Document US 5,367,709; inventor N. A. Teasley, discloses adjustable clothing for infants and toddlers that reversibly adjusts in length what accommodates the growth of a child. Adjusting is performed via drawstrings situated in the side seams, and fixing in a desired position is provided via knots formed by the drawstrings.

Document US 2010/0281597; inventor J. A. Lang discloses a partial garment lift/quick-access system for installation in the upper body garment for wearers who have a need for immediate and unobstructed access to the waist/belt line to retrieve essential items. The quick-access system allows the wearer to immediately expose an item at the waist/belt line, for a complete and unobstructed access by pulling a simple cord at the chest pocket. This action produces a curtain-like effect at the bottom hem of the garment; assisting the wearer to make a rapid hand-to-item contact while keeping the hem of the garment suspended for the duration of the required activity.

Document US 2006/0143779; inventor C. Lee discloses an article of clothing with two panels, front and back, that are easily detachable one from another, and which may serve also as a takeoff helping means.

[0013] Document US 2011/277212; inventor C. G. Jones discloses a vest according to the preamble of claim 1 that the user can remove without removing an outer garment such as a coat. The vest utilizes the hook and loop fasteners to allow the back and front to be separated. In order to facilitate the separation, a pull cord is attached at the rear shoulder and crosses the back of the vest and passes through a guide near the opposing hip. When the pull cord is pulled the opposing shoulder that has been separated is peeled back and down across the back allowing the user to remove the vest without removing an overcoat.

[0014] Document JP 2002242008; inventor F. Kawaguchi discloses a bodysuit which has a concise structure and that is easily taken off. The said bodysuit comprises an upper trunk with arm parts and a neck part with an opening, and a lower trunk with leg parts wherein at least one tensile operation member is used for transforming the opening of the neck part in order to be easily taken off.

[0015] From the above-cited documents it is easy to conclude that none of the cited documents solve the takeoff problem observed with the skintight sportswear. The drawstrings or cords are used exclusively to lift trousers, skirts, or similar garments and to adjust or modify the garments appearance and functionality; not to perform the takeoff action for the skintight and wet sportswear; or even regular T-shirts used by elderly or disabled people.

Summary of the Invention

[0016] The present invention discloses a wet sportswear takeoff helping means for the upper sportswear that is worn extremely tight to the wearer's skin and is wet from sweat, as a product of exercise, environmental conditions, or both. The said takeoff helping means consists of one or more guides for guiding the drawstrings and the handgrip used to activate the said takeoff

helping means.

[0017] The one or more guides are made on the back part of the said upper sportswear and are situated on the inner sportswear surface oriented to the wearer's skin, outer sportswear surface or on both sportswear surfaces simultaneously. Each guide has a guide beginning situated close to the hemline from which the said guide propagates to the upper part of the sportswear in a continuous way, or having one or more interruptions formed along the said guide.

Each drawstring is connected with the hemline in the joint region. The said drawstring enters into the corresponding guide beginning, and passes through the corresponding guide till the guide end, or till the connection of the two or more guides. The drawstrings end fixed to the handgrip or fixed to another drawstring within the connection of the two or more guides. Pulling of the handgrip by the wearer's hand causes lifting of the sportswear hemline towards the wearer's neck.

[0018] In one variant each guide is formed from a material which is partially fixed to one of the sportswear sides allowing an unobstructed movement of the corresponding drawstring within. The material used for the guides is fixed to the sportswear via stitching, ultrasound or laser welding, by gluing the said material to the said sportswear; or any other way that is known in the art. In one sub-variant, the material for the guides is selected to be textile material.

[0019] In another variant, the guides are formed via stitches that enclose the drawstrings situated on the back part of the said sportswear. The said stitches were fixed to the sportswear in a way allowing an unobstructed movement of the drawstrings situated between the said stitches and the sportswear. In one-sub variant, the said guides are formed as zigzag stitches.

[0020] The invention also discloses other variants for the drawstrings propagation. The said invention is applicable as an ordinary T-shirt takeoff means helping elderly or disabled people to take off the said upper garment.

Brief Description of Drawings

[0021] Some embodiments were described via figures representing the invention variants. The figures represent the embodiments where the guides are formed on the inner side of the sportswear; the guides being formed as dense zigzag stitching where the drawstrings are inserted into the said guides.

Fig. 1A shows the technical solution with only one drawstring situated centrally on the inner side of the sportswear. Fig. 1B shows the inside construction of the said sportswear when the inner side is turned to be the outer side in order to better depict the technical solution. Fig. 1C shows the way of connecting the drawstring with the hemline, and Fig 1D shows the activation of the said embodiment.

Fig. 2A shows the technical solution with two drawstrings situated on the inner side of the sportswear. Fig. 2B shows the inside construction of the said sportswear when the inner side is turned to be the outer side in order to better depict the technical solution. Fig. 2C shows the activation of the said embodiment.

Fig. 3A shows the technical solution with three drawstrings situated on the inner side of the sportswear. Fig. 3B shows the inside construction of the said sportswear when the inner side is turned to be the outer side in order to better depict the technical solution. Fig. 3C shows the activation of the said embodiment.

Fig. 4A shows the technical solution with three drawstrings, two being connected to the central drawstring and situated on the inner side of the sportswear. Fig. 4B shows the inside construction of the said sportswear when the inner side is turned to be the outer side in order to better depict the technical solution. Fig. 4C shows the activation of the said embodiment.

Fig. 5A shows the technical solution with two intersecting drawstrings situated on the inner side of the sportswear where each drawstring can move independently. Fig. 5B shows the inside construction of the said sportswear when the inner side is turned to be the outer side in order to better depict the technical solution. Fig. 5C shows the activation of the said embodiment.

Fig. 6A shows the technical solution with two drawstrings having the side seams as the guides, situated on the inner side of the sportswear. Fig. 6B shows the inside construction of the said sportswear when the inner side is turned to be the outer side in order to better depict the technical solution. Fig. 6C shows the activation of the said embodiment.

Figs. 7A, 7B and 7C show the technical solution similar to those presented via Figs. 6A, 6B and 6C where an extra guide and a drawstring are added in the manner already depicted via Figs. 1A, 1B, 1C and 1D.

Detailed Description

[0022] The present invention discloses a sportswear takeoff helping means that helps in taking off the wet sportswear from the wearer, especially the upper part of the sportswear. The garment equipped with a high-performance, microfiber, polyester fabric such as Nike's DRI-FIT® is designed to remove sweat away from the body and to the fabric surface, where it evaporates. As the technical result the wearer is dry all the time and does not lose the heat that is necessary for achieving good sports results. The said class of materials is used for many different garments, not only for manufacturing upper sportswear.

[0023] However, in case of rain or heavy exercises being performed, the sportswear becomes entirely wet. In case of the upper sportswear it becomes almost impossible to take it off over the head by the wearer alone. Usually the takeoff procedure requires one person for assistance in order not to damage the skintight sportswear, e.g. during long-distance running,

cycling or extreme climbing. Wet DRY-FIT® or similar garments produce significant friction between the wearer's skin and the said material, and a forced takeoff will result in the garment damage.

[0024] The present invention helps to solve the above-observed technical problems via embodiments described hereby in detail. It discloses a simple, reliable and aesthetically acceptable takeoff helping means for the upper sportswear that is worn extremely tight to the wearer's skin, and which is wet from sweat as a product of exercise, environmental conditions, or both.

[0025] The wet sportswear takeoff helping means for the upper sportswear (10) that is worn extremely tight to the wearer's skin (90) consists of one or more guides (20) for guiding the drawstrings (30) and handgrip (80) used for activation of the said takeoff helping means.

[0026] One or more guides (20) are made on the back part of the said upper sportswear (10) and are situated on the inner sportswear (10) surface oriented to the wearer's skin (90), the outer sportswear (10) surface or on both sportswear (10) surfaces simultaneously. Each guide (20) propagates to the upper part of the sportswear (10) in a continuous way, or having one or more interruptions (24) formed along the said guide (20) as we will discuss in the examples.

[0027] The drawstrings (30) used for activation are connected to the hemline (11) in the joint region (12) as depicted in Fig. 1C. The drawstring (30) can be connected to the hemline (11) by any known method in the art such as: gluing, ultrasound or laser welding. However, the most practical way is to sew the drawstring (30) directly into the hemline (11).

[0028] In the present invention, each drawstring (30) enters into the corresponding guide beginning (21) and passes through the corresponding guide (20) till the guide end (22), or till the connection (23) where this, and possibly other guides (20), are connected together.

[0029] The drawstring material can be selected from the set of suitable materials known in the art, having appropriate tensile strength. As a good example one can use even shoelaces. Each drawstring (30) end fixed to the handgrip (80) or fixed to another drawstring (30) within the connection (23) to other drawstrings (30) where two or more guides (20) are merged together.

[0030] Figs. 1D, 2C, 3C, ... 7C depict the activation of the sportswear (10) takeoff means by pulling off the handgrip (80) by the wearer's hand which causes lifting of the sportswear hemline (11) towards the wearer's neck. It is important to note that the handgrip (80) is situated close to the sportswear (10) top, i.e. within the wearer's neck region. The handgrip (80) can be manufactured from any suitable material known in the art capable of being connected with the used drawstrings (30) and comfortable enough for the wearer, preferably from textile materials, thermoplastic resins or elastomer materials. The guides (20) can be manufactured from any convenient material known in the related art. The material used has to be appropriately fixed to the back side of the sportswear (10), to ensure an unobstructed movement of the corresponding drawstring (30) within the guides (20). Furthermore, the said

material used for the guides (20) is fixed to the back side of the sportswear (10) by any suitable manner known in the art; by sewing / stitching, ultrasound or laser welding or gluing, where the said material together with the material used for the sportswear back forms sleeves that serve as the drawstring (30) guides (20). Preferred material for the guides (30) is any textile material, but the optimal material is any material that has mechanical properties similar to those used to manufacture sportswear.

[0031] In another aspect of the invention, the guides (20) can be formed solely via stitches that enclose the drawstrings (30). The said stitches are fixed to the sportswear (10) in a way that allows an unobstructed movement of the drawstrings (30) situated between the said stitches and the material used to form the sportswear (10). The longitudinal stitches density has to be carefully chosen as well as the stitches tension exerted to the material used for the sportswear in order to maintain an unobstructed movement of the drawstrings (30) in all cases, and to prevent slitting of the sportswear by extreme use. The zigzag stitches are found to be adequate for the above-mentioned task and can be considered as a preferred solution.

Examples - General Remarks

[0032] The following examples, which we will study in more details, use the guides (20) formed as the zigzag stitches which are situated in a way to enclose the drawstrings (30) positioned on the inner side of the sportswear, i.e. oriented towards the wearer's skin (90). These examples do not limit the scope of protection given by the claims and are used solely to demonstrate the simplest possible variants of the present invention.

[0033] A person skilled in the art will, without any difficulties or further assumptions, extend the disclosed teaching to more complex cases.

Example 1 - Uninterrupted Guide

[0034] Figs. 1A-1D depict the construction and use of the takeoff means that consists of only one guide (20) and a drawstring (30). The other side of the sportswear (10), as visible from Fig. 1A, the guide (20) propagates from the guide beginning (21) till the guide end (22) situated close to the neck position of the said sportswear (10), within the region where the wearer can reach it by hand via wearer's shoulder, Fig. 1D.

[0035] In the above-mention case, the guide (20) is formed around the drawstring (30) on the back side of the sportswear (10). Fig. 1B shows the said sportswear (10) and its appearance when the inner side is turned out. In this specific case, the drawstring (30) is positioned on the said inner sportswear (10) side that is previously turned out and then zigzag stitches enclose the drawstring (30) forming the guide (20). The said drawstring (10) can be stitched to the hemline (11) in the joint region (12) before or after the guide (20) is formed, as depicted in Fig.

1C. Another end of the drawstring (10) is attached to the handgrip (80) as shown in Fig 1B.

[0036] Now, the sportswear (10) can be again turned from the state depicted in Fig. 1B where the inner side is turned out again to show the "normal" appearance of the sportswear (10) as seen in Fig 1A where the guide (20) is situated behind the sportswear (10) material used to form the backside.

[0037] The activation of the takeoff helping means is shown in Fig. 1D; the user / wearer tucks the hand beneath the neck portion of the sportswear (10), grabs the handgrip (80) and pulls it up towards the head. This action causes lifting of the hemline (11) resembling another person assisting the wearer in case where the sportswear (10) does not have any takeoff helping means. The wearer grabs the front part of the hemline (11) with another hand so that the wearer can, despite significant friction between the skin (90) and the sportswear (10), lift the said sportswear (10) and take it off without damaging it.

[0038] The handgrip (80) used in the aforementioned example can be manufactured from any suitable material while being big enough to be easily gripped. In addition, it is important for the handgrip (80) to be wider than the guide (20), more precisely, wider than the guide end (22) in order to prevent unwanted entrance of the handgrip (80) into the guide (20). A preferable solution for the handgrip (80) is to be made as a loop of textile material in order to preserve the wearer's comfort. The disadvantage of the disclosed solution is that the force exerted to the joint region (12) might be too high and can damage the sportswear (10) fabrics in the long-term use.

Example 2 - Two Uninterrupted Guides

[0039] Figs. 2A-2C show the construction and use of the takeoff means that consists of two guides (20) and two corresponding drawstrings (30). The guides (20) are formed in the way described in the example 1. The solution with two guides (20) has the advantage over the solution disclosed in the example 1 because the force exerted on each joint region (12), where the drawstrings (30) are attached to the hemline (11), is reduced to 1/2, thus preventing the tearing of the joint region (12). The activation is similar to the procedure already explained in the example 1.

Example 3 - Three Uninterrupted Guides

[0040] Figs. 3A-3C show the construction and use of the takeoff means that consists of three guides (20) and three corresponding drawstrings (30). The guides (20) are formed in the way described in the example 1. The solution with three guides (20) has the advantage over the solution disclosed in the example 1 because the force exerted on each joint region (12), where the drawstrings (30) are attached to the hemline (11), is reduced to 1/3, thus preventing the

tearing of the joint region (12). The activation is similar to that explained in the example 1.

Example 4 - Three Guides

[0041] Figs. 4A-4C show the construction and use of the takeoff means that consists of three guides (20) and three corresponding drawstrings (30). The two of the mentioned guides (20) end in the connection (23) formed on the central guide (20), at approx. 1/2 of its length. The said central guide (20) is propagating from the hemline (11) to the neck part of the sportswear (10).

[0042] This example has two sub-variants; the first one in which all the drawstrings (30) are propagating from the joint region (12) till the handgrip (80), and the second one, where the two side drawstrings (30) ends connected to the drawstring (30) belonging to the central guide (20) in the part where the side guides (20) end in the connection (23). In the latter case, the drawstring (30) belonging to the central guide (20) propagates from the joint region (12) till the handgrip (80).

[0043] Regardless of the sub-variant, as in previous examples the system of drawstrings (30) is prepared and positioned on the outer side of the sportswear (10) as depicted in Fig. 4B. The drawstrings (30) can be immediately fixed to the hemline (11) and/or handgrip (80), or after the guides (20) are formed. Then, the guides (20) are formed around the drawstrings (30) by using zigzag stitches. If the first sub-variant is used than the zigzag stitches for the central guide (20) in the part starting from the connection (23) to the corresponding guide end (22) should be formed slightly wider. Namely, that part should guide all three drawstrings (30) towards the handgrip (80). Once the guides (20) are formed around the drawstrings (30) connected to the hemline (11) and handgrip (80) or other drawstrings (30), the sportswear (10) is turned onto its ordinary wearing side depicted in Fig. 4A where only the stitches are visible. The activation is similar to those explained in the previous examples.

Example 5 - Two Intersecting Guides

[0044] Figs. 5A-5C show the construction and use of the takeoff means that consists of two intersecting guides (20) and two corresponding drawstrings (30) crossing each other in the guides interruption (24) region that overlapped each other.

[0045] As described in the previous examples the system of drawstrings (30) is prepared and positioned on the outer side of the sportswear (10) as depicted in Fig. 5B. The drawstrings (30) can be immediately fixed to the hemline (11) and/or handgrip (80), or after the guides (20) are formed. Then, the guides (20) are formed around the drawstrings (30) by using zigzag stitches. In this example, each guide (20) is formed in two parts; the first part starts from the guide beginning (21) to the interruption (24), and the second part from the interruption (24)

region till the guide end (22). The interruption (24) is depicted in Figs. 5A, 5B and 5C via a dashed circle. In the above-mentioned way, the drawstrings (30) cross each other across the interruption (24) without interference and so the produced technical effect is more or less similar to that described in the example 2.

[0046] Once the guides (20) are formed around the drawstrings (30) connected to the hemline (11) and handgrip (80), the sportswear (10) is turned onto its ordinary wearing side depicted in Fig. 5A where only the stitches are visible. The activation is similar to those explained in the previous examples and depicted in Fig. 5C. It has to be mentioned that by tilting the handgrip (80), if it is formed as a solid body, or by pulling mainly the left or right part of the depicted handgrip (80) it is possible to dose the pulling force exerted on the left or right drawstring (30) and transmitted to the appropriate part of the hemline (11).

Example 6 - Guides as the Side Seams

[0047] Figs. 6A-6C show the construction and use of the takeoff means that consists of two guides (20) and two corresponding drawstrings (30) where the said guides (20) are partially used side seams of the sportswear (10) connecting the front and back part of the said sportswear (10).

[0048] As described in the previous examples the system of drawstrings (30) is prepared and positioned on the outer side of the sportswear (10) as depicted in Fig. 6B. The drawstrings (30) can be immediately fixed to the hemline (11) and/or handgrip (80), or after the guides (20) are formed. Then, the guides (20) are formed around the drawstrings (30) by using zigzag stitches. In this example the sportswear (10) side seams are used as the guide (20) for the drawstring (30) from the hemline (11) to the kinks (25) situated beneath the sleeves. Additional guides (20) that pass from the said kinks (25) towards the neck portion which ends with the guide ends (22) are formed in the manner already explained in the previous examples.

[0049] Once the guides (20) are formed around the drawstrings (30) connected to the hemline (11) and handgrip (80), the sportswear (10) is turned onto its ordinary wearing side depicted in Fig. 6A where only the stitches are visible. The activation is similar to those explained in the previous examples and depicted in Fig. 6C.

Example 7 - Guides as the Side Seams with Additional Central Guide

[0050] Figs. 7A-7C show the construction and use of the takeoff means that consists of three guides (20) and three corresponding drawstrings (30) where two of the said guides (20) are partially used side seams of the sportswear (10) connecting the front and back part of the said sportswear (10), and one guide (20) is a central guide as in the example 1. So, the mentioned solution represents the fusion of the solutions described in the example 6 and example 1; the

way of producing is the same as described in the mentioned examples.

[0051] Once the guides (20) are formed around the drawstrings (30) connected to the hemline (11) and handgrip (80), the sportswear (10) is turned onto its ordinary side depicted in Fig. 7A where only the stitches are visible. The activation is similar to those explained in the previous examples and depicted in Fig. 7C.

Other Variants

[0052] As already mentioned before, the above simple examples serve merely as an illustration of the invention potential. There is also a possibility to form hybrid versions where the guides are formed on both sides of the sportswear (10), or exclusively on the other side which we did not elaborate in the examples. The person skilled in the art will certainly recognize how to form more sophisticated modifications of the present invention. However, having in mind the aesthetic criteria and other factors related to the manufacture, it is to be expected that the most frequent implementation of the disclosed invention will be the solution where the guides are situated in the inner side of the sportswear (10).

[0053] The said invention is possible to be implemented on already formed upper garments that are not worn extremely tight to the wearer's skin, such as ordinary T-shirts. Namely, the present invention can be very easily used in an ordinary upper garment as a takeoff means for helping elderly or disabled people to take off the said upper garment.

Industrial Applicability

[0054] The present invention is suitable as a simple, reliable and aesthetically acceptable helping means that allows the wet sportswear, in particular the upper sportswear designed to be extremely skintight to the wearer, to be simply taken off over the wearer's head. Therefore, the industrial applicability is obvious.

[0055] Considering the fact that elderly people have problems with T-shirts or similar garments when taking them off over the head due to their health condition, the possible application of the mentioned takeoff helping means is wider than initially being contemplated.

[0056] The embodiments hereby mentioned and represented via figures have to be used only as an example of carrying out the invention as defined by the claims. A skilled person in the art will certainly modify the above embodiments to fit a desired fashion potential.

References

[0057]

- 10
 - sportswear
- 11
 - hemline
- 12
 - joint region
- 20
 - guide
- 21
 - guide beginning
- 22
 - guide end
- 23
 - connection
- 24
 - interruption
- 25
 - kink
- 30
 - drawstring
- 80
 - handgrip
- 90
 - skin
- S
 - segment

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US560683A [0008]

- US724758A [0009]
- US2127763A [0010]
- US5299323A [0011]
- US5367709A [0012]
- US20100281597A [0012]
- US20060143779A [0012]
- US2011277212A [0013]
- JF2002242008E [0014]

Patentkrav

1. Hjælpemiddel til at aftage våd sportsbeklædning til en øvre sportsbeklædning (10), der bæres ekstremt tæt til en bærers hud (90) og er våd af sved som et resultat af motion, miljøforhold eller begge dele; **kendetegnet ved at**

5 det nævnte hjælpeorgan til aftagning består af en eller flere føringer (20) til at føre træklinier (30) og et håndgreb (80) anvendt til aktivering af nævnte hjælpeorgan til aftagning;

hvor:

10 de en eller flere føringer (20) er fremstillet på ryggsiden af den nævnte øvre sportsbeklædning (10) og er placeret på den indvendige overflade af sportsbeklædningen (10) orienteret mod bærerens hud (90), udvendige overflade af sportsbeklædningen (10) eller på begge overflader af sportsbeklædningen (10) samtidig; idet hver føring (20) har en føringsbegyndelse (21) placeret tæt på en sømlinje (11) hvorfra den

15 nævnte føring (20) spreder sig til en øvre del af sportsbeklædningen (10) på en kontinuerlig måde eller har en eller flere afbrydelser (24) dannet langs den nævnte føring (20);

hver trækline (30) er forbundet til sømlinjen (11) i et sammenføjningsområde (12), hver trækline (30) går ind i den tilsvarende føringsbegyndelse (21) og passerer gennem den tilsvarende føring (20) til føringsenden (22), eller til forbindelsen (23) af to eller flere føringer (20);

20 hver trækline (30) ender fastgjort til håndgrebet (80) eller fastgjort til en anden trækline (30) inden for forbindelsen (23) af to eller flere føringer (20);

25 hvor det nævnte håndgreb (80) er placeret tæt på sportsbeklædningens (10) øverste del, inden for bærerens halsområde;

hvor det at trække i nævnte håndgreb (80) med bærerens hånd forårsager, at sportsbeklædningens sømlinje løftes (11) mod bærerens hals.

30

2. Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge krav 1, **kendetegnet ved** at hver føring (20) er dannet af materiale, som er delvist fastgjort til en af siderne af sportsbeklædningen (10) og tillader en uafbrudt bevægelse af den tilsvarende trækline (30) inden i, hvor det nævnte materiale til

føringen (20) er fastgjort til sportsbeklædningen (10) via sømning, ultralyd eller lasersvejsning eller ved at lime det nævnte materiale til den nævnte sportsbeklædning (10).

- 5 **3.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge krav 2, **kendetegnet ved** at materialet dertil er valgt til at være tekstilmateriale.
- 4.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge krav 1, **kendetegnet ved** at de nævnte føringer (20) er dannet via sømninger, der omgiver træklinerne (30) placeret på rygside af den nævnte sportsbeklædning (10); idet de nævnte sømninger er fastgjort til sportsbeklædningen (10) på en måde, der tillader en uafbrudt bevægelse af træklinerne (30) placeret mellem de nævnte sømninger og sportsbeklædningen (10).
- 10
- 15 **5.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge krav 4, **kendetegnet ved** at de nævnte føringer (20) er dannet som zigzagsømninger.
- 6.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge et hvilket som helst af de foregående krav, **kendetegnet ved** at hver føring (20) spreder sig fra sømlinjen (11) til området tæt på håndgrebet (80) på en kontinuerlig måde.
- 20
- 7.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge et hvilket som helst af kravene 1-5, **kendetegnet ved** at nogle af føringerne (20) er rettet fra sømlinjen (11) til forbindelsen (23) af to eller flere føringer (20) dannet på en bestemt føring (20), der spreder sig langs rygside af den nævnte sportsbeklædning (10) på en kontinuerlig måde og ender tæt på håndgrebet (80).
- 25
- 8.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge krav 7, **kendetegnet ved** at alle trækliner (30) fra de tilsvarende føringer (20) ender fastgjort til håndgrebet (80) bærerens hals.
- 30
- 9.** Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge krav 7, **kendetegnet ved** at alle trækliner (30) fra føringerne (20), som ender i forbindelsen (23) af to eller flere føringer (20), er forbundet til en trækline (30),

der ender fastgjort alene til håndgrebet (80).

10. Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge et hvilket som helst af kravene 1-5, **kendetegnet ved** at mindst to føringer (20) er dannet med 5 afbrydelserne (24), der overlapper hinanden, så de tilsvarende træklinier (30), ført af de nævnte føringer (20), krydser hinanden i de overlappende afbrydelser (24), og de nævnte træklinier (30) ender fastgjort til håndgrebet (80).

11. Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge et hvilket som
10 helst af kravene 1-5, **kendetegnet ved** at mindst to føringer (20) er placeret inden for sidesømmene, der forbinder de bagerste og forreste dele af nævnte sportsbeklædning (10); idet de nævnte føringer (20) passerer fra sømlinjen (11) på tværs af knækket (25) placeret nedenunder ærmerne, hvorfra nævnte føringer (20) passerer hen mod retningen af håndgrebet (80).

15

12. Hjælpemiddel til at aftage våd sportsbeklædning (10) ifølge et hvilket som helst af de foregående krav, **kendetegnet ved** at alle føringer (20) og tilsvarende træklinier (30) er placeret på den indvendige side af den nævnte sportsbeklædning (10) orienteret mod bærerens hud (90).

20

13. Anvendelse af hjælpeorgan til aftagning af sportsbeklædningen (10) ifølge et hvilket som helst af de foregående krav i en almindelig øvre beklædningsgenstand som et organ til aftagning til at hjælpe ældre eller handicappede med at tage nævnte øvre beklædningsgenstand af.

DRAWINGS




Fig. 1A




Fig. 1B




Fig. 1C




Fig. 1D




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 3A




Fig. 3B




Fig. 3C




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 6A




Fig. 6B




Fig. 6C




Fig. 7A




Fig. 7B




Fig. 7C