




(11) (21) (C) **2,153,233**
(86) 1994/01/04
(87) 1994/07/21
(45) 2000/05/16


(72) Banks, Stewart, CA
(72) Williamson, Nicholas, CA
(72) Jamison, Mark D., US
(72) Roders, George W., US
(72) Banks, Stewart, CA
(73) DEB IP LIMITED, GB
(51) Int.Cl.⁶ A47K 5/12, G01F 11/08
(30) 1993/01/04 (08/000,247) US

(54) **DISTRIBUTEUR DE LIQUIDE AMELIORE**
(54) **IMPROVED FLUID DISPENSER**



(57) L'invention concerne un distributeur de fluide (20) conçu pour distribuer du fluide en provenance d'une poche (200) présentant un passage de décharge s'étendant le long d'une voie tortueuse. Le distributeur (20) est constitué d'une station de distribution dans laquelle est prévu un mécanisme de distribution qui, dans un mode de réalisation, comprend un plot de repos (80) d'un côté de la voie d'écoulement du distributeur et un galet (62) cylindrique à cames (60) en face dudit plot de

(57) A fluid dispenser (20) is disclosed for dispensing a fluid from a pouch (200) having a discharge passage that extends along a tortuous path. The dispenser (20) has a dispenser station and dispenser mechanism in the dispenser station. In one aspect the dispenser mechanism comprises a backstop (80) on one side of the dispenser path and a cam (60) operated cylindrical roller (62) confronting the backstop (80), located on the other side of the dispenser path. The roller (62), is attached to a



(11) (21) (C) **2,153,233**
(86) 1994/01/04
(87) 1994/07/21
(45) 2000/05/16

repos (80), de l'autre côté de la voie d'écoulement du distributeur. Le galet (62) est fixé à un support à galet (68) fixé pivotant à l'intérieur d'un bouton-poussoir creux (44). Ledit bouton-poussoir (44) est monté dans une ouverture située dans le couvercle frontal (14) du distributeur. Des ressorts (78) sont fixés audit support (68) et au couvercle frontal (14) qui maintiennent le galet (62) contre le compartiment flexible (132) de distribution de la poche (200). Lorsque le bouton-poussoir (44) est enfoncé, le galet (62) recouvre la partie supérieure du compartiment de distribution (132) flexible de la poche entre le galet (62) et le plot de repos (80) de manière à fermer hermétiquement le compartiment (130) en son extrémité supérieure. De plus, une pression supplémentaire sur le bouton-poussoir (44) fait descendre le galet (62) dans le compartiment de distribution (132) et provoque l'expulsion du fluide emprisonné dans ce dernier.

roller bracket (68), which is pivotally attached to the interior of a hollow pushbutton (44). The pushbutton (44) is mounted in an opening in the dispenser front cover (14). Springs (78) are attached to the bracket (68) and the front cover (14) which maintain the roller (62) against the flexible dispenser compartment (132) of the pouch (200). Depressing the pushbutton (44) forces the roller (62) to trap the upper portion of the pouch flexible dispenser compartment (132) between the roller (62) and backstop (80) to initially seal the dispenser compartment (130) at its upper end and further pushbutton (44) action forces the roller (62) down the dispenser compartment (132) thereby causing expulsion of the fluid trapped in the dispenser compartment (132).





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁵:A47K 5/12, G01F 11/08 **2153233**

A1

(11) International Publication Number:

WO 94/15515

(43) International Publication Date:

21 July 1994 (21.07.94)

(21) International Application Number: PCT/CA94/00003

(22) International Filing Date: 4 January 1994 (04.01.94)

(30) Priority Data:

000,247

4 January 1993 (04.01.93)

US

(71) Applicant: MARLINGFORD HOLDINGS LIMITED [Stateless/-]; P.O. Box 266, Albert House, South Esplanade, St. Peter Port, Guernsey GY1 3QX (GB).

(71)(72) Applicant and Inventor: BANKS, Stewart [GB/CA]; 26 Myrtleville Drive, Brantford, Ontario N3V 1C1 (CA).

(74) Agents: SCHUMACHER, Lynn, C. et al.; Borges, Hill & Schumacher, 372 Bay Street, Suite 1600, Toronto, Ontario M5H 2W9 (CA).


(81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: IMPROVED FLUID DISPENSER

(57) Abstract

A fluid dispenser (20) is disclosed for dispensing a fluid from a pouch (200) having a discharge passage that extends along a tortuous path. The dispenser (20) has a dispenser station and dispenser mechanism in the dispenser station. In one aspect the dispenser mechanism comprises a backstop (80) on one side of the dispenser path and a cam (60) operated cylindrical roller (62) confronting the backstop (80), located on the other side of the dispenser path. The roller (62), is attached to a roller bracket (68), which is pivotally attached to the interior of a hollow pushbutton (44). The pushbutton (44) is mounted in an opening in the dispenser front cover (14). Springs (78) are attached to the bracket (68) and the front cover (14) which maintain the roller (62) against the flexible dispenser compartment (132) of the pouch (200). Depressing the pushbutton (44) forces the roller (62) to trap the upper portion of the pouch flexible dispenser compartment (132) between the roller (62) and backstop (80) to initially seal the dispenser compartment (130) at its upper end and further pushbutton (44) action forces the roller (62) down the dispenser compartment (132) thereby causing expulsion of the fluid trapped in the dispenser compartment (132).



IMPROVED FLUID DISPENSERFIELD OF THE INVENTION

The present invention relates to fluid dispensers for use with flexible fluid pouches for dispensing fluids such as liquid soaps stored in the pouches.

BACKGROUND OF THE INVENTION

This invention relates to improved fluid dispensers of the type used to dispense liquid soap from a flexible pouch having a tortuous discharge passageway. An example of a pouch of this nature is disclosed in United States Patent No. 4,491,245.

Fluid dispensers for dispensing small quantities of liquid soap from a pouch are well known. U.S. Patents No. 4,463,876 and No. 4,564,127 are directed to typical fluid dispensers which include upper and lower jaws which can be manipulated to sequentially open and close to meter a predetermined quantity of fluid from the container. Difficulty has been experienced with this type of container in obtaining a tight seal between both upper and lower jaws. United States Patent No. 3,881,641 is directed to a dispensing device using peristaltic action to dispense liquid from a bag through an elongate hose.

Other dispensers such as disclosed in United States Patent No. 4,932,562 use hard swash plates or cams having hard surfaces to compress a portion of the pouch for expelling liquid therefrom. A drawback to such arrangements are that the swash plates or cams do not ride smoothly down the pouch since the surfaces thereof are hard with the result that the cam or swash plate jiggles side-to-side causing uneven pressure across the discharge portion of the pouch. Another drawback with current dispensers employing flexible dispenser pouches is that the pouches are designed to be hung from pegs or suspended in the dispenser housing. This necessitates wasting time aligning the dispenser pegs with holes in the pouch. Further, at present the only

AMENDED SHEET

indication that a fluid pouch is nearly empty is when a reduced volume of fluid is being discharged from the pouch.

Accordingly, it would be advantageous to provide a fluid dispenser for dispensing liquids such as soap detergents, foodstuffs and the like which provides smooth fluid expulsion and which is provided with an indicator for indicating that the pouch is nearing empty.

SUMMARY OF THE INVENTION

The present invention provides a fluid dispenser for dispensing fluid from a flexible dispenser compartment of a pouch of the type having a discharge passage that extends along a tortuous path to a discharge opening at a lower end of the pouch. The dispenser housing is provided with a dispenser station through which the fluid is to be dispensed along a dispenser path that extends therethrough. The dispenser housing includes means for supporting the pouch and a backstop on one side of the dispenser path substantially below said support means. The dispenser is provided with cam means having an arcuate face portion confronting the backstop and located on the other side of the dispenser path. A pushbutton means confronts the backstop and engages the cam means. The pushbutton means is pivotally attached to the housing and the cam means is pivotally coupled to the pushbutton means. The dispenser includes spring bias means coupled between the cam means and the dispenser housing. Pushing the pushbutton means toward the backstop causes the cam means to pivot with respect to the pushbutton means and to move downwardly along the backstop and against the action of the spring bias means with the flexible dispenser compartment between the cam means and the backstop thereby expelling a quantity of fluid from the dispenser. The dispenser includes a view port for looking into the interior of the dispenser station and an indicator means engaging the pouch when the pouch is supported within the dispenser housing for indicating when the pouch has been substantially depleted of fluid and in

need of being replaced. The indicator means is a visual indicator means comprising an arm with opposed ends, a visually distinctive portion mounted at one end of the arm and a pouch engagement member attached to the other end of the arm. The arm is pivotally mounted in close proximity to the fluid pouch with the pouch engagement member bearing against the pouch so that when the pouch contains fluid therein the visually distinctive portion is not viewable through the view port and as fluid is depleted from the pouch the pouch collapses causing the arm to pivot until the visually distinctive portion comes into view through the view port.

In another aspect of the invention there is, provided a dispenser for dispensing fluid from a flexible dispenser compartment of a pouch. The dispenser comprises a housing provided with a dispenser station through which the fluid is to be dispensed, the dispenser station being provided with a backstop. The dispenser is characterized in that the housing includes a support member inclined from the vertical, including a retaining plate attached to said backstop and extending upwardly therefrom. The retaining plate includes a cutout portion and the pouch is receivable in the dispenser and cradled between the inclined support member and the retaining plate with the flexible dispenser compartment inserted through the cutout portion and located adjacent to the backstop. The dispenser includes a roller having an axle confronting the backstop, including a roller bracket comprising two spaced arms each provided with means for engaging the axle for rotationally mounting the roller to the roller bracket. The dispenser includes a pushbutton pivotally attached to the housing and the arms are pivotally attached to the pushbutton. A spring bias means is attached at one end thereof to the arms and at the other end thereof to the housing, whereby when the pushbutton is pushed inwardly the roller is pressed against the flexible discharge compartment of the pouch and is forced downwardly along the flexible discharge compartment and the roller

bracket pivots about the pivotal attachment. The dispenser includes an indicator means engaging to the pouch for indicating when the pouch has been substantially depleted of fluid.

BRIEF DESCRIPTION OF THE DRAWINGS

The following is a description, by way of example only, of various embodiments of the fluid dispenser constructed in accordance with the present invention, reference being had to the drawings, in which:

Figure 1 is a perspective exploded view of a fluid dispenser constructed in accordance with the present invention;

Figure 2 is an elevational view of a fluid pouch which may be used with the dispenser of Figure 1;

Figure 3 is a sectional side view of the dispenser of Figure 1 assembled, showing the fluid dispenser mechanism disengaged from the fluid pouch;

Figure 4 is a sectional side view, broken away, similar to Figure 3 but showing the fluid dispenser mechanism engaged with the fluid pouch for dispensing fluid therefrom; and

Figure 5 is side view of the dispenser of Figure 3, broken away, showing the liquid level indicator in the empty position.

DETAILED DESCRIPTION OF THE INVENTION

In the ensuing description of the structure and operation of the fluid dispenser, reference will be made to the drawings wherein like numerals refer to like parts. Referring first to Figures 1 to 3, a fluid dispenser 10 is made of a suitable molded plastic material and has a back wall 12 and a front cover 14. Cover 14 is provided with a pair of apertures 16 forming view ports in the sides of the cover and an aperture 26 located in the front portion of the cover. Cover 14 includes a cut-out portion 18 in the bottom portion of the cover and a pair of spaced pins 20

integrally formed with the cover project into the cut-out portion. Cover 14 also includes a pair of arcuate hooks 22 and a pair of spaced brackets 24 (only one shown in Figure 1) integrally formed on the inside of the front portion of cover 14.

Back wall 12 includes a longitudinal bar 30 along the bottom thereof which is provided with holes 32 in the ends thereof for receiving pins 20 therein for pivotally attaching cover 14 to the back wall, as indicated by the lower broken line in Figure 1. Back wall 12 includes a pair of spaced, resilient, triangular arms 34 integrally formed on the inner surface which project toward cover 14 when the dispenser is assembled, only one visible in Figure 1. The purpose of arms 34 will be discussed presently. A resilient arm 36 having a triangular shaped end portion 38 is integrally formed with back wall 12 along the upper edge thereof which snaps over an downwardly protruding edge on the inside of the upper portion of front cover 14, not shown, for securing the upper edge of the front cover to the back wall. Back wall 12 is provided with triangular shaped support struts 40 integrally formed therewith which receive thereon a fluid or soap dispenser pouch 200, best seen in Figure 2. Struts 40 have a cut-out portion along the bottom edge thereof to provide a retaining edge 41 to be discussed below.

Dispenser 10 is provided with a pushbutton 44 mounted in aperture 26 of the cover, see particularly Figures 3 and 4. Pushbutton 44 includes a hollow portion 46 having a front opening 48 and a pair of spaced support arms 50 having pins 52 extending outwardly therefrom which are received by brackets 24 for pivotal attaching pushbutton 44 to cover 14, see the upper broken line in Figure 1. Hollow portion 46 partially accommodates a cam shown generally at 60 within front opening 48. Cam 60 comprises a cylindrical roller 62 provided with an arcuate surface or face 64. Roller 62 includes an axle 66 extending from each end thereof. Roller 62 is preferably fabricated of a resilient

AMENDED SHEET

deformable material such as rubber, an elastomer or a soft flexible plastic. Cam 60 includes a roller bracket 68 comprising a pair of spaced arms 70 joined by a connector 72. Roller 62 is rotatably mounted in bracket 68 by axle 66 extending through holes 74 in arms 70. Arms 70 include pins 75 extending outwardly therefrom which are received in holes 76 located in portion 46 of pushbutton 44 so that cam 60 can pivot with respect to the pushbutton. Attached to each arm 70 is a bracket 77 to which one end of a spring 78 is attached (only one spring 78 is shown in Figure 1). The other end of springs 78 are hooked over arcuate hooks 22 integrally formed on the inside of front cover 14.

Dispenser 10 includes an anvil block, or backstop, 80 having a front face 82, sides 84, a top surface 86 and spaced mounting pins 88 projecting from face 82 spaced from the side edges thereof. A boss 90 extends outwardly from each side 84 from the upper back corner thereof, each boss being integrally formed with backstop 80. A pair of spaced stops 92 are integrally formed with top surface 86 and extend upwardly therefrom. A retaining plate 94 is provided and includes a cut-out portion 96 with an upper edge 98 and spaced holes 100 extending therethrough. Plate 94, backstop 80 and back wall 12 are secured together by inserting pins 88 into holes 100 and ultrasonically welding backstop 80 and plate 94 together. Backstop 80 is then secured to back wall 12 by aligning the backstop between arms 34 with bosses 90 in contact with the inner surface of the bosses. Backstop 80 is then pushed against back wall 12 whereby arms 34 snap over bosses 90 to lock the combination together. The alignment of these connections being represented by the middle broken lines in Figure 1. The upper edge 98 of cut-out portion 96 is located above top surface 86 of backstop 80 when plate 94 is attached to the backstop and back wall 12. Formed between front face 82 of backstop 80 and the cylindrical surface of roller 62 is a dispenser path 102 when dispenser 10 is assembled, see Figure 3.

Referring specifically to Figures 1 and 3, dispenser 10 is provided with a fluid level indicator means 110 comprising an elongate, cylindrical rod 112 having two liquid level flags or indicators 114 attached one to each end thereof. Indicators 114 may be brightly colored so as to be clearly visible. An L-shaped member 116 comprises a first arm 118 attached to rod 112 in the middle thereof and a projecting pouch engagement arm 120 attached to first arm 118. Pouch engagement arm 120 includes a rounded end portion 122 suitable to be in physical contact with pouch 200 without piercing the pouch. Indicator 110 is received on top surface 86 of backstop 80 behind stops 92 and can rotate about the longitudinal axis of rod 112, best seen in, Figure 3.

Referring to Figure 2, a non-limiting example of a pouch 200 which may be used in combination with dispenser 10 is seen to comprise a flexible, main storage compartment 130 in flow communication with a lower, flexible dispenser compartment 132 and a pair of narrow and symmetric discharge passageways 134 that extend along two tortuous paths from the bottom of the flexible discharge compartment to a pair of discharge openings 136. As shown, pouch 200 is still intact but before commencement of use, the bottom end of the pouch comprising a tear tab 140 will be severed along a tear line collinear with line 138 joining notches 142 to open discharge openings 136. Because of the nature of the liquid in pouch 200 (preferably soap) and because of the tortuous path of discharge passageways 134, the liquid in the pouch does not leave the opening 136 until part of the pouch is actuated as by pressing by roller 62 or other mechanical equivalent. Since more than one discharge passageway 134 is provided in pouch 200, these passageways can be narrower than would be required in a pouch having only one discharge passageway. Alternatively, it will be appreciated that other currently known fluid pouches having a single serpentine fluid outlet passageway may be used.

Pouch 200 is received in dispenser 10 between

support struts 40 and retaining plate 94 with flexible dispenser compartment 132 inserted through cut-out portion 96 of retaining plate 94 and received against front face 82 of backstop 80 in dispenser path 102 of the dispenser. Tear tab 140 is then detached from the rest of pouch 200. In the position shown in Figure 3 in which pushbutton 44 is not depressed, outer surface 64 of roller 62 is spaced from pouch 200 beneath main storage compartment 130 thereby dividing storage compartment 130 from pouch dispenser compartment 132.

Referring to Figures 3-5, in operation, when pushbutton 44 is pressed inwards, it moves through opening 26 in front cover 14, and this causes the roller 62 to move, towards pouch 200 away from the rest position seen in Figure 3 in which it is spaced from pouch 200. As pushbutton 44 is pushed further towards backstop 80, roller 62 pivots downwards about pins 74 against the restoring force of springs 78 and against front face 82 of backstop 80 with the dispenser compartment 132 between roller 62 and backstop 80 thereby expelling a quantity of fluid 140 from the dispenser compartment, best seen in Figure 4.

The use of rubber, soft flexible plastic or an elastomer material for the construction of flexible roller 62 is advantageous because it provides some give when rolling down the flexible dispenser compartment thereby maintaining constant pressure on the dispenser compartment to provide uniform expulsion of fluid from the pouch. In contrast, hard rollers having no give tend to twist about side to side away from the dispenser compartment when rolling down a non-uniform dispenser compartment. This results in a non-uniform pressure applied across flexible dispenser compartment 132 and non-uniform expulsion of fluid from pouch 200.

An advantage associated with the use of support struts 40 and retaining plate 94 to hold pouch 200 rather than hanging the pouch from pins along the upper edge of back wall 12 is the simplified procedure of removing and

APR 10 1961

replacing pouch 200 in dispenser 10 so no aligning of pouch holes and dispenser mounted pegs is required.

Release of pushbutton 44 returns it by the action of springs 78 to the position seen in Figure 3 whereby extensible springs 78 pull roller 62 upwardly causing it to pivot upwardly about pins 74 to the start position wherein the roller is lightly engaging pouch 200. In order for springs 78 to return roller 62 to the rest position with pushbutton 44 fully retracted, hooks 22 are located forward of brackets 76 so that springs 78 which extend between the hooks and brackets are inclined downwardly and inwardly as viewed in Figure 3 and 4.

The operation of the fluid indication means is, best described with reference to Figures 3-5. The fluid pouch 200 as shown in Figure 3 and 4 is filled with the result that pouch engagement arm 120 is pushed fully to the left so that indicators 114 attached to the ends of rod 112 are pivoted far enough to the right away from view port 16 to be out of view. As the fluid in pouch 200 is depleted the lower portion of storage compartment 130 begins to collapse as shown in Figure 5 so that engagement arm 120 rotates outwardly towards retaining plate 94 causing indicator 114 to rotate inwardly toward view port 16 and into the range of view port 16 thereby indicating a need to replace pouch 200. Rod 112 is locked between edges 41 of support struts 40 and stops 92 on top surface 86 of backstop 80 act to stop rod 112 from moving on the top surface of the backstop when dispenser 10 is assembled.

Those skilled in the art will appreciate that other cam means having an arcuate outer surface for rolling down the dispenser portion of pouch 200 could be employed in the dispenser of the present invention as an alternative to roller 62 discussed herein.

Thus, while the fluid dispenser having an arcuate shaped cam and an indicator means for indicating when the fluid pouch needs replacement has been described and illustrated with respect to various embodiments, it will be

2153233

-10-

appreciated that numerous variations of these embodiments may be made without departing from the scope of the invention disclosed herein.

AMENDED SHEET

- 11 -

THEREFORE WHAT IS CLAIMED IS:

1. In a dispenser (10) for dispensing a fluid from a flexible dispenser compartment (132) of a pouch (200) of the type having a discharge passage that extends along a tortuous path to a discharge opening (136) at a lower end of the pouch (200), comprising a housing having a back wall (12) and a cover (14) and enclosing a dispenser path (102) and a backstop (80); characterized in that:

(a) a support member (40) inclined from the vertical is attached to the back wall (12), including a retaining plate (94) attached to said backstop (80) and extending upwardly therefrom, said retaining plate (94) including a cutout portion (96), said pouch (200) being cradled between said support member (40) and said retaining plate (94) with the flexible dispenser compartment (132) inserted through said cutout portion (96) and located adjacent to said backstop (80);

(b) a cam means (60) having an arcuate face (64) confronting said backstop (80);

(c) a pushbutton means (44) confronting said backstop (80) and engaging cam means (60), pushbutton means (44) being pivotally attached to said cover (14), cam means (60) being pivotally coupled to said pushbutton means (44);

(d) spring bias means (78) coupled between said cam means (60) and said cover (14), whereby pushing pushbutton means (44) toward backstop (80) causes cam means (60) to pivot with respect to pushbutton means (44) and to move downwardly along backstop (80) and against the action of spring bias means (78) with flexible dispenser compartment (132) between cam means (60) and backstop (80) thereby expelling a quantity of fluid from pouch (200); and

(e) indicator means (110) engaging to said pouch (200) for indicating when the pouch (200) has been substantially depleted of fluid.

- 12 -

2. The fluid dispenser (10) according to claim 1 wherein said cam means (60) includes a roller (62) having an elongate axle (66) extending from the ends thereof, including a roller bracket (68) comprising two spaced arms (70) each provided with a hole (74) extending therethrough for receiving therein the axle (66) for rotationally mounting said roller (62), said spring bias means (78) is a pair of extensible springs attached at one end to said arms (70) and at the other end to said cover (14), and wherein said roller bracket arms (70) are pivotally attached to said pushbutton means (44) so that in operation when the pushbutton means (44) is pushed inwardly, the roller (62) is pressed against the flexible discharge compartment (132) of the pouch (200) and is forced downwards against the spring bias (78) along the flexible discharge compartment (132) and the roller bracket (68) pivots about said pivotal attachment.

3. The fluid dispenser (10) according to claim 2 wherein said roller (62) is fabricated of a resilient material from the group consisting of rubber, soft flexible plastic and an elastomer material.

4. The fluid dispenser (10) according to claim 2 in which said pushbutton means (44) is a hollow pushbutton mounted in said front cover (14).

5. The fluid dispenser (10) according to claim 4 in which said pushbutton (44) partially accommodates said cylindrical roller (62) and said roller bracket (68) within a front opening, the pushbutton (44) being pivotally attached to said front cover (14), said pushbutton (44) being operable to effect relative movement between said cylindrical roller (62) and said backstop (80) to initially seal said flexible dispenser compartment (132) at its upper end and thereafter by rolling action to expel therefrom the fluid trapped in said flexible dispenser compartment (132).

- 13 -

6. The fluid dispenser (10) according to claim 1 including a view port (16) for viewing the interior of the dispenser, wherein said indicator means (110) is a visual indicator means comprising an arm (118), a visually distinctive portion (114) mounted at one end of the arm (118) and a pouch engagement member (122) attached to the other end of the arm (118), the arm (118) being pivotally mounted in close proximity to said fluid pouch (200) with said pouch engagement member (122) bearing against said pouch (200) so that when the pouch contains fluid therein the visually distinctive portion (114) is pivoted away from said view port (16) and as fluid is depleted from said pouch (200) and the pouch collapses causing the arm (118) to pivot until the visually distinctive portion (114) comes into full view through said view port (16).

7. A fluid dispenser (10) for dispensing fluid from a flexible dispenser compartment (132) of a pouch (200), comprising a housing having a back wall (12) and a cover (14) enclosing a dispenser path (102) and a backstop (80); characterized in that:

(a) a support member (40) inclined from the vertical is attached to the back wall (12), including a retaining plate (94) attached to said backstop (80) and extending upwardly therefrom, said retaining plate (94) including a cutout portion (96), said pouch (200) being cradled between said inclined support member (40) and said retaining plate (94) with the flexible dispenser compartment (132) inserted through said cutout portion (96) and located adjacent to said backstop (80);

(b) a roller (62) having an axle (66) confronting the backstop (80), including a roller bracket (68) comprising two spaced arms (70) rotationally engaging the axle (66);

(c) a pushbutton means (44) being pivotally attached to said cover (14), said roller bracket (68) being pivotally coupled to said pushbutton means (44);

- 14 -

(d) spring bias means (78) coupled between said roller (62) and said cover (14), whereby pushing pushbutton means (44) toward backstop (80) causes roller (62) to pivot with respect to pushbutton means (44) and to move downwardly along backstop (80) and against the action of spring bias means (78) with flexible dispenser compartment (132) between roller (62) and backstop (80) thereby expelling a quantity of fluid from pouch (200); and

(e) indicator means (110) engaging to said pouch (200) for indicating when the pouch (200) has been substantially depleted of fluid.

8. The fluid dispenser (10) according to claim 7 wherein said roller (62) is fabricated of a resilient material selected from the class consisting of rubber, soft flexible plastic and an elastomer material.

9. The fluid dispenser (10) according to claim 7 in which said pushbutton means (44) is a hollow pushbutton mounted in said front cover (14).

10. The fluid dispenser (10) according to claim 9 in which said pushbutton (44) partially accommodates said roller (62) and said roller bracket (68) within a front opening, the pushbutton (44) being pivotally attached to said front cover (14), said pushbutton (44) being operable to effect relative movement between said roller (62) and said backstop (80) to initially seal said flexible dispenser compartment (132) at its upper end and thereafter by rolling action to expel therefrom the fluid trapped in said flexible dispenser compartment (132).

11. The fluid dispenser (10) according to claim 7 including a view port (16) for looking into the interior thereof, wherein said indicator means (110) is a visual indicator means comprising an arm (118), a visually distinctive portion (114) mounted at one end of the arm

- 15 -

(118) and a pouch engagement member (122) attached to the other end of the arm (118), the arm (118) being pivotally mounted in close proximity to said fluid pouch (200) with said pouch engagement member (122) bearing against said pouch (200) so that when the pouch contains fluid therein the visually distinctive portion (114) is pivoted away from said view port (16) and as fluid is depleted from said pouch (200) and the pouch collapses causing the arm (118) to pivot until the visually distinctive portion (114) comes into full view through said view port (16).

12. A fluid dispenser (10) for dispensing fluid from a flexible dispenser compartment (132) of a pouch (200), comprising:

(a) a dispenser housing provided with a dispenser station through which the fluid is to be dispensed along a dispenser path (102) that extends therethrough, the dispenser station being provided with a backstop (80);

(b) said dispenser housing including a support member (40) inclined from the vertical and a retaining plate (94) attached to said backstop (80) and extending upwardly therefrom, said retaining plate (94) including a cutout portion (96), said pouch (200) being receivable in the dispenser and cradled between said inclined support member (40) and said retaining plate (94) with the flexible dispenser compartment (132) inserted through said cutout portion (96) and extending along said dispenser path (102) adjacent to said backstop (80);

(c) a cam (60) confronting the backstop (80) and located on the other side of the dispenser path (102), said cam (60) having a substantially cylindrical shaped roller (62) having an axle (66) extending from the ends thereof, said cam including a roller bracket (68) comprising two spaced arms (70) each provided with means for engaging the axle (66) for rotationally mounting said roller (62) in said bracket (68);

(d) a pushbutton (44) being pivotally attached to


- 16 -

said housing,

(e) spring bias means (78) attached at one end thereof to said arms (70) and at the other end thereof to said dispenser housing, and wherein said roller bracket arms (70) are pivotally attached to said pushbutton (44), whereby when the pushbutton (44) is pushed inwardly the roller (62) is pressed against the flexible discharge compartment (132) of the pouch and is forced downwards along the flexible discharge compartment (132) and the roller bracket (68) pivots about said pivotal attachment; and

(f) indicator means (110) engaging to said pouch (200) when said pouch (200) is supported within said dispenser housing for indicating when the pouch (200) has been substantially depleted of fluid and in need of being replaced.

1/4



2/4




FIG. 2




FIG. 3




FIG. 5




FIG. 4