

(19)  
(12)

(KR)  
(B1)

(51) 。 Int. Cl. <sup>6</sup>  
C08G 69/36  
C08G 69/02

(45)  
(11)  
(24)

2002 11 23  
10 - 0347314  
2002 07 22

(21) 10 - 1996 - 0076044  
(22) 1996 12 30

(65) 1998 - 0056774  
(43) 1998 09 25

(73)

450

(72)

2 276 - 8

912 C 1

(74)

:

(54)

%, 20 40 % 60 80  
가 가 .

가 , 가

6 66

가

가

( U.S.2,696,482 )

(U.S.2,516,5

85)  
가

가

가

1,595,354 - (4 - - )

- (4 - - )

( 2,585,163)

1,933,395 - (4 - - )

- (4 - - )

)

50%  
가

- (4 - - )

2,215,906 ( 3,808,181)

- (4 - - )  
가

3 - - 1,10

130

3 - - 1,10 -

2,642,244

- (4 - - )  
9

, 20


40 %

60 80 %

가

, 5 - - , 2,4,4 -

, 2,2,4 -



X 3 4 .

30 %가

60 80 %, 10

20 40 %  
40 %

1)

2)

3) 가 가

4)

5)

가

가 , 가 , 가

1

2490g  
000g  
80

4595g

3000g  
260 2

17

4  
2

245

2

1950g                      540g                      4595g                      3000g  
 240                      4000g                      1                      .

3320g                      3340g                      3600g                      5000g  
 1                      1                      .                      255

가 .1 .

1

	용점(℃)	상대점도	굴곡강도 (Kgf/cm <sup>2</sup> )	굴곡탄성율 (Kgf/cm <sup>2</sup> )	충격강도 (Kg · cm/cm <sup>2</sup> )
실시에1	245	2.2	1021	20015	6.5
2	240	2.2	1011	19800	6.4
비교예1	255	2.3	1220	22600	7.8

(57)

1.

40 %                      ,                      60   80   %                      20 .

2.

1 ,

3.

2 ,

30 %