

14350/88

1 APPLICATION ACCEPTED AND AMENDMENTS

ALLOWED

12-4-90

COMMONWEALTH of AUSTRALIA

PATENTS ACT 1952

59 86 57

APPLICATION FOR A STANDARD PATENT

X

We MITSUBISHI PLASTICS INDUSTRIES LIMITED
of 5-2, Marunouchi 2-chome,
Chiyoda-ku, Tokyo,
Japan.

hereby apply for the grant of a Standard Patent for an invention entitled:

"APPARATUS FOR FORMING A BLOWN BOTTLE WITH A HANDLE AND METHOD
OF FORMING THE SAME"

which is described in the accompanying ~~provisional~~
complete specification.

Details of basic application(s):—

<u>Number</u>	<u>Convention Country</u>	<u>Date</u>
NIL	NIL	NIL

LODGED AT SUB-OFFICE
- 7 APR 1988
Melbourne

The address for service is care of DAVIES & COLLISON, Patent Attorneys, of 1 Little
Collins Street, Melbourne, in the State of Victoria, Commonwealth of Australia.

Dated this 7th

day of April

19 88

To: THE COMMISSIONER OF PATENTS

H. A. Rimington
.....
(a member of the firm of DAVIES &
COLLISON for and on behalf of the Applicant).

Davies & Collison, Melbourne and Canberra.

COMMONWEALTH OF AUSTRALIA

PATENTS ACT 1952

DECLARATION IN SUPPORT OF CONVENTION OR
NON-CONVENTION APPLICATION FOR A PATENT

Insert title of invention.

entitled: In support of the Application made for a patent for an invention
APPARATUS FOR FORMING A BLOWN BOTTLE WITH A
HANDLE AND METHOD OF FORMING THE SAME
Toshihisa Muramatsu, President, of
I Mitsubishi Plastics Industries Limited
~~We~~ of 5-2, Marunouchi 2-chome, Chiyoda-ku, Tokyo,
Japan

Insert full name(s) and address(es)
of declarant(s) being the appli-
cant(s) or person(s) authorized to
sign on behalf of an applicant
company.

Cross out whichever of paragraphs
1(a) or 1(b) does not apply

1(a) relates to application made
by individual(s)

1(b) relates to application made
by company; insert name of
applicant company.

do solemnly and sincerely declare as follows :-

1.-(a) ~~I am~~ the applicant..... for the patent
~~We are~~

or (b) I am authorized by

mitsubishi plastics industries limited

Cross out whichever of paragraphs
2(a) or 2(b) does not apply

2(a) relates to application made
by inventor(s)

2(b) relates to application made
by company(s) or person(s) who
are not inventor(s); insert full
name(s) and address(es) of inven-
tors.

the applicant..... for the patent to make this declaration on ^{its} ~~their~~ behalf.

2.-(a) ~~I am~~ the actual inventor..... of the invention
~~We are~~

or (b)

Hideo Hasegawa, Toshio Takahashi and Masayuki Miyagawa all
of Mitsubishi Plastics Industries Limited Hiratsuka Kojo,
2480, Shindo, Hiratsuka-shi, Kanagawa-ken, Japan

~~ditto~~ and

~~ditto~~ -

~~is~~ the actual inventor(s)..... of the invention and the facts upon which the applicant.....
~~are~~ is
~~are~~ entitled to make the application are as follows :-

State manner in which applicant(s)
derive title from inventor(s)

The applicant would, if a patent were granted upon an
application made by the said actual inventors, be
entitled to have the patent assigned to it.

Cross out paragraphs 3 and 4
for non-convention applications.
For convention applications,
insert basic country(s) followed
by date(s) and basic applicant(s).

~~* The basic application..... as defined by Section 141 of the Act was made
in on the
by
in on the
by
in on the
by~~

* The basic application..... referred to in paragraph 3 of this Declaration was
the first application..... made in a Convention country in respect of the invention the subject
of the application.....

Insert place and date of signature.

Declared at Japan

this 15th

day of April, 1988

Signature of declarant(s) (no
attestation required)

Toshihisa Muramatsu
Toshihisa Muramatsu, President
Mitsubishi Plastics Industries
Limited

Note Initial all alterations.

(12) PATENT ABRIDGMENT (11) Document No. AU-B-14350/88
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 598657

(54) Title
BLOW MOULDING A BOTTLE WITH A HANDLE

International Patent Classification(s)
(51)⁴ B29C 049/20 B29C 049/36

(21) Application No. : 14350/88 (22) Application Date : 07.04.88

(43) Publication Date : 25.01.90

(44) Publication Date of Accepted Application : 28.06.90

(71) Applicant(s)
MITSUBISHI PLASTICS INDUSTRIES LIMITED

(72) Inventor(s)
HIDEO HASEGAWA; TOSHIO TAKAHASHI; MASAYUKI MIYAGAWA

(74) Attorney or Agent
DAVIES & COLLISON, MELBOURNE

(57) Figure 1 is a plane view of an embodiment of the apparatus for forming a blown bottle with a handle to carry out the method of the present invention in which a parison holding unit and a handle holding unit are shown in detail;

Figure 2 is a front view of the holding units shown in Figure 1;

Figure 3 is a longitudinal cross-sectional view of a blow mold;

Figure 4 is a cross-sectional view taken along a line A - A' in Figure 3;

CLAIM

1. A method of forming a blown bottle with a handle which is a one-piece-molded product by blowing a pressurized fluid into a thermoplastic parison heated at a temperature suitable for molding which is placed in a blow mold together with said handle, said method being characterized in that said parison and said handle are previously held with a correct positional relation and they are

(11) AU-B-14350/88
(10) 598657

-2-

simultaneously moved in said blow mold to be subjected to blow molding.

6. An apparatus for forming a blown bottle with a handle which comprises:

- a circularly transferring unit,
- a first holder attached to said transferring unit to hold a parison vertically,
- a second holder attached to said transferring unit to hold a handle so that said handle is at a predetermined position with respect to said parison,
- a heating unit to heat said parison,
- a blow mold which receives said parison and said handle on said first and second holders, and
- an air-blowing unit to supply pressurized air to said parison when it is in said blow mold.

598657

COMMONWEALTH OF AUSTRALIA

PATENT ACT 1952

COMPLETE SPECIFICATION

(ORIGINAL)

FOR OFFICE USE

CLASS

INT. CLASS

Application Number:
Lodged:

Complete Specification Lodged:
Accepted:
Published:

Priority:

Related Art:

This document contains the
amendments made under
Section 49 and is correct for
printing.

NAME OF APPLICANT: MITSUBISHI PLASTICS INDUSTRIES LIMITED

ADDRESS OF APPLICANT: 5-2, Marunouchi 2-chome,
Chiyoda-ku, Tokyo,
Japan.

NAME(S) OF INVENTOR(S) Hideo HASEGAWA
Toshio TAKAHASHI
Masayuki MIYAGAWA

ADDRESS FOR SERVICE: DAVIES & COLLISON, Patent Attorneys
1 Little Collins Street, Melbourne, 3000.

COMPLETE SPECIFICATION FOR THE INVENTION ENTITLED:

"APPARATUS FOR FORMING A BLOWN BOTTLE WITH A HANDLE AND METHOD
OF FORMING THE SAME"

The following statement is a full description of this invention,
including the best method of performing it known to us :-

- 1A -

APPARATUS FOR FORMING A BLOWN BOTTLE WITH A HANDLE AND
METHOD OF FORMING THE SAME

The present invention relates to an apparatus for and a method of forming a thermoplastic bottle with a handle.

5 It has been known that it is difficult to form a thermoplastic bottle with a handle by blow-molding a single parison of a material such as polyethylene terephthalate.

10 There is a proposal in a publication, for instance, Japanese Unexamined Patent Publication No. 99350/1983 to form the blown bottle with a handle in such a manner that a parison and a handle are separately formed; the handle is first put on a handle holder placed at a predetermined position in a blow mold; then, the parison is put in the
15 blow mold; and thereafter, blow molding is carried out.

20 In the conventional method, however, an additional device is required to move the handle holder since the handle is fixed at a predetermined position by the handle holder separate from the parison. Further, there easily causes error in positional relation between the handle and

the parison since the parison is moved after the handle is fixed. As a result, there takes place deviation in position where the handle is attached to the blown bottle.

It is an object of the present invention to provide an apparatus for and a method of forming a blown bottle with
5 a handle having a correct positional relation.

In one aspect of the present invention, there is provided a method of forming a blown bottle with a handle which is a one-piece-molded product by blowing a
10 pressurized fluid into a thermoplastic parison heated at a temperature suitable for molding which is placed in a blow mold together with the handle, the method being characterized in that the parison and the handle are previously held with a correct positional relation and
15 they are simultaneously moved in the blow mold to be subjected to blow molding.

In another aspect of the present invention, there is provided an apparatus for forming a blown bottle with a handle which comprises:

- 20 a circularly transferring unit,
- a first holder attached to the transferring unit to hold a parison vertically,
- a second holder attached to the transferring unit to hold a handle so that the handle is at a predetermined
25 position with respect to the parison,
- a heating unit to heat the parison,
- a blow mold which receives the parison and the handle

by injection molding of synthetic resin such as polyethylene terephthalate or by an extrusion method after which one end of tubular product is closed.

The handle may be formed by injection molding of synthetic resin such as polypropylene, polyethylene and so on.

In the present invention, the parison and the handle are held with a correct positional relation. For this, a holder for holding the parison and a holder for holding the handle are attached on the same transferring unit at predetermined positions, and they are simultaneously moved in the blow mold in the state that they respectively hold the parison and the handle. The parison holder may have a rotatable mandrel and the handle holder may be in a non-rotatable state so that only the parison is caused to rotate while being heated at a forming temperature before it is moved in the blow mold.

Alternatively, the parison and the handle are injection-molded by using a forming mold in which a cavity for the parison and a cavity for the handle are formed so as to keep a correct positional relation when they are subjected to blow molding, and then, the parison and the handle are moved in the blow mold in such a state that the mouth portion of the parison and the runner for the handle are held with a predetermined positional relation.

Under the above-mentioned condition, the parison and the handle are simultaneously put in the blow mold in

which the handle is set in a recess formed in the inner wall of the blow mold. Then, a pressurized fluid is supplied in the parison as in the usual manner, whereby a blown bottle with the handle attached to it at a correct position can be obtained.

Figure 1 is an example showing an apparatus for forming a blown bottle with a handle to carry out a forming method according to the present invention.

In Figure 1, a reference numeral 5 designates a circularly transferring unit. A first holder 1 having a rotatable mandrel 11 is attached to a peripheral part of the transferring unit 5. The mandrel 11 is so adapted to support a parison 3 on it with the neck portion of the parison directing downwardly. A second holder 2 for supporting a handle 4 is also attached to the peripheral part of the transferring unit 5 in a non-rotatable manner. The first and second holders 1, 2 have a predetermined positional relation to each other on the transferring unit 5. The first and second holders 1, 2 are moved circularly to a heating station and a blowing station as the transferring unit 5 is turned. Reference numerals 6 designates heaters.

In this embodiment, the parison and the handle are formed in separate steps, and the parison 3 is put on the mandrel 11 in an inverted state, i.e. the neck portion of the parison being directed downwardly. Then, the transferring unit 5 is circularly driven to thereby move

the parison holder 1 with the parison 3 to the heating station, where the parison 3 is heated at a forming temperature by the heaters 6 while the mandrel 11 is rotated. Then, the handle 4 is fitted to a pin 21 of the handle holder 2 at a predetermined level. Then, the parison holder 1 and the handle holder 2 are simultaneously moved into the blow mold 8.

As shown in Figures 3 and 4, the blow mold 8 comprises a pair of half-cylindrical molds 81, 82. The parison 3 and the handle 4 are simultaneously moved into the half-cylindrical molds 81, 82, which are in an opened state, while they keep a predetermined positional relation, and then, they are closed. Then, a pressurized fluid is supplied into the parison as indicated by an arrow mark to expand the parison 3 to thereby have its shape correspond to the configuration of the blow mold 8. At the same time, the handle 4 is firmly connected to the trunk portion of the blown product. Thus, a blown bottle with a handle is formed as shown in Figure 5.

In the above-mentioned embodiment, the handle and the parison are prepared separately and attached to the holders separately, but they are simultaneously transferred into the blow mold with the holders which are fixed on the transferring unit 5 at a predetermined positional relation.

Figures 6 and 7 show another embodiment of the method of and the apparatus for forming a blown bottle with a

handle according to the present invention. In this embodiment, an injection molding operation for the parison and the handle and a blow molding operation to form a blown bottle are conducted in series in an inline system.

5 A numeral 10 designates an inline injection and blow-molding apparatus which comprises an injection-molding station 101, a parison heating station 106, a blow-molding station 107 and a blown product removing station 108 which are circularly arranged around
10 the transferring unit. In the injection-molding station 101, there are arranged a first injection mold 103 for forming the handle and second injection molds 102 for forming the parison 3 at both sides of the first injection mold 103 so that elements for blown bottles are
15 obtainable. The cavity for the handles formed in the first injection mold 103 is so determined that the handle is connected to a predetermined position on the blown product. For this purpose, the length of the runners 109 for the handles is suitably determined. Under the
20 above-mentioned condition, injection-molding is simultaneously or separately carried out for the parisons and handles by using an injection-molding machine 13. Then, each of the injection molds are opened. In this state, the mouth portion of each of the parisons 3 and the
25 runner 109 of each of the handles 4 are respectively held by a holder plate 105 which constitute a part of the injection molds 102, 103, and the holder plate 105 with

the parisons 3 and the handles 4 is transferred to the parison heating station 106. In the parison heating station 106, only the parisons are heated by a plurality of heaters (not shown) arranged so as to surround the

5 parisons 3. Then, the parisons and the handles 4, each held by the holder plate 105, are simultaneously moved to the blow-molding station 107 to be put at their predetermined positions in the blow molds. After the blow molds are closed, blow molding is carried out. Then, the

10 blow molds are moved to the blown product removing station 108, where the blow molds are opened, and the runners 109 for the handles are cut. Thus, blown bottles with handle as shown in Figure 5 are produced.

In accordance with the present invention, since the

15 handle is held at a correct position with respect to the parison when blow molding is carried out, the handle is connected to the blown bottle at a correct position. Accordingly, a blown bottle with a handle can be easily produced without a problem of scattering in the products.

20 When the parison and the handle are formed by injection-molding at predetermined positions, a blown bottle with a handle can be certainly and effectively produced by a single forming apparatus.

on the first and second holders, and

an air-blowing unit to supply pressurized air to the parison when it is in the blow mold.

In the drawings:

5 Figure 1 is a plane view of an embodiment of the apparatus for forming a blown bottle with a handle to carry out the method of the present invention in which a parison holding unit and a handle holding unit are shown in detail;

10 Figure 2 is a front view of the holding units shown in Figure 1;

Figure 3 is a longitudinal cross-sectional view of a blow mold;

15 Figure 4 is a cross-sectional view taken along a line A - A' in Figure 3;

Figure 5 is a perspective view showing an embodiment of the blown bottle with a handle obtained by the method of the present invention;

20 Figure 6 is a diagram showing another embodiment of the apparatus for forming a blown bottle with a handle according to the present invention; and

Figure 7 is a cross-sectional view taken along a line B - B' in Figure 6.

25 Preferred embodiments of the present invention will be described with reference to the drawings.

In the present invention, a parison in a tubular form with a bottom wall is used. The parison is formed either

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method of forming a blown bottle with a handle which is a one-piece-molded product by blowing a pressurized fluid into a thermoplastic parison heated at a temperature
5 suitable for molding which is placed in a blow mold together with said handle, said method being characterized in that said parison and said handle are previously held with a correct positional relation and they are simultaneously moved in said blow mold to be subjected to
10 blow molding.
2. The method according to Claim 1, wherein said parison and said handle are set on respective holders, and are moved circularly to a blowing station via a heating station.
- 15 3. The method according to Claim 1, which comprising a first step of setting said parison on a holder, a second step of heating said parison, a third step of setting said handle on another holder so as to keep a correct positional relation to said parison and a fourth step of
20 blow-molding said parison to connect said handle therewith, said first and fourth steps being conducted circularly.
4. The method according to Claim 1, wherein said parison and said handle are simultaneously formed by injection
25 molding while keeping the correct positional relation at an injection molding station, and are moved circularly to a blowing station via a heating station.

5. The method according to Claim 1, wherein said parison is set on a rotatable holder and said handle is set on a non-rotatable holder.

6. An apparatus for forming a blown bottle with a handle
5 which comprises:

a circularly transferring unit,

a first holder attached to said transferring unit to hold a parison vertically,

a second holder attached to said transferring unit to
10 hold a handle so that said handle is at a predetermined position with respect to said parison,

a heating unit to heat said parison,

a blow mold which receives said parison and said handle on said first and second holders, and

15 an air-blowing unit to supply pressurized air to said parison when it is in said blow mold.

7. The apparatus according to Claim 5, wherein an injection molding station for forming a parison and a handle, a heating station for heating said parison, a
20 blow-molding station for expanding said parison into a blown bottle so that said bottle and said handle join, and a removing station for removing a blown product are circularly arranged, and wherein an injection mold in said injection molding station has a holder plate for holding
25 said parison and said handle, as a separable part of said mold.

8. The apparatus according to Claim 6, wherein plural

sets of said first and second holders are attached to said circularly transferring unit.

9. A method of forming a blown bottle with a handle substantially as hereinbefore described with reference to the drawings.

10. An apparatus for forming a blown bottle with a handle substantially as hereinbefore described with reference to the drawings.

~~11. The steps or features disclosed herein or any combination thereof.~~

Dated this 7th day of April 1988

DAVIES & COLLISON
By its Patent Attorneys
MITSUBISHI PLASTICS INDUSTRIES LIMITED



14350/88

FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6




FIGURE 7

