



US006581181B1

(12) **United States Patent**
Sonu

(10) **Patent No.:** **US 6,581,181 B1**
(45) **Date of Patent:** **Jun. 17, 2003**

(54) **DOMINANT ERROR CORRECTION CIRCUITRY FOR A VITERBI DETECTOR**

(75) Inventor: **Gene Sonu**, San Jose, CA (US)

(73) Assignee: **Oak Technology, Inc.**, Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/538,134**

(22) Filed: **Mar. 29, 2000**

(51) Int. Cl.⁷ **H03M 13/03; H03D 1/00**

(52) U.S. Cl. **714/795; 375/262**

(58) Field of Search **714/795, 796, 714/794; 360/65; 375/262**

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,552,942	A	*	9/1996	Ziperovich et al.	360/51
5,781,590	A	*	7/1998	Shiokawa et al.	375/341
5,844,741	A	*	12/1998	Yamakawa et al.	360/65
5,938,790	A	*	8/1999	Marrow	714/795
6,002,538	A	*	12/1999	Kanegae et al.	360/46
6,111,835	A	*	8/2000	Honma	369/59.13
6,154,870	A	*	11/2000	Fredrickson et al.	714/786
6,345,074	B1	*	2/2002	Turk et al.	375/341

* cited by examiner

Primary Examiner—David Ton


Assistant Examiner—Esaw Abraham

(74) *Attorney, Agent, or Firm*—Pennie & Edmonds LLP

(57) **ABSTRACT**

The apparatus corrects a data detection error caused by baseline wandering in an optical PRML read channel. The apparatus includes error detection circuitry and error correction circuitry. The error detection circuitry monitors a serial output signal from the optical PRML read channel and a first set of input signals to the optical PRML read channel to detect an error event associated with baseline wandering. The error detection circuitry deems the error event to have occurred when three conditions are satisfied. First, a bit sequence represented by the serial output signal matches a first bit sequence associated with the error event. Second, a first difference in a first set of consecutive values represented by the first set of input signals is within a first range of values associated with the error event. Third, a second difference in a second set of consecutive values of the first input signal is within a second range of values associated with the error event. The error detection circuitry responds to satisfaction of all three conditions by asserting an error signal. The error correction circuitry responds to assertion of the error signal by modifying a pair of consecutive bits represented by the serial output signal to generate a corrected output signal having a second bit sequence.

17 Claims, 13 Drawing Sheets






FIG. 1
(Prior Art)




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 3F




FIG. 3G




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12

1

DOMINANT ERROR CORRECTION CIRCUITRY FOR A VITERBI DETECTOR

BRIEF DESCRIPTION

The present invention relates generally to data detection in an optical Partial Response Maximum Likelihood (PRML) read channel, and particularly to error correction circuitry for improving data detection by correcting errors due to a dominant error event in an optical PRML read channel.

BACKGROUND

DVD, an acronym for Digital Video Disc or Digital Versatile Disc, is a relatively new type of Compact-Disc Read-Only-Memory (CD-ROM) with a minimum capacity of approximately 4.7 gigabytes. FIG. 1 illustrates in block diagram form apparatus for recording to and reading data from DVD 22. Recording Unit 20 takes digital data m_k and records it on DVD 20. (The subscript "k" is used throughout to indicate generally a time-variant signal and the subscript "kn" indicates the value of a time-variant signal at a time $k+n$.) DVD player 24 includes Optical Pick-up Unit (OPU) 26, and an optical Partial Response Maximum Likelihood (PRML) Read Channel (Read Channel) 30. OPU 26 converts information read from DVD 22 into an analog RF signal on line 27. Read Channel 30 takes this RF signal and generates a digital signal q_k . Read Channel 30 includes Automatic Gain Control (AGC) & Equalization Circuitry 32, Analog-to-Digital Converter (ADC) 34 and Viterbi Decoder 36. AGC & Equalization Circuitry 32 filters and limits the voltage magnitude of the RF signal on line 27, producing the analog signal on line 33. ADC 34 samples the analog signal on line 33 and produces a multi-bit digital signal, y_k , on line 35 that represents the magnitude of the analog signal on line 33. Viterbi Decoder 36 analyzes the y_k signal over several sample values and determines the most likely value represented by each sample. Viterbi Decoder 36 represents the most likely values via its output signal, q_k , on line 40, which is a single bit in a Non-Return to Zero Inverted (NRZI) format. Ideally, q_k should be identical to m_k ; however, errors prevents this.

Much of the error in q_k is caused by baseline wandering. As used herein, baseline wandering refers to low frequency disturbances of a radio frequency signal. FIG. 2A illustrates an ideal input signal to ADC 34, which is free from baseline wandering. The signal graphed in FIG. 2A remains centered about a baseline, zero volts in this example, throughout the illustrated time period. FIG. 2B illustrates a second input signal to ADC 34, which is subject to baseline wandering. The illustrated input signal has no fixed baseline; i.e., it exhibits a variable DC offset. The variable DC offset of the radio frequency signal produces a time variable error in y_k , the output of ADC 34. FIG. 3A is a histogram of the y_k signal given an input signal to ADC 34 that is free from baseline wandering; i.e., given the signal of FIG. 2A. In the absence of baseline wandering, the histogram of the y_k signal represents five distinctive sample values, 1, $\frac{2}{3}$, 0, $-\frac{2}{3}$ and -1 . Baseline wandering of the signal to be sampled by ADC 34 produces a quite different histogram. FIG. 3B is a histogram of the y_k signal given the input signal of FIG. 2B. FIG. 3B indicates that ADC 34 does not produce distinct sample values in the presence of baseline wandering, producing instead every sample value between approximately -1.25 to 1.25 . FIG. 3C through FIG. 3G are individual histograms for each ideal sample value. Thus, FIG. 3C is a histogram of

2

sample values corresponding the ideal value of 1; FIG. 3D is a histogram of sample values corresponding to the ideal value of $\frac{2}{3}$; FIG. 3E is a histogram of sample values corresponding to the ideal value of 0; FIG. 3F is a histogram of sample values corresponding to the ideal value of $-\frac{2}{3}$; and FIG. 3G is a histogram of sample values corresponding to the ideal value of -1 . These histograms reveal that baseline wandering destroys the one to one correspondence between ideal sample values and the values output by ADC 34. For example, FIGS. 3C and 3D indicate that a y_k value of $+\frac{2}{3}$ may be due to either an ideal sample value of either 1 or $\frac{2}{3}$. Thus, a need exists for circuitry to correct data detection errors caused by baseline wandering.

SUMMARY

The apparatus of the present invention corrects a data detection error caused by baseline wandering in an optical PRML read channel. The apparatus includes error detection circuitry and error correction circuitry. The error detection circuitry monitors a serial output signal from the optical PRML read channel and a first set of input signals to the optical PRML read channel to detect an error event associated with baseline wandering. The error detection circuitry deems an error event to have occurred when three conditions are satisfied. First, a bit sequence represented by the serial output signal matches a first bit sequence associated with the error event. Second, a first difference in a first set of consecutive values represented by the first set of input signals is within a first range of values associated with the error event. Third, a second difference in a second set of consecutive values of the first input signal is within a second range of values associated with the error event. The error detection circuitry responds to satisfaction of all three conditions by asserting an error signal. The error correction circuitry responds to assertion of the error signal by modifying a pair of consecutive bits represented by the serial output signal to generate a corrected output signal having a second bit sequence.

BRIEF DESCRIPTION OF THE DRAWINGS

Additional features of the invention will be more readily apparent from the following detailed description and appended claims when taken in conjunction with the drawings, in which:

FIG. 1 illustrates prior art apparatus for recording to, and reading data from, a DVD.

FIG. 2A illustrates an ideal input signal, free from baseline wandering, to the ADC of FIG. 1.

FIG. 2B illustrates a input signal to the ADC of FIG. 1, which is subject to baseline wandering.

FIG. 3A is a histogram of the output signal from the ADC of FIG. 1 given an input signal that is free from baseline wandering.

FIG. 3B is a histogram of the output signal from the ADC of FIG. 1 given the input signal of FIG. 2B.

FIG. 3C is a histogram of sample values corresponding to the ideal value of 1.

FIG. 3D is a histogram of sample values corresponding to the ideal value of $\frac{2}{3}$.

FIG. 3E is a histogram of sample values corresponding to the ideal value of 0.

FIG. 3F is a histogram of sample values corresponding to the ideal value of $-\frac{2}{3}$.

FIG. 3G is a histogram of sample values corresponding to the ideal value of -1 .

FIG. 4 illustrates an optical PRML Read Channel including the Post-Processor of the present invention.

FIG. 5 illustrates trellis diagrams for when the ideal NRZ bit stream is [0000111000_b], but is falsely detected by the PRML read channel as [0001111000_b].

FIG. 6 illustrates trellis diagrams for when the ideal NRZ bit [1111000111_b] is falsely detected by the PRML read channel as [1110000111_b].

FIG. 7 illustrates an embodiment of the Post-Processor of FIG. 4.

FIG. 8 illustrates an embodiment of the Output Sequence Detector of FIG. 7.

FIG. 9 illustrates an embodiment of the First Difference Comparator of FIG. 7.

FIG. 10 illustrates an embodiment of the Second Difference Comparator of FIG. 7.

FIG. 11 illustrates an embodiment of the Error Correction Circuitry of FIG. 7.

FIG. 12 illustrates the timing relationship between the various signals for the Error Correction Circuitry of FIG. 11.

DETAILED DESCRIPTION

FIG. 4 illustrates in block diagram form optical PRML Read Channel (Read Channel) 50, which includes Post-Processor 52 of the present invention. Post-Processor 52 improves data detection within Read Channel 50 by correcting errors in the q_k signal that result from a dominant error event produced by baseline wandering. Briefly described, Post-Processor 52 first determines whether a bit sequence of the q_k signal matches that associated with the dominant error event. Next, Post-Processor 52 compares difference sequences of the y_k signal to difference sequences known to produce the dominant error event. Post-Processor 52 deems the error event to have occurred if the q_k bit sequence matches that associated with the dominant error event and the associated difference sequences match those known to produce to the dominant error event. If the dominant error event has occurred, Post-Processor 52 corrects the q_k signal to produce the corrected output signal, p_k .

A. The Dominant Error Event

Prior to a detailed discussion of Post-Processor 52, consider first the dominant error event within Read Channel 50. Produced by baseline wandering, the dominant error event causes a m_k NRZI bit sequence of $x000100100x_b$ (the earliest bit occupies the far left position of the bit sequence) to be detected as a q_k NRZI bit sequence of $x001000100x_b$. (Bolding in the m_k and q_k NRZI bit sequences indicates the location of the error event.) The dominant error event can be described in terms of states of Viterbi Decoder 36, which are defined by Non-Return to Zero (NRZ) format, rather than NRZI format. The dominant error event can be produced by either of two complementary cases:

- (1) The transmitted NRZ bit stream is [0000111000_b], but is falsely detected as the NRZ bit stream of [0001111000_b]; and
- (2) The transmitted NRZ bit stream is [1111000111_b], but is falsely detected as the NRZ bit stream of [1110000111_b].

The trellis diagrams of FIGS. 5 and 6 illustrate the sequence of events leading to each of the two complementary cases. Each trellis diagram includes a number of linked circles, which represent Viterbi Decoder states. Each trellis diagram includes two sequences of states, the ideal sequence

of states and the falsely detected sequence of states. The NRZ states of the ideal sequence are linked by dashed lines, while the NRZ states of the falsely detected sequence are linked by solid lines. The identity of each state is identified by a three bit number, s_k , within the state, which is defined as $[p_{k2}, p_{k1}, p_{k0}]$. Immediately to the right of each state is a box indicating the input, p_k , and the output, y_k , for the state. For all states p_k is a member of $\{1,0\}$ and y_k is a member of $\{3, 2, 0, -2, 3\}$ and is equal to $\frac{1}{2}p_{k3}+p_{k2}+p_{k1}+\frac{1}{2}p_{k0}$.

FIG. 5 illustrates trellis diagrams for Case 1: the ideal NRZ bit stream is [0000111000_b], but is falsely detected as [0001111000_b]. States 72–76 indicate the erroneous sequence of states, while States 82–86 indicate the ideal sequence of States. While in State 70, rather than generating a p_k of 0, Viterbi Decoder 36 generates a p_k of 1. This single instance of an erroneous value of p_k , subsequently causes Viterbi Decoder 36 to branch through States 72–76. This sequence of States produces four erroneous values of $[y_{k3}, y_{k2}, y_{k1}, y_{k0}]$ equal to $[3, 2, 0, -2]$. This sequence of states also produce a difference sequence $[(y_{k3}-y_{k2}), (y_{k2}-y_{k1}), (y_{k1}-y_{k0})]$ equal to $[1, 2, 2]$. In contrast, the correct sequence of States 82–86 produces $[y_{k3}, y_{k2}, y_{k1}, y_{k0}]$ equal to $[2, 0, 2, -3]$ and a difference sequence $[(y_{k3}-y_{k2}), (y_{k2}-y_{k1}), (y_{k1}-y_{k0})]$ equal to $[2, 2, 1]$.

FIG. 6 illustrates trellis diagrams for Case 2: The transmitted NRZ bit [1111000111_b] is falsely detected as [1110000111_b]. States 92–96 indicate the erroneous sequence of states, while States 100–104 indicate the ideal sequence. While in State 90, rather than generating a p_k of 1, Viterbi Decoder 36 outputs a p_k of 0. This single instance of an erroneous value of p_k , subsequently causes Viterbi Decoder 36 to branch through States 92–96. This sequence of States produces $[y_{k3}, y_{k2}, y_{k1}, y_{k0}]$ equal to $[-3, -2, 0, 2]$ and a difference sequence $[(y_{k3}-y_{k2}), (y_{k2}-y_{k1}), (y_{k1}-y_{k0})]$ equal to $[-1, -2, -2]$. In contrast, the correct sequence of States 100–104 produces $[y_{k3}, y_{k2}, y_{k1}, y_{k0}]$ equal to $[-2, 0, 2, 3]$ and a difference sequence $[(y_{k3}-y_{k2}), (y_{k2}-y_{k1}), (y_{k1}-y_{k0})]$ equal to $[-2, -2, -1]$.

Comparison of output and difference sequences for both the correct and erroneous sequences of States for Cases 1 and 2 reveals that their absolute values are the same. For example, the absolute values of the difference sequence for the erroneous sequence of States for Case 1 is $[|1|, |2|, |2|]$ and the absolute values of the difference sequence for the erroneous sequence of States for Case 2 is $[|-1|, |-2|, |-2|]$. The absolute values of the difference sequences for the correct sequence of States for Cases 1 and 2 is $[2, 2, 1]$. Combining knowledge of the absolute values of difference sequences for the correct and incorrect sequence of States with knowledge of the sequence of input values associated with the dominant error event permits correction and detection of errors caused by the dominant error event. In particular, an error associated with the dominant error event may be detected by searching for a sequence of p_k values of [10001_b] and determining whether the resulting input difference sequence $[|y_{k3}-y_{k2}|, |y_{k2}-y_{k1}|, |y_{k1}-y_{k0}|]$ is closer to the absolute values for the correct difference sequence, $[2, 2, 1]$, or the absolute values for the erroneous difference sequence, $[1, 2, 2]$.

B. The Post-Processor

FIG. 7 illustrates Post-Processor 52 in block diagram form. Post-Processor 52 includes Error Detection Circuitry 100 and Error Correction Circuitry 102. Error Detection Circuitry 100 examines the signals input to and output from Viterbi Decoder 36 to determine whether an error associated with the dominant error event has occurred. If so, Error

Detection Circuitry **100** informs Error Correction Circuitry **102** by asserting the Error signal on line **104**. Error Correction Circuitry **102** responds to assertion of the Error signal by replacing the erroneous sequence of bits of q_k with the correct sequence of bits.

Error Detection Circuitry **100** includes Output Sequence Detector **110**, Difference Sequence Comparator **114** and logical AND gate **120**. Output Sequence Detector **110** examines the output from Viterbi Detector **36**, the q_k signal, to determine whether the current output sequence matches that associated with the dominant error event. In particular, Output Sequence Detector **110** determines whether $[q_{k4}, q_{k3}, q_{k2}, q_{k1}, q_{k0}]$ equals $[10001_b]$. If so, Output Sequence Detector **110** asserts the Sequence Detect signal on line **112**. Difference Sequence Comparator **114** takes the input to Viterbi Decoder, the y_k signal, and generates a difference sequence that it compares to the incorrect difference sequence. In particular, Difference Sequence Comparator **114** compares input difference sequence $[|y_{k3}-y_{k2}|, |y_{k2}-y_{k1}|, |y_{k1}-y_{k0}|]$ to $[2, 2, 1]$. If the Difference Sequence Comparator **114** determines that the two sequences resemble one another, it asserts a First and a Second Difference Detect signal. These two signals, along with the Sequence Detect signal, are input to logical AND gate **120**. When all three of its input signals are asserted, logical AND gate asserts the Error signal on line **104**, indicating to Error Correction Circuitry **102** that a sequence of bits output by Viterbi Decoder **36** should be corrected. In particular, the Error signal indicates that an error occurred five clock cycles ago. This effects the design of Error Correction Circuitry **102**.

Difference Sequence Comparator **114** includes First Difference Comparator **130** and Second Difference Comparator **136**. First Difference Comparator **130** examines the $|y_{k3}-y_{k2}|$ term of the input difference sequence and compares it to a first range of values about the value associated with the dominant error event; i.e. 2. When $|y_{k3}-y_{k2}|$ is approximately 2, then First Difference Comparator **130** asserts the First Difference Detect signal. Second Difference Comparator **136** examines the $|y_{k0}-y_{k1}|$ term of the input difference sequence and compares it to a second range of values about the value associated with the dominant error event, 1. When $|y_{k1}-y_{k0}|$ is approximately 1, Second Difference Comparator **136** asserts the Second Difference Detect Signal. Difference Sequence Comparator **114** does not include circuitry for examining difference term $|y_{k2}-y_{k1}|$ because the same value is associated with both the correct and dominant error event difference sequences.

Error Correction Circuitry **102** includes First Delay Circuit **150**, Second Delay Circuit **154** and Bit Flip Circuitry **156**. First Delay Circuit **150** receives on line **111** the r_k signal, a delayed version of q_k , which it further delays to generate the s_k signal on line **152**. Second Delay Circuit **154** receives the Error signal on line **104**, which it further delays prior to coupling it to Bit Flip Circuitry **156**. In response to the Delayed Error signal, Bit Flip Circuitry **156** flips those bits of the s_k signal representing q_{k0} and q_{k1} to generate the corrected p_k signal.

B1. The Output Sequence Detector

FIG. **8** illustrates, in block diagram form, Output Sequence Detector **110**, which determines whether $[q_{k4}, q_{k3}, q_{k2}, q_{k1}, q_{k0}]$ matches the bit sequence associated with the dominant error event; i.e., $[11000_b]$. Output Sequence Detector **110** includes serially-coupled Latches **170**, **172**, **174**, **176** & **180** and logical AND gate **182**. The first of the serially-coupled Latches, Latch **170** has its D-input coupled to the NRZI output of Viterbi Decoder **36**, the q_k signal. The Q output of Latch **170** is used to route the value of q_{k4} to

logical AND gate **182**. The Q output of Latch **170** is coupled to the D-input of Latch **172**, whose Q Bar output is coupled to logical AND gate **182** to represent the inverse of q_{k3} . Latch **174** receives as its input the Q output of Latch **172**. The Q Bar output of Latch **174** is coupled to logical AND gate **182** to represent the inverse of q_{k2} . The Q output of Latch **174** is coupled to the input of Latch **176**, which couples its Q Bar output to logical AND gate **182** to represent the inverse of q_{k1} . Latch **180** receives its input from the Q output of Latch **176**. The Q output of Latch **180** is coupled to logical AND gate **182** to represent q_{k0} and is coupled to Error Correction Circuitry **102** as the r_k signal. Logical AND gate **182** asserts its output, the Seq Detect signal on line **112**, whenever each signal input to it is asserted; i.e. when $q_{k4}=1$, $\text{inverse}(q_{k3})=1$, $\text{inverse}(q_{k2})=1$, $\text{inverse}(q_{k1})=1$, and $q_{k0}=1$, which occurs only when $[q_{k4}, q_{k3}, q_{k2}, q_{k1}, q_{k0}]$ equals $[10001_b]$.

B2. The First Difference Comparator

FIG. **9** illustrates, in block diagram form, First Difference Comparator **130**, which determines whether the $|y_{k3}-y_{k2}|$ term of the input difference sequence is approximately equal to the value associated with the dominant error event sequence; i.e. 2. First Difference Comparator **130** includes Third Delay Circuit **190**, serially-coupled Latches **194**, **196** & **198**, Subtractor **200**, Absolute Value Circuit **202**, Less-Than-Equal Circuit **208**, Greater-Than Circuit **214**, and logical AND gate **218**. Third Delay Circuit **190** receives as its input the multi-bit y_k signal, which it delays and couples to Latch **194**. Latches **194** & **196** further delay this signal to generate a representation of y_{k3} , which is coupled to Subtractor **200** and Latch **198**. Latch **198** delays its input to generate as its output a signal representing y_{k2} . Subtractor **200** subtracts y_{k3} from y_{k2} to generate a First Difference signal on line **201**. The First Difference signal is coupled to Absolute Value Circuit **202**, which determines the absolute value of $y_{k3}-y_{k2}$ and represents it as the First Absolute Value signal on line **204**. Less-Than-Equal Circuit **208** determines whether the value represented by the First Absolute Value signal is less than, or equal to 2.5. If so, Less-Than-Equal Circuit **204** asserts its output signal, LTE, on line **210**. Greater-Than Circuit **214** operates simultaneous to Less-Than-Equal Circuit **208**, determining whether the value represented by the First Absolute Value signal is greater than 1.5. If so, Greater-Than Circuit **214** asserts its output signal, GT1, on line **216**. When both the LTE1 and GT1 signals are asserted logical AND gate **218** asserts its output signal, 1st Dif Detect, indicating that the value of the $|y_{k3}-y_{k2}|$ term of the input difference sequence is within a range of values associated with the dominant error event.

B3. The Second Difference Comparator

FIG. **10** illustrates, in block diagram form, Second Difference Comparator **136**, which determines whether the $|y_{k1}-y_{k0}|$ term of the input difference sequence is approximately equal to the value associated with the dominant error event; i.e., 1. Second Difference Comparator **136** includes Latches **230** & **232**, Subtractor **234**, Absolute Value Circuit **240**, Less-Than-Equal Circuit **246**, Greater-Than Circuit **252** and logical AND gate **256**. Latch **230** receives as its input the y_{k2} signal from First Difference Comparator **130**, which it further delays to generate its output, the y_{k1} signal. Latch **230** couples the y_{k1} signal to both Latch **232** and Subtractor **234**. Latch **232** delays the y_{k1} signal to generate the y_{k0} signal, which it couples to Subtractor **234**. Subtractor **234** subtracts y_{k0} from y_{k1} to generate the Second Difference signal, which it outputs on line **236**. Absolute Value Circuit **240** generates the Second Absolute Value signal by taking the absolute value of the Second Difference signal. Less-

Than-Equal Circuit **246** determines whether the Second Absolute Value is less than, or equal to, 1.5. If so, Less-Than-Equal Circuit **246** asserts its output, the LTE2 signal. Operating simultaneous to Less-Than-Equal Circuit **246**, Greater-Than Circuit **252** determines whether the Second Absolute Value is greater than 0.5. If so, Greater-Than Circuit **252** asserts its output, the GT2 signal. When both the LTE2 and GT2 signals are asserted logical AND gate **256** asserts its output signal, 2nd Dif Detect, indicating that the value of the $|y_{k1}-y_{k0}|$ term of the input difference sequence is within a range of values associated with a dominant error event.

B4. The Error Correction Circuitry

FIG. **11** illustrates, in block diagram form, Error Correction Circuitry **102**, which corrects the Viterbi Decoder output when a dominant error event is detected. In particular, when $[q_{k1}, q_{k0}]$ is erroneously detected as $[01_b]$ Error Correction Circuitry **102** forces $[q_{k1}, q_{k0}]$ to equal $[10_b]$ by flipping two bits. Error Correction Circuitry **102** includes First Delay Circuit **150**, Second Delay Circuit **154** and Bit Flip Circuitry **156**. First Delay Circuit **150** delays the r_k signal to produce the s_k signal on line **278** and Second Delay Circuit **154** delays the Error signal to produce the Enable signal on line **155**. Bit Flip Circuitry **156** responds to assertion of the Enable signal by simultaneously flipping q_{k1} while it is represented by the s_k signal and q_{k0} while it is represented by the u_k signal on line **283**.

First Delay Circuit **150** is realized as four serially coupled Latches **270**, **272**, **274** & **276** and outputs the s_k signal on line **278**. Second Delay Circuit **154** is also realized by five serially coupled latches (not illustrated) to produce the Enable signal on line **155**. Bit Flip Circuitry **156** includes logical XOR gate **280**, Latch **282** and logical XOR gate **284**. Logical XOR gate **280** performs an exclusive OR operation on the s_k and Enable signals to flip q_{k1} , producing its output signal t_k on line **281**, which is coupled to Latch **282**. Latch **282** couples its output, the u_k signal, on line **283** to logical XOR gate **284**. Logical XOR gate performs an exclusive OR operation on the u_k and Enable signals to produce the p_k signal.

FIG. **12** illustrates the timing relationship between the various signals relevant to Error Correction Circuitry **102**. The transitions of the clock, CK signal **298**, to which Error Correction Circuitry **102** responds are labeled "k0, k1, k2 . . ." etc, with lower numbered transitions occurring earlier than higher numbered transitions. In FIG. **12**, the error in the q_k signal **300** occurs at q_{k0} and q_{k1} ; however, this error is not recognized by Error Detect Circuitry **102** until CK_{k5} , at which time Error signal **304** is asserted. (The location of the representation of q_{k0} and q_{k1} in the signals of FIG. **12** is indicated by a circle.) At this point the r_k signal represents q_{k0} . Thus, by the time an error is detected the erroneous bits, q_{k0} and q_{k1} , are beginning to exit Output Sequence Detector **110**. First and Second Delay Circuits **150** and **154** adjust the relative delay between the Enable signal **306** and the s_k signal **308** so that Enable signal **306** is active while both q_{k0} and q_{k1} are represented by Bit Flip Circuitry **156**. In response to the four clock cycle delay provided by First Delay Circuit **150**, during CK_{k9} the s_k signal **308** represents q_{k0} and during CK_{k10} the s_k signal **308** represents q_{k1} . Consequently, during CK_{k10} Bit Flip Circuitry **156** represents both q_{k0} , via the u_k signal **314**, and q_{k1} , via the t_k signal **312**. Second Delay Circuit **154** delays the Error signal **304** by five clock cycles to bring the Enable signal **306** active at CK_{k10} .

During clock cycle CK_{k9} the inputs to logical XOR gate **280** are S_{k9} , representing q_{k0} , and Enable signal **306**, which

is inactive. Logical XOR gate **280** responds to these inputs by bringing t_{k9} to a voltage level representative of a logical 1. Latch **282** then latches t_{k9} . The next clock cycle, CK_{k10} , the inputs to logical XOR gate are s_{k10} , which now represents q_{k1} , and Enable signal **306**, which is now active. At c_{k10} , logical XOR gate **280** outputs a voltage level representative of a logical 1, thereby flipping q_{k1} as subsequently represented by the t_k signal **312** and Bit Flip Circuitry **156**. In response to CK_{k10} , Latch outputs t_{k9} as u_{k10} . During CK_{k10} Logical XOR gate **284** responds to the high levels of u_{k10} and the Enable signal **306**, by outputting a voltage level representative of a logical 0. This flips the subsequent representation of q_{k0} from a logical 1 to a logical 0. Latch **282** responds to CK_{k10} by latching in t_{k10} , which it outputs during CK_{k11} as a representation of q_{k1} , via u_{k11} . Logical XOR gate responds to u_{k11} and the inactive Enable signal **306** by outputting a logical high.

ALTERNATE EMBODIMENTS

While the present invention has been described with reference to a few specific embodiments, the description is illustrative of the invention and is not to be construed as limiting the invention. Various modifications may occur to those skilled in the art without departing from the true spirit and scope of the invention as defined by the appended claims.

What is claimed is:

1. An apparatus to correct an error in a serial output signal generated by an optical Partial Response Maximum Likelihood (PRML) read channel processing a first set of input signals, the serial output signal representing a series of consecutive bits, the first set of input signals representing digitally a series of consecutive values, the apparatus comprising:

error detection circuitry receiving the serial output signal and the first set of input signals, the error detection circuitry asserting an error signal in response to a determination that the serial output signal matches a first bit sequence associated with the error, that a first difference in a first pair of consecutive values represented by the first set of input signals is within a first range of values and that a second difference in a second pair of consecutive values represented by the first set of input signals is within a second range of values; and error correction circuitry receiving the error signal and the serial output signal, the error correction circuitry responding to assertion of the error signal by modifying a pair of consecutive bits represented by the serial output signal to generate a corrected output signal having a second bit sequence.

2. The apparatus of claim 1 wherein the error detection circuitry identifies the first bit sequence as 10001_b.

3. The apparatus of claim 2 wherein the error correction circuitry generates the second bit sequence of 01001_b.

4. The apparatus of claim 1 wherein the error detection circuitry comprises:

an output sequence detector analyzing the serial output signal to determine whether it matches the first bit sequence associated with the error and, if so, asserting a sequence detect signal;

a first difference comparator analyzing the first set of input signals to determine whether the first difference between the first pair of consecutive values represented by the first pair of input signals is within the first range of values and, if so, asserting a first difference detect signal;

9

- a second difference comparator analyzing the first set of input signals to determine whether the second difference between the second pair of consecutive values represented by the first pair of input signals is within the second range of values and, if so, asserting a second difference detect signal; and
 - a first logical AND gate generating the error signal in response to the first difference detect signal, the second difference detect signal and the sequence detect signal.
5. The apparatus of claim 4 wherein the first difference comparator comprises:
- a first delay circuit delaying the first set of input signals to generate a second set of input signals;
 - a first bank of latches receiving the second set of input signals and generating a third set of input signals, the third set of input signals representing one of the first pair of consecutive values represented by the first set of input signals;
 - a second bank of latches receiving the third set of input signals and generating the fourth set of input signals, the fourth set of input signals representing an other of the first pair of consecutive values represented by the first set of input signals; and
 - a first sequence detector analyzing the third and fourth set of input signals to determine whether the first difference is within the first range of values and, if so, asserting the first difference detect signal.
6. The apparatus of claim 5 wherein the first range of values comprises values between 2.5 and 1.5.
7. The apparatus of claim 6 wherein the first sequence detector comprises:
- a first subtractor circuit for subtracting the fourth set of input signals from the third set of input signals to generate a first set of difference signals;
 - a first absolute value circuit receiving the first set of difference signals and generating a first set of absolute value signals representing a first absolute value of the first difference;
 - a first comparator circuit analyzing the first set of absolute value signals to determine whether the first absolute value is less than 2.5 and, if so, asserting a first comparator output signal;
 - a second comparator circuit analyzing the first set of absolute value signals to determine whether the first absolute value is greater than 1.5 and, if so, asserting a second comparator output signal; and
 - a second logical AND gate generating the first difference detect signal in response to the first and the second comparator output signals.
8. The apparatus of claim 4 wherein the second difference comparator comprises:
- a third bank of latches receiving the first set of input signals and generating a fifth set of input signals, the fifth set of input signals representing one of the second pair of consecutive values represented by the first set of input signals;
 - a fourth bank of latches receiving the fifth set of input signals and generating the sixth set of input signals, the sixth set of input signals representing an other of the second pair of consecutive values represented by the first set of input signals; and
 - a second sequence detector analyzing the fifth and sixth set of input signals to determine whether the second difference is within the second range of values and, if so, asserting the second difference detect signal.

10

9. The apparatus of claim 8 wherein the second range of values comprises values between 1.5 and 0.5.
10. The apparatus of claim 9 wherein the second sequence detector comprises:
- a second subtractor circuit for subtracting the fifth set of input signals from the sixth set of input signals to generate a second set of difference signals;
 - a second absolute value circuit receiving the second set of difference signals and generating a second set of absolute value signals representing a second absolute value of the second difference;
 - a third comparator circuit analyzing the second set of absolute value signals to determine whether the second absolute value is less than 1.5 and, if so, asserting a third comparator output signal;
 - a fourth comparator circuit analyzing the second set of absolute value signals to determine whether the second absolute value is greater than 0.5 and, if so, asserting a fourth comparator output signal; and
 - a third logical AND gate generating the second difference detect signal in response to the third and the fourth comparator output signals.
11. The apparatus of claim 4 wherein the output sequence detector comprises:
- a first latch receiving the serial output signal and outputting a first delayed output signal;
 - a second latch receiving the first delayed output signal and outputting a second delayed output signal and a first complement signal, the first complement signal being a complement of the second delayed output signal;
 - a third latch receiving the second delayed signal and outputting a third delayed output signal and a second complement signal, the second complement signal being a complement of the third delayed output signal;
 - a fourth latch receiving as an input the third delayed output signal and outputting a fourth delayed output signal and a third complement signal, the third complement signal being a complement of the third delayed output signal;
 - a fifth latch receiving as an input the fourth delayed output signal and outputting a fifth delayed uncorrected output signal; and
 - a fourth logical AND gate receiving as inputs the first and fifth delayed output signals and the first, second and third complement signals, the fourth logical AND gate generating the sequence detect signal.
12. An apparatus for improved data detection in an optical Partial Recovery Maximum Likelihood (PRML) read channel, the apparatus comprising:
- a Viterbi detector receiving a first set of digital input signals representing a series of consecutive data values, the Viterbi detector generating an output signal in response to the first set of digital input signals, the output signal representing a set of serial Non-Return to Zero Invert (NRZI) bits, baseline wandering of the first set of digital input signals causing an error to occur in the output signal;
 - an output sequence detector analyzing the output signal to determine whether it matches a first bit sequence associated with the error and, if so, asserting a sequence detect signal;
 - a first difference comparator analyzing the first set of digital input signals to determine whether a first difference between a first pair of consecutive data values represented by the first set of digital input signals is

11

within a first range of values and, if so, asserting a first difference detect signal;

- a second difference comparator analyzing the first set of input signals to determine whether a second difference between a second pair of consecutive data values represented by the first set of digital input signals is within a second range of values and, if so, asserting a second difference detect signal;
- a first logical AND gate generating an error signal in response to the first difference detect signal, the second difference detect signal and the sequence detect signal; and

error correction circuitry receiving the error signal and the output signal, the error correction circuitry responding to the error signal by modifying a pair of consecutive NRZI bits represented by the output signal to generate a corrected output signal having a second bit sequence different than the first bit sequence.

13. The apparatus of claim 12 wherein the output sequence detector identifies the first bit sequence of 10001_b and the error correction circuitry generates the second bit sequence of 01001_b .

14. The apparatus of claim 13 wherein the first range of values comprises values between 2.5 and 1.5 and the second range of values comprises values between 1.5 and 0.5.

15. The apparatus of claim 14 wherein the first difference comparator comprises:

- a first delay circuit delaying the first set of input signals to generate a second set of input signals;
- a first bank of latches receiving the second set of input signals and generating a third set of input signals, the third set of input signals representing one of the first pair of consecutive values represented by the first set of input signals;
- a second bank of latches receiving the third set of input signals and generating a fourth set of input signals, the fourth set of input signals representing an other of the first pair of consecutive values represented by the first set of input signals;
- a first subtractor circuit for subtracting the third set of input signals from the fourth set of input signals to generate a first set of difference signals;
- a first absolute value circuit receiving the first set of difference signals and generating a first set of absolute value signals representing a first absolute value of the first difference;
- a first comparator circuit analyzing the first set of absolute value signals to determine whether the first absolute value is less than 2.5 and, if so, asserting a first comparator output signal;
- a second comparator circuit analyzing the first set of absolute value signals to determine whether the first absolute value is greater than 1.5 and, if so, asserting a second comparator output signal; and

12

a second logical AND gate generating the first difference detect signal in response to the first and the second comparator output signals.

16. The apparatus of claim 15 wherein the second difference comparator comprises:

- a third bank of latches receiving the fourth set of input signals and generating a fifth set of input signals, the fifth set of input signals representing one of the second pair of consecutive values represented by the first set of input signals;
- a fourth bank of latches receiving the fifth set of input signals and generating the sixth set of input signals, the sixth set of input signals representing an other of the second pair of consecutive values represented by the first set of input signals;
- a second subtractor circuit for subtracting the fifth set of input signals from the sixth set of input signals to generate a second set of difference signals;
- a second absolute value circuit receiving the second set of difference signals and generating a second set of absolute value signals representing a second absolute value of the second difference;
- a third comparator circuit analyzing the second set of absolute value signals to determine whether the second absolute value is less than 1.5 and, if so, asserting a third comparator output signal;
- a fourth comparator circuit analyzing the second set of absolute value signals to determine whether the second absolute value is greater than 0.5 and, if so, asserting a fourth comparator output signal; and
- a third logical AND gate generating the second difference detect signal in response to the third and the fourth comparator output signals.

17. The apparatus of claim 16 wherein the output sequence detector delays the output signal to generate a second output signal and wherein the error correction circuitry comprises:

- a second delay circuit delaying the second output signal to generate a third output signal, the second delay circuit having a second delay;
- a third delay circuit delaying the error signal to generate a delayed error signal, the third delay circuit having a third delay that is approximately equal to the second delay;
- bit flip circuitry receiving the third output signal and the delayed error signal, the bit flip circuitry responding to assertion of the delayed error signal by flipping a final two consecutive NRZI bits of the series of consecutive NRZI bits represented by the third output signal to generate the corrected output signal.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,581,181 B1
DATED : July 17, 2003
INVENTOR(S) : Gene Sonu

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Title page, Item [54] and Column 1, line 1,
After “**DOMINANT ERROR**”, please insert -- **EVENT** --.

Signed and Sealed this

Twenty-first Day of October, 2003

A handwritten signature in black ink, appearing to read "James E. Rogan", with a horizontal line drawn underneath it.

JAMES E. ROGAN
Director of the United States Patent and Trademark Office