



(51) International Patent Classification:
A24F 47/00 (2006.01)

(21) International Application Number:
PCT/IB2017/050035

(22) International Filing Date:
5 January 2017 (05.01.2017)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
14/988,496 5 January 2016 (05.01.2016) US

(71) Applicant: RAI STRATEGIC HOLDINGS, INC.
[US/US]; 401 North Main Street, Winston-Salem, NC
27101 (US).

(72) Inventor: SUR, Rajesh; 1774 Queen Catherine Lane,
Winston-Salem, NC 27106 (US).

(74) Agent: SPENCE, Andrew T.; Womble Carlyle Sandridge
& Rice, LLP, Attn: Patent Docketing, P.O. Box 7037, At-
lanta, GA 30357-0037 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,

HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN,
KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA,
MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG,
NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS,
RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY,
TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the
earlier application (Rule 4.17(iii))

Published:

- with international search report (Art. 21(3))

(54) Title: CAPACITIVE SENSING INPUT DEVICE FOR AN AEROSOL DELIVERY DEVICE




FIG. 2

(57) Abstract: A control body (102) is coupled or coupleable with a cartridge (104) that is equipped with a heating element (222) and contains an aerosol precursor composition, the control body (102) and cartridge (104) forming an aerosol delivery device (100). The control body (102) includes a control component (208) to control the heating element (222) to activate and vaporize components of the aerosol precursor composition. An input device (248) including a capacitive sensor is configured to detect a user input. And the input device (248) or control component (208) controls operation of at least one functional element of the control body (102), cartridge (104) or aerosol delivery device in response to the user input so detected. In another aspect, a cartridge (104) may include an input device (252) including a capacitive sensor to detect a user input, and operation of functional element(s) may be controlled in response to thereto.

CAPACITIVE SENSING INPUT DEVICE FOR AN AEROSOL DELIVERY DEVICE

TECHNOLOGICAL FIELD

The present disclosure relates to aerosol delivery devices such as smoking articles, and more particularly to aerosol delivery devices that may utilize electrically generated heat for the production of aerosol (e.g., smoking articles commonly referred to as electronic cigarettes). The smoking articles may be configured to heat an aerosol precursor, which may incorporate materials that may be made or derived from, or otherwise incorporate tobacco, the precursor being capable of forming an inhalable substance for human consumption.

BACKGROUND

Many smoking devices have been proposed through the years as improvements upon, or alternatives to, smoking products that require combusting tobacco for use. Many of those devices purportedly have been designed to provide the sensations associated with cigarette, cigar or pipe smoking, but without delivering considerable quantities of incomplete combustion and pyrolysis products that result from the burning of tobacco. To this end, there have been proposed numerous smoking products, flavor generators and medicinal inhalers that utilize electrical energy to vaporize or heat a volatile material, or attempt to provide the sensations of cigarette, cigar or pipe smoking without burning tobacco to a significant degree. See, for example, the various alternative smoking articles, aerosol delivery devices and heat generating sources set forth in the background art described in U.S. Pat. Nos. 7,726,320 to Robinson et al. and 8,881,737 to Collett et al., which are incorporated herein by reference. See also, for example, the various types of smoking articles, aerosol delivery devices and electrically-powered heat generating sources referenced by brand name and commercial source in U.S. Pat. Pub. No. 2015/0216232 to Bless et al., which is incorporated herein by reference. Additionally, various types of electrically powered aerosol and vapor delivery devices also have been proposed in U.S. Pat. Pub. Nos. 2014/0096781 to Sears et al. and 2014/0283859 to Minskoff et al., as well as U.S. Pat. App. Ser. Nos. 14/282,768 to Sears et al., filed May 20, 2014; 14/286,552 to Brinkley et al., filed May 23, 2014; 14/327,776 to Ampolini et al., filed July 10, 2014; and 14/465,167 to Worm et al., filed August 21, 2014; all of which are incorporated herein by reference.

BRIEF SUMMARY

The present disclosure relates to aerosol delivery devices, methods of forming such devices, and elements of such devices. The present disclosure includes, without limitation, the following example implementations.

Example Implementation 1: A control body coupled or coupleable with a cartridge that is equipped with a heating element and contains an aerosol precursor composition, the control body being coupled or coupleable with the cartridge to form an aerosol delivery device in which the heating element is configured to activate and vaporize components of the aerosol precursor composition, the control body

comprising a control component configured to operate in an active mode in which the control body is coupled with the cartridge, the control component in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition; and an input device including a capacitive sensor configured to detect a user input, the input device or control component being further configured to control operation of at least one functional element of the control body, cartridge or aerosol delivery device in response to the user input so detected.

Example Implementation 2: The control body of the preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a zero-dimensional capacitive sensor configured to implement a button.

Example Implementation 3: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a one-dimensional capacitive sensor configured to implement a slider or wheel.

Example Implementation 4: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a two-dimensional capacitive sensor configured to implement a touchscreen or touchpad.

Example Implementation 5: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a three-dimensional capacitive sensor configured to detect a presence of an object nearby the control body, and thereby the user input, without requiring any physical contact with the object.

Example Implementation 6: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the input device or control component being configured to control at least one functional element includes being configured to alter a power or locked state of the control body, cartridge or aerosol delivery device.

Example Implementation 7: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the input device or control component being configured to control at least one functional element includes being configured to alter an operational parameter of the at least one functional element.

Example Implementation 8: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the at least one functional element includes at least one sensor, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the at least one sensor.

Example Implementation 9: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the at least one functional element includes a communication interface that is coupled to the control component and configured to enable wireless communication, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the communication interface.

Example Implementation 10: The control body of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor includes a shield electrode configured to at least partially attenuate an effect of liquid on the capacitive sensor, and a guard sensor configured to detect above a threshold level of liquid on the capacitive sensor.

5 **Example Implementation 11:** A cartridge coupled or coupleable with a control body that is equipped with a control component, the control body being coupled or coupleable with the cartridge to form an aerosol delivery device, the cartridge comprising a housing defining a reservoir configured to retain aerosol precursor composition; a heating element configured to operate in an active mode in which the
10 cartridge is coupled with the control body, the heating element in the active mode being controllable by the control component to activate and vaporize components of the aerosol precursor composition; and an input device including a capacitive sensor configured to detect a user input, the input device or control component being configured to control operation of at least one functional element of the control body, cartridge or aerosol delivery device in response to the user input so detected.

15 **Example Implementation 12:** The cartridge of the preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a zero-dimensional capacitive sensor configured to implement a button.

20 **Example Implementation 13:** The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a one-dimensional capacitive sensor configured to implement a slider or wheel.

25 **Example Implementation 14:** The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a two-dimensional capacitive sensor configured to implement a touchscreen or touchpad.

30 **Example Implementation 15:** The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor is a three-dimensional capacitive sensor configured to detect a presence of an object nearby the cartridge, and thereby the user input, without requiring any physical contact with the object.

35 **Example Implementation 16:** The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the input device or control component being configured to control at least one functional element includes being configured to alter a power or locked state of the control body, cartridge or aerosol delivery device.

40 **Example Implementation 17:** The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the input device or control component being configured to control at least one functional element includes being configured to alter an operational parameter of the at least one functional element.

45 **Example Implementation 18:** The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the at least one functional element includes at least one

sensor, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the at least one sensor.

Example Implementation 19: The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the at least one functional element includes a communication interface that is coupled to the control component and configured to enable wireless communication, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the communication interface.

Example Implementation 20: The cartridge of any preceding or any subsequent example implementation, or any combination thereof, wherein the capacitive sensor includes a shield electrode configured to at least partially attenuate an effect of liquid on the capacitive sensor, and a guard sensor configured to detect above a threshold level of liquid on the capacitive sensor.

These and other features, aspects, and advantages of the present disclosure will be apparent from a reading of the following detailed description together with the accompanying drawings, which are briefly described below. The present disclosure includes any combination of two, three, four or more features or elements set forth in this disclosure, regardless of whether such features or elements are expressly combined or otherwise recited in a specific example implementation described herein. This disclosure is intended to be read holistically such that any separable features or elements of the disclosure, in any of its aspects and example implementations, should be viewed as combinable, unless the context of the disclosure clearly dictates otherwise.

It will therefore be appreciated that this Brief Summary is provided merely for purposes of summarizing some example implementations so as to provide a basic understanding of some aspects of the disclosure. Accordingly, it will be appreciated that the above described example implementations are merely examples and should not be construed to narrow the scope or spirit of the disclosure in any way. Other example implementations, aspects and advantages will become apparent from the following detailed description taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of some described example implementations.

BRIEF DESCRIPTION OF THE DRAWING(S)

Having thus described the disclosure in the foregoing general terms, reference will now be made to the accompanying drawings, which are not necessarily drawn to scale, and wherein:

FIG. 1 illustrates a side view of an aerosol delivery device including a cartridge coupled to a control body according to an example implementation of the present disclosure;

FIG. 2 is a partially cut-away view of the aerosol delivery device according to various example implementations;

FIG. 3 illustrates an input device according to various example implementations; and

FIG. 4 illustrates a capacitive sensor according to various example implementations.

DETAILED DESCRIPTION

The present disclosure will now be described more fully hereinafter with reference to example implementations thereof. These example implementations are described so that this disclosure will be thorough and complete, and will fully convey the scope of the disclosure to those skilled in the art. Indeed, the disclosure may be embodied in many different forms and should not be construed as limited to the implementations set forth herein; rather, these implementations are provided so that this disclosure will satisfy applicable legal requirements. As used in the specification and the appended claims, the singular forms “a,” “an,” “the” and the like include plural referents unless the context clearly dictates otherwise.

As described hereinafter, example implementations of the present disclosure relate to aerosol delivery systems. Aerosol delivery systems according to the present disclosure use electrical energy to heat a material (preferably without combusting the material to any significant degree) to form an inhalable substance; and components of such systems have the form of articles most preferably are sufficiently compact to be considered hand-held devices. That is, use of components of preferred aerosol delivery systems does not result in the production of smoke in the sense that aerosol results principally from by-products of combustion or pyrolysis of tobacco, but rather, use of those preferred systems results in the production of vapors resulting from volatilization or vaporization of certain components incorporated therein. In some example implementations, components of aerosol delivery systems may be characterized as electronic cigarettes, and those electronic cigarettes most preferably incorporate tobacco and/or components derived from tobacco, and hence deliver tobacco derived components in aerosol form.

Aerosol generating pieces of certain preferred aerosol delivery systems may provide many of the sensations (e.g., inhalation and exhalation rituals, types of tastes or flavors, organoleptic effects, physical feel, use rituals, visual cues such as those provided by visible aerosol, and the like) of smoking a cigarette, cigar or pipe that is employed by lighting and burning tobacco (and hence inhaling tobacco smoke), without any substantial degree of combustion of any component thereof. For example, the user of an aerosol generating piece of the present disclosure can hold and use that piece much like a smoker employs a traditional type of smoking article, draw on one end of that piece for inhalation of aerosol produced by that piece, take or draw puffs at selected intervals of time, and the like.

Aerosol delivery systems of the present disclosure also can be characterized as being vapor-producing articles or medicament delivery articles. Thus, such articles or devices can be adapted so as to provide one or more substances (e.g., flavors and/or pharmaceutical active ingredients) in an inhalable form or state. For example, inhalable substances can be substantially in the form of a vapor (i.e., a substance that is in the gas phase at a temperature lower than its critical point). Alternatively, inhalable substances can be in the form of an aerosol (i.e., a suspension of fine solid particles or liquid droplets in a gas). For purposes of simplicity, the term “aerosol” as used herein is meant to include vapors, gases and aerosols of a form or type suitable for human inhalation, whether or not visible, and whether or not of a form that might be considered to be smoke-like.

Aerosol delivery systems of the present disclosure generally include a number of components provided within an outer body or shell, which may be referred to as a housing. The overall design of the outer body or shell can vary, and the format or configuration of the outer body that can define the overall size and shape of the aerosol delivery device can vary. Typically, an elongated body resembling the shape of a cigarette or cigar can be formed from a single, unitary housing or the elongated housing can be formed of two or more separable bodies. For example, an aerosol delivery device can comprise an elongated shell or body that can be substantially tubular in shape and, as such, resemble the shape of a conventional cigarette or cigar. In one example, all of the components of the aerosol delivery device are contained within one housing. Alternatively, an aerosol delivery device can comprise two or more housings that are joined and are separable. For example, an aerosol delivery device can possess at one end a control body comprising a housing containing one or more reusable components (e.g., an accumulator such as a rechargeable battery (e.g., lithium-ion battery), solid-state battery, thin-film solid-state battery, and/or supercapacitor, and various electronics for controlling the operation of that article), and at the other end and removably coupleable thereto, an outer body or shell containing a disposable portion (e.g., a disposable flavor-containing cartridge).

Aerosol delivery systems of the present disclosure most preferably comprise some combination of a power source (i.e., an electrical power source), at least one control component (e.g., means for actuating, controlling, regulating and ceasing power for heat generation, such as by controlling electrical current flow the power source to other components of the article – e.g., a microprocessor, individually or as part of a microcontroller), a heater or heat generation member (e.g., an electrical resistance heating element or other component, which alone or in combination with one or more further elements may be commonly referred to as an “atomizer”), an aerosol precursor composition (e.g., commonly a liquid capable of yielding an aerosol upon application of sufficient heat, such as ingredients commonly referred to as “smoke juice,” “e-liquid” and “e-juice”), and a mouthend region or tip for allowing draw upon the aerosol delivery device for aerosol inhalation (e.g., a defined airflow path through the article such that aerosol generated can be withdrawn therefrom upon draw).

More specific formats, configurations and arrangements of components within the aerosol delivery systems of the present disclosure will be evident in light of the further disclosure provided hereinafter. Additionally, the selection and arrangement of various aerosol delivery system components can be appreciated upon consideration of the commercially available electronic aerosol delivery devices, such as those representative products referenced in background art section of the present disclosure.

In various examples, an aerosol delivery device can comprise a reservoir configured to retain the aerosol precursor composition. The reservoir particularly can be formed of a porous material (e.g., a fibrous material) and thus may be referred to as a porous substrate (e.g., a fibrous substrate).

A fibrous substrate useful as a reservoir in an aerosol delivery device can be a woven or nonwoven material formed of a plurality of fibers or filaments and can be formed of one or both of natural fibers and synthetic fibers. For example, a fibrous substrate may comprise a fiberglass material. In particular

examples, a cellulose acetate material can be used. In other example implementations, a carbon material can be used. A reservoir may be substantially in the form of a container and may include a fibrous material included therein.

FIG. 1 illustrates a side view of an aerosol delivery device **100** including a control body **102** and a cartridge **104**, according to various example implementations of the present disclosure. In particular, FIG. 1 illustrates the control body and the cartridge coupled to one another. The control body and the cartridge may be detachably aligned in a functioning relationship. Various mechanisms may connect the cartridge to the control body to result in a threaded engagement, a press-fit engagement, an interference fit, a magnetic engagement or the like. The aerosol delivery device may be substantially rod-like, substantially tubular shaped, or substantially cylindrically shaped in some example implementations when the cartridge and the control body are in an assembled configuration. The aerosol delivery device may also be substantially rectangular or rhomboidal in cross-section, which may lend itself to greater compatibility with a substantially flat or thin-film power source, such as a power source including a flat battery. The cartridge and control body may include separate, respective housings or outer bodies, which may be formed of any of a number of different materials. The housing may be formed of any suitable, structurally-sound material. In some examples, the housing may be formed of a metal or alloy, such as stainless steel, aluminum or the like. Other suitable materials include various plastics (e.g., polycarbonate), metal-plating over plastic, ceramics and the like.

In some example implementations, one or both of the control body **102** or the cartridge **104** of the aerosol delivery device **100** may be referred to as being disposable or as being reusable. For example, the control body may have a replaceable battery or a rechargeable battery and thus may be combined with any type of recharging technology, including connection to a typical wall charger, connection to a car charger (i.e., a cigarette lighter receptacle), connection to a computer, such as through a universal serial bus (USB) cable or connector, connection to a photovoltaic cell (sometimes referred to as a solar cell) or solar panel of solar cells, or connection to a RF-to-DC converter. Further, in some example implementations, the cartridge may comprise a single-use cartridge, as disclosed in U.S. Pat. No. 8,910,639 to Chang et al., which is incorporated herein by reference in its entirety.

FIG. 2 more particularly illustrates the aerosol delivery device **100**, in accordance with some example implementations. As seen in the cut-away view illustrated therein, again, the aerosol delivery device can comprise a control body **102** and a cartridge **104** each of which include a number of respective components. The components illustrated in FIG. 2 are representative of the components that may be present in a control body and cartridge and are not intended to limit the scope of components that are encompassed by the present disclosure. As shown, for example, the control body can be formed of a control body shell **206** that can include a control component **208** (e.g., a microprocessor, individually or as part of a microcontroller), a flow sensor **210**, a power source **212** and one or more light-emitting diodes (LEDs) **214**, and such components can be variably aligned. The power source may include, for example, a battery (single-use or rechargeable), solid-state battery, thin-film solid-state battery, supercapacitor or the like, or

some combination thereof. Some examples of a suitable power source are provided in U.S. Pat. App. Ser. No. 14/918,926 to Sur et al., filed October 21, 2015, which is incorporated by reference. The LED may be one example of a suitable visual indicator with which the aerosol delivery device **100** may be equipped. Other indicators such as audio indicators (e.g., speakers), haptic indicators (e.g., vibration motors) or the like
5 can be included in addition to or as an alternative to visual indicators such as the LED.

The cartridge **104** can be formed of a cartridge shell **216** enclosing a reservoir **218** configured to retain the aerosol precursor composition, and including a heater **222** (sometimes referred to as a heating element). In various configurations, this structure may be referred to as a tank; and accordingly, the terms “cartridge,” “tank” and the like may be used interchangeably to refer to a shell or other housing enclosing a
10 reservoir for aerosol precursor composition, and including a heater.

As shown, in some examples, the reservoir **218** may be in fluid communication with a liquid transport element **220** adapted to wick or otherwise transport an aerosol precursor composition stored in the reservoir housing to the heater **222**. In some examples, a valve may be positioned between the reservoir and heater, and configured to control an amount of aerosol precursor composition passed or delivered from the
15 reservoir to the heater.

Various examples of materials configured to produce heat when electrical current is applied therethrough may be employed to form the heater **222**. The heater in these examples may be a resistive heating element such as a wire coil, micro heater or the like. Example materials from which the heating element may be formed include Kanthal (FeCrAl), Nichrome, stainless steel, Molybdenum disilicide
20 (MoSi₂), molybdenum silicide (MoSi), Molybdenum disilicide doped with Aluminum (Mo(Si,Al)₂), graphite and graphite-based materials (e.g., carbon-based foams and yarns) and ceramics (e.g., positive or negative temperature coefficient ceramics). Example implementations of heaters or heating members useful in aerosol delivery devices according to the present disclosure are further described below, and can be incorporated into devices such as illustrated in FIG. 2 as described herein.

An opening **224** may be present in the cartridge shell **216** (e.g., at the mouthend) to allow for egress of formed aerosol from the cartridge **104**.
25

The cartridge **104** also may include one or more electronic components **226**, which may include an integrated circuit, a memory component, a sensor, or the like. The electronic components may be adapted to communicate with the control component **208** and/or with an external device by wired or wireless means.

30 The electronic components may be positioned anywhere within the cartridge or a base **228** thereof.

Although the control component **208** and the flow sensor **210** are illustrated separately, it is understood that the control component and the flow sensor may be combined as an electronic circuit board with the air flow sensor attached directly thereto. Further, the electronic circuit board may be positioned horizontally relative the illustration of FIG. 1 in that the electronic circuit board can be lengthwise parallel to
35 the central axis of the control body. In some examples, the air flow sensor may comprise its own circuit board or other base element to which it can be attached. In some examples, a flexible circuit board may be utilized. A flexible circuit board may be configured into a variety of shapes, include substantially tubular

shapes. In some examples, a flexible circuit board may be combined with, layered onto, or form part or all of a heater substrate as further described below.

The control body **102** and the cartridge **104** may include components adapted to facilitate a fluid engagement therebetween. As illustrated in FIG. 2, the control body can include a coupler **230** having a cavity **232** therein. The base **228** of the cartridge can be adapted to engage the coupler and can include a projection **234** adapted to fit within the cavity. Such engagement can facilitate a stable connection between the control body and the cartridge as well as establish an electrical connection between the power source **212** and control component **208** in the control body and the heater **222** in the cartridge. Further, the control body shell **206** can include an air intake **236**, which may be a notch in the shell where it connects to the coupler that allows for passage of ambient air around the coupler and into the shell where it then passes through the cavity **232** of the coupler and into the cartridge through the projection **234**.

A coupler and a base useful according to the present disclosure are described in U.S. Pat. App. Pub. No. 2014/0261495 to Novak et al., which is incorporated herein by reference in its entirety. For example, the coupler **230** as seen in FIG. 2 may define an outer periphery **238** configured to mate with an inner periphery **240** of the base **228**. In one example the inner periphery of the base may define a radius that is substantially equal to, or slightly greater than, a radius of the outer periphery of the coupler. Further, the coupler may define one or more protrusions **242** at the outer periphery configured to engage one or more recesses **244** defined at the inner periphery of the base. However, various other examples of structures, shapes and components may be employed to couple the base to the coupler. In some examples the connection between the base of the cartridge **104** and the coupler of the control body **102** may be substantially permanent, whereas in other examples the connection therebetween may be releasable such that, for example, the control body may be reused with one or more additional cartridges that may be disposable and/or refillable.

The aerosol delivery device **100** may be substantially rod-like or substantially tubular shaped or substantially cylindrically shaped in some examples. In other examples, further shapes and dimensions are encompassed – e.g., a rectangular or triangular cross-section, multifaceted shapes, or the like.

The reservoir **218** illustrated in FIG. 2 can be a container or can be a fibrous reservoir, as presently described. For example, the reservoir can comprise one or more layers of nonwoven fibers substantially formed into the shape of a tube encircling the interior of the cartridge shell **216**, in this example. An aerosol precursor composition can be retained in the reservoir. Liquid components, for example, can be sorptively retained by the reservoir. The reservoir can be in fluid connection with the liquid transport element **220**. The liquid transport element can transport the aerosol precursor composition stored in the reservoir via capillary action to the heater **222** that is in the form of a metal wire coil in this example. As such, the heater is in a heating arrangement with the liquid transport element. Example implementations of reservoirs and transport elements useful in aerosol delivery devices according to the present disclosure are further described below, and such reservoirs and/or transport elements can be incorporated into devices such as illustrated in FIG. 2 as described herein. In particular, specific combinations of heating members and

transport elements as further described below may be incorporated into devices such as illustrated in FIG. 2 as described herein.

In use, when a user draws on the aerosol delivery device **100**, airflow is detected by the flow sensor **210**, and the heater **222** is activated to vaporize components of the aerosol precursor composition. Drawing upon the mouthend of the aerosol delivery device causes ambient air to enter the air intake **236** and pass through the cavity **232** in the coupler **230** and the central opening in the projection **234** of the base **228**. In the cartridge **104**, the drawn air combines with the formed vapor to form an aerosol. The aerosol is whisked, aspirated or otherwise drawn away from the heater and out the opening **224** in the mouthend of the aerosol delivery device.

In some examples, the aerosol delivery device **100** may include a number of additional software-controlled functions. For example, the aerosol delivery device may include a power-source protection circuit configured to detect power-source input, loads on the power-source terminals, and charging input. The power-source protection circuit may include short-circuit protection, under-voltage lock out and/or over-voltage charge protection. The aerosol delivery device may also include components for ambient temperature measurement, and its control component **208** may be configured to control at least one functional element to inhibit power-source charging – particularly of any battery – if the ambient temperature is below a certain temperature (e.g., 0 °C) or above a certain temperature (e.g., 45 °C) prior to start of charging or during charging.

Power delivery from the power source **212** may vary over the course of each puff on the device **100** according to a power control mechanism. The device may include a “long puff” safety timer such that in the event that a user or component failure (e.g., flow sensor **210**) causes the device to attempt to puff continuously, the control component **208** may control at least one functional element to terminate the puff automatically after some period of time (e.g., four seconds). Further, the time between puffs on the device may be restricted to less than a period of time (e.g., 100 seconds). A watchdog safety timer may automatically reset the aerosol delivery device if its control component or software running on it becomes unstable and does not service the timer within an appropriate time interval (e.g., eight seconds). Further safety protection may be provided in the event of a defective or otherwise failed flow sensor **210**, such as by permanently disabling the aerosol delivery device in order to prevent inadvertent heating. A puffing limit switch may deactivate the device in the event of a pressure sensor fail causing the device to continuously activate without stopping after the four second maximum puff time.

The aerosol delivery device **100** may include a puff tracking algorithm configured for heater lockout once a defined number of puffs has been achieved for an attached cartridge (based on the number of available puffs calculated in light of the e-liquid charge in the cartridge). The aerosol delivery device may include a sleep, standby or low-power mode function whereby power delivery may be automatically cut off after a defined period of non-use. Further safety protection may be provided in that all charge/discharge cycles of the power source **212** may be monitored by the control component **208** over its lifetime. After the power source has attained the equivalent of a predetermined number (e.g., 200) of full discharge and full

recharge cycles, it may be declared depleted, and the control component may control at least one functional element to prevent further charging of the power source.

The various components of an aerosol delivery device according to the present disclosure can be chosen from components described in the art and commercially available. Examples of batteries that can be used according to the disclosure are described in U.S. Pat. App. Pub. No. 2010/0028766 to Peckerar et al., which is incorporated herein by reference in its entirety.

The aerosol delivery device **100** can incorporate the sensor **210** or another sensor or detector for control of supply of electric power to the heater **222** when aerosol generation is desired (e.g., upon draw during use). As such, for example, there is provided a manner or method of turning off power to the heater when the aerosol delivery device is not be drawn upon during use, and for turning on power to actuate or trigger the generation of heat by the heater during draw. Additional representative types of sensing or detection mechanisms, structure and configuration thereof, components thereof, and general methods of operation thereof, are described in U.S. Pat. No. 5,261,424 to Sprinkel, Jr., U.S. Pat. No. 5,372,148 to McCafferty et al., and PCT Pat. App. Pub. No. WO 2010/003480 to Flick, all of which are incorporated herein by reference in their entireties.

The aerosol delivery device **100** most preferably incorporates the control component **208** or another control mechanism for controlling the amount of electric power to the heater **222** during draw.

Representative types of electronic components, structure and configuration thereof, features thereof, and general methods of operation thereof, are described in U.S. Pat. No. 4,735,217 to Gerth et al., U.S. Pat. No. 4,947,874 to Brooks et al., U.S. Pat. No. 5,372,148 to McCafferty et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 7,040,314 to Nguyen et al., U.S. Pat. No. 8,205,622 to Pan, U.S. Pat. App. Pub. No. 2009/0230117 to Fernando et al., U.S. Pat. App. Pub. No. 2014/0060554 to Collet et al., U.S. Pat. App. Pub. No. 2014/0270727 to Ampolini et al., and U.S. Pat. App. Ser. No. 14/209,191 to Henry et al., filed March 13, 2014, all of which are incorporated herein by reference in their entireties.

Representative types of substrates, reservoirs or other components for supporting the aerosol precursor are described in U.S. Pat. No. 8,528,569 to Newton, U.S. Pat. App. Pub. No. 2014/0261487 to Chapman et al., U.S. Pat. App. Ser. No. 14/011,992 to Davis et al., filed August 28, 2013, and U.S. Pat. App. Ser. No. 14/170,838 to Bless et al., filed February 3, 2014, all of which are incorporated herein by reference in their entireties. Additionally, various wicking materials, and the configuration and operation of those wicking materials within certain types of electronic cigarettes, are set forth in U.S. Pat. App. Pub. No. 2014/0209105 to Sears et al., which is incorporated herein by reference in its entirety.

The aerosol precursor composition, also referred to as a vapor precursor composition, may comprise a variety of components including, by way of example, a polyhydric alcohol (e.g., glycerin, propylene glycol or a mixture thereof), nicotine, tobacco, tobacco extract and/or flavorants. Representative types of aerosol precursor components and formulations also are set forth and characterized in U.S. Pat. No. 7,217,320 to Robinson et al. and U.S. Pat. Pub. Nos. 2013/0008457 to Zheng et al.; 2013/0213417 to Chong et al.; 2014/0060554 to Collett et al.; 2015/0020823 to Lipowicz et al.; and 2015/0020830 to Koller, as well as

WO 2014/182736 to Bowen et al, the disclosures of which are incorporated herein by reference. Other aerosol precursors that may be employed include the aerosol precursors that have been incorporated in the VUSE® product by R. J. Reynolds Vapor Company, the BLU™ product by Imperial Tobacco Group PLC, the MISTIC MENTHOL product by Mistic Ecigs, and the VYPE product by CN Creative Ltd. Also
5 desirable are the so-called “smoke juices” for electronic cigarettes that have been available from Johnson Creek Enterprises LLC.

Additional representative types of components that yield visual cues or indicators may be employed in the aerosol delivery device **100**, such as visual indicators and related components, audio indicators, haptic indicators and the like. Examples of suitable LED components, and the configurations and uses thereof, are
10 described in U.S. Pat. No. 5,154,192 to Sprinkel et al., U.S. Pat. No. 8,499,766 to Newton, U.S. Pat. No. 8,539,959 to Scatterday, and U.S. Pat. App. Ser. No. 14/173,266 to Sears et al., filed February 5, 2014, all of which are incorporated herein by reference in their entireties.

Yet other features, controls or components that can be incorporated into aerosol delivery devices of the present disclosure are described in U.S. Pat. No. 5,967,148 to Harris et al., U.S. Pat. No. 5,934,289 to
15 Watkins et al., U.S. Pat. No. 5,954,979 to Counts et al., U.S. Pat. No. 6,040,560 to Fleischhauer et al., U.S. Pat. No. 8,365,742 to Hon, U.S. Pat. No. 8,402,976 to Fernando et al., U.S. Pat. App. Pub. No. 2005/0016550 to Katase, U.S. Pat. App. Pub. No. 2010/0163063 to Fernando et al., U.S. Pat. App. Pub. No. 2013/0192623 to Tucker et al., U.S. Pat. App. Pub. No. 2013/0298905 to Leven et al., U.S. Pat. App. Pub. No. 2013/0180553 to Kim et al., U.S. Pat. App. Pub. No. 2014/0000638 to Sebastian et al., U.S. Pat. App.
20 Pub. No. 2014/0261495 to Novak et al., and U.S. Pat. App. Pub. No. 2014/0261408 to DePiano et al., all of which are incorporated herein by reference in their entireties.

The control component **208** includes a number of electronic components, and in some examples may be formed of a printed circuit board (PCB) that supports and electrically connects the electronic components. The electronic components may include a microprocessor or processor core, and a memory. In some
25 examples, the control component may include a microcontroller with integrated processor core and memory, and may further include one or more integrated input/output peripherals. In some examples, the control component may be coupled to a communication interface **246** to enable wireless communication with one or more networks, computing devices or other appropriately-enabled devices. Examples of suitable communication interfaces are disclosed in U.S. Pat. App. Ser. No. 14/638,562, filed March 4, 2015, to
30 Marion et al., the content of which is incorporated by reference in its entirety. And examples of suitable manners according to which the aerosol delivery device may be configured to wirelessly communicate are disclosed in U.S. Pat. App. Ser. No. 14/327,776, filed July 10, 2014, to Ampolini et al., and U.S. Pat. App. Ser. No. 14/609,032, filed January 29, 2015, to Henry, Jr. et al., each of which is incorporated herein by reference in its entirety.

35 In accordance with some example implementations, the control body **102** may include an input device **248** including a capacitive sensor configured to detect a user input. In various examples, the capacitive sensor may be or include a zero-dimensional, one-dimensional or two-dimensional capacitive

sensor configured to implement respectively a button, slider or wheel, or touchscreen or touchpad. In some examples, the capacitive sensor may be or include a three-dimensional capacitive sensor configured to detect a presence of an object nearby the control body, and thereby the user input, without requiring any physical contact with the object.

5 The input device **248** or control component **208** may be configured to control operation of at least one functional element of the control body **102**, cartridge **104** or aerosol delivery device **100** in response to the user input so detected. Functional element(s) of the control body, cartridge or aerosol delivery device may be controlled in any of a number of different manners in response to the user input. For example, the input device or control component may control a sensory-feedback member **250** (e.g., a LED, auditory
10 element, vibratory element) to provide a user-perceptible feedback (e.g., visual, audible, haptic feedback). As another example, the input device or control component may alter a power or locked state of the control body, cartridge or aerosol delivery device. This may include, for example, enabling one or more components of the aerosol delivery device for operation in response to the user input.

 In a similar example, the input device **248** or control component **208** may alter a power or active
15 state of at least one functional element such as the communication interface **246**. This may include, for example, power-up or activation of the communication interface and/or perhaps other functional elements from a low-power or inactive state. Other examples of suitable functional elements that may be powered up or activated in response to the user input may include sensors such as a proximity sensor, accelerometer, gyroscope, camera or the like. Further information regarding various suitable sensors may be found in the
20 following: U.S. Pat. App. Ser. Nos. 14/565,137 to Henry et al., filed December 9, 2014; 14/609,032 to Henry et al., filed January 29, 2015; 14/961,421 to Sur et al., filed December 7, 2015; 14/961,517 to Sur et al., filed December 7, 2015; and 14/975,121 to Sur et al., filed December 18, 2015; all of which are incorporated herein by reference.

 As another example, the input device **248** or control component **208** may alter an operational
25 parameter of at least one functional element. This may include, for example, changing the aerosol delivery device **100** from a high-power to a low-power setting (or vice versa) for a cartridge **104**. The change may be effected in a number of different manners, such as by changing the value of a resistor across a load in the cartridge by selecting various resistive loads.

 As further shown in FIG. 2, in addition to or in lieu of the control body **102**, the cartridge **104** may
30 include an input device **252** including a capacitive sensor, and perhaps also a sensory-feedback member **254**. The input device or control component **208**, then, may be configured to control operation of functional element(s) of the control body, cartridge or aerosol delivery device **100** in response to user input detected by the input device.

 The input device **252** of the cartridge **104** and/or functional element(s) controlled in response to
35 thereto may be the same or similar to the input device **248** of the control body **102** and/or functional element(s) controlled in response thereto. Similar to on the control body, the capacitive sensor of the input device on the cartridge may be or include a zero-dimensional, one-dimensional, two-dimensional or three-

dimensional capacitive sensor. For example, a sensory-feedback member **250, 254** may be controlled to provide a user-perceptible feedback. Additionally or alternatively, for example, user input detected by the input device of the cartridge may be useful to alter a power or locked state of the control body, cartridge or aerosol delivery device, alter a power or active state of at least one functional element (e.g., communication interface **246**, sensor(s)), or alter an operational parameter of at least one functional element.

FIG. 3 illustrates an input device **300** that in some examples may correspond to the input device **248** of the control body **102**, or the input device **252** of the cartridge **104**, shown in FIG. 2. As shown in FIG. 3, the input device may include a source of excitation **302** configured to drive a capacitive sensor **304** configured to measure a change in capacitance in the presence of a nearby object such as a user's finger or other instrument to effect user input. The measured capacitance may be provided to a capacitance-to-digital converter (CDC) **306** configured to convert the capacitance to a corresponding digital signal. This digital signal may be passed to a microprocessor **308** or other digital processing logic, which may be onboard the input device or in some examples part of the control component **208**. The microprocessor may be in turn configured to control operation of at least one functional element in response to the digital signal and thereby the user input. This may include, for example, control of a sensory-feedback member **310**, which may also be onboard the input device or separate from but in communication with the input device (e.g., sensory-feedback member **250, 254**).

FIG. 4 illustrates a capacitive sensor **400** that in some examples may correspond to the capacitive sensor **304** of FIG. 3. As shown, the capacitive sensor may include a panel-covered substrate **402** on which one or more electrodes **404** (sometimes referred to more simply as the sensors) are disposed. The electrodes may be included in number, shape and arrangement to individually or collectively implement an appropriate input device such as a button (two shown), slider or wheel, or touchscreen or touchpad. In some examples, the substrate and electrodes may be formed of a circuit board, flexible circuit board, indium tin oxide (ITO) or the like.

In addition to the electrodes **404**, the capacitive sensor **400** may include one or more of each of a number of other electronic components disposed on the substrate **402**. In some examples, at least some of these other electronic components may offset or otherwise enable the capacitive sensor to respond to environmental conditions such as water or other liquid on the capacitive sensor. As shown, for example, the capacitive sensor may include a shield electrode **406** configured to at least partially attenuate an effect of liquid on the capacitive sensor. Additionally or alternatively, for example, the capacitive sensor may include a guard sensor **408** configured to detect above a threshold level of liquid on the capacitive sensor. When an above threshold level of liquid is detected, the capacitive sensor or input device (e.g., input device **300**) may appropriately respond, such as by ignoring what may be considered false-detected user input.

The foregoing description of use of the article(s) can be applied to the various example implementations described herein through minor modifications, which can be apparent to the person of skill in the art in light of the further disclosure provided herein. The above description of use, however, is not intended to limit the use of the article but is provided to comply with all necessary requirements of

disclosure of the present disclosure. Any of the elements shown in the article(s) illustrated in FIGS. 1-4 or as otherwise described above may be included in an aerosol delivery device according to the present disclosure.

5 Many modifications and other implementations of the disclosure set forth herein will come to mind to one skilled in the art to which this disclosure pertains having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the disclosure is not to be limited to the specific implementations disclosed, and that modifications and other
10 implementations are intended to be included within the scope of the appended claims. Moreover, although the foregoing descriptions and the associated drawings describe example implementations in the context of certain example combinations of elements and/or functions, it should be appreciated that different combinations of elements and/or functions may be provided by alternative implementations without departing from the scope of the appended claims. In this regard, for example, different combinations of elements and/or functions than those explicitly described above are also contemplated as may be set forth in some of the appended claims. Although specific terms are employed herein, they are used in a generic and
15 descriptive sense only and not for purposes of limitation.

WHAT IS CLAIMED IS:

1. A control body coupled or coupleable with a cartridge that is equipped with a heating element and contains an aerosol precursor composition, the control body being coupled or coupleable with the cartridge to form an aerosol delivery device in which the heating element is configured to activate and vaporize components of the aerosol precursor composition, the control body comprising:

5 a control component configured to operate in an active mode in which the control body is coupled with the cartridge, the control component in the active mode being configured to control the heating element to activate and vaporize components of the aerosol precursor composition; and

10 an input device including a capacitive sensor configured to detect a user input, the input device or control component being further configured to control operation of at least one functional element of the control body, cartridge or aerosol delivery device in response to the user input so detected.

2. The control body of Claim 1, wherein the capacitive sensor is a zero-dimensional capacitive sensor configured to implement a button.

15 3. The control body of Claim 1, wherein the capacitive sensor is a one-dimensional capacitive sensor configured to implement a slider or wheel.

4. The control body of Claim 1, wherein the capacitive sensor is a two-dimensional capacitive sensor configured to implement a touchscreen or touchpad.

20 5. The control body of Claim 1, wherein the capacitive sensor is a three-dimensional capacitive sensor configured to detect a presence of an object nearby the control body, and thereby the user input, without requiring any physical contact with the object.

25 6. The control body of Claim 1, wherein the input device or control component being configured to control at least one functional element includes being configured to alter a power or locked state of the control body, cartridge or aerosol delivery device.

30 7. The control body of Claim 1, wherein the input device or control component being configured to control at least one functional element includes being configured to alter an operational parameter of the at least one functional element.

35 8. The control body of Claim 1, wherein the at least one functional element includes at least one sensor, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the at least one sensor.

9. The control body of Claim 1, wherein the at least one functional element includes a communication interface that is coupled to the control component and configured to enable wireless communication, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the communication interface.

5

10. The control body of Claim 1, wherein the capacitive sensor includes a shield electrode configured to at least partially attenuate an effect of liquid on the capacitive sensor, and a guard sensor configured to detect above a threshold level of liquid on the capacitive sensor.

10

11. A cartridge coupled or coupleable with a control body that is equipped with a control component, the control body being coupled or coupleable with the cartridge to form an aerosol delivery device, the cartridge comprising:

a housing defining a reservoir configured to retain aerosol precursor composition;

15

a heating element configured to operate in an active mode in which the cartridge is coupled with the control body, the heating element in the active mode being controllable by the control component to activate and vaporize components of the aerosol precursor composition; and

an input device including a capacitive sensor configured to detect a user input, the input device or control component being configured to control operation of at least one functional element of the control body, cartridge or aerosol delivery device in response to the user input so detected.

20

12. The cartridge of Claim 11, wherein the capacitive sensor is a zero-dimensional capacitive sensor configured to implement a button.

25

13. The cartridge of Claim 11, wherein the capacitive sensor is a one-dimensional capacitive sensor configured to implement a slider or wheel.

14. The cartridge of Claim 11, wherein the capacitive sensor is a two-dimensional capacitive sensor configured to implement a touchscreen or touchpad.

30

15. The cartridge of Claim 11, wherein the capacitive sensor is a three-dimensional capacitive sensor configured to detect a presence of an object nearby the cartridge, and thereby the user input, without requiring any physical contact with the object.

35

16. The cartridge of Claim 11, wherein the input device or control component being configured to control at least one functional element includes being configured to alter a power or locked state of the control body, cartridge or aerosol delivery device.

17. The cartridge of Claim 11, wherein the input device or control component being configured to control at least one functional element includes being configured to alter an operational parameter of the at least one functional element.

5 18. The cartridge of Claim 11, wherein the at least one functional element includes at least one sensor, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the at least one sensor.

10 19. The cartridge of Claim 11, wherein the at least one functional element includes a communication interface that is coupled to the control component and configured to enable wireless communication, and input device or control component being configured to control at least one functional element includes being configured to alter a power or active state of the communication interface.

15 20. The cartridge of Claim 11, wherein the capacitive sensor includes a shield electrode configured to at least partially attenuate an effect of liquid on the capacitive sensor, and a guard sensor configured to detect above a threshold level of liquid on the capacitive sensor.




FIG. 1




FIG. 2

3/3




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2017/050035

A. CLASSIFICATION OF SUBJECT MATTER
 INV. A24F47/00
 ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 A24F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2014/261486 A1 (POTTER DENNIS LEE [US] ET AL) 18 September 2014 (2014-09-18) paragraphs [0027], [0030], [0062], [0066], [0069], [0072] - [0075], [0078]; figures 1-3 -----	1,2,5-8, 10-12, 15-18,20
X	US 2014/123989 A1 (LAMOTHE ANDRÉ JOSEPH [US]) 8 May 2014 (2014-05-08) paragraphs [0018], [0047] - [0048], [0059] - [0060]; figures 1,11 -----	1,2,9, 11,12,19
X	US 2015/245658 A1 (WORM STEVEN L [US] ET AL) 3 September 2015 (2015-09-03) paragraphs [0032], [0034], [0038], [0039], [0053], [0055], [0084]; figures 1,2,9 -----	1,3,4, 11,13,14



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

2 March 2017

Date of mailing of the international search report

17/03/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040,
 Fax: (+31-70) 340-3016

Authorized officer

Schwarzer, Bernd

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2017/050035

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2014261486 A1	18-09-2014	CN 105163611 A EP 2967144 A1 JP 2016510994 A US 2014261486 A1 WO 2014159250 A1	16-12-2015 20-01-2016 14-04-2016 18-09-2014 02-10-2014
US 2014123989 A1	08-05-2014	CN 105050434 A US 2014123989 A1 WO 2014071329 A1	11-11-2015 08-05-2014 08-05-2014
US 2015245658 A1	03-09-2015	CN 106231933 A EP 3110271 A2 KR 20160127086 A US 2015245658 A1 WO 2015130598 A2	14-12-2016 04-01-2017 02-11-2016 03-09-2015 03-09-2015