

(19) AUSTRALIAN PATENT OFFICE

- (54) Title
Method and apparatus for reporting WLAN capabilities of a dual mode GPRS/WLAN or UMTS/WLAN WTRU
- (51)⁶ International Patent Classification(s)
H04L 12/28 (2006.01) 05BMAU H04W
H04W 28/18 28/18
(2009.01) 20090101ALI2009090
H04W 92/02 3BHAU H04W
(2009.01) 92/02
H04L 12/28 20090101ALI2009090
20060101AFN200710 3BHAU
- (21) Application No: 2007221734 (22) Application Date: 2007 .09 .28
- (43) Publication Date : 2007 .10 .25
(43) Publication Journal Date : 2007 .10 .25
- (62) Divisional of:
2004306892
- (71) Applicant(s)
InterDigital Technology Corporation
- (72) Inventor(s)
Purkayashtha, Debashish, Shaheen, Kamel M.
- (74) Agent/Attorney
Watermark Patent & Trademark Attorneys, 302 Burwood Road, Hawthorn, VIC, 3122

2007221734 28 Sep 2007

ABSTRACT

Method and apparatus for enabling a wireless terminal to communication
the dual-mode capabilities and reporting the interworking capabilities of the two
5 networks with which the wireless terminal have the added capability of obtaining
services from either one of the interworking networks.

2007221734 28 Sep 2007

P001
Section 29
Regulation 3.2(2)

AUSTRALIA
Patents Act 1990

COMPLETE SPECIFICATION STANDARD PATENT

Application Number:

Lodged:

Invention Title: **Method and apparatus for reporting WLAN capabilities of a dual mode GPRS/WLAN or UMTS/WLAN WTRU**

The following statement is a full description of this invention, including the best method of performing it known to us:

**METHOD AND APPARATUS FOR REPORTING WLAN CAPABILITIES OF A
DUAL MODE GPRS/WLAN OR UMTS/WLAN WTRU**

FIELD OF THE INVENTION

5 The present invention relates to WTRUs having dual-mode capabilities and more particularly to method and apparatus for reporting dual mode capabilities and for reporting availability of network interworking.

BACKGROUND TO THE INVENTION

10 The current developments of wireless local area networks (WLANs) interworking with general packet radio service/universal mobile telecommunications system/third generation (GPRS/UMTS/3G) networks has resulted in products that include two radio units in a common enclosure (e.g., cards supporting 802.11b + GPRS air interfaces and 802.11b +UMTS air interfaces). The units may be separate cards or may be integrated onto one
15 common card.

 Hereafter a wireless transmit/receive unit (WTRU) includes but is not limited to a user equipment, mobile station, fixed or mobile subscriber unit, pager, or any other type of device capable of operating in a wireless environment. When referred to hereafter, a base station (BS) includes but is not limited to a Node-B,
20 site controller, access point or any other type of interfacing device in a wireless environment.

 Currently the network may not be aware of the dual-mode capabilities of the terminal. In addition, the offered services may change dramatically based on the terminal capabilities in terms of processing power, memory availability,
25 screen size, bit rate, etc. For example, a dual mode 802+GPRS personal digital assistant (PDA) may be able to receive short message service (SMS) or multimedia message service (MMS) messages over a GPRS or an 802 network, however, several variations of these services may be provided in accordance with allotted memory space of the wireless terminal. Rich multimedia services may
30 require larger memory size than that available in the PDA. Therefore, the same multimedia services may be provided via black and white or a reduced set of colors depending on terminal capabilities. Also, the possibility of network-assisted handoff can be provided to those terminals that indicate dual mode

(WLAN/GPRS or WLAN/3G) capabilities. A mechanism is needed to indicate these capabilities to the existing GPRS/UMTS networks.

5 In addition, in network interworking, there is no capability of informing a wireless terminal having dual-mode radio capabilities and relying upon one of the networks with which it communicates to be advised of the interworking capability to enable the wireless terminal to have the increased ability of communicating with either of the two networks.

10 Any discussion of documents, devices, acts or knowledge in this specification is included to explain the context of the invention. It should not be taken as an admission that any of the material formed part of the prior art base or the common general knowledge in the relevant art in Australia on or before the priority date of the claims herein.

SUMMARY OF THE INVENTION

15 In accordance with a first aspect of the present invention there is provided a method for use in a dual-mode wireless transmit/receive unit (WTRU), the method including:

establishing a wireless connection with a wireless local area network (WLAN);

20 transmitting to the WLAN an indication of WTRU capabilities;
receiving from the WLAN an indication of capabilities of the WLAN; and
receiving services provided by the WLAN based on the WTRU capabilities.

In accordance with a further aspect of the present invention there is provided adual-mode wireless transmit/receive unit (WTRU) capable of wireless communication with a cellular network and a wireless local area network (WLAN),
25 the WTRU having a plurality of communication capabilities, the WTRU including:

a transmitter configured to transmit a registration request message to the WLAN, wherein the registration request message includes an indication of the WTRU's capabilities;

30 a receiver configured to receive a registration complete message from the WLAN, wherein the registration complete message includes an indication of capabilities of the WLAN, and configured to receive services from the WLAN based on the WTRU's capabilities.

In a further aspect the present invention provides a method for use in a dual-mode wireless transmit/receive unit (WTRU) for associating with a network node of a first technology, the method including:

- 5 generating an association request message including a WTRU capability indicator indicating the WTRU is configured to communicate via a second technology that is a packet-switched technology;
- communicating the association request message to the network node; and
- receiving services via the network node based on the capability indicator.

10 In another aspect the present invention provides a wireless transmit/receive unit (WTRU) including:

- 15 a processor configured to generate an association request message for associating with a network node of a first technology, the association request message including a WTRU capability indicator indicating the WTRU is configured to communicate via a second technology that is a packet-switched technology;
- a transmitter configured to transmit the association request message to the network node; and
- 20 a receiver configured to receive services via the network node based on the capability indicator.

"Comprises/comprising" when used in this specification is taken to specify the presence of stated features, integers, steps or components but does not preclude the presence or addition of one or more other features, integers, steps, components or groups thereof.

25 **BRIEF DESCRIPTION OF THE DRAWINGS**

The present invention will be understood from a consideration of the figures in which like elements are designated by like numerals and, wherein:

- 30 Figure 1 is a simplified schematic diagram of the network having integrated universal mobile telephone service (UMTS) and wireless local area network (WLAN) networks.

Figure 2 is a simplified schematic diagram showing an attach procedure and embodying the capabilities of the present invention.

Figure 3 shows a WTRU network capability information element (IE).

5 Figures 4 and 5 respectively show the existing and modified network capability and radio access (RA) capability information element (IE).

Figure 4A shows the modified network capabilities IE of Figure 4 in greater detail.

10 Figures 5A1-5A2 and 5B show the modified RA capability IE of Figure 5 in greater detail and Figure 5A shows the manner in which Figures 5A1 and 5A2 are arranged.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

15 The problem solved by this invention is the mechanism by which a terminal that supports both GPRS and WLAN, or 3G and WLAN can report its WLAN capabilities to the supporting GPRS/UMTS networks. Also, the invention identifies the mechanism by which a 3G network can indicate that 3G or packet switched domain services over WLAN are available.

Figure 1 shows a simplified block diagram of a network in which a UMTS and a WLAN are integrated. The WTRUs 12, 14 and 16 communicate with the

20

network over respective radio links (RL-1, RL-2 and RL-3). More particularly, WTRU 12 communicates with a GSM radio access network (RAN); WTRU 14 communicates with a 2.5/3G RAN and WTRU 16 communicates with a WLAN access point (AP). WTRUs 12 and 14 may be cellular telephones while WTRU 5 16 may be a laptop, personal digital assistant (PDA) or other like device having an appropriate card enabling communication with the WLAN AP.

The GSM RAN communicates with a mobile switching center (MSC) which, as is known in the art, has the capability of interworking with location data bases. The MSC communicates with the visitor location register (VLR) to identify, 10 authenticate, etc. the WTRU 12. The MSC also communicates with the short message service-gateway mobile switching center/interworking-mobile switching center (SMS-GMSC/IW-MSC) which provides the services such as short message service (SMS) data. The home location register (HLR) is a data base 15 within the home public land mobile network (HPLMN) providing routing information for mobile terminated calls and SMS data and is also responsible for maintenance of user subscription information distributed to the relevant VLR (note the VLR in Figure 1) or GSN (GPRS support node) through the attached process and mobility management procedures such as location area and routing area 20 updates.

The WLAN AP communicates with a packet data gateway/WLAN access gateway (PDG/WAG). Capability information is exchanged between the GSN and the PDG/WAG. Services such as SMS data services are communicated to the PDG/WAG and hence to the WTRU 16 by way of the PDG/WAG and WLAN AP. Based on the capability of the WTRU 16, SMS data may be delivered 25 thereto.

The WTRUs 12 and 14 when respectively communicating with the network through their associated RAN, provide information regarding their capability which, in accordance with the present invention, includes WLAN compatibility.

Figure 2 shows an attach procedure combined with a WLAN capability 30 update. In the procedure shown in Figure 2, a UMTS dual mode WTRU, at step S1, powers up for a signaling connection to perform the ATTACH procedure. At step S2, a radio resource control (RRC) connection request message is conveyed to the radio network controller (RNC). Admission control and availability of

resources is performed by the RNC, at step S3, which then conveys an RRC connection setup message to the dual mode WTRU, at step S4. The WTRU, at step S5, provides an RRC connection set up complete message providing the WTRU radio access (RA) compatibility and, at step S6, provides the initial direct transfer message, which includes the attach request and the point-to-multipoint system information (PtM SI), instant messaging system information (IM SI), network (NW) capability and radio access (RA) capability. The RNC, at step S7, provides an initial WTRU Message: attach request including the network and radio access capabilities. In addition to the UMTS capabilities, the message further contains WLAN capability. At step S8, authentication and ciphering request and security mode commands are performed and the WTRU is authenticated, at step S9. Thereafter, the SGSN provides to the SGSN a WTRU capability update to the WAG-PDG, at step S10, and provides an attach-accept message to the RNC, at step S11, which is then conveyed, at S12, to the WTRU.

The update of the WTRU capability sent to WAG-PDG, at step S10, causes the SGSN to update the WAG, which may then decide if the service request can be terminated.

The purpose of a mobile station WTRU network capability information element is to provide the network with information concerning aspects of the WTRU related to the GPRS. The contents of the information element can affect the manner in which the network handles the operation of the WTRU. WTRU network capability information indicates general WTRU characteristics and, except for fields explicitly indicated, is independent of the frequency band of the sending channel.

WTRU network capability is a type 4 information element (IE) having a maximum length of ten octets.

The value part of the WTRU network capability IE is coded, as shown in Figure 3.

Figure 4 is a comparison of the existing network capability IE with the network capability information element of the present invention and Figure 5 shows a comparison of the radio access capability information element (RAC IE) with the RAC IE of the present invention.

The purpose of the mobile station (MS) network capability IE is to provide the network with information concerning aspects of the mobile station (i.e., WTRU) related to GPRS. The contents can affect the manner in which the network handles the operation of the mobile station. The MS network capability information indicates general mobile station characteristics and except for fields explicitly indicated, is independent of the frequency band of the channel it is sent on. The MS network capability is a type 4 information element with a maximum of ten octets length. The value part of a MS network capability information element is coded as shown in Figure 3.

Making reference to Figure 4, which shows the network capability IE in amplified fashion, item (1) of both the existing and new IE, namely the system management capabilities by way of dedicated channels, are the same. Item (2) listed in the existing and new IE, the system management capabilities by way of GPRS channels are the same. Item (3) in the existing IE, and item (6) in the new information element, the Universal Multiple – Octet Coded Character Set (UCS), USC2 16 bit coding support, are the same.

Item (4) in the existing IE and item (7) in the new IE, i.e. the supplementary service (SS) screening indicator, are the same. The support of localized service area (SoLSA) capability, item (5) of the existing IE and item (8) of the new IE, are the same.

Item (6) in the existing IE, the revision level indicator, is the same as item (9) in the new IE. Items (4) and (5) in the new IE, namely, the system management capability by way of the WLAN and the short message system (SMS) item which identifies text only, text and animation, the instant message service and the multimedia service as well as others are provided to the WTRU, are not provided in the existing IE. Items (7) through (10) of the existing IE are omitted from the new IE and will not be discussed herein for simplicity.

Figure 4A shows the network capability IE in greater detail. For example, as shown in Figure 4A, the location service (LCS) value added (VA) location request notification bit, (in binary format) is "0" when not supported and is "1" when supported. WLAN capability is supported when its binary bit is "1" and is not supported when in the "0" state. The bit or bits identifying each capability are assigned predetermined locations with the IE. This is also the case for the RA

capabilities. Also note that the GPRS encryption algorithm (GEA) capability bit is "0" when not supported and "1" when supported.

The purpose of the mobile station radio access (MS RA) capability information element (IE) is to provide the radio part of the network with information concerning radio aspects of the mobile station (i.e., the WTRU). The contents can affect the manner in which the network handles the operation of the mobile station. The MS RA capability is a type 4 information element, with a maximum length of 52 octets. The value part of a MS RA capability information element is coded as shown in Figures 5A and 5B.

Figure 5 compares the existing and new radio access capability IEs. Items (1) through (4) of the existing IE, namely the access technology type, access capabilities, UMTS FDD RA technology capability and UMTS 3.84 Mcps TDD RA technology capability, are identical to the items (1) through(4) in the new IE.

Items (5) and (6) in the existing IE are omitted from the new IE and hence will not be discussed herein for purposes of simplicity. Item (5) of the new IE does not appear in the existing IE and provides WLAN radio access capability which identifies the type of remote terminal, (such as PDA, laptop, phone, etc.), memory size, screen size, processing power, technology version (such as 802.11, 802.15, 802.16 and so forth), service profile, (such as SMS text only or text and animation), MMS, IMS, location, MBMS, and the like.

Figures 5A1-5A2/5B show the MS RA capability IE in greater detail. In Figures 5A1-5A2, the Access Technology type of four binary bits, represents the technology type used for access. Gaussian minimum shift keying (GMSK) is a form of frequency shift keying providing good spectral efficiency. 8PSK is a modulation technique where the carrier exists in one of eight states. Figure 5B shows the fields and binary bits for identifying some of the capabilities. For example, a three bit field is used to identify WLAN 802 RA Technology wherein the technology supported is identified by a particular combination of binary bits. Note that no support of WLAN 802.xx technology is represented by "000," support for WLAN 802.11b technology represented by "001" and so forth. As another example, the CDMA 2000 RA Technology capability is "0" when not supported and "1" when supported.

A dual mode WTRU provides a WLAN capability report over its UMTS (or GPRS) network depending on whether the dual mode WTRU has WLAN/UMTS or WLAN/GPRS capability.

5 As shown in Figure 2, when the WTRU is powered up, it first communicates by way of the UMTS channels and performs a non-access stratum (NAS) "ATTACH" procedure whereupon the UMTS/WLAN capability is exchanged with the network, as shown in Figure 2.

10 Depending on implementation, the user may chose to continue communicating with the UMTS network, manually switch over to WLAN channels or perform an automatic handover to the WLAN network, if available.

The present invention thus introduces two new IEs to existing GPRS/UMTS capability messages between WTRU and network and network and WTRU. The radio access capability information element (RAC IE) is modified to inform the network about the dual-mode capabilities of the WTRU/card, i.e.,
15 GPRS + WLAN or UMTS/WLAN. The radio access capability (RAC), carries all aspects of the WLAN capabilities including terminal type, (such as PDA, laptop, cell phone), memory size, screen size, processing power, technology version (such as 802.11, 802.15, 802.16 and so forth), service profile (such as SMS text only or text and animation), SMS, MMS, IMS, location, multicast broadcast media
20 service (MBMS) and so forth. The WLAN capability update procedures are achieved without modification of the existing "ATTACH" procedure. The network capability is modified to inform dual mode WTRUs regarding the existence of WLAN interworking capabilities and the different types of services that can be provided over a WLAN network.

25

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method for use in a dual-mode wireless transmit/receive unit (WTRU), the method including:
 - establishing a wireless connection with a wireless local area network (WLAN);
 - transmitting to the WLAN an indication of WTRU capabilities;
 - receiving from the WLAN an indication of capabilities of the WLAN; and
 - receiving services provided by the WLAN based on the WTRU capabilities.
2. The method of claim 1, wherein the dual mode WTRU has an active session with a cellular network, further including:
 - the cellular network handing over the WTRU to the WLAN based on the WTRU capabilities.
3. The method of claim 1, wherein the indication of WTRU capabilities includes a listing of IEEE 802.x protocols supported by the WTRU.
4. The method of claim 3, wherein the IEEE 802.x protocols include at least one of 802.11, 802.15, and 802.16.
5. The method of claim 1, wherein the indication of WTRU capabilities includes at least one of a terminal type, a memory capacity, a screen size, and a processing speed.
6. The method of claim 1, wherein the indication of WTRU capabilities includes short message service (SMS) capabilities.
7. The method of claim 6, wherein the indication of WTRU SMS capabilities includes an indication of support for text only SMS messages.
8. The method of claim 6, wherein the indication of WTRU SMS capabilities includes an indication of support for text and animation SMS messages.

9. The method of claim 1, wherein the indication of WTRU capabilities includes multimedia message service (MMS) capabilities.
10. The method of claim 1, wherein the indication of WTRU capabilities includes Internet protocol (IP) multimedia subsystem (IMS) capabilities.
11. The method of claim 1, wherein the indication of WTRU capabilities includes location services capabilities.
12. The method of claim 1, wherein the indication of WTRU capabilities includes multimedia broadcast/multicast service (MBMS) capabilities.
13. The method of claim 1, wherein the indication of WLAN capabilities includes SMS via WLAN capability.
14. The method of claim 13, wherein the indication of SMS via WLAN capability includes a text only capability.
15. The method of claim 13, wherein the indication of SMS via WLAN capability includes a text and animation capability.
16. The method of claim 1, wherein the indication of WLAN capabilities includes IMS capabilities.
17. The method of claim 1, wherein the indication of WLAN capabilities includes MMS capabilities.
18. The method of claim 1, wherein the indication of WLAN capabilities includes MBMS capabilities.
19. A dual-mode wireless transmit/receive unit (WTRU) capable of wireless communication with a cellular network and a wireless local area network (WLAN), the WTRU having a plurality of communication capabilities, the WTRU including:

a transmitter configured to transmit a registration request message to the WLAN, wherein the registration request message includes an indication of the WTRU's capabilities;

a receiver configured to receive a registration complete message from the WLAN, wherein the registration complete message includes an indication of capabilities of the WLAN, and configures to receive services from the WLAN based on the WTRU's capabilities.

20. The WTRU of claim 19, wherein the indication of WTRU capabilities includes a listing of IEEE 802.x protocols supported by the WTRU.

21. The WTRU of claim 20, wherein the IEEE 802.x protocols include at least one of 802.11, 802.15, and 802.16.

22. The WTRU of claim 19, wherein the indication of WTRU capabilities includes at least one of a terminal type, a memory capacity, a screen size, and a processing speed.

23. The WTRU of claim 19, wherein the indication of WTRU capabilities includes short message service (SMS) capabilities.

24. The WTRU of claim 23, wherein the indication of WTRU SMS capabilities includes an indication of support for text only SMS messages.

25. The WTRU of claim 23, wherein the indication of WTRU SMS capabilities includes an indication of support for text and animation SMS messages.

26. The WTRU of claim 19, wherein the indication of WTRU capabilities includes multimedia message service (MMS) capabilities.

27. The WTRU of claim 19, wherein the indication of WTRU capabilities includes Internet protocol (IP) multimedia subsystem (IMS) capabilities.

28. The WTRU of claim 19, wherein the indication of WTRU capabilities includes location services capabilities.

29. The WTRU of claim 19, wherein the indication of WTRU capabilities includes multimedia broadcast/multicast service (MBMS) capabilities.

30. The WTRU of claim 19, wherein the indication of WLAN capabilities includes SMS via WLAN capability.

31. The WTRU of claim 30, wherein the indication of SMS via WLAN capability includes a text only capability.

32. The WTRU of claim 30, wherein the indication of SMS via WLAN capability includes a text and animation capability.

33. The WTRU of claim 19, wherein the indication of WLAN capabilities includes IMS capabilities.

34. The WTRU of claim 19, wherein the indication of WLAN capabilities includes MMS capabilities.

35. The WTRU of claim 19, wherein the indication of WLAN capabilities includes MBMS capabilities.

36. A method for use in a dual-mode wireless transmit/receive unit (WTRU) for associating with a network node of a first technology, the method including:

generating an association request message including a WTRU capability indicator indicating the WTRU is configured to communicate via a second technology that is a packet-switched technology;

communicating the association request message to the network node; and receiving services via the network node based on the capability indicator.

37. The method of claim 36, wherein the second technology is an IEEE 802.11x technology.

38. The method of claim 36, wherein the second technology is general packet radio service (GPRS).
39. The method of 36, wherein the second technology is IEEE 802.16.
40. The method of claim 36, wherein the WTRU capability indicator is included in a radio access capability information element.
41. The method of claim 37, further including:
 - receiving Short Message Service (SMS) messages via the IEEE 802.11x technology.
42. The method of claim 36, further including:
 - receiving an acknowledgement of the association request message from the network node.
43. A wireless transmit/receive unit (WTRU) including:
 - a processor configured to generate an association request message for associating with a network node of a first technology, the association request message including a WTRU capability indicator indicating the WTRU is configured to communicate via a second technology that is a packet-switched technology;
 - a transmitter configured to transmit the association request message to the network node; and
 - a receiver configured to receive services via the network node based on the capability indicator.
44. The WTRU of claim 41, wherein the second technology is an IEEE 802.11x technology.
45. The WTRU of claim 41, wherein the second technology is general packet radio service (GPRS).
46. The WTRU of claim 41, wherein the second technology is IEEE 802.16.

2007221734 18 Nov 2008

14

47. The WTRU of claim 41, wherein the WTRU capability indicator is included in a radio access capability information element.

48. The WTRU of claim 42 wherein the receiver is further configured to receive Short Message Service (SMS) via the IEEE 802.11x technology.

49. The WTRU of claim 41, wherein the receiver is further configured to receive an acknowledgement of the association request message from the network node.

InterDigital Technology Corporation

WATERMARK PATENT & TRADE MARK ATTORNEYS
P26573AU01




FIG. 1




FIG. 2




FIG. 3




FIG. 4A

NETWORK CAPABILITY IE




FIG. 4



RADIO ACCESS CAPABILITY IE

• **NEW**

- <MS RA CAPABILITY VALUE
PART:= [24,008]
1. <ACCESS TECHNOLOGY TYPE>
2. <ACCESS CAPABILITIES : BIT>
3. <UMTS FDD RADIO ACCESS
TECHNOLOGY CAPABILITY : BIT>
4. <UMTS 3.84 Mcps TDD
RADIO ACCESS TECHNOLOGY
CAPABILITY : BIT>
5. <WLAN RADIO ACCESS
CAPABILITY : TERMINAL TYPE (PDA,
LAPTOP, PHONE), MEMORY SIZE,
SCREEN SIZE, PROCESSING POWER,
TECHNOLOGY VERSION (802.11,
802.15, 802.16,...ETC.), SERVICE
PROFILE (SMS (TEXT ONLY,
TEXT & ANIMATION)), MMS, IMS,
LOCATION, MBMS...ETC.>

• **EXISTING**

- <MS RA CAPABILITY
VALUE PART:= [24,008]
1. <ACCESS TECHNOLOGY TYPE>
2. <ACCESS CAPABILITIES : BIT>
3. <UMTS FDD RADIO ACCESS
TECHNOLOGY CAPABILITY : BIT>
4. <UMTS 3.84 Mcps TDD
RADIO ACCESS TECHNOLOGY
CAPABILITY : BIT>
5. <CDMA 2000 RADIO
ACCESS TECHNOLOGY
CAPABILITY : BIT>
6. <UMTS 1.28 Mcps TDD
RADIO ACCESS TECHNOLOGY
CAPABILITY : BIT>

FIG. 5



FIG. 5A **FIG. 5A1**
FIG. 5A2

```

<MS RA capability value part ; <MS RA capability value part struct >>
<spare bits>** ; -- available for future enhancements

<MS RA capability value part struct > ::= -- recursive structure allows any number of Access technologies
{
  {
    <Access Technology Type : bit (4) > exclude 1111
    <Access capabilities : <Access capabilities struct > > }
  |
  {
    <Access Technology Type : bit (4) == 1111 > -- structure adding Access
    technologies with same capabilities
    <Length : bit (7) > -- length in bits of list of Additional access technologies
    and spare bits
    ( 1 <Additional access technologies ; <Additional access technologies struct >> } ** 0
    <spare bits>** )
  }
  { 0 | 1 <MS RA capability value part struct > } ;
  <Additional access technologies struct > ::=
  <Access Technology Type : bit (4) >
  <GMSK Power Class : bit (3) >
  <8PSK Power Class : bit (2) > ;
  <Access capabilities struct > ::=
  <Length : bit (7) > -- length in bits of Content and spare bits
  <Access capabilities : <Content>>
  <spare bits>** ; -- expands to the indicated length
  -- available for future enhancements

```

FIG. 5A1


```

<Content> ::=
< RF Power Capability : bit (3) >
{ 0 | 1 < A5 bits : < A5 bits > }
-- zero means that the same values apply for parameters as in the
immediately preceding Access capabilities field within this IE
< ES INTD : bit >
< RS : bit >
< YGCS : bit >
< VBS : bit >
{ 0 | 1 < Multislot capability : Multislot capability struct > } -- zero means that the same values for multislot
parameters as given in an earlier Access capabilities field within this IE apply also here
-- Additions in release 99
{ 0 | 1 < 8PSK Power Capability : bit(2) > } -- '1' also means 8PSK modulation capability in the uplink
< COMPACT Interference Measurement Capability : bit >
< Revision Level Indicator : bit >
< UMTS FDD Radio Access Technology Capability : bit > -- 3G RAT
< UMTS 3.84 Mcps TDD Radio Access Technology Capability : bit > -- 3G RAT
< CDMA 2000 Radio Access Technology Capability : bit > -- 3G RAT
-- Additions in release 4
< UMTS 1.28 Mcps TDD Radio Access Technology Capability : bit > -- 3G RAT
< GERAN Feature Package 1 : bit >
{ 0 | 1 < Extended DTM GPRS Multi Slot Class : bit(2) >
< Extended DTM EGPRS Multi Slot Class : bit(2) > }
< Modulation based multislot class support : bit >
-- Additions in release 5
{ 0 | 1 < High Multislot Capability : bit(2) > }
< GERAN 1u Mode Capability : bit >
{ 0 | 1
< GMSK_MULTISLOT_POWER_PROFILE : bit (2) >
< 8-PSK_MULTISLOT_POWER_PROFILE : bit (2) > };
-- Additions in release 6
< WLAN 802.xx Radio Access Technology Capability : bit(3) >

```

FIG. 5A2

DTM GPRS Multi Slot Class (2 bit field)	
This field indicates the DTM GPRS multislot capabilities of the MS. It is coded as follows:	
Bits	
2 1	
0 0	Unused. If received, the network shall interpret this as '01'
0 1	Multislot class 5 supported
1 0	Multislot class 9 supported
1 1	Multislot class 11 supported
.....	
UMTS FDD Radio Access Technology Capability (1 bit field)	
Bit	
0	UMTS FDD not supported
1	UMTS FDD supported
UMTS 3.84 Mcps TDD Radio Access Technology Capability (1 bit field)	
Bit	
0	UMTS 3.84 Mcps TDD not supported
1	UMTS 3.84 Mcps TDD supported
CDMA 2000 Radio Access Technology Capability (1 bit field)	
Bit	
0	CDMA 2000 not supported
1	CDMA 2000 supported
UMTS 1.28 Mcps TDD Radio Access Technology Capability (1 bit field)	
Bit	
0	UMTS 1.28 Mcps TDD not supported
1	UMTS 1.28 Mcps TDD supported
WLAN 802 Radio Access Technology Capability (3 bit field)	
Bits	
000	WLAN 802.xx not supported
001	WLAN 802.11b supported
010	WLAN 802.11a supported
011	WLAN 802.16 supported

GERAN Feature Package 1 (1 bit field)	
This field indicates whether the MS supports the GERAN Feature Package 1 (see 3GPP TS 44.060). It is coded as follows:	
Bit	
0	GERAN feature package 1 not supported.
1	GERAN feature package 1 supported.

FIG. 5B