



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:  
**Corrected version no 1 (W1 A1)**  
**Corrections, see**  
**Bibliography INID code(s) 72**

(51) International Patent Classification (IPC):  
**E05B 13/00** <sup>(2006.01)</sup> **E05B 15/00** <sup>(2006.01)</sup>  
**E05B 17/00** <sup>(2006.01)</sup> **E05B 17/20** <sup>(2006.01)</sup>  
**E05B 47/06** <sup>(2006.01)</sup> **E05B 47/00** <sup>(2006.01)</sup>  
**E05B 63/00** <sup>(2006.01)</sup>

(48) Corrigendum issued on:  
**11.10.2023 Bulletin 2023/41**

(52) Cooperative Patent Classification (CPC):  
**E05B 13/004; E05B 15/0033; E05B 17/0062;**  
**E05B 17/2092; E05B 47/0692;** E05B 47/0012;  
E05B 63/0056; E05B 2047/002; E05B 2047/0058;  
E05B 2047/0094

(43) Date of publication:  
**30.08.2023 Bulletin 2023/35**

(21) Application number: **23158338.6**

(22) Date of filing: **23.02.2023**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB**  
**GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL**  
**NO PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA**  
Designated Validation States:  
**KH MA MD TN**

(72) Inventors:  

- **Rossall, Robert**  
**Coventry, CV5 6UR (GB)**
- **Golder, Simon**  
**Coventry, CV5 6UR (GB)**

(30) Priority: **25.02.2022 GB 202202674**

(74) Representative: **Wilson Gunn**  
**Charles House**  
**148/9 Great Charles Street**  
**Birmingham B3 3HT (GB)**

(71) Applicant: **Gretsch Unitas Limited**  
**Coventry, West Midlands CV5 6UR (GB)**

(54) **A DOOR HANDLE ARRANGEMENT**

(57) Disclosed is a door handle arrangement comprising: a first door handle for use on a first side of a door; a second door handle for use on a second side of the door; a spindle for connecting between the first and second door handles, wherein rotating either or both of the first or second door handles rotates the spindle; wherein either the first or second door handle comprises a spindle lock which is movable between a stowed position in which the spindle is free to rotate and an engaged position in which the spindle lock prevents rotation of the spindle, wherein the spindle lock is configured to move between the stowed position and engaged position upon removal of the second door handle from the door.

