



US010742658B2

(12) **United States Patent**
Lelcuk et al.

(10) **Patent No.:** **US 10,742,658 B2**

(45) **Date of Patent:** **Aug. 11, 2020**

(54) **METHOD AND SYSTEM FOR
BLOCKCHAIN-BASED ANTI-BOT
PROTECTION**

(56) **References Cited**

U.S. PATENT DOCUMENTS

(71) Applicant: **RADWARE, LTD.**, Tel Aviv (IL)

7,721,107 B2 5/2010 Golle et al.
9,426,182 B1* 8/2016 Zeljko H04L 63/20
(Continued)

(72) Inventors: **Alon Lelcuk**, Ramot Meir (IL); **David Aviv**, Tel Aviv (IL)

FOREIGN PATENT DOCUMENTS

(73) Assignee: **Radware, Ltd.**, Tel Aviv (IL)

CN 107079036 A 8/2017
KR 101837169 B1 3/2018

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 76 days.

(Continued)

OTHER PUBLICATIONS

(21) Appl. No.: **16/182,011**

International Search Report and Written Opinion of International Searching Authority for PCT/US2019/027476, ISA/RU, Moscow, Russia, dated Aug. 8, 2019.

(22) Filed: **Nov. 6, 2018**

(Continued)

(65) **Prior Publication Data**

US 2019/0334905 A1 Oct. 31, 2019

Primary Examiner — Darren B Schwartz

(74) *Attorney, Agent, or Firm* — M&B IP Analysts, LLC

Related U.S. Application Data

(60) Provisional application No. 62/663,132, filed on Apr. 26, 2018.

(51) **Int. Cl.**

H04L 29/06 (2006.01)
H04L 9/06 (2006.01)

(Continued)

(57) **ABSTRACT**

A method and a trust broker system for blockchain-based anti-bot protection are provided. The method includes identifying, on a blockchain network, a request from a client to access a protected entity; selecting an access policy in response to the access request, wherein the access policy includes at least one game to be performed by the client; causing execution of the at least one game defined in the access policy; identifying, on the blockchain network, results of the at least one game, wherein the results are deposited by the client upon completion of the game; determining a bias of the client based on the completion results, wherein the determined bias is utilized for a cybersecurity assessment of the client, wherein the determined bias for the client is maintained on the blockchain network; and granting or denying access to the protected entity by the client based on the determined bias.

(52) **U.S. Cl.**


CPC **H04L 63/10** (2013.01); **G06Q 20/3823** (2013.01); **H04L 9/0637** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC H04L 63/10; H04L 9/0637; H04L 9/3213; H04L 63/1441; H04L 63/20;

(Continued)

47 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
G06Q 20/38 (2012.01)
H04L 9/32 (2006.01)
- (52) **U.S. Cl.**
 CPC **H04L 9/3213** (2013.01); **H04L 63/1441**
 (2013.01); **H04L 63/20** (2013.01); **H04L**
2209/38 (2013.01); **H04L 2463/144** (2013.01)
- (58) **Field of Classification Search**
 CPC H04L 2209/38; H04L 2463/144; H04L
 63/12; H04L 2209/56; H04L 9/3239;
 G06Q 20/3823
 See application file for complete search history.

(56) **References Cited**
 U.S. PATENT DOCUMENTS

9,452,355	B1	9/2016	Lin	
9,514,293	B1*	12/2016	Moritz	H04L 63/102
9,705,895	B1	7/2017	Gutzmann	
9,807,092	B1	10/2017	Gutzmann	
10,049,202	B1*	8/2018	Johansson	G06F 21/36
10,097,583	B1*	10/2018	Demirjian	H04L 63/20
10,268,817	B1*	4/2019	Pham	G06F 21/45
10,587,596	B1*	3/2020	Sahar	H04L 63/104
2007/0150934	A1*	6/2007	Fiszman	H04L 63/1425 726/1
2010/0037319	A1*	2/2010	Steeves	G06F 21/31 726/23
2010/0162357	A1*	6/2010	Chickering	G06F 21/36 726/3
2010/0222142	A1	9/2010	Mori	
2013/0179958	A1	7/2013	Fujiwara et al.	
2014/0325223	A1*	10/2014	Turgeman	H04L 63/1408 713/168
2014/0325645	A1*	10/2014	Turgeman	H04L 63/1408 726/22
2015/0317463	A1	11/2015	Herunde et al.	
2015/0356555	A1	12/2015	Pennanen	
2016/0012424	A1	1/2016	Simon et al.	
2016/0162897	A1	6/2016	Feeney	
2016/0292592	A1	10/2016	Patthak et al.	
2016/0330235	A1*	11/2016	Thompson	H04L 63/10

2017/0048234	A1	2/2017	Lohe et al.	
2017/0149560	A1	5/2017	Shah	
2017/0221052	A1	8/2017	Sheng et al.	
2017/0237570	A1	8/2017	Vandervort	
2017/0243208	A1	8/2017	Kurian et al.	
2017/0244707	A1	8/2017	Johnsrud et al.	
2017/0293912	A1	10/2017	Furche et al.	
2017/0323392	A1*	11/2017	Kasper	H04L 63/123
2017/0366564	A1*	12/2017	Ping	G06F 21/36
2017/0366566	A1*	12/2017	Demirjian	G06F 21/36
2018/0060496	A1	3/2018	Bulleit et al.	
2018/0068130	A1	3/2018	Chan et al.	
2018/0096175	A1	4/2018	Schmeling et al.	
2018/0197172	A1*	7/2018	Coburn	G06Q 10/00
2018/0225466	A1	8/2018	Ducatel	
2018/0332063	A1*	11/2018	Ford	H04L 63/1416
2019/0073666	A1	3/2019	Ortiz et al.	
2019/0172026	A1*	6/2019	Vessenes	G06Q 20/3674
2019/0184286	A1*	6/2019	Du	A63F 13/35
2019/0220592	A1*	7/2019	Liu	H04L 63/102
2019/0334717	A1	10/2019	Lelcuk et al.	
2019/0370793	A1*	12/2019	Zhu	H04L 9/3239
2019/0370813	A1*	12/2019	Bravick	G06Q 20/223
2020/0027089	A1*	1/2020	Kuchar	G06F 16/1837
2020/0028853	A1*	1/2020	Ford	H04L 63/108

FOREIGN PATENT DOCUMENTS

WO	2017021154	A1	2/2017
WO	2017136956	A1	8/2017

OTHER PUBLICATIONS

International Search Report and Written Opinion of International Searching Authority for PCT/US2019/028029, ISA/RU, Moscow, Russia, dated Aug. 26, 2019.

International Search Report and Written Opinion of International Searching Authority for PCT/US2019/028031, ISA/RU, Moscow, Russia, dated Aug. 8, 2019.

The International Search Report and the Written Opinion for PCT/US2019/028030, ISA/RU, Moscow, Russia, dated Jul. 23, 2019.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

1

METHOD AND SYSTEM FOR BLOCKCHAIN-BASED ANTI-BOT PROTECTION

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of U.S. Provisional Application Ser. No. 62/663,132 filed on Apr. 26, 2018, the contents of which are hereby incorporated by reference.

TECHNICAL FIELD

This disclosure generally relates to network security technology, and more particularly to detection, classification, and mitigation of Internet bots.

BACKGROUND

A bot is a software application that is configured to execute automated tasks, often over large networks such as the Internet. Bots can be used to perform helpful functions but are often employed for more nefarious purposes. Botnets are collections of coordinated bots that run over one or more systems and can be programmed to execute harmful codes. Because botnets are often implemented using infected home computers or Internet of Things (IoT) devices with random IP addresses, or virtual machines which can regularly change certain identifying characteristics such as MAC address or Internet Protocol (IP) addresses, it can be difficult to identify, track and block attacks initiated by such botnets. Botnets can share an attacked system with legitimate users such that their presence is effectively hidden.

Advanced botnets utilize machine learning techniques to better coordinate the attack. Such machine learning techniques are used to alleviate the Command and Control (C&C) burden, optimize the attack, and circumnavigate counter measures. One common technique used is based on Swarm intelligence allowing for self-organization of botnets.

The Open Web Application Security Project (OWASP) foundation has classified automated threats (Bots) against Web applications into 6 categories: Account Credentials, Availability of Inventory, Abuse of Functionality (other), Payment Cardholder Data, Vulnerability Identification, and Denial of Service (DoS). The nature and operation of threats in each such category is different and should be handled differently. For example, in the "Availability of Inventory" category, threats related to Denial of Inventory, Scalping, and Sniping are executed. On the other hand, threats in the "Vulnerability Identification" category include vulnerability scanning, footprinting, and fingerprinting. As such, different detection and mitigation techniques should be utilized for different types of detected threats.

Existing anti-bot solutions use a simple "human or machine" test to establish trust and security context, i.e., a human is trusted but not machines. Current solutions utilize interactive challenges to verify if a transaction is initiated by a legitimate client application (e.g., a web browser) and is under control of a human. Examples for such challenges are a SYN cookie, a web redirect (e.g., 302 HTTP redirect message), a JavaScript challenge, a CAPTCHA, and the like used individually or orchestrated to a single flow.

Establishing security context and trust based on web challenges suffers from several limitations. For example, such challenges require an interactive session with a client device. Further, for at least a CAPTCHA challenge, a

2

graphical user interface (GUI) is also required. As such, the challenges negatively affect the user experience while accessing the web services. In addition, challenges that require a GUI cannot operate to allow machine-to-machine authentication, such as through Application Programming Interfaces (APIs). This is a major disadvantage since many of today's legitimate clients, such as IoT devices, are not equipped with suitable GUIs. Further, CAPTCHAs can be bypassed using "sweatshops."

Further, in the related art, existing anti-bot solutions rely on tracking user activities and devices using "fingerprinting" techniques to monitor and identify bot activity. A fingerprint of a computing device is information collected about the device (e.g., a smartphone) for identification. Fingerprints can be used to fully or partially identify individual users or devices even when cookies are turned off. Tracking user activity includes collecting behavioral data over time.

Generating a unique fingerprint for a large number of devices requires the fingerprints to be very sensitive to variations in the collected data, as such fingerprints become less stable over time and, as a result, a device may not exhibit the same fingerprint over time. This adversely affects the value of the collected data. Fingerprinting techniques are also susceptible to spoofing. A bot may actively modify its fingerprint to alter its historical date or to identify its data as that of another device. Further, anti-bot solutions impose exponential penalties when validating fingerprints.

Furthermore, existing anti-bot solutions attempt to cross-correlate the data with device or personal information such as, for example, a user name, a phone number, login credentials, and so on. As such, existing anti-bot solutions breach privacy of users, and thus may not be effective due to privacy regulations. For example, general data protection regulation (GDPR) prohibits sharing devices' fingerprints across sites.

Currently there is no available cyber-security solution that provides both effective detection while maintaining the privacy of the users. Therefore, with malicious bot activity accounting for about a third of all Internet traffic, it would be advantageous to provide an efficient solution that would cure the deficiencies of existing anti-bot solutions.

SUMMARY

A summary of several example embodiments of the disclosure follows. This summary is provided for the convenience of the reader to provide a basic understanding of such embodiments and does not wholly define the breadth of the disclosure. This summary is not an extensive overview of all contemplated embodiments, and is intended to neither identify key or critical elements of all embodiments nor to delineate the scope of any or all aspects. Its sole purpose is to present some concepts of one or more embodiments in a simplified form as a prelude to the more detailed description that is presented later. For convenience, the term "certain embodiments" may be used herein to refer to a single embodiment or multiple embodiments of the disclosure.

Certain embodiments disclosed herein include a method for method for blockchain-based anti-bot protection. The method comprises identifying, on a blockchain network, a request from a client to access a protected entity; selecting an access policy in response to the access request, wherein the access policy includes at least one game to be performed by the client; causing execution of the at least one game defined in the access policy; identifying, on the blockchain network, results of the at least one game, wherein the results are deposited by the client upon completion of the game;

determining a bias of the client based on the completion results, wherein the determined bias is utilized for a cyber-security assessment of the client, wherein the determined bias for the client is maintained on the blockchain network; and granting or denying access to the protected entity by the client based on the determined bias.

Certain embodiments disclosed herein include a system for blockchain-based anti-bot protection. The system comprises a processing circuitry; and a memory, the memory containing instructions that, when executed by the processing circuitry, configure the system to: identifying, on a blockchain network, a request from a client to access a protected entity; selecting an access policy in response to the access request, wherein the access policy includes at least one game to be performed by the client; causing execution of the at least one game defined in the access policy; identifying, on the blockchain network, results of the at least one game, wherein the results are deposited by the client upon completion of the game; determining a bias of the client based on the completion results, wherein the determined bias is utilized for a cyber-security assessment of the client, wherein the determined bias for the client is maintained on the blockchain network; and granting or denying access to the protected entity by the client based on the determined bias.

BRIEF DESCRIPTION OF THE DRAWINGS

The subject matter disclosed herein is particularly pointed out and distinctly claimed in the claims at the conclusion of the specification. The foregoing and other objects, features, and advantages of the disclosed embodiments will be apparent from the following detailed description taken in conjunction with the accompanying drawings.

FIG. 1 is a network diagram utilized to describe the various disclosed embodiments.

FIG. 2 is a flowchart illustrating a method for blockchain-based anti-bot protection mechanism according to an embodiment.

FIG. 3 is an example block diagram of the trust broker system according to an embodiment.

DETAILED DESCRIPTION

The embodiments disclosed herein are only examples of the many possible advantageous uses and implementations of the innovative teachings presented herein. In general, statements made in the specification of the present application do not necessarily limit any of the various claimed embodiments. Moreover, some statements may apply to some inventive features but not to others. In general, unless otherwise indicated, singular elements may be in plural and vice versa with no loss of generality. In the drawings, like numerals refer to like parts through several views.

According to the disclosed embodiments, a method and system for blockchain-based anti-bot protection are provided. In an example embodiment, a game is used to control access to protected entities. Specifically, a game is a mechanism by which the bias is established and henceforth access rights and privileges are gained, exchanged, or otherwise used. The game, when executed, can also reveal the behavior of the client (or its user). A bias may be defined as metadata utilized for cyber-security assessments. Different types of biases are defined herein. Such types include, but are not limited to, a cognitive bias, a behavior bias, and an intent

bias. The various types of biases are determined using different types of games executed by a client attempting to access a protected entity.

The game's type, scope and available strategies are set in an access policy defined for the protected entity. A bias is determined based on the results of the game. Based on the bias, a determination can be made if a client accessing a protected entity is, for example, a bot. That is, drift or deviation from the expected or previously established bias would be indicative of a bot.

FIG. 1 shows an example network diagram **100** utilized to describe the various disclosed embodiments. The network diagram **100** illustrated in FIG. 1 includes an admission system **110**, a client **120**, a blockchain peer-to-peer network **130** (hereinafter referred to as the blockchain network **130**, merely for simplicity purposes), a protected entity **140**, a trust broker **160**, and an audit system **170**. The entities in the network diagram **100** communicate via a network **150**, reside in the network **150**, or both.

The client **120** may be a PC, a mobile phone, a smart phone, a tablet computer, a server, and the like. The client **120** may be operated by a legitimate user or a legitimate program, or may be an attack tool. The client **120** may execute an application or program to access the protected entity **140**.

The protected entity **140** is the entity to be protected from malicious threats. The protected entity **140** may be any network or computing element including resources that can be accessed by the client **120**. For example, the protected entity **140** may be a function in a serverless architecture, an application server, a web server, a cloud application, a datacenter, a network device (e.g., a router, an ADC, etc.), a firewall (e.g., a web-application firewall), and so on.

In certain implementations, the audit system **170** is utilized to record or log any transactions performed between two or more of the admission system **110**, the client **120**, the trust broker **160**, and the protected entity **140**. For example, the audit system **170** is configured to record any suspicious user or bot activity (e.g., many access attempts by a client, a high rate for utilizing access tokens, and so on). In another embodiment, the function of logging transactions by the audit system **170** is performed on the blockchain network **130**, i.e., using a distributed ledger maintained thereon.

According to an embodiment, the trust broker **160** may be connected with the protected entity **140**, where both the trust broker **160** and the protected entity **140** are peers in the blockchain network **130** and each may act as a proxy to the network **150**. For example, acting as a proxy may include translating from HTTPS messages to messages that can be transported on the network **150**. Each of the trust broker **160** and the protected entity **140** may be configured to receive or otherwise intercept requests (such as, but not limited to, HTTP/HTTPS requests) generated by the client **120**.

In an embodiment, the trust broker **160** is configured to administer the games that a client **120** needs to participate in to gain access to the protected entity **140** or to specific resources (not shown) within the protected entity **140**. In an embodiment, the trust broker **160** is configured with a plurality of access policies. An access policy defines at least: the protected entities and resources under protection, one or more games used in the protection template, a game scope for each game, initialization parameters of each game, completion criteria for each game, and the steps to perform upon completion of a successful game or game completion awards.

A game scope is the group of cooperating protected entities or resources within the protected entity **140** and the

visibility and validity of access tokens within the group. The game scope may be private in which case there is an active instance of a game per a protected entity resource. An entity game is a single game instance shared by multiple protected resources within the protected entity **140**. A global game is a single game instance shared by all protected resources across multiple protected entities within a Trust Broker. The various games and their respective strategies are discussed in greater detail below.

It should be noted that, although one client **120**, one admission server **110**, and one protected entity **140** are illustrated in FIG. **1** merely for the sake of simplicity, the embodiments disclosed herein can be applied to a plurality of clients, a plurality of admission servers, a plurality of protected entities, or any combination of thereof. Further, a plurality of admission systems and trust brokers can be utilized or be configured in a distributed implementation. The clients may be in different geographical locations. Furthermore, a single client **120** may be served by a plurality of admission servers **110** or trust brokers **160** concurrently.

It should be further noted that, in certain embodiments, the admission system **110** and the trust broker **160** may be implemented in a single system or as a distributed system. Further, each element discussed above can also be integrated in a single system, for example: the admission system **110** and the protected entity **140** may be implemented as a single unified gateway. In an embodiment, the audit system **170** is integrated in the admission system **110**.

In another embodiment, the admission system **110**, the trust broker **160**, the protected entity **140**, or a combination thereof, can be implemented in a network device (not shown) already deployed in the network **150**. Examples for such a network device include an application delivery controller (ADC), a load balancer, a web application firewall (WAF), a router, a firewall, and the like.

The blockchain network **130** is a collection of one or more nodes (not labeled) utilized to maintain a decentralized ledger and verified blocks, as discussed above. A node may be a physical machine, or a virtual machine executed by a machine having a sufficient computing power to verify a block. In an embodiment, the nodes of the blockchain network **130** may be configured to handle proprietary access tokens (e.g., verified block of transactions for converting proprietary tokens). The proprietary access tokens may be of different types.

In another embodiment, the nodes of the blockchain network **130** may be configured to handle tokens of standard virtual currencies such as, but not limited to, Bitcoin, Ethereum, Litecoin, and the like. For example, the infrastructure to the Ethereum blockchain network is based on a collection of nodes realized as Ethereum Virtual Machines (EVM) connected in a mesh connection. Each such node runs a copy of the entire blockchain and competes to mine the next block or validate a transaction. Further, each node in the blockchain network **130**, implemented as Ethereum, maintains an updated copy of the entire Ethereum blockchain. In an embodiment, the blockchain network **130** can be configured as a private network. In this embodiment, access tokens (or contracts) accessible to nodes that are connected to the blockchain network **130** operate in a private mode. In yet another embodiment, a private token is utilized as part of a public or private Ethereum blockchain.

In another embodiment, the trust broker **160** may be implemented as a smart contract using the crypto EVM capabilities. A smart contract is a computer protocol intended to digitally facilitate, verify, or enforce the negotiation or performance of a contract and is defined as a

collection of executable computer code in one of many possible computer languages such as, but not limited to, "Python", "Java", "R", "Solidity" or any other computer languages used now or in the future to implement such smart contracts. Smart contracts allow the performance of credible transactions without the existence of trusted third parties. These transactions are trackable and irreversible.

It should be appreciated that, in some embodiments, utilizing the blockchain network **130** for the admission process allows maintaining privacy of the user accessing the protected entity **140** while providing transparency of admission transactions. Further, the blockchain network **130** can be easily scaled, therefore providing a scalable solution.

According to the disclosed embodiments, any client, e.g., the client **120**, attempting to access the protected entity **140** is required to execute a game as defined by an access policy provided by the trust broker **160** for the protected entity **140** or one of its resources being accessed. The game and the game scope is defined in an access policy selected by the trust broker **160**.

According to the disclosed embodiments, the game may be realized as executable code executed by the trust broker **160**. In another embodiment, the game can be realized as parametric data loaded dynamically by the trust broker **160**. In yet another embodiment, a rule engine or other programmatic mechanism is utilized to enforce game progression according to established game rules.

A game may be executed in the trust broker **160** or can be executed by the client **120**, wherein the capabilities of the blockchain network **130** are used to secure the interaction between the client **120** and the trust broker **160**.

Each game is designed to allow the trust broker **160** to establish a bias for the client **120**. The bias is established as the client **120** progresses with the game, at the completion of the game, or both. In an embodiment, a game is used to establish a behavior bias using risks represented as access tokens. The tokens may be proprietary tokens or based on standard virtual currencies (e.g., Bitcoins) or contracts. Further, the access tokens can be of the same type or different type. In an embodiment, the trust broker **160** is further configured, based on the knowledge of the client historical game behavior and game rules, to set a dynamic conversion value from a first type of token to a second type of token.

In one embodiment, a cognitive bias may be established based on accumulation of access tokens. To this end, when the game executed would present the user with options to pick-up access tokens while solving riddles, navigating through a maze, and the like.

As a non-limiting example for a game for establishing a cognitive bias, a maze with treasures is used. The maze is generated based on a complexity level defined in the respective access policy. For example, for a highly secure protected entity, a complex maze would be generated. The maze can be realized as portable executable code or parametric data loaded dynamically by the client **120** to the rules engine. A user of the client **120** is requested to navigate the maze to collect objects. The collection of objects results in awarding the user with access tokens, that is the objects represent access tokens. As another non-limiting example, the game may include a series of questions for which answers to the questions reveal cognitive bias inclinations.

The game progression is monitored to determine how the client (or its user) interacts with the game. This allows for determining the cognitive bias. The progress may be measured with respect to, but not limited to, time of activities, choices made by the user, and the like. For example, the time

it was required to collect the objects, the number of collected objects, type of collected objects (candies or bugs), and so on. The cognitive bias is associated with the client **120** and saved in the blockchain network **130** as an encrypted block. Thus, no entity but the trust broker **160** has knowledge of the determined bias.

In another embodiment, a behavioral bias may be established based on access tokens spending. To this end, the executed game would present the client **120** (or its user) with options to spend access tokens and, based on the actual tokens spent, the behavioral bias is determined.

As a non-limiting example for a game for establishing a behavioral bias, the game may be a bidding game where the user is requested to place a bid on, for example, accessing a protected entity, purchasing access tokens, and the like. The higher the bid is, the behavioral bias is determined to be of a spender.

In yet another embodiment, an intent bias may be established based on a balance of the access tokens. The intent bias also defines the intent of a client navigating through a protected entity. For example, if the protected entity is an e-commerce website, the intent may indicate if the user is scarping for information, comparing prices, or shopping. In an embodiment, the games can be hiding in links of products in such an e-commerce website. For example, the games may include crafting interactions that have intent hidden in the game for selection (e.g., “are you looking for similar products” versus “are you looking for a cheap present for a friend”).

Other embodiments to establish the intent bias may include presenting the client **120** with multiple games and requesting the client to select one game. Based on the game selection, the intent is established. As another example embodiment, by building a hiding decision tree in a game, each decision branch allocates/deallocate the client **120** with a certain number of tokens. Further, by tracking the selected branches, the trust broker **160** can infer the intent bias.

The trust broker **160** is configured to allow or deny access to the protected entity **140** based on the bias or any deviation thereof. The trust broker **160** may further provide a recommendation as whether to allow admission or not. It should be emphasized that the admission is not granted merely based on the fact that the user successfully completed the game, but rather based on the determined bias. For example, the maze game may be successfully completed when the user collected a number of objects, but the cognitive bias is determined based on the type of collected objects (e.g., candies vs. bugs). Thus, if even all objects have been collected, still admission may not be granted. Any failed admission may be logged in the audit system **170**.

It should be noted that all transactions related to the game to be performed, awarding access tokens, and saving the established biases are performed over the blockchain network **130**.

Specifically, the granting of the access tokens is recorded as a transaction included in a block of a blockchain maintained by the blockchain network **130**. Upon requesting an access to the protected entity **140** by the client **120**, the client **120** “pays” the protected entity **140** the required number of access tokens.

This may be performed by revoking (spending) access tokens granted to the client **120** to gain access. In other words, the use of the access tokens is recorded as a transaction and included in a block of the blockchain maintained by the blockchain network **130**. Thus, the validation of the transaction (access request) is performed through the blockchain network **130**. The validation can be performed prior to

admitting an access to the protected entity **140**. In yet another embodiment, the validation is performed after an admission is conditionally granted to the client. If the validation fails, the client **120** is disconnected from the protected entity **140**.

The policies, games, and biases can be utilized to detect various types of attacks. Such attacks include an account takeover, a denial of inventory, a denial of service, and anti-scraping.

An example, the access policy may periodically administer a similar cognitive bias game to the client **120** by monitoring cognitive bias drifts. If such a bias drift is identified, the protected entity **140** may conclude that the client **120** has undergone an account take over attack.

As another example, the access policy can cross reference the client’s **120** intent with the client’s **120** behavior. When the protected entity **140** identifies that the client’s **120** behavior is similar, yet the intent has changed, may be determined that the client **120** has now changed its role and a cognitive bias game may be administered to further validate the user authenticity.

As another example, the intent bias may signify the user’s role in the system and deviation from that intent bias is indicative of an attack. For instance, the intent bias of a user may be determined to be only about reading transactions. If that bias intent is modified into writing transactions, this may signify an access violation.

It should be noted that the changes in the intent bias may not be deterministic. For example, many embodiments can utilize a numerical dimension for an intent bias. For example, the user may have 20/80 write/read intent bias. By monitoring the change of ratios between intent biases, potential security risks may be determined based on changes in ratio and thus the protected entity **140** may change its access restriction.

In yet another embodiment, the client **120** and the protected entity **140** may optionally include means for maintaining tokens issued by the admission system **110** and the trust broker **160** or can utilize the cryptocurrency wallet described herein.

Further, each established bias for a client **120** is recorded as a transaction included in a block of a blockchain maintained by the blockchain network **130**. The transaction can be signed by the keys of the client **120** and trust broker **160**.

In another embodiment, the blockchain network **130** can maintain an entire game instance or a URL to the game location. After retrieving and playing the game, the client **120** deposits the game completion results or criteria as metadata in a blockchain transaction.

FIG. 2 shows an example flowchart **200** for establishing bias and trust for clients attempting to access a protected entity according to an embodiment. The method may be performed by the trust broker **160** using the blockchain network **130**.

At **S210**, the blockchain network is monitored to identify a client **120** may stake (i.e., place a bet) a number of previously awarded access tokens. The staked access tokens are provided as a payment transaction in the blockchain network **130**. The staked access tokens can be associated with a request to access a protected entity. The access request includes an identifier (e.g., an IP address, a URL, and the like) of the protected entity (or resource) to access.

At **S215**, the blockchain transaction is analyzed to identify the protected entity (“entity ID”) addressed by the client form the transaction metadata. That is, an entity ID is extracted from the transaction. **S215** also include identifying an identifier of the client (“client ID”). The client ID can be

supplied by the protected entity **140** or by an admission system **110**. In other embodiments, the client **120** may generate its own ID. To this end, the client ID can be randomly selected or derived based on the client's system parameters, such as, but not limited to, an IP address, a MAC address, and the like. The client ID may be mathematically derived using proof of knowledge to track client activity across multiple protected entities. In yet another embodiment, the client ID may be a USER-ID as provided by an external authentication service such as those using OAuth or SAML systems and used as admission controller **110**.

It should be noted that the client ID does not reveal any information about the user of the client **120**. Further, the generation of the client ID on the client **120** does not require exposing or sharing personal information related to the user device, or even the identifying details on the device or user. The client **120** merely shares a proof about the client ID.

At **S220**, using the entity ID, the respective access policy assigned to the protected entity attempted is retrieved.

An access policy defines a game type and a scope of the game. A scope of a game may be a private game, an entity game, or a global game. For each game instance, the game specific parameters are defined. The game parameters may include, for example, a conversion value, a number of starter tokens to participate in the game, an expiration time, terms on the usability of the access tokens, and so on.

The access policy further designates a protected entity (or resources of the protected entity) and corresponding games the client has to execute in order to access the designated protected entity or resources. As noted above, a protected entity resource can be assigned multiple games, each game may be assigned with its own priority (e.g., optional, required, required and sufficient, and so on). The access policy may define replenishment method.

In an embodiment, a number of access policies may be associated with a single protected entity. In such an embodiment, the selection of the access policy is based on the protected entity designated in the received access request. Further, the selection may be based on a plurality of selection parameters. Such parameters may be related to the client **120**, the protected entity **140**, or a combination thereof.

In an embodiment, the selection of the policy is based on information retrieved from external sources. Examples for such sources include, for example, external databases, reputation services, and historical records. The historical records may include, for example, successful or failed access attempts, previously selected games, and so on. The historical records are retrieved from the audit system **170**. As an example, for a client with a "bad" reputation, an access policy with multiple games will be selected.

At **S230**, the staked access tokens are converted into a first type of access tokens, thereby allowing the client **120** to execute a game. The conversion value may be dynamically determined based on the access policy, historical records (e.g., about past gaming behavior of the client), or both. The first type of tokens are deposited on the blockchain network **130**. It should be noted that, if the client **120** does not hold enough staked access tokens, no conversion is made and execution terminates.

At **S240**, the blockchain network **130** is monitored to determine if the client **120** deposited enough of the first type of access tokens to participate in a game. The first type of access tokens may be proprietary tokens, cryptocurrency tokens, and the like. The type and sum of tokens require to participate in a game are specified in the access policy. In an

embodiment, the client **120** is required to deposit (pay) the designated sum of access tokens at every instance of the game.

Upon identification of such tokens, at **S250**, the game to be executed by the client **120** is posted as a transaction on the blockchain network **130**. As noted above, the game instance can be embedded wholly in the blockchain network **130** or, in another embodiment, the blockchain network **130** may hold a URL to the game location.

The game and its complexity to be executed by the client **120** are defined in the respective policy. As noted above, different games can be utilized to determine a different bias, such as an intent, cognitive, or behavior bias.

At **S260**, the blockchain network **130** is monitored to identify the game completion results deposited by the client **120**. The results may be deposited as metadata in a blockchain transaction.

At **S270**, based on the identified completion results, the respective bias for the executed game is established. As demonstrated above, the cognitive bias is characterized by access tokens accumulation, the intent bias is characterized by access tokens balance, and the behavior bias is characterized by access tokens spending. Examples for establishing a bias using the executed games are provided above.

At **S280**, based on the established bias, an access to the protected entity is granted or denied. That is, the admission is not granted merely based on the fact the client **120** (or its user) successfully completed the game, but rather based on the determined bias. For example, if the behavior bias is established as a spender, admission may not be granted. This is because as bot behavior would attempt to access the protected entity many times, thus would require more token spending.

It should be noted that the method discussed herein with reference to FIG. **1** merely for the sake of simplicity and ease of the description. The disclosed embodiments are not limited to the arrangement shown in FIG. **1**.

FIG. **3** is an example block diagram of the trust broker **160** according to an embodiment. The trust broker **160** includes a processing circuitry **310** coupled to a memory **320**, a storage **330**, and a network interface **340**. In an embodiment, the components of the trust broker **160** may be communicatively connected via a bus **350**.

The processing circuitry **310** may be realized as one or more hardware logic components and circuits. For example, and without limitation, illustrative types of hardware logic components that can be used include: field programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), application-specific standard products (ASSPs), GPUs, system-on-a-chip systems (SOCs), general-purpose microprocessors, microcontrollers, digital signal processors (DSPs), and the like, or any other hardware logic components that can perform calculations or other manipulations of information. In an embodiment, the processing circuitry **310** (or the entire system **110**) may be implemented as a Turing machine over the blockchain network.

The memory **320** may be volatile (e.g., RAM, etc.), non-volatile (e.g., ROM, flash memory, etc.), or a combination thereof. In one configuration, computer readable instructions to implement one or more embodiments disclosed herein may be stored in the storage **330**.

In another embodiment, the memory **320** is configured to store software. Software shall be construed broadly to mean any type of instructions, whether referred to as software, firmware, middleware, microcode, or hardware description language. Instructions may include code (e.g., in source code format, binary code format, executable code format, or

any other suitable format of code). The instructions, when executed by the one or more processors, cause the processing circuitry **210** to perform the various processes described herein. Specifically, the instructions, when executed, cause the processing circuitry **310** to perform blockchain-based admission, as discussed hereinabove. In a further embodiment, the memory **320** may further include a memory portion **325** including the instructions.

The storage **330** may be magnetic storage, optical storage, and the like, and may be realized, for example, as flash memory or other memory technology, CD-ROM, Digital Versatile Disks (DVDs), hard-drives, SSD, or any other medium which can be used to store the desired information, such as, log of transactions, public keys, and so on. The storage **330** may include the various access policies and games.

The network interface **340** allows the trust broker **160** to communicate with the blockchain network, clients, trust broker, and protected entities. The network interface **340** furthers peer-to-peer communication with these elements.

It should be understood that the embodiments described herein are not limited to the specific architecture illustrated in FIG. 3, and that other architectures may be equally used without departing from the scope of the disclosed embodiments.

It should be further noted that the trust breaker **160** may be realized using a computing architecture similar to the architecture illustrated in FIG. 3, but that other architectures may be equally used without departing from the scope of the disclosed embodiments. Further, the memory **320** may include instructions for executing the function of the trust broker **160**.

The various embodiments disclosed herein can be implemented as any combination of hardware, firmware, and software. Moreover, the software is preferably implemented as an application program tangibly embodied on a program storage unit or computer readable medium. The application program may be uploaded to, and executed by, a machine comprising any suitable architecture. Preferably, the machine is implemented on a computer platform having hardware such as one or more central processing units (“CPUs”), a memory, and input/output interfaces. The computer platform may also include an operating system and a microinstruction code. The various processes and functions described herein may be either part of the microinstruction code or part of the application program, or any combination thereof, which may be executed by a CPU, whether or not such computer or processor is explicitly shown. In addition, various other peripheral units may be connected to the computer platform such as an additional data storage unit and a printing unit. Furthermore, a non-transitory computer readable medium is any computer readable medium except for a transitory propagating signal.

It should be understood that any reference to an element herein using a designation such as “first,” “second,” and so forth does not generally limit the quantity or order of these elements. Rather, these designations are generally used herein as a convenient method of distinguishing between two or more elements or instances of an element. Thus, a reference to first and second elements does not mean that only two elements may be employed there or that the first element must precede the second element in some manner. Also, unless stated otherwise a set of elements comprises one or more elements. In addition, terminology of the form “at least one of A, B, or C” or “one or more of A, B, or C” or “at least one of the group consisting of A, B, and C” or “at least one of A, B, and C” used in the description or the

claims means “A or B or C or any combination of these elements.” For example, this terminology may include A, or B, or C, or A and B, or A and C, or A and B and C, or 2A, or 2B, or 2C, and so on.

All examples and conditional language recited herein are intended for pedagogical purposes to aid the reader in understanding the disclosed embodiments and the concepts contributed by the inventor to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and embodiments of the invention, as well as specific examples thereof, are intended to encompass both structural and functional equivalents thereof. Additionally, it is intended that such equivalents include both currently known equivalents as well as equivalents developed in the future, i.e., any elements developed that perform the same function, regardless of structure.

What is claimed is:

1. A method for blockchain-based anti-bot protection, comprising:
 - identifying, on a blockchain network, a request from a client to access a protected entity;
 - selecting an access policy in response to the access request, wherein the access policy includes at least one game to be performed by the client;
 - causing execution of the at least one game defined in the access policy;
 - identifying, on the blockchain network, results of the at least one game, wherein the results are deposited by the client upon completion of the game, and wherein the results are deposited onto a blockchain transaction on the blockchain network;
 - determining a bias of the client based on the completion results, wherein the determined bias is utilized for a cyber-security assessment of the client, wherein the determined bias for the client is maintained on the blockchain network; and
 - granting or denying access to the protected entity by the client based on the determined bias.
2. The method of claim 1, wherein identifying the request from the client to access the protected entity further comprises:
 - identifying, on the blockchain network, staked access tokens posted as a blockchain transaction on the blockchain network.
3. The method of claim 2, further comprising:
 - identifying, in the posted blockchain transaction, an identifier of the client and an identifier of the protected entity, wherein a client identifier does not reveal any information about a user of the client.
4. The method of claim 2, further comprising:
 - converting the staked access tokens to a first type of access tokens based on a conversion value; and
 - causing execution of the game when the client holds a sufficient amount of the first type of access tokens.
5. The method of claim 4, wherein the staked access tokens and the first-type access tokens are cryptocurrency tokens having different cryptographic identities.
6. The method of claim 2, wherein the blockchain transaction is realized as at least one of: a smart contract on the blockchain network, and an off-chain Oracle on the blockchain network.
7. The method of claim 1, wherein the access policy is selected based on the protected entity.
8. The method of claim 7, wherein the access policy designates at least one of: the at least one game, the

13

protected entity, a resource within the protected entity, and a scope of the at least one game.

9. The method of claim 8, wherein the scope of the at least one game is any one of: a private game, an entity game, and a global game.

10. The method of claim 1, wherein the access policy is further selected based on at least one selection parameter.

11. The method of claim 10, wherein the at least one selection parameter includes any one of: reputation data and historical records.

12. The method of claim 1, wherein the at least one game is programmed to at least establish the bias of the client.

13. The method of claim 1, wherein the at least one game is shared with the client over the blockchain network.

14. The method of claim 1, wherein the bias includes any one of: a cognitive bias, a behavioral bias, and an intent bias.

15. The method of claim 14, wherein the bias includes the cognitive bias, wherein the cognitive bias is characterized by access tokens accumulation, wherein the access tokens are accumulated during execution of the at least one game.

16. The method of claim 15, wherein the at least one game utilized to establish the cognitive bias is a navigation through a maze for collection of objects, wherein the objects represent access tokens.

17. The method of claim 14, wherein the bias includes the behavioral bias, wherein the behavioral bias is characterized by access tokens spending, wherein the access tokens are spent during execution of the at least one game.

18. The method of claim 17, wherein the at least one game utilized to establish the behavioral bias is a bidding game.

19. The method of claim 14, wherein the bias includes the intent bias, wherein the intent bias is characterized by an access tokens balance.

20. The method of claim 14, wherein the at least one game utilized to establish the intent bias is a navigation through resources of the protected entity.

21. The method of claim 14, wherein each type of bias is defined to detect a cyber-security threat.

22. The method of claim 21, wherein the cyber-security threat is any one of: account takeover, denial of inventory, denial of service, and anti-scraping.

23. The method of claim 1, wherein granting the client an access the protected entity based on the determined bias further comprises:

determining a drift from a previously established bias; and denying access to the protected entity when the drift from the previously established bias is determined.

24. A non-transitory computer readable medium having stored thereon instructions for causing a processing circuitry to execute a process for blockchain-based anti-bot protection, the comprising:

identifying, on a blockchain network, a request from a client to access a protected entity;

selecting an access policy in response to the access request, wherein the access policy includes at least one game to be performed by the client;

causing execution of the at least one game defined in the access policy;

identifying, on the blockchain network, results of the at least one game, wherein the results are deposited by the client upon completion of the game, and wherein the results are deposited onto a blockchain transaction on the blockchain network;

determining a bias of the client based on the completion results, wherein the determined bias is utilized for a

14

cyber-security assessment of the client, wherein the determined bias for the client is maintained on the blockchain network; and

granting or denying access to the protected entity by the client based on the determined bias.

25. A trust broker system for blockchain-based anti-bot protection, comprising:

a processing circuitry; and

a memory, the memory containing instructions that, when executed by the processing circuitry, configure the system to:

identifying, on a blockchain network, a request from a client to access a protected entity;

selecting an access policy in response to the access request, wherein the access policy includes at least one game to be performed by the client;

causing execution of the at least one game defined in the access policy;

identifying, on the blockchain network, results of the at least one game, wherein the results are deposited by the client upon completion of the game, and wherein the results are deposited onto a blockchain transaction on the blockchain network;

determining a bias of the client based on the completion results, wherein the determined bias is utilized for a cyber-security assessment of the client, wherein the determined bias for the client is maintained on the blockchain network; and

granting or denying access to the protected entity by the client based on the determined bias.

26. The system of claim 25, wherein the system is further configured to:

identify, on the blockchain network, staked access tokens posted as a blockchain transaction on the blockchain network.

27. The system of claim 26, further comprising: converting the staked access tokens to a first type of access tokens based on a conversion value; and causing execution of the game when the client holds a sufficient amount of the first type of access tokens.

28. The system of claim 27, wherein the staked access tokens and the first-type access tokens are cryptocurrency tokens having different cryptographic identities.

29. The system of claim 26, wherein the blockchain transaction is realized as at least one of: a smart contract on the blockchain network, and an off-chain Oracle on the blockchain network.

30. The system of claim 26, wherein granting the client an access the protected entity based on the determined bias further comprises:

determining a drift from a previously established bias; and denying access to the protected entity when the drift from the previously established bias is determined.

31. The system of claim 25, wherein the system is further configured to:

identify, in the blockchain transaction, an identifier of the client and an identifier of the protected entity, wherein the client identifier does not reveal any information about a user of the client.

32. The system of claim 25, wherein the access policy is selected based on the protected entity.

33. The system of claim 25, wherein the access policy designates at least one of: the at least one game, the protected entity, a resource within the protected entity, and a scope of the at least one game.

15

34. The system of claim 33, wherein the scope of the at least one game is any one of: a private game, an entity game, and a global game.

35. The system of claim 25, wherein the access policy is further selected based on at least one selection parameter.

36. The system of claim 35, wherein the at least one selection parameter includes any one of: reputation data and historical records.

37. The system of claim 25, wherein the at least one game is programmed to at least establish the bias of the client.

38. The system of claim 25, wherein the at least one game is shared with the client over the blockchain network.

39. The system of claim 25, wherein the bias includes any one of: a cognitive bias, a behavioral bias, and an intent bias.

40. The system of claim 39, wherein the bias includes the cognitive bias, wherein the cognitive bias is characterized by access tokens accumulation, wherein the access tokens are accumulated during execution of the at least one game.

41. The system of claim 40, wherein the at least one game utilized to establish the cognitive bias is a navigation through a maze for collection of objects, wherein the objects represent access tokens.

16

42. The system of claim 39, wherein the bias includes the behavioral bias, wherein the behavioral bias is characterized by access tokens spending, wherein the access tokens are spent during execution of the at least one game.

43. The system of claim 42, wherein the at least one game utilized to establish the behavioral bias is a bidding game.

44. The system of claim 39, wherein the bias includes the intent bias, wherein the intent bias is characterized by an access tokens balance.

45. The system of claim 44, wherein the at least one game utilized to establish the intent bias is a navigation through resources of the protected entity.

46. The system of claim 39, wherein each type of bias is defined to detect a cyber-security threat.

47. The system of claim 46, wherein the cyber-security threat is any one of: account takeover, denial of inventory, denial of service, and anti-scraping.

* * * * *