



US005704799A

United States Patent [19] Wood

[11] Patent Number: **5,704,799**
[45] Date of Patent: ***Jan. 6, 1998**

[54] FIELD REPAIRABLE ELECTRICAL CONNECTOR

[75] Inventor: **Richard G. Wood**, Magnolia, Tex.

[73] Assignee: **Tescorp Seismic Products, Inc.**,
Houston, Tex.

[*] Notice: The term of this patent shall not extend
beyond the expiration date of Pat. No.
5,470,248.

[21] Appl. No.: **486,357**

[22] Filed: **Jun. 7, 1995**

Related U.S. Application Data

[63] Continuation-in-part of Ser. No. 226,009, Apr. 11, 1994, Pat.
No. 5,470,248.

[51] Int. Cl.⁶ **H01R 13/52**

[52] U.S. Cl. **439/281; 439/271; 439/587**

[58] Field of Search **439/271, 281,**
439/587, 651, 655, 692, 736

[56] References Cited

U.S. PATENT DOCUMENTS

H113	8/1986	McNeel	439/282
2,843,133	7/1958	Barbara	131/207
2,881,406	4/1959	Arson	439/589
3,197,730	7/1965	Hargett	339/102
3,449,182	6/1969	Wiltshire	156/69
3,461,529	8/1969	Van Dorn	29/149.5
3,497,864	2/1970	Barnet	339/60
3,641,479	2/1972	O'Brien et al.	439/277
3,693,133	9/1972	Harbom et al.	339/48
3,739,330	6/1973	Hazelhurst et al.	340/17
3,745,511	7/1973	Fussell	339/49
3,783,434	1/1974	Ransford	439/281
3,888,559	6/1975	Geib	339/46
3,937,545	2/1976	Cairns et al.	339/60 R
3,954,154	5/1976	Kruppenbach et al.	181/112
4,032,214	6/1977	McNerney	339/218 M
4,090,759	5/1978	Herrmann	439/281
4,150,866	4/1979	Snyder et al.	439/275
4,284,312	8/1981	Patchett et al.	439/281
4,355,855	10/1982	Rebikoff	339/94 A

4,445,741	5/1984	Annoot	339/49
4,480,151	10/1984	Dozier	174/153 R
4,497,531	2/1985	Baker	339/94 M
4,588,247	5/1986	Grappe et al.	339/94 M
4,589,939	5/1986	Mohebban et al.	156/49
4,609,247	9/1986	Annoot	339/60 M
4,632,482	12/1986	Punako et al.	339/59 M
4,758,174	7/1988	Michaels et al.	439/281
4,767,349	8/1988	Pottier et al.	439/191
4,767,356	8/1988	Grappe	439/455
4,790,768	12/1988	Domingues	439/320
4,820,170	4/1989	Redmond et al.	439/66
4,861,288	8/1989	Friedman	439/736
4,921,452	5/1990	Dozier	439/622
5,014,813	5/1991	Fussell	181/122
5,120,237	6/1992	Fussell	439/282
5,120,268	6/1992	Gerrans	439/736
5,130,954	7/1992	Fussell	367/188
5,145,410	9/1992	Maejima et al.	439/587
5,183,966	2/1993	Hurtado et al.	474/20
5,199,893	4/1993	Fussell	439/271
5,297,974	3/1994	Fussell	439/320
5,362,258	11/1994	Arnsward et al.	439/695
5,387,119	2/1995	Wood	439/281
5,470,248	11/1995	Wood	439/281
5,542,856	8/1996	Wood	439/281

FOREIGN PATENT DOCUMENTS

63398	8/1968	Germany .
2131633	6/1984	United Kingdom .


Primary Examiner—Gary E. Elkins


Attorney, Agent, or Firm—Jenkins & Gilchrist, P.C.


[57] ABSTRACT

An electrical connector having pin members that are partially encapsulated within, and socket members that are completely encapsulated within, electrically nonconductive sheaths that are respectively integrally formed with male and female body members. The male and female body members are joined together by an electrically nonconductive coupling member having a plurality of internally disposed passageways that seal around each of the sheaths. The male and female body members and the coupling member are separately disassemblable and the coupling member is replaceable without the use of special tools or equipment.

11 Claims, 2 Drawing Sheets







FIELD REPAIRABLE ELECTRICAL CONNECTOR

CROSS-REFERENCE TO RELATED APPLICATION

This is a continuation-in-part of application Ser. No. 08/226,009, filed Apr. 11, 1994, now U.S. Pat. No. 5,470,248.

TECHNICAL FIELD

This invention relates generally to a field repairable electrical connector that is adaptable for use in either underwater or dry land applications, and more particularly to such a connector having a replaceable coupling member disposed between male and female body members.

BACKGROUND ART

Waterproof electrical connections require either an internal seal element around the electrically conductive parts of the connector or, alternatively, the entire connector enclosed within a sealed case. Heretofore, failed or faulty waterproof connectors have generally required disassembly in a repair shop and the seals or molded component assemblies replaced with new components. Thus, a long standing problem with electrical connectors in general, and specifically with sealed connectors intended for use in underwater applications, has been the inability to service and repair such connectors in the field.

For example, U.S. Pat. No. 5,387,119, issued Feb. 7, 1995 to the inventor of the present invention, discloses an underwater electrical connector having a male member formed of a rigid plastic material that has a plurality of pins, each of which have a portion that is enclosed by a sheath formed of the same rigid plastic material. The underwater connector has a female member formed of an elastomeric material and has a plurality of passageways formed in the elastomeric material in which a portion of the passageway sealably surrounds the rigid sheaths of the male member. This arrangement provides an excellent open-face waterproof seal to exclude moisture from the connection between the pin and a socket encapsulated within the female member. However, the softer elastomeric material of the female member is prone to wear more quickly than the rigid plastic material of the male member, and after a period of use may lose its sealing capability and must be replaced. Also, the connecting ends of the individual wires of the cable bundle are positioned within the molded female member to form a single molded component. Thus, it is not practical, in the field, to replace only the female connector because the repair must necessarily include the cable to which the female member is molded.

Other electrical connectors have male or female members, or both, in which the respective pins and sockets are encased in a relatively soft, elastomeric body that is bonded to a hard plastic or metallic case surrounding the body. When a single component of a connector is constructed of two or more materials having different physical characteristics, even though they are initially bonded together, the components are prone to subsequent separation and failure.

An important feature of the above referenced U.S. Pat. No. 5,387,119 is the protective sheaths formed around the pin conductors of the male member. The sheaths not only provide a sealing surface, but also provide increased bonding surface area between the pins of the male member and the surrounding encapsulating material of the male body

member. Furthermore, the sheaths effectively increase the electrical isolation of each conductive pin by forming a longer path that an electrical charge must travel along a surface between adjacently disposed pins. Without the sheaths, an electrical charge would only need to traverse the face surface of the body component to form a short circuit between pins. With the sheaths, the electrical charge must travel from the tip of one pin, down the outer surface of the sheath, across the body face surface to an adjacent sheath, and up the outer surface of that sheath to the second pin. However, heretofore, it has not been possible to provide a protective, electrically nonconductive, sheath around both male and female electrical contact elements of a connector, i.e., both the pins and sockets, and simultaneously provide a separate seal around each contact element to form a waterproof connector.

The present invention is directed to overcoming the problems set forth above. It is desirable to have an electrical connector that has a coupling providing a seal around each contact connection, is easily replaceable in the field, and is useable in both underwater and dry land environments. It is also desirable to have such an electrical connector in which every one of the electrical contact elements of both the male and female components are protectively surrounded by a nonconductive sheath.

BRIEF SUMMARY OF THE INVENTION

In accordance with one aspect of the present invention, an electrical connector includes a male member having a body formed of an electrically nonconductive material, and a plurality of electrically conductive pins each having a portion embedded within the body and surrounded a sheath extending outwardly from the body. The electrical connector also includes a female member likewise formed of an electrically nonconductive material, and has a plurality of electrically conductive sockets adapted to receive a respective one of the pins of the male member. Each of the sockets are encapsulated within a sheath that extends outwardly from a face surface of the female member. The electrical connector further includes a coupling member having a body portion, formed of a nonconductive material, and having a plurality of internally disposed passageways that are shaped so that, upon assembly, the passageways receive and completely surround each of the sheaths of the male and female members.

In other aspects of the present invention, if desired, all of the electrically nonconductive components of the electrical connector may be formed of resiliently compressible materials. However, it is preferable that at least the male and female members, or alternatively the coupling member, be formed of rigid materials.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a longitudinal cross section of an electrical connector embodying the present invention, showing the components of the connector in unassembled, spaced apart relationship; and

FIG. 2 is a longitudinal cross section of the electrical connector shown in FIG. 1, showing the components of the connector in assembled relationship.

BEST MODE FOR CARRYING OUT THE INVENTION

In the preferred embodiment of the present invention, an electrical connector 10 has a male member 12 and a female

member 14, both of which respectively have a body portion 16,18 that, preferably, is formed of a hard, rigid, electrically nonconductive material having an electrical resistivity of at least 10^{10} ohm cm. and high resistance to water absorption. Suitable materials for formation of body portions 16,18 of the male and female members 12,14 include, but are not limited to, thermoset plastics and thermoplastics such as urethane, polyphenyl sulfone, polyaryl sulfone, polychlorotrifluoroethylene (PCTFE), phenylene ether/phenylene oxide, polyester, alkyd encapsulating putty, granular and glass reinforced alkyds, fiber filled diallyl phthalates, high density polyethylene, rigid cast or molded epoxies, polyurethane rubber, standard electrical glass, low loss electrical borosilicate glass, and electrical ceramics such as steatite and alumina.

Depending on the selected material, the body portions 16,18 may be formed by injection molding, compression or transfer molding, or casting. Preferably, the body portions 16,18 are constructed of glass filled thermoplastic urethane, and formed by injection molding.

Alternatively, although less desirable because of inherent problems of bonding with embedded conductive elements, the body portions 16,18 of the male and female members 12,14 may be formed of a relatively soft, resiliently compressible material. Suitable materials include both thermoset and thermoplastic elastomers, such as natural-rubber and synthetic rubber polymers. In particular, a blend of polyethylene and neoprene rubber has been found to be suitable for forming electrically nonconductive components of the connector embodying the present invention.

The male member 12 also includes a plurality of electrically conductive pins 20 that are preferably arranged in a predetermined pattern within a mold cavity prior to injection molding the body 16. Simultaneously with molding the body 16, a sheath 22 is formed about a portion of each of the pins 20 thereby encapsulating each of the pins not only within the body 16 but also within a respective sheath 22. The sheaths 22 extend outwardly from a first face surface 24 of the body 16, which also has a second face surface 26 spaced from the first face surface 24. Although less desirable than molding or casting the body portion 16 around the pins 20, the body portion 16 may be preformed without the pins 20, after which the pins 20 are inserted into prearranged holes and adhesively bonded to the body portion 16.

Each of the pins 20 have a first portion 28 completely encapsulated within the body 16 and a respective one of the sheaths 22, an exposed second portion 30 extending outwardly from a distal end of the sheath 22, and an exposed third portion 32 extending outwardly from the second face surface 26 of the body 16. The outer surface of the first, or encapsulated, portion 28 of the pins 20 preferably have a plurality of inwardly extending annular grooves to aid in the retention of the pins 20 in the body 16 and to improve sealing of the body 16 and sheath 22 around each of the pins 20. The third portion 32 of the pins 20 preferably have a socket formed therein for receiving the pin end of an insertable/removable solder lug that is soldered to a wire conductor (not shown). Alternatively, although less desirable from a field repair aspect, the solder lug may be directly formed on the outer end of the pin 20. For the sake of clarity, only the first and second portions of two of the pins 20, and their respective sheaths 22, are shown in FIG. 1.

The body portion 18 of the female member 14 has a first face surface 34, a second face surface 36 spaced from the first face surface 34, and a plurality of integrally formed sheaths 38 extending outwardly from the first face surface

34. The female member 14 also includes a plurality of electrically conductive sockets 40 that are arranged in the same predetermined pattern as the pins 20. Each of the sockets 40 are shaped to receive substantially all of the exposed second portion 30 of the pins 20 and grip the pins so that they are maintained in electrically conductive contact with the socket 40. In the preferred embodiment of the present invention, the pin receiving portions of the sockets 40 are shaped so that it has a depth slightly greater than the length of the exposed first portion 28 of the pins 20 to assure that the pins will not "bottom out" in the socket. Also, it is desirable that the end of the sheaths 22,38 surrounding the pins and sockets be slightly spaced apart to preclude potential wear or damage to the sheaths.

Each of the sockets 40 have a first portion 42 in which the outer perimeter of the socket is completely encapsulated within the body 18 and a respective one of the sheaths 38 of the female member 14, and a second portion 44 that extends outwardly from the second face surface 36 of the body 18. Preferably, a plurality of annular grooves are provided along at least a portion of the length of the outer surface of the sockets 40 to assure retention of the socket in the body 18 and enhance sealing between the socket 40 and the body 18. The second portion 44 of the sockets 40 preferably have a solder lug formed on an outer end for attachment of a wire conductor (not shown).

The body portion 18 and the sheaths 38 of the female member 14 are desirably simultaneously formed by injection molding, compression or transfer molding, casting, or preformed and adhesively joined with the sockets 40, in the manner described above with respect to the body portion 16 of the male member 12.

The electrical connector 10 embodying the present invention also has a coupling member 46 that is preferably formed of an injection moldable, resiliently compressible and electrically nonconductive material such as thermoplastic rubber. In particular, it has been found that a blend of polyethylene and neoprene rubber, provides the resilience and compressibility desirable for sealing around the sheaths as described below in more detail. Preferably, after curing, the coupling member 46 has a hardness of from about 40 to about 70 durometer as measured by the Shore A scale.

However, if the body portions 16,18 of the male and female members 12,14 are formed of relatively soft elastomeric materials, the coupling member 46 may be formed of a rigid nonconductive material. This combination of soft body members and hard coupling materials provides somewhat less sealing between the internal passageways 52 in the coupling member 46 (described below) and the respective sheaths 22,38 of the male and female body members 12,14.

Alternatively, the coupling member 46 may be advantageously formed of two separate materials. In the alternative construction, the coupling member 46 has a body portion formed of a relatively soft, resiliently compressible material, such as the above described blend of polyethylene and neoprene rubber, and a thin externally disposed casing formed of a flexible nonconductive material having a hardness greater than that of the body portion. The casing is disposed about the circumferential surface areas of the body portion and may extend over one, or both, of the ends of the coupling member. Desirably, the casing is formed of a material such as high density polyethylene that, during molding, is self-bonding to the body portion. Other suitable self-bonding materials include polyurethane having a hardness from about 40 to about 70 durometer (Shore A scale) for the body portion and a harder, glass filled polyurethane for

the casing. In a preferred embodiment of the alternative construction of the coupling member 46, the casing has a thickness of about 0.050 in (0.13 mm) in the areas surrounding the cylindrical peripheral surface of the body portion, and a thickness of about 0.100 in (0.25 mm) in the radial areas over, or adjacent, the end faces.

The coupling member 46 has a first face surface 48 that is shaped to abut the first face surface 24 of the male member 12, and a second face surface 50 that is shaped to enable it to abut the first face surface 34 of the female member 14.

The coupling member 46 also has a plurality of passageways 52 extending between the first and second face surfaces 48,50 of the coupling 46. The passageways 52 are arranged in the same predetermined pattern as the pins 20 and the sockets 40. It is also desirable that the coupling member 46 have a locator hole 54 adapted to receive a locator pin 56, preferably provided on the female member 14, to aid radial orientation of the coupling 46 when connecting the components together. In the alternative arrangement of the coupling member, a key may be provided on an external circumferential surface of the coupling member 46, and conveniently formed of the same relatively hard material as the casing. The key, being formed of the relatively hard material, is capable of being effortlessly inserted into a keyway, described below, for relative orientation and alignment with a mating member.

Each of the passageways 52 have an internal wall surface that is shaped to receive and completely surround each of the sheaths 22,38 on the body portions 16,18 of the male and female members 12,14. In arid above ground applications where water or moisture sealing is not required, the internal wall surfaces may advantageously have a smooth cylindrical surface with an internal diameter substantially the same as, or even slightly greater than, the external diameter of the sheaths 20,40.

In underwater uses however, it is desirable to provide a tight waterproof seal about the sheaths 20,40. As described above with respect to the preferred embodiment of the present invention, the body portions 16,18 and sheaths 22,38 of the male and female members 12,14 are desirably formed of a rigid material and the coupling member 46 formed of a resiliently compressible elastomer. Each of the passageways 52 in the coupling member 46 of the preferred embodiment have a generally circular cross sectional shape in which at least one, and desirably a plurality of, annular alternating grooves 58 and ridges 60 are formed. The ridges 60 preferably have an internal diameter slightly less than the diameter of the sheaths 22,38 so that, when the sheaths are inserted into the passageways 52, each of the ridges 60 form a lip, or O-ring type, seal about the circumference of each sheath. Importantly, when the connector 10 is mated, or connected, underwater, the ridges 60 push water away from the pin-socket connection. It has also been found that if, after initial connection of the components, the components are subsequently slightly separated, e.g., moved apart about 1/4 inch (0.64 cm), and then rejoined, the ridges coact to provide a pumping action that further clears water from the pin-socket joint.

In an actual construction of the connector 10 embodying the present invention, each of the sheaths 22,38 have an external diameter of 0.200 inches (0.079 cm), and each of the ridges 60 have a diameter of 0.150 inches (0.059 cm). The annular grooves 58 between the ridges 60 in the passageways 52 have a diameter of 0.205 inches (0.081 cm) which is slightly greater than the external diameter of the sheaths 22,38.

If, as suggested in one of the above described alternative constructions, the coupling member 46 is formed of a rigid material, and the respective body portions 16,18 and sheaths 22,38 of the male and female members 12,14 formed of a resiliently compressible elastomeric material, the ridges 60 may be advantageously disposed on the exterior surface of the sheaths 22,38.

In the electrical connector 10 embodying the present invention, it can be readily seen that underwater sealing of the electrical connection between a pin 20 and a socket 40 is not dependent upon forming a face seal between adjacently disposed face surfaces of the coupling member 46 and either the male or the female member 12,14. Importantly, because underwater sealing of the electrical connection is provided by the internally disposed ridges 60 in each of the passageways 52, the application of an essentially isostatic pressure, such as that applied by subsurface water pressure, will compress an outer circumferential surface 62 of the coupling 46 when formed of an elastomeric material, and thereby increase the sealing pressure applied by each of the internally disposed ridges 60 against each of the sheaths 22,38. Thus, when the coupling member 46 is formed of a resiliently compressible elastomeric material, the sealing pressure imposed by the passageways 52 about each of the sheaths 22,38 will increase in response to increased pressure on the outer circumferential surface 62, even if the sheaths 22,38 are formed of a somewhat softer material than the coupling 46.

If the coupling member 46 is formed of a rigid material as suggested in an above described alternative embodiment of the present invention, an increase in isostatic pressure will not result in additional compression of the passageways 52. Accordingly, when used with a rigid coupling member 46, the electrical connector 10 will be limited to use in relatively shallow water depths, e.g., up to about 125 feet. Thus, it can be seen that, depending upon intended end use, the electrical connector 10 embodying the present invention may be constructed with either rigid or resiliently compressible male and female body members 16,18, and either a resiliently compressible or rigid coupling member 46. The only combination of rigid and compressible components that would not provide a waterproof connector is when all of the components are formed of rigid materials.

As discussed above, if sealing against moisture or water is not required, such as in dry desert applications, it is desirable to form a single smooth cylindrical wall in the passageway 52 that is somewhat greater than the external diameter of the sheaths 22,38. For example, in the above described actual construction in which the external diameter of the sheaths was 0.200 inches (0.079 cm) the internal passageways 52 would preferably be formed to a diameter of, for example, about 0.210 inches (0.083 cm).

Thus, it can be seen that by simply changing the coupling member 46, i.e., selecting a coupling member having either smooth wall or ridged wall passageways, the connector 10 can be adapted for use in applications having very different environmental requirements. Also, if the pins and sockets 20,40 are arranged in a symmetrical pattern, the coupling member 46 is reversible, i.e., it can be installed with either face 48,50 abutting either the male member 12 or the female member 14.

In yet another embodiment, the electrical connector 10 may have pins 20 and sockets 40 disposed in the same body member. For example, each half of the connector may be arranged so that one half of the contacts are male members, and the remaining half female members. In this

arrangement, the coupling member may be split longitudinally to form two components, one for each group of mating male-female members.

In the above described actual construction, the sheaths 22 surrounding the pins 20 have a length of 0.581 inch (1.48 cm) and the sheaths 38 surrounding the sockets 40 have a length of 0.400 inch (1.02 cm). Thus, the total combined length of the sheaths 22,38 is 0.981 inches (2.49 cm). The length of the coupling member 46, and accordingly the length of the passageways 52 in the coupling member is 1.081 inches (2.75 cm). Therefore, upon assembly, as described below in additional detail, there will be a gap, or "stand-off distance", of about 0.100 inch (0.25 cm) between the ends of the sheaths 22,38.

Importantly, the length of the sheaths 22 surrounding the pins 20 is longer than the length of the sheaths 38 formed around the sockets 40. Therefore, there is more contact surface between the pin sheaths 22 and the internal surfaces of the passageways 52 in the coupling 46 than between the socket sheaths 38 and the passageways. Because of the longer contact area, the coupling member 46 will, upon disassembly, be captured by and retained with the male member 12. Also, because each of the passageways 52 is longer than the combined length of the pin sheath and the exposed pin portion 30, each of the exposed pin portions 30 are completely surrounded and protects the pins 20 from damage during handling or repair operations.

Preferably, the electrical connector 10 includes a means 64 for maintaining the first and second face surfaces 48,50 of the coupling 46 in respective abutting contact with the first face surfaces 24,34 of the male and female members 12,14. In the illustrative embodiment of the present invention shown in FIGS. 1 and 2, the means 64 includes a female adaptor member 66 having internal threads 68 which are threadably engageable with a plurality of threads 70 provided on a circumferential surface of the female member 14. The female adaptor 66 secures the female member 14 in a fixed mounted position against a wall or case surface by drawing an annular shoulder on the circumference of the female member against the wall in response to tightening the threaded connection between the adaptor 66 and female member 14.

In similar fashion, a male adaptor member 72 has internal threads 74, formed adjacent one end, which are adapted to threadably engage a plurality of external threads 76 formed on the male member 12. The male adaptor 76 preferably has a provision for receiving a cable containing a plurality of wires in the other end and for sealing the entrance of the cable into the male adaptor 72. Alternatively, although less desirable for field repairs, the cable may be directly molded to the male member 12, thereby forming a single integrated component.

If the body portion of either the male member or the female member 14 is formed of a relatively soft elastomeric material, in certain configurations it may be desirable to provide a harder casing about the member. Suitable, mutually compatible, body and casing materials were described above with respect to an alternate embodiment of the coupling member 46. The external threads 70,76 on the respective female and male members 14,12 may advantageously be formed of the same harder material as the casing.

In the preferred embodiment of the present invention, the means 64 for maintaining the coupling 46 and the male and female members 12,14 in their respective abutting relationships also includes a rigid outer shell 78 that has a plurality of internal threads 80 disposed at one end of the shell that are

adapted to mate with a plurality of external threads 82 provided on the female adaptor member 66. The shell 78 also has an internally disposed groove 84 adjacent the other end which is adapted to receive a snap ring 86 that, when the connector 10 is assembled as shown in FIG. 2, abuts a shoulder 88 formed on the outer surface of the male adaptor member 72. It is also desirable that the outer shell 78 have a plurality of open slots 90 extending through the periphery of the shell. The slots 90 advantageously provide an aid to gripping and turning the shell during assembly or disassembly of the connector, and additionally provide an important self cleaning action. For these purposes, it is even desirable that at least part of the threaded portion of the outer shell 78 also have open slots 90 through the shell.

Alternatively, the means 64 for maintaining the first and second face surfaces 48,50 of the coupling member 46 in respective abutting contact with the respective first face surfaces 24,34 of male and female members 12,14, may comprise one or more shell or retention members that mechanically interact directly with a predefined shoulder or other surface to positively fix the respective position of the element components.

Preferably the female adaptor member 66, the male adaptor member 72, and the shell 78 are all constructed of a rigid plastic material, such as fiberglass filled polyurethane, that is electrically nonconductive, resistant to corrosion, and easily formable by conventional molding techniques. Furthermore, if the coupling member 46 is constructed with an external key, a preselected one, or both, of the adaptor members may have a mating keyway formed in the internal bore of the respective adaptor.

The electrical connector 10 embodying the preferred arrangement of the present invention is assembled, as shown in FIG. 2, by first inserting the female member 14 through one side of an aperture 92 in a data box or control panel, with a shoulder of the female member having an o-ring seal disposed therein in contact with the panel. The female adaptor member 66 is then threaded onto the female member 14 and tightened against the mounting wall or panel. This effectively locks the female member 14 in place with respect to the fixed wall surface.

The elastomeric coupling member 46 is then inserted over the pins 20 and the sheaths 22 of the male member 12. Next, while not entirely necessary because of the below described subsequent drawing of the element together, the coupling member 46 is desirably pushed onto the male member 12 until the second face surface 48 of the coupling member is in abutting contact with the face surface 24 of the body member 16.

The male adaptor member 72 is then joined with the assembled coupling and male member 46,12 by threading the external threads 76 on the male member 12 into the internal threads 74 in the male adaptor member 72. Prior to this last step, unless already connected, the individual lead wires from a line cable assembly are attached to the ends, i.e., the third portion 32, of the pins 20.

The assembled coupling member 46, male member with wires attached, and male adaptor member 72 are then inserted, as a unit, through the left end (as viewed in FIGS. 1 and 2) of the outer shell 78 to a position at which the shoulder 88 on the male adaptor member 72 passes to the right of the groove 84 in the outer shell 78. The snap ring 86 is then inserted into the groove 84 which coacts with the shoulder 84 to prevent leftward movement of the male adaptor member 72 and the components previously assembled therewith.

The coupling member 46, male member 12 and the male adaptor 72 are rotated, if needed, to align the locator hole 54 in the coupling member with the locator pin 56. In the alternative constructions of the coupling member 46, the assembly may be rotated to align the key with the keyway formed in the female adaptor member. The outer shell 78 is then moved into contact with the female adaptor member 66 and rotated to engage the internal threads 80 on the outer shell with the external threads 82 on the female adaptor member. Tightening the outer shell 78 against the female adaptor member 66 will draw the male and female members 12,14, toward the coupling member 46 that is positioned between the male and female members. Thus, after tightening the outer shell 78 onto the female adaptor member 66, the second face surface 50 of the coupling member 46 and the first face surface 34 of the female member 14, and the first face surface 24 of the male member 12 and the first face surface 48 of the coupling member 46, are in respective abutting contact with each other. After assembly, the exposed pins 20 of the male member 12 captured by, and maintained in electrical contact with, the sockets 40, and the sheaths 22,38 of both the male and female members 12,14, are effectively sealed by the passageways 52 of the resiliently compressible coupling member 46.

Desirably, as described above, the length of the sheaths 22 of the male member 12 are longer than sheaths 38 of the female member 14. Upon disassembly, the inwardly extending shoulder 94 formed on the outer shell 78 will pull the coupling member 46 away from of the female member 14. Also, as a result of the greater contact area between the male sheath 22 and the interior surface of the passageways 52, the coupling member 46 is captured by, and retained on, the male member 12. This makes subsequent reassembly, particularly underwater, easier because it eliminates the need to separately orient and install the coupling member 46 on the male member 12. Also, as described above, the coupling member 46 extends beyond the ends of the pins 20 of the male member 12, thereby protecting the pins when the connector 10 is in an uncoupled state.

The assembled electrical connector 10 is easily disassembled, in the field, by reversal of the above described assembly procedure. Thus, as described with respect to the construction of the sheaths 23,38 and the passageways 52, it can be seen that the connector 10 can be disassembled and reassembled for service, even underwater if necessary. The coupling member 46 is immediately field replaceable. Also, if they are not part of an assembly molded as a unit with their respective cables, the male and female member 12,14 may be individually replaced by removing the solder tabs from the socket connection provided on the ends of the pins 20 and the sockets 40.

In another embodiment, the electrical connector 10 is used as a line connector, i.e., without one of the members being mounted in a box or to a wall. Other applications, changes and modifications of the above described electrical connector may similarly be made without departing from the spirit and scope of the present invention.

Thus, it can be seen that the electrical connector 10 embodying the present invention advantageously provides protective sheaths 22,38 around both the pins 20 of the male member 12 and the sockets 40 of the female member 38. The sheaths 22,38 around both electrical contact elements provide increased bonding surface area to assure a tight waterproof seal with the surrounding body. The sheaths 22,38 also provide increased structural support for both contact elements, and increases the electrical signal crossover distance between adjacently disposed conductors thereby improving the electrical isolation of the components.

Industrial Applicability

The present invention is particularly useful in applications that require sealing of electrical connections against adverse environmental conditions such as underwater data acquisition and transmission systems, subsurface or ground level instruments subjected to adverse operational and atmospheric environments such as seismic exploration applications, and other uses where it is desirable to protect the electrical contact portions of the connector.

All of the electrical contact elements, i.e., both the pins and their mating sockets, are surrounded by a protective sheath that provides increased bonding surface between the respective contact element and its supporting nonconductive material. The protective sheath also improves the electrical separation of the conductive elements.

The present invention, because of the coupling provided between components housing the electrical contact elements, also has important uses in applications where the electrical connector is subjected to high vibration or shock, such as in rough terrain vehicles and earthmoving machines.

Importantly, the electrical connector 10 embodying the present invention comprises individual components that can be disassembled, the coupling member replaced, and the connector reassembled, even underwater, without the need of special tools or repair facilities. Thus, the electrical connector described above and defined by the claims is particularly suited for use in remote geographical locations where repair facilities are not readily available.

Other aspects, features and advantages of the present invention can be obtained from a study of this disclosure together with the appended claims.

What is claimed is:

1. An electrical connector, comprising:

a male member having a body formed of an electrically nonconductive material and a plurality of electrically conductive pins arranged in a predetermined pattern in said body, said body having a first face surface, a second face surface, and a plurality of sheaths extending outwardly from said first face surface, and each of said electrically conductive pins having a first portion completely encapsulated within the body and a respective one of said sheaths of said male member, a second portion extending outwardly from an outer end of the sheath respectively imbedding the first portion of said pins, and a third portion extending outwardly from the second face surface of the body of said male member, each of said third portions being connectable to an electrical wire conductor;

a female member having a body formed of an electrically nonconductive material and a plurality of electrically conductive sockets arranged in said predetermined pattern in the body of said female member and adapted to receive the second portion of a respective one of the pins of said male member and maintain said respective pin in electrically conductive contact with the socket, said body of the female member having a first face surface, a second face surface, and a plurality of sheaths extending outwardly from said first face surface, and each of said electrically conductive sockets having a first portion completely encapsulated within the body and a respective one of the sheaths of said female member and a second portion extending outwardly from the second face surface of the body of said female member, said second portion of each of the sockets being connectable to an electrical wire conductor; and,

a coupling member comprising a body portion formed of an electrically nonconductive material having a prede-

terminated hardness and having a first face surface abutable with the first face surface of said male member, a second face surface abutable with the first face surface of said female member, and a plurality of internally disposed passageways extending between said first and second face surfaces of the coupling member, said passageways being arranged in said predetermined pattern and having an internal wall shape adapted to receive and completely surround each of the sheaths of said male and said female members.

2. An electrical connector, as set forth in claim 1, wherein at least one of said male body portion and said female body portion is formed of a material having a hardness greater than the predetermined hardness of said coupling member.

3. An electrical connector, as set forth in claim 1, wherein at least one of said male body portion and said female body portion is formed of a material having a hardness less than the predetermined hardness of said coupling member.

4. An electrical connector, as set forth in claim 1, wherein said male body portion, said female body portion, and said coupling member are all formed of a resiliently compressible material having a hardness of from about 40 to about 70 durometer as measured with reference to the Shore A scale.

5. An electrical connector, as set forth in claim 1, wherein the body portions of said male and female members are formed of a material selected from the group consisting of urethane, polyphenyl sulfone, polyaryl sulfone, polychlorotrifluoroethylene (PCTFE), phenylene ether/phenylene oxide, polyester, alkyd encapsulating putty, granular and glass reinforced alkyds, fiber filled diallyl phthalates, high density polyethylene, rigid cast or molded epoxies, polyurethane rubber, standard electrical glass, low loss electrical borosilicate glass, and electrical ceramics.

6. An electrical connector, as set forth in claim 1, wherein said coupling member includes an external casing disposed about the periphery of the body portion, said external casing being formed of a flexible nonconductive material having a hardness greater than that of the body portion and forming a unitary structure with said body portion.

7. An electrical connector, comprising: a male member formed of an electrically nonconductive material and having a face surface and a plurality of sheaths extending outwardly from said face surface, and a plurality of electrically conductive pins each having a portion encapsulated by a respective one of said sheaths;

a female member formed of an electrically nonconductive material and having a face surface and a plurality of

sheaths extending outwardly from said face surface, and a plurality of electrically conductive sockets each of which are encapsulated by a respective one of said sheaths;

a coupling member having a body portion formed of a resiliently compressible, electrically nonconductive material having a predetermined hardness, a pair of spaced apart end faces, and a plurality of internal passageways adapted to sealably receive the sheaths of said male and female members therein, said coupling member being interposed said male and female members with each one of the end faces of said coupling member in abutting contact with a respective end face surface of the male and female member, said internal passageways of the coupling member being radially reduced in response to applying an essentially isostatic pressure on said external casing of the coupling member.

8. An electrical connector, as set forth in claim 7, wherein at least one of said male body portion and said female body portion is formed of a material having a hardness greater than the predetermined hardness of said coupling member.

9. An electrical connector, as set forth in claim 7, wherein said male body portion, said female body portion, and said coupling member are all formed of a resiliently compressible material having a hardness of from about 40 to about 70 durometer as measured with reference to the Shore A scale.

10. An electrical connector, as set forth in claim 7, wherein the body portions of said male and female members are formed of a material selected from the group consisting of urethane, polyphenyl sulfone, polyaryl sulfone, polychlorotrifluoroethylene (PCTFE), phenylene ether/phenylene oxide, polyester, alkyd encapsulating putty, granular and glass reinforced alkyds, fiber filled diallyl phthalates, high density polyethylene, rigid cast or molded epoxies, polyurethane rubber, standard electrical glass, low loss electrical borosilicate glass, and electrical ceramics.

11. A electrical connector, as set forth in claim 7, wherein said coupling member includes an external casing formed of a flexible nonconductive material having a hardness greater than that of the body portion, said casing being disposed about the periphery of the body portion and forming a unitary structure with said body portion.

* * * * *