

LIQUID-EJECTING BEARINGS FOR TRANSPORT OF GLASS SHEETS

RELATED APPLICATIONS

[0001] This application claims the benefit of U.S. Provisional Application No. 61/100,486, filed 09/26/2008, entitled, "Liquid-Ejecting Bearings for Transport of Glass Sheets" and of U.S. Application No. 12/428,672, filed on 4/23/2009, entitled, "Liquid-Ejecting Bearings for Transport of Glass Sheets."

FIELD

[0002] This invention relates to methods and apparatus for transporting glass sheets, e.g., the glass sheets used as substrates in the manufacture of liquid crystal displays (LCDs). More particular, the invention relates to transporting glass sheets without mechanical contact with the sheet's major surfaces.

BACKGROUND

[0003] The process of manufacturing substrates for liquid crystal displays includes a number of steps in which glass sheets need to be supported and conveyed without damage to the sheet's major surfaces and, in particular, without damage to the sheet's "quality" surface upon which components of the display, e.g., thin film transistors and color filters, will be formed. For example, during the substrate manufacturing process, sheets need to be cut to size, edge ground, washed, and packaged and shipped or otherwise provided to the display manufacturer. Not only does the sheet need to be transported between the stations at which these steps are performed, but in some cases, the sheet also needs to be turned (rotated) during a step.

[0004] As sheet size has grown from a length of 1 meter to greater than 2 meters without a corresponding increase in sheet thickness, the lateral stiffness of the sheet has significantly decreased. At the same time, transport speed requirements have either remained constant or increased. Thus, the problem of transporting glass substrates for liquid crystal displays as it exists today can be described as trying to move a large glass sheet whose mechanical properties are not unlike those of tissue paper at high speed without touching the major surfaces of the sheet.

[0005] The present invention addresses this problem by providing non-contact bearings which eject a liquid (e.g., water) against at least one of the sheet's major surfaces in patterns and at rates which stabilize the sheet and thus reduce the sheet's transverse movement during transport, i.e., the sheet's movement in a direction orthogonal to the direction of transport. In this way, large and thin sheets of glass can be safely transported at high speeds.

SUMMARY

[0006] In accordance with a first aspect, the invention provides a method for conveying a glass sheet (13) in a substantially vertical orientation including:

- (a) providing a moving conveyor (2) configured to contact an edge of the sheet (13) and move the sheet (13) at a conveyance speed;
- (b) providing a non-contact bearing (3) configured to eject liquid (40) against a portion of a major surface of the sheet (13); and
- (c) contacting the edge of the sheet (13) with the moving conveyor (2) and moving the sheet (13) at the conveyance speed while ejecting liquid (40) from the non-contact bearing (3) against the portion of the major surface of the sheet (13);

wherein the non-contact bearing (3) includes a plurality of orifices (22) which eject the liquid (40) against the portion of the major surface of the sheet (13) and the method has at least one of the following characteristics:

- (i) the rate at which the liquid (40) is ejected from the non-contact bearing (3) averaged over the orifices (22) is in the range of 100-800 milliliters/minute/orifice; or
- (ii) the orifices' (22) average horizontal pitch (P) is in the range of 20-55 millimeters; or
- (iii) the orifices' (22) average size (D_0) is in the range of 1.0-4.5 millimeters.

[0007] In accordance with a second aspect, the invention provides a method for conveying a glass sheet (13) in a substantially vertical orientation including:

- (a) providing a moving conveyor (2) configured to contact an edge of the sheet (13) and move the sheet (13) at a conveyance speed;
- (b) ejecting a liquid (40) against an upper portion of a major surface of the glass sheet (13); and
- (c) ejecting a liquid (40) against a lower portion of the major surface of the glass sheet (13);

wherein:

- (i) the upper portion is vertically above the lower portion; and
- (ii) the amount of liquid (40) ejected against the upper portion per unit time is more than the amount of liquid (40) ejected against the lower portion per unit time.

[0008] In accordance with a third aspect, the invention provides a non-contact bearing (3) for use in transporting a glass sheet (13), the bearing (3) having a front surface (20) which has a plurality of orifices (22), the front surface (20) facing the glass sheet (13) and the orifices (22) ejecting liquid (40) towards a major surface of the glass sheet (13) during use of the bearing (3), wherein:

- (a) the orifices (22) are distributed on the front surface (20) to form at least one row (23,24,25) that is oriented horizontally during use of the bearing (3); and
- (b) the orifices (22) have an average horizontal pitch P which satisfies the relationship:

$$20 \leq P \leq 55,$$

where P is in millimeters.

[0009] The reference numbers used in the above summaries of the various aspects of the invention are only for the convenience of the reader and are not intended to and should not be interpreted as limiting the scope of the invention. More generally, it is to be understood that both the foregoing general description and the following detailed description are merely exemplary of the invention and are intended to provide an overview or framework for understanding the nature and character of the invention.

[0010] Additional features and advantages of the invention are set forth in the detailed description which follows, and in part will be readily apparent to those skilled in the art from that description or recognized by practicing the invention as described herein. The accompanying drawings are included to provide a further understanding of the invention, and are incorporated in and constitute a part of this specification. It is to be understood that the various features of the invention disclosed in this specification and in the drawings can be used in any and all combinations.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] FIGS. 1 and 2 are schematic drawings of conveying apparatus for a glass sheet employing an array of non-contact, liquid-ejecting bearings. FIG. 1 is a front view and FIG. 2 is a side view.

[0012] FIGS. 3 through 7 show calculated plots of the pressure distribution produced on a glass sheet by the flow of liquid out of an orifice for various orifice-to-sheet spacings and liquid flow rates. Table 1 sets forth the particular parameters used for each of FIGS. 3 through 7.

[0013] FIGS. 8 and 9 are schematic drawings of apparatus used in testing the effects of various parameters on the conveyance of glass sheets using non-contact, liquid-ejecting bearings. FIG. 8 is a front view and FIG. 9 is a side view.

[0014] FIG. 10 shows the front face of a non-contact, liquid-ejecting bearing.

[0015] FIG. 11 is a plot of pressure/orifice in kilopascals (kPa) at the surface of a glass sheet (y-axis) versus spacing in millimeters (mm) between the glass sheet and the front face of a non-contact, liquid-ejecting bearing (x-axis). The shaded area of this figure illustrates a representative operating window for use of the bearing.

[0016] FIG. 12 is a plot of pressure/orifice in kilopascals (kPa) at the surface of a glass sheet (y-axis) versus spacing in millimeters (mm) between the glass sheet and the front face of a non-contact, liquid-ejecting bearing (x-axis) for average horizontal pitches of 15, 30, 43, and 65 millimeters.

[0017] FIG. 13 is a plot of pressure/orifice in kilopascals (kPa) at the surface of a glass sheet (y-axis) versus spacing in millimeters (mm) between the glass sheet and the front face of a non-contact, liquid-ejecting bearing (x-axis) for average orifice sizes of 0.5, 1.4, 3.0, and 5.0 millimeters.

[0018] FIG. 14 is a plot of pressure/orifice in kilopascals (kPa) at the surface of a glass sheet (y-axis) versus spacing in millimeters (mm) between the glass sheet and the front face of a non-contact, liquid-ejecting bearing (x-axis) for average flow rates of 80, 190, 350, and 900 milliliters/minute/orifice.

[0019] FIG. 15 is a schematic diagram illustrating interaction between individual bearings of an array of non-contact, liquid-ejecting bearings.

[0020] FIG. 16 is a plot of the spacing in millimeters (mm) between a glass sheet and the front face of a non-contact, liquid-ejecting bearing (y-axis) versus average flow rate in milliliters/minute/orifice through the lower of two non-contact, liquid-ejecting bearings (x-axis) for average flow rates of zero and 200 milliliters/minute/orifice through the upper of the two bearings.

[0021] Detailed Description of the Preferred Embodiments

[0022] As discussed above, non-contact, liquid-ejecting bearings for transporting glass sheets in a vertical or near vertical orientation are provided. The bearing ejects (dispenses) a liquid (e.g., water) against a portion of a major surface of the glass sheet. The liquid is preferably water, although other liquids may be used if desired. The liquid may include one or more additives, such as a biocide to prevent bacterial growth in cases where recycled water is used.

[0023] The glass sheet is preferably suitable for use as a substrate in the manufacture of flat panel displays, such as LCD displays. At present, the largest substrates being provided to flat panel display manufacturers are known as "Gen 10" substrates and have dimensions of 2850 mm x 3050 mm x 0.7 mm. The non-contact bearings disclosed herein can be used with these substrates, as well as with larger substrates that may be developed in the future and smaller substrates which have been developed in the past.

[0024] FIG. 1 shows a representative embodiment of apparatus 10 for conveying a glass sheet 13 using non-contact, liquid-ejecting bearings 3. As shown in this figure, an array of bearings 3 are carried by supports 31. The supports, in turn, are carried by platform 49 which may include casters 7 for transporting the apparatus to different locations in a manufacturing plant.

[0025] The number of non-contact bearings used in any particular application, as well as the lengths of the individual bearings, will depend on the size of the glass sheet being conveyed, e.g., in the case of Gen 10 substrates, a preferred embodiment employs an array having on the order of 10 bearings, each bearing having a length of 1.5 meters. More or less bearings, as well as longer and shorter bearings, can, of course, be used as desired. For example, more bearings can be used if a glass sheet is being transported in a portrait orientation as opposed to a landscape orientation. In general terms, the bearings preferably have a vertical height in the range of 50-150 millimeters and, when an array of bearings is used, the vertical spacing between the bearings is preferably in the range of 200-400 millimeters.

[0026] Supports 31 may hold the bearings in a vertical orientation as shown in FIG. 1 or at an angle displaced from vertical, e.g., at an angle in the range of 1-20° from vertical. (As used herein, the phrase "a substantially vertical orientation" means an orientation between 0° and 20° from vertical.) A vertical orientation is generally preferred.

[0027] As shown in FIG. 1, platform 49 includes conveyor 2, e.g., a V-shaped or U-shaped belt, for engaging the bottom edge of sheet 13. The conveyor is driven by, for example, an

electric motor (not shown) at the desired conveyance speed for the glass sheet. The conveyance speed will depend on the particular application. Preferably, the conveyance speed is equal to or greater than 15 meters/minute. For example, the conveyance speed may be in the range of 15 to 22 meters/minute, although slower speeds, e.g., speeds down to 7 meters/minute can be used if desired.

[0028] FIG. 10 shows the front surface (sheet facing surface) 20 of a representative liquid-ejecting bearing 3. As can be seen in this figure, the front surface includes a plurality of orifices 22 arranged, in this case, in three rows 23, 24, 25, with each row having the same number of orifices and with the orifices in adjacent rows being aligned vertically. Also, in this figure, the orifices have a uniform size (i.e., a uniform diameter D_0). This arrangement has been found to work successfully in practice, but numerous variations of the arrangement can be used if desired. As representative examples, the liquid-ejecting bearing can include more or less than three rows of orifices, the various rows can have different numbers of orifices, the orifices in adjacent rows can be staggered instead of vertically aligned, and the orifice sizes and the horizontal spacings (pitches) between some or all of the orifices can have different values. Also, the orifices need not be circular, in which case rather than being the orifice's diameter, the orifice's size is its maximum cross-sectional dimension.

[0029] During use, the orifices of bearing 3 are connected to a source of pressurized liquid. For example, a pump can be used to feed pressurized liquid from a reservoir to a plenum which distributes the liquid to the various orifices, e.g., through flexible tubes connected to the entrance ends of the orifices on the back surface of the bearing. A wide variety of commercially-available equipment, well known to those skilled in the art, can be used to provide the pressurized liquid. Alternatively, customized equipment can be constructed if desired.

[0030] The non-contact bearing(s) may be used on only one side of the sheet (see the solid lines in FIG. 2) or may be disposed on both sides of the sheet (see the solid and dashed lines in FIG. 2), depending upon the operation that is to be performed on the sheet. For example, the bearing(s) may be used for sheet support and conveyance during the cut-to-size, sheet rotation, sheet transport, sheet grinding, and sheet washing steps of the substrate manufacturing process. Examples of these and other applications for the bearing(s) can be found in U.S. Patent Application Publication No. US 2007/0271756, the contents of which are incorporated herein by reference in their entirety.

[0031] During use, the liquid emitted from the bearing(s) forms a membrane or film that supports the glass sheet so that it does not contact the front surface of the bearing(s). More particularly, the bearing(s) employ localized flow acceleration to create a negative pressure and hence a suction force to hold the glass sheet against the bearing during transport. FIGS. 3 through 7 illustrate the phenomena being employed.

[0032] In these figures, 100 is an area of high positive pressure (the impingement point of the liquid), 110 is a region of low negative pressure resulting from local acceleration of the liquid tangential to the glass surface, and 120 is a region of low positive pressure at the periphery. For purposes of illustration, the positive and negative regions shown in this figure were calculated for a single orifice without surrounding orifices. The area shown in each panel of FIGS. 3 through 7 is 50 mm x 50 mm. The calculations were performed using the commercially-available fluid dynamics program sold under the FLUENT trademark by ANSYS, Inc. (Canonsburg, PA). Other programs, including non-commercial programs, can, of course, be used to make the calculations shown in FIGS. 3 through 7, as well as the other calculations discussed herein.

[0033] FIGS. 3 through 7 show the distributions of positive and negative pressures for various combinations of 1) the spacing between the exit end of the orifice and the substrate's surface and 2) the flow rate through the orifice. Table 1 sets forth the specific values used, as well as the total integrated pressure (total force) at the surface of the substrate. A positive total force means that the sheet is being pushed away from the orifice (repelled from the bearing), while a negative total force means that the sheet is being pulled towards the orifice (attracted to the bearing).

[0034] As illustrated by FIGS. 3 through 7 and Table 1, positive and negative net forces can be achieved for various combinations of orifice-to-sheet spacings and flow rates. In particular, this data shows that positive forces (repulsive forces) can be achieved for close spacings and negative forces (attractive forces) for large spacings. As a result, an equilibrium point (equilibrium spacing) can be identified at which the sheet is neither pulled toward nor pushed away from the orifice. For orifice-to-sheet spacings smaller than the equilibrium spacing, the sheet is pushed away from the orifice back towards the equilibrium point. For orifice-to-sheet spacings greater than the equilibrium spacing, the sheet is pulled back towards the equilibrium point. In this way, the orifice-to-sheet spacing will hover around the equilibrium spacing.

[0035] In particular, the orifice-to-sheet spacing will hover around the equilibrium spacing as the sheet is transported past the orifice. Such transporting will cause the spacing between the sheet and the orifice to change over time as a result of 1) vibration of the moving sheet and/or 2) bowing, waviness, warp, or other non-flat surface characteristics of the sheet.

Because the net force applied to the sheet by the liquid ejected from the orifice changes sign at the equilibrium point, these variations in the orifice-to-sheet spacing can be accommodated by setting the orifice parameters, including the liquid flow rate, at values which produce an equilibrium point and attractive/repulsive forces on either side of the equilibrium point that can hold the sheet on the bearing notwithstanding the inevitable variations in the orifice-to-sheet spacing.

[0036] The data of FIGS. 3 through 7 is for a single orifice. In practice, a single orifice will not generate sufficient force to hold a moving glass sheet on a liquid-ejecting bearing.

Rather, an array of orifices may be used. More generally, arrays of liquid-ejecting bearings, e.g., two or more liquid-ejecting bearings arranged above one another (see FIGS. 1 and 2), are typically used in transporting glass sheets, especially as the size of the sheet increases. Each liquid-ejecting bearing will have its own array of orifices, which may be the same for all of the bearings or may differ between bearings, if desired.

[0037] The effects of an array of orifices on a glass sheet were found to be substantially more complex than the effects of a single orifice. Similarly, an array of liquid-ejecting bearings was found to exhibit more complex behavior than a single liquid-ejecting bearing. To study these effects, experiments were performed using equipment of the type shown schematically in FIGS. 8 and 9. In these figures, 13 is the glass sheet, 2 is a conveyor for the sheet, 3 is a liquid-ejecting bearing, 14 is a force transducer, 15 is a position sensor, 18 is a transducer/sensor support, 17 are leads to the transducers and sensors, and 16 is equipment for recording the output of the transducers and sensors.

[0038] FIG. 10 shows a representative liquid-ejecting bearing 3 used in the experiments. In addition to the structure of the bearing, the figure also shows parameters that were varied during the experiments, i.e., the average horizontal pitch parameter P , i.e., the average center-to-center spacing between orifices in the direction of motion of the glass sheet, and the average orifice size parameter, specifically, in this case, the average diameter D_0 of the orifices.

[0039] FIG. 11 is a plot of the average pressure in kilopascals (kPa) applied to a glass sheet by an orifice of a bearing's array of orifices versus the spacing in millimeters (mm) between

the front surface of the liquid-ejecting bearing and the glass sheet (or, equivalently, between the exit ends of the orifices and the glass sheet since the exit ends of the orifices are typically flush with the surface of the bearing). In this figure, as well as in FIGS. 12 through 14, positive pressures represent repulsion between the bearing and the sheet and negative pressures represent attraction. The hatched portion of this plot shows a representative operating window for the bearing, i.e., the portion of the pressure-versus-spacing curve over which high speed transport of glass sheets can be performed reliably using the bearing.

[0040] Using equipment of the type shown in FIGS. 8 and 9 and a bearing of the type shown in FIG. 10, pressure-versus-spacing curves were determined for a wide range of potential parameters. As a result of these experiments, it was found that the key parameters are: 1) the average horizontal pitch between orifices, 2) the average size of the orifices, and 3) the average flow rate through the orifices, where in each case, the averages are over all of the orifices of the bearing. It was further found that specific ranges of values for these parameters produced practical operating windows of the type shown in FIG. 11. FIGS. 12, 13, and 14 show representative data which illustrates the ranges for average horizontal pitch, average orifice size, and average flow rate, respectively.

[0041] As shown in FIG. 12, an average horizontal pitch of 15 millimeters (solid triangle data points) produced unacceptably large repulsive forces on the glass sheet as the sheet approached the surface of the bearing. Consequently, the sheet would tend to fly off of the bearing since the attractive forces were insufficient to restrain the sheet once it had, in effect, bounced off of the bearing as a result of an inward movement towards the bearing. On the other hand, an average horizontal pitch of 65 millimeters (x data points) produced insufficient repulsive force so that there would be no guarantee that the sheet would not be damaged during use as a result of contact with the bearing.

[0042] Both an average horizontal pitch of 43 millimeters (open square data points) and an average horizontal pitch of 30 millimeters (open diamond data points) produced desirable pressure-versus-spacing curves, with the 30 millimeter average horizontal pitch being somewhat better than the 43 millimeter value since the magnitudes of the repulsive pressures and at least some of the attractive pressures for the 30 millimeter pitch were larger than those of the 43 millimeter pitch. Based on this and similar data, it was determined that the average horizontal pitch should be in the range of 20 to 55 millimeters, preferably 25 to 50 millimeters, and more preferably 30 to 40 millimeters (e.g., approximately 35 millimeters), where, in each case, the end points of the ranges are included within the range.

[0043] FIG. 13 shows data for the average orifice size parameter. In this case, an average orifice size of 5 millimeters (solid triangular data points) was found to produce too small a repulsive pressure at small bearing to sheet spacings and an average orifice size of 0.5 millimeters (x data points) was found to produce too large a repulsive pressure.

[0044] Both an average orifice size of 3 millimeters (open square data points) and one of 1.4 millimeters (open diamond data points) produced desirable pressure-versus-spacing curves, with the 1.4 millimeter average orifice size being somewhat better than the 3 millimeter size since the magnitudes of both the repulsive and attractive pressures for the 1.4 millimeter average orifice size were larger than those of the 3 millimeter size. Based on this and similar data, it was determined that the average orifice size should be in the range of 1.0 to 4.5 millimeters, preferably 1.0 to 3.5 millimeters, and more preferably 1.25 to 2.25 millimeters, where, in each case, the end points of the ranges are included within the range.

[0045] FIG. 14 shows data for average flow rate. In this case, an average flow rate of 900 milliliters/minute/orifice (solid triangular data points, 14.3) was found to produce too large a repulsive pressure at small bearing to sheet spacings and an average flow rate of 80 milliliters/minute/orifice (x data points, 14.4) was found to produce too small a repulsive pressure.

[0046] Both an average flow rate of 350 milliliters/minute/orifice (open square data points, 14.2) and 190 milliliters/minute/orifice (open diamond data points, 14.1) produced desirable pressure-versus-spacing curves, with the 190 milliliters/minute/orifice average flow rate being somewhat better than the 350 milliliters/minute/orifice average flow rate since lower average flow rates mean less liquid consumption which, in turn, means smaller and thus less expensive equipment is needed to supply the liquid. Based on this and similar data, it was determined that the average flow rate should be in the range of 100 to 800 milliliters/minute/orifice, preferably 125 to 300 milliliters/minute/orifice, and more preferably 150 to 190 milliliters/minute/orifice, where, in each case, the end points of the ranges are included within the range.

[0047] Each of these three key parameters, i.e., average horizontal pitch, average orifice size, and average flow rate, provides benefits to the system and thus for some applications, only one or two of the parameters will be in the ranges discussed above. In general terms, the average flow rate parameter is most important, followed by the horizontal pitch and average orifice size parameters in that order.

[0048] For many applications, the average horizontal pitch, average orifice size, and average flow rate parameters are preferably all within the above designated ranges, more preferably, all within the above preferred ranges, and most preferably, all within the above more preferred ranges. In keeping with this approach, the data shown for each of FIGS. 12, 13, and 14 is for the "open diamond" parameter values of the other two figures. Thus, for FIG. 12, the average orifice size is 1.4 millimeters and the average flow rate is 190 milliliters/minute/orifice, while for FIG. 13, the average horizontal pitch is 30 millimeters and the average flow rate is 190 millimeters/minute/orifice, and for FIG. 14, the average horizontal pitch is 30 millimeters and the average orifice size is 1.4 millimeters.

[0049] In addition to the average horizontal pitch, average orifice size, and average flow rate parameters, the total force applied to a major surface of the sheet, i.e., the pressure integrated over the major surface, is preferably within the range of -0.6 Newtons to +0.6 Newtons, where the endpoints of the range are part of the range. The total force will vary over time as the distance between the sheet and the bearing changes, but preferably remains in the above range. The total force is preferably a measured value, but can also be a calculated value based on a simulation of the system using fluid dynamics software such as the FLUENT program discussed above. This total force range can serve as a useful guide in selecting the number, arrangement, sizes, and flow rates of the orifices. In particular, when choosing orifice flow rates, a rate which generates negative forces but not excessive total forces in view of the other parameters of the system (e.g., total number of orifices, orifice spacing, and orifice size) is preferred, i.e., a total force less than or equal to the upper limit of the above range is preferred.

[0050] The above ranges for the average horizontal pitch, average orifice size, and average flow rate parameters have been found to provide effective transport of glass sheets with controlled amounts of variation in the spacing between the glass sheet and the front surface of the bearing. In particular, when non-contact, liquid-ejecting bearings having an average flow rate in the range of 100 to 800 milliliters/minute/orifice, an average orifice size in the range of 1.0 to 4.5 millimeters, and an average horizontal pitch in the range of 20 to 55 millimeters, are tested at a conveyance speed of 15 meters/minute using a glass sheet whose modulus is 73 GPa and whose dimensions are 2 meters long, 2 meters high, and 0.7 millimeters thick, the time-averaged spacing between the sheet and the front face of the bearing at all points on the front face of the bearing is in the range of 500-1000 microns and the time-averaged peak-to-peak variation in the spacing at all points on the front face of the bearing is no greater than

100 microns. Such a small variation relative to the average spacing means that the likelihood of any part of the sheet contacting the bearing during transport of the sheet is negligible. It also means that the chances of the sheet becoming disconnected from the bearing is also negligible.

[0051] As noted above, not only are the phenomena more complex when multiple orifices are involved, but they are also more complex when multiple bearings are used in an array. FIGS. 15 and 16 illustrate the inter-bearing interaction that has been discovered.

[0052] In FIG. 15, three bearings 3U, 3M, and 3L eject liquid 40 against a glass sheet 13. As schematically illustrated by arrows 41, in practice, the liquid ejected from bearing 3U interacts with that ejected from bearing 3M, and the liquid ejected from bearing 3M (as well as some of the liquid ejected from bearing 3U) interacts with that ejected from bearing 3L. In particular, it has been found that for equal average flow rates for all three bearings, the spacing between glass sheet 13 and the bearing's front surface is greater for bearing 3M and bearing 3L than for bearing 3U, with the spacing for bearing 3L being the largest of them all. (Recall that because of its thinness, glass sheet 13 is highly flexible so that although bearings 3U, 3M, and 3L may be vertically aligned, the lower parts of the sheet can flex away from bearings 3M and 3L to create the larger spacing.)

[0053] FIG. 16 quantifies the effect for a two bearing system, e.g., bearings 3M and 3L in FIG. 15. The horizontal axis in FIG. 16 shows the average flow rate through bearing 3L, while the vertical axis plots the spacing between the front surface of bearing 3L and the glass sheet. The solid diamond data points show the spacing for zero flow through bearing 3M, i.e.,

$F_M = 0$. As shown, the spacing to the sheet increases as the average flow rate through the bearing 3L increases.

[0054] The open square data points show the effect of a 200 milliliters/minute/orifice average flow rate through bearing 3M. Again, the spacing between bearing 3L and the sheet increases with the average flow rate through bearing 3L, but all of the values are now shifted upward to larger spacings. Accordingly, to maintain substantially equal spacings between the glass sheet and all of the bearings in a bearing array, the operating parameters and/or physical properties of the bearings need to be different. In particular, the operating parameters and/or the physical properties of the bearings need to differ so that the amount of liquid ejected by the lower bearing is less than the amount of liquid ejected by the upper bearing. This can be accomplished in various ways.

[0055] For example, the average liquid flow rate for the lower bearing can be reduced. As one example, using the data of FIG. 16, the combination of a 200 milliliters/minute/orifice average flow rate through bearing 3M and a 150 milliliters/minute/orifice average flow rate through bearing 3L can be seen to produce substantially the same spacing between bearing 3L and the glass sheet as an average flow rate of 250 milliliters/minute/orifice through bearing 3L alone. Similar data can be generated for three or more active bearings, with the average flow rates through the lower bearings being reduced to produce relatively uniform bearing-to-sheet spacings at all bearings. (Note that for some applications, it may be desirable to have unequal spacings which can be achieved by adjusting the average flow rates of the various bearings in accordance with the present disclosure.)

[0056] As an alternative to using different flow rates, the physical properties of the bearings can be different. For example, the average horizontal pitch of the lower bearing can be made larger than that of the upper bearing and/or the average orifice size can be made smaller. For many applications, the physical properties approach may be preferable to the flow rate approach since it can avoid the need to individually control/monitor the flow of liquid through the individual bearings.

[0057] From the foregoing, it can be seen that non-contact, liquid-ejecting bearings have been provided which can successfully convey flexible glass sheets, e.g., LCD substrates, at high speeds, e.g., speeds of 15 meters/minute and above. To achieve this result, the operating parameters and physical properties of the bearing(s) satisfy one and preferably all of the following conditions: (a) the average flow rate from the bearing's orifices is in the range of 100-800 milliliters/minute/orifice; (b) the orifices' average horizontal pitch is in the range of 20-55 millimeters; and/or (c) the orifices' average size is in the range of 1.0-4.5 millimeters. By means of these conditions, the time-averaged, peak-to-peak variation in the spacing between a LCD substrate traveling at 15 meters/minute and the face of a liquid-ejecting bearing can be reduced to less than 100 microns, thus reducing the chances that the bearing will lose control of the substrate or that the substrate will hit the bearing.

[0058] A variety of modifications that do not depart from the scope and spirit of the invention will be evident to persons of ordinary skill in the art from the foregoing disclosure. The following claims are intended to cover the specific embodiments set forth herein as well as modifications, variations, and equivalents of those embodiments.

Table 1

FIG.	Spacing (mm)	Flow Rate (liters/min)	Total Force (Newtons)
3	0.3	0.68	+0.48
4	0.4	0.81	-0.30
5	0.7	1.00	-0.82
6	1.0	1.10	-0.55
7	1.3	1.13	-0.39

[0059] For example, any one or more of the following aspects may be embodied in the invention:

Aspect 1. A method for conveying a glass sheet in a substantially vertical orientation comprising:

- (a) providing a moving conveyor configured to contact an edge of the sheet and move the sheet at a conveyance speed;
- (b) providing a non-contact bearing configured to eject liquid against a portion of a major surface of the sheet; and
- (c) contacting the edge of the sheet with the moving conveyor and moving the sheet at the conveyance speed while ejecting liquid from the non-contact bearing against the portion of the major surface of the sheet;

wherein the non-contact bearing comprises a plurality of orifices which eject the liquid against the portion of the major surface of the sheet and the method has at least one of the following characteristics:

- (i) the rate at which the liquid is ejected from the non-contact bearing averaged over the orifices is in the range of 100-800 milliliters/minute/orifice; or
- (ii) the orifices' average horizontal pitch is in the range of 20-55 millimeters; or
- (iii) the orifices' average size is in the range of 1.0-4.5 millimeters.

Aspect 2. The method of Aspect 1 wherein the method has characteristic (i).

Aspect 3. The method of Aspect 2 wherein the rate at which the liquid is ejected from the non-contact bearing averaged over the orifices is in the range of 125-300 milliliters/minute/orifice.

Aspect 4. The method of Aspect 2 wherein the rate at which the liquid is ejected from the non-contact bearing averaged over the orifices is in the range of 150-190 milliliters/minute/orifice.

Aspect 5. The method of any one of Aspects 1-4 wherein the method has characteristic (ii).

Aspect 6. The method of Aspect 5 wherein the orifices' average horizontal pitch is in the range of 25-50 millimeters.

Aspect 7. The method of Aspect 5 wherein the orifices' average horizontal pitch is in the range of 30-40 millimeters.

Aspect 8. The method of any one of Aspects 1-7 wherein the method has characteristic (iii).

Aspect 9. The method of Aspect 8 wherein the orifices' average size is in the range of 1.0-3.5 millimeters.

Aspect 10. The method of Aspect 8 wherein the orifices' average size is in the range of 1.25-2.25 millimeters.

Aspect 11. The method of any one of Aspects 1-10 wherein the method has characteristics (i) and (ii)

Aspect 12. The method of any one of Aspects 1-10 wherein the method has characteristics (i) and (iii).

Aspect 13. The method of any one of Aspects 1-10 wherein the method has characteristics (i), (ii), and (iii).

Aspect 14. The method of any one of Aspects 1-13 wherein the method has the further characteristic that the total force applied to the major surface of the sheet is within the range of -0.6 Newtons to +0.6 Newtons.

Aspect 15. The method of any one of Aspects 1-14 wherein the method has the further characteristic that when conveying a glass sheet whose modulus is 73 GPa and whose dimensions are 2 meters long, 2 meters high, and 0.7 millimeters thick, the time-averaged spacing between the sheet and a front face of the bearing at all points on the front face is in the range of 500-1000 microns and the time-averaged peak-to-peak variation in the spacing at all points on the front face is no greater than 100 microns for a conveyance speed equal to 15 meters/minute.

Aspect 16. A method for conveying a glass sheet in a substantially vertical orientation comprising:

- (a) providing a moving conveyor configured to contact an edge of the sheet and move the sheet at a conveyance speed;
- (b) ejecting a liquid against an upper portion of a major surface of the glass sheet; and
- (c) ejecting a liquid against a lower portion of the major surface of the glass sheet; wherein:
 - (i) the upper portion is vertically above the lower portion; and
 - (ii) the amount of liquid ejected against the upper portion per unit time is more than the amount of liquid ejected against the lower portion per unit time.

Aspect 17. The method of Aspect 16 wherein:

- (a) the liquid is ejected against the upper portion using an upper non-contact bearing which comprises a plurality of orifices having an average horizontal pitch P_U ;
- (b) the liquid is ejected against the lower portion using a lower non-contact bearing which comprises a plurality of orifices having an average horizontal pitch P_L ; and
- (c) P_U and P_L satisfy the relationship:

$$P_L > P_U.$$

Aspect 18. The method of Aspect 17 wherein the upper non-contact bearing and the lower non-contact bearing are any two adjacent members of an array of non-contact bearings.

Aspect 19. A non-contact bearing for use in transporting a glass sheet comprising a front surface which has a plurality of orifices, the front surface facing the glass sheet and the orifices ejecting liquid towards a major surface of the glass sheet during use of the bearing, wherein:

- (a) the orifices are distributed on the front surface to form at least one row that is oriented horizontally during use of the bearing; and
- (b) the orifices have an average horizontal pitch P which satisfies the relationship:

$$20 \leq P \leq 55,$$

where P is in millimeters.

Aspect 20. The non-contact bearing of Aspect 19 wherein the orifices have an average size which is in the range of 1.0-4.5 millimeters.

What is claimed is:

1. A method for conveying a glass sheet in a substantially vertical orientation comprising:
 - (a) providing a moving conveyor configured to contact an edge of the sheet and move the sheet at a conveyance speed;
 - (b) providing a non-contact bearing configured to eject liquid against a portion of a major surface of the sheet; and
 - (c) contacting the edge of the sheet with the moving conveyor and moving the sheet at the conveyance speed while ejecting liquid from the non-contact bearing against the portion of the major surface of the sheet;
wherein the non-contact bearing comprises a plurality of orifices which eject the liquid against the portion of the major surface of the sheet and the method has at least one of the following characteristics:
 - (i) the rate at which the liquid is ejected from the non-contact bearing averaged over the orifices is in the range of 100-800 milliliters/minute/orifice; or
 - (ii) the orifices' average horizontal pitch is in the range of 20-55 millimeters; or
 - (iii) the orifices' average size is in the range of 1.0-4.5 millimeters.
2. The method of Claim 1 wherein:
if the method has characteristic (i), then the rate at which the liquid is ejected from the non-contact bearing averaged over the orifices is in the range of 125-300 milliliters/minute/orifice;
if the method has characteristic (ii), then the orifices' average horizontal pitch is in the range of 25-50 millimeters; and
if the method has characteristic (iii), then the orifices' average size is in the range of 1.0-3.5 millimeters.
3. The method of Claim 1 wherein:
if the method has the characteristic (i), then the rate at which the liquid is ejected from the non-contact bearing averaged over the orifices is in the range of 150-190 milliliters/minute/orifice;
if the method has the characteristic (ii), then the orifices' average horizontal pitch is in the range of 30-40 millimeters; and

if the method has the characteristic (iii), then the orifices' average size is in the range of 1.25-2.25 millimeters.

4. The method of any one of Claims 1-3 wherein the method has the further characteristic that when conveying a glass sheet whose modulus is 73 GPa and whose dimensions are 2 meters long, 2 meters high, and 0.7 millimeters thick, the time-averaged spacing between the sheet and a front face of the bearing at all points on the front face is in the range of 500-1000 microns and the time-averaged peak-to-peak variation in the spacing at all points on the front face is no greater than 100 microns for a conveyance speed equal to 15 meters/minute.

5. The method of any one of claims 1-3 further comprising:

- (c) ejecting a liquid against an upper portion of a major surface of the glass sheet; and
- (d) ejecting a liquid against a lower portion of the major surface of the glass sheet; wherein:
 - (i) the upper portion is vertically above the lower portion; and
 - (ii) the amount of liquid ejected against the upper portion per unit time is more than the amount of liquid ejected against the lower portion per unit time.

1/10




FIG. 1

FIG. 2

2/10




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

3/10




FIG. 9

FIG. 8

4/10




FIG. 10

5/10




FIG. 11

6/10




FIG. 12

7/10




FIG. 13

8/10




FIG. 14

9/10




FIG. 15

10/10




FIG. 16

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2009/058537

A. CLASSIFICATION OF SUBJECT MATTER
INV. B65G49/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
B65G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EP0-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 027 941 A (LENHARDT KARL [DE]) 2 July 1991 (1991-07-02) column 3, lines 34-47; figures 2,4 -----	1-5
A	US 2005/199493 A1 (BANGERT STEFAN [DE] ET AL) 15 September 2005 (2005-09-15) paragraphs [0029], [0034]; figures 3,9 -----	1-5
A	US 2005/011229 A1 (LISEC PETER [AT]) 20 January 2005 (2005-01-20) paragraph [0021]; figure 3 -----	1-5
A	US 2007/271756 A1 (AOKI YOSHIAKI [JP] ET AL) 29 November 2007 (2007-11-29) cited in the application the whole document -----	1-5



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority, claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

19 January 2010

Date of mailing of the international search report

25/01/2010

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Marrec, Patrick

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No PCT/US2009/058537

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
US 5027941	A 02-07-1991	CA	1269632 A1	29-05-1990
		DE	3536846 A1	16-04-1987
		EP	0222096 A1	20-05-1987
US 2005199493	A1 15-09-2005	CN	1697767 A	16-11-2005
		DE	10319379 A1	25-11-2004
		EP	1618056 A1	25-01-2006
		WO	2004096678 A1	11-11-2004
		JP	2006513117 T	20-04-2006
		TW	248981 B	11-02-2006
US 2005011229	A1 20-01-2005	WO	2004050516 A1	17-06-2004
		AT	368629 T	15-08-2007
		AU	2002361368 A1	23-06-2004
		CA	2464699 A1	05-06-2004
		CN	1578749 A	09-02-2005
		EP	1567433 A1	31-08-2005
US 2007271756	A1 29-11-2007	CN	1917983 A	21-02-2007
		EP	1731261 A1	13-12-2006
		WO	2005077594 A1	25-08-2005