



US011827155B2

(12) **United States Patent**
Lynam

(10) **Patent No.:** **US 11,827,155 B2**

(45) **Date of Patent:** ***Nov. 28, 2023**

(54) **VEHICULAR EXTERIOR REARVIEW MIRROR ASSEMBLY WITH BLIND SPOT INDICATOR**

(71) Applicant: **Magna Mirrors of America, Inc.**,
Holland, MI (US)

(72) Inventor: **Niall R. Lynam**, Holland, MI (US)

(73) Assignee: **Magna Mirrors of America, Inc.**,
Holland, MI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/054,964**

(22) Filed: **Nov. 14, 2022**

(65) **Prior Publication Data**

US 2023/0075827 A1 Mar. 9, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/649,808, filed on Feb. 3, 2022, now Pat. No. 11,498,487, which is a
(Continued)

(51) **Int. Cl.**
B60R 1/12 (2006.01)
B60R 1/06 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **B60R 1/1207** (2013.01); **B60R 1/06** (2013.01); **B60R 1/0602** (2013.01); **B60R 1/062** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC B60R 1/1207; B60R 1/06; B60R 1/0602; B60R 1/08; B60R 2001/1215
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,096,452 A 5/1914 Perrin
1,114,559 A 10/1914 Weed
(Continued)

FOREIGN PATENT DOCUMENTS

CA 1063695 A 10/1979
DE 3624321 A1 2/1988
(Continued)


Primary Examiner — Anne M Hines

(74) *Attorney, Agent, or Firm* — HONIGMAN LLP

(57) **ABSTRACT**

A vehicular exterior breakaway rearview mirror assembly includes a skull-cap mirror shell and a reflective element. With the mirror assembly mounted at an exterior side of a vehicle, the skull-cap mirror shell has an inboard wall that faces toward the exterior side of the vehicle. A blind spot indicator is disposed at an aperture established at the inboard wall of the skull-cap mirror shell. An illumination source of the blind spot indicator is activated to illuminate the blind spot indicator responsive to an electronic blind spot monitoring system of the vehicle detecting another vehicle that is approaching or overtaking the equipped vehicle. Illumination of the blind spot indicator by activation of the illumination source is readily viewable by the driver of the equipped vehicle and is not readily viewable by a driver of the detected other vehicle.

45 Claims, 35 Drawing Sheets



Related U.S. Application Data

- continuation of application No. 16/819,693, filed on Mar. 16, 2020, now Pat. No. 11,242,009, which is a continuation of application No. 15/083,895, filed on Mar. 29, 2016, now Pat. No. 10,589,686, which is a continuation of application No. 14/714,762, filed on May 18, 2015, now Pat. No. 9,302,624, which is a continuation of application No. 13/919,489, filed on Jun. 17, 2013, now Pat. No. 9,035,754, which is a continuation of application No. 13/572,045, filed on Aug. 10, 2012, now Pat. No. 8,466,779, which is a continuation of application No. 13/290,644, filed on Nov. 7, 2011, now Pat. No. 8,242,896, which is a continuation of application No. 12/446,507, filed as application No. PCT/US2007/082099 on Oct. 22, 2007, now Pat. No. 8,058,977, said application No. 13/919,489 is a continuation of application No. 13/452,121, filed on Apr. 20, 2012, now Pat. No. 8,466,780, which is a continuation of application No. 13/017,346, filed on Jan. 31, 2011, now Pat. No. 8,164,482, which is a continuation of application No. 12/794,111, filed on Jun. 4, 2010, now Pat. No. 7,880,596, which is a continuation of application No. 12/370,050, filed on Feb. 12, 2009, now Pat. No. 7,760,111, which is a continuation of application No. 11/994,471, filed as application No. PCT/US2006/026148 on Jul. 5, 2006, now Pat. No. 7,492,281, said application No. 14/714,762 is a continuation-in-part of application No. 14/486,133, filed on Sep. 15, 2014, now Pat. No. 9,045,091, which is a continuation of application No. 13/646,960, filed on Oct. 8, 2012, now Pat. No. 8,833,987, which is a continuation of application No. 13/335,135, filed on Dec. 22, 2011, now Pat. No. 8,282,253, which is a continuation of application No. 12/550,054, filed on Aug. 28, 2009, now Pat. No. 8,083,386, which is a continuation of application No. 11/520,193, filed on Sep. 13, 2006, now Pat. No. 7,581,859.
- (60) Provisional application No. 60/970,687, filed on Sep. 7, 2007, provisional application No. 60/918,089, filed on Mar. 15, 2007, provisional application No. 60/853,850, filed on Oct. 24, 2006, provisional application No. 60/696,953, filed on Jul. 6, 2005, provisional application No. 60/784,570, filed on Mar. 22, 2006, provisional application No. 60/717,093, filed on Sep. 14, 2005.
- (51) **Int. Cl.**
B60R 1/062 (2006.01)
B60R 1/08 (2006.01)
- (52) **U.S. Cl.**
 CPC *B60R 1/08* (2013.01); *B60R 2001/1215* (2013.01)
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- | | | | |
|-----------|---|---------|------------------|
| 1,563,258 | A | 11/1925 | Cunningham |
| 1,672,559 | A | 6/1928 | Doble |
| RE17,274 | E | 4/1929 | Porter |
| 2,010,138 | A | 8/1935 | Condon |
| 2,135,262 | A | 11/1938 | Schumacher |
| 2,263,382 | A | 11/1941 | Gotzinger |
| 2,457,348 | A | 12/1948 | Chambers |
| 2,514,989 | A | 7/1950 | Buren |
| 2,561,582 | A | 7/1951 | Marbel |
| 2,580,014 | A | 12/1951 | Gazda |
| 2,636,419 | A | 4/1953 | Kerr |
| 2,778,273 | A | 1/1957 | Fellmeth |
| 2,911,177 | A | 11/1959 | West |
| 3,104,274 | A | 9/1963 | King |
| 3,131,250 | A | 4/1964 | Ely |
| 3,146,296 | A | 8/1964 | Fischer |
| 3,170,985 | A | 2/1965 | Katulich |
| 3,175,463 | A | 3/1965 | Seashore |
| 3,266,016 | A | 8/1966 | Maru |
| 3,267,806 | A | 8/1966 | Azegami |
| 3,280,701 | A | 10/1966 | Donnelly et al. |
| 3,337,285 | A | 8/1967 | Travis |
| 3,338,655 | A | 8/1967 | Young |
| 3,375,053 | A | 3/1968 | Ward |
| 3,389,952 | A | 6/1968 | Tobin, Jr. |
| 3,404,935 | A | 10/1968 | Creager |
| 3,408,136 | A | 10/1968 | Travis |
| 3,424,517 | A | 1/1969 | Budreck |
| 3,563,638 | A | 2/1971 | Panozzo |
| 3,601,614 | A | 8/1971 | Platzer |
| 3,610,739 | A | 10/1971 | Seashore |
| 3,667,833 | A | 6/1972 | Baldwin, Sr. |
| 3,708,222 | A | 1/1973 | Stern |
| 3,764,201 | A | 10/1973 | Haile |
| 3,806,232 | A | 4/1974 | Gray |
| 3,826,563 | A | 7/1974 | Davis |
| 3,881,811 | A | 5/1975 | French |
| 3,887,788 | A | 6/1975 | Seibel et al. |
| 3,909,117 | A | 9/1975 | Takahashi et al. |
| 4,200,359 | A | 4/1980 | Lawson |
| 4,223,983 | A | 9/1980 | Bloom |
| 4,258,979 | A | 3/1981 | Mahin |
| 4,264,144 | A | 4/1981 | McCord |
| 4,268,120 | A | 5/1981 | Jitsumori |
| 4,274,078 | A | 6/1981 | Isobe et al. |
| 4,281,899 | A | 8/1981 | Oskam |
| 4,293,191 | A | 10/1981 | Kim |
| 4,303,308 | A | 12/1981 | Kobrin |
| 4,306,770 | A | 12/1981 | Marhauer |
| 4,311,362 | A | 1/1982 | LaPorte |
| 4,311,363 | A | 1/1982 | Marsalka et al. |
| 4,325,609 | A | 4/1982 | Alford |
| 4,331,382 | A | 5/1982 | Graff |
| 4,350,412 | A | 9/1982 | Steenblik et al. |
| 4,435,042 | A | 3/1984 | Wood et al. |
| 4,436,371 | A | 3/1984 | Wood et al. |
| 4,436,372 | A | 3/1984 | Schmidt et al. |
| 4,439,013 | A | 3/1984 | Hagn et al. |
| 4,449,786 | A | 5/1984 | McCord |
| 4,470,665 | A | 9/1984 | Blom |
| 4,499,451 | A | 2/1985 | Suzuki et al. |
| 4,526,446 | A | 7/1985 | Adams |
| 4,549,786 | A | 10/1985 | Albers et al. |
| 4,555,166 | A | 11/1985 | Enomoto |
| 4,575,202 | A | 3/1986 | McGuire |
| 4,588,267 | A | 5/1986 | Pastore |
| 4,609,266 | A | 9/1986 | Blom |
| 4,623,222 | A | 11/1986 | Itoh et al. |
| 4,629,296 | A | 12/1986 | White |
| 4,630,904 | A | 12/1986 | Pastore |
| 4,674,849 | A | 6/1987 | Stewart |
| 4,674,850 | A | 6/1987 | Blom |
| 4,678,294 | A | 7/1987 | Van Nostrand |
| 4,679,906 | A | 7/1987 | Brandenburg |
| 4,712,879 | A | 12/1987 | Lynam et al. |
| 4,715,701 | A | 12/1987 | Urban |
| 4,721,364 | A | 1/1988 | Itoh et al. |
| 4,727,302 | A | 2/1988 | Mizuta et al. |
| 4,733,335 | A | 3/1988 | Serizawa et al. |
| 4,733,336 | A | 3/1988 | Skogler et al. |
| 4,770,522 | A | 9/1988 | Alten |
| 4,773,740 | A | 9/1988 | Kawakami et al. |
| D297,926 | S | 10/1988 | Kesler |
| 4,793,690 | A | 12/1988 | Gahan et al. |
| 4,799,768 | A | 1/1989 | Gahan |
| 4,803,599 | A | 2/1989 | Trine et al. |
| 4,824,231 | A | 4/1989 | Quintana |

(56)

References Cited

U.S. PATENT DOCUMENTS

4,826,289	A	5/1989	Vandenbrink et al.	5,438,487	A	8/1995	Schmid et al.
4,828,379	A	5/1989	Parsons et al.	5,446,576	A	8/1995	Lynam et al.
4,853,283	A	8/1989	Skolnick	5,448,397	A	9/1995	Tonar
4,859,046	A	8/1989	Traynor et al.	D363,920	S	11/1995	Roberts et al.
4,882,466	A	11/1989	Friel	5,481,409	A	1/1996	Roberts
4,882,565	A	11/1989	Gallmeyer	5,497,305	A	3/1996	Pastrick et al.
4,906,075	A	3/1990	Matsumiya	5,497,306	A	3/1996	Pastrick
4,906,085	A	3/1990	Sugihara et al.	5,509,606	A	4/1996	Breithaupt et al.
4,913,542	A	4/1990	Adolfsson	5,517,367	A	5/1996	Kim et al.
4,917,477	A	4/1990	Bechtel et al.	5,523,877	A	6/1996	Lynam
4,917,485	A	4/1990	Baldwin, Sr.	5,525,264	A	6/1996	Cronin et al.
4,929,074	A	5/1990	Urban	5,526,195	A	6/1996	Thomas
4,931,627	A	6/1990	Watts	5,528,422	A	6/1996	Roberts
4,932,769	A	6/1990	Goosen	5,530,588	A	6/1996	Vivier
4,932,770	A	6/1990	Caravaty	5,535,056	A	7/1996	Caskey et al.
4,948,242	A	8/1990	Desmond et al.	5,550,677	A	8/1996	Schofield et al.
4,951,179	A	8/1990	Machida	5,557,467	A	9/1996	McColgan et al.
4,989,964	A	2/1991	Meise	5,559,640	A	9/1996	Vachss et al.
5,005,962	A	4/1991	Edelman	5,563,744	A	10/1996	Matsumiya
5,014,167	A	5/1991	Roberts	5,567,360	A	10/1996	Varaprasad et al.
5,016,996	A	5/1991	Ueno	5,575,552	A	11/1996	Faloon et al.
5,017,903	A	5/1991	Krippelz, Sr.	5,579,133	A	11/1996	Black et al.
5,022,747	A	6/1991	Polanyi et al.	5,587,236	A	12/1996	Agrawal et al.
5,033,835	A	7/1991	Platzer, Jr.	5,587,699	A	12/1996	Faloon et al.
5,044,739	A	9/1991	do Espirito Santo	5,594,222	A	1/1997	Caldwell
5,050,977	A	9/1991	Platzer, Jr.	5,594,593	A	1/1997	Milner
5,052,792	A	10/1991	McDonough	5,610,756	A	3/1997	Lynam et al.
5,059,015	A	10/1991	Tran	5,619,374	A	4/1997	Roberts
5,066,112	A	11/1991	Lynam et al.	5,619,375	A	4/1997	Roberts
5,073,012	A	12/1991	Lynam	5,621,569	A	4/1997	Schlenke
5,076,673	A	12/1991	Lynam et al.	5,621,577	A	4/1997	Lang et al.
5,076,674	A	12/1991	Lynam	5,632,551	A	5/1997	Roney et al.
5,078,480	A	1/1992	Warszawski	5,644,442	A	7/1997	Lemere
5,080,492	A	1/1992	Platzer, Jr.	5,649,756	A	7/1997	Adams et al.
5,107,374	A	4/1992	Lupo et al.	5,659,423	A	8/1997	Schierbeek et al.
5,115,346	A	5/1992	Lynam	5,668,663	A	9/1997	Varaprasad et al.
5,115,352	A	5/1992	do Espirito Santo	5,669,698	A	9/1997	Veldman et al.
5,117,346	A	5/1992	Gard	5,669,699	A	9/1997	Pastrick et al.
5,118,540	A	6/1992	Hutchison	5,669,704	A	9/1997	Pastrick
5,140,455	A	8/1992	Varaprasad et al.	5,669,705	A	9/1997	Pastrick et al.
5,142,407	A	8/1992	Varaprasad et al.	5,670,935	A	9/1997	Schofield et al.
5,151,816	A	9/1992	Varaprasad et al.	5,689,370	A	11/1997	Tonar et al.
5,151,824	A	9/1992	O'Farrell	5,691,855	A	11/1997	Lupkas
5,166,833	A	11/1992	Shyu	5,715,093	A	2/1998	Schierbeek et al.
5,178,448	A	1/1993	Adams et al.	5,722,836	A	3/1998	Younker
5,179,471	A	1/1993	Caskey et al.	5,724,187	A	3/1998	Varaprasad et al.
5,183,099	A	2/1993	Bechu	5,751,489	A	5/1998	Caskey et al.
5,189,537	A	2/1993	O'Farrell	D394,833	S	6/1998	Muth
5,193,029	A	3/1993	Schofield et al.	5,760,962	A	6/1998	Schofield et al.
5,207,492	A	5/1993	Roberts	5,784,211	A	7/1998	Mingledorff
5,225,943	A	7/1993	Lupo	5,786,772	A	7/1998	Schofield et al.
5,233,461	A	8/1993	Dorman et al.	5,788,357	A	8/1998	Muth et al.
5,237,458	A	8/1993	Polanyi et al.	5,790,298	A	8/1998	Tonar
5,237,459	A	8/1993	Strauss	5,790,327	A	8/1998	Lee et al.
5,239,405	A	8/1993	Varaprasad et al.	5,793,542	A	8/1998	Kondo et al.
5,247,395	A	9/1993	Martinez	5,796,094	A	8/1998	Schofield et al.
5,253,109	A	10/1993	O'Farrell et al.	5,796,176	A	8/1998	Kramer et al.
5,285,060	A	2/1994	Larson et al.	5,796,532	A	8/1998	Kanazawa
5,295,021	A	3/1994	Swanson	5,798,575	A	8/1998	O'Farrell et al.
5,296,973	A	3/1994	Burke	5,803,579	A	9/1998	Turnbull et al.
5,313,335	A	5/1994	Gray et al.	5,805,367	A	9/1998	Kanazawa
5,327,288	A	7/1994	Wellington et al.	5,808,777	A	9/1998	Lynam et al.
5,340,503	A	8/1994	Varaprasad et al.	5,818,625	A	10/1998	Forgette et al.
5,354,965	A	10/1994	Lee	5,823,654	A	10/1998	Pastrick et al.
5,355,245	A	10/1994	Lynam	5,825,527	A	10/1998	Forgette et al.
5,355,284	A	10/1994	Roberts	5,835,294	A	11/1998	Minegishi
5,361,190	A	11/1994	Roberts et al.	5,838,505	A	11/1998	Palathingal
5,371,659	A	12/1994	Pastrick et al.	5,847,889	A	12/1998	Komiyama et al.
5,402,103	A	3/1995	Tashiro	5,863,116	A	1/1999	Pastrick et al.
5,406,414	A	4/1995	O'Farrell et al.	5,864,434	A	1/1999	Taylor
5,412,512	A	5/1995	Zebold et al.	5,877,897	A	3/1999	Schofield et al.
5,424,875	A	6/1995	Davis, II	5,879,074	A	3/1999	Pastrick
5,432,643	A	7/1995	Huang	D409,540	S	5/1999	Muth
5,436,741	A	7/1995	Crandall	5,900,999	A	5/1999	Huizenga et al.
5,437,931	A	8/1995	Tsai et al.	5,910,854	A	6/1999	Varaprasad et al.
				5,922,176	A	7/1999	Caskey
				5,923,457	A	7/1999	Byker et al.
				5,929,786	A	7/1999	Schofield et al.
				5,938,320	A	8/1999	Crandall

(56)

References Cited

U.S. PATENT DOCUMENTS

5,959,367	A	9/1999	O'Farrell et al.	6,286,965	B1	9/2001	Caskey et al.
5,980,050	A	11/1999	McCord	6,294,989	B1	9/2001	Schofield et al.
5,986,364	A	11/1999	Bingle et al.	6,296,379	B1	10/2001	Pastrick
6,001,486	A	12/1999	Varaprasad et al.	6,299,333	B1	10/2001	Pastrick et al.
6,002,511	A	12/1999	Varaprasad et al.	6,310,611	B1	10/2001	Caldwell
6,002,544	A	12/1999	Yatsu	6,310,738	B1	10/2001	Chu
6,005,724	A	12/1999	Todd	6,313,454	B1	11/2001	Bos et al.
6,007,207	A	12/1999	Liu	6,315,419	B1	11/2001	Platzer, Jr.
6,007,222	A	12/1999	Thau	6,318,870	B1	11/2001	Spooner et al.
6,030,084	A	2/2000	Schmidt	6,320,282	B1	11/2001	Caldwell
6,032,323	A	3/2000	Smith et al.	6,329,925	B1	12/2001	Skiver et al.
6,033,078	A	3/2000	Su et al.	6,335,548	B1	1/2002	Roberts et al.
6,045,243	A	4/2000	Muth et al.	6,336,737	B1	1/2002	Thau
D425,466	S	5/2000	Todd et al.	6,340,849	B1	1/2002	Kramer et al.
6,064,508	A	5/2000	Forgette et al.	6,340,850	B2	1/2002	O'Farrell et al.
6,065,840	A	5/2000	Caskey et al.	6,341,523	B2	1/2002	Lynam
D426,506	S	6/2000	Todd et al.	6,343,402	B1	2/2002	Smith et al.
D426,507	S	6/2000	Todd et al.	6,347,880	B1	2/2002	Furst et al.
D427,128	S	6/2000	Mathieu	6,353,392	B1	3/2002	Schofield et al.
6,074,068	A	6/2000	Palathingal	6,356,376	B1	3/2002	Tonar et al.
6,074,077	A	6/2000	Pastrick et al.	6,359,274	B1	3/2002	Nixon et al.
6,076,948	A	6/2000	Bukosky et al.	6,362,548	B1	3/2002	Bingle et al.
D428,372	S	7/2000	Todd et al.	6,363,326	B1	3/2002	Scully
D428,373	S	7/2000	Todd et al.	6,379,013	B1	4/2002	Bechtel et al.
6,086,229	A	7/2000	Pastrick	6,390,632	B1	5/2002	Palathingal
6,093,976	A	7/2000	Kramer et al.	6,396,397	B1	5/2002	Bos et al.
D428,842	S	8/2000	Todd et al.	6,398,377	B1	6/2002	Chou
D429,202	S	8/2000	Todd et al.	6,402,328	B1	6/2002	Bechtel et al.
D430,088	S	8/2000	Todd et al.	6,416,208	B2	7/2002	Pastrick et al.
6,097,023	A	8/2000	Schofield et al.	6,420,036	B1	7/2002	Varaprasad et al.
6,099,155	A	8/2000	Pastrick et al.	6,426,485	B1	7/2002	Bulgajewski et al.
6,102,546	A	8/2000	Carter	6,428,172	B1	8/2002	Hutzel et al.
6,109,586	A	8/2000	Hoek	6,441,943	B1	8/2002	Roberts et al.
6,111,683	A	8/2000	Cammenga et al.	6,441,964	B1	8/2002	Chu et al.
6,111,684	A	8/2000	Forgette et al.	6,445,287	B1	9/2002	Schofield et al.
6,116,743	A	9/2000	Hoek	6,447,130	B2	9/2002	Chu
6,124,647	A	9/2000	Marcus et al.	6,449,082	B1	9/2002	Agrawal et al.
6,124,886	A	9/2000	DeLine et al.	6,467,920	B2	10/2002	Schnell et al.
6,132,072	A	10/2000	Turnbull et al.	6,471,362	B1	10/2002	Carter et al.
6,142,656	A	11/2000	Kurth	6,472,979	B2	10/2002	Schofield et al.
6,146,003	A	11/2000	Thau	6,476,358	B1	11/2002	Lang et al.
6,149,287	A	11/2000	Pastrick et al.	6,498,620	B2	12/2002	Schofield et al.
6,152,590	A	11/2000	Furst et al.	6,501,387	B2	12/2002	Skiver et al.
6,154,306	A	11/2000	Varaprasad et al.	6,504,142	B2	1/2003	Nixon et al.
6,163,083	A	12/2000	Kramer et al.	6,511,192	B1	1/2003	Henion et al.
6,164,564	A	12/2000	Franco et al.	6,512,624	B2	1/2003	Tonar et al.
6,166,848	A	12/2000	Cammenga et al.	6,521,916	B2	2/2003	Roberts et al.
6,170,956	B1	1/2001	Rumsey et al.	6,522,451	B1	2/2003	Lynam
6,172,613	B1	1/2001	DeLine et al.	6,523,976	B1	2/2003	Turnbull et al.
6,175,164	B1	1/2001	O'Farrell et al.	6,537,138	B2	3/2003	Ohmori et al.
6,175,300	B1	1/2001	Kendrick	6,582,109	B2	6/2003	Miller
6,176,602	B1	1/2001	Pastrick et al.	6,595,649	B2	7/2003	Hoekstra et al.
6,178,034	B1	1/2001	Allemand et al.	6,598,980	B2	7/2003	Marusawa et al.
6,195,194	B1	2/2001	Roberts et al.	6,598,982	B2	7/2003	Witt
6,196,688	B1	3/2001	Caskey et al.	6,612,708	B2	9/2003	Chu
6,198,409	B1	3/2001	Schofield et al.	6,615,438	B1	9/2003	Franco et al.
6,199,993	B1	3/2001	Mou	6,616,314	B2	9/2003	Thau
6,201,642	B1	3/2001	Bos	6,627,918	B2	9/2003	Getz et al.
6,206,553	B1	3/2001	Boddy et al.	6,642,851	B2	11/2003	Deline et al.
6,207,083	B1	3/2001	Varaprasad et al.	6,648,477	B2	11/2003	Hutzel et al.
6,213,612	B1	4/2001	Schnell et al.	6,650,457	B2	11/2003	Busscher et al.
6,227,689	B1	5/2001	Miller	6,657,767	B2	12/2003	Bonardi et al.
6,229,226	B1	5/2001	Kramer et al.	6,669,109	B2	12/2003	Ivanov et al.
6,229,435	B1	5/2001	Knapp et al.	6,669,267	B1	12/2003	Lynam et al.
6,239,898	B1	5/2001	Byker et al.	6,685,864	B2	2/2004	Bingle et al.
6,243,218	B1	6/2001	Whitehead	6,690,268	B2	2/2004	Schofield et al.
6,244,716	B1	6/2001	Steenwyk et al.	6,700,692	B2	3/2004	Tonar et al.
6,245,262	B1	6/2001	Varaprasad et al.	6,717,109	B1	4/2004	Macher et al.
6,250,148	B1	6/2001	Lynam	6,717,610	B1	4/2004	Bos et al.
6,257,746	B1	7/2001	Todd et al.	6,717,712	B2	4/2004	Lynam et al.
6,260,608	B1	7/2001	Kim	6,719,215	B2	4/2004	Drouillard
6,264,353	B1	7/2001	Caraher et al.	6,731,205	B2	5/2004	Schofield et al.
6,270,225	B1	8/2001	Goolsby	6,737,629	B2	5/2004	Nixon et al.
6,276,821	B1	8/2001	Pastrick et al.	6,742,904	B2	6/2004	Bechtel et al.
6,280,069	B1	8/2001	Pastrick et al.	6,755,544	B2	6/2004	Schnell et al.
				6,757,109	B2	6/2004	Bos
				D493,131	S	7/2004	Lawlor et al.
				D493,394	S	7/2004	Lawlor et al.
				6,824,281	B2	11/2004	Schofield et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,831,268	B2	12/2004	Bechtel et al.
6,832,848	B2	12/2004	Pastrick
6,855,431	B2	2/2005	Varaprasad et al.
6,882,287	B2	4/2005	Schofield
6,902,284	B2	6/2005	Hutzel et al.
6,916,100	B2	7/2005	Pavao
6,919,796	B2	7/2005	Boddy et al.
6,932,483	B2	8/2005	Strumolo et al.
6,979,090	B1	12/2005	Wnuk
7,004,593	B2	2/2006	Weller et al.
7,005,974	B2	2/2006	McMahon et al.
7,038,577	B2	5/2006	Pawlicki et al.
7,073,914	B2	7/2006	Pavao
7,080,914	B1	7/2006	Boddy
7,097,312	B2	8/2006	Platzer, Jr.
7,106,392	B2	9/2006	You
7,126,456	B2	10/2006	Boddy et al.
7,167,294	B2	1/2007	Ynam et al.
7,167,796	B2	1/2007	Taylor et al.
7,168,830	B2	1/2007	Pastrick et al.
7,184,190	B2	2/2007	McCabe et al.
7,195,381	B2	3/2007	Lynam et al.
7,249,860	B2	7/2007	Kulas et al.
7,255,451	B2	8/2007	McCabe et al.
7,267,448	B2	9/2007	Schmidt et al.
7,274,501	B2	9/2007	McCabe et al.
7,289,037	B2	10/2007	Uken et al.
7,293,901	B2	11/2007	Tuttle et al.
7,306,355	B2	12/2007	Walser et al.
7,324,261	B2	1/2008	Tonar et al.
7,334,922	B2	2/2008	Bonardi et al.
7,338,177	B2	3/2008	Lynam
7,339,149	B1	3/2008	Schofield et al.
7,342,707	B2	3/2008	Roberts et al.
7,345,680	B2	3/2008	David
7,349,143	B2	3/2008	Tonar et al.
7,370,983	B2	5/2008	DeWind et al.
7,372,611	B2	5/2008	Tonar et al.
7,377,675	B2	5/2008	Pastrick et al.
7,391,563	B2	6/2008	McCabe et al.
7,400,435	B2	7/2008	Byers et al.
7,420,756	B2	9/2008	Lynam
7,423,522	B2	9/2008	O'Brien et al.
7,492,281	B2	2/2009	Lynam et al.
7,517,099	B2	4/2009	Hannah
7,526,103	B2	4/2009	Schofield et al.
7,581,859	B2	9/2009	Lynam
7,626,749	B2	12/2009	Baur et al.
7,636,188	B2	12/2009	Baur et al.
7,674,025	B2	3/2010	Liesener
7,748,856	B2	7/2010	Zhao
7,760,111	B2	7/2010	Lynam et al.
7,824,045	B2	11/2010	Zhao
7,880,596	B2	2/2011	Lynam et al.
7,887,204	B2	2/2011	Zhao
7,934,844	B1	5/2011	Zhao
7,944,371	B2	5/2011	Foote et al.
8,058,977	B2	11/2011	Lynam
8,102,279	B2	1/2012	Foote et al.
8,164,482	B2	4/2012	Lynam et al.
8,242,896	B2	8/2012	Lynam
8,287,164	B2	10/2012	Fehn et al.
8,466,779	B2	6/2013	Lynam
8,466,780	B2	6/2013	Lynam et al.
9,013,288	B2	4/2015	Foote et al.
9,035,754	B2	5/2015	Lynam
9,302,624	B2	4/2016	Lynam
10,589,686	B2	3/2020	Lynam
11,242,009	B2	2/2022	Lynam
11,498,487	B2	11/2022	Lynam
2002/0003571	A1	1/2002	Schofield et al.
2002/0036828	A1	3/2002	Wong
2002/0105741	A1	8/2002	Platzer
2002/0159169	A1	10/2002	McCord
2002/0159270	A1	10/2002	Fynam et al.
2003/0002179	A1	1/2003	Roberts et al.
2003/0043589	A1	3/2003	Blank
2003/0117731	A1	6/2003	Platzer
2004/0032638	A1	2/2004	Tonar et al.
2004/0032675	A1	2/2004	Weller et al.
2004/0032676	A1	2/2004	Drummond et al.
2004/0165291	A1	8/2004	Platzer
2004/0264011	A1	12/2004	Lynam
2005/0078389	A1	4/2005	Kulas et al.
2005/0083577	A1	4/2005	Varaprasad et al.
2005/0099693	A1	5/2005	Schofield et al.
2005/0134983	A1	6/2005	Lynam
2005/0232469	A1	10/2005	Schofield et al.
2005/0248859	A1	11/2005	Platzer
2006/0050018	A1	3/2006	Hutzel et al.
2006/0056086	A1	3/2006	Hannah
2006/0061008	A1	3/2006	Karner et al.
2006/0125919	A1	6/2006	Camilleri et al.
2006/0126150	A1	6/2006	Tonar et al.
2006/0171704	A1	8/2006	Bingle et al.
2006/0181772	A1	8/2006	Byers et al.
2006/0184297	A1	8/2006	Higgins-Luthman
2006/0268440	A1	11/2006	Platzer
2007/0058257	A1	3/2007	Lynam
2007/0285789	A1	12/2007	Lindahl et al.
2008/0212189	A1	9/2008	Baur et al.
2008/0225421	A1	9/2008	Platzer
2008/0304170	A1	12/2008	Zhao
2009/0040306	A1	2/2009	Foote et al.
2009/0115631	A1	5/2009	Foote et al.
2009/0237820	A1	9/2009	McCabe et al.
2010/0026475	A1	2/2010	Hwang
2010/0039691	A1	2/2010	Thomas et al.
2010/0321757	A1	12/2010	Cammenga et al.
2011/0260845	A1	10/2011	Henion et al.
2013/0027952	A1*	1/2013	Lynam B60R 1/1207 362/494

FOREIGN PATENT DOCUMENTS

DE	3743072	A1	7/1989
DE	4026578	A1	4/1992
DE	10054315	A1	5/2002
EP	0210757	A2	2/1987
EP	0310261	A1	4/1989
EP	0356099	A2	2/1990
EP	0443185	A2	8/1991
EP	0551802	A1	7/1993
EP	0728618	A2	8/1996
EP	0729864	A1	9/1996
EP	0791503	A2	8/1997
EP	0917987	A1	5/1999
FR	2551005		3/1985
FR	2628042	A1	9/1989
GB	1172382	A	11/1969
GB	2161440	A	1/1986
JP	362075619		4/1987
JP	62105103		5/1987
JP	1186443		7/1989
JP	1208245		8/1989
JP	491539		8/1992
JP	08268188		10/1996
JP	0681836		3/1997
JP	10086899		4/1998
KR	2002092059		12/2002
WO	1995030495		11/1995
WO	2001081956	A1	11/2001
WO	2004026633	A2	4/2004
WO	2004047421	A2	6/2004
WO	2004103772	A2	12/2004
WO	2005086777	A2	9/2005
WO	2006017019	A1	2/2006
WO	2006124682	A2	11/2006
WO	2007005942	A2	1/2007
WO	2008051910	A2	5/2008

* cited by examiner




FIG. 1




FIG 2




FIG. 3A




FIG. 3




FIG. 4




FIG 5




FIG 6




FIG. 7




FIG. 8




FIG 9




FIG. 10




FIG. 11




FIG. 12




FIG. 15




FIG. 17




FIG. 18




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 21A




FIG. 21B




FIG. 22




FIG. 23




FIG 24




FIG. 25




FIG. 26




FIG. 27




FIG. 27A




FIG. 28




FIG. 29




FIG. 30




FIG. 31A





FIG. 31B






FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37B




FIG. 37A




FIG. 38

1

**VEHICULAR EXTERIOR REARVIEW
MIRROR ASSEMBLY WITH BLIND SPOT
INDICATOR**

CROSS REFERENCE TO RELATED
APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 17/649,808, filed Feb. 3, 2022, now U.S. Pat. No. 11,498,487, which is a continuation of U.S. patent application Ser. No. 16/819,693, filed Mar. 16, 2020, now U.S. Pat. No. 11,242,009, which is a continuation of U.S. patent application Ser. No. 15/083,895, filed Mar. 29, 2016, now U.S. Pat. No. 10,589,686, which is a continuation of U.S. patent application Ser. No. 14/714,762, filed May 18, 2015, now U.S. Pat. No. 9,302,624, which is a continuation of U.S. patent application Ser. No. 13/919,489, filed Jun. 17, 2013, now U.S. Pat. No. 9,035,754, which is a continuation of U.S. patent application Ser. No. 13/572,045, filed Aug. 10, 2012, now U.S. Pat. No. 8,466,779, which is a continuation of U.S. patent application Ser. No. 13/290,644, filed Nov. 7, 2011, now U.S. Pat. No. 8,242,896, which is a continuation of U.S. patent application Ser. No. 12/446,507, filed Apr. 21, 2009, now U.S. Pat. No. 8,058,977, which is a 371 national phase application of PCT Application No. PCT/US07/82099, filed Oct. 22, 2007, which claims benefit of U.S. provisional applications, Ser. No. Ser. No. 60/970,687, filed Sep. 7, 2007, Ser. No. 60/918,089, filed Mar. 15, 2007, and 60/853,850, filed Oct. 24, 2006, which are hereby incorporated herein by reference in their entireties. And U.S. patent application Ser. No. 13/919,489 is a continuation-in-part of U.S. patent application Ser. No. 13/452,121, filed Apr. 20, 2012, now U.S. Pat. No. 8,466,780, which is a continuation of U.S. patent application Ser. No. 13/017,346, filed Jan. 31, 2011, now U.S. Pat. No. 8,164,482, which is a continuation of U.S. patent application Ser. No. 12/794,111, filed Jun. 4, 2010, now U.S. Pat. No. 7,880,596, which is a continuation of U.S. patent application Ser. No. 12/370,050, filed Feb. 12, 2009, now U.S. Pat. No. 7,760,111, which is a continuation of U.S. patent application Ser. No. 11/994,471, filed Jan. 2, 2008, now U.S. Pat. No. 7,492,281, which is a 371 national phase application of PCT Application No. PCT/US2006/026148, filed Jul. 5, 2006, which claims benefit of U.S. provisional applications, Ser. No. 60/696,953, filed Jul. 6, 2005, and Ser. No. 60/784,570, filed Mar. 22, 2006. And U.S. patent application Ser. No. 14/714,762 is a continuation-in-part of U.S. patent application Ser. No. 14/486,133, filed Sep. 15, 2014, now U.S. Pat. No. 9,045,091, which is a continuation of U.S. patent application Ser. No. 13/646,960, filed Oct. 8, 2012, now U.S. Pat. No. 8,833,987, which is a continuation of U.S. patent application Ser. No. 13/335,135, filed Dec. 22, 2011, now U.S. Pat. No. 8,282,253, which is a continuation of U.S. patent application Ser. No. 12/550,054, filed Aug. 28, 2009, now U.S. Pat. No. 8,083,386, which is a continuation of U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, which claims the benefit of U.S. provisional application Ser. No. 60/717,093, filed Sep. 14, 2005.

FIELD OF THE INVENTION

The present invention relates to exterior rearview mirror assemblies and, more particularly, to an exterior rearview mirror assembly having a blind spot/object detection indi-

2

cator and/or a lane change aid (LCA) indicator and/or a turn signal or other indicator at the exterior rearview mirror assembly.

BACKGROUND OF THE INVENTION

It is known to provide an object in a blind spot detection/LCA system for a vehicle that detects the presence of another vehicle or object in the lane next to the host vehicle, where it may be difficult for the driver of the host vehicle to determine whether or not there is another vehicle or object adjacent to the host vehicle. Such an object in a blind spot detection/LCA system often includes a visual indicator that visually indicates the detection of another vehicle or object to the driver of the host vehicle. It is also known to provide a turn signal indicator that is activated when a turn signal is activated by the driver of the host vehicle so as to provide an indication of the vehicle turning or changing lanes to the driver of a vehicle in an adjacent lane to the host or subject vehicle or to another person external to the host or subject vehicle. The visual indicator or indicators (commonly a light emitting diode or the like) of such systems is/are often located at the mirror reflective element of the exterior rearview mirror assembly.

The object/LCA visual indicator or indicators indicate or alert the driver of the host vehicle of the presence or impending presence of another vehicle or object in a blind spot in an adjacent side lane that typically cannot be readily seen within the field of view of the exterior mirror reflective element of the exterior mirror assembly mounted at that side of the vehicle and/or cannot be readily seen by the driver's peripheral vision or the like. The object/LCA visual indicators typically are arranged to be viewable principally or solely by the driver of the host vehicle and not by drivers of other vehicles. Similarly, the turn signal visual indicator or indicators indicate or alert a person external of the host vehicle (such as the driver of another vehicle alongside or approaching the host vehicle) that the turn signal of the host vehicle is activated to indicate that the driver of the host vehicle is contemplating or commencing a turn or lane change or the like. It is desirable that such turn signal visual indicators are not readily viewable by the driver of the host vehicle when they are activated. Because of vehicle regulations and mirror and vehicle configurations and geometries, and because of the need to provide an uninterrupted reflective surface to satisfy the likes of the FMVSS 111 field of view regulation, blind spot/LCA indicators in the prior art are typically located towards or at the outboard edge, and typically towards or at the upper corner/quadrant, of the reflective mirror element of the exterior mirror assembly.

Somewhat costly and complicated indicator constructions have been contemplated that, when placed behind and supported by the mirror reflective element, attempt to have their projected beam of emitted light directed principally to be viewed by the driver of the host vehicle (or other persons external to the host vehicle for turn signal applications) through the mirror reflective element and shielded from view by other drivers in blind spot alert detection systems (or from the driver of the host vehicle for turn signal applications). In some applications, the mirror reflective element may have a transreflective reflector coating or may have a window or port formed in a non-transreflective reflector coating. For example, transreflective mirror coatings (such as, for example, those described in U.S. Pat. Nos. 3,280,701; 6,855,431; 5,724,187; 5,340,503; 6,286,965; 6,196,688; 6,045,023; 5,788,357; 5,535,056; 5,751,489 and 6,065,840, which are hereby incorporated herein by reference in their

entireties) may be used, or alternately, a transmissive window or port may be formed in the reflective coating or coatings of the mirror reflective element (such as, for example, those described in U.S. Pat. Nos. 6,005,724; 6,257,746; 6,111,683, 5,786,772, 5,313,335 and 5,285,060, which are hereby incorporated herein by reference in their entireties). An illumination source or indicator may be positioned so as to direct or emit illumination through the window or display area and toward the driver of the host vehicle so as to be viewable by the driver of the host vehicle (or outwardly away from the vehicle so as to be generally not viewable by the driver of the host vehicle for turn signal applications).

Such a mirror assembly and indicator often include a baffle or other light directing element and an illumination source positioned at the rear of the mirror reflective element (and generally at the transmissive window or port if applicable). The baffle shields from view by an observer or the light directing element directs the light or illumination from the illumination source toward the desired or appropriate viewer (such as the driver of the host vehicle for blind spot/LCA applications or the driver of another vehicle for turn signal applications) and away from others (such as away from other drivers for blind spot/LCA applications or away from the driver of the host vehicle for turn signal applications).

Typically, such baffles or other light directing elements are adhered to the rear surface of the mirror reflective element. In some applications, the illumination source may be provided as a module to the mirror assembly facility and adhered to the rear of the mirror reflective element as a unit or module (for instance, light from LEDs facing and emitting light in the direction away from the mirror element may be reflected back towards the mirror reflector, and hence through the mirror element, using suitably angled or disposed mirrored surfaces). After the baffle or module is attached to the reflective element, the back plate of the mirror assembly may be adhered to the mirror reflective element to complete the mirror reflector sub assembly that is then assembled with the actuator and casing and other components to form the complete mirror assembly for mounting to the side of the vehicle.

A variety of interior and exterior mirror assemblies with indicators are known in the art, such as U.S. Pat. Nos. 5,355,284; 5,788,357; 6,257,746; 6,005,724; 5,481,409; 6,111,683; 6,045,243; 6,512,624; 6,356,376; 2,263,382; 2,580,014; 3,266,016; 4,499,451; 4,588,267; 4,630,904; 4,623,222; 4,721,364; 4,906,085; 5,313,335; 5,587,699; 5,575,552; 5,436,741, 5,587,699; 5,938,320; 6,700,692 and 5,786,772, and Canadian Pat. No. CA 1,063,695, and Great Britain Patent Specification 1,172,382 and Pat. Abstracts of Japan Publication No. 0917573, published Jul. 8, 1997, and PCT Publication WO 95/30495, published Nov. 16 1995, which are all hereby incorporated herein by reference in their entireties.

Therefore, there is a need in the art for an improved object in a blind spot/LCA indicator that is readily viewable by a driver of the host vehicle and not visible or viewable by a driver of another vehicle and/or an improved turn signal indicator that is readily viewable by the driver of another vehicle and not visible or viewable by the driver of the host vehicle.

SUMMARY OF THE INVENTION

The present invention provides an object in a blind spot indicator or lane change assist (LCA) indicator or turn signal indicator or other indicator that is integral with the mirror

reflector carrier or back plate of the mirror reflector sub-assembly so as to be positioned at and attached to the mirror reflective element as the back plate is adhered or otherwise attached at the back of the mirror reflective element. Preferably, the signal indicator is provided as a sealed or substantially sealed unit or module that can be snapped into or otherwise attached or secured (preferably mechanically but optionally adhesively) at the mirror back plate (and does so substantially or wholly sealingly to limit or substantially preclude water ingress to the module so that the module and back plate are substantially water impervious), preferably at the mirror sub-assembly manufacturing operation when the mirror reflective element (and any associated heater or other item or element) is joined to the mirror back plate, such as by utilizing aspects of the indicators described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, and/or PCT Application No. PCT/US2006/018567, filed May 16, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties. The present invention thus provides a mirror reflector carrier or back plate with an integrated blind spot indicator/indicators and/or turn signal indicator/indicators and/or other indicator/indicators.

According to an aspect of the present invention, an exterior rearview mirror assembly for a vehicle includes a mirror reflective element, a back plate and an indicator or display device. The back plate is molded or formed with a baffle having a plurality of light baffle elements that define a plurality of slots through the back plate. The back plate is attached to the rear surface of the reflective element (the surface opposite the front surface, with the front surface facing generally rearward and toward the driver of the vehicle when the mirror assembly is mounted to the vehicle) and includes an indicator mount or mounting portion for mounting the indicator at the back plate and generally at the light baffle. The indicator mounting portion extends rearward away from the reflective element and may be integrally formed with the back plate, preferably by injection molding. The indicator mounting portion is formed to receive a transparent or translucent block or glow element, and one or more light sources are disposed at the block, such that light emitted by the light source or sources is transmitted through the block and through the slots at the light baffles and through the reflective element for viewing by a person viewing the reflective element at an angle that generally corresponds to the angle established by the light baffles and/or the indicator mounting portion, while shielding or shading the light from viewing by a person viewing the reflective angle at another angle that does not generally correspond to the angle established by the light baffles and/or indicator mounting portion.

The indicator thus is mounted at the indicator mounting portion and is activatable so that illumination from the indicator is directed through the slots at the light baffles and is thus viewable through the reflective element by a person viewing the mirror reflective element at a desired or generally corresponding angle. The angle of the light direction may be established by an angle of the light baffles of the back plate and/or an angle of the transparent or translucent block established by the block itself and/or the indicator mounting portion of the back plate.

The mirror back plate, including the light baffles and/or the indicator mounting portion or display receiving portion, may be configured to orient the block or display element at a predetermined angle so that light exiting the block when the light source is activated is directed one of (a) generally

5

away from the vehicle when the mirror assembly is mounted to the vehicle so as to be principally viewed by drivers of other vehicles and so as to be substantially not viewed by the driver of the host vehicle, and (b) generally toward the driver of the vehicle when the mirror assembly is mounted to the vehicle so as to be principally viewed by the driver of the host vehicle and so as to be substantially not viewed by drivers of other vehicles.

Optionally, the display element is associated with a blind spot detection system of the vehicle. Optionally, the display element is associated with a turn signal of the vehicle. Optionally, the display element may comprise first and second display elements, with a first display element being associated with a turn signal of the vehicle and a second display element being associated with a blind spot detection system of the vehicle.

For applications of a turn signal indicator, the baffle protects or shields the driver from seeing the light or illumination from the illumination source by shading or direct line of sight occlusion (like a Venetian blind). The baffle thus allows illumination to be viewed by a targeted viewer (such as the driver of the host vehicle for blind spot/LCA applications or the driver of another vehicle for turn signal applications) and limits viewability (or provides direct line of sight occlusion) by others (such as away from other drivers for blind spot/LCA applications or away from the driver of the host vehicle for turn signal applications).

The back plate may comprise a plastic molding, such as a plastic molding formed by injection molding or co-injection molding or the like. The back plate may be formed with an attaching portion, such as a raised annular ring or annular prongs or annular snaps or the like at its rear surface (opposite from the mounting face or surface that attaches to the mirror reflective element) for attaching the back plate to a mirror actuator (for manually or electrically adjusting an angle of the mirror reflective element relative to the mirror casing).

Therefore, the present invention provides a display device or indicator at the back plate of a mirror reflector sub-assembly. The mirror reflector sub-assembly thus may achieve enhanced assembly processes, and may be supplied or provided to a mirror manufacturer or assembler as a unit that includes the indicator mounting portion (and that may also include the indicator) and display. The integrally formed back plate and indicator mount or mounting portion and light baffles may be readily attached to the mirror reflective element, and the indicator may be readily plugged into or connected to or received in the indicator mount to assemble the mirror reflector sub-assembly. The back plate may include one or more indicator mounts or mounting portions and associated light baffles for providing one or more displays at the reflective element, such as a blind spot/LCA display and/or a turn signal display and/or the like.

These and other objects, advantages, purposes and features of the present invention will become apparent upon review of the following specification in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a view of an exterior mirror assembly with a display device or indicator in accordance with the present invention, shown as viewed in the direction of travel of the vehicle;

FIG. 2 is a sectional view of a mirror reflector sub-assembly having a back plate and indicator element in accordance with the present invention;

6

FIG. 3 is a perspective view of a display element or block suitable for use with the indicator element of the present invention;

FIG. 3A is a plan view of a display element or block of the present invention;

FIG. 4 is a partial sectional view of the block and a circuit element at a rear surface of the block in accordance with the present invention;

FIG. 5 is a sectional view of the back plate of the mirror reflector sub-assembly of FIG. 2;

FIG. 6 is a plan view of the back plate of FIG. 5;

FIG. 7 is a sectional view of another mirror reflector sub-assembly having a back plate and indicator element in accordance with the present invention, shown with the indicator element detached from the back plate;

FIG. 8 is another sectional view of the mirror reflector sub-assembly of FIG. 7, shown with the indicator element attached to the back plate;

FIG. 9 is a sectional view of another mirror reflector sub-assembly having a back plate and indicator element in accordance with the present invention, shown with the indicator element detached from the back plate;

FIG. 10 is another sectional view of the mirror reflector sub-assembly of FIG. 9, shown with the indicator element attached to the back plate;

FIG. 11 is a sectional view of another back plate of the present invention, having an angled attachment element for receiving an indicator element thereat;

FIG. 12 is a plan view of the back plate of FIG. 11;

FIG. 13 is a sectional view of another mirror reflector sub-assembly in accordance with the present invention;

FIG. 14 is a sectional view of another mirror reflector sub-assembly similar to the mirror reflector sub-assembly of FIG. 13, with an anti-reflection coating at a front surface of the reflective element;

FIG. 15 is a sectional view of a back plate and indicator modules in accordance with the present invention;

FIG. 16 is a sectional view of a mirror reflector sub-assembly having the back plate and indicator modules of FIG. 15;

FIG. 17 is a sectional view of another back plate and indicator modules in accordance with the present invention;

FIG. 18 is a sectional view of another back plate and indicator modules in accordance with the present invention;

FIG. 19A is a sectional view of another back plate and indicator module in accordance with the present invention;

FIG. 19B is a plan view of an indicator stencil or mask for use with the back plate and indicator module of FIG. 19A;

FIG. 19C is a plan view of a mirror reflective element having the back plate and indicator module and indicator mask of FIGS. 19A and 19B;

FIG. 20A is a sectional view of another mirror reflector sub-assembly having a back plate and indicator modules in accordance with the present invention;

FIG. 20B is a plan view of the mirror reflector subassembly of FIG. 20A;

FIG. 21A is a perspective view of a rear substrate coated with a metallic reflector in accordance with the present invention;

FIG. 21B is a side elevation of the coated rear substrate of FIG. 21A;

FIG. 22 is a sectional view of a mirror reflective element assembly incorporating the coated rear substrate of FIGS. 21A and 21B;

FIG. 23 is a diagram showing the process of forming and coating the rear substrate of FIGS. 21A and 21B;

FIG. 24 is a sectional view of another mirror reflective element assembly in accordance with the present invention;

FIG. 25 is a sectional view of another mirror reflective element assembly in accordance with the present invention;

FIG. 26 is a perspective view of an exterior mirror assembly with a blind spot indicator in accordance with the present invention, shown with the indicator as an ISO icon;

FIG. 27 is a perspective view of an exterior mirror assembly similar to FIG. 26, shown with the indicator as a multi-stage indicator;

FIG. 27A is a perspective view of another exterior mirror assembly similar to FIG. 27, with the indicator located at an upper region of the inboard portion of the mirror assembly;

FIG. 28 is a perspective view of another exterior mirror assembly similar to FIG. 26, shown with the indicator as a hazard icon;

FIG. 29 is a perspective view of a vehicle with an exterior mirror assembly and blind spot indicator of the present invention, shown as the driver of a trailing vehicle may view the vehicle and exterior mirror assembly;

FIG. 30 is a perspective view of the vehicle of FIG. 29, shown as the driver of an overtaking vehicle may view the vehicle and exterior mirror assembly;

FIGS. 31A and 31B are perspective views of the driver and passenger side exterior mirror assemblies and of the interior rearview mirror assembly, with blind spot indicators in accordance with the present invention;

FIG. 32 is a perspective view of another exterior mirror assembly with a blind spot indicator in the support arm of the mirror assembly in accordance with the present invention, shown with the indicator as an ISO icon;

FIG. 33 is a perspective view of an exterior mirror assembly similar to FIG. 32, shown with the indicator as a multi-stage indicator;

FIG. 34 is a perspective view of another exterior mirror assembly similar to FIG. 32, shown with the indicator as a hazard icon;

FIG. 35 is a perspective view of another exterior mirror assembly similar to FIG. 32, shown with a multi-stage indicator at the side of the mirror shell;

FIG. 36 is a perspective view of another exterior mirror assembly similar to FIG. with the indicator at the side of the mirror shell and above the support arm;

FIGS. 37A and 37B are perspective views of the driver and passenger side exterior mirror assemblies of a vehicle, with blind spot indicators in accordance with the present invention; and

FIG. 38 is a perspective view of another exterior mirror assembly with a blind spot indicator in accordance with the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the drawings and the illustrative embodiments depicted therein, an exterior rearview mirror assembly 10 for a vehicle includes a mirror reflector sub-assembly 12 and a mirror shell or casing 14 (FIG. 1). Mirror assembly 10 is mounted at the side 16a of a host or subject vehicle 16. As shown in FIG. 2, mirror reflector sub-assembly 12 includes a mirror reflective element 18 and a mirror reflector carrier or back plate 20 attached to or mounted to or adhered to a rear surface 18a of mirror reflective element 18. Mirror assembly 10 includes an indicator or display element or device or signal indication module 22 that is disposed at back plate 20 and behind reflective element 18, and that is operable to provide a

display or indication at the reflective element for viewing the display or indication through the mirror reflective element. Signal indication module 22 includes a transparent or translucent polymeric block or element or indicating light source or element 24 (that is received into or attached to an indicator receiving portion or mounting portion or structure 26 of back plate so as to be disposed generally at a rear surface 20a of back plate 20) and an illumination source or indicator 28, such as one or more light emitting diodes (LEDs) or other suitable illumination source. Signal indication module 22 is attached to or mounted to or received in or at the indicator mounting portion 26 of back plate 20 so as to be disposed generally at and behind a light baffle 30 (FIGS. 2, 5 and 6) integrally formed with back plate 20. In the illustrated embodiment of FIGS. 2-6, the mirror assembly includes a signal indication module 22 for an object detection in a blind spot detection system or LCA system, as discussed below, but could also or otherwise include a display device for a turn signal indicator or signal indication module or other indicator device (as also discussed below). The indicator element or signal indication module thus may be readily mounted to or attached to a unitary back plate (including an indicator mounting portion), such as by utilizing aspects of the indicators described in U.S. patent applications, Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859; and/or Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008, and/or PCT Application No. PCT/US2006/018567, filed May 16, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties.

Optionally, the mirror assembly may include multiple display elements or devices or signal indication modules (such as two or more display elements or devices or signal indication modules) for providing both an object in a blind spot/LCA indicator and display area 19a and a turn signal indicator and display area 19b, such as shown in FIG. 1. The two or more signal indication modules may be incorporated together into a single unitary display module or unit (and thus with a common connector incorporated in the single unitary module and servicing, for example, a commonly housed turn signal indicator element and blind spot indicator element), or the two or more signal indication modules may be separate display devices (for example, a LCA blind spot indicator unitary module may be disposed at a bottom/lower inward portion of the mirror sub-assembly and a separate turn signal indicator unitary module may be disposed at an upper outward portion of the mirror sub-assembly), while remaining within the spirit and scope of the present invention. Optionally, for example, a turn signal indicator or device or element or module of the present invention may be incorporated into a mirror sub-assembly, and the exterior rearview mirror assembly may include a blind spot or lane change assist indicating device or element at a portion of the mirror casing (such as at an inboard facing portion of the casing that faces generally inboard toward the side of the vehicle so as to be readily viewable by the driver of the vehicle), such as by utilizing aspects of the indicating elements described in PCT Application No. PCT/US2006/026148, filed Jul. 5, 2006 and published Jan. 11, 2007 as International Publication No. WO 2007/005942, which is hereby incorporated herein by reference in its entirety.

As shown in FIGS. 2 and 4, signal indication module 22 includes a circuit element 32, such as a printed circuit board or the like (such as a rigid or flexible circuit board or element), with illumination sources or LEDs 28 disposed

thereat (such as surface mounted or otherwise disposed LEDs or other suitable or equivalent light sources). Circuit element **32** is attachable to a rear surface **24a** of indicating light source or block **24**, whereby the illumination sources **28** are located at the rear surface and preferably at or partially within light source receiving apertures or recesses **24b** at the rear surface **24a** of indicating light source or block **24**. The signal indication module **22** may be purchased as a display element assembly (including the circuit element and circuitry, which are attached at the rear of the indicating light source or block **24**) and assembled to the mirror reflective element sub-assembly **12**, such as at a mirror assembly facility, such as described below. Circuit element **32** preferably includes an electrical connector **32a** or lead or terminal for electrically connecting the circuitry and light source to electrical power or electrical control at the mirror assembly when the signal indication module is attached to the back plate and installed at the mirror casing.

Indicating light source or block **24** of signal indication module **22** comprises a transparent or translucent polymeric block, such as may be cast or injection molded from an optical light transmitting polymeric resin, such as a polycarbonate or an acrylic, or an acrylate, or a polystyrene, or a CR-39 or a COC olefin or other suitable material. The block may be molded as a translucent element, and may comprise a material that is at least partially crystalline, or the material may have a light scattering material mixed therein, or may be otherwise selected so as to provide a diffuse block, whereby the illumination emitted by the illumination source or LED will emanate from the forward surface of the block as a substantially uniform glow. The translucent diffuse block or element may be formed to a desired or suitable shape, such as an arrow or chevron shape (such as shown in FIG. 3), so as to provide the desired form for viewing by the driver of the vehicle. Preferably, the block comprises a translucent block, and thus transmits and diffuses light passing therethrough so that the light sources are not clearly or readily seen through the block by a person viewing the block. The block thus provides substantially uniform light distribution and provides a glowing indicating light source or block when the illumination source or LED/LEDs are activated or energized. Thus, the light emanating from the signal indicating module will not be seen as one or more point sources of light (i.e., the LED or LEDs will not be seen as individual point sources of light), but the light will be provided via a substantially uniformly glowing light source or indicating light source via the diffuse, translucent block or element.

Preferably, the indicating light source or block is partially or substantially coated or painted or covered or sleeved or formed so as to have a light reflecting rear surface **24a** and side surfaces **24c** (FIG. 3) so that light emitted by illumination sources **28** at the receiving apertures **24b** is directed through the block and toward and through the light baffle **30** and through the reflective element **18**, and is not transmitted through the side walls or surfaces **24c** and rear wall or surface **24a** of the indicating light source or block **24**, such that light is not emitted into the cavity of the mirror casing. For example, the rear surface (excluding the light source receiving apertures) and side surfaces of the block may be formed or coated to have white diffuse or silvery specular surfaces, such as via application of a reflective tape or a reflective coating or paint or a white tape or coating or paint (such as a diffuse coating such as a white paint or argon paint or titanium paint or the like) at the side and rear surfaces of the block (in other words, the block may be covered or coated at all of its surfaces except its front surface that faces

generally toward the reflective element). Optionally, and desirably, the color of the coating or paint (or other material or surface layer or characteristic) may be selected to provide enhanced reflectivity depending on the color and/or type of illumination source or LED of the signal indicating module. For example, if a red LED is used as the illumination source, the indicating light source or block may have a red coating or paint at its side surfaces and rear surface so as to enhance reflectivity of the red light emitted by the red LED at the sides and rear of the block so that the light is reflected and transmitted through the block and toward the reflective element for viewing as a substantially uniform glowing block or indicating light source (if other color LEDs are used, then other correspondingly colored coatings may be used to generally correspond to the wavelengths of light emitted by the colored LEDs). Thus, light emitted by the illumination sources **28** is emitted into the block where the light may pass through the block (and toward the reflective element) or may reflect off of the sides and rear of the block and toward the reflective element so as to provide a substantially uniform glow to the indicating light source or block when the illumination sources are activated.

Back plate **20** is molded or formed, such as by injection molding, so as to provide the display receiving portion **26** and a generally planar backing portion **20a** that attaches to the rear surface of the reflective element **18** (such as via adhesive or other suitable attachment means). Preferably, back plate **20**, including display receiving portion **26** and light baffle **30**, is molded of a substantially dark or opaque or black material, such as from an ABS or polycarbonate polymeric resin material or from any other suitable material such as known in the exterior rearview mirror art, so as to be substantially opaque such that light does not pass through the opaque back plate and the indicator mounting portion.

As shown in FIGS. 2, 5 and 6, indicator mounting portion **26** is unitarily or integrally formed with back plate **20** and may be formed with a pocket **26a** for receiving or partially receiving block **24** to locate indicating light source or block **24** at the generally planar backing portion **20a** of back plate **20**. For example, the pocket **26a** may receive indicating light source or block **24** at least partially therein, and the indicator mounting portion **26** may secure (such as by snapping or the like) the block at or in the pocket **26a** of indicator mounting portion **26** of back plate **20**.

Back plate **20** is formed (such as via injection molding or the like, such as injection molding of ABS or polypropylene or the like) with light baffle **30** at the pocket defined by mounting portion **26**. As can be seen with reference to FIGS. 2 and 5, light baffle **30** comprises a plurality of angled or slanted ribs or vanes or baffle elements **30a** that are separated or defined by gaps or slots or slits **30b** formed through the back plate **20**, whereby light from the light sources **28** is transmitted through the block **24** and through the gaps or slots **30b** at the back plate **20**. The baffle elements thus may be integrally formed with the back plate, with the slots being formed as openings or apertures or passageways through the generally planar back plate and between the baffle elements **30a**. As can be seen in FIGS. 2 and 5, baffle elements **30a** are integrally formed or molded with back plate **20** and are angled to direct or angle the light or allow the light passing through the slots to be viewed from a desired or appropriate direction, while shielding or shading the light or providing line of sight occlusion of the light so that the light is substantially not viewed from another direction. Optionally, the surfaces of the baffle elements **30a** (such as the surfaces facing partially toward the reflective element when the back plate is attached to the rear of the reflective element) may be

textured or stippled to diffuse or absorb light so as to reduce visibility of the baffle elements to a person viewing the reflective element when the signal indicating module is deactivated.

Optionally, and desirably, and as can be seen in FIG. 6, the baffle elements **30a** and slots or slits **30b** are substantially vertically oriented so as to be substantially vertical when the mirror assembly is mounted at the side of a vehicle (so as to shade or shield or limit viewability of light emanating from the indicator module in a generally horizontal direction). However, it is envisioned that the baffle elements and slots may be angled or canted (or non-vertical) depending on the particular application and desired shielding by the light baffle. In the illustrated embodiment of FIGS. 5 and 6, the generally vertical baffle elements are angled or slanted so that light emanating from indicator module **22** is viewable from a location outboard of the vehicle (such as for viewing of a turn signal indicator by a driver of a vehicle at the side of or rearward of the host vehicle), and is substantially non-viewable by the driver of the host vehicle. The angle or slant of the baffle elements may be selected depending on the particular application of the indicator module and on the location of the indicator module at the mirror assembly. For example, the baffle elements may be slanted so as to allow light to pass through the slots or gaps at an angle of about 65 degrees (or more or less) relative to the generally vertical plane of the back plate and reflective element (i.e., about 25 degrees outboard from a line extending perpendicularly from the plane of the back plate and reflective element). The baffle thus allows a person to view the indicator from an angle around 25 degrees outboard, yet substantially shields or provides direct line of sight occlusion to a person viewing the reflective element from another angle such as from within the vehicle, such as from a typical location of a driver's head.

Optionally, and desirably, the baffle elements may be formed to provide a minimum or reduced thickness while the gaps or slots are formed to allow a substantial amount of light from the glow block to pass therethrough, in order to enhance the viewability of the indicator along the targeted direction when the indicator is activated. For example, the baffle elements may be formed with a wall thickness of about 0.75 mm to about 1.1 mm (or more or less depending on the particular application), while the slots or gaps may be sized to each provide a passageway that is wider than the thickness of the baffle elements, such as about 1 mm to about 1.3 mm (or more or less depending on the particular application). The particular width of the baffle elements and slots or gaps may be selected to provide the desired viewability of light emanating from the indicator module in one direction, while shading or shielding or limiting viewability of the light from another direction, and thus may vary depending on the particular application of the indicator module and light baffle while remaining within the spirit and scope of the present invention.

Although shown in FIG. 6 as being a generally rectangular-shaped display region, the light baffle **30** and mounting portion **26** may be formed to provide the desired icon or indicator or display, such as a chevron shape or arrow shape or the like. Optionally, the light baffle and mounting portion may be formed as shown in FIG. 6, while the glow block or indicating light source may be formed to the desired shape such that the glow emanating from the indicating light source is viewable as the desired shape and from the desired or targeted direction (such an application may include a dark

or opaque layer or element at the rear of the light baffle and around the glow block to limit passage of light there-through).

For example, and as shown in FIG. 3, the glow block or indicating light source may have an arrow or chevron shape (and may be mounted at the mounting portion with the arrow pointing generally outward and away from the vehicle as shown in FIG. 1). The size of the block may be selected so that the light emanating therefrom (when the illumination source is activated) is readily viewable by the targeted viewer. For example, and as shown in FIG. 3A, the block may have a length (from the left tip in FIG. 3A to the right end of the block in FIG. 3A) of about 35 mm and a height of about 60 mm, with each leg being about 35 mm long and about 8 mm wide. The thickness of the block may be selected to provide the desired diffusion of the light from the illumination source so as to provide the desired glow by the block when the illumination source is activated. For example, the block may have a thickness t of about 15 mm (as shown in FIG. 4) so as to emanate the desired or appropriate diffuse light or glow when the illumination source is activated. Other size dimensions may be selected and may depend on the particular application of the block, without affecting the scope of the present invention.

Thus, the unitary back plate provides the mounting structure for mounting the signal indication module at the rear of the back plate and provides the light baffles or ribs or elements for directing the light from the signal indication module at a desired or appropriate direction toward and through the reflective element when the back plate (with the signal indication module attached thereto) is attached to the reflective element. As shown in FIG. 6, the indicator mounting portion **26** of back plate **20** is formed around the light baffle **30** of back plate **20**, so as to generally frame or surround the light baffle, whereby the signal indication module is generally at or aligned with the light baffle when received in or mounted at the indicator mounting portion.

As shown in FIGS. 2, 5 and 6, an attachment element or elements **20b** (such as an annular ring or tab or annular prongs or annular snaps or the like) may be formed or established at the rear of the backing portion **20a** for attaching the back plate **20** and reflective element **18** to a mirror actuator (such as a mirror actuator as known in the art and/or as described in U.S. Pat. Nos. 7,080,914; 7,073,914; 6,916,100; 6,755,544; 6,685,864; 6,467,920; 6,362,548; 6,243,218; 6,229,226; 6,213,612; 5,986,364 and 5,900,999, which are hereby incorporated herein by reference herein in their entireties), which is adjustable or operable to adjust a viewing angle of mirror reflective element **18**. When the mirror reflective element is canted or angled partially toward the driver of the host vehicle (which is typically the orientation of the reflective element during use so as to provide a generally rearward field of view to the driver of the host vehicle), there is sufficient space within the mirror casing at or near the outboard portion of the mirror assembly for the indicator mounting portion and signal indication module. The back plate and signal indication module of the present invention thus utilizes the space within the mirror head or casing that is already available and typically not used or occupied by other components.

Illumination source or sources **28** is/are operable or activatable or energizable to provide illumination at and through indicating light source or block **24**, whereby the illumination is transmitted through indicating light source or block **24** and through the slots **30b** of light baffle **30** of back plate **20** and through the reflective element **18** so as to be viewable through mirror reflective element **18** by a person

viewing the mirror assembly **10**. Preferably, the width of the slots are made so as to enhance or optimize light transmission through the light baffle of the back plate, whereby the baffle elements may be formed to be substantially thin. The signal indication module **22** may comprise a blind spot or object detection indicating device or module that is operable to indicate to the driver of the subject or host vehicle that an object or other vehicle is detected at the side or blind spot region of the host vehicle by a blind spot detection system (or may comprise a turn signal indicating device or module that is operable to indicate to the driver or passenger of another vehicle that the vehicle is turning or changing lanes, or may comprise other forms or types of display or illumination or indicating devices or modules, as discussed below).

Illumination source **28** (such as one or more light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) or the like) is/are energized to direct or emit illumination through indicating light source or block **24** so that the indicator/light is viewable through the reflective element. The indicating light source or block **24** and/or light baffle **30** may be formed to provide a desired shape for viewing of the light passing through the reflective element or the mirror reflective element may include one or more iconistic display areas so that the illumination is viewable and discernible at the reflective element by the desired or targeted viewer, depending on the angle of the ribs or baffle elements **30a** of light baffle **30**. The mirror assembly thus may provide an iconistic display for an object detection/LCA system and/or an iconistic display for a turn signal indication, and/or may provide other displays or illumination devices, without affecting the scope of the present invention. Optionally, the baffle elements may be painted or coated with a diffuse reflecting layer or paint or coating to enhance the intensity of the light emanating from the light baffle and through the reflective element. Optionally, and desirably, however, the baffle elements may be dark colored and may include textured surfaces to substantially absorb light so as to reduce visibility of the light baffle through the reflective element when the illumination source is deactivated.

Preferably, the mirror reflective element **18** comprises a transmissive display on demand reflective element that is partially transmissive and partially reflective, so that the light emanating or glowing from the block may be transmitted through the reflective element when the illumination source is activated, but the indicator and light baffle is substantially non-visible or viewable when the illumination source is deactivated. Optionally, the mirror reflective element **18** may comprise a single substrate or non-electro-optic reflective element (such as shown in FIG. 2), which has a glass substrate **34** with a translector coating or layer **36** at its forward surface **34a**. For example, the translector coating or layer **36** may comprise an elemental semiconductor coating, such as a silicon-based coating, or may comprise a multilayer stack of non-conducting or poorly conducting but highly transparent thin film coatings (such as metal oxides, such as silicon dioxide or titanium dioxide or zirconium oxide, or metal halides, such as magnesium fluoride), and where the outermost layer of such a stack that is in contact with any electro-optic medium, such as an electrochromic medium, is electrically conducting, and preferably comprises an indium tin oxide layer of sheet resistance in the range of about 5 ohms-square to about 20 ohms-square range, or the translector coating or layer **36** may comprise a metal oxide/metal/metal oxide stack (with at least one of the metal oxide layers comprising a conducting or semiconducting layer), such as an IMI (such as ITO/silver/ITO or

ITO/silver alloy/ITO or other suitable alternating layers of materials or the like) stack of layers or coatings such as by utilizing aspects of the reflective elements described in U.S. Pat. Nos. 6,690,268; 5,668,663 and/or 5,724,187, and/or in U.S. patent application Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; Ser. No. 10/533,762, filed May 4, 2005, now U.S. Pat. No. 7,184,190; and/or Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451, which are all hereby incorporated herein by reference in their entireties. Optionally, the reflective element may comprise an electro-optic, such as electrochromic, reflective element, such as discussed below.

Optionally, a heater pad **38** may be provided at the rear surface **34b** of the glass substrate **34** of reflective element **18** and between the backing portion **20a** of back plate **420** and the reflective element **18** to provide an anti-fogging or de-fogging feature to the exterior mirror assembly (such as by utilizing aspects of the heater elements or pads described in U.S. patent application Ser. No. 11/334,139, filed Jan. 18, 2006, now U.S. Pat. No. 7,400,435, which is hereby incorporated herein by reference in its entirety). The back plate and/or heater pad may include suitable electrical connectors and connections incorporated therein (such as by utilizing aspects of the mirror assembly described in U.S. patent application Ser. No. 11/334,139, filed Jan. 18, 2006, now U.S. Pat. No. 7,400,435, which is hereby incorporated herein by reference in its entirety) for electrically connecting the heater pad and/or display element (or other suitable electrical connectors may be utilized, such as electrical leads or wire harnesses or pigtailed or other separate connectors or cables or the like). The heater pad **38** includes a hole or opening or aperture **38a** therethrough (or optionally a window or transparent or translucent or diffuse portion of the heater pad, such as a clear or diffusing transparent polyester flexible plastic film or element) that generally corresponds to the light baffle **30** of back plate **20** when the heater pad **38** is attached to the rear surface **34b** of glass substrate **34** and when the back plate **20** is attached to the rear surface of the heater pad **38**. Optionally, and desirably, the heater pad **38** may include an adhesive layer (such as a pressure sensitive adhesive layer) at its rear surface for adhering the back plate **20** to the heater pad **38** and thus to the rear surface **34b** of the glass substrate **34** of the reflective element **18**. As shown in FIG. 2, back plate **20** is adhered to heater pad **38** such that indicator mounting portion **26** and light baffle **30** are positioned or located generally at the aperture **38a** of heater pad **38** so as to be generally at the display area of the reflective element.

Optionally, the back plate may include a perimeter framing portion or bezel portion that extends around the perimeter edges of the reflective element to support the reflective element and frame the reflective element at the mirror assembly (such as by utilizing aspects of the mirror assemblies described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, which is hereby incorporated herein by reference in its entirety). The perimeter bezel portion may be narrow or small depending on the particular application of the reflective element and mirror reflector sub-assembly. Optionally, the mirror reflector sub-assembly may comprise a bezelless or frameless reflective element (such as the types described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008; Ser. No. 10/533,762, filed May 4, 2005, now U.S. Pat. No. 7,184,190; and/or Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451, and/or PCT Application No. PCT/US2006/018567, filed May 15, 2006 and

published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties), whereby the back plate may not include a perimeter framing portion or bezel portion around the perimeter of the reflective element.

Optionally, and preferably, indicator element or display element or signal indication module **22** may snap into or may be threaded into the end or pocket of the indicator mounting portion **26** or may otherwise be attached or stuck at the indicator mounting portion, and may have a gasket or seal at the signal indication module to provide a substantially water proof or water resistant or water tight seal at the signal indication module, whereby the signal indication module may be sealed at the indicator mounting portion, such as by gluing or pressing or screwing or gasketing or hermetically sealing or otherwise substantially sealing the signal indication module at the indicator mounting portion. The signal indication module may comprise a self-contained, unitary, sealed or substantially sealed, indicator module that includes the translucent block, an illumination source (such as one or more LEDs or the like), a DC converter with a voltage dropping resistor (such as described in U.S. Pat. Nos. 6,902,284 and 6,690,268 and/or U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381, which are hereby incorporated herein by reference in their entireties). The signal indication module thus may be connected to a power source and may be activated or energized to illuminate the display for viewing by the driver of the vehicle. Optionally, the electrical connections to the signal indication module may be made while the signal indication module is attached to the mirror assembly, such as via a plug and socket type arrangement or configuration, and such as by utilizing aspects of the mirror assembly described in U.S. Pat. No. 6,669,267, which is hereby incorporated herein by reference in its entirety. The unitary signal indication module may include or utilize aspects of various light modules or systems or devices, such as the types described in U.S. Pat. Nos. 6,227,689; 6,582,109; 5,371,659; 5,497,306; 5,669,699; 5,823,654; 6,176,602 and/or 6,276,821, and/or U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, and/or PCT Application No. PCT/US2006/018567, filed May 16, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties.

Optionally, the signal indication module may be supplied or provided to an assembly facility (such as a mirror assembly facility or the like) from a module supplier while the back plate may be supplied or provided to the assembly facility from a back plate supplier. An operator at the assembly facility may attach the module to the back plate, preferably by snapping or pressing the module to the back plate to assemble the module to the back plate (whereby the module may have a snug fit within the receiving portion or pocket such that the module and back plate are preferably substantially water impervious). Optionally, and desirably, electrical connection (such as to a power supply or 12 volt power wire of the vehicle battery/ignition system or to a power feed from a LIN bus controller) to the module may be made when the module is snapped or otherwise attached (preferably mechanically but optionally adhesively) to the back plate (such as by making electrical contact between the module and mirror circuitry [including circuitry associated with the reflective element and/or mirror assembly, such as electrochromic mirror circuitry, mirror lights and display circuitry and the like, typically disposed at a printed circuit board of the mirror assembly] when the module is snapped

to the back plate, such as by press attaching the display module into receiving fingers or clips or snaps or the like that are integrally formed with the back plate in the injection molding operation that manufactures or forms the back plate itself) or alternately, electrical connection to the module may be made via other means, such as wires or leads or the like before or after the module is snapped or attached to the back plate.

Optionally, and as shown in FIGS. 7 and 8, a reflective element assembly **12'** includes a reflective element **18'** and a back plate **20'**, which includes a plurality of angled baffle elements **30a'** of a light baffle **30'**. Back plate **20'** includes an attachment element or snap element **26a'** for attaching to or snapping to a corresponding attachment element or snap element **26b'** of a signal indicating module **22'** to attach or support signal indicating module **22'** at the rear of back plate **20'** and at and rearward of light baffle **30'**. The attachment element **26a'** may be integrally formed at the rear of the back plate **20'** (such as during the integral molding formation of the back plate itself and such as via an injection molding tool or the like) and at or near baffle elements **30a'** of light baffle **30'** of back plate **20'**, while attachment elements **26b'** may be integrally formed or otherwise established at a forward surface of signal indicating module **22'**. Although described as snaps or snap elements, other mechanical or adhesive means may be utilized to attach the signal indicating module to the back plate, while remaining within the spirit and scope of the present invention. Thus, the signal indicating module **22'** may be mounted to or supported at the rear surface of the light baffle **30'** (and may be substantially parallel to the rear surface of the reflective element **18'** or to the generally planar portion **20a'** or rear surface of the back plate **20'**). Back plate **20'** may also include a mounting portion **20b'** for mounting or attaching the back plate **20'** to a mirror actuator (not shown), such as described above.

Signal indication module **22'** includes a transparent or translucent polymeric block or element or indicating light source or element **24'** and an illumination source or indicator **28'**, such as one or more light emitting diodes (LEDs) or other suitable illumination source, such as described above. In the illustrated embodiment, signal indicating module **22'** comprises a rhombus-shaped or parallelogram shaped element having a transparent or translucent optical plastic block **24'** at least partially surrounded by or encased by side walls **25'**. The optical block **24'** may be light reflecting or light absorbing or light diffusing depending on the particular application and desired lighting effect for the signal indicating module. Optionally, the optical block may be cast or injection molded from an optical light transmitting polymeric resin, such as a polycarbonate or an acrylic, or an acrylate, or a polystyrene, or a CR-39 or a COC olefin or other suitable material. The block may be molded as a translucent element, and may comprise a material that is at least partially crystalline, or the material may have a light scattering material mixed therein, or may be otherwise selected so as to provide a diffuse block, whereby the illumination emitted by the illumination source or LED will emanate from the forward surface of the block as a substantially uniform glow. The translucent diffuse block or element may be formed to a desired or suitable shape, such as described above, so as to provide the desired form for viewing by the driver of the vehicle.

Signal indication module **22'** includes a circuit element **32'**, such as a printed circuit board or the like (such as a rigid or flexible circuit board or element), with illumination sources or LEDs **28'** disposed thereat (such as surface mounted or otherwise disposed LEDs or other suitable or

equivalent light sources). Circuit element 32' is attachable to a rear surface 24a' of indicating light source or block 24', whereby the illumination sources 28' are located at the rear surface and preferably at or partially within light source receiving apertures or recesses 24b' at the rear surface 24a' of indicating light source or block 24'. The signal indication module 22' may be purchased as a display element assembly or module (including the circuit element and circuitry, which are attached at the rear of the indicating light source or block 24') and assembled to the mirror reflective element sub-assembly 12', such as at a mirror assembly facility, and such as via snapping the attachment elements 26a' and 26b' together to attach the signal indicating module 22' at the rear of the back plate 20' and generally at light baffle 30' molded or formed as part of the back plate 20'. Circuit element 32' preferably includes an electrical connector or lead or terminal for electrically connecting the circuitry and light source to electrical power or electrical control at the mirror assembly when the signal indication module is attached to the back plate and installed at the mirror casing.

Thus, signal indicating module 22' provides an angled shape with the side walls 25' being angled generally along a similar angle as the angle of the baffle elements or vanes 30a' of light baffle 30'. For application as a turn signal indicator, the angle of the vanes 30a' is selected so that the vanes 30a' are generally canted toward or directed toward the portion of the roadway adjacent to the side of the vehicle to which the exterior rearview mirror assembly utilizing signal indicating module 22' is mounted, and where the driver of an overtaking vehicle generally adjacent to the equipped vehicle would readily observe the indication. Alternatively, should the indicator be a blind spot indicator, the angle of the vanes or baffle elements may be selected so that the vanes are generally canted toward or directed toward the side of the vehicle to which the exterior rearview mirror assembly utilizing the signal indicating module is mounted, and where the driver of the equipped vehicle would readily observe the indication or alert provided by the indicating module.

The parallelogram shape of signal indicating module 22' provides the angled side walls 25' while providing a rear surface 24a' of optical block 24' that is generally parallel to the generally planar back plate 20', such that the non-angled rear surface of the optical block 24' may have a reduced depth into the mirror casing so as to be more readily packaged within the mirror assembly. The optical block 24' may be formed to the desired shape and the outer side walls 25' may be formed or established or coated therearound, such as via overmolding techniques or painting or the like, or the outer side walls 25' may be formed and the optical block 24' may be molded or injected or established therein, such as via a separate molding process or co-injection molding process or the like. The inner surfaces of the outer side walls 25' may have a surface treatment or characteristic, such as by decoration or treatment, such as by coatings or paints or the like, or such as by physical establishment, such as grain, stipple, pits/light traps or the like established during the molding of the plastic elements themselves, to provide the desired reflectivity/diffusivity of the signal indicating module 22'. Optionally, a cover or seal or the like may be provided at least partially around the signal indicating module to cover and/or substantially seal the circuit element and optical block at and within the signal indicating module. The signal indicating module thus provides a self-contained module or device that may be readily attached to the mirror back plate and readily connected to electrical wiring or leads of the mirror assembly.

In the illustrated embodiment, reflective element 18' comprises an electrochromic reflective element (but could comprise a non-electrochromic reflective element without affecting the scope of the present invention) having a front substrate 40, a rear substrate 42 and an electrochromic medium 43 (such as a solid polymer matrix electrochromic medium or the like) sandwiched therebetween and sealed via a perimeter seal 44. Front substrate 40 has a transparent conductor coating 46 (such as an indium tin oxide (ITO) coating or layer) disposed at its rear surface 40a, while rear substrate 42 has a translector coating 48 (such as a non-dichroic translector, such as an ITO/Ag/ITO stack of layers or coatings or the like) disposed at its front surface 42a. Optionally, the reflective element may include a perimetal metallic reflector band 50 (such as chromium or other suitable material), such as by utilizing aspects of the reflective elements described in U.S. patent application Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; Ser. No. 10/533,762, filed May 4, 2005, now U.S. Pat. No. 7,184,190; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008, which are all hereby incorporated herein by reference in their entireties. In the illustrated embodiment, the metallic reflector band 50 is disposed at the rear surface 40a of front substrate 40, with the transparent conductor coating 46 overlapping the band 50 at the perimeter regions of the reflective element, but the reflector band may otherwise be disposed over the transparent conductor, depending on the particular or selected or desired tint or appearance of the metallic perimeter band.

Mirror reflector sub-assembly 12' also includes a heater pad 38 disposed between back plate 20' and the rear surface 42b of rear substrate 42. As shown in FIGS. 7 and 8, heater pad 38 has an aperture 38a formed therethrough that generally corresponds with the light baffle 30' of back plate 20' when the heater element is attached or adhered to the back plate. Optionally, and desirably, an opacifying element or layer or coating or film 52 (such as black or dark color, such as dark blue or dark grey, paint or ink or film or coating or tape or lacquer or the like, and preferably a dark, light-absorbing layer that is printed or screened onto the fourth or rear surface of the electrochromic reflective element or cell) may be disposed between heater element 38 and rear surface 42b of rear substrate 42. The dark or opacifying layer may be established via any suitable establishing methods or means, such as painting, printing, ink jet printing, pad printing, screening or the like.

Optionally, and with reference to FIGS. 9 and 10, a reflective element assembly 12" includes a reflective element 18" (such as similar to the reflective element described above) and a back plate 20". Back plate 20" includes an attachment element or snap element 26a" for attaching to or snapping to a corresponding attachment element or snap element 26b" of a signal indicating module 22" to attach or support signal indicating module 22" at the rear of back plate 20" and at and rearward of an aperture 20a" formed through back plate 20". The attachment element 26a" may be integrally formed at the rear of the back plate 20" and at or near aperture 20a" of back plate 20", while attachment elements 26b" may be integrally formed or otherwise established at a forward surface of signal indicating module 22". Thus, the signal indicating module 22" may be mounted to or supported at the rear surface of the back plate 20" (and may be substantially parallel to the rear surface of the reflective element 18' or to the generally planar portion 20a" or rear surface of the back plate 20"). Back plate 20" may also

include a mounting portion **20b**" for mounting or attaching the back plate **20**" to a mirror actuator (not shown), such as described above.

As shown in FIGS. **9** and **10**, signal indicating module **22**" includes a transparent or translucent polymeric block or element or indicating light source or element **24**" disposed at least partially within an outer casing or shell **25**", and an illumination source or indicator **28**", such as one or more light emitting diodes (LEDs) or other suitable illumination source, disposed at the rear surface **24a**" of the optical block **24**". Similar to signal indicating module **22**", discussed above, signal indicating module **22**" comprises a rhombus-shaped or parallelogram shaped element having a transparent or translucent optical plastic block **24**" at least partially surrounded by or encased by outer shell **25**". Optionally, the signal indicating module or shell or element may be any suitable or desirable or appropriate shape (at least at its terminal portion closest to the rear of the reflective mirror element) to provide a desired indicator or icon as seen by a person viewing from the front of the reflective mirror element when the signal indicator is activated. For example, the signal indicating module or tube or shell or element may comprise a triangular-shaped tube or element for providing a triangular-shaped indicator or icon, such as for a signal indicative of a hazard signal of the vehicle being activated, or may be any other shape as desired.

In the illustrated embodiment, outer shell **25**" includes side walls **25a**" and a forward surface or portion **25b**", which includes a light baffle **30**" molded as part of the outer shell. As shown in FIGS. **9** and **10**, forward portion **25b**" of outer shell **25**" has the light baffle **30**" (which includes a plurality of baffle elements or vanes **30a**" formed at an angle relative to the planar forward surface of the forward portion **25b**" with slots formed between the vanes for light from the illumination source **28**" to pass therethrough) integrally formed therewith. Although shown in FIGS. **9** and **10** as extending partially along the depth of the outer shell **25**", the baffle elements **30a**" may extend substantially the entire depth of the shell **25**" so that a rearward end or region of the baffle elements is generally at or near the rear surface of the optical block **24**" when the optical block **24**" is established within shell **25**", as discussed below. Optionally, the baffle elements or vanes **30a**" may be formed with apertures or holes therethrough to allow light from within optical block **24**" (such as at the sides of the baffle) to pass through the vanes **30a**" to enhance the light emanating from the forward portion of the signal indicating module when the illumination source is activated. The vanes at either or both sides of the baffle portion may have more holes or apertures therethrough, while the inner vanes may not have holes therethrough, in order to provide the desired degree of light emanating from the signal indicating module. The forward portion **25b**" of shell **25**" further includes attachment elements **26b**", such as receiving portions for receiving the attachment elements **26a**" of back plate **20**".

Optionally, the outer shell **25**" may be molded of a plastic or polymeric material, such as a dark plastic resin or a light or white plastic resin or the like, and the inner surfaces of the side walls **25a**" may have a surface treatment or characteristic, such as stippling or texturing or coating or the like (such as discussed above), established thereon. The optical block **24**" may be formed via a separate injection molding process or a co-injection molding process, wherein the polymeric material of the optical block (such as a polycarbonate or acrylic material or the like) may be injected or established within the side walls **25a**" of outer shell **25**" and within the slots between the baffle elements **30a**". Option-

ally, the tube or shell or element or side walls of the tube or shell or element may be lined with a visible light highly reflecting material (such as by being formed at least partially of a bright reflecting material and/or by being coated or painted or decorated with a bright reflecting material and/or by being sleeved with a highly reflecting metal thin film or foil or coating) so as to enhance passage of light down along the tube or shell or element and so as to enhance the luminance of the displayed hazard or other indication as viewed by a person viewing the mirror assembly when the illumination source is activated and when being viewed such as on a bright sunny day where display wash-out might be a concern, or the tube or shell or side walls of the tube or shell or element may only have the distal part or portion (the portion or end region of the shell that is further away from the rear surface of the reflective element and toward or at the illumination source) be reflective (which may be specularly reflective, such as from a metal coating or foil, and/or may be diffusely reflective, such as from a white paint or pigment or from an Argent paint or coating), while the rest of the tube or shell or element, or side walls of the shell or tube or element, closest to the terminal end at the rear of the mirror reflective element are substantially not reflecting or are light absorbing or black or the like, in order to enhance the directionality of the light emitted by the indicator module.

The illumination source **28**" or circuit element **32**" (such as a printed circuit board or the like) may be attached or snapped to the rear of the module, such as to the rear surface **24a**" of the optical block **24**" or to a rear attachment portion of the outer shell, whereby the illumination sources **28**" are located at the rear surface of the optical block and preferably at or partially within light source receiving apertures or recesses **24b**" at the rear surface **24a**" of optical block **24**". The circuit element **32**" may include electrical connectors or terminals for connecting the signal indicating module **22**" to electrical leads of the mirror assembly when the reflective element assembly **12**" is installed at or in a mirror assembly.

Optionally, a cover or seal or the like may be provided at least partially around the signal indicating module to cover and/or substantially seal the circuit element and optical block at and within the signal indicating module (or the signal indicating module may be otherwise substantially sealed) so that the signal indicating module may be substantially water impervious. The signal indicating module thus provides a self-contained module or device that may be readily attached to the mirror back plate and readily connected to electrical wiring or leads of the mirror assembly. Advantageously, the substantially sealed signal indicating module may be brought in or installed as a single or unitary module with sealed elements and mechanical connections and electrical connectors pre-established as part of the sealed unitary signal indicating module. Thus, the mechanical connectors or elements or connections may mechanically connect to the mirror back plate, and the electrical connectors may be electrically connected to electrical wiring or leads of the mirror assembly when the sealed, self-contained signal indicating module is installed at or in or at least partially in the exterior rearview mirror assembly.

Thus, signal indicating module **22**" provides an angled shape with the side walls **25a**" of the outer shell **25**" being angled generally along a similar angle as the angle of the baffles or vanes or elements **30a**" of light baffle **30**" of outer shell **25**" of signal indicating module **22**". The parallelogram shape of signal indicating module **22**" provides the angled side walls **25**" while providing a rear surface **24a**" of optical block **24**" that is generally parallel to the generally planar back plate **20**", such that the non-angled rear surface of the

optical block **24**" may have a reduced depth into the mirror casing so as to be more readily packaged within the mirror assembly with a reduced packing density within the mirror assembly.

The signal indicating module of the present invention (such as, for example, as shown in FIGS. **9** and **10**) provides an economical and effective signal indicator without requiring the expense or complexity of providing a lens or other optical device that receives the light from the light assembly and emits it in a given direction as parallel rays. Thus, no collimating optical element, or equivalent thereof, is utilized or needed in the construction of the signal indicating module of the present invention. The present invention provides a semi-transparent mirror reflective element (having a substrate with a coating on one surface that is substantially transparent and reflective at any given point, e.g., a half-silvered or one way mirror) without any discreet apertures or individual apertures in the substantially continuous and uninterrupted reflector utilized. Thus, there are no identifiable gaps in the mirror coating through which light from the light assembly transmits.

Accordingly, the signal indication module **22**" may be purchased as a display element assembly or module (including the circuit element and circuitry, which is/are attached at the rear of the block **24**" and assembled to the mirror reflective element sub-assembly **12**", such as at a mirror assembly facility, and such as via snapping the attachment elements **26a**" and **26b**" together to attach the signal indicating module **22**" at the rear of the back plate **20**" and generally at aperture **20a**" of back plate **20**". Circuit element **32**" preferably includes an electrical connector or lead or terminal for electrically connecting the circuitry and light source to electrical power or electrical control at the mirror assembly when the signal indication module is attached to the back plate and installed at the mirror casing.

Optionally, and as shown in FIGS. **11** and **12**, a back plate **120** may include an attachment element or indicator receiving portion **126** that has an angled or canted or slanted surface for receiving or supporting a signal indicating module **122** thereat. The indicator receiving portion **126** is integrally formed at the rear of the angled baffle elements **130a** of a light baffle **130** of back plate **120**. Thus, the signal indicating module **122** may be mounted to or supported at the canted surface **120c** of the light baffle **130**, such that the indicating light source or block **124** is angled relative to the generally planar backing portion **120a** of back plate **120**. Back plate **120** may also include a mounting portion **120b** for mounting or attaching the back plate **120** to a mirror actuator (not shown), such as described above.

In the illustrated embodiment of FIGS. **11** and **12**, the signal indicating module **122** includes a transparent or translucent indicating light source or glow block **124** (such as similar to block **24** described above) and a light source **128** at the rear of indicating light source or block **124**. The light source **128** is preferably a power LED, such as of the types described in U.S. patent application Ser. No. 10/054, 633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381, which is hereby incorporated herein by reference in its entirety. Illumination emitted by the power LED is directed through indicating light source or block **124** (which may have reflecting rear and side surfaces as described above) and is transmitted through slots **130b** of light baffle **130**, and is shaded or shielded from view from another angle via baffle elements **130a**, such as in a similar manner as described above. Because the signal indicating module **122** and back plate **120** may be otherwise substantially similar to the signal indicating module **22** and back plate **20** described

above, a detailed discussion of the modules and back plates need not be repeated herein. Because the block comprises a translucent diffusing block, the illumination emitted by the power LED is transmitted through the block (and preferably reflected off of the sides and rear of the block as described above) such that the light emanating from the block is viewed as a substantially uniform glow and not as a point source of light.

In the illustrated embodiment, the slots **130b** and baffle elements **130a** are angled through indicator mounting portion **126** and are generally normal to block **124**. As can be seen in FIG. **11**, the slots and baffle elements are angled outward and away from the host vehicle and away from the driver of the host vehicle. The light source **128** is located at block **124** (such as at a circuit element or board or the like), which is at or near the end of the slots **130b** so that light emitted by light source **128** is emitted through slots **130b** and away from the view of the driver of the host vehicle sitting in the vehicle cabin. The angle of the rear surface and/or the slots and baffle elements may be selected to provide the desired angle of the light path as the light exits the indicator receiving portion, depending on the particular application of the signal indicating module and reflective element sub-assembly. The light baffle may be established to provide the desired indicator form or shape, such as a chevron shape or arrowhead shape or other suitable shape or form, and may be readily viewable and discernible and recognizable when the light source is activated. Because the back plate **120** and indicator receiving portion **126** of back plate **120** are substantially opaque, the slots and block and light source are not readily viewable and discernible when the light source is deactivated. Optionally, the surfaces of the baffle elements **130a** (such as the surfaces facing partially toward the reflective element when the back plate is attached to the rear of the reflective element) may be textured or stippled to diffuse or absorb light so as to reduce visibility of the baffle elements to a person viewing the reflective element when the signal indicating module is deactivated.

Optionally, and with reference to FIG. **13**, a mirror reflector sub-assembly **112** may comprise back plate **120**, a signal indicating module **122'** and an electro-optic (such as electrochromic) reflective element **118**. Back plate **120** is substantially similar to the back plate of FIGS. **11** and **12**, and receives or supports signal indicating module **122'** at the angled or canted surface **120c** of the back plate **120** at the rear of the light baffle **130**. In the illustrated embodiment, signal indicating module **122'** includes a indicating light source or block **124'** and an illumination source **128'**, which may comprise a power LED or the like. As shown in FIG. **13**, illumination source **128'** may be located at or in (such as recessed in) a side portion or surface **124c'** of indicating light source or block **124'**. The rear surface **124a'** and side surfaces **124c'** of indicating light source or block **124'** may be coated or painted so as to have reflective surfaces, such as described above. Thus, the light emitted by the light source **128'** at the side of the indicating light source or block **124'** is reflected off of the side and rear surfaces of the block and is transmitted through the block and through and along the slots **130b** of light baffle **130** and through the reflective element **118**.

In the illustrated embodiment, reflective element **118** comprises an electrochromic reflective element having a front substrate **140**, a rear substrate **142** and an electrochromic medium **143** (such as a solid polymer matrix electrochromic medium or the like) sandwiched therebetween and sealed via a perimeter seal **144**. Front substrate **140** has a transparent conductor coating **146** (such as an indium tin

oxide (ITO) coating or layer) disposed at its rear surface **140a**, while rear substrate **142** has a transflector coating **148** (such as a non-dichroic transflector, such as an ITO/Ag/ITO stack of layers or coatings or the like) disposed at its front surface **142a**. Optionally, the reflective element may include a perimetal metallic reflector band **150** (such as chromium or other suitable material), such as by utilizing aspects of the reflective elements described in U.S. patent application Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; Ser. No. 10/533,762, filed May 4, 2005, now U.S. Pat. No. 7,184,190; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008, which are all hereby incorporated herein by reference in their entireties. In the illustrated embodiment, the metallic reflector band **150** is disposed at the rear surface **140a** of front substrate **140**, with the transparent conductor coating **146** overlapping the band **150** at the perimeter regions of the reflective element, but the reflector band may otherwise be disposed over the transparent conductor, depending on the particular or selected or desired tint or appearance of the metallic perimeter band.

Mirror reflector sub-assembly **112** also includes a heater pad **138** disposed between back plate **120** and the rear surface **142b** of rear substrate **142**. As shown in FIG. **13**, heater pad **138** has an aperture **138a** formed therethrough that generally corresponds with the light baffle **130** of back plate **120** when the heater element is attached or adhered to the back plate. Optionally, and desirably, an opacifying element or layer or coating or film **152** (such as black or dark color, such as dark blue or dark grey, paint or ink or film or coating or tape or lacquer or the like, and preferably a dark, light-absorbing layer that is printed or screened onto the fourth or rear surface of the electrochromic reflective element or cell) may be disposed between heater element **138** and rear surface **142b** of rear substrate **142**. The dark or opacifying layer may be established via any suitable establishing methods or means, such as painting, printing, ink jet printing, pad printing, screening or the like.

Optionally, and with reference to FIG. **14**, the reflective element **118'** may include an anti-reflection layer or layers **154** disposed at the front surface **140b** of front substrate **140** to reduce reflection of light incident on the reflective element. The anti-reflection layer/layers **154** may be deposited at the front surface of the front substrate during a pyrolytic deposition process. For example, the anti-reflection layer (such as an OPTIVIEW™ layer such as commercially available from Pilkington) may be deposited pyrolytically in a glass manufacturing plant where the anti-reflection layer may be formed by deposition onto the glass surface at the glass float-line itself when the glass ribbon is first being formed from the molten glass raw materials (where the red-hot molten glass exiting the glass furnace is floated onto a tin bath and where the coating materials or gasses or precursors are blown onto the red hot glass ribbon prior to it cooling to form the glass sheet, i.e., while the glass exits the tin bath and while it is still in a very hot condition to form the anti-reflection coatings on the glass surface by pyrolytic chemical reaction of the gaseous precursors as they are incident on the red-hot glass surface). It is envisioned that the conductive coating may also or otherwise be disposed or deposited at the surface of the glass via a pyrolytic deposition process, such as by utilizing aspects described in PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which is hereby incorporated herein by reference in its entirety. Because the other components or

elements of mirror reflective element **118'** and mirror reflector sub-assembly **112'** may be substantially similar to those of reflective element **118** and sub-assembly **112**, discussed above, a detailed discussion of the reflective elements and sub-assemblies need not be repeated herein. The similar or common elements of the reflective elements and sub-assemblies are shown in FIGS. **13** and **14** with like reference numbers.

Although it is known to dispose an anti-reflection coating or layer at a first surface of a reflective element (such as described in U.S. Pat. No. 5,076,674, which is hereby incorporated herein by reference in its entirety), such coatings have not to date achieved commercial success due to the costs associated with such coatings. The prior concerns can be overcome utilizing a glass substrate or sheet that is coated with a durable and preferably bendable and most desirably temperable anti-reflection means. Preferably, such material is deposited pyrolytically in a glass manufacturing plant and as the glass ribbon being formed (and while still a red hot glass ribbon) is exiting the float bath (typically floating on molten tin). The bendability and temperability of the coated glass so formed via an in-float pyrolytic deposition process when the flat glass sheet is itself being made at the glass sheet manufacturing plant also allows the glass to be purchased in flat glass sheets and formed or cut and bent at a later time, such as by the mirror manufacturer.

Such pyrolytically coated glass provides a durable, bendable and temperable substrate that provides reduced reflectance of light incident thereon when the so-coated surface is used as the first surface in an EC mirror cell construction. For example, such coated glass preferably transmits at least 90 percent of visible light and has a first surface reflectance of less than 2 percent, more preferably less than 1 percent and more preferably less than 0.75 percent (broadly across the visible light spectrum). Such pyrolytic deposited coatings and coated substrates provide durable, bendable and temperable anti-reflection means, and preferably also have a low ultraviolet (UV) light transmission. For example, such coated glass may typically pass less than about 1 percent of solar UV energy therethrough (by comparison, clear float glass typically passes about 62 percent of solar UV energy therethrough).

Because the coated glass is durable, bendable and temperable, the mirror reflector manufacturer may purchase the coated glass in flat sheets and may cut and/or form and/or bend and/or temper the glass to make the desired or appropriately shaped mirror substrates or shapes. Also, because the coated glass provides a reduced reflectance at the first surface of the reflective element, a reflectance of light incident on the mirror reflective element of only about 4 to 5 percent (as measured in accordance with SAE J964a, which is hereby incorporated herein by reference in its entirety) can be achieved when the electrochromic mirror is dimmed to its maximum level (according to the applied voltage for the particular unit, typically about 1.2 to 1.4 volts and typically about 1.25 volts, when applied to the conductive coatings of the substrates of the reflective element). By comparison, typical interior and exterior rearview mirrors may dim to a minimum reflectance of light incident thereon that is at about 5 to 8 percent when the electrochromic mirror is dimmed to its maximum level. Optionally, the anti-reflection coating or layer may be disposed at the first or front surface of the reflective element utilizing aspects of the reflective elements described in U.S. Pat. No. 5,076,674, which is hereby incorporated herein by reference in its entirety.

Thus, the mirror reflective element of the present invention may provide a reduced reflectivity at the reflective element when the electro-optic reflective element is at its maximum dimming state. The mirror reflective element may be configured to provide the desired reflectivity at the maximum dimmed state (such as a photopic reflectance of light incident thereon of at least about 4 percent and at most about 5 percent), and the optical characteristics or properties may be selected or configured to attain the desired range of reflectivity. For example, the first surface anti-reflectivity coating (such as properties thereof) may be selected or adjusted, and/or the thickness of the transparent conductor coating (such as ITO) may be selected or adjusted, and/or the reflectivity of the third surface translector coating may be selected or adjusted, and/or the type or thickness of the electrochromic medium itself may be selected or adjusted to adjust or reduce the reflectivity of the mirror to the desired range when the mirror reflector is at its fully dimmed state. For example, if a mirror reflective element provides about 3 percent reflectance of light incident thereon, the mirror manufacturer may reduce the thickness of the electrochromic medium to increase the reflectance to about 4 percent or more, while keeping the reflectance at or below 5 percent of light incident thereon.

Optionally, the back plate may have two or more indicator display elements or modules mounted thereto, such as in a similar manner as described above. For example, a light baffle may be formed at an outboard portion of the back plate (away from the vehicle when the mirror assembly is mounted at the side of the vehicle) and may have the baffle elements angled so as to direct the light or glow from the block generally outwardly so as to not be readily viewable by the driver of the vehicle and, thus, to provide a turn signal indicator at the exterior mirror assembly, while another light baffle may be formed at an inboard portion of the back plate (toward the vehicle when the mirror assembly is mounted at the side of the vehicle) and may have the baffle elements angled so as to direct the light or glow from the block generally inwardly so as to be readily viewable by the driver of the vehicle and, thus, to provide a blind spot alert or indicator for a side object detection system or blind spot detection system or lane change assist system or the like. The indicators or display modules may be substantially similar to those described above, or may utilize aspects of the indicator modules described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, and/or PCT Application No. PCT/US2006/018567, filed May 16, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, and/or U.S. provisional application Ser. No. 60/857,025, filed Nov. 6, 2006, which are hereby incorporated herein by reference in their entireties.

For example, and with reference to FIGS. 15 and 16, a back plate 220 may include a turn signal indicator mounting portion 226a (such as at an outboard portion or region of the back plate) and a blind spot indicator mounting portion 226b (such as at an inboard portion or region of the back plate). In the illustrated embodiment, the turn signal indicator mounting portion 226a and signal indicating module 222a may be similar to mounting portion 126 and module 122 described above with respect to FIG. 11, and may include a translucent block or indicating light source or element 224 and illumination source 228a at a rear portion of the mounting portion 226a and generally at a light baffle 230 of back plate 220. Optionally, the blind spot indicator or alert module or element 222b at mounting portion 226b may utilize aspects of the indicator modules and mounting por-

tions described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, which is hereby incorporated herein by reference in its entirety. Briefly, such a mounting portion 226b may comprise a hollow tube 227 integrally formed with and extending from the rear of the back plate 220, and with a passageway extending therethrough or therealong, whereby the indicator module 222b is mounted at the rearward portion of the hollow tube 227. The indicator module 222b includes an illumination source or LED 228b that is operable to emit light into and along and through the passageway of the hollow tube 227 and toward and through the reflective element 218 (FIG. 16) for viewing by the driver of the vehicle. Back plate 220 also includes an actuator mounting portion 220b for attaching the back plate and reflective element to a mirror actuator for providing adjustment of the reflective element by the driver of the vehicle.

The reflective element 218 may comprise any type of reflective element, preferably a transfective or display on demand type reflective element such as described above. In the illustrated embodiment, reflective element 218 comprises a transfective electrochromic reflective element having a first or front substrate 240 and a second or rear substrate 242 with an electrochromic medium 243 sandwiched therebetween and sealed with a perimeter seal 244. The front substrate 240 includes a transparent conductor coating 246 at its rear surface and may include a perimeter metallic band 250 at the perimeter of the rear surface, such as described above. The rear substrate 242 includes a transfective coating or a metal oxide/metal/metal oxide stack (with at least one of the metal oxide layers comprising a conducting or semiconducting layer), such as an IMI stack of coatings or layers 248, at its front surface. The back plate 220 is adhered or attached at the rear surface of the rear substrate, and the mirror reflective element sub-assembly 212 may include a heater element 238 and an opacifying element or layer or coating or film 252 disposed between the back plate and rear substrate. As can be seen in FIG. 16, the heater element 238 and opacifying layer 252 include apertures therethrough at the location of the light baffle 230 and the passageway of the indicator mounting portion 226b of the back plate 220, so that light emanating from the signal indicating modules 222a, 222b is transmitted through the apertures in the heater element and opacifying layer and through the reflective element for viewing by a person viewing the reflective element at the appropriate angle.

Thus, the blind spot indicator mounting portion 226b may be angled so as to direct the light toward the vehicle and toward a driver or occupant of the host vehicle. More particularly, the light beam emitted from the blind spot signal indicating module 222b and transmitted through the reflective element is angled so as to have its principle beam axis directed generally toward the eyes of a driver seated in the interior cabin of the host vehicle. The indicator mounting portion thus may extend from the rear of the back plate at an acute angle (such as approximately about 25 to about 30 degrees or thereabouts) relative to the plane defined by the back plate so as to direct or guide light through the passageway and in the desired direction toward the side of the equipped/host vehicle for viewing the object/LCA indication principally or solely by the driver of the host vehicle. Should, however, the signal module be a turn signal module, then the indicator mounting portion may extend from the rear of the back plate at an acute angle (such as approximately about 55 to about 60 degrees or thereabouts) relative to the plane defined by the back plate so as to direct or guide light through the passageway and in the desired direction

away from the side of the equipped/host vehicle for viewing the turn indication principally or solely by the drivers of overtaking vehicles and principally other than by the driver of the host vehicle.

The indicator may be activated or energized in response to a detection of an object or other vehicle approaching or adjacent to the host vehicle in order to alert or warn the driver of the host vehicle not to attempt or initiate a lane change that moves the subject or host vehicle into the already occupied (or soon to be occupied) side lane or region adjacent either the driver side or the passenger side of the host vehicle. The inboard display area may be for displaying or indicating to the driver of the host vehicle that an object has been detected in the blind spot, while the outboard display area may be for displaying or indicating a turn signal activation to the driver of another vehicle. Optionally, the inboard display area may comprise an industry standard icon, such as an ISO icon (showing icons representing the host vehicle and another vehicle at the side and/or rearward of the host vehicle) or the like, to indicate to the driver of the host vehicle that another vehicle has been detected at the side and/or rearward of the host vehicle. The iconistic display may be established at the reflective element, such as by providing indicia at the reflective element such as by utilizing aspects of the reflective elements described in PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which is hereby incorporated herein by reference in its entirety.

Optionally, however, the display area may comprise other forms, such as, for example, a multi-stage indicator having multiple indicating portions or elements or devices for indicating a degree of hazard or the like of an object or vehicle detected alongside and/or rearward of the host vehicle (such as an indicating display of the types described in PCT Application No. PCT/US2006/026148, filed Jul. 5, 2006 and published Jan. 11, 2007 as International Publication No. WO 2007/005942; and U.S. provisional applications, Ser. No. 60/696,953, filed Jul. 6, 2005, and Ser. No. 60/784,570, filed Mar. 22, 2006, which are hereby incorporated herein by reference in their entirety), or other types of indicating means, such as by utilizing aspects of the displays or indicators described in U.S. Pat. No. 6,598,982, issued to Witt; U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008; and/or PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entirety, without affecting the scope of the present invention.

For example, the icons or pattern that define the display may be established at the rear of the rear substrate and between the rear surface of the rear substrate and the back plate. The icons or pattern that define the display may be established through or defined by the dark layer or opacifying layer so that icons or iconistic portions of the dark layer form the icon or icons of the iconistic display area. Optionally, the iconistic portions of the display area may be established by etching the dark layer or by a mask or the like positioned at the rear surface of the substrate during the painting or screening or coating process that applies the dark layer. Optionally, the iconistic portions of the display area may be established by etching or masking at a fourth surface conductive busbar or coating (such as a fourth surface conductive busbar of the types described in U.S. patent application Ser. No. 11/021,065, filed Dec. 23, 2004, now

U.S. Pat. No. 7,255,451; and/or Ser. No. 11/334,139, filed Jan. 18, 2006, now U.S. Pat. No. 7,400,435; and/or U.S. provisional applications, Ser. No. 60/644,903, filed Jan. 19, 2005; and Ser. No. 60/667,049, filed Mar. 31, 2005, which are hereby incorporated herein by reference in their entirety). Optionally, the icons or pattern may be established via cutouts or holes or patterns or indicia portions formed in and through or partially through a heater pad (that may be attached to or adhered to the dark or opacifying layer at the rear surface of the reflective element, as discussed below), with the dark layer having an opening or aperture formed therethrough and generally corresponding with the indicia portions of the heater pad when the heater pad is adhered to the dark layer at the rear surface of the reflective element.

As described in U.S. provisional application Ser. No. 60/696,953, incorporated above, the present invention provides a blind spot indicator or lane change assist (LCA) indicator that is fixedly located at the mirror shell or casing and/or at a support arm of an exterior rearview mirror assembly, so as not to move or adjust when the mirror reflective element is moved or adjusted to set its field of view. Preferably, the blind spot indicator is fixedly located at the inboard wall or portion of the mirror shell or casing, so as to be readily viewed by the driver of the host vehicle, while being substantially non-visible or non-viewable by a driver of another vehicle. The blind spot/LCA indicator is preferably located at an angled, outwardly extending rearward portion of the mirror assembly that is angled so as to slope or extend at an angle away from the body side of the vehicle, so that the blind spot/LCA indicator is generally facing the driver of the host vehicle and is readily viewable by the driver of the host vehicle and substantially non-visible or non-viewable by a driver of another vehicle at or approaching the host vehicle.

According to an aspect of the present invention, an exterior rearview mirror assembly for a vehicle includes a reflective element, a mirror shell or casing and a blind spot indicator. The shell or casing has an inboard portion that is inboard of the reflective element relative to the position of the reflective element with respect to the body side of the vehicle when the exterior mirror assembly is mounted thereto, and thus is between the reflective element and the body side of the vehicle to which the mirror assembly is attached. The blind spot indicator is located at and oriented at the inboard portion of the mirror shell or casing so as to be viewable by the driver of the vehicle and so as to be substantially to totally non-viewable by the drivers of other vehicular traffic, such as other vehicular traffic rearward of, sideward of, approaching, overtaking, forward of or otherwise at or near the host vehicle.

The inboard portion of the mirror shell or casing (which at least in part defines a cavity within which the mirror reflective element is disposed and within which the mirror reflective element is adjustable) may comprise an inboard wall of the mirror shell or casing. Typically, the exterior mirror assembly comprises a stalk or support arm or member of the mirror assembly that extends from the side of the vehicle to where the mirror shell is disposed.

The blind spot indicator may include a light source or illumination source (such as one or more light emitting diodes (LEDs) or the like), and may include a lens or other optic or light directing/guiding device or element or means or a light channel, conduit or means, or a light baffle or means, or a light louver or blind or means, or a light directing element or means, preferably at the mirror shell or casing (and substantially disposed therein so as not to overly protrude to create aerodynamic drag and so as to provide an

aesthetically pleasing exterior appearance) for directing the light emitted by the light source toward the driver for viewing by the driver of the host vehicle and, if required, for limiting or restricting viewing by drivers of other vehicles.

Thus, the present invention provides an exterior rearview mirror assembly for a vehicle that includes a mirror shell portion and a blind spot or lane change assist (LCA) indicator. A cavity of the mirror shell portion is formed or defined at least partially by the walls of the shell portion. A variety of suitable mirror shells are known in the exterior mirror assembly art, such as skull-cap mirror shells (such as described in U.S. Pat. Nos. 6,612,708; 6,447,130 and 6,310,738), uni-body mirror shells, and the like. A reflective element is disposed within the cavity, along with any accessories or displays and associated adjustment device or actuator associated with the reflective element or mirror assembly. The mirror shell consists of an inner or inboard wall or side or portion that, when the mirror assembly is mounted at the side of the vehicle, preferably proximate to or at the driver or passenger side front door and proximate to or at the join of the door to the front portion of the vehicle body side (often referred to as the A-pillar region of the vehicle), the inner wall portion is at or near to the vehicle side body and readily viewable by the driver of the host vehicle. The mirror shell also includes an outer or outboard side or wall or portion that is further from the side of the vehicle and outward or outboard from the inner or inboard wall or portion. The mirror reflective element is disposed within the mirror shell and between the inner wall or portion or side and the outer wall or portion or side of the mirror shell. The blind spot or LCA indicator is located at the inboard or inner wall or side or portion of the mirror shell and, thus, is readily viewable by the driver of the host vehicle.

The mirror assembly is mounted to the body side of the vehicle (such as to a front door portion or to a vehicle body portion, depending on the particular application of the mirror assembly). The mounting portion of the mirror assembly often includes a stalk or mounting arm or member or support arm or member that extends from the mounting area of the vehicle body side to where the mirror shell is disposed. The mounting arm may extend from the vehicle body side by about an inch or more, and often about two to three inches or thereabouts, depending on the styling, type or size of the vehicle and associated exterior mirror assembly.

Note that, the inner portion of the driver side mirror assembly is most readily visible/viewable to the driver of the vehicle, as compared to the inner portion of the passenger side mirror assembly. The blind spot/LCA indicator of the present invention is thus highly suited for applications where the blind spot indicator is on the driver side only. However, it is envisioned that a blind spot/LCA indicator of the present invention may also or otherwise be located at the inner or inboard portion or wall or side of the passenger side exterior rearview mirror assembly, without affecting the scope of the present invention.

Therefore, the present invention provides a blind spot indicator at an inboard wall or portion of an exterior rearview mirror assembly. The blind spot indicator is located at an inboard wall or portion of the mirror casing or shell or at an inboard support arm or the like of the mirror assembly and, thus, is readily viewable by the driver of the host vehicle, and without the driver having to look across to the outboard dimension of the mirror reflective element to see or notice actuation or illumination of the blind spot indicator. The blind spot indicator thus may be readily viewable by the driver and may be so viewable without the driver having to

look at the reflective element of the exterior mirror to see the blind spot indicator. Also, because the blind spot indicator is located at the inboard portion of the mirror assembly, the blind spot indicator is viewable principally or solely by the driver of the host vehicle, and is not readily viewable or visible to a driver of another vehicle. Because the blind spot indicator is not located at a primary viewing area, the curb-side appeal or appearance of the vehicle is not adversely impacted by the choice and styling of the blind spot indicator. Also, because the blind spot indicator of the present invention is not located behind a window in the reflective element, or behind a transfective portion of the reflective element, the blind spot indicator may be fixedly placed and may provide a low cost indicator that may be readily incorporated into an exterior rearview mirror assembly of a vehicle.

As shown in FIG. 26, an exterior rearview mirror assembly **810** for a vehicle includes a reflective element **812** and a mirror shell or casing **814**. Mirror assembly **810** is mounted at the side **816a** of a host or subject vehicle **816**, and includes a blind spot indicator **818** at an inboard portion **820** of mirror assembly **810**. The blind spot indicator **818** is operable by illumination to indicate to the driver of the subject or host vehicle that an object or other vehicle is detected at the side or blind spot region of the host vehicle by a blind spot detection system, as discussed below. The indicator may be activated or energized in response to a detection of an object or other vehicle approaching or adjacent to the host vehicle in order to alert or warn the driver of the host vehicle not to attempt or initiate a lane change that moves the subject or host vehicle into the already occupied (or soon to be occupied) side lane or region adjacent either the driver side or the passenger side of the host vehicle.

Mirror assembly **810** is connected at the side **816a** of vehicle **816** and includes a mounting arm or stem **822** or the like, which is mounted to or extends from the side **816a** of vehicle **816**. In the illustrated embodiment of FIG. 26, the inboard portion **820** of mirror assembly **810** comprises the inboard wall or side of the mirror shell or casing **814**. The inboard portion or wall is at the inboard side of the mirror assembly and generally faces the side **816a** of the vehicle **816**. As can be seen in FIG. 26, the inboard portion **820** is spaced from and opposite from an outboard portion or side **824** of the mirror assembly **810**.

Typically, side exterior rearview mirror assemblies for vehicles extend from the side of the vehicle and are angled to reduce aerodynamic drag and to provide an aesthetically pleasing appearance. Thus, the inboard portion of the exterior rearview mirror may be angled outwardly from the vehicle and thus slopes away from vehicle and provides a surface at which to mount/install the blind spot indicator, whereby the blind spot indicator is generally facing the driver of the host vehicle while being generally or substantially or entirely hidden from the view of drivers of other vehicles encountered by the host vehicle. Also, because the indicator is located at the inboard portion of the mirror shell or casing, the indicator may be selected to be substantially large, since the size of the indicator is not constrained by the field of view regulations of the mirror reflective element. The blind spot indicator of the present invention thus may be located at the mirror inboard wall or portion or side, which is contoured so that the wall or surface slopes away from the body side of the vehicle. By positioning the indicator at this location, the presence of the indicator at the inboard or inner wall or side of the exterior mirror is substantially or totally obscured from the view of drivers of trailing or side over-

taking vehicles by the very body and structure of the exterior mirror. Also, because of the natural aerodynamic styling and structure of the inboard wall portion or section, operation of the blind spot indicator is substantially or totally non-viewable by the drivers of leading vehicles (traveling in front of the host vehicle) or vehicles approaching the host vehicle from in front of the host vehicle.

Blind spot/LCA indicator **818** may include an illumination or light source (such as one or more light emitting diodes (LEDs) or organic light emitting diodes (OLEDs) or the like that is/are energized to direct or emit illumination toward the driver of the host vehicle. The illumination source may be positioned within or behind the inboard wall or portion of the mirror assembly and the indicator may include an iconistic display area (such as transparent or substantially transparent or translucent windows or apertures formed or established at the inboard wall so that the illumination passes through the windows for viewing and discerning by the driver of the host vehicle). The iconistic display may be established or formed at a lens or element that attaches to the shell or casing or may be formed or established at the shell or casing wall itself. The indicator may include baffles or light piping or tubing or electroluminescent foil or other light direction means or occluding means, such as louvers or shutters or filters or light directing film or the like for directing or guiding the illumination from the illumination source at the desired angle and through the inboard wall or portion so as to be principally or solely viewable by the driver of the host vehicle. Because the blind spot indicator is located at an area or region that is not readily viewable by a person outside of the vehicle cabin, the indicator may be located at the surface of the inboard wall or portion (and may protrude partially therefrom), and need not be recessed within the casing surface, without adversely affecting the appearance of the exterior mirror assembly. The location and degree of recess or inset of the blind spot indicator may be selected depending on the particular application of the blind spot indicator and on the location of any internal mirror content (such as an actuator, security light or other indicators or accessories or the like) located within the mirror shell.

As shown in FIG. 26, blind spot indicator **818** may comprise an ISO icon (showing icons representing the host vehicle and another vehicle at the side and/or rearward of the host vehicle) to indicate to the driver of the host vehicle that another vehicle has been detected at the side and/or rearward of the host vehicle. The iconistic representation may be formed as a translucent window or portion of the inboard wall or portion or may be otherwise established at the inboard wall or portion of the mirror assembly. Optionally, however, the indicator may comprise other forms, without affecting the scope of the present invention. For example, and with reference to FIG. 27, a blind spot indicator or LCA indicator **818'** of an exterior mirror assembly **810'** may comprise a multi-stage indicator having multiple indicating portions or elements or devices for indicating a degree of hazard or the like of an object or vehicle detected alongside and/or rearward of the host vehicle. The indicating portions or elements or devices may comprise different color indicators, such as green, amber and red or the like, to indicate the degree of hazard detected. Such an indicator is suitable for use with a lane change assist (LCA) system, and may provide a green indication when the adjacent side lane is clear, an amber indication when a vehicle approaches the side lane area, and a red indication when another vehicle is occupying the side lane area adjacent to the host vehicle. As shown in FIG. 27, the blind spot indicator or LCA indicator

818' may be positioned at a lower region of the inboard portion **820'** of the mirror assembly **810'**, or (and as shown in FIG. 27A), the blind spot indicator **818''** may be positioned at an upper region of the inboard portion **20''** of the mirror assembly **810''** (where the indicator may be more readily visible/viewable to the driver of the host vehicle). Optionally, for example, and with reference to FIG. 28, a blind spot indicator **818'''** of an exterior rearview mirror assembly **810'''** may comprise a hazard indicator or the like at the inboard portion **820'''** to provide a hazard indication or warning or alert signal to the driver of the host vehicle when an object or vehicle is detected at the side and/or rearward of the host vehicle, and when the driver of the host vehicle is attempting a lane change or the like (such as when the driver activates the turn signal of the host vehicle). Other iconistic images or indicia or the like may be used for the blind spot/LCA indicator, without affecting the scope of the present invention.

As can be seen in FIGS. 29 and 30, the blind spot indicator of the present invention is not readily viewable or discernible by a driver of a vehicle approaching the host vehicle from the rear of the host vehicle (as shown in FIG. 29) or a driver of a vehicle approaching and overtaking the host vehicle along a side of the host vehicle (as shown in FIG. 30). Although not shown, the blind spot indicator is also substantially not viewable by or visible to a driver of a vehicle ahead of or leading the host vehicle. The blind spot indicator of the present invention thus may be sufficiently large to enhance viewability and discernibility of the indicator by the driver of the host vehicle, without detracting from the appearance of the mirror assembly and without being readily viewable/discernible by the driver of another vehicle, thereby limiting or substantially precluding confusion (to the driver of the other vehicle) between a turn signal indicator (not shown) of the mirror assembly and the blind spot indicator.

Although shown in FIGS. 26-30 and described above as being located at a driver side exterior mirror, the blind spot/LCA indicator of the present invention may also or otherwise be located at the passenger side exterior mirror, if desired. Optionally, the blind spot indicator of the present invention may be located at both the driver side mirror assembly and the passenger side mirror assembly of the host vehicle. The indicator at either side may be selectively activated or illuminated to indicate to the driver of the host vehicle that an object or other vehicle has been detected at that particular side lane region of the host vehicle. Optionally, the blind spot indicator may be associated with a blind spot detection and indication system that includes one or more indicators at the interior rearview mirror assembly of the host vehicle. For example, and with reference to FIG. 31, a blind spot indicator **918a** may be located at an inboard portion or wall **920a** of a driver side exterior rearview mirror assembly **910a**, while a blind spot indicator **918b** may be located at an inboard portion or wall **920b** of a passenger side exterior rearview mirror assembly **910b**. Also, an interior rearview mirror assembly **930** may include one or more indicators **919a**, **919b** that provide further indication to the driver of the host vehicle of a detection of an object or other vehicle at either side and/or rearward of the host vehicle, so that the driver of the host vehicle has a cognitive association of the indicators. The blind spot indicators may provide a redundant indication at both the interior and exterior mirrors in order to assist the driver in recognizing the conditions surrounding the host vehicle, such as by utilizing aspects of the blind spot detection system described in U.S. Pat. Nos. 6,198,409; 5,929,786 and 5,786,772.

Optionally, and with reference to FIG. 32, an exterior rearview mirror assembly 1010 may include a reflective element 1012 and a mirror casing or shell 1014 supported on a mounting arm 1032 that is mounted to and/or that extends from the side 1016a of the host vehicle 1016. The blind spot indicator 1018 may be located at an inboard portion 1020 of the casing 1014, such as at a support arm or portion or stem 1032 of the casing which mounts to the mounting arm 1022. In the illustrated embodiment, the casing 1014 is pivotally mounted to the mounting arm 1022, such as for a powerfold exterior mirror or a breakaway exterior mirror or the like. The inboard portion 1020 thus may be positioned along the support arm and/or mounting portion (and preferably along a surface that is angled outwardly with respect to the vehicle side) so as to be directed generally toward the driver of the host vehicle and not readily viewable by drivers of other vehicles at or near the host vehicle.

As shown in FIG. 32, the indicator 1018 may comprise an ISO indicator with the iconistic representation of the host vehicle and adjacent or approaching vehicle, such as described above with respect to FIG. 25. Optionally, and such as described above with respect to FIGS. 26 and 27, the blind spot indicator may comprise a multi-stage indicator 1018' (FIG. 33) or a hazard indicator 1018" (FIG. 34) at the support arm or stem of the mirror assembly.

Optionally, and as shown in FIG. 35, the blind spot indicator 1118 (such as a multi-stage indicator or other type of indicator) may be located at the inboard wall 1120 of the mirror casing 1114 of an exterior mirror assembly 1110 and generally at or rearward of the support arm or stem 1132 (which mounts to a mounting arm or portion 1122 at the vehicle) of the casing 1114 (where the indicator is rearward of the support arm and thus facing generally rearwardly with respect to the forward direction of travel of the vehicle, and preferably on an outwardly angled portion so as to be facing partially inward toward the driver of the vehicle). The indicator thus is readily viewable by the driver of the host vehicle at the mirror casing and rearward of the support arm or stem of the mirror assembly. As shown in FIG. 36, the blind spot indicator 1118' may be located at the inboard portion 1120' of the casing 1114' of an exterior mirror assembly 1110' and generally above the support arm or stem 1132' (which mounts to the mounting arm or portion 1122'), if desired. The particular location of the blind spot indicator may be selected depending on the geometries and content of the mirror assembly and support arm and mounting portion of the mirror assembly and on the vehicle door design and/or the vehicle A-pillar design, so as to provide enhanced viewability and discernibility of the blind spot indicator to the driver of the host vehicle. As shown in FIGS. 37A and 37B, a blind spot indicator 1118a" may be located at the inboard portion 1120a" of the casing 1114a" of a driver side exterior mirror assembly 1110a", while a blind spot indicator 1118b" may be located at the inboard portion 1120b" of the casing 1114b" of a passenger side exterior rearview mirror assembly 1110b", so that the indicators 1118a", 1118b" are readily viewable and discernible by the driver of the host vehicle while being substantially non-viewable to drivers of other vehicles at or near or trailing or approaching or overtaking or leading the host vehicle.

Optionally, the blind spot indicator or LCA indicator of the present invention may be provided as an indicator module that is a unitary module including an illumination source, electrical connectors and cover and/or light directing or guiding elements or means. The unitary indicator module is preferably sealed so as to be substantially impervious to water so as to provide a robust module that can withstand the

exposure to the elements at the exterior rearview mirror assembly. The mirror assembly may be formed with a cavity or opening for receiving or attaching the unitary indicator module therein or thereat, and may include the electrical connectors at the cavity or opening for making the appropriate electrical connections to the indicator module. Optionally, the electrical connections may be made while the indicator module is attached to the mirror assembly, such as via a plug and socket type arrangement or configuration, and such as by utilizing aspects of the mirror assembly described in U.S. Pat. No. 6,669,267. The unitary indicator module may include or utilize aspects of various light modules or systems or devices, such as the types described in U.S. Pat. Nos. 6,227,689; 6,582,109; 5,371,659; 5,497,306; 5,669,699; 5,823,654; 6,176,602 and/or 6,276,821.

The unitary indicator module thus may be readily installed at an exterior mirror assembly to provide the blind spot/LCA indicator at the inboard wall or portion of the exterior mirror. The blind spot detection system (and thus the blind spot indicator) thus may be selected by a customer as an option for their vehicle. Optionally, the exterior mirror assembly may be shipped to a vehicle assembly plant with the module already installed, or the exterior mirror assembly may be shipped to the vehicle assembly plant with a socket or structure for receiving or mounting or attaching the indicator module. The indicator module may be connected or plugged in or otherwise attached to the mirror assembly at the socket or structure at the vehicle assembly plant. The indicator module may make both the mechanical and electrical connections to the mirror assembly when attached thereto, such as by utilizing aspects described in U.S. Pat. No. 6,669,267. The indicator module thus may be installed at the appropriate mirror assembly (such as for a vehicle that has the blind spot indicator selected as an option) at the vehicle assembly plant, while a blank out panel or the like may be attached to the mirror assembly for vehicles that do not have the blind spot indicator option selected. Because the blind spot indicator and associated electronics may be costly, the indicator module allows the indicator to be added to the exterior mirror only for those vehicles with the indicator option selected, and without affecting the mirror assembly structure and design, so that a common mirror shell may be utilized for a standard mirror and for a mirror with the indicator option selected, thereby deproliferating parts and providing economies of scale for the mirror assemblies.

The blind spot indicator of the present invention thus is positioned at the inboard portion of the exterior mirror and thus is positioned at an area that is readily viewable by the driver of the host vehicle. Because an exterior rearview mirror for a vehicle is formed to be angled for aerodynamic and aesthetic purposes, the exterior rearview mirror typically has an inboard portion or wall that is contoured or formed to be sloping outwardly and away from the vehicle, so as to provide a wall that is generally facing toward the driver of the vehicle so that the portion is readily viewable by the driver of the vehicle. This outwardly sloping portion or wall provides a location for the blind spot/LCA indicator of the present invention, where the indicator is readily viewable by the driver of the host vehicle, but is substantially hidden from the view of drivers of other vehicles at or near the host vehicle. Since the inboard wall or side or portion is not a primary viewing area, the blind spot indicator may be located at this portion without adversely affecting the styling lines and appearance of the mirror assembly. Optionally, a cowling or cover element or dome element or baffle or louver or the like may be provided at the

mirror shell or support arm to further restrict the view of the indicator by drivers of other vehicles.

Typically, the mirror reflective element is recessed slightly within the cavity of the mirror shell, and it is not uncommon to have water beads, dirt, ice and the like build up in that area, since that area is sheltered from and is not directly exposed to the wind or slip stream as the vehicle travels along the road. By placing the indicator at the inboard wall or portion of the exterior mirror, the indicator is located in the slip stream and thus is exposed to the wind as the vehicle travels along the road. The blind spot indicator thus may be more visible to the driver of the host vehicle, since ice buildup and/or debris build up is less likely in this area and since any water or ice or dirt or other debris or contaminants are often blown away from where the indicator is located, thus enhancing its visibility to the driver. Also, because the blind spot indicator is closer to the window (through which the driver views the indicator), the indicator is more readily viewable in fog or hazy conditions or other extreme weather conditions, such as during a snow storm or rain storm or the like, even if the driver cannot readily view the mirror reflective element of the exterior mirror.

The blind spot indicator thus is positioned at a location that is closer than conventional or known external indicators (which are typically located at the outboard upper corner of the reflective element) may be seen and discerned by the driver of the host vehicle even when the driver is not viewing the reflective element of the exterior rearview mirror. Because the blind spot indicator is located at the side or inboard portion of the mirror assembly or casing, the blind spot indicator may be relatively large (such as compared to indicators at the reflective element) to enhance viewing of the indicator, since the size of the indicator is not limited by the viewing requirements at the reflective element. For example, the blind spot indicator of the present invention may provide a viewing area dimension of preferably at least about one square centimeter, and more preferably at least about two square centimeters, and more preferably at least about four square centimeters. The size of the blind spot indicator thus may be selected to provide a desired viewing area, and is less fettered by the design constraints and regulations of the exterior mirror.

The blind spot indicator thus may be sized to provide the desired appearance and viewability/discernibility and may be positioned at the inboard portion in a manner that does not interfere with the movable parts of the exterior mirror assembly. Also, by locating the blind spot indicator at the inboard portion of the exterior rearview mirror assembly, the indicator is naturally occluded by the exterior mirror from the view of the driver of another vehicle or any other person outside of the host vehicle. The blind spot indicator of the present invention thus may be provided at the desired size, shape and location, and thus provides the potential for enhanced flexibility in the design and implementation of the blind spot indicator, since the size, shape and design of the indicator is not constrained by the regulations and limitations otherwise applicable at the reflective element of the exterior mirror.

The blind spot indicator preferably is fixedly positioned at the inboard portion of the mirror assembly (such as substantially within the mirror shell and visible at the inner shell wall adjacent to the driver side or passenger side front window, depending on whether it is a driver side or pass side mirror). However, it is envisioned that the blind spot indicator may be adjustable (such as via a user input within the vehicle cabin) to direct the indicator toward the particular driver's head area. The indicator may be adjusted by the

driver of the host vehicle to enhance viewing of the indicator by the driver. The indicator may be adjusted separately from any adjustment of the reflective element so that the indicator may be adjusted toward the driver's head area and irrespective of the desired adjustment of the reflective element of the exterior rearview mirror. The indicator and any adjustment or alignment thereof may utilize aspects of the alignment device described in U.S. Pat. No. 6,598,982.

Optionally, and with reference to FIG. 38, an exterior rearview mirror assembly 1210 for a vehicle includes a reflective element 1212 and a mirror shell or casing 1214. Mirror assembly 1210 is mounted at the side 1216a of a host or subject vehicle 1216, and includes a blind spot indicator 1218 at an inboard portion or surface 1220 of an outer wall 1224 of the mirror casing 1214 of mirror assembly 1210. The blind spot indicator 1218 thus may be located at a cusp or inboard surface of the outer wall 1224 of mirror casing 1214 so as to be readily viewable by the driver of the host vehicle, while being substantially hidden or not viewable by the driver of another vehicle at or near or approaching the host vehicle. The blind spot indicator 1218 thus is located at a region that is remote from the reflective element of the mirror assembly so as to limit or substantially preclude confusion between the blind spot indicator and any display or indicator (such as a turn signal display or the like) that is located at the reflective element of the mirror assembly (and thus that may be intended for viewing by the driver of another vehicle).

The blind spot indicator thus is operable to provide an indication to the driver of the host vehicle that an object or other vehicle has been detected in the lane or area adjacent to the side of the host vehicle. The blind spot indicator may be operable in association with a blind spot detection system, which may include an imaging sensor or sensors, or ultrasonic sensor or sensors, or sonar sensor or sensors or the like. For example, the blind spot detection system may utilize aspects of the blind spot detection and/or imaging systems described in U.S. Pat. Nos. 6,882,287; 6,198,409; 5,929,786 and/or 5,786,772, and/or U.S. patent application Ser. No. 10/427,051, filed Apr. 30, 2003, now U.S. Pat. No. 7,038,577, and/or U.S. provisional applications, Ser. No. 60/638,687, filed Dec. 23, 2004; Ser. No. 60/628,709, filed Nov. 17, 2004; Ser. No. 60/614,644, filed Sep. 30, 2004; and/or Ser. No. 60/618,686, filed Oct. 14, 2004, and/or of the reverse or backup aid systems, such as the rearwardly directed vehicle vision systems described in U.S. Pat. Nos. 5,550,677; 5,760,962; 5,670,935; 6,201,642; 6,396,397; 6,498,620; 6,717,610 and/or 6,757,109, and/or U.S. patent application Ser. No. 10/418,486, filed Apr. 18, 2003, now U.S. Pat. No. 7,005,974, and/or of the automatic headlamp controls described in U.S. Pat. Nos. 5,796,094 and/or 5,715,093; and/or U.S. patent application Ser. No. 11/105,757, filed Apr. 14, 2005, now U.S. Pat. No. 7,526,103; and/or U.S. provisional application Ser. No. 60/607,963, filed Sep. 8, 2004, and/or of the rain sensors described in U.S. Pat. Nos. 6,250,148 and 6,341,523, and/or of other imaging systems, such as the types described in U.S. Pat. Nos. 6,353,392 and 6,313,454, which may utilize various imaging sensors or imaging array sensors or cameras or the like, such as a CMOS imaging array sensor, a CCD sensor or other sensors or the like, such as the types disclosed in commonly assigned, U.S. Pat. Nos. 5,550,677; 5,760,962; 6,097,023 and 5,796,094, and U.S. patent application Ser. No. 09/441,341, filed Nov. 16, 1999, now U.S. Pat. No. 7,339,149, and/or PCT Application No. PCT/US2003/036177 filed Nov. 14, 2003, published Jun. 3, 2004 as PCT Publication No. WO 2004/047421, with all of the above referenced U.S.

patents, patent applications and provisional applications and PCT applications being commonly assigned.

Optionally, the indicator of the present invention may alert the driver of the host vehicle of other situations or status or the like. For example, the indicator could function to alert the driver of the host vehicle that the brake lights of the host vehicle are functioning properly. Other applications or uses of the indicator may be implemented, without affecting the scope of the present invention.

The reflective element of the rearview mirror assembly may comprise an electro-optic or electrochromic reflective element or cell, such as an electrochromic mirror assembly and electrochromic reflective element utilizing principles disclosed in commonly assigned U.S. Pat. Nos. 6,690,268; 5,140,455; 5,151,816; 6,178,034; 6,154,306; 6,002,544; 5,567,360; 5,525,264; 5,610,756; 5,406,414; 5,253,109; 5,076,673; 5,073,012; 5,117,346; 5,724,187; 5,668,663; 5,910,854; 5,142,407 and/or 4,712,879, and/or U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381; and/or Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451, and/or U.S. provisional applications, Ser. No. 60/695,149, filed Jun. 29, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; Ser. No. 60/681,250, filed May 16, 2005; and/or Ser. No. 60/692,113, filed Jun. 20, 2005, and/or as disclosed in the following publications: N. R. Lynam, "Electrochromic Automotive Day/Night Mirrors", *SAE Technical Paper Series* 870636 (1987); N. R. Lynam, "Smart Windows for Automobiles", *SAE Technical Paper Series* 900419 (1990); N. R. Lynam and A. Agrawal, "Automotive Applications of Chromogenic Materials", *Large Area Chromogenics: Materials and Devices for Transmittance Control*, C. M. Lampert and C. G. Granquist, EDS., Optical Engineering Press, Wash. (1990). The thicknesses and materials of the coatings on the substrates of the electrochromic reflective element, such as on the third surface of the reflective element assembly, may be selected to provide a desired color or tint to the mirror reflective element, such as a blue colored reflector, such as is known in the art and/or such as described in U.S. Pat. Nos. 5,910,854 and 6,420,036, and in PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633.

Optionally, use of an elemental semiconductor mirror, such as a silicon metal mirror, such as disclosed in U.S. Pat. Nos. 6,286,965; 6,196,688; 5,535,056; 5,751,489 and 6,065,840, and/or in U.S. patent application Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177, can be advantageous because such elemental semiconductor mirrors (such as can be formed by depositing a thin film of silicon) can be greater than 50 percent reflecting in the photopic (SAE J964a measured), while being also substantially transmitting of light (up to 20 percent or even more). Such silicon mirrors also have the advantage of being able to be deposited onto a flat glass substrate and to be bent into a curved (such as a convex or aspheric) curvature, which is also advantageous since many passenger-side exterior rearview mirrors are bent or curved.

Optionally, the reflective element 12 includes a perimeter metallic band, such as the types described in PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; and/or PCT Application No. PCT/US03/35381, filed Nov. 5, 2003 and published May 21, 2004 as International Publication No. WO 2004/042457; and/or U.S. patent application Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or U.S. provisional applications, Ser. No. 60/692,113, filed Jun. 20, 2005; Ser. No.

60/677,990, filed May 5, 2005; Ser. No. 60/653,787, filed Feb. 17, 2005; Ser. No. 60/642,227, filed Jan. 7, 2005; Ser. No. 60/638,250, filed Dec. 21, 2004; Ser. No. 60/624,091, filed Nov. 1, 2004, and Ser. No. 60/609,642, filed Sep. 14, 2004. Optionally, the reflective element may include indicia formed at and viewable at the reflective element, such as by utilizing aspects of the reflective elements described in U.S. provisional applications, Ser. No. 60/695,149, filed Jun. 29, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; and/or Ser. No. 60/681,250, filed May 16, 2005.

Although shown and described as an electro-optic or electrochromic reflective element assembly or cell, the reflective element may comprise a single substrate with a reflective coating at its rear surface, without affecting the scope of the present invention. The mirror assembly thus may comprise a prismatic mirror assembly or other mirror having a single substrate reflective element, such as a mirror assembly utilizing aspects described in U.S. Pat. Nos. 6,318,870; 6,598,980; 5,327,288; 4,948,242; 4,826,289; 4,436,371 and 4,435,042; and PCT Application No. PCT/US04/015424, filed May 18, 2004 and published Dec. 2, 2004 as International Publication No. WO 2004/103772; and U.S. patent application Ser. No. 10/933,842, filed Sep. 3, 2004, now U.S. Pat. No. 7,249,860. Optionally, the reflective element may comprise a conventional prismatic or flat reflective element or prism, or may comprise a prismatic or flat reflective element of the types described in PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; U.S. patent application Ser. No. 10/709,434, filed May 5, 2004, now U.S. Pat. No. 7,420,756; Ser. No. 10/933,842, filed Sep. 3, 2004, now U.S. Pat. No. 7,249,860; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published Dec. 2, 2004 as International Publication No. WO 2004/103772, without affecting the scope of the present invention.

Optionally, the mirror assembly may include one or more displays, such as the types disclosed in U.S. Pat. Nos. 5,530,240 and/or 6,329,925, and/or display-on-demand or transreflective type displays, such as the types disclosed in U.S. Pat. Nos. 6,690,268; 5,668,663 and/or 5,724,187, and/or in U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381; and/or Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; and/or PCT Application No. PCT/US03/35381, filed Nov. 5, 2003 and published May 21, 2004 as International Publication No. WO 2004/042457; and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004; Ser. No. 60/667,048, filed Mar. 31, 2005; Ser. No. 60/629,926, filed Nov. 22, 2004; Ser. No. 60/531,838, filed Dec. 23, 2003; Ser. No. 60/553,842, filed Mar. 17, 2004; and Ser. No. 60/563,342, filed Apr. 19, 2004, and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 and published Jul. 15, 2004 as International Publication No. WO 2004/058540, or may include or incorporate video displays or the like, such as the types described in PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 and published Jul. 15, 2004 as International Publication No. WO 2004/058540, and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004; and Ser. No. 60/667,048, filed Mar. 31, 2005.

Optionally, the mirror assembly may include an imaging device, such as an imaging array sensor for imaging systems

of the types described in U.S. Pat. Nos. 6,757,109; 6,717,610; 6,396,397; 6,201,642; 6,353,392; 6,313,454; 6,396,397; 5,550,677; 5,670,935; 5,796,094; 5,877,897; 6,097,023 and 6,498,620, and U.S. patent application Ser. No. 09/441,341, filed Nov. 16, 1999, now U.S. Pat. No. 7,339,149, and Ser. No. 10/427,051, filed Apr. 30, 2003, now U.S. Pat. No. 7,038,577.

Optionally, and with reference to FIG. 17, a back plate 320 may be formed (such as via injection molding) to include the mirror actuator attachment portion 320b, an indicator mounting or receiving portion 326a and a second indicator mounting or receiving portion 326b. As can be seen in FIG. 17, indicator receiving portion 326a is formed to receive a signal indicating module 322a such that light emanating from indicating module 322a is transmitted through a passageway 325 of indicator receiving portion 326a. Signal indicating module 322a may be similar to the signal indicating modules described above, and may include a translucent diffusing block or glow element 324 and an illumination source 328a (such as at a rear portion of the block or at a side portion of the block) that emits light into the block, whereby the light reflects off of the sides and rear of the block and is transmitted along the passageway 325 of indicator receiving portion 326a and toward the reflective element. Likewise, signal indicating module 322b may be similar to signal indicating module 222b discussed above, and may include an illumination source or LED 328b at a passageway along a hollow tube 327 of indicator mounting portion 326b. Preferably, signal indicating module 322a includes a light control film 356a at a forward surface of the glow block or indicating light source 324 to direct the substantially uniform diffuse light emanating from block 324 in a direction generally along passageway 325 of indicator receiving portion 326a. Likewise, the signal indicating module 322b may include a light control film 356b for directing light emitted by illumination source 328b toward and along the passageway of the hollow tube 327 of indicator mounting portion 326b.

The depth or length (or rearward extending dimension) of the indicator receiving portion 326a may be selected to provide the desired degree of shielding or blocking the viewability of light emanating from the indicator module by the driver of the vehicle and to provide the desired viewability of light emanating from the indicator module by the driver of another vehicle when the illumination source of the indicator module is activated, while limiting viewability of the indicator module when the illumination source is deactivated (desirable for example for a turn signal indicator). For example, the indicator receiving portion may extend about 40 mm (or more or less) rearward from the rear surface of the planar back plate portion 320a. Likewise, the angle of the passageway 325 may be selected depending on the particular application of the indicator module. For example, the passageway may be slanted so as to allow light to pass therethrough at an angle A of about 65 degrees (or more or less, such as plus or minus about 5 degrees or thereabouts) relative to the generally vertical plane of the planar back plate portion and reflective element (i.e., about 25 degrees outboard from a line extending perpendicularly from the plane of the planar back plate portion and reflective element), so that the axis formed by the slats or baffles or vanes is generally pointed away from the side of the vehicle (such as for a turn signal indicator application). Optionally, if it is desired, for example, to provide a blind spot indicator or LCA indicator, the passageway of the indicator receiving portion may be slanted so as to allow light to pass through at an angle of about 65 degrees (or more or less,

such as plus or minus about 5 degrees or thereabouts) relative to the generally vertical plane of the planar back plate portion and reflective element (i.e., about 25 degrees inboard from a line extending perpendicularly from the plane of the planar back plate portion and reflective element), so that the axis formed by the slats or baffles or vanes is generally pointed toward the side of the vehicle so that the light emanating from the indicator module is viewable by the driver of the host vehicle.

Optionally, and as shown in FIG. 18, a back plate 320' may be molded to include a mirror actuator mounting portion 320b', an indicator receiving or mounting portion 326a' for receiving or mounting a signal indicating module 322a', and another indicator receiving or mounting portion 326b' for receiving or mounting a signal indicating module 322b'. In the illustrated embodiment, the indicator mounting portion 326a' and signal indicating module 322a' are substantially similar to the indicator mounting portion 326a and signal indicating module 322a, discussed above, such that a detailed discussion of the mounting portions and indicating modules need not be repeated herein. Suffice it to say that indicating module 322a may include an optical block or glow element 324a' and at least one illumination source 328a' (such as a power LED) at the block, such as described above.

Likewise, the indicator mounting portion 326b' and signal indicating module 322b' may be similar in construction to the mounting portion 326a' and indicating module 322a' (although signal indicating module 322b' is shown in FIG. 18 with two illumination sources or LEDs 328b at the rear of the translucent optical block or glow element 324b'), but may be angled at a generally opposite direction as the indicating module 322a' and mounting portion 326a'. For example, indicating module 322a' may be configured so as to direct light (such as via the light control film 356a' and passageway 325a') in an outboard direction (generally away from the vehicle when the mirror assembly is mounted at the vehicle), such as for a turn signal indicator (whereby the transparent/translucent optical plastic block or glow element may be formed in the shape of an arrow head or a chevron or other suitable icon or shape), while indicating module 322b' may be configured so as to direct light (such as via the light control film 356b' and passageway 325b') in an inboard direction (generally toward the vehicle when the mirror assembly is mounted at the vehicle), such as for a blind spot alert indicator. Because the signal indicating modules 322a', 322b' and indicator mounting portions 326a', 326b' may be similar to the modules and mounting portions described above, a detailed discussion of the modules and mounting portions need not be repeated herein.

The light control film disposed at the indicator module may be disposed or adhered otherwise attached to the translucent block or to the rear surface of the respective indicator receiving portion so that light emanating from the block or illumination source is directed through the light control film and directed along and through the passageway established through the respective indicator receiving portion. The light control film may comprise any suitable film and may function as microlouvers, so as to preferentially direct light that is received from one angle whereby the light is redirected or controlled to another direction (such as the films of the types described in PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which is hereby incorporated herein by reference in its entirety). An example of a suitable light control film or material is disclosed in U.S. Pat. No. 5,481,409 (which is

hereby incorporated herein by reference in its entirety), and may comprise a light control film manufactured by the 3M Company of Minn., such as the light control film commercially available under the trade name LCF-P (light control film-polycarbonate).

Such a light control film comprises a thin plastic film enclosing a plurality of closely spaced, light black colored microlouvers. A preferred light control film is approximately 0.75 mm thick or thereabouts, and the angled microlouvers are spaced approximately 0.127 mm apart. The microlouvers may be in various angular positions to provide a particular viewing angle, such as from as narrow as about a 48 degree angle to as wide as about a 90 degree angle, depending on the desired angle of the microlouvers for the particular application for angling/directing the light in a desired or appropriate direction or angle. Thus, the light control film controls or directs the light emanating from the block along a desired or appropriate or predetermined angle with respect to the back plate and mirror substrate or reflective element, and helps assure that the driver of the host vehicle is largely unaware or not bothered by actuation of the turn signal indicating light sources.

The likes of a 3M Light Control Film comprises a thin plastic film containing closely spaced dark or black or light absorbing microlouvers. When used as described herein, the film simulates a tiny Venetian blind, wherein the microlouvers allow for controlled transmission of the light emitted by the indicator light sources (that are disposed behind the transmissive mirror element) along the axis of the microlouvers so that the light is seen by drivers overtaking the host vehicle in a side-lane blind spot area but the line of sight from the driver of the host vehicle to the turn signal indicator's emitted light beam is substantially blocked by the microlouvers. Examples of light directing or regulating filters or baffle assemblies can be found in U.S. Pat. Nos. 4,906,085 and 5,313,335, the entire disclosures of which are hereby incorporated by reference herein.

Optionally, and typically, the light control film may have its microlouvers at an angle of about zero degrees (i.e., generally perpendicular to the plane of the light control film) so as to direct the principle beam axis of the light emitted by the illumination sources at the desired or appropriate angle established by the angling of the rear surface of the display receiving portion relative to its front surface and so as to have the light beam emitted by the light sources pass through the display receiving portion to exit at the desired or set or selected angle. Placement of the light control film on the angled rear surface of the display receiving portion is advantageous when the light control film (such as 3M's VIKUTITM ALCF-P or LCF-P) is used where the louver angle is zero degrees and where on-axis vertically incident light from the light sources is highly transmitted but where off-axis light is cut-off by the embedded microlouvers. Such zero degree louvered light control film is used for privacy filters for laptop computer screens and ATM screens, and so is economically available. By being able to purchase and use zero angle louvered light control film, and by using the likes of an angled rear surface (pre-established via molding of the mirror back plate at its display receiving portion) to support the light control film at an angle in front of the light sources that are similarly angled and supported, economical assembly can be enhanced. Optionally, and alternatively, a mechanical support to mutually support and angle the light control film/light sources relative to the plane of the rear of the mirror reflective element may be used so that light emitted by the light sources is generally aligned with or on-axis with the light transmission axis between the louvers,

and so that the light beam passed through the light control film has its principal beam axis directed in the desired or appropriate direction, such as in a direction generally away (for a turn signal indicator) from the vehicle body side and away from direct view by a driver of the host vehicle to which the exterior mirror reflective element is attached, or such as in a direction generally toward (for a blind spot indicator) the vehicle body side for direct viewing by the driver of the host vehicle and away from direct view by a driver of another vehicle.

Preferably, the indicator mounting portion or portions **326a**, **326b** of back plate **320** include light absorbing means to substantially absorb non-axially directed light rays passing through the respective passageway. For example, the inner wall or surface of the passageway of the indicator mounting portion may be black or dark (such as due to the molding of the dark or opaque back plate), and may be at least partially light absorbing, and preferably substantially light absorbing, and most preferably fully light absorbing of light incident thereon. Thus, principally only light rays that pass substantially or entirely through the full length of the inner passageway exit the end of the light emitting passageway, and, therefore, the light emitting source is mainly visible only by viewing axially along or substantially along the line of direction of the passageway. For example, the inner surface of the passageway may be stippled or textured or faceted to make the passageway substantially light absorbing, or the inner surface may include a honeycomb structure that may substantially absorb the light that is not directed along the axis of the passageway.

Optionally, the blind spot indicator of the present invention may include a blind spot alert indicator stencil or mask, at the front surface of the back plate and behind the reflective element, for providing a dark mask at the indicator module or passageway while having a cut out of the desired or appropriate icon or light pattern for viewing by the driver of the vehicle (or other person in the subject vehicle or in a vehicle approaching or at the side of the subject vehicle) when the indicator or illumination source is activated. For example, and as shown in FIGS. **19A-C**, a back plate **420** may include a blind spot indicator mounting portion **426** (such as at an inboard portion or region of the back plate) and blind spot indicator or alert module or element **422**. Optionally, the blind spot indicator or alert module or element **422** at mounting portion **426** may utilize aspects of the blind spot indicator or alert module or element **222b** and/or the indicator modules and mounting portions described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, which is hereby incorporated herein by reference in its entirety.

In the illustrated embodiment, mounting portion **426** comprises a hollow tube **427** integrally formed with and extending from the rear of the back plate **420**, and with a passageway extending therethrough or therealong, whereby the indicator module **422** is mounted at the rearward portion of the hollow tube **427**. An indicator stencil or mask or masking element **425** is disposed at the front surface of the planar portion **420a** of back plate **420** (and preferably received within a recess **420c** established at the front surface of the planar portion **420a** of back plate **420**) and generally at the forward end of the passageway extending through the hollow tube **427**. The indicator module **422** includes an illumination source or LED **428** that is operable to emit light into and along and through the passageway of the hollow tube **427** and through the stenciled element or masking element **425** and toward and through the reflective element **418** (FIG. **19C**) for viewing by the driver of the vehicle.

Optionally, the indicator module **422** may include a light control film **429** (such as a light control film of the types described above with respect to indicator modules **322a**, **322b**, **322a'**, **322b'**) to direct the light emitted by illumination source **428** in a direction generally along the passageway of the hollow tube **427** of indicator mounting portion **426**.

As can be seen in FIG. **19B**, the masking element **425** may be a dark or opaque substrate or element **425a** with one or more apertures or icons or characters or patterns **425b** etched or cut or otherwise established therethrough so that light will pass through the apertures or icons yet not through the other portions of the masking element. The reflective element **418** comprises a transfective display-on-demand reflective element that is partially transmissive to allow the light from the indicator module **422** to transmit through the stenciled icons **425b** of masking element **425** and through the transfective reflective element. The transfective reflective element **418** is substantially reflective of light incident thereon, such the dark masking element **425** is substantially hidden or substantially non-viewable or discernible by a person viewing the reflective element when the indicator module is deactivated. Thus, the blind spot indicator is viewable and discernible when the illumination source **428** of indicator module **422** is activated and is substantially not viewable or discernible when the illumination source **428** of indicator module **422** is deactivated.

Back plate **420** includes an actuator mounting portion **420b** for attaching the back plate and reflective element to a mirror actuator for providing adjustment of the reflective element by the driver of the vehicle. The indicator module and mounting portion **426** are disposed toward the inboard side of the reflective element subassembly and at a space that is available to the rear of the reflective element and clear of the mirror actuator.

Optionally, the reflective element subassembly and/or indicator module of the present invention may include a non-illuminated icon etched or otherwise formed or established at the mirror reflector and at or near an illuminated blind spot indicator so as to be readily viewed by the driver of the vehicle when the blind spot alert indicator is activated (such as in response to a detection of a vehicle or object in a lane adjacent to the subject vehicle and/or in response to the driver of the subject vehicle activating a turn signal indicator in anticipation of making a lane change and/or the like). For example, and as shown in FIG. **20A**, a reflective element subassembly **510** includes a reflective element **518** and a back plate **520**, which includes a turn signal indicator mounting portion **526a** (such as at an outboard portion or region of the back plate) and a blind spot indicator mounting portion **526b** (such as at an inboard portion or region of the back plate), such as in a similar manner as described above with respect to the reflective element subassembly of FIG. **16**. In the illustrated embodiment, the turn signal indicator mounting portion **526a** and signal indicating module **522a** include a translucent block or indicating light source or element **524** and illumination source **528a** at a rear portion of the mounting portion **526a** and generally at a light baffle **530** of back plate **520**. Optionally, the blind spot indicator or alert module or element **522b** at mounting portion **526b** may utilize aspects of the indicator modules and mounting portions described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, which is hereby incorporated herein by reference in its entirety, and may comprise a hollow tube **527** integrally formed with and extending from the rear of the back plate **520**, and with a passageway extending therethrough or therealong, whereby the indicator module **522b** is mounted at the rearward

portion of the hollow tube **527**. The indicator module **522b** includes an illumination source or LED **528b** that is operable to emit light into and along and through the passageway of the hollow tube **527** and toward and through the reflective element **518** for viewing by the driver of the vehicle. Back plate **520** also includes an actuator mounting portion **520b** for attaching the back plate and reflective element to a mirror actuator for providing adjustment of the reflective element by the driver of the vehicle.

The reflective element **518** may comprise any type of reflective element, preferably a transfective or display on demand type reflective element such as described above. In the illustrated embodiment, reflective element **518** comprises a transfective electrochromic reflective element having a first or front substrate **540** and a second or rear substrate **542** with an electrochromic medium **543** sandwiched therebetween and sealed with a perimeter seal **544**. The front substrate **540** includes a transparent conductor coating **546** at its rear surface and may include a perimeter metallic band **550** at the perimeter of the rear surface, such as described above. The reflective element may comprise a "third surface" reflective element with its rear substrate **542** having a transfective coating or a metal oxide/metal/metal oxide stack (with at least one of the metal oxide layers that contacts any electro-optic medium comprising a conducting or semiconducting layer), such as an IMI stack of coatings or layers **548**, at its front surface. An icon or character or indicia **525** may be etched or otherwise created or established (such as via masking during deposition of the reflector coating or later etching or ablation or the like) at and at least partially through the third surface reflective coatings or layers **548**.

The back plate **520** is adhered or attached at the rear surface of the rear substrate, and the mirror reflective element sub-assembly **512** may include a heater element **538** and an opacifying element or layer or coating or film **552** disposed between the back plate and rear substrate. As can be seen in FIG. **20A**, the heater element **538** and opacifying layer **552** include apertures therethrough (or transparent or translucent or light transmitting or light diffusing portion or portions of the heater element and/or opacifying layer) at the location of the light baffle **530** and the passageway of the indicator mounting portion **526b** of the back plate **520**, so that light emanating from the signal indicating modules **522a**, **522b** is transmitted through the apertures in the heater element and opacifying layer and through the reflective element for viewing by a person viewing the reflective element at the appropriate angle.

The icon or indicia may be formed through the reflector coating or coatings or partially through the reflector coating or coatings and thus may provide a non-reflective icon (which may appear as a dark icon due to the darkened or opaque opacifying element or layer **552**), or may provide a partially reflective icon or indicia and may be a different tint or color as compared to the spectral reflectivity of the reflector coatings or layers. Optionally, the indicia may be established utilizing aspects of the reflective element assemblies described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008; and/or PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties. Optionally, if the reflective element has a transfective reflector, the reflective element may have a white or light colored layer or element behind the reflective element at the icon or indicia to make the presence of icon

or indicia less covert and thus to provide enhanced viewing of the icon or indicia (by giving an indication of the presence of the icon or indicia without establishing a window through the mirror reflector). Thus, the presence of the blind spot feature is subtly rendered when the mirror reflective element is viewed such as on a sunny day. Since the translector of the transfective mirror element can be made to have a visible light transmission of about 20% T to as high as about 35% T, or higher, the use of a white or lighter colored element or icon or mask close to and contacting the substrate surface to the rear of the reflective element's substrate, and adjacent to where the blind spot indicator will illuminate, can stand out during daylight and be perceived in contrast to the otherwise highly light absorbing, generally opaque backing at the rear of the transfective mirror element. Thus, the owner of the vehicle gets a subtle indication that the vehicle is equipped with such a "another-vehicle-is-in-a-side-lane" blind spot alert system.

The icon or icons **525** etched or otherwise established at the mirror reflector are located at or near or adjacent to where the illuminated blind spot indicator **523** is viewable to the driver of the subject vehicle. As can be seen in FIG. 20B, the illumination of the blind spot indicator (via activation of the illumination source **528b** of blind spot indicator module **522b**) functions to alert the driver or draw the driver's attention to that region of the reflective element where the indicator is disposed. The non-illuminated icon functions to indicate to the driver that the illuminated indicator pertains to the blind spot detection system so that the driver is alerted to a detection of a vehicle or object at or in the respective blind spot of the vehicle. As can also be seen in FIG. 20B, the turn signal module **522a** is activatable to illuminate a turn signal indicator icon **529** for viewing by the drivers of other vehicles rearward of and/or to the side of the subject vehicle. Because the reflective element **518** is preferably a transfective display-on-demand reflective element, the illuminated icons or indicators are viewable by a person viewing the reflective element when they are activated, but are substantially not viewable or discernible by a person viewing the reflective element when they are deactivated.

Thus, the indicator module is covertly placed at the back plate and behind the reflective element so that it is not readily visible to a person viewing the reflective element when the illumination source is deactivated. The dark or black walled passageway of the back plate functions to camouflage the presence of the indicator module. The length of the passageway and indicator mounting portion is selected so that the indicator module is located far enough back from the reflective element so as to be substantially not visible to a person viewing the reflective element (when the illumination source or module is deactivated). Preferably, the indicator module is disposed or located at least about 0.5 cm back from the rear surface of the reflective element, and more preferably is disposed or located at least about 1 cm back from the rear surface of the reflective element, and more preferably is disposed or located at least about 1.5 cm back from the rear surface of the reflective element. However, the indicator module may be located closer to or further back from the reflective element while remaining within the spirit and scope of the present invention.

Therefore, the indicator mounting portion and back plate and the signal indicating module of the present invention provide enhanced displays or indications at the mirror reflective element, while reducing the costs and complexities associated with displays or indicators of the prior art. For example, an advantage of creating a light baffle via molding the back plate is that such a back plate and light

baffle obviates the costs and complexities associated with utilizing a separate light control film, such as what is disclosed in U.S. Pat. Nos. 4,906,085; 5,355,284; 5,788,357 and 6,045,243, which are hereby incorporated herein by reference in their entireties. Further, utilizing the glow block and its simple construction obviates the complexities and costs associated with the prior art mirror assemblies, such as those described in U.S. Pat. Nos. 5,788,357 and 6,045,243, which are hereby incorporated herein by reference in their entireties.

Thus, the mirror assembly or assemblies of the present invention obviate the need to have the likes of a collimating optical element and/or a refractive optical element or optical elements having total internal reflective portions. As can be seen from the figures and the above discussions, the present invention has a very economical construction comprising a glowing light source or block and a light baffle (which may comprise a light directing film or the innovative establishment of a light baffle during the molding of the back plate itself). The present invention thus may provide a reduced cost indicator for a turn signal indicator or blind spot alert indicator at an exterior rearview mirror of the vehicle. Optionally, aspects of the present invention may be utilized for displays or indicators of an interior rearview mirror assembly, while remaining within the spirit and scope of the present invention.

The angle and direction of the indicator mounting portions may be selected depending on the particular associated display indicia or icons and on the particular mirror application. The reflector carrier or back plate of the mirror reflector sub-assemblies may have an aperture or opening therethrough for at least partially receiving the indicator mounting portion or portions or hollow tube or tubes or passageways therethrough when the back plate is attached to the rear surface of the reflective element, whereby the hollow tube or tubes (and associated indicator or indicators) may protrude at least partially through the back plate when the mirror reflector sub-assembly is assembled. Optionally, the icons or displays of the mirror reflector sub-assemblies described herein may be established utilizing aspects of the icons or symbols or indicia described in U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008; and/or PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties.

Optionally, the mirror reflector sub-assembly may include masks or baffles or additional light direction means or occluding means or directional filtering. For example, the mirror reflective element sub-assembly may comprise louvers or shutters for shading from view, or filters or light directing film or the like, at the rear of the reflective element (such as between the back plate and the iconistic portions) for further directing or guiding the illumination from the illumination source at the desired angle and through the reflective element so as to be principally or solely viewable by the driver of the host vehicle (for blind spot/LCA applications) or so as to be principally or solely viewable by others at the side or rear of the vehicle but not principally by the host driver (for turn signal applications).

Therefore, the present invention provides a back plate that includes one or more indicator mounting portions or display receiving portions integrally formed therewith, so that the display element or device may be readily assembled to the mirror reflector sub-assembly via attachment or adherence of the back plate to the mirror reflective element. The present

invention thus provides a display element or device that is readily assembled to a mirror reflector sub-assembly, and thus facilitates assembly of the mirror reflector sub-assembly at a facility remote from the mirror assembly facility, such that the mirror reflector sub-assembly (including the back plate and indicator mounting portion) may be provided or supplied to the mirror manufacturer as a unit. The mirror manufacturer then may install or attach the indicator or indicator module to the indicator mounting or receiving portion (or may electrically connect an already installed indicator to a wire or lead of the mirror assembly), and may attach the mirror reflector sub-assembly to the mirror actuator. The present invention thus provides enhanced assembly processing of the mirror assembly, while taking advantage of the otherwise typically unused space within the casing and behind the back plate of the exterior rearview mirror assembly. For example, a mirror manufacturer may purchase a sealed, pre-assembled signal indicator module (including the necessary electrical connectors for establishing electrical connection and power and control to the module as it is attached or mounted to the reflective element or back plate), and may insert the module into the housing or shell or structure of the back plate (that is pre-configured to receive such) or may otherwise engage the module with the rear of the reflective element assembly, such as by inserting one end of the module into the side walls of the shell or structure of the back plate and against the rear of the reflective element, whereby the module makes an at least partially efficient optical connection/coupling to the rear surface or portion of the transreflective reflective element or to a light transmitting portion of any heater pad disposed between the back plate and the rear of the reflective element, preferably while also making a mechanical connection and alignment to the back plate of the reflective element assembly. Note that the receiving portion of the back plate at the rear of the heater pad/reflective element and where the signal indicator/light unit emits light therethrough when its light source or light sources are activated may itself comprise a resilient light transmitting clear and/or light-diffusing material or element (such as a low durometer soft plastic material or element, such as an element having less than 120 Shore A durometer hardness for example, such as a silicone pad or film, or such as an optical adhesive or optical tape or film) that at least one of (a) light-couples the receiving part of the back plate to the signal indicator/light unit and (b) light couples the part of the back plate where the signal indicator/light unit is disposed at (and emits light through) to the corresponding aperture or light transmitting window of the heater pad and/or to the rear surface of the substrate of the reflective element.

Optionally, a spring-like resilient light transmitting and/or light diffusing interface or pad, such as a silicone or other soft or pliable plastic having light transmitting qualities, may be provided at the interface end of the module (or at or in any aperture in the back plate where a light indicator shines through) to provide an interface at the rear (typically a glass surface that may be coated or uncoated) of the reflective element with little or no air gap between the module and the rear of the reflective element. Also, the indicator module (having a shape or structure, such as a triangular or trapezoid shape or the like, with one or more light sources or light emitting diodes and an electrical connector) may have a light transmitting element or window or lens (that may or may not have an optical light directing property) at its interfacing end that is at least somewhat soft or pliable, so that the module creates intimate contact at the rear of the reflective element when pressed against the reflective element. The module may be purchased with the

light transmitting interface or pad already incorporated therein, or the pad may be a separate element at the rear of the reflective element or may be separately disposed between the module and the rear of the reflective element.

The signal indicator or blind spot indicator or turn signal indicator of the present invention thus provides a visible signal that is viewable at the exterior mirror by a person viewing the reflective element of the exterior rearview mirror at or near an appropriate angle or location relative to the exterior mirror. If the mirror reflective element is not a transreflective mirror reflective element (such as a construction using laser ablation to create a hole or holes in the mirror reflector such as is now used on the likes of 2008 Toyota Tundra and 2008 Cadillac Escalade vehicles), the size of the icon or indicia of the display or signal indicator module is typically limited if used for blind spot indication, such as to a size dimension that is circumscribed by a circle having a diameter of about 5 mm to about 7 mm or less, since a larger indicator or display may interfere with viewing of the reflective element during normal driving conditions and when the signal indicator module is not activated, and may be aesthetically unacceptable. However, if the reflective element is a transreflective mirror reflective element, the display area or icon or indicia may be larger than that of a non-transreflective mirror reflective element, and may have a size dimension that is circumscribed by a circle having a diameter of greater than about 7 mm or preferably greater than about 15 mm and up to about 30 mm or thereabouts. This is because, for transreflective mirror reflector applications, the icon or indicia or display of the signal indicator module is only viewable and discernible by a person viewing the rearview mirror assembly when it is activated and, thus, when it is desired or appropriate that the person viewing the mirror assembly readily sees and discerns the signal, and is substantially not viewable or discernible during normal driving conditions and when the signal indicator module is deactivated.

Desirably, the signal indicator module (such as for a blind spot indicator) will be sufficiently bright or intense when activated so as to be viewable during high ambient or daytime driving conditions. For example, the blind spot indication signal indicator module preferably has a luminance of preferably in the range of about 5,000 nits (candelas/square meter) to about 30,000 nits or greater when activated during daytime and when viewed via the reflective element from the front along its axis of highest brightness/directionality, and with the blind spot signal indicator behind the reflective element and emitting light therethrough. The signal indicator module is operable (such as via a photo sensor control) to have a significantly reduced intensity during low ambient lighting, night time driving conditions (and may be automatically adjusted to the reduced intensity in response to an ambient light sensor detecting an ambient light level at or below a threshold light level).

Although shown and described as being located at a driver side exterior mirror, the blind spot/LCA/turn signal indicator of the present invention may also or otherwise be located at the passenger side exterior mirror, if desired. Optionally, a blind spot indicator in accordance with the present invention may be located at both the driver side mirror assembly and the passenger side mirror assembly of the host vehicle. The indicator at either side may be selectively activated or illuminated to indicate to the driver of the host vehicle that an object or other vehicle has been detected at that particular side lane region of the host vehicle. Optionally, the blind spot indicator may be associated with a blind spot detection and indication system that includes one or more indicators at

the interior rearview mirror assembly of the host vehicle. The blind spot indicators may utilize aspects of the blind spot indicators and/or blind spot detection systems described in U.S. Pat. Nos. 6,198,409; 5,929,786 and 5,786,772, and/or PCT Application No. PCT/US2006/026148, filed Jul. 5, 2006 and published Jan. 11, 2007 as International Publication No. WO 2007/005942, which are hereby incorporated herein by reference in their entireties.

Such an indicator or indicators may function as a lane change assist (LCA) indicator or indicators and/or a blind spot indicator or indicators. Such blind spot indicators are typically activated when an object is detected (via a side object or blind spot detection system or the like such as described in U.S. Pat. Nos. 7,038,577; 6,882,287; 6,198,409; 5,929,786 and 5,786,772, and/or U.S. patent application Ser. No. 11/315,675, filed Dec. 22, 2005, now U.S. Pat. No. 7,720,580; and/or PCT Application No. PCT/US2006/026148, filed Jul. 5, 2006 and published Jan. 11, 2007 as International Publication No. WO 2007/005942, which are hereby incorporated herein by reference in their entireties) at the side and/or rear of the vehicle (at the blind spot) and when the turn signal is also activated, so as to provide an alert to the driver of the host vehicle that there is an object or vehicle in the lane next to the host vehicle at a time when the driver of the host vehicle intends to move over into the adjacent lane. Optionally, and alternately, the indicator or indicators may function as a lane change assist indicator or indicators, where the host vehicle may be detected to be moving into an adjacent lane without the turn signal being activated, and an object or vehicle may be detected at the adjacent lane, whereby the LCA indicator or indicators may be activated to provide an alert to the driver of the lane change to assist the driver in avoiding unintentional lane changes and/or lane changes when a vehicle or object is detected in the adjacent lane.

A challenge to providing an indicator at the exterior rearview mirror reflective element is that the back plate and associated components of the exterior reflective element subassembly may be exposed to harsh environmental conditions, such as water spray, rain, dirt and debris and the like, when the reflective element is mounted at a vehicle. Thus, it is desirable to provide a sealed, water impervious indicator module or display element so as to limit or substantially preclude water ingress or the like into the module or element. Optionally, the back plate and indicator module may be integrally molded to limit water entry into the module, whereby the illumination source and/or light directing film or the like may be sealed at the module to protect the electronic components of the module. Optionally, a lens or cover element may be provided at the planar portion of the back plate and may be sealed thereat to limit water entry into the indicator module through the back plate.

Optionally, and desirably, the display element or signal indicating module (such as a module of the types having a hollow tube configuration or a translucent block configuration as described above) may comprise a stand-alone unitary module that is a substantially sealed, water impervious, indicator module or display module, so as to be substantially impervious to water ingress or to debris ingress, and preferably with electrical connectors (such as a plug or socket connector) established or incorporated therein or with a lead or wire harness (such as a flying lead or pigtail) established or incorporated therein. The indicator module may be provided as a sealed or substantially sealed unit or module that can be snapped into or otherwise attached or secured (preferably mechanically but optionally adhesively) at the mirror back plate (and does so substantially or wholly sealingly to

limit or substantially preclude water ingress to the module so that the module and back plate are substantially water impervious), preferably at the mirror sub-assembly manufacturing operation when the mirror reflective element (and any associated heater or other item or element) is joined to the mirror back plate, such as by utilizing aspects of the indicators described in U.S. patent application Ser. No. 11/520,193, filed Sep. 13, 2006, now U.S. Pat. No. 7,581,859, and/or PCT Application No. PCT/US2006/018567, filed May 16, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entireties. For example, the indicator module may be provided with the illumination source and associated elements sealed to the hollow tube or sidewalls of the module, and a lens or optic element (such as a transparent lens element or the like) may be sealed at the opposite end of the hollow tube or housing structure of the module, such that both ends of the hollow tube or housing structure of the module are closed and sealed so that the module is substantially water impervious as a stand-alone module. The sealed signal indicating module, including the light source and circuitry, may be supplied or provided to an assembly facility (such as a mirror assembly facility or the like) from a display element supplier, while the back plate may be molded and supplied or provided to the assembly facility from a back plate supplier. An operator at the assembly facility may attach the display device or indicator module and/or circuitry to the back plate (such as to the rear surface of the display receiving portion of the back plate), preferably by snapping the display device or module to snaps or clips or clasps or fingers or the like molded into the back plate (at its display element receiving portion) to assemble the display or indicator module to the back plate. Optionally, and desirably, the display receiving portion of the back plate and/or the display element (such as at the circuit element or circuit board) or indicator module may have attaching elements or snaps or clips or prongs (such as cooperating structure molded into the module and back plate so that the module is readily attached to or snapped or clasped to the back plate) to ease the assembly and securement of the display element or indicator module to the back plate, such as at or to a display receiving portion of the back plate, so that an operator may attach the display element or indicator module to the back plate via a snap connection or attachment.

Optionally, and desirably, electrical connection (such as to a power supply or 12 volt power wire of the vehicle battery/ignition system or to a power feed from a LIN bus controller) to the display circuitry may be made when the display element is snapped or otherwise attached (preferably mechanically but optionally adhesively) to the back plate, such as by making electrical contact between the display element and mirror circuitry (including circuitry associated with the reflective element and/or mirror assembly, such as electrochromic mirror circuitry, mirror lights and/or display circuitry and the like, typically disposed at a printed circuit board of the mirror assembly) when the display element is snapped to the back plate, such as via pressed contact or connection between respective electrical terminals or contacts of the display element and mirror circuitry as the display element is pressed or snapped or received to the display receiving portion of the back plate, such as by press attaching the display element or module into receiving fingers or clips or snaps or the like that are integrally formed with the display receiving portion of the back plate in the injection molding operation that manufactures or forms the back plate itself. For example, electrical terminals or con-

tacts may be insert molded in the display receiving portion so as to be exposed at (or otherwise located at) the rear surface of the display receiving portion for electrical connection to the display element when the display element is attached or snapped to the display receiving portion of the back plate. Alternately, electrical connection to the display device may be made via other means, such as wires or leads or flying leads or wire harnesses or the like such as pigtailed or other suitable connectors or leads, and before or after the display device is snapped or otherwise attached to the back plate, while remaining within the spirit and scope of the present invention.

Thus, a method of assembling such a mirror reflective element sub-assembly may include molding the back plate having an indicator mounting or receiving portion and providing the back plate and reflective element to an assembly facility, while also providing a display element or signal indicating module at the assembly facility. Preferably, the display element and the back plate are supplied or provided to the assembly facility from different sources. An operator at the assembly facility takes a back plate and a display element and snaps the display element to the rear surface of the display receiving portion of the back plate to attach and secure the display element at the display receiving portion. The operator also makes the electrical connection between circuitry or wiring of the mirror assembly or sub-assembly and the display element, either as the display element is snapped to the display receiving portion of the back plate (such as via contacts at the display element and display receiving portion of the back plate) or at a separate time from the attachment of the display element to the back plate (such as via separate connectors at or extending from the display element). Optionally, electrical connection to the display element may be made during assembly of the reflective element sub-assembly to the mirror casing of the mirror assembly (such as via connectors or leads or pigtailed extending from the display element).

Thus, the display elements or devices or modules of the present invention provide a desired or appropriate iconistic display or indication that, when electrically actuated, emits light that is viewable by a person viewing the mirror reflective element. The display element may be formed with the back plate or may attach to the back plate (such as by snapping to the back plate or the like), and provides the desired angle effect relative to the reflective element. For example, the reflective element may be attached to or snapped into the back plate (which includes the display element at a perimeter region thereof), whereby the display element or module is thus positioned at a desired or appropriate angle relative to the reflective element to provide the desired or appropriate angle effect for directing the light from the light sources (when electrically actuated) in a desired or predetermined angle relative to the mirror reflective element. Thus, the display element provides the desired or appropriate preset angle when the mirror reflective element is attached to the back plate.

The blind spot indicators of the present invention thus provide a display element or indicator that is disposed at or integrally provided with the back plate. A back plate thus may be provided to a mirror manufacturer with mounting or attachment structure or receiving structure for the display element or display circuitry integrally formed with the back plate. The attachment structure or receiving portion is configured to receive or attach to a display element or display circuitry or indicator element. A mirror assembler or manufacturer may attach the display element to the attachment structure or receiving portion of the back plate (such as by

snapping display circuitry or a circuit board at the attachment structure), whereby the display element is oriented at a desired angle relative to the mirror reflective element when attached to the back plate. Thus, illumination emanating from the display element is directed at the desired or appropriate angle for viewing, either by the driver of the host vehicle (for a blind spot detection system) or a driver of another vehicle (for a turn signal indicator).

The blind spot indicators of the present invention thus are operable to provide an indication to the driver of the host vehicle that an object or other vehicle has been detected in the lane or area adjacent to the side of the host vehicle. The blind spot indicator may be operable in association with a blind spot detection system, which may include an imaging sensor or sensors, or an ultrasonic sensor or sensors, or a sonar sensor or sensors or the like. For example, the blind spot detection system may utilize aspects of the blind spot detection and/or imaging systems described in U.S. Pat. Nos. 7,038,577; 6,882,287; 6,198,409; 5,929,786 and/or 5,786,772, and/or U.S. patent application Ser. No. 11/239,980, filed Sep. 30, 2005, now U.S. Pat. No. 7,881,496; and/or Ser. No. 11/315,675, filed Dec. 22, 2005, now U.S. Pat. No. 7,720,580, and/or U.S. provisional applications, Ser. No. 60/638,687, filed Dec. 23, 2004; Ser. No. 60/628,709, filed Nov. 17, 2004; Ser. No. 60/614,644, filed Sep. 30, 2004; and/or Ser. No. 60/618,686, filed Oct. 14, 2004, and/or of the reverse or backup aid systems, such as the rearwardly directed vehicle vision systems described in U.S. Pat. Nos. 5,550,677; 5,760,962; 5,670,935; 5,877,897; 6,201,642; 6,396,397; 6,498,620; 6,717,610 and/or 6,757,109, and/or U.S. patent application Ser. No. 10/418,486, filed Apr. 18, 2003, now U.S. Pat. No. 7,005,974, and/or of the automatic headlamp controls described in U.S. Pat. Nos. 5,796,094 and/or 5,715,093; and/or U.S. patent application Ser. No. 11/105,757, filed Apr. 14, 2005, now U.S. Pat. No. 7,526,103; and/or U.S. provisional application Ser. No. 60/607,963, filed Sep. 8, 2004, and/or of the rain sensors described in U.S. Pat. Nos. 6,250,148 and 6,341,523, and/or of other imaging systems, such as the types described in U.S. Pat. Nos. 6,353,392 and 6,313,454, which may utilize various imaging sensors or imaging array sensors or cameras or the like, such as a CMOS imaging array sensor, a CCD sensor or other sensors or the like, such as the types disclosed in commonly assigned, U.S. Pat. Nos. 5,550,677; 5,760,962; 6,097,023 and 5,796,094, and U.S. patent application Ser. No. 09/441,341, filed Nov. 16, 1999, now U.S. Pat. No. 7,339,149, and/or PCT Application No. PCT/US2003/036177 filed Nov. 14, 2003, published Jun. 3, 2004 as PCT Publication No. WO 2004/047421, with all of the above referenced U.S. patents, patent applications and provisional applications and PCT applications being commonly assigned and being hereby incorporated herein by reference in their entireties.

Optionally, the indicator or indicators of the present invention may alert the driver of the host vehicle of other situations or status or the like. For example, the indicator could function to alert the driver of the host vehicle that the brake lights of the host vehicle are functioning properly. Other applications or uses of the indicator may be implemented, without affecting the scope of the present invention.

The reflective element of the rearview mirror assembly may comprise an electro-optic or electrochromic reflective element or cell, such as an electrochromic mirror assembly and electrochromic reflective element utilizing principles disclosed in commonly assigned U.S. Pat. Nos. 6,690,268; 5,140,455; 5,151,816; 6,178,034; 6,154,306; 6,002,544; 5,567,360; 5,525,264; 5,610,756; 5,406,414; 5,253,109;

5,076,673; 5,073,012; 5,117,346; 5,724,187; 5,668,663; 5,910,854; 5,142,407 and/or 4,712,879, and/or U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008, and/or PCT Application No. PCT/US2006/018567, filed May 16, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, and/or U.S. provisional applications, Ser. No. 60/695,149, filed Jun. 29, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; Ser. No. 60/681,250, filed May 16, 2005; and/or Ser. No. 60/692,113, filed Jun. 20, 2005, which are all hereby incorporated herein by reference in their entireties, and/or as disclosed in the following publications: N. R. Lynam, "Electrochromic Automotive Day/Night Mirrors", SAE Technical Paper Series 870636 (1987); N. R. Lynam, "Smart Windows for Automobiles", SAE Technical Paper Series 900419 (1990); N. R. Lynam and A. Agrawal, "Automotive Applications of Chromogenic Materials", Large Area Chromogenics: Materials and Devices for Transmittance Control, C. M. Lampert and C. G. Granquist, EDS., Optical Engineering Press, Wash. (1990), which are hereby incorporated by reference herein in their entireties. The thicknesses and materials of the coatings on the substrates of the electrochromic reflective element, such as on the third surface of the reflective element assembly, may be selected to provide a desired color or tint to the mirror reflective element, such as a blue colored reflector, such as is known in the art and/or such as described in U.S. Pat. Nos. 5,910,854; 6,420,036 and 7,274,501, and in PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633, which are all hereby incorporated herein by reference in their entireties.

Optionally, use of an elemental semiconductor mirror, such as a silicon metal mirror, such as disclosed in U.S. Pat. Nos. 6,286,965; 6,196,688; 5,535,056; 5,751,489 and 6,065,840, and/or in U.S. patent application Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177, which are all hereby incorporated herein by reference in their entireties, can be advantageous because such elemental semiconductor mirrors (such as can be formed by depositing a thin film of silicon) can be greater than 50 percent reflecting in the photopic (SAE J964a measured), while being also substantially transmitting of light (up to 20 percent or even more). Such silicon mirrors also have the advantage of being able to be deposited onto a flat glass substrate and to be bent into a curved (such as a convex or aspheric) curvature, which is also advantageous since many passenger-side exterior rearview mirrors are bent or curved.

Optionally, the reflective element may include a perimeter metallic band, such as the types described in U.S. Pat. Nos. 7,255,451 and 7,274,501, and PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; and/or PCT Application No. PCT/US03/35381, filed Nov. 5, 2003 and published May 21, 2004 as International Publication No. WO 2004/042457; and/or U.S. patent application Ser. No. 11/226,628, filed Sep. 14, 2005 and published Mar. 23, 2006 as U.S. Publication No. US-2006-0061008; and/or U.S. provisional applications, Ser. No. 60/692,113, filed Jun. 20, 2005; Ser. No. 60/677,990, filed May 5, 2005; Ser. No. 60/653,787, filed Feb. 17, 2005; Ser. No. 60/642,227, filed Jan. 7, 2005; Ser. No. 60/638,250, filed Dec. 21, 2004; Ser. No. 60/624,091, filed Nov. 1, 2004, and Ser. No. 60/609,642, filed Sep. 14, 2004, which are all hereby incorporated herein

by reference in their entireties. Optionally, the reflective element may include indicia formed at and viewable at the reflective element, such as by utilizing aspects of the reflective elements described in PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682; and U.S. provisional applications, Ser. No. 60/681,250, filed May 16, 2005; Ser. No. 60/690,400, filed Jun. 14, 2005; Ser. No. 60/695,149, filed Jun. 29, 2005; Ser. No. 60/730,334, filed Oct. 26, 2005; Ser. No. 60/750,199, filed Dec. 14, 2005; Ser. No. 60/774,449, filed Feb. 17, 2006; and Ser. No. 60/783,496, filed Mar. 18, 2006, which are all hereby incorporated herein by reference in their entireties.

Optionally, the reflective element may comprise a single substrate with a reflective coating at its rear surface, without affecting the scope of the present invention. The mirror assembly thus may comprise a prismatic mirror assembly or planar or non-planar mirror or other mirror having a single substrate reflective element, such as a mirror assembly utilizing aspects described in U.S. Pat. Nos. 6,318,870; 6,598,980; 5,327,288; 4,948,242; 4,826,289; 4,436,371 and 4,435,042; and PCT Application No. PCT/US04/015424, filed May 18, 2004 and published Dec. 2, 2004 as International Publication No. WO 2004/103772; and U.S. patent application Ser. No. 10/933,842, filed Sep. 3, 2004, now U.S. Pat. No. 7,249,860, which are hereby incorporated herein by reference in their entireties. Optionally, the reflective element may comprise a conventional prismatic or flat reflective element or prism, or may comprise a prismatic or flat reflective element of the types described in PCT Application No. PCT/US03/29776, filed Sep. 19, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; U.S. patent application Ser. No. 10/709,434, filed May 5, 2004, now U.S. Pat. No. 7,420,756; Ser. No. 10/933,842, filed Sep. 3, 2004, now U.S. Pat. No. 7,249,860; Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or Ser. No. 10/993,302, filed Nov. 19, 2004, now U.S. Pat. No. 7,338,177, and/or PCT Application No. PCT/US2004/015424, filed May 18, 2004 and published Dec. 2, 2004 as International Publication No. WO 2004/103772, which are all hereby incorporated herein by reference in their entireties, without affecting the scope of the present invention.

Optionally, and with reference to FIGS. 21A, 21B and 22, a reflective element **618** may comprise a vehicular electrochromic reflective element (but could comprise a non-electrochromic reflective element without affecting the scope of the present invention) having a front substrate **640** (such as a transparent glass substrate or the like), a rear substrate **642** (such as a transparent glass substrate or the like) and an electrochromic medium **643** (such as a solid polymer matrix electrochromic medium such as the types disclosed in U.S. Pat. Nos. 5,724,187 or 5,910,854, or a liquid electrochromic medium such as the types disclosed in U.S. Pat. No. 4,902,108, the entire disclosures of which are incorporated by reference herein, or the like) sandwiched therebetween and sealed via a perimeter seal **644**. Front substrate **640** has a transparent conductor coating **646** (such as an indium tin oxide (ITO) coating or layer) disposed at its rear surface **640a**, while rear substrate **642** has a transreflective mirror reflector or transreflector coating **648** (such as a non-dichroic transreflector, such as an IMI stack such as an ITO/Ag/ITO stack of layers or coatings or the like) disposed at its front surface **642a**. The reflective element **618** includes a third surface tab-in portion or coating **650** and a fourth surface wraparound coating **652** at an edge region of the rear substrate so as to provide electrical conductivity or conti-

nunity between the fourth or rear surface **642b** of the rear substrate **642** and the front or third surface **642a** of the rear substrate **642**.

As can be seen in FIGS. **21A**, **21B** and **22**, the tab-in coating **650** may be established (such as via sputter deposition or other suitable coating or establishing means) at a perimeter region **643** of the third or front surface **642a** of the rear substrate **642** and at least partially around and over the perimeter edge dimension **656** of rear substrate **642**, while the fourth or rear surface wraparound coating **652** may be disposed so as to overlap a portion of the third surface tab-in portion **650** (such as at the edge dimension **656** of the rear substrate) and may wrap around at least partially onto the rear or fourth surface **642b** of the rear substrate (such as by utilizing aspects of the reflective elements described in U.S. Pat. Nos. 7,274,501; 7,255,451; 7,184,190 and 7,004,593, which are hereby incorporated herein by reference in their entirety). Optionally, the third surface tab-in portion **650** and fourth surface wraparound portion may be commonly established via a common or same deposition process or the like. The third surface tab-in portion **650** may comprise any suitable conductive materials, such as a metallic or conductive layer or coating, such as a silver or silver alloy (such as an alloy with greater than about three percent and less than about 25 percent minority content), such as a silver-palladium alloy, a silver-platinum alloy, a silver-gold alloy, a silver-rhodium alloy, a silver-ruthenium alloy or the like, or an electrically conducting metal oxide layer, such as an indium tin oxide (ITO) transparent electrically conductive layer or the like, or a thin conductive ink or frit layer or film or tape or the like.

As shown in FIGS. **21A**, **21B** and **22**, the third surface transfective mirror reflector **648** may be established at the front surface **642a** of the rear substrate **642** and with an uncoated or non-conducting pathway or raceway **654** established around the perimeter region **643** of the front surface **642a** of the rear substrate **642**, such as by masking during the deposition of the mirror reflector on the front surface or by laser ablating or otherwise deleting or removing the mirror reflector from the front surface of the rear substrate at and around the perimeter region of the front surface **642a** of the rear substrate **642**. The third surface mirror reflector **648** may comprise any suitable reflective and transmissive material or materials, such as a silicon coating or a metal oxide/metal/metal oxide stack (with at least one of the metal oxide layers comprising a conducting or semiconducting layer), such as an IMI (such as ITO/silver/ITO or other suitable alternating layers of materials or the like) stack of layers or coatings such as by utilizing aspects of the reflective elements described in U.S. Pat. Nos. 7,274,501; 7,255,451; 7,184,190; 6,690,268; 5,724,187 and/or 5,668,663, which are all hereby incorporated herein by reference in their entirety.

As can be seen in FIGS. **21B** and **22**, the third surface mirror reflector **648** is disposed on the substrate surface after the tab-in portion has already being coated or otherwise dispose on the substrate and so as to partially overlap the tab-in portion **650** (with a portion of the tab-in portion being tucked under and making electrical contact with an outboard perimeter portion of the third surface mirror reflector), and at a location that is spanned or encompassed by the perimeter seal **644**. With reference to FIG. **23**, the process **670** of forming and coating the rear substrate includes shape cutting or forming the rear substrate at **672**. The third surface of the cut substrate is then masked and coated at **674** to establish the tab-in coating or coatings at the third surface (and optionally at the edge dimension and fourth surface of the

substrate depending on the particular application). After the tab-in coating is established, the third surface of the cut substrate is remasked and coated at **676** with the third surface reflector or transfective mirror reflector or transfective coating or coatings. An outboard portion of the third surface transfective coating is thus established over the previously established tab-in portion, and at a region that is encompassed by the perimeter seal when the reflective element is assembled together and the front and rear substrates are joined and sealed together by the perimeter seal.

Optionally, and desirably, the tab-in portion comprises a thin coating or layer (such as a layer having a thickness of about 20 microns or less, such as less than 10 microns (while remaining sufficiently electrically conductive), but could be more depending on the particular application) so as to limit any step or change in thickness of the coatings under the seal (that typically has a thickness in the range of from about 80 microns to about 150 microns or thereabouts) so as to limit any effect the presence of the thickness of the tab-in coatings may have on the sealing function of the perimeter seal at that location and/or any impact it might have on the uniformity of the inter-pane spacing between the front and rear substrates (although other means for providing a substantially uniform thickness of the various layers at the perimeter seal may be implemented to reduce non-uniformity at the interface between the perimeter seal and the third surface coatings or layers, such as by having the tab-in coating or stack of coating circumscribe the perimeter of the cut shape that constitutes the rear substrate).

Thus, the overlap region of the reflector **648** and tab-in coating **650** is entirely within, is under and is encompassed/protected by the perimeter seal **644** at that location at the perimeter region of the rear substrate (with the outer edge/periphery of the potentially environmentally vulnerable third surface reflector being inboard of an outer region/wall of the perimeter seal **644** and with the inner edge/periphery of the more environmentally robust tab-in coating or coatings (such as chromium or ruthenium or the like) preferably being outboard of an inner region of the perimeter seal **644** so as not to be visible to a viewer viewing the electrochromic-active region bounded by the perimetral seal). Thus, environmental concerns or environmental vulnerability of the transfective mirror reflector coating **648** are reduced by sealing the environmentally vulnerable third surface reflector coatings entirely within and under the bounds of the perimeter seal and providing electrical continuity/connection to the mirror reflector coating via an environmentally robust, electrically conducting tab-in coating, and with the electrical joint/overlap made and terminating under the seal. Optionally, an additional encapsulant or protectant **658** (such as a silicone sealant or an epoxy sealant or another suitable sealant) may be established at the tab-in portion and fourth surface wraparound portion to environmentally seal and protect the metallic or conductive tab-in and wrap-around portions outside of the perimeter seal of the reflective element. This may conveniently be applied after the electrochromic mirror cell has been fabricated. Such additional sealing can augment the inherent environmental robustness of the tab-in coating or layers used, and such additional or secondary encapsulation well suits exterior mirror construction of the flush and/or frameless types, such as the types that are disclosed in U.S. Pat. Nos. 7,274,501; 7,255,451 and 7,184,190, which are all hereby incorporated herein by reference in their entirety.

The third surface tab-in portion thus extends from the overlap region (where the third surface reflector overlaps or overlays an inboard portion of the tab-in portion) or perim-

eter seal region and out to the perimeter edge of the cut shape of the rear substrate. In the illustrated embodiment, the tab-in portion extends over or wraps around a portion of the edge of the substrate (between the front and rear surfaces of the rear substrate), and a fourth surface wraparound portion covers a portion of the fourth surface and overlays or underlays a portion of the wraparound tab-in portion at the substrate edge. Because the reflective element does not necessarily require a wraparound coating at the edge dimension of the substrate, the tab-in portion may optionally be coated only on the perimeter region of the third or front surface of the rear substrate without any significant wrap-around or coating on the edge dimension of the rear substrate. Optionally, the tab-in portion may wraparound a portion of the edge of the substrate or may be coated substantially across the edge dimension of the substrate, yet the reflective element may not include a fourth surface wraparound portion, whereby the tab-in portion may extend to the edge of the rear substrate and may extend or encompass a portion of the edge dimension of the substrate, such that electrical connection to the tab-in portion may be made at the perimeter region of the third surface of the rear substrate or at the edge or edge dimension of the rear substrate, while remaining within the spirit and scope of the present invention. Optionally, if a fourth surface wraparound coating is desired, the fourth surface wraparound coating may be established before or after or at the same time as the tab-in portion, such as via simultaneously sputter coating the tab-in coating and the fourth surface wraparound coating at the opposite sides and perimeter edge of the substrate via a two-sided sputter coating process, such as a sputter coating process that sputter coats the top and bottom surfaces of a substrate shape held in a fixture of a sputter coating chamber (with the coatings comprising the same coating composition or different coating composition as desired).

The fourth surface wraparound electrically conductive coating (or stack of coatings) thus may be deposited or disposed or coated onto the cut-edge dimension of the substrate, which has already been first coated with a portion of the tab-in coating (or stack of coatings) that wraps around or partially wraps around the edge dimension of the substrate so that the fourth surface wraparound electrically conductive coating (or stack of coatings) overlays, and thus protects, the underlying tab-in portion. Optionally, the fourth surface wraparound coating may comprise an environmentally robust composition or material, such as metallic chromium or ruthenium or the like, and thus may provide at least some enhanced environmental protection to the undercoated tab-in portion at the edge dimension of the substrate shape. Optionally, the sputter chamber in which the substrate shape is placed for coating of the fourth surface wraparound portion may utilize baffles or scattering techniques or other means for sputter coating the more environmentally robust coating(s) of the fourth surface wraparound portion over the tab-in portion at the edge dimension of the substrate shape and/or over the tab-in portion at the third surface of the substrate. Thus, the sputter-coated environmentally-protective coating(s) may sufficiently cover the tab-in portion so as to envelop and further environmentally protect the tab-in portion of the rear substrate. Also, and for constructions such as are disclosed in U.S. Pat. Nos. 7,255,451 and 7,184,190, and/or PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which are hereby incorporated herein by reference in their entirety, where a third surface metallic reflector is principally protected by the seal of the electrochromic laminate assembly but with a tab-out

portion that extends out beyond the seal to a cut edge (and preferably wraps-around the cut edge dimension) so as to facilitate electrical connection to the metallic reflector, the fourth surface coating or stack of coatings may be extended (such as by appropriate use of baffles or scattering means during sputter deposition in a vacuum chamber) from the fourth surface, along the cut edge dimension, and along the perimeter edge portion of the third surface where the tab-out of the third surface reflector has already been established so that the fourth surface coating (or stack of coatings) can overlay and thus help environmentally-protect the tab-out portion of the third surface reflector, not just along the cut edge dimension but also along the part of the tab-out portion that extends beyond the seal at the edge perimeter of the seal on the third surface of the rear substrate of the electrochromic mirror element.

Optionally, the mirror assembly may include one or more displays, such as the types disclosed in U.S. Pat. Nos. 5,530,240 and/or 6,329,925, which are hereby incorporated herein by reference in their entirety, and/or display-on-demand or transfective type displays, such as the types disclosed in U.S. Pat. Nos. 6,690,268; 5,668,663 and/or 5,724,187, and/or in U.S. patent application Ser. No. 10/054,633, filed Jan. 22, 2002, now U.S. Pat. No. 7,195,381; Ser. No. 10/528,269, filed Mar. 17, 2005, now U.S. Pat. No. 7,274,501; Ser. No. 10/533,762, filed May 4, 2005, now U.S. Pat. No. 7,184,190; Ser. No. 10/538,724, filed Jun. 13, 2005 and published Mar. 9, 2006 as U.S. Publication No. US-2006-0050018; Ser. No. 11/284,543, filed Nov. 22, 2005, now U.S. Pat. No. 7,370,983; and/or Ser. No. 11/021,065, filed Dec. 23, 2004, now U.S. Pat. No. 7,255,451; and/or PCT Application No. PCT/US03/29776, filed Sep. 9, 2003 and published Apr. 1, 2004 as International Publication No. WO 2004/026633; and/or PCT Application No. PCT/US03/35381, filed Nov. 5, 2003 and published May 21, 2004 as International Publication No. WO 2004/042457; and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004; Ser. No. 60/667,048, filed Mar. 31, 2005; Ser. No. 60/629,926, filed Nov. 22, 2004; Ser. No. 60/531,838, filed Dec. 23, 2003; Ser. No. 60/553,842, filed Mar. 17, 2004; and Ser. No. 60/563,342, filed Apr. 19, 2004, and/or PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 and published Jul. 15, 2004 as International Publication No. WO 2004/058540, which are all hereby incorporated herein by reference in their entirety, or may include or incorporate video displays or the like, such as the types described in PCT Application No. PCT/US03/40611, filed Dec. 19, 2003 and published Jul. 15, 2004 as International Publication No. WO 2004/058540, and/or U.S. patent application Ser. No. 10/538,724, filed Jun. 13, 2005 and published Mar. 9, 2006 as U.S. Publication No. US-2006-0050018; and/or Ser. No. 11/284,543, filed Nov. 22, 2005, now U.S. Pat. No. 7,370,983; and/or U.S. provisional applications, Ser. No. 60/630,061, filed Nov. 22, 2004; and Ser. No. 60/667,048, filed Mar. 31, 2005, which are hereby incorporated herein by reference in their entirety.

Telecommunications and wireless communication/data transfer between, from and within a vehicle equipped with the present invention may be by means of airwaves designated for other technologies in the standard known as IMT-2000, and can be over networks based on WiMAX. WiMAX—Worldwide Interoperability for Microwave Access—is capable of delivering wireless broadband connections at speeds of 70 megabits per second or more across an area of up to 40 miles. It is properly referred to as 802.16e-2005. WiMAX provides wireless data over long distances in a variety of ways, from point-to-point links to

full mobile cellular type access, and is based on the IEEE 802.16 standard (which is also called WirelessMAN). The 802.16 specification applies across a wide swath of the RF spectrum, and WiMAX can function on any frequency below 10 GHz (although higher frequencies can decrease the range to a few hundred meters in an urban environment). Although there is no uniform global licensed spectrum for WiMAX, WiMAX has three licensed spectrum profiles: 2.3 GHz, 2.5 GHz and 3.5 GHz.

Optionally, and with reference to FIG. 24, a reflective element assembly 712, such as for an interior rearview mirror assembly, may include a video display element 714 at a rear portion of the reflective element 718 for viewing video display information through the reflective element when the video display element 714 is activated. In the illustrated embodiment, reflective element 718 comprises an electro-optic reflective element having a front substrate 740 (such as a transparent glass substrate or the like), a rear substrate 742 (such as a transparent glass substrate or the like) and an electro-optic medium 743 (such as a solid type, such as a solid polymer matrix electrochromic medium or the like, such as the types described in U.S. Pat. Nos. 7,004,592; 5,724,187; 5,668,663 and 5,910,854, and commonly owned and co-assigned and co-pending U.S. patent application Ser. No. 11/653,254, filed Jan. 16, 2007, now U.S. Pat. No. 7,349,144; Ser. No. 11/244,182, filed Oct. 6, 2005, now U.S. Pat. No. 7,543,947; and Ser. No. 11/655,096, filed Jan. 19, 2007, now U.S. Pat. No. 7,572,017, which are all hereby incorporated herein by reference in their entirety, or such as a liquid type, such as the types described in U.S. Pat. Nos. 4,902,108; 5,128,799 and 5,818,625, which are hereby incorporated herein by reference in their entirety) sandwiched therebetween and sealed via a perimeter seal 744. Front substrate 740 has a transparent conductor coating 746 (such as a 1/2 wave indium tin oxide (ITO) layer or doped tin oxide layer or doped zinc oxide layer, such as an AZO layer, or the like) disposed at its rear surface 740a, while rear substrate 742 has a third surface transparent electrical conductor coating 748 (such as a 1/2 wave indium tin oxide (ITO) layer or doped tin oxide layer or doped zinc oxide layer, such as an AZO layer, or the like) disposed at its front surface 742a and a fourth surface dichroic translector coating or layer or layers 749 disposed at its rear surface 742b. Optionally, the conductive coatings or layers may be disposed or deposited at the surface of the glass substrate or substrates via any suitable means, such as via a sputter deposition process or via a pyrolytic deposition process, such as by utilizing aspects described in PCT Application No. PCT/US2006/018567, filed May 15, 2006 and published Nov. 23, 2006 as International Publication No. WO 2006/124682, which is hereby incorporated herein by reference in its entirety.

The dichroic translector coating 749 of reflective element 718 comprises a stack of dielectric thin film layers, such as by utilizing aspects of optical dichroic mirrors as known in the optical dichroic mirror art. The dichroic reflector provides a reduced absorption level as compared to a metallic transmissive layer, such that the reflective element 718 may provide enhanced transmissivity of light therethrough for a given level of reflectance of light incident thereon. Preferably, the reflectivity of light off of the dichroic translector stack is greater than about 60% R, more preferably greater than about 70% R and more preferably greater than about 80% R, while the transmission of light through the dichroic translector stack may be preferably greater than about 20% T, more preferably greater than about 25% T, and more preferably greater than about 30% T, but preferably less than

about 40% T or thereabouts. Preferably, the dichroic translector stack provides a non-specularly selective (i.e., neutral and substantially untinted and "silvery") reflection of light incident thereon and is also substantially neutral in transmission across the visible range of the electromagnetic spectrum (so that the likes of color video images generated on the video screen disposed to the rear of and emitting through the reflective element can be seen substantially true-to-color), such that the dichroic translector is highly suitable for transmitting color video images therethrough. Thus, the dichroic translector provides a wide band pass transmission of light substantially across the visible band of the electromagnetic spectrum. Thus, these dichroic reflectors have a wide band pass substantially across the visible light spectrum for transmission, and similarly for reflection.

In the illustrated embodiment, the display element 714 is disposed to the rear of the dichroic translector stack 749 for emitting illumination therethrough. A light absorbing element 760 (such as a dark colored ink or paint or frit or coating or tape or film or layer or adhesive or plastic part or the like) may be disposed at the rear of the dichroic translector stack 749 (except where the display element 714 is at) to limit light transmission through the reflective element except at the display element 714. Optionally, and as shown in FIG. 23, a first surface anti-reflector 762 may be provided at or established on the front or first surface 740b of the front substrate 740 to limit reflectance of light incident on the front substrate. Optionally, the anti-reflection layer (such as an OPTIVIEW™ layer such as commercially available from Pilkington) may be deposited pyrolytically in a glass manufacturing plant, such as described above or such as is disclosed in U.S. Pat. No. 5,076,674, which is hereby incorporated herein by reference in its entirety. The anti-reflector 762 may limit or reduce the first surface reflectivity to be, for example, preferably less than about 2 percent reflective of light incident thereon, preferably less than about 1 percent reflective of light incident thereon, and more preferably less than about 0.5 percent reflective of light incident thereon.

The display element 714 may comprise any suitable display element, such as a color video screen, such as a back-lit liquid crystal display video screen, such as a back-lit thin film transistor (TFT) liquid crystal display (LCD) video screen, such as a back-lit TFT LCD video screen that is back lit by a plurality of white light emitting light emitting diodes (such as an array of at least four white light emitting light emitting diodes or the like), such as light emitting diodes that utilize aspects of the light emitting diodes described in U.S. Pat. Nos. 6,690,268; 7,167,796 and 7,195,381, which are hereby incorporated herein by reference in their entirety.

Preferably, display element 714 comprises a video screen construction of the type disclosed in PCT Application No. PCT/US2006/042718, filed Oct. 31, 2006 and published May 10, 2007 as International Publication No. WO 2007/053710, which is hereby incorporated herein by reference in its entirety, that utilizes visible light transmitting brightness enhancing films such as VIKUIT™ Dual Brightness Enhancement Films (DBEF) that are commercially available from 3M® Corporation of Minneapolis, MN and that are typically a light transmitting plastic optical film consisting of over 800 polymer layers. VIKUIT™ Dual Brightness Enhancement (DBEF) film is a reflective polarizer made using multi-layer optical polymer film technology that manages light by preferentially transmitting one polarization state (P1) while reflecting the opposite polarization state (P2) back into the display. When a DBEF film is placed to

the rear of the LCD panel of the video screen used with a video mirror of the present invention, so as to be between the LCD panel and the back-lighting light sources, and with the axis of polarization of the DBEF aligned with the axis of polarization (P1) of the polarizer at the rear of the rear glass substrate of the LCD panel, then light in the P2 polarization state emitted by the back-lighting light sources that would normally be absorbed by/not passed by the rear polarizer of the liquid crystal panel is recycled by reflection off the DBEF film back towards the back-lighting array to be in turn reflected off the likes of a mirror-like reflector of the back-lighting array with a concomitant change/scramble in handedness of polarization state back at least partially to a P1 polarization state, thus increasing the overall amount of light ultimately exiting the LCD display panel to pass through the reflective element for viewing by the driver of the vehicle equipped with the video mirror. Use can also be made of a VIKUITI™ BEF 111-1 OT film that provides about a 37 percent increase in on-axis brightness for direct-light systems, or the like. VIKUITI™ Brightness Enhancement Film (BEF) uses a microreplication process to create a prism structure that manages the angle of light ultimately exiting a display. Using the likes of total internal reflection and reflection/refraction at the micro prisms forming a random prism pattern, off-axis light rays incident at the rear of the BEF prism film can be made to exit more perpendicular to the plane of the BEF film and so on-axis display brightness is enhanced. When combined with VIKUITI™ DBEF-D400 (or D550) film or similar film or element, on-axis brightness can be increased by up to 68 percent or thereabouts.

Additionally, combining VIKUITI™ BEF ITT-I OT film with VIKUITI™ DBEF film may beneficially improve contrast when viewing an image displayed at the video mirror. For example, a video mirror can be constructed utilizing a video screen that comprises a thin film transistor liquid crystal display (LCD) panel that is back lit by an array of a plurality of white light emitting light emitting diodes (preferably more than four white LEDs) and including a VIKUITI™ DBEF reflecting polarizer and a VIKUITI™ BEF prism film, preferably disposed between the rear of the LCD panel and the back-lighting array of LEDs (and with the DBEF film closer to the LCD panel and the BEF film closer to the back-lighting so that light emitted by the back-lighting LEDs impinges on the BEF film (typically having passed through a light diffuser film, although a diffusing property may be included in the DBEF film such as VIKUITI™ Diffuse Reflective Polarizer Film DRPF or VIKUITI™ DBEF-D280) before passing through the DBEF film and then, in turn, passes through the LCD panel and then through the reflective element itself. Also, two BEF sheets crossed at degrees can optionally be used to increase display brightness. Also, VIKUITI™ Brightness Enhancement Film-Reflective Polarizer (BEF-RP) that combines light recycling and reflection/refraction in a single multi-layer polymeric film/sheet that includes micro-prism structures and polarized light management may be used in the video screen device construction of a video mirror of the present invention. Also, VIKUITI™ BEF-RP or VIKUITI™ BEFRP2-RC multi-functional film that combines polarizing recycling and light angle management may be used in the video screen device construction of a video mirror of the present invention. Also, VIKUITI™ DBEF MF1-650 (having a film/sheet thickness of 650 microns) or multi-functional film VIKUITI™ DBEF MF1-470 (having a film/sheet thickness of 470 microns) that combines polarizing recy-

cling and light angle management may be used in the video screen device construction of a video mirror of the present invention.

When viewed via the front substrate and when operated during normal driving conditions and under high ambient lighting (such as daylight driving conditions), the luminance of the images seen at the video display screen as viewed through the front substrate and through the electro-optic medium and through the rear substrate is preferably at least about 900 candelas/square meter, more preferably at least about 1,200 candelas/square meter, and more preferably at least about 1,500 candelas/square meter, when the electro-optic medium is in its undimmed state and with the back lighting light sources of the video screen being powered to their maximum normally-allowed power level for use in the interior rearview mirror assembly in the vehicle.

Optionally, and with reference to FIG. 25, the dichroic translector layers 749' of a reflective element 718' may be disposed at the front surface or third surface 742a' of the rear substrate 742' and between the third surface 742a' and the transparent electrical conductor 748'. Similar to reflective element 718, a video display element 714' is disposed at a rear portion of the reflective element 718' for viewing video display information through the reflective element when the video display element 714' is activated. Reflective element 718' comprises an electro-optic reflective element having a front substrate 740', rear substrate 742' and an electro-optic medium 743' sandwiched therebetween and sealed via a perimeter seal 744'. Front substrate 740' has a transparent conductor coating 746' disposed at its rear surface 740a' and an anti-reflective coating or layer 762' disposed at its front surface 740b', while rear substrate 742' has a light absorbing element 760' disposed at its rear surface 742b'.

The transparent electrical conductor layer 748' is thus disposed over the third surface dichroic translector layers 749' and is between the electro-optic medium 743' and the dichroic translector layers 749'. The transparent electrical conductor is thus in contact with the electro-optic medium and preferably has a resistivity of about 5-15 ohms per square for powering the electro-optic medium when a current is applied to the transparent electrical conductor. The third surface dichroic translector reflective element 718' may be substantially similar to the fourth surface dichroic translector reflective element 718, discussed above (although the stack design may be adjusted so as to accommodate use of the likes of a half-wave ITO transparent thin film as the outermost layer in electrical contact with the electro-optically active inter-pane medium), such that a detailed discussion of the reflective elements need not be repeated herein. The difference in appearance (as viewed by a person viewing the reflective elements when the respective mirror assemblies are normally mounted in a vehicle) between a third surface dichroic translector reflective element and a fourth surface dichroic translector reflective element is not readily discernible to a person viewing the reflective elements of the interior rearview mirror assemblies due to the size of the mirrors and mirror substrates.

The third and fourth surface dichroic translector reflective elements of the present invention thus provide dichroic transfectors that have reduced absorption as compared to non-dichroic metallic transfectors (such as metal oxide/metal/metal oxide stacks of layers), so that the dichroic translector reflective element exhibits enhanced transmissivity of light therethrough for a given level of reflectivity of light incident thereon. This is because the dichroic translector layers used in the dichroic transfectors, being all non-metallic (such as transparent metal oxides or transparent

metal halides or transparent metal nitrides or other transparent non-metallic metal compounds), have a significantly lower extinction coefficient (smaller “k” value in the optical constants) than a metal layer (such as a thin silver thin film coating or a thin silver alloy thin film coating or a thin aluminum thin film coating or a thin aluminum alloy thin film coating) used in a non-dichroic metallic transreflector. The extinction coefficient for the layers or coatings is a measure of how well the layers or coatings absorb electromagnetic radiation. If electromagnetic waves can pass through with reduced absorption, the material has a lower extinction coefficient.

The constructions of the present invention are economical and effective compared to the more complicated and potentially more costly constructions of other mirror assemblies. For example, no collimating optical element (or any equivalent thereof) need be positioned at the light assembly of the embodiments of the present invention, since the slanted baffle in tandem with the slanted orientation of the light assembly to the rear of the back plate obviates the need for a collimating optical element. The present invention also obviates the cost and complexity of use of an optics block with collimating and deviator portions to control direction of light rays, or any equivalent thereof, such as is disclosed in PCT Application No. PCT/US00/07437, filed Mar. 7, 2005 by Gentex Corporation, and published Sep. 22, 2005 as International Publication No. WO 2005/086777, which is hereby incorporated herein by reference in its entirety.

Changes and modifications to the specifically described embodiments may be carried out without departing from the principles of the present invention, which is intended to be limited only by the scope of the appended claims as interpreted according to the principles of patent law.

The invention claimed is:

1. A vehicular exterior breakaway rearview mirror assembly, the vehicular exterior breakaway rearview mirror assembly comprising:

a skull-cap mirror shell;
a reflective element;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at an exterior side of a vehicle equipped with the vehicular exterior breakaway rearview mirror assembly, the skull-cap mirror shell has an inboard wall that faces toward the exterior side of the equipped vehicle;

a blind spot indicator disposed at an aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly, wherein the blind spot indicator comprises an illumination source comprising at least one light emitting diode;

wherein the blind spot indicator comprises an electrical connector;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, the inboard wall of the skull-cap mirror shell is viewable by a driver of the equipped vehicle;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, the illumination source is activated to illuminate the blind spot indicator responsive to an electronic blind spot monitoring system of the equipped vehicle detecting another vehicle that is at least one selected from the group consisting of (i) approaching the equipped vehicle from rearward of the equipped vehicle and (ii) overtaking the equipped

vehicle from rearward of the equipped vehicle at a side lane adjacent to the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, and upon the electronic blind spot monitoring system of the equipped vehicle detecting the other vehicle, the blind spot indicator indicates a hazard;

wherein the blind spot indicator disposed at the aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly provides a viewing area of at least two square centimeters viewable by the driver of the equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle; and

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, illumination of the blind spot indicator by activation of the illumination source is readily viewable by the driver of the equipped vehicle and is not readily viewable by a driver of the detected other vehicle.

2. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the blind spot indicator is disposed at a sloping wall portion of the inboard wall of the skull-cap mirror shell.

3. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the blind spot indicator is aerodynamically disposed at a sloping wall portion of the inboard wall of the skull-cap mirror shell.

4. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the blind spot indicator disposed at the aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly provides a viewing area of at least four square centimeters viewable by the driver of equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle.

5. The vehicular exterior breakaway rearview mirror assembly of claim **4**, wherein the blind spot indicator comprises an optic element.

6. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted is a driver side of the equipped vehicle.

7. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted is a passenger side of the equipped vehicle.

8. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the blind spot indicator comprises a light directing element for directing illumination from the illumination source toward the exterior side of the equipped vehicle to enhance viewing of the blind spot indicator by the driver of the equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle and when the illumination source is illuminated.

9. The vehicular exterior breakaway rearview mirror assembly of claim **1**, wherein the blind spot indicator comprises at least two light emitting diodes.

65

10. The vehicular exterior breakaway rearview mirror assembly of claim 9, wherein the blind spot indicator comprises a first light emitting diode, a second light emitting diode and a third light emitting diode.

11. The vehicular exterior breakaway rearview mirror assembly of claim 1, wherein the vehicular exterior breakaway rearview mirror assembly is a powerfold vehicular exterior breakaway rearview mirror assembly.

12. The vehicular exterior breakaway rearview mirror assembly of claim 1, wherein the reflective element comprises an electro-optic reflective element with electrically variable reflectivity.

13. The vehicular exterior breakaway rearview mirror assembly of claim 1, wherein the blind spot indicator comprises at least one selected from the group consisting of (i) a lens, (ii) a light directing element, (iii) a light guiding element, (iv) a light channel, (v) a light conduit, (vi) a light baffle and (vii) a light louver.

14. The vehicular exterior breakaway rearview mirror assembly of claim 1, wherein the blind spot indicator is aerodynamically disposed at the inboard wall of the skull-cap mirror shell.

15. The vehicular exterior breakaway rearview mirror assembly of claim 14, wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, and when the illumination source is illuminated, the driver of the equipped vehicle who is viewing the blind spot indicator sees a hazard alert.

16. The vehicular exterior breakaway rearview mirror assembly of claim 1, wherein the blind spot indicator is disposed at the skull-cap mirror shell at a location that is inboard relative to the position of the reflective element with respect to the exterior side of the equipped vehicle.

17. The vehicular exterior breakaway rearview mirror assembly of claim 1, wherein electrical connection is made with the blind spot indicator via a plug and socket type arrangement.

18. A vehicular exterior breakaway rearview mirror assembly, the vehicular exterior breakaway rearview mirror assembly comprising:

- a skull-cap mirror shell;
- a reflective element;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at an exterior side of a vehicle equipped with the vehicular exterior breakaway rearview mirror assembly, the skull-cap mirror shell has an inboard wall that faces toward the exterior side of the equipped vehicle;

a blind spot indicator disposed at an aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly, wherein the blind spot indicator comprises an illumination source comprising at least two light emitting diodes;

wherein the blind spot indicator is disposed at the skull-cap mirror shell at a location that is inboard relative to the position of the reflective element with respect to the exterior side of the equipped vehicle;

wherein the blind spot indicator comprises an electrical connector;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, the inboard wall of the skull-cap mirror shell is viewable by a driver of the equipped vehicle;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the

66

equipped vehicle, the illumination source is activated to illuminate the blind spot indicator responsive to an electronic blind spot monitoring system of the equipped vehicle detecting another vehicle that is at least one selected from the group consisting of (i) approaching the equipped vehicle from rearward of the equipped vehicle and (ii) overtaking the equipped vehicle from rearward of the equipped vehicle at a side lane adjacent to the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, and upon the electronic blind spot monitoring system of the equipped vehicle detecting the other vehicle, the blind spot indicator indicates a hazard;

wherein the blind spot indicator disposed at the aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly provides a viewing area of at least two square centimeters viewable by the driver of the equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle; and

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, illumination of the blind spot indicator by activation of the illumination source is readily viewable by the driver of the equipped vehicle and is not readily viewable by a driver of the detected other vehicle.

19. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the blind spot indicator is disposed at a sloping wall portion of the inboard wall of the skull-cap mirror shell.

20. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the blind spot indicator is aerodynamically disposed at a sloping wall portion of the inboard wall of the skull-cap mirror shell.

21. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted is a driver side of the equipped vehicle.

22. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted is a passenger side of the equipped vehicle.

23. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the blind spot indicator comprises a light directing element for directing illumination from the illumination source toward the exterior side of the equipped vehicle to enhance viewing of the blind spot indicator by the driver of the equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle and when the illumination source is illuminated.

24. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the blind spot indicator comprises a first light emitting diode, a second light emitting diode and a third light emitting diode.

25. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the vehicular exterior breakaway rearview mirror assembly is a powerfold vehicular exterior breakaway rearview mirror assembly.

67

26. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the reflective element comprises an electro-optic reflective element with electrically variable reflectivity.

27. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the blind spot indicator comprises at least one selected from the group consisting of (i) a lens, (ii) a light directing element, (iii) a light guiding element, (iv) a light channel, (v) a light conduit, (vi) a light baffle and (vii) a light louver.

28. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein the blind spot indicator is aerodynamically disposed at the inboard wall of the skull-cap mirror shell.

29. The vehicular exterior breakaway rearview mirror assembly of claim 28, wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, and when the illumination source is illuminated, the driver of the equipped vehicle who is viewing the blind spot indicator sees a hazard alert.

30. The vehicular exterior breakaway rearview mirror assembly of claim 18, wherein electrical connection is made with the blind spot indicator via a plug and socket type arrangement.

31. A vehicular exterior breakaway rearview mirror assembly, the vehicular exterior breakaway rearview mirror assembly comprising:

a skull-cap mirror shell;

a reflective element;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at an exterior side of a vehicle equipped with the vehicular exterior breakaway rearview mirror assembly, the skull-cap mirror shell has an inboard wall that faces toward the exterior side of the equipped vehicle;

a blind spot indicator disposed at an aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly, wherein the blind spot indicator comprises an illumination source comprising at least two light emitting diodes;

wherein the blind spot indicator comprises an electrical connector;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, the inboard wall of the skull-cap mirror shell is viewable by a driver of the equipped vehicle;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, the illumination source is activated to illuminate the blind spot indicator responsive to an electronic blind spot monitoring system of the equipped vehicle detecting another vehicle that is at least one selected from the group consisting of (i) approaching the equipped vehicle from rearward of the equipped vehicle and (ii) overtaking the equipped vehicle from rearward of the equipped vehicle at a side lane adjacent to the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted;

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, and upon the electronic blind spot monitoring system of the equipped vehicle detecting the other vehicle, the blind spot indicator indicates a hazard;

68

wherein the blind spot indicator disposed at the aperture established at the inboard wall of the skull-cap mirror shell of the vehicular exterior breakaway rearview mirror assembly provides a viewing area of at least four square centimeters viewable by the driver of the equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle; and

wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, illumination of the blind spot indicator by activation of the illumination source is readily viewable by the driver of the equipped vehicle and is not readily viewable by a driver of the detected other vehicle.

32. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator is disposed at a sloping wall portion of the inboard wall of the skull-cap mirror shell.

33. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator is aerodynamically disposed at a sloping wall portion of the inboard wall of the skull-cap mirror shell.

34. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator comprises an optic element.

35. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted is a driver side of the equipped vehicle.

36. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the exterior side of the equipped vehicle at which the vehicular exterior breakaway rearview mirror assembly is mounted is a passenger side of the equipped vehicle.

37. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator comprises a light directing element for directing illumination from the illumination source toward the exterior side of the equipped vehicle to enhance viewing of the blind spot indicator by the driver of the equipped vehicle when the vehicular exterior breakaway rearview mirror assembly is mounted at the exterior side of the equipped vehicle and when the illumination source is illuminated.

38. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator comprises a first light emitting diode, a second light emitting diode and a third light emitting diode.

39. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the vehicular exterior breakaway rearview mirror assembly is a powerfold vehicular exterior breakaway rearview mirror assembly.

40. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the reflective element comprises an electro-optic reflective element with electrically variable reflectivity.

41. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator comprises at least one selected from the group consisting of (i) a lens, (ii) a light directing element, (iii) a light guiding element, (iv) a light channel, (v) a light conduit, (vi) a light baffle and (vii) a light louver.

42. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator is aerodynamically disposed at the inboard wall of the skull-cap mirror shell.

43. The vehicular exterior breakaway rearview mirror assembly of claim 42, wherein, with the vehicular exterior breakaway rearview mirror assembly mounted at the exterior side of the equipped vehicle, and when the illumination source is illuminated, the driver of the equipped vehicle who is viewing the blind spot indicator sees a hazard alert. 5

44. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein the blind spot indicator is disposed at the skull-cap mirror shell at a location that is inboard relative to the position of the reflective element with respect to the exterior side of the equipped vehicle. 10

45. The vehicular exterior breakaway rearview mirror assembly of claim 31, wherein electrical connection is made with the blind spot indicator via a plug and socket type arrangement. 15

* * * * *