



US009411416B2

(12) **United States Patent**  
**Song et al.**

(10) **Patent No.:** **US 9,411,416 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **COMPUTER DEVICE OPERABLE WITH USER'S EYE MOVEMENT AND METHOD FOR OPERATING THE COMPUTER DEVICE**

G02B 27/0179; G02B 27/021; G02B 27/01;  
G02B 27/02; G02B 2027/014; G02B  
2027/0138; G02B 2027/0187; G02B  
2027/0181; A61B 2017/00216; G06T 19/006;  
G06T 11/60; G06T 7/208; G06K 9/00604;  
G06K 9/00335

(76) Inventors: **Wenjuan Song**, Beijing (CN); **Jianping Song**, Beijing (CN); **Lin Du**, Beijing (CN)

See application file for complete search history.

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 67 days.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,973,149 A \* 11/1990 Hutchinson ..... 351/210  
5,360,971 A \* 11/1994 Kaufman ..... A61B 3/113  
250/221

(Continued)

FOREIGN PATENT DOCUMENTS

CN 1694045 11/2005  
CN 101291364 10/2008

(Continued)

OTHER PUBLICATIONS

Kumar et al., "Gaze-Enhanced Scrolling Techniques", UIST'07, Oct. 7-10, 2007, ACM Symposium.

(Continued)

(21) Appl. No.: **14/128,625**

(22) PCT Filed: **Jun. 24, 2011**

(86) PCT No.: **PCT/CN2011/076288**

§ 371 (c)(1),  
(2), (4) Date: **Dec. 22, 2013**

(87) PCT Pub. No.: **WO2012/174743**

PCT Pub. Date: **Dec. 27, 2012**

(65) **Prior Publication Data**

US 2014/0125585 A1 May 8, 2014

(51) **Int. Cl.**  
**G06F 3/01** (2006.01)  
**H04N 13/04** (2006.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **G06F 3/013** (2013.01); **G06F 3/017**  
(2013.01); **A61B 3/113** (2013.01); **A61B**  
**2017/00216** (2013.01); **H04N 13/0484**  
(2013.01)



(58) **Field of Classification Search**  
CPC ..... G06F 3/013; G06F 3/01; G06F 3/017;  
G06F 3/04842; G06F 3/012; G06F 3/041;  
G06F 3/011; G06F 3/0484; G06F 3/0346;  
G06F 3/0486; G06F 3/04883; G06F 3/005;  
G06F 3/038; G06F 17/30867; B60W 50/10;  
G09G 2354/00; H04N 13/0484; G02B 27/017;

*Primary Examiner* — Ariel Balaoing  
*Assistant Examiner* — Darlene M Ritchie  
(74) *Attorney, Agent, or Firm* — Meagher Emanuel Laks  
Goldberg & Liao, LLP

(57) **ABSTRACT**

The present invention relates to a method for operating a computer device with user's eye movement. The method comprises the steps of detecting the user's eye movement, analyzing the user's eye movement to specify an eye movement pattern in the detected user's eye movement and a time period for completing the eye movement pattern, determining a command associated with a combination of the eye movement pattern and the time period and operating the device according to the command.

**8 Claims, 8 Drawing Sheets**



(51) **Int. Cl.**  
*A61B 3/113* (2006.01)  
*A61B 17/00* (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,517,021 A \* 5/1996 Kaufman ..... A61B 3/113  
 250/221  
 5,751,260 A \* 5/1998 Nappi ..... G06F 3/013  
 340/4.13  
 5,835,083 A \* 11/1998 Nielsen ..... G06F 1/3209  
 345/211  
 6,106,119 A \* 8/2000 Edwards ..... 351/209  
 6,195,640 B1 2/2001 Mullaly et al.  
 6,873,314 B1 \* 3/2005 Campbell ..... A61B 3/113  
 345/156  
 7,091,471 B2 8/2006 Wenstrand et al.  
 8,331,993 B2 \* 12/2012 Lee ..... H04M 1/67  
 340/571  
 8,451,246 B1 \* 5/2013 Scholler ..... G06F 3/04883  
 345/173  
 8,655,796 B2 \* 2/2014 Udani ..... G06F 19/363  
 705/2  
 2003/0098885 A1 \* 5/2003 Yabe ..... G06F 3/0485  
 715/785  
 2005/0199783 A1 \* 9/2005 Wenstrand et al. .... 250/214.1  
 2006/0281969 A1 12/2006 Wang et al.  
 2007/0024579 A1 \* 2/2007 Rosenberg ..... G06F 3/013  
 345/156  
 2007/0226646 A1 \* 9/2007 Nagiyama ..... G06F 3/016  
 715/784  
 2008/0143674 A1 6/2008 Molander et al.  
 2008/0211766 A1 9/2008 Westerman et al.  
 2009/0077501 A1 \* 3/2009 Partridge ..... G06F 3/017  
 715/846  
 2009/0289895 A1 11/2009 Nakada et al.  
 2009/0315827 A1 \* 12/2009 Elvesj et al. .... 345/157

2010/0182232 A1 7/2010 Zamoyski  
 2010/0191727 A1 \* 7/2010 Malik ..... G06F 17/30867  
 707/734  
 2011/0077548 A1 \* 3/2011 Torch ..... A61B 3/112  
 600/558  
 2011/0270123 A1 \* 11/2011 Reiner ..... 600/558  
 2012/0105486 A1 \* 5/2012 Lankford ..... G06F 3/013  
 345/661  
 2013/0106921 A1 5/2013 Nakayama

FOREIGN PATENT DOCUMENTS

CN	101308400	11/2008
CN	101441513	5/2009
CN	101681201	3/2010
JP	H06318235	11/1994
JP	2000010722	1/2000
JP	2000020534	1/2000
JP	2006107048	4/2006
JP	2007310815	11/2007
JP	2009075937	4/2009
JP	2010102581	5/2010
JP	2012063899	3/2012
KR	2009127779	12/2009
WO	WO2006100645	9/2006

OTHER PUBLICATIONS

Porta et al., "WyeB, and Eye-Controlled Web Browser for Hands-Free Navigation", IEEE, 2009, Catania, Italy, May 21-23, 2009. Search Report dated Mar. 29, 2012.  
 Wong et al., "Eye Tracker for Mobile Device", Research Disclosure 535068, Nov. 10, 2008, pp. 1-2.  
 Milekic, S., "The more you look the more you get: intention-based interface using gaze tracking", Museums and the web 2003: Proceedings, Jan. 1, 2003, pp. 1-17.

\* cited by examiner




Fig. 1




Fig. 2A




Fig. 2B




Fig.3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9

## COMPUTER DEVICE OPERABLE WITH USER'S EYE MOVEMENT AND METHOD FOR OPERATING THE COMPUTER DEVICE

This application claims the benefit, under 35 U.S.C. §365  
of International Application PCT/CN2011/076288, filed Jun.  
24, 2011, which was published in accordance with PCT  
Article 21(2) on Dec. 27, 2012 in English.

### FIELD OF THE INVENTION

The present invention relates to a computer device operable  
with user's eye movement and a method for operating a  
computer device with user's eye movement.

### BACKGROUND OF THE INVENTION

An electronic book (also referred to as e-Book, eBook or  
digital book) is known as a text and image-based publication  
in digital form produced on, published by, and readable on  
computers or other digital devices. eBooks are usually read  
on dedicated hardware devices known as eReaders or eBook  
devices. Computer devices such as smart-phones can also be  
used to read eBooks.

As more people get to use a computer device for reading  
eBooks, more convenient operations for operating the com-  
puter device are expected.

Eye tracking is one of research hotspots. Eye tracking is the  
process of measuring the point of eye gaze and the motion of  
a user's eye relative to the head. There are a number of  
methods for measuring eye movement. The most popular  
variant uses video images from which the eye position is  
extracted. Detecting of eye gaze is used in a lot of human  
computer interaction applications. There are both intrusive  
and nonintrusive approaches to estimate the eye gaze. For the  
intrusive techniques, a user needs to wear a headgear camera  
to fix the position of the eyes with the view of screen on the  
camera, or use an infrared light on camera to detect the eyes.  
For the nonintrusive approaches, a user only needs a simple  
camera for imaging the user's eye and does not have to wear  
any other equipment. At currently, most of computer devices  
such as smart-phones and portable electronic game machines  
are provided with a camera for imaging a user and can be as  
eReaders.

Movement Pattern Analysis (MPA) is a comprehensive  
system for assessing an individual's core motivations in deci-  
sion-making processes, based on the disciplined analysis of  
nonverbal behavior.

An eye tracking apparatus which recognizes a user's eye  
movement pattern is shown in U.S. 20080143674A1.

An aim of the present invention is to provide more con-  
venient operations with a user's eye movement for operating a  
computer device.

### SUMMARY OF THE INVENTION

According to an aspect of the present invention, there is  
provided a computer device operable with a user's eye move-  
ment. The computer device comprises means for detecting the  
user's eye movement, means for analyzing the user's eye  
movement to specify an eye movement pattern in the detected  
user's eye movement and a time period for completing the eye  
movement pattern, means for determining a command asso-  
ciated with a combination of the eye movement pattern and  
the time period and means for operating the device according  
to the command.

According to another aspect of the present invention, there  
is provided a method for operating a computer device with  
user's eye movement. The method comprises the steps of  
detecting the user's eye movement, analyzing the user's eye  
movement to specify an eye movement pattern in the detected  
user's eye movement and a time period for completing the eye  
movement pattern, determining a command associated with a  
combination of the eye movement pattern and the time period  
and operating the device according to the command.

### BRIEF DESCRIPTION OF DRAWINGS

These and other aspects, features and advantages of the  
present invention will become apparent from the following  
description in connection with the accompanying drawings in  
which:

FIG. 1 is an exemplary block diagram of a computer device  
according to an embodiment of the present invention;

FIG. 2A illustrates a basic environment of the use of the  
computer device according to an embodiment of the present  
invention;

FIG. 2B illustrates the same basic environment as shown in  
FIG. 2A except for the added optical lines;

FIGS. 3 (a) to (c) illustrate a basic reading process for  
reading one text line on a page presented on the display of the  
computer device from left to right of the text line;

FIGS. 4 (a) to (c) illustrate a basic reading process for  
reading a page presented on the display of the computer  
device from the top to the bottom of the page;

FIG. 5 shows eye movement pattern detected as a result of  
the reading process for reading a page presented on the dis-  
play of the computer device shown in FIGS. 4 (a) to (c);

FIG. 6 illustrates on how a page shown on the display of the  
computer device will be scrolled to the next page according to  
the eye movement pattern shown in FIG. 5.

FIGS. 7 (a) to (f) show different kinds of combinations of  
eye movement pattern and time period for completing the eye  
movement pattern which combinations generate different  
kinds of commands for operating the computer device  
according to the present invention;

FIGS. 8 (a) to (c) illustrate eye movement patterns tracked  
at different positions on the display; and

FIG. 9 is a flow chart showing a method for operating the  
computer device with user's eye movement according to an  
embodiment of the present invention.

### DETAIL DESCRIPTION OF PREFERRED EMBODIMENTS

In the following description, various aspects of an embodi-  
ment of the present invention will be described. For the pur-  
pose of explanation, specific configurations and details are set  
forth in order to provide a thorough understanding. However,  
it will also be apparent to one skilled in the art that the present  
invention may be practiced without the specific details  
present herein.

FIG. 1 illustrates an exemplary block diagram of a com-  
puter device **110** according to an embodiment of the present  
invention. The computer device **110** can be a tablet, smart-  
phone, eBook-reader and so on. The computer device **110**  
comprises a CPU (Central Processing Unit) **111**, an eye  
movement detector **112**, a storage **113**, a display **114** and an  
user input module **115**. A memory **116** such as RAM (Ran-  
dom Access Memory) may be connected to the CPU **111** as  
shown in FIG. 1.

The eye movement detector **112** is an element for detecting  
an eye of a user of the device **110** and monitoring the motion

of the eye and the eye gaze. The eye movement detector **112** is also configured to detect and collect eye gaze positions on the display **114** and to measure a time for each eye gaze. The eye movement detector **112** can employ many different types of techniques for the eye gaze tracking purpose. For example, the eye movement detector **112** can employ three steps to realize the eye gaze tracking: in the first step the eye on the user's face is detected based on the Haar-like features, in the second step tracking the motion of the eye is performed using the Lucas Kanade algorithm and in the third step the eye gaze is detected using Gaussian processes. A person skilled in the art will recognize that the above-described technique is not only a solution for the eye gaze tracking and that many other techniques can be used for the eye gaze tracking.

The display **114** is configured to visually present text, image, video and any other contents to a user of the device **110**. The display **114** can be a touch-screen so that it can provide a possibility to the user to operate the device **110** on the display **114** in addition to the user input module **115**.

The user input module **115** may include keys or buttons on the device **110** to input characters or commands and also comprise a function to recognize the characters or commands input with the keys or buttons. The user input module **115** can be an option if the display **114** is a touch-screen and the device **110** is configured so that characters or commands can be input on the display **114**.

The storage **113** is configured to store software programs and data for the CPU **111** to drive and operate the eye movement detector **112**, the display **114** and the user input module **115** as will be explained below.

FIG. 2A illustrates a basic environment of the use of the computer device according to an embodiment of the present invention. FIG. 2B illustrates the same basic environment as shown in FIG. 2A except for the added optical lines. In FIGS. 2A and 2B, the computer device **110** shown in FIG. 1 is indicated with the reference number "11".

FIGS. 2A and 2B show that user **12** is reading or browsing contents presented on the display of the device **11**. The device **11** is equipped with a camera **10** for imaging the face of the user **12** to detect eyes of the user **12** and to monitor the motion of the eyes and the eye gaze. The camera **10** is responsible for capturing the face of the user **12** and for detecting of eye gaze point **16** of the user **12**. The camera **10** may be an element of the eye movement detector **112** shown in FIG. 1.

In FIG. 2B, the dashed lines **14** represent a field-of-view or range of the camera **10**. The general area of the user's attention is approximately shown by two dashed lines **15**.

FIGS. 3 (a) to (c) illustrate a basic reading process for reading one text line on a page presented on the display of the device **11** from left to right of the text line. The left and right eyes **20** of the user move during the reading process. As shown in FIG. 3(a), the gaze point **21** is located on the front of the text line at the beginning of the reading process. Then the gaze point **22** moves to the middle of the text line as shown in FIG. 3(b) and finally the gaze point **23** moves to the end of the text line as shown in FIG. 3(c). These eye movements are detected and time periods for each eye gaze on the text line are measured by the eye movement detector **112** (FIG. 1). The total time for reading the one text line is approximately calculated by summing the time periods for each eye gaze on the text line by the CPU **111** shown in FIG. 1.

FIGS. 4 (a) to (c) illustrate a basic reading process for reading an entire page presented on the display of the device **11** from the top to the bottom of the page. As shown in FIG. 4(a), at first, the user **30** reads the first text line **31** on the page from left to right of the text line **31**. Then the user **30** reads the second text line **32** from left to right of the text line **32** and

repeats the same reading process for the other text lines (FIG. 4(b)). Finally, the user **30** reads the last text line **33** from left to right of the text line **33** (FIG. 4(c)). In the same manner as described with reference to FIGS. 3 (a) to (c), eye movements during the user **30** reads the text lines on the page are detected and time periods for each eye gaze on the text lines are measured by the eye movement detector **112** (FIG. 1). The total time for reading the page is approximately calculated by summing the time periods for each eye gaze on the text lines by the CPU **111** (FIG. 1).

As a result of the reading process for reading a page presented on the display of the device shown in FIGS. 4 (a) to (c), eye movement pattern as illustrated in FIG. 5 is detected by the device. Each black point shown in FIG. 5 indicates the user's eye gaze point. The arrows mean moving direction of the user's eye gaze point. As can be seen from FIG. 5, the user's eye gaze point moves in zigzag-shape from left to right of each text line and from top text line to bottom text line.

In this basic reading process shown in FIGS. 4 (a) to (c), for example, the device **11** (FIG. 2A and 2B) is configured to flip a page presented on the display to the next page when the user reads the page on the display from beginning to end.

The operation mechanism for flipping the page on the display will be explained here with reference to FIGS. 1, 5 and 6. In the storage **113** of the device **110**, a table including eye movement patterns and commands is stored. In the table, each command is associated with respective eye movement pattern. When the user **50** reads the page **51** from beginning to end **53** as illustrated in module **55** in FIG. 6, the zigzag-shaped eye movement pattern shown in FIG. 5 is detected using the CPU **111** and the eye movement detector **112**. Then the CPU **111** compares the detected eye movement pattern with the eye movement patterns in the table stored in the storage **113**. If an eye movement pattern that matches the detected eye movement pattern is found in the table, the CPU **111** executes a command associated with the matched eye movement pattern in the table. If the command is "flip a page on the display", then the page **51** on the display will be scrolled to the next page **52** by the CPU **111** as illustrated in module **56** in FIG. 6. According to an embodiment of the present invention, page **51** presented on the display of the device can be flipped with the user's eye movement detected by the eye movement detector **112** (FIG. 1) which may include the camera **10** (FIGS. 2A and 2B) as described above and then the user **50** can begin to read next page **52** from the beginning **54** as illustrated in module **57** in FIG. 6.

FIGS. 7 (a) to (f) show different kinds of combinations of eye movement pattern and time period for completing the eye movement pattern which combinations generate different kinds of commands for operating the computer device according to the present invention.

FIG. 7 (a) illustrates an eye movement pattern in which eye gaze point moves from left to right. A "LEFT" command is associated with the combination of this eye movement pattern and a threshold time period T for completing this eye movement pattern. If this eye movement pattern is detected and the time period t for completing the eye movement pattern is less than the predetermined threshold time period T, the "LEFT" command is executed so that the previous page of the content such as eBook comes from left side and to be shown on the display.

FIG. 7 (b) shows an eye movement pattern in which eye gaze point moves from top to down. A "NEXT" command is associated with combination of this eye movement pattern and a threshold time period T for completing this eye movement pattern. If this eye movement pattern is detected and the time period t for completing the eye movement pattern is less

than the predetermined threshold time period  $T$ , the "NEXT" command is executed to show next page of the content on the display.

FIGS. 7 (c) to (f) show further different eye movement patterns. Similar to the cases as shown in FIGS. 7 (a) and (b), commands are associated with combination of an eye movement pattern and a threshold time period  $T$  for completing the eye movement pattern and corresponding command is executed if any one of the eye movement patterns shown in FIGS. 7 (c) to (f) are detected and the time period  $t$  for completing the eye movement pattern is less than the predetermined threshold time period  $T$ . In these examples, the eye movement pattern in FIG. 7 (c) may be associated with a "VERSION" command for indicating the version of the content being presented on the display, the eye movement pattern in FIG. 7 (d) may be associated with an "END" command for jumping to the last page of the content, the eye movement pattern in FIG. 7 (e) may be associated with an "HOME" command for jumping to the first page of the content and the eye movement pattern in FIG. 7 (f) may be associated with an "ROTATE" command for rotating the content being presented on the display. These commands and combinations of eye movement pattern and threshold time period are associated with each other and stored in the storage 113 (FIG. 1).

In the above-described examples, no commands will be executed if the time period  $t$  is  $T$  or more. It is recognized that the user is just reading or watching the content on the display when the time period  $t$  fulfills  $T \leq t$ .

It should be noted that more different threshold time periods can be associated with an eye movement pattern. Referring to FIG. 7 (a) as an example, threshold time period  $T/2$  can be associated with the eye movement pattern in addition to the above-described threshold time period  $T$ . In this example, the "LEFT" command may be executed so that two or more previous page comes from left side and shows the page on the display if the time period  $t$  for completing the detected eye movement pattern fulfills  $t < T/2$ , whereas a single previous page comes from left side to be shown on the display if the time period  $t$  fulfills  $2/T \leq t < T$ . As can be seen from these examples, a plural of commands can be generated using a single eye movement pattern by associating a plural of threshold time periods with the single eye movement pattern.

Further, it should be noted that different positions of eye movement pattern to be tracked on the display can be associated with the eye movement pattern in addition to the threshold time period(s).

FIGS. 8 (a) to (c) illustrate that eye movement patterns are tracked at different positions on the display. It is shown that the eye movement pattern is tracked on left side of the display (FIG. 8(a)), on the middle of the display (FIG. 8(b)) and on right side of the display (FIG. 8(c)).

Provided that threshold time period  $T$  is associated with the eye movement pattern in which eye gaze point moves from top to down, for examples, a "Font Size" command can be associated with the combination of the eye movement pattern, threshold time period  $T$  for completing this eye movement pattern and the position of the eye movement pattern tracked on the display (left side position as shown in FIG. 8 (a)), a "NEXT" command can be associated with the combination of the eye movement pattern, threshold time period  $T$  for completing this eye movement pattern and the position of the eye movement pattern tracked on the display (middle position as shown in FIG. 8 (b)) and a "Zooming" command can be associated with the combination of the eye movement pattern, threshold time period  $T$  for completing this eye movement pattern and the position of the eye movement pattern tracked on the display (right side position as shown in FIG. 8 (c)).

In a condition that the eye movement pattern as shown in FIGS. 8 (a) to (c) is detected and the time period  $t$  for completing the eye movement pattern is less than the predetermined threshold time period  $T$ ;

- 1) if the eye movement pattern is tracked on left side of the display as shown in FIG. 8 (a), the "Font Size" command is executed to allow the user to adjust the font size on the display;
- 2) if the eye movement pattern is tracked on the middle of the display as shown in FIG. 8 (b), the "NEXT" command is executed to show next page of the content on the display; and
- 3) if the eye movement pattern is tracked on the right side of the display as shown in FIG. 8 (c), the "Zooming" command is executed to enlarge the content on the display.

Of course, more different threshold time periods can be associated with each of the different positions of the eye movement pattern. More commands can be generated using a single eye movement pattern by associating different threshold time periods and different positions of eye movement pattern on the display with the single eye movement pattern, compared to the case in which either different threshold time periods or different positions of eye movement pattern is associated with the single eye movement pattern.

Different combinations of eye movement pattern and threshold time period are stored in the storage 113 (FIG. 1). Each combination may include position of the eye movement pattern on the display. Also, different commands are stored in the storage 113 in a state that the different commands are associated with the respective combination in the storage 113. These different combinations and their associated commands may be stored in the storage in a table format.

It should be noted that an eye movement patterns formed by a user on the display may not be exactly the same as one of the eye movement patterns indicated in FIGS. 7 and 8 and that, in the above described embodiment of the present invention, an eye movement pattern may be detected even if the eye movement pattern is deformed in a certain tolerant range compared to its reference eye movement pattern.

Also it should be noted that relative size of each eye movement pattern shown in FIGS. 7 and 8 with respect to the size of the display is not limited to the examples illustrated in FIGS. 7 and 8. The eye movement patterns on the display can be any size as long as the eye movement patterns can be detected by the device.

FIG. 9 is a flow chart showing a method for operating the computer device with user's eye movement according to an embodiment of the present invention. The method for operating the computer device will be described below with reference to FIGS. 1 and 9.

At step S102, eye movement of a user of the computer device 110 is detected by means of the eye movement detector 112 of the device 110. In this step, an eye of the user of the device 110 is detected and the motion of the eye and the eye gaze are monitored by the eye movement detector 112. Also each eye gaze position on the display 114 is detected and time for each eye gaze is measured by the eye movement detector 112.

At step S104, the detected eye movement of the user is analyzed by the CPU 111 of the device 110. In this step, the eye movement pattern included in the detected eye movement and time period for completing the eye movement pattern is specified by the CPU 111 of the device 110. The CPU 111 determines the eye movement pattern by comparing detected eye movement with the eye movement patterns stored in the storage 113. If the eye movement pattern is specified, then the CPU 111 specifies the time period for completing the speci-

fied eye movement pattern by calculating total eye gaze time for the specified eye movement pattern. In this step, the position of the specified eye movement pattern on the display **114** may also be specified by the CPU **111**.

At step **S106**, a command associated with a combination of the eye movement pattern and the threshold time period for the eye movement pattern is determined by the CPU **111**. In this step, the CPU **111** searches the storage **113** to find the eye movement pattern to which the specified eye movement pattern matches. Then the CPU **111** determines whether the specified time period for completing the specified eye movement pattern fulfills the predetermined threshold time period associated with the matched eye movement pattern. If the specified time period fulfills the predetermined threshold time period, a command, associated with combination of the matched eye movement pattern and the predetermined threshold time period for the matched eye movement pattern, is determined by the CPU **111**.

In step **S106**, if positions of eye movement pattern on the display are also associated with the combinations of eye movement pattern and threshold time period and the position of the specified eye movement pattern on the display **114** is specified by the CPU **111**, a command, associated with combination of three elements including the matched eye movement pattern, threshold time period for the matched eye movement pattern and position of the matched eye movement pattern on the display, is determined by the CPU **111**.

At step **S108**, the CPU **111** executes the determined command and then the computer device **110** is operated in accordance with the command.

These and other features and advantages of the present principles may be readily ascertained by one of ordinary skill in the pertinent art based on the teachings herein. It is to be understood that the teachings of the present principles may be implemented in various forms of hardware, software, firmware, special purpose processors, or combinations thereof.

Most preferably, the teachings of the present principles are implemented as a combination of hardware and software. Moreover, the software may be implemented as an application program tangibly embodied on a program storage unit. The application program may be uploaded to, and executed by, a machine comprising any suitable architecture. Preferably, the machine is implemented on a computer platform having hardware such as one or more central processing units ("CPU"), a random access memory ("RAM"), and input/output ("I/O") interfaces. The computer platform may also include an operating system and microinstruction code. The various processes and functions described herein may be either part of the microinstruction code or part of the application program, or any combination thereof, which may be executed by a CPU. In addition, various other peripheral units may be connected to the computer platform such as an additional data storage unit.

It is to be further understood that, because some of the constituent system components and methods depicted in the accompanying drawings are preferably implemented in software, the actual connections between the system components or the process function blocks may differ depending upon the manner in which the present principles are programmed. Given the teachings herein, one of ordinary skill in the pertinent art will be able to contemplate these and similar implementations or configurations of the present principles.

Although the illustrative embodiments have been described herein with reference to the accompanying drawings, it is to be understood that the present principles is not limited to those precise embodiments, and that various changes and modifications may be effected therein by one of

ordinary skill in the pertinent art without departing from the scope or spirit of the present principles. All such changes and modifications are intended to be included within the scope of the present principles as set forth in the appended claims.

The invention claimed is:

**1.** A computer device operable with a user's eye movement, the device comprising:

a detector for detecting the user's eye movement;

a processor configured to:

analyze the user's eye movement to specify an eye movement pattern in the detected user's eye movement from one eye gaze position to another eye gaze position and a time period for completing the eye movement pattern;

determine a command associated with a combination of the eye movement pattern and the time period, wherein the command is determined based on the combination of the eye movement pattern from the one eye gaze position to the another eye gaze position and the time period for completing the eye movement pattern from the one eye gaze position to the another eye gaze position, wherein the command is generated if the time period for completing the eye movement pattern is less than a threshold time period, and different threshold time periods can be associated with the same eye movement pattern to generate different commands; and

operate the device according to the command.

**2.** The device according to claim **1**, wherein the detector is configured to collect the user's eye gaze positions,

wherein the processor is further configured to:

determine if the collected user's eye gaze positions conform with another eye movement pattern.

**3.** The device according to claim **1**, wherein the device further comprises a display, wherein the processor is configured to identify a left, middle or right position of the detected eye movement pattern on the display and wherein the command is further determined based on the identified left middle or right position of the detected eye movement pattern on the display.

**4.** The computing device of claim **1**, wherein the computing device is an eBook-reader.

**5.** A method for operating a computer device with user's eye movement, comprising:

detecting the user's eye movement;

analyzing the user's eye movement from one eye gaze position to another eye gaze position to specify an eye movement pattern in the detected user's eye movement and a time period for completing the eye movement pattern;

determining a command associated with a combination of the eye movement pattern and the time period, wherein the command is determined based on the combination of the eye movement pattern from the one eye gaze position to the another eye gaze position and the time period for completing the eye movement pattern from the one eye gaze position to the another eye gaze position, wherein the command is generated if the time period for completing the eye movement pattern is less than a threshold time period, and different threshold time periods can be associated with the same eye movement pattern to generate different commands; and

operating the device according to the command.

**6.** The method according to claim **5**, wherein the detecting includes collecting the user's eye gaze positions;

wherein the analyzing includes:

determining if the collected user's eye gaze positions conform with another eye movement pattern.

7. The method according to claim 5, wherein the device comprising a display, wherein the analyzing further identifies a left, middle, or right position of the detected eye movement pattern on the display and wherein the command is further determined based on the identified left, middle or right position of the detected eye movement pattern on the display. 5

8. The method of claim 5, wherein the computing device is an eBook-reader.

\* \* \* \* \*