



US008892738B2

(12) **United States Patent**
de Vries et al.

(10) **Patent No.:** **US 8,892,738 B2**
(45) **Date of Patent:** **Nov. 18, 2014**

(54) **DERIVING COMPONENT STATISTICS FOR A
STREAM ENABLED APPLICATION**

(75) Inventors: **Jeffrey de Vries**, Sunnyvale, CA (US);
Arthur Shingen Hitomi, Huntington
Beach, CA (US)

(73) Assignee: **Numecent Holdings, Inc.**, Irvine, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1215 days.

(21) Appl. No.: **12/062,766**

(22) Filed: **Apr. 4, 2008**

(65) **Prior Publication Data**

US 2009/0119644 A1 May 7, 2009

Related U.S. Application Data

(60) Provisional application No. 60/986,260, filed on Nov.
7, 2007.

(51) **Int. Cl.**

G06F 9/46 (2006.01)

G06F 11/34 (2006.01)

(52) **U.S. Cl.**

CPC **G06F 11/3476** (2013.01); **G06F 2201/865**
(2013.01); **G06F 9/463** (2013.01)

USPC **709/226**; 702/179; 717/149

(58) **Field of Classification Search**

CPC ... G06F 9/3851; G06F 9/463; G06F 11/3476;
G06F 17/18; G06F 17/30516

USPC 717/101–178; 707/601–831; 709/203,
709/219–220, 231, 240; 370/400; 375/240;
703/26–27; 713/153, 160; 380/277;
718/1–108

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,562,306 A	12/1985	Chou et al.
4,796,220 A	1/1989	Wolfe
4,949,257 A	8/1990	Orbach
4,970,504 A	11/1990	Chen
4,999,806 A	3/1991	Chernow et al.
5,012,512 A	4/1991	Basso et al.
5,032,979 A	7/1991	Hecht et al.
5,047,928 A	9/1991	Wiedemer

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0658837	6/1995
EP	0813325	12/1997

(Continued)

OTHER PUBLICATIONS

Fast Data Stream Algorithms using Associative Memories—
Nagender Bandi, Ahmed Metwally, Divyakant Agrawal, Amr El
Abbadi—Department of Computer Science, University of Califor-
nia, Santa Barbara—SIGMOD'07, Jun. 12–14, 2007.*

(Continued)

Primary Examiner — Lewis A Bullock, Jr.

Assistant Examiner — Francisco Aponte

(74) *Attorney, Agent, or Firm* — Sheppard, Mullin, Richter
& Hampton LLP


(57)

ABSTRACT

A technique for generating component usage statistics
involves associating components with blocks of a stream-
enabled application. When the streaming application is
executed, block requests may be logged by Block ID in a log.
The frequency of component use may be estimated by ana-
lyzing the block request log with the block associations.

10 Claims, 17 Drawing Sheets

1400



(56)

References Cited

U.S. PATENT DOCUMENTS

5,063,500 A	11/1991	Shorter	5,933,822 A	8/1999	Braden-Harder et al.
5,109,413 A	4/1992	Comerford et al.	5,940,591 A	8/1999	Boyle et al.
5,166,886 A	11/1992	Molnar et al.	5,943,424 A	8/1999	Berger et al.
5,210,850 A	5/1993	Kelly et al.	5,948,062 A	9/1999	Tzelnic et al.
5,293,556 A	3/1994	Hill et al.	5,948,065 A	9/1999	Eilert et al.
5,311,596 A	5/1994	Scott et al.	5,949,877 A	9/1999	Traw et al.
5,325,489 A	6/1994	Mitsuhira et al.	5,950,195 A	9/1999	Stockwell et al.
5,442,791 A	8/1995	Wrabetz et al.	5,953,506 A	9/1999	Kalra et al.
5,481,611 A	1/1996	Owens et al.	5,956,717 A	9/1999	Kraay et al.
5,495,411 A	2/1996	Ananda	5,960,411 A	9/1999	Hartman et al.
5,533,123 A	7/1996	Force et al.	5,960,439 A	9/1999	Hamner et al.
5,537,566 A	7/1996	Konno et al.	5,961,586 A	10/1999	Pedersen
5,544,321 A	8/1996	Theimer et al.	5,961,591 A	10/1999	Jones et al.
5,546,526 A	8/1996	Li et al.	5,963,444 A	10/1999	Shidara et al.
5,547,202 A	8/1996	Tsumura	5,963,944 A	10/1999	Adams
5,548,645 A	8/1996	Ananda	5,968,176 A	10/1999	Nessett et al.
5,553,139 A	9/1996	Ross et al.	5,973,696 A	10/1999	Agranat et al.
5,553,143 A	9/1996	Ross et al.	5,987,454 A	11/1999	Hobbs
5,555,376 A	9/1996	Theimer et al.	5,987,608 A	11/1999	Roskind
5,611,050 A	3/1997	Theimer et al.	6,003,065 A	12/1999	Yan et al.
5,629,980 A	5/1997	Stefik et al.	6,003,095 A	12/1999	Pekowski et al.
5,630,049 A	5/1997	Cardoza et al.	6,014,686 A	1/2000	Elnozahy et al.
5,635,906 A	6/1997	Joseph	6,018,619 A	1/2000	Allard et al.
5,638,513 A	6/1997	Ananda	6,026,166 A	2/2000	LeBourgeois
5,652,887 A	7/1997	Dewey et al.	6,028,925 A	2/2000	Van Berkum et al.
5,666,293 A	9/1997	Metz et al.	6,038,379 A	3/2000	Fletcher et al.
5,696,965 A	12/1997	Dedrick	6,038,610 A	3/2000	Belfiore et al.
5,701,427 A	12/1997	Lathrop	6,047,323 A	4/2000	Krause
5,706,440 A	1/1998	Compliment et al.	6,049,792 A	4/2000	Hart et al.
5,715,403 A	2/1998	Stefik	6,049,835 A	4/2000	Gagnon
5,758,150 A	5/1998	Bell et al.	6,061,738 A	5/2000	Osaku et al.
5,761,445 A	6/1998	Nguyen	6,065,043 A	5/2000	Domenikos et al.
5,764,906 A	6/1998	Edelstein et al.	6,076,104 A	6/2000	McCue
5,764,918 A	6/1998	Poulter	6,081,842 A	6/2000	Shachar
5,765,152 A	6/1998	Erickson	6,085,186 A	7/2000	Christianson et al.
5,765,153 A	6/1998	Benantar et al.	6,085,193 A	7/2000	Malkin et al.
5,768,528 A	6/1998	Stumm	6,088,705 A	7/2000	Lightstone et al.
5,768,539 A	6/1998	Metz et al.	6,092,194 A	7/2000	Touboul
5,771,354 A	6/1998	Crawford	6,094,649 A	7/2000	Bowen et al.
5,778,395 A	7/1998	Whiting et al.	6,098,072 A	8/2000	Sluiman et al.
5,790,753 A	8/1998	Krishnamoorthy et al.	6,099,408 A	8/2000	Schneier et al.
5,805,809 A	9/1998	Singh et al.	6,101,482 A	8/2000	DiAngelo et al.
5,809,144 A	9/1998	Sirbu et al.	6,101,491 A	8/2000	Woods
5,812,865 A	9/1998	Theimer et al.	6,101,537 A	8/2000	Edelstein et al.
5,812,881 A	9/1998	Ku et al.	6,108,420 A	8/2000	Larose et al.
5,818,711 A	10/1998	Schwabe et al.	6,115,741 A	9/2000	Domenikos et al.
5,822,537 A	10/1998	Katseff et al.	6,138,271 A	10/2000	Keeley
5,832,289 A	11/1998	Shaw et al.	6,154,878 A	11/2000	Saboff
5,835,722 A	11/1998	Bradshaw et al.	6,157,948 A	12/2000	Inoue et al.
5,838,910 A	11/1998	Domenikos et al.	6,167,510 A	12/2000	Tran
5,839,910 A	11/1998	Meller et al.	6,167,522 A	12/2000	Lee et al.
5,855,020 A	12/1998	Kirsch	6,173,311 B1	1/2001	Hassett et al.
5,874,986 A	2/1999	Gibbon et al.	6,173,330 B1	1/2001	Guo et al.
5,878,425 A	3/1999	Redpath	6,185,608 B1	2/2001	Hon et al.
5,881,229 A	3/1999	Singh et al.	6,192,398 B1	2/2001	Hunt
5,881,232 A	3/1999	Cheng et al.	6,192,408 B1	2/2001	Vahalia et al.
5,892,915 A	4/1999	Duso et al.	6,195,694 B1	2/2001	Chen et al.
5,892,953 A	4/1999	Bhagria et al.	6,212,640 B1	4/2001	Abdelnur et al.
5,895,454 A	4/1999	Harrington	6,219,693 B1	4/2001	Napolitano et al.
5,895,471 A	4/1999	King et al.	6,226,412 B1	5/2001	Schwab
5,901,315 A	5/1999	Edwards et al.	6,226,665 B1	5/2001	Deo et al.
5,903,721 A	5/1999	Sixtus	6,253,234 B1	6/2001	Hunt et al.
5,903,732 A	5/1999	Reed et al.	6,275,470 B1	8/2001	Ricciulli
5,903,892 A	5/1999	Hoffert et al.	6,275,496 B1	8/2001	Burns et al.
5,905,868 A	5/1999	Baghai et al.	6,278,992 B1	8/2001	Curtis et al.
5,905,990 A *	5/1999	Inglett 1/1	6,281,898 B1	8/2001	Nikolovska et al.
5,909,545 A	6/1999	Frese, II et al.	6,282,712 B1	8/2001	Davis et al.
5,911,043 A	6/1999	Duffy et al.	6,298,356 B1	10/2001	Jawahar et al.
5,918,015 A	6/1999	Suzuki et al.	6,301,584 B1	10/2001	Ranger
5,923,885 A	7/1999	Johnson et al.	6,301,605 B1	10/2001	Napolitano et al.
5,925,126 A	7/1999	Hsieh	6,301,629 B1	10/2001	Sastri et al.
5,926,552 A	7/1999	McKeon	6,301,685 B1	10/2001	Shigeta
5,929,849 A	7/1999	Kikinis	6,311,221 B1	10/2001	Raz et al.
5,931,907 A	8/1999	Davies et al.	6,314,425 B1	11/2001	Serbinis et al.
5,933,603 A	8/1999	Vahalia et al.	6,321,260 B1	11/2001	Takeuchi et al.
			6,330,561 B1	12/2001	Cohen et al.
			6,343,287 B1	1/2002	Kumar et al.
			6,347,398 B1	2/2002	Parthasarathy et al.
			6,356,946 B1	3/2002	Clegg et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,369,467	B1	4/2002	Noro	7,192,352	B2	3/2007	Walker et al.
6,370,686	B1	4/2002	Delo et al.	7,197,516	B1	3/2007	Hipp et al.
6,374,402	B1	4/2002	Schmeidler et al.	7,197,570	B2 *	3/2007	Eylon et al. 709/231
6,385,696	B1	5/2002	Doweck	7,246,119	B2	7/2007	Kuwata et al.
6,389,467	B1	5/2002	Eyal	7,577,751	B2 *	8/2009	Vinson et al. 709/231
6,418,554	B1	7/2002	Delo et al.	7,653,742	B1 *	1/2010	Bhargava et al. 709/240
6,418,555	B2	7/2002	Mohammed	7,716,335	B2 *	5/2010	Dinker et al. 709/226
6,418,556	B1	7/2002	Bennington et al.	8,014,400	B2 *	9/2011	Zhang 370/392
6,424,991	B1	7/2002	Gish	2001/0003828	A1	6/2001	Peterson et al.
6,425,017	B1	7/2002	Dievendoff et al.	2001/0014878	A1	8/2001	Miltra et al.
6,449,688	B1	9/2002	Peters et al.	2001/0027493	A1	10/2001	Wallace
6,453,334	B1	9/2002	Vinson et al.	2001/0034736	A1	10/2001	Eylon et al.
6,457,076	B1	9/2002	Cheng et al.	2001/0037399	A1 *	11/2001	Eylon et al. 709/231
6,508,709	B1	1/2003	Karmarkar	2001/0037400	A1	11/2001	Raz et al.
6,510,458	B1	1/2003	Berstis et al.	2001/0042833	A1	11/2001	Kenway
6,510,462	B2	1/2003	Blumenau	2001/0044850	A1 *	11/2001	Raz et al. 709/231
6,510,466	B1	1/2003	Cox et al.	2001/0044851	A1	11/2001	Rothman et al.
6,524,017	B2	2/2003	Lecocq et al.	2002/0015106	A1	2/2002	Taylor
6,574,618	B2 *	6/2003	Eylon et al. 1/1	2002/0019864	A1	2/2002	Mayer
6,584,507	B1	6/2003	Bradley et al.	2002/0035674	A1	3/2002	Vetrivelkumaran et al.
6,587,857	B1	7/2003	Carothers et al.	2002/0038374	A1	3/2002	Gupta et al.
6,594,682	B2	7/2003	Peterson et al.	2002/0042833	A1	4/2002	Hendler et al.
6,598,125	B2	7/2003	Romm	2002/0057893	A1	5/2002	Wood et al.
6,601,103	B1	7/2003	Goldschmidt Iki et al.	2002/0059402	A1	5/2002	Belanger
6,601,110	B2	7/2003	Marsland	2002/0065848	A1	5/2002	Walker et al.
6,605,956	B2	8/2003	Farnworth et al.	2002/0078170	A1	6/2002	Brewer et al.
6,609,114	B1	8/2003	Gressel et al.	2002/0078203	A1	6/2002	Greschler et al.
6,611,812	B2	8/2003	Hurtado et al.	2002/0083183	A1	6/2002	Pujare et al.
6,615,166	B1 *	9/2003	Guheen et al. 703/27	2002/0083187	A1	6/2002	Sim et al.
6,622,137	B1	9/2003	Ravid et al.	2002/0087717	A1	7/2002	Artzi et al.
6,622,171	B2	9/2003	Gupta et al.	2002/0087883	A1	7/2002	Wohlgemuth et al.
6,636,961	B1	10/2003	Braun et al.	2002/0087963	A1	7/2002	Eylon et al.
6,651,251	B1	11/2003	Shoff et al.	2002/0091763	A1 *	7/2002	Shah et al. 709/203
6,687,745	B1	2/2004	Franco et al.	2002/0091901	A1	7/2002	Romm
6,694,510	B1	2/2004	Willems	2002/0116476	A1	8/2002	Eyal et al.
6,697,869	B1	2/2004	Mallart et al.	2002/0133491	A1	9/2002	Sim et al.
6,711,619	B1	3/2004	Chandramohan et al.	2002/0138640	A1	9/2002	Raz et al.
6,732,179	B1	5/2004	Brown et al.	2002/0147849	A1	10/2002	Wong et al.
6,735,601	B1 *	5/2004	Subrahmanyam 1/1	2002/0156911	A1	10/2002	Croman et al.
6,735,631	B1	5/2004	Oehrke et al.	2002/0157089	A1	10/2002	Patel et al.
6,757,708	B1	6/2004	Craig et al.	2002/0161908	A1	10/2002	Benitez et al.
6,757,894	B2	6/2004	Eylon et al.	2002/0174215	A1	11/2002	Schaefer
6,763,370	B1	7/2004	Schmeidler et al.	2003/0004882	A1 *	1/2003	Holler et al. 705/51
6,772,209	B1	8/2004	Chernock et al.	2003/0009538	A1	1/2003	Shah et al.
6,775,779	B1	8/2004	England et al.	2003/0056112	A1	3/2003	Vinson et al.
6,779,179	B1	8/2004	Romm et al.	2003/0065917	A1 *	4/2003	Medvinsky et al. 713/160
6,785,768	B2	8/2004	Peters et al.	2003/0105816	A1	6/2003	Goswami
6,785,865	B1	8/2004	Cote et al.	2003/0138024	A1	7/2003	Williamson et al.
6,801,507	B1	10/2004	Humpleman et al.	2003/0140160	A1 *	7/2003	Raz et al. 709/231
6,810,525	B1	10/2004	Safadi et al.	2003/0187617	A1 *	10/2003	Murphy et al. 702/186
6,816,909	B1	11/2004	Chang et al.	2003/0221099	A1 *	11/2003	Medvinsky et al. 713/153
6,816,950	B2	11/2004	Nichols	2004/0036722	A1	2/2004	Warren
6,832,222	B1	12/2004	Zimowski	2004/0128342	A1	7/2004	Maes et al.
6,836,794	B1	12/2004	Lucovsky et al.	2004/0133657	A1 *	7/2004	Smith et al. 709/219
6,854,009	B1	2/2005	Hughes	2004/0199566	A1	10/2004	Carlson et al.
6,891,740	B2	5/2005	Williams	2004/0230784	A1	11/2004	Cohen
6,918,113	B2 *	7/2005	Patel et al. 717/178	2004/0230971	A1	11/2004	Rachman et al.
6,925,495	B2	8/2005	Hegde et al.	2004/0267813	A1	12/2004	Rivers-Moore et al.
6,938,096	B1	8/2005	Greschler et al.	2004/0268361	A1	12/2004	Schaefer
6,959,320	B2 *	10/2005	Shah et al. 709/203	2005/0010607	A1	1/2005	Parker et al.
6,970,866	B1	11/2005	Pravetz et al.	2005/0010670	A1	1/2005	Greschler et al.
6,985,915	B2	1/2006	Somalwar et al.	2005/0091534	A1	4/2005	Nave et al.
7,010,492	B1 *	3/2006	Bassett et al. 705/14.1	2005/0114472	A1	5/2005	Tan
7,024,677	B1	4/2006	Snyder et al.	2005/0193139	A1	9/2005	Vinson et al.
7,028,305	B2	4/2006	Schaefer	2005/0289617	A1	12/2005	Safadi et al.
7,043,524	B2	5/2006	Shah et al.	2006/0010074	A1	1/2006	Zeitsiff et al.
7,051,315	B2	5/2006	Artzi et al.	2006/0031165	A1	2/2006	Nave et al.
7,062,567	B2	6/2006	Benitez et al.	2006/0047716	A1	3/2006	Keith
7,093,077	B2	8/2006	Cooksey et al.	2006/0048136	A1	3/2006	de Vries et al.
7,096,253	B2	8/2006	Vinson et al.	2006/0064673	A1 *	3/2006	Rogers et al. 717/113
7,112,138	B2	9/2006	Hedrick et al.	2006/0083305	A1 *	4/2006	Dougherty et al. 375/240.12
7,130,616	B2	10/2006	Janik	2006/0106770	A1	5/2006	de Vries
7,137,072	B2	11/2006	Bauer et al.	2006/0120385	A1 *	6/2006	Atchison et al. 370/400
7,171,390	B1	1/2007	Song et al.	2006/0123185	A1	6/2006	de Vries et al.
7,191,441	B2	3/2007	Abbott et al.	2006/0136389	A1	6/2006	Cover et al.
				2007/0038642	A1	2/2007	Durgin et al.
				2007/0043550	A1	2/2007	Tzuya
				2007/0067435	A1	3/2007	Landis et al.
				2007/0074223	A1	3/2007	Lescouet et al.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2007/0126749	A1	6/2007	Tzruya et al.	
2007/0129146	A1	6/2007	Tzruya et al.	
2007/0129990	A1	6/2007	Tzruya et al.	
2007/0130075	A1	6/2007	Song et al.	
2007/0130292	A1	6/2007	Tzruya et al.	
2007/0168309	A1	7/2007	Tzruya et al.	
2007/0196074	A1	8/2007	Jennings et al.	
2007/0256056	A1 *	11/2007	Stern et al.	717/121
2008/0077366	A1 *	3/2008	Neuse et al.	703/2
2008/0155074	A1 *	6/2008	Bacinski	709/222

FOREIGN PATENT DOCUMENTS

EP	1020824	7/2000
EP	1143349	10/2001
TW	200644550	12/2006
WO	WO-98/40993	9/1998
WO	WO-98/50853	11/1998
WO	WO-99/57863	11/1999
WO	WO-99/60458	11/1999
WO	WO-00/04681	1/2000
WO	WO-00/31657	6/2000
WO	WO-00/31672	6/2000
WO	WO-00/56028	9/2000
WO	WO-01/27805	4/2001
WO	WO-01/46856	6/2001
WO	WO-02/44840	6/2002
WO	WO-2006/022745	3/2006
WO	WO-2006/047133	5/2006
WO	WO-2006/055445	5/2006
WO	WO-2006/102532	9/2006
WO	WO-2006/102621	9/2006

OTHER PUBLICATIONS

Bailey et al., "Chart of Darkness: Mapping a Large Intranet", Dept of Computer Science, FEIT, The Australian National University, Canberra ACT 0200, Australia, pp. 1-23, <http://pastime.anu.edu.au/nick/pubs/www9/cod.html>, Feb. 21, 2001.

Binto et al., "Secure Transaction Processing in Firm Real-Time Database Systems", SIGMOD International Conference on Management of Data 1997, 462-473, V26, Issue 2, Association for Computing Machinery (ACM) Press, Tucson, Arizona, United States.

Boneh et al., "An Attack on RSA Given a Small Fraction of the Private Key Bits", Advances in Cryptology—ASIACRYPT '98, Lecture Notes in Computer Science, 25-34, V.1514, Springer-Verlag Berlin Heidelberg, retrieved online on Jun. 15, 2006 at <http://crypto.stanford.edu/about.dabo/abstracts/bits.sub.-of.sub.-d.html> (1998).

Brin et al., "The Anatomy of a Large-Scale Hypertextual Web Search Engine", Computer Science Department, Stanford University, Stanford, CA 94305, pp. 1-20.

Chu et al., "REFEREE: Trust Management for Web Applications", Proceedings of the Sixth International World Wide Web Conference, 1997, retrieved online on Jun. 15, 2006 at <http://www.si.umich.edu/~presnick/papers/Referee/www6-referee.html>.

Faupel, Status of Industry Work in Signed Mobile Code, Joint European Networking Conference (JENC), May 1997, pp. 313-1-313-8.

Fiedler et al., "UNIX System V, Release 4 Administration", Second Edition, 1991, 1-13, 37-116, 152-153, 175-200, 291-312, Hayden Books, Carmel, Indiana, USA.

Gralla, Chapter 44, "Shopping on the Internet" How the Internet Works, IEEE Personal Communications, Aug. 1999, 260-67, QUE—A division of Macmillan Computer Publishing, Millenium Edition.

Microsoft Corp., Computer Dictionary, 3rd edition, 1997, 119 & 305, Microsoft Press.

Microsoft, "Understanding Universal Plug and Play", pp. 1-39, Feb.-Jun. 2000.

Morrow et al., "Indexing Within—The Lost Gold Within the Enetprise", Endeavors Technology, Aug. 22, 2000, pp. 1-6.

Mullender et al., "Amoeba: A Distributed Operating System for the 1990s", Computer Magazine, May 1990, 44-53, 23(5).

Nakayoshi et al., "A Secure Private File System with Minimal System Administration", Communications, Computers and Signal Processing, 1997 IEEE Pacific Rim Conference, 251-255, vol. 1.

O'Mahony, "Security Considerations in a Network Management Environment", 1994, 12-17, vol. 8, IEEE, USA.

Pyarali et al., "Design and Performance of an Object-Oriented Framework for High-Speed Electronic Medical Imaging, Fall 1996", Computing Systems Journal, 331-375, vol. 9 No. 4, USENIX, retrieved online on Jun. 15, 2006 at <http://www.cs.wustl.edu/about.schmidt/PDF/COOTS-96.pdf>.

Rappaport, "Robots & Spiders & Crawlers: How Web and Intranet Search Engines Follow Links to Build Indexes", Infoseek Software, pp. 1-38 (Oct. 1999).

Reinhardt, "An Architectural Overview of UNIX Network Security", ARINC Research Corporation, Sep. 19, 1992, retrieved online on Jun. 15, 2006 at <http://www.clusit.it/whitepapers/unixnet.pdf>.

Sirbu et al., "Netbill: An Internet Commerce System Optimized for Network-Delivered Services", IEEE Personal Communications, 2(4):34-39 (Aug. 1995).

Tardo et al., "Mobile Agent Security and Telescript", 4.sup.th International Conference of the IEEE Computer Society (IEEE CompCon1996), Feb. 1996.

International Search Report of PCT Application No. PCT/US2004/28195, May 2, 2006, 3 Pages.

Written Opinion of PCT Application No. PCT/US2004/28195, May 2, 2006, 4 Pages.

International Search Report of PCT Application No. PCT/US2005/41024, Feb. 27, 2007, 1 Page.

Written Opinion of PCT Application No. PCT/US2005/41024, Feb. 27, 2007, 3 Pages.

International Search Report of PCT Application No. PCT/US2006/10637, Sep. 25, 2007, 1 Page.

Written Opinion of PCT Application No. PCT/US2006/10637, Sep. 25, 2007, 4 Pages.

International Search Report of PCT Application No. PCT/US2006/10904, Dec. 26, 2007, 1 Page.

Co-pending U.S. Appl. No. 09/098,075, filed Jun. 16, 1998.

Notice of Allowance Mailed Feb. 19, 2002 in Co-pending U.S. Appl. No. 09/098,075, filed Jun. 16, 1998.

Non-Final Office Action Mailed May 22, 2001 in Co-pending U.S. Appl. No. 09/098,075, filed Jun. 16, 1998.

Non-Final Office Action Mailed Nov. 14, 2000 in Co-pending U.S. Appl. No. 09/098,075, filed Jun. 16, 1998.

Final Office Action Mailed Aug. 30, 2000 in Co-pending U.S. Appl. No. 09/098,075, filed Jun. 16, 1998.

Non-Final Office Action Mailed Mar. 16, 2000 in Co-pending U.S. Appl. No. 09/098,075, filed Jun. 16, 1998.

Co-pending U.S. Appl. No. 10/228,680, filed Aug. 26, 2002.

Notice of Allowance Mailed Aug. 19, 2005 in Co-pending U.S. Appl. No. 10/228,680, filed Aug. 26, 2002.

Non-Final Office Action Mailed Apr. 28, 2005 in Co-pending U.S. Appl. No. 10/228,680, filed Aug. 26, 2002.

Non-Final Office Action Mailed Feb. 10, 2005 in Co-pending U.S. Appl. No. 10/228,680, filed Aug. 26, 2002.

Co-pending U.S. Appl. No. 11/100,956, filed Apr. 6, 2005.

Notice of Allowance Mailed Apr. 10, 2009 in Co-pending U.S. Appl. No. 11/100,956, filed Apr. 6, 2005.

Non-Final Office Action Mailed Apr. 7, 2008 in Co-pending U.S. Appl. No. 11/100,956, filed Apr. 6, 2005.

Non-Final Office Action Mailed Sep. 26, 2007 in Co-pending U.S. Appl. No. 11/100,956, filed Apr. 6, 2005.

Co-pending U.S. Appl. No. 12/509,210, filed Jul. 24, 2009.

Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.

Notice of Allowance Mailed Jul. 7, 2008 in Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.

Advisory Office Action May 30, 2008 in Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.

Final Office Action Mailed Jan. 8, 2008 in Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.

Non-Final Office Action Mailed Jan. 3, 2007 in Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.

(56)

References Cited**OTHER PUBLICATIONS**

Final Office Action Mailed Apr. 5, 2006 in Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.
 Non-Final Office Action Mailed Jun. 29, 2005 in Co-pending U.S. Appl. No. 10/023,915, filed Dec. 14, 2001.
 Co-pending U.S. Appl. No. 11/273,862, filed Nov. 14, 2005.
 Final Office Action Mailed Feb. 25, 2010 in Co-pending U.S. Appl. No. 11/273,862, filed Nov. 14, 2005.
 Non-Final Office Action Mailed Jun. 8, 2009 in Co-pending U.S. Appl. No. 11/273,862, filed Nov. 14, 2005.
 Co-pending U.S. Appl. No. 10/926,635, filed Aug. 25, 2004.
 Final Office Action Mailed Dec. 12, 2007 in Co-pending U.S. Appl. No. 10/926,635, filed Aug. 25, 2004.
 Non-Final Office Action Mailed Jun. 21, 2007 in Co-pending U.S. Appl. No. 10/926,635, filed Aug. 25, 2004.
 Co-pending U.S. Appl. No. 10/988,014, filed Nov. 12, 2004.
 Notice of Allowance Mailed Mar. 21, 2007 in Co-pending U.S. Appl. No. 10/988,014, filed Nov. 12, 2004.
 Non-Final Office Action Mailed Oct. 16, 2006 in Co-pending U.S. Appl. No. 10/988,014, filed Nov. 12, 2004.
 Co-pending U.S. Appl. No. 11/274,442, filed Nov. 14, 2005.
 Non-Final Office Action Mailed Dec. 10, 2008 in Co-pending U.S. Appl. No. 11/274,442, filed Nov. 14, 2005.
 Co-pending U.S. Appl. No. 11/371,627, filed Mar. 8, 2006.
 Non-Final Office Action Mailed Feb. 20, 2008 in Co-pending U.S. Appl. No. 11/371,627, filed Mar. 8, 2006.
 Co-pending U.S. Appl. No. 11/388,381, filed Mar. 23, 2006.
 Final Office Action Mailed Mar. 29, 2010 in Co-pending U.S. Appl. No. 11/388,381, filed Mar. 23, 2006.
 Non-Final Office Action Mailed Dec. 9, 2008 in Co-pending U.S. Appl. No. 11/388,381, filed Mar. 23, 2006.
 Co-pending U.S. Appl. No. 09/784,699, filed Jun. 13, 2006.
 Notice of Allowance Mailed Dec. 23, 2005 in Co-Pending U.S. Appl. No. 09/784,699, filed Feb. 14, 2001.
 Non-Final Office Action Mailed Oct. 3, 2005 in Co-Pending U.S. Appl. No. 09/784,699, filed Feb. 14, 2001.
 Final Office Action Mailed Mar. 7, 2005 in Co-Pending U.S. Appl. No. 09/784,699, filed Feb. 14, 2001.
 Non-Final Office Action Mailed Jun. 16, 2004 in Co-Pending U.S. Appl. No. 09/784,699, filed Feb. 14, 2001.
 Co-pending U.S. Appl. No. 11/453,301, filed Jun. 13, 2006.
 Non-Final Office Action Mailed Apr. 7, 2010 in Co-Pending U.S. Appl. No. 11/453,301, filed Jun. 13, 2006.
 Non-Final Office Action Mailed Aug. 6, 2009 in Co-Pending U.S. Appl. No. 11/453,301, filed Jun. 13, 2006.
 Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Final Office Action Mailed Jan. 8, 2008 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Non-Final Office Action Mailed Jul. 3, 2007 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Final Office Action Mailed Mar. 16, 2007 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Non-Final Office Action Mailed Dec. 7, 2006 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Non-Final Office Action Mailed Jul. 13, 2006 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.

Non-Final Office Action Mailed Feb. 16, 2006 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Final Office Action Mailed Sep. 20, 2005 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Non-Final Office Action Mailed Feb. 15, 2005 in Co-Pending U.S. Appl. No. 09/847,813, filed May 1, 2001.
 Co-Pending U.S. Appl. No. 10/010,147, filed Nov. 6, 2001.
 Notice of Allowance Mailed Oct. 28, 2005 in Co-Pending U.S. Appl. No. 10/010,147, filed Nov. 6, 2001.
 Non-Final Office Action Mailed Feb. 9, 2005 in Co-Pending U.S. Appl. No. 10/010,147, filed Nov. 6, 2001.
 Co-Pending U.S. Appl. No. 11/021,569, filed Dec. 22, 2004.
 Non-Final Office Action Mailed Oct. 28, 2008 in Co-Pending U.S. Appl. No. 11/021,569, filed Dec. 22, 2004.
 Final Office Action Mailed Mar. 21, 2008 in Co-Pending U.S. Appl. No. 11/021,569, filed Dec. 22, 2004.
 Office Action Mailed Sep. 18, 2007 in Co-Pending U.S. Appl. No. 11/021,569, filed Dec. 22, 2004.
 Co-Pending U.S. Appl. No. 09/826,607, filed Apr. 5, 2001.
 Advisory Action Mailed Oct. 23, 2006 in Co-Pending U.S. Appl. No. 09/826,607, filed Apr. 5, 2001.
 Final Office Action Mailed Jun. 19, 2006 in Co-Pending U.S. Appl. No. 09/826,607, filed Apr. 5, 2001.
 Non-Final Office Action Mailed Nov. 20, 2005 in Co-Pending U.S. Appl. No. 09/826,607, filed Apr. 5, 2001.
 Final Office Action Mailed May 24, 2005 in Co-Pending U.S. Appl. No. 09/826,607, filed Apr. 5, 2001.
 Non-Final Office Action Mailed Oct. 6, 2004 in Co-Pending U.S. Appl. No. 09/826,607, filed Apr. 5, 2001.
 Co-Pending U.S. Appl. No. 09/827,030, filed Apr. 5, 2001.
 Notice of Allowance Mailed Jan. 26, 2005 in Co-Pending U.S. Appl. No. 09/827,030, filed Apr. 5, 2001.
 Office Action Mailed Jun. 18, 2004 in Co-Pending U.S. Appl. No. 09/827,030, filed Apr. 5, 2001.
 Co-Pending U.S. Appl. No. 09/858,260, filed May 15, 2001.
 Notice of Allowance Mailed May 10, 2005 in Co-Pending U.S. Appl. No. 09/858,260, filed May 15, 2001.
 Office Action dated Sep. 7, 2004 in Co-Pending U.S. Appl. No. 09/858,260, filed May 15, 2001.
 Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Final Office Action Mailed Jan. 25, 2010 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Non-Final Office Action Mailed Mar. 3, 2009 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Advisory Action Mailed May 8, 2007 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Final Office Action Mailed Dec. 1, 2006 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Non-Final Office Action Mailed Nov. 17, 2005 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Non-Final Office Action Mailed Jun. 7, 2005 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Non-Final Office Action Mailed Dec. 14, 2004 in Co-Pending U.S. Appl. No. 10/005,729, filed Nov. 6, 2001.
 Co-Pending U.S. Appl. No. 09/996,180, filed Nov. 27, 2001.
 Office Action Mailed Feb. 24, 2005 in Co-Pending U.S. Appl. No. 09/996,180, filed Nov. 27, 2001.
 Co-Pending U.S. Appl. No. 12/062,789, filed Apr. 8, 2008.

* cited by examiner

100 →




FIG. 1

200 →




FIG. 2




FIG. 3




FIG. 4

500 →




FIG. 5

600 →




FIG. 6




FIG. 7

800 →




FIG. 8

900 →




FIG. 9




FIG. 10

1100 →




FIG. 11

1200 →




FIG. 12

1300 →

1302

1	0	0	1	0	1	1	0	1	0	1
2	1	0	0	1	0	1	0	1	0	1
3	0	1	1	1	0	1	1	1	1	0
4	1	0	1	0	0	0	1	1	0	0
5	0	1	0	1	0	0	1	1	1	1
6	0	1	1	1	1	0	0	0	0	1
7	1	0	1	0	1	1	0	0	0	1
8	1	1	1	0	1	1	0	1	0	0
9	0	1	1	0	0	1	0	1	0	0
10	1	0	0	1	1	0	1	1	1	0
	1	2	3	4	5	6	7	8	9	10

block

session

FIG. 13

1400 →




FIG. 14

1500 →




FIG. 15

1600 →




FIG. 16

1700 →




FIG. 17

DERIVING COMPONENT STATISTICS FOR A STREAM ENABLED APPLICATION

RELATED APPLICATIONS

This application claims priority to U.S. Provisional Appln. Ser. No. 60/986,260 filed Nov. 7, 2007 entitled "Deriving Component Statistics For A Stream-Enabled Application," which is incorporated herein by reference in its entirety.

BACKGROUND

A software application may include various functionality. Persons designing software may be confronted with a limited knowledge of their users. Developing functionality for software applications for users without understanding the ways in which users use software inhibits development. Developers wonder: Is certain functionality used? How popular is the functionality?

The foregoing examples of the related art and limitations related therewith are intended to be illustrative and not exclusive. Other limitations of the related art will become apparent to those of skill in the art upon a reading of the specification and a study of the drawings.

SUMMARY

The following examples and aspects thereof are described and illustrated in conjunction with systems, tools, and methods that are meant to be exemplary and illustrative, not limiting in scope. In various examples, one or more of the above described problems have been reduced or eliminated, while other examples are directed to other improvements.

A technique for determining component statistics may include associating blocks with components. A component in a block may begin at a block offset and have a length. A component included in multiple blocks may have multiple block offsets and lengths. A component may be identified within a block. In addition, for example, it may be desirable to analyze statistics to determine component popularity.

A method based on the technique may include associating a component with a block, receiving a log of requests for blocks, and providing the association of the component with one or more requests for the block from the log.

BRIEF DESCRIPTION

FIG. 1 depicts a diagram of an example of a system for determining component statistics.

FIG. 2 depicts a diagram of an example of a conventional software provider producing deliverables such as software and data from source files.

FIG. 3 depicts a flowchart of an example of a method for creating feature associations.

FIG. 4 depicts a diagram of an example of a stream enabler breaking deliverables into blocks and creating block associations.

FIG. 5 depicts a flowchart of an example of a method for creating blocks and block associations.

FIG. 6 depicts a diagram of an example of a block with a component located in a portion of the block.

FIG. 7 depicts a diagram of an example of two blocks associated with a deliverable, the second block including a component.

FIG. 8 depicts a diagram of an example of multiple blocks with a component spanning the multiple blocks.

FIG. 9 depicts a diagram of an example of a streaming system logging block requests.

FIG. 10 depicts a flowchart of an example of a method for logging block requests.

FIG. 11 depicts a diagram of an example of an aggregator producing a formatted log.

FIG. 12 depicts a flowchart of an example of a method for formatting a log.

FIG. 13 depicts a diagram of an example of a block-session grid indicating requests for blocks during sessions.

FIG. 14 depicts a diagram of an example of a component statistics engine generating report(s) including component statistics.

FIG. 15 depicts a flowchart of an example of a method for generating reports including component statistics.

FIG. 16 depicts a flowchart of an example of a method for associating a component of a stream-enabled application with one or more requests for a block of a stream-enabled application.

FIG. 17 depicts a diagram of an example of a system capable of determining component statistics.

DETAILED DESCRIPTION

In the following description, several specific details are presented to provide a thorough understanding. One skilled in the relevant art will recognize, however, that the concepts and techniques disclosed herein can be practiced without one or more of the specific details, or in combination with other components, etc. In other instances, well-known implementations or operations are not shown or described in detail to avoid obscuring aspects of various examples disclosed herein.

FIG. 1 depicts a diagram of an example of a system **100** for determining component statistics. The system **100** includes conventional software provider **102**, stream enabler **104**, component statistics engine **108**, and streaming software system **106**. The parts portrayed in this figure can be arbitrarily combined or divided into separate software, firmware, and/or hardware components. Such components, regardless of how they are combined or divided, can execute on the same computing device or multiple computing devices. The multiple computing devices may be connected by one or more networks.

In the example of FIG. 1, conventional software provider **102** provides deliverables such as data, executable code, and libraries. Providing may be by way of download over a network, from an input/output (I/O) device, or via any known or convenient mechanism.

A component of a conventionally coded software application may be a part of a deliverable file. The deliverable file may have a filename. A component may be identified by a tuple including a filename, an offset, and a length. A component may be equivalent to a deliverable file, or may include only a portion of a deliverable file. An application may be made up of one or more components. In a non-limiting example, a component may include executable code, game level data, phone number data, or any other data that may be stored in a file.

A feature may include one or more components, one or more features, or any combination of zero or more components and zero or more features. A feature defined in terms of components and other features may be reduced to a list of unique components by merging, without duplication, the components of the other features. In a non-limiting example a first feature may include the components that compose the English spell checking module; a second feature may include

the components that compose the Spanish spell checking module; while a third feature may include the first and second features.

In the example of FIG. 1, the conventional software provider **102** may maintain link maps. A link map associates features with files, offsets, and lengths. Each file, offset, and length may correspond to a component. A link map may be used to associate features with components. In a non-limiting example, function names are associated with files, offsets, and lengths in a conventional link map.

Some features could be identified using a link map interpreting tool that locates components. In a non-limiting example, the tool may take a file including a description of levels of a game; the tool may provide information to identify the locations in files of components included in the features.

In the example of FIG. 1, the stream enabler **104** receives non-stream-enabled deliverables associated with an application and breaks the deliverables into blocks. The stream enabler **104** may or may not associate files with blocks, block offsets and lengths and create block associations. This association may be stored in a file for subsequent use. The stream enabler **104** may also convert the deliverables into a stream-enabled application for use with a streaming software system.

In the example of FIG. 1, the streaming software system **106** may be one or more computing devices. The one or more computing devices receive the stream-enabled application and execute the stream-enabled application. The stream-enabled application may or may not be an executable. It may be possible for the stream-enabled application to be a single executable including the entire stream-enabled application. It may also be possible for the stream-enabled application to be only data, having no executable content.

In the example of FIG. 1, the streaming software system **106** may collect block statistics, such as by logging block usage as discussed later with reference to FIGS. 7-9.

In the example of FIG. 1, the component statistics engine **108** may or may not receive feature associations from the conventional software provider **102**, block associations from the stream enabler **104**, and/or log information or block statistics from the streaming software system **106**.

An engine typically includes a processor and memory. The memory may include instructions for execution by the processor. The memory may include random access memory (RAM), non-volatile (NV) storage, or any other known or convenient mechanism for storing data.

In the example of FIG. 1, the component statistics engine **108** may use block associations to create statistics. In a non-limiting example, component statistics engine **108** receives a set of blocks requested during sessions and a map file associating components with blocks. Component statistics engine generates reports of components most frequently requested. These reports can be used by a party, such as a person associated with the conventional software provider **102**, by way of example, but not limitation, estimate the popularity of a particular component.

FIG. 2 depicts a diagram **200** of an example of a conventional software provider producing deliverables from source files. The diagram **200** includes source files **202**, compilation tool **204**, feature associations **206**, and deliverables **208**.

In the example of FIG. 2, source files **202** could be conventional source files, code, specifications for products, specifications of game levels, or any description of data that could be processed and or compiled into a file. A variety of programming languages, scripting languages, and descriptive languages could be used to prepare source files. Collections of files organized as a project could be source files. In a non-limiting example, a source file is a high level description

of a function written in the C++ programming language. Another non-limiting example of a source file is a data file prepared for interpretation by an interpreter.

In the example of FIG. 2, compilation tool **204** could be a conventional compiler or any other tool that could take a source file and produces, for example, a deliverable file. The compilation tool **204** could be a low level assembler, or a high level compiler for languages. The compilation tool **204** could be an interpreter. In a non-limiting example, the compilation tool **204** operates with the Java programming language. In another non-limiting example, the compilation tool **204** operates with an assembly language.

In the example of FIG. 2, feature associations file **206** associate components with deliverables, offsets and lengths. In a non-limiting example, a particular component of a word processing program could be a spell-checker. The spell-checker could be associated with components and identified in files at particular offsets and having particular lengths. A particular feature could be spread across multiple files, in which case multiple files, offsets and lengths could be included in the feature associations to associate the feature with the file(s).

The feature associations file **206** could be created using link maps. Link maps may enable finer component analysis. With the link map it may be possible to locate functions, and components that are not readily identifiable from analysis of the deliverables. In some cases at least some of the information in a link map may be ascertainable through analysis of a software application. In a non-limiting example, a component can be associated with file "foo.dll," offset **1000**, length 128 Kb. Feature associations **206** would include an entry associating the component with file foo.dll at offset **1000**, length 128K.

In the example of FIG. 2, deliverables **208** may include a variety of different components including any file necessary to support the application. In a non-limiting example, deliverables **208** could be executable files, library files, and data files. These files are typically delivered to a consumer via a CD, DVD, downloadable media, or other software delivery mechanism. The deliverables may or may not include an installer program that can be used to install the software on an end user's computing device.

In the example of FIG. 2, in operation, compilation tool **204** may produce feature associations **206** and deliverables **208** from source files **202**. Compilation of source files **202** may involve translating a source file language into a target language. The deliverables **208** may be generated by translating. The feature associations **206** may be generated while translating. A function or other component of interest may be compiled into one or more files, at offsets and lengths. A link map may be generated. In a non-limiting example, machine code, a lower level language, is generated from code written in a high level programming language, Java.

FIG. 3 depicts a flowchart **300** of an example of a method for creating feature associations. The method is organized as a sequence of modules in the flowchart **300**. However, it should be understood that these and modules associated with other methods described herein may be reordered for parallel execution or into different sequences of modules.

In the example of FIG. 3, the flowchart **300** starts at module **302** with receiving source files. Source files could be received by an interface, such as on a CD-ROM, a DVD-ROM, or via a downloadable file. Source files may be created, stored locally, and received from a local memory. A compilation tool may receive source files.

In the example of FIG. 3, the flowchart **300** continues to module **304** with translating a source language into a target

5

language. A source language may be a high level descriptive language or a low level descriptive language. A file encoding could be a source language. A target language include binary code, object code, executable code, non-executable code, interpreted file encoding, or any other target language known or convenient.

In the example of FIG. 3, the flowchart 300 continues to module 306 with creating feature associations useful in determining component statistics of a stream-enabled application. Feature associations could include link maps and may also include associations not found in a link map such as associations between functional and non-functional components of an application. In a non-limiting example, a data component may be associated with an executable component where each is part of an image searching function. A particular feature could include multiple components and the multiple components could be spread across multiple files. Feature associations may identify the components and the data as part of a feature. Feature associations may allow for analysis of features associated with multiple components. Having created feature associations useful in determining component statistics of a stream-enabled application, the flowchart terminates.

FIG. 4 depicts a diagram 400 of an example of a stream enabler breaking deliverables into blocks and creating block associations. The diagram 400 includes deliverables 402, stream enabler 404, blocks 406, and block associations 408.

In the example of FIG. 4, deliverables 402 may be executable files, library files, data files, and any other files required to support an application. The deliverables 402 collectively may be one or more conventionally coded software applications designed for execution on a conventional computing device. Deliverables may be included on one or more disks, CD-ROMs, DVD-ROMs, or in one or more downloadable files. An installer may be included in deliverables 402 to install deliverables 402 on to a conventional computing device.

In the example of FIG. 4, stream enabler 404 includes chunking engine 410, block associations engine 412, first interface 414, second interface 416, and third interface 418. Stream enabler 404 may include a processor and memory. Memory may include random access memory (RAM), non-volatile (NV) storage, or any storage medium known or convenient. In the example of FIG. 4, first interface 414, second interface 416, and third interface 418 could be a single interface capable of both input and output.

In the example of FIG. 4, chunking engine 410 may include a module for reading deliverables into a memory and writing out blocks of an optimal block size. Locations for reading deliverables and writing blocks may be specified. Rules for determining an optimal block size may be specified. An optimal block size may be specified. In a non-limiting example, the value may be in bytes, bits or other size known or convenient. Instructions for operation may be provided prior to or concurrent with operation.

In the example of FIG. 4, block association engine 412 may include a module for associating a deliverable file, offset and length, with a block. A module for producing a file containing block associations may be specified. A format for the file including the block associations may be specified.

In the example of FIG. 4, the blocks 406 may include one or more blocks associated with a stream-enabled application. The blocks 406 may include an executable file associated with executing the stream-enabled application. One or more blocks of the blocks 406 may include components stored in various blocks at various offsets and lengths.

In the example of FIG. 4, the block associations 408 associate blocks with files, offsets and lengths. A block associa-

6

tion may include a block identifier and a deliverable filename, offset, and length. Block associations 408 may include each file, offset and length for a plurality of blocks and a plurality of deliverables. In a non-limiting example, a deliverable is a file, foo.exe, and foo.exe is broken into three blocks, block A, block B, and block C; a block association is created associating blocks A, B, and C with foo.exe where each block has a specific offset and length.

In the example of FIG. 4, block associations 408 may be related with feature associations to identify components. In a non-limiting example, a feature may be identified as corresponding to blocks 27, 28, 29, and 30. Component utilization through requests for blocks 27, 28, 29, and 30 may thus be used to determine statistics for the feature.

In the example of FIG. 4, in operation, stream enabler 404 receives deliverables 402 through first interface 414, and chunking engine 410 breaks deliverables 402 into blocks 406. If a deliverable is smaller than the optimal block size it is theoretically possible for the stream enabler 404 to create a single block including the deliverable. Concurrently, block associations engine 412 creates block associations 408 identifying blocks with deliverables.

FIG. 5 depicts a flowchart 500 of an example of a method for creating blocks and block associations. The method is organized as a sequence of modules in the flowchart 500. However, it should be understood that these and modules associated with other methods described herein may be reordered for parallel execution or into different sequences of modules.

In the example of FIG. 5, the flowchart 500 starts at module 502 with receiving deliverables via an interface. The interface may receive deliverables via one or more disks, CD-ROMs, DVD-ROMs, one or more downloadable files, or any manner known or convenient.

In the example of FIG. 5, the flowchart 500 continues to module 504 with breaking deliverables into blocks. A stream enabler may break a deliverable into blocks. If a deliverable is smaller than the optimal block size it is theoretically possible for a stream enabler to create a single block. However, deliverables may be broken into many blocks. An optimal block size may be used to break deliverables into blocks.

In the example of FIG. 5, the flowchart 500 continues to module 506 with creating block associations. A block association may include a block identifier and a deliverable filename, offset, and length. Block associations may include a file and a plurality of blocks associated with the file. Block associations may be created while a stream enabler breaks deliverables into blocks. Having created block associations, the flowchart terminates.

FIG. 6 depicts a diagram 600 of an example of a component located in part of a block. M may be measured in any known or convenient manner, e.g., bits or bytes. Diagram 600 includes block 608, block offset 610, and block offset 612. In a non-limiting example, the block 608 includes a part of a file foo.dll and a component starting at block offset 610, and having length M includes a function for which analysis is desirable.

FIG. 7 depicts a diagram 700 of an example of a deliverable broken into two blocks, the second block including a component. The diagram 700 includes block 702, block 704, and block offset 706. Foo.exe is an example of a deliverable that has been broken into multiple blocks including block 702 and block 704. For the purpose of this example only, foo.exe spans block 702 and block 704. However, features could span portions of a plurality of not-necessarily-sequential blocks. A component of the deliverable is stored in a part of block 704. The component begins at block offset 706, and spans length

7

L. Accessing a portion of the component might require, for example, requesting block **704**, blockoffset **706**, length 512 bytes.

FIG. **8** depicts a diagram **800** of an example of a component spanning multiple blocks. FIG. **8** includes block **802**, block **804**, block **806**, block offset **810**, and block offset **812**. A stream enabler may break a deliverable file into multiple blocks. As a result, a component included in the deliverable file identified by a file, offset, and length may be included in multiple blocks when the deliverable is broken into multiple blocks. Accessing a part of the component may include a request to a part of block **802**, a part of block **804**, or a part of block **806**. Creating statistics of the component's usage may require tracking requests for the multiple blocks. A first sub-component begins at block **802** offset **810** and spans length L. The component continues with a second sub-component at block **804**, offset zero, and spans length M, all of block **804**. The component continues with a third sub-component that begins at block **806**, offset zero, and spans length N.

FIG. **9** depicts a diagram **900** of an example of a streaming system logging block requests. The diagram **900** includes virtually installed application **902**, virtual environment **904**, raw log **906**, blocks **908**, and streaming system **910**.

In the example of FIG. **9**, the virtually installed application **902** is an instance of a program that has been stream-enabled. The virtually installed application can operate as though it has access to local components at particular offsets and lengths. A conventional OS may be made available to virtually installed application **902**, and virtually installed application may execute as though it is executing on the conventional OS.

In the example of FIG. **9**, virtual environment **904** enables a streamed application to execute on a computing device in a virtualized execution environment. An example of a virtualized execution environment is discussed in U.S. patent application Ser. No. 09/098,095 entitled "METHOD AND APPARATUS TO ALLOW REMOTELY LOCATED COMPUTER PROGRAMS AND/OR DATA TO BE ACCESSED ON A LOCAL COMPUTER IN A SECURE, TIME-LIMITED MANNER, WITH PERSISTENT CACHING," which is incorporated by reference. The virtual environment **904** may include an agent process associated with virtually installed application, and capable of requesting blocks. The virtual environment **904** may include an agent process associated with logging.

In the example of FIG. **9**, raw log **906** includes zero or more entries, an entry including a unique session identifier and zero or more block IDs. If the raw log does not include any entries, it may be referred to as an empty log. A plurality of entries may be maintained. It may be desirable to store raw log **906** as a database. Any known or convenient implementation of a database may be used. It should be noted that the term "database" is intended to be afforded a meaning broad enough to include a log file or a data dump.

In some cases it may be desirable to maintain raw log **906** in a format. Any format known or convenient may be used, and raw log **906** could be unformatted, as well. It should be noted that, as used herein, a "formatted log" is normally referred to in association with a log processed from the raw log. In this context, the raw log, regardless of format, would not be referred to as a "formatted log."

In the example of FIG. **9**, blocks **908** may include one or more blocks of a stream-enabled application. Deliverables of a conventionally coded application may be broken into the blocks **908** during stream-enablement. The blocks **908** may include one or more components of the stream-enabled application.

8

In the example of FIG. **9**, streaming system **910** may include one or more computing devices. Streaming system **910** may include a server and a streaming playback device. A streaming playback device may be any computing device for executing a stream-enabled application, and would typically include the virtual environment **904**. Streaming system **910** may be a stand alone device executing a stream-enabled application.

The agent process associated with logging may have an associated delta transmission protocol. In a delta transmission protocol, the agent process remembers identifiers (ID)s of blocks that have already been transmitted and only sends the block IDs of blocks not previously transmitted. Advantageously, with a delta transmission protocol, block IDs are not normally redundantly retransmitted.

In the example of FIG. **9**, in operation, a virtually installed application executes and receives a unique session identifier. If the streamed application is being executed multiple times in the virtual environment **904** each instance may receive a unique session identifier. If a streamed application is run concurrently in multiple environments, each instance may receive a unique session identifier. While executing, the virtually installed application **902** makes a resource request to virtual environment **904**. The virtually installed application **902** operates as though it is opening and reading resources from local components at particular offsets and lengths. The virtualized environment **904** receives the request instead. The resource request is ultimately translated into a list including one or more blocks. Block IDs of the one or more blocks are provided to raw log **906**. The agent process of the virtual environment may buffer the IDs of blocks that have been requested. The agent process may then transmit the buffer to subsequent logging processes that ultimately provide block IDs to raw log **906**. An agent process may choose to use a delta transmission protocol. The block request may be provided to streaming system **910** which, if necessary, requests the blocks included in the list. Streaming system **910** receives the blocks. A subset of block data of the one or more blocks may then be delivered to the virtualized environment **904**. Virtualized environment **904** may then provide the subset of block data as resources to virtually installed application **902** to satisfy the resource request.

In the example of FIG. **9**, in operation, caching may occur in one or more places. For example, the virtual environment **904** may maintain a cache for requested resources. If the virtual environment receives a request for a resource, it may provide a block ID associated with the resource to the raw log **906** so that the number of requests for resources is recorded even if the actual block request is not sent to the streaming system **910**. Then the virtual environment **904** may, depending upon the implementation, either provide the resource to the virtually installed application **902**, or request the resource from the streaming system **910**, which satisfies the request. It may be noted that not all virtual environments **904** will necessarily include a cache.

As another example, the streaming system **910** may maintain a cache of recently used blocks and may satisfy block requests from the cache. Streaming system **910** may or may not record block requests regardless of whether the requests are satisfied from the cache. If the raw log **906** is implemented to include substantially all resource requests, some block request logging might be redundant. Block access statistics may be generated from the block request log (not shown) of the streaming system **910** and/or from the raw log **906**.

In a non-limiting example, an operating system (OS) may maintain a cache of recently used pages. If a request from a stream-enabled application can be satisfied from an OS's

virtual machine (VM) cache, the OS may satisfy the request from the VM cache. An initial request may be logged, but subsequent requests to the cached blocks may be invisible to the streaming system, and thus, may or may not be used to generate block frequency statistics.

In one implementation, a streaming playback device is remotely coupled to a server. The server may include the blocks **908**. One or more block-caching servers might exist between the streaming playback device and the server. Such block-caching servers may provide a block to the playback device without a request reaching the server. In another implementation, a streaming playback device is coupled to an I/O device that includes the block **908**. In this case, the playback device may be described as streaming from a peripheral device. In any case, the streaming system **910** may be treated in most requests as an OS or kernel of the playback device.

FIG. **10** depicts a flowchart **1000** of an example of a method for logging block requests. The method is organized as a sequence of modules in the flowchart **1000**. However, it should be understood that these and modules associated with other methods described herein may be reordered for parallel execution or into different sequences of modules.

In the example of FIG. **10**, the flowchart **1000** starts at module **1002** with virtually installing an application. Virtually installing an application may include instantiating an instance of the application within a virtualized environment. Virtually installing an application may or may not require a prior installation of a virtualized environment. Blocks that include data necessary to fully utilize the virtual application may be transferred, either in advance or upon request, to a computing device for execution of the virtually installed application.

In the example of FIG. **10**, the flowchart **1000** continues to module **1004** with generating a session identifier for the virtually installed application. If the virtually installed application is being executed multiple times, each instance may receive a unique session identifier. If the virtually installed application is run concurrently in multiple virtual environments, each instance may receive a unique session identifier. It may be desirable to generate a unique session identifier, which can be maintained to identify the session and virtually installed application without confusing the application with other sessions, other instances of the application, other versions of the application, or other applications. The session identifier may be used by the virtually installed application to identify itself as a source of a request for blocks and the destination for the blocks so that the request may be logged.

In the example of FIG. **10**, the flowchart **1000** continues to module **1006** with receiving a resource request from the virtually installed application. A virtualized environment may receive the resource request. A virtually installed application may operate as though it is opening and reading resources from local components at particular offsets and lengths, and may request resources as though it is executing locally.

In the example of FIG. **10**, the flowchart **1000** continues to module **1008** with translating the resource request into a list including one or more blocks. The resource request may be translated into a list including one or more blocks. The blocks may include resources relevant to the request from the virtual application. In one implementation, the virtual environment may add resources the virtual environment believes will be requested soon by the virtually installed application.

In the example of FIG. **10**, the flowchart **1000** continues to module **1010** with providing block IDs of the one or more blocks to a raw log. An entry in the raw log may include a session identifier (ID) associated with the block IDs. In some cases it may be desirable to format the entries as they are

provided to the raw log. Any format known or convenient may be used. The raw log may be unformatted. A plurality of entries may be maintained, or the raw log may be sent upstream to a streaming software server as entries are generated.

It should be noted that in some cases, a streaming client will not be interested in waiting around for a streaming program to complete a clean-up routine. For example, if it takes time for a machine to close a streaming program when the user is finished with it, the user may turn off the computer or kill the program in some other manner. Thus, if the raw log is maintained on the client machine until the streaming session is over, and then attempts to send it, the raw log may never be sent. Accordingly, in one implementation, raw log entries are sent immediately to the streaming server as the entries are generated. A disadvantage of such an implementation is that formatting of the raw log may not be possible at the client.

In the example of FIG. **10**, the flowchart **1000** continues to module **1012** with receiving the blocks. The blocks may include one or more components of a stream-enabled application. The virtualized environment may be executing on a computing device. An interface of the computing device may receive the blocks. Notably, the blocks could be received in advance of receiving a resource request (module **1006**) by employing techniques such as background downloading of blocks, predictive streaming, and caching.

In the example of FIG. **10**, the flowchart **1000** continues to module **1014** with satisfying the resource request of the virtually installed application. A subset of block data of the blocks may then be delivered to the virtually installed application via a virtual execution environment to satisfy the resource request. Having satisfied the resource request, the flowchart **1000** continues to decision point **1016** where it is determined whether additional requests are made.

In the example of FIG. **10**, if it is determined that additional requests are made (**1016**—Yes), then the flowchart **1000** continues to module **1006** and proceeds as described previously. If, on the other hand, it is determined that additional requests are not made (**1016**—No), then the flowchart **1000** ends. It should be noted that a virtual environment may have no way of determining whether there are additional resource requests until the virtual environment actually intercepts such a request from the virtually installed application.

FIG. **11** depicts a diagram **1100** of an example of an aggregator producing a formatted log. The diagram **1100** includes raw streaming session logs **1102**, aggregator **1104**, aggregation preferences **1106**, and formatted streaming session log **1108**.

In the example of FIG. **11**, the raw streaming session logs **1102** include one or more logs, a raw streaming session log including zero or more entries. An entry may include a unique session identifier (ID) and zero or more block IDs. The raw streaming session log **1102** may be unformatted, or any known or convenient format may be used. As was noted previously, although the raw streaming session logs **1102** may have a format, it is not referred to as such to avoid confusing the raw streaming session logs **1102** with the formatted streaming session log **1108**.

In the example of FIG. **11**, the aggregator **1104** may include a processor and memory. Memory may include random access memory (RAM), non-volatile (NV) storage, or any storage medium known or convenient. The memory may include instructions for formatting the raw streaming session log into the formatted streaming session log **1108**.

In the example of FIG. **11**, the aggregation preferences **1106** may include one or more user generated or pre-deter-

11

mined preferences. Log formats may be included. Criteria for aggregating logs to focus on only a subset of block IDs or sessions may be included.

In the example of FIG. 11, formatted streaming session log 1108 may include entries of blocks associated with a session. The encoding of the formatted streaming session log 1108 could be a bit map with one bit associated with each block in the application. A set bit may indicate that the block associated with that bit was accessed. Another encoding could be to associate a unique session ID with a list of one or more block IDs. Any other encoding format known or convenient could be used.

In the example of FIG. 11, in operation, the aggregator 1104 may receive via one or more interfaces some or all of the raw streaming session log 1102, and the aggregation preferences 1106. The aggregator 1104, in accordance with the aggregation preferences 1106, may then aggregate block IDs in accordance with the aggregation preferences 1106. In a non-limiting example aggregator 1104 aggregates block statistics for a plurality of sessions by collating blocks IDs by unique session ID to produce the formatted log 1106. In a non-limiting example the aggregator 1104 produces a formatted streaming session log 1108 having a logical representation as a block-session grid.

FIG. 12 depicts a flowchart 1200 of an example of a method for formatting a log. The method is organized as a sequence of modules in the flowchart 1200. However, it should be understood that these and modules associated with other methods described herein may be reordered for parallel execution or into different sequences of modules.

In the example of FIG. 12, the flowchart 1200 starts at module 1202 with receiving one or more raw streaming session logs including session IDs and block IDs. The one or more raw streaming session logs may be received via an interface.

In the example of FIG. 12, the flowchart 1200 continues to module 1204 with receiving aggregation preferences. Aggregation preferences may be generated locally by a user, or received via a communication interface. Aggregation preferences may specify one or more log formats as well as criteria for aggregating a log.

In the example of FIG. 12, the flowchart 1200 continues to module 1206 with aggregating block IDs and session IDs in accordance with the aggregation preferences. One or more formatted logs may be produced. The encoding of the formatted log could be a logical block-session grid, a sequential list of unique session IDs with associated block IDs, or any other applicable known or convenient format.

In the example of FIG. 12, the flowchart 1200 continues to module 1208 with providing a formatted log. Providing may be accomplished via an interface, or via delivery to a local computing device. The formatted log may be stored in a file, database, or other known or convenient data structure. A known or convenient storage medium may be used. Having provided a formatted log, the flowchart 1200 terminates.

FIG. 13 depicts a diagram 1300 of an example of a block-session grid indicating requests for blocks during sessions. The diagram 1300 includes block-session grid 1302. Block-session grid 1302 presents an example of a grid for storing block access requests. If an entry in the grid is set to 1 then the given block was accessed in the corresponding session. In another way of formatting a log file, a block-session grid could be used to store a frequency count indicating an approximation of the total number of accesses for that block for the given session. In such a case, the values stored in the cells of the grid could be 0, 1, 2 . . . n, as opposed to a binary representation of 0 or 1.

12

FIG. 14 depicts a diagram 1400 of an example of a component statistics engine generating report(s) including component statistics. The diagram 1400 includes block associations 1402, formatted log 1404, component statistics engine 1406, and report(s) 1408.

In the example of FIG. 14, the block associations 1402 may include relationships for each file, offset and length for a plurality of blocks and a plurality of deliverables.

In the example of FIG. 14, the formatted log file 1404 may include one or more entries. An entry may include a unique session identifier (ID) and zero or more block IDs. The formatted log file 1404 may be formatted in any manner known or convenient. In a non-limiting example, the format is a logical block-session grid, or a sequential list of sessions and block IDs.

In the example of FIG. 14, the component statistics engine 1406 may include component statistics & determination module 1410, optional demographics module 1412, and report generation module 1414. In the example of FIG. 14, the component statistics & determination module 1410 may include various functionality for analyzing log files using block associations, and optionally feature associations 1416. Feature associations 1416 may enable finer component analysis. A particular feature could be spread across multiple deliverables, in which case multiple files, offsets and lengths could be included in the feature associations to associate a feature with deliverables. Feature associations 1416 may include listings of tuples of files, offsets and lengths. Although optional, the feature associations 1416 could advantageously provide more detailed analysis of, e.g., functions/procedures.

In the example of FIG. 14, the optional demographics module 1412 may include functionality for identifying the use of components and functions by various users and groups of users. Optional demographics module 1412 may receive optional demographics data 1418. Demographics data 1418 may include information directed to various age groups, geographic locations, occupations, and any other group defining factor. In a non-limiting example, demographic data could be useful for distinguishing between urban and rural users to determine that a business address locating feature is more popular with urban users than with rural users.

In the example of FIG. 14, the report generation module 1414 includes various functionality to provide a formatted or unformatted report. In addition, the report generation module 1414 may receive optional report preferences 1420. In the example of FIG. 14, the report preferences 1406 may include user generated or precompiled options for generating reports. In a non-limiting example, a user might specify a set of unique sessions for analysis, or might specify known blocks for analysis to narrow the scope of statistics generated. Although the report preferences 1420 are optional, because the reports could be generated in a predetermined manner, report preferences will typically be desirable to ensure that reports are generated in a manner most useful for a given situation, application, enterprise, or person.

In the example of FIG. 14, the reports 1408 may include any formatted or unformatted data produced by the component statistics engine 1406. In a non-limiting example: a % of sessions that used a certain components could be included in a report. A % coverage, or amount of the streamed application used, could be included. A % coverage of an individual feature, or amount of an individual feature requested in terms of its associated blocks could be included.

In the example of FIG. 14, in operation, the component statistics engine 1406 receives the block associations 1402 and the formatted log file 1404, and outputs report(s) 1408. The component statistics & determination module processes

13

the formatted log file **1404** using the block associations **1402**. The processing involves determining which blocks were requested, and perhaps how many times the blocks were requested, per session. Then, using the block associations **1402** and the optional feature associations **1416**, the component statistics engine **1406** may estimate how many times components were used by streaming clients (or consumers of stream-enabled application content). Optionally, the demographics module **1412** may apply the demographics data **1416** to analyze and further characterize the users of the components and/or identify usage of various components by demographic.

Optionally, the feature association module **1412** may provide fine analysis using feature associations **1416**. Feature associations **1416** may be provided by the manufacturer of the deliverables prior to stream enabling. Feature associations are often confidential, and associated functionality may be normally disabled and may only be enabled if the feature association data is available. So, a stream enabler service might make use of the component statistics engine **1406** without the feature associations **1416**, while a software deliverables manufacturer might make use of the component statistics engine **1406** with the feature association module. Alternatively, a service may utilize the component statistics engine **1406** as a tool for multiple parties, but only enable functionality associated with the feature associations **1416** for those parties that provide feature associations **1416**.

The report generation module **1414** uses the data from the component statistics & determination module **1410** and optionally the demographics module **1412** to generate report (s) **1408**. Optionally, the report generation module receives report preferences **1420** and creates a formatted or unformatted report in accordance with the preferences. A variety of reports may be generated. In a non-limiting example, a % of sessions that used a certain component could be included in a report; a % coverage, or percentage of the streamed application used, could be included; a % coverage of an individual feature, or amount of an individual feature requested could be included.

FIG. 15 depicts a flowchart **1500** of an example of a method for generating reports including component statistics. The method is organized as a sequence of modules in the flowchart **1500**. However, it should be understood that these and modules associated with other methods described herein may be reordered for parallel execution or into different sequences of modules.

In the example of FIG. 15, the flowchart **1500** starts at module **1502** with receiving block associations, a formatted log file, and optional feature associations. User preferences may also be received. Specifically, a user may specify statistics to be determined and/or desired reporting layout. Receiving may be accomplished via a network interface, an I/O interface, or some other known or convenient interface. Receiving may be accomplished by retrieving from a local storage medium.

In the example of FIG. 15, the flowchart **1500** continues to module **1504** with processing block associations with the formatted log file. Optionally, feature associations may be employed. For example, the popularity of a component may be estimated by determining the frequency of block requests for blocks associated with the component. Components that are used infrequently may also be identified.

Sometimes requesting a feature requires requesting more than one block. There, a number of blocks may be requested. In evaluating the number of block requests for the feature the number of associated block requests may be divided by the number of blocks of the feature to determine a number of

14

requests for the feature. In a non-limiting example, 3 blocks are associated with components of a feature B. The three blocks are necessary to use feature B. 9 block requests are logged for the components of the feature B. The 9 block requests may be divided by the three blocks associated with the feature to determine that the feature was requested 3 times.

In the example of FIG. 15, the flowchart **1500** continues to module **1506** with optionally processing the formatted log file (or the results of module **1504**) with feature associations. For example, a popularity of a feature may be estimated by determining the frequency of block requests for blocks associated with the feature. Features may be spread across not-necessarily-sequential blocks.

In the example of FIG. 15, the flowchart **1500** continues to module **1508** with generating one or more reports. Reports associated with coverage and usage may be generated. Having generated one or more reports from a formatted log file and lock associations, the flowchart terminates.

FIG. 16 depicts a flowchart **1600** of an example of a method for associating a component of a stream-enabled application with one or more requests for a block of a stream-enabled application. The method is organized as a sequence of modules in the flowchart **1600**. However, it should be understood that these and modules associated with other methods described herein may be reordered for parallel execution or into different sequences of modules.

In the example of FIG. 16, the flowchart **1600** starts at module **1602** with associating a component of a stream-enabled application with a block of the stream-enabled application. This may be accomplished such as by using feature associations with block associations.

In the example of FIG. 16, the flowchart **1600** continues to module **1604** with receiving logs of requests for blocks of the stream-enabled application intercepted by a virtual environment. This may be accomplished such as by collecting a formatted log.

In the example of FIG. 16, the flowchart **1600** continues to module **1606** with providing the association of the component with the one or more requests for the stream-enabled application. A file including the association may be generated, or alternatively, the association may be transmitted. Having associated requests for blocks with components, the flowchart **1600** ends.

FIG. 17 depicts an example of a system **1700** capable of determining component statistics. The computing system **1700** may be a conventional computing system that can be used as a client computing system, such as a wireless client or a workstation, or a server computing system. The computing system **1700** includes a computer **1702**, and a display device **1706**. The computer **1702** includes a processor **1708**, interface **1710**, memory **1712**, display controller **1714**, and non-volatile storage **1716**. The computer **1702** may be coupled to or include display device **1706**.

The computer **1702** interfaces to external systems through the interface **1710**, which may include a modem, network interface, CD-ROM drive, DVD-ROM drive, or any known or convenient interface. An interface may include one or more input-output devices. Interface **1710** may include one or more interfaces. An interface may include a device for reading a fixed media. An interface may receive deliverables. An interface may transmit a stream-enabled application. It will be appreciated that the interface **1710** can be considered to be part of the computing system **1700** or a part of the computer **1702**. The interface **1710** can be an analog modem, ISDN modem, cable modem, token ring interface, satellite trans-

15

mission interface (e.g. "direct PC"), or other interface for coupling a computing system to other computing systems.

The processor 1708 may be, for example, a conventional microprocessor such as an Intel Pentium microprocessor or Motorola power PC microprocessor. The memory 1712 is coupled to the processor 1708 by a bus 1720. The memory 1712 can be Dynamic Random Access Memory (DRAM) and can also include Static RAM (SRAM). The bus 1720 couples the processor 1708 to the memory 1712, also to the non-volatile storage 1716, and to the display controller 1714.

The non-volatile storage 1716 is often a magnetic hard disk, an optical disk, or another form of storage for large amounts of data. Some of this data is often written, by a direct memory access process, into memory 1712 during execution of software in the computer 1702. One of skill in the art will immediately recognize that the terms "machine-readable medium" or "computer-readable medium" includes any type of storage device that is accessible by the processor 1708 and also encompasses a carrier wave that encodes a data signal.

The computing system 1700 is one example of many possible computing systems which have different architectures. For example, personal computers based on an Intel microprocessor often have multiple buses, one of which can be an I/O bus for the peripherals and one that directly connects the processor 1708 and the memory 1712 (often referred to as a memory bus). The buses are connected together through bridge components that perform any necessary translation due to differing bus protocols.

Network computers are another type of computing system that can be used in conjunction with the teachings provided herein. Network computers do not usually include a hard disk or other mass storage, and the executable programs are loaded from a network connection into the memory 1712 for execution by the processor 1708. A Web TV system, which is known in the art, is also considered to be a computing system, but it may lack some of the features shown in FIG. 17, such as certain input or output devices. A typical computing system will usually include at least a processor, memory, and a bus coupling the memory to the processor.

In addition, the computing system 1700 is controlled by operating system software which includes a file management system, such as a disk operating system, which is part of the operating system software. One example of operating system software with its associated file management system software is the family of operating systems known as Windows® from Microsoft Corporation of Redmond, Wash., and their associated file management systems. Another example of operating system software with its associated file management system software is the Linux operating system and its associated file management system. The file management system is typically stored in the non-volatile storage 1716 and causes the processor 1708 to execute the various acts required by the operating system to input and output data and to store data in memory, including storing files on the non-volatile storage 1716.

Some portions of the detailed description are presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of operations leading to a desired result. The operations are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared,

16

and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as "processing" or "computing" or "calculating" or "determining" or "displaying" or the like, refer to the action and processes of a computing system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computing system's registers and memories into other data similarly represented as physical quantities within the computing system memories or registers or other such information storage, transmission or display devices.

The teachings included herein also relate to an apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may comprise a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but is not limited to, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, or any type of media suitable for storing electronic instructions, and each coupled to a computing system bus.

The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will appear from the description below. In addition, there is no reference to any particular programming language, and various examples may be implemented using a variety of programming languages.

It will be appreciated to those skilled in the art that the preceding examples are not limiting in scope. It is intended that all permutations, enhancements, equivalents, and improvements thereto that are apparent to those skilled in the art upon a reading of the specification and a study of the drawings are included within the true spirit and scope of these teachings. It is therefore intended that the following appended claims include all such modifications, permutations, and equivalents as fall within the true spirit and scope of these teachings.

What is claimed is:

1. A system comprising:

a processor and a memory;

a raw log;

a link map that associates files, offsets, and lengths that correspond to a component of a stream-enabled application with a feature of the stream-enabled application;

a virtual execution environment, wherein, in operation:

the stream-enabled application is a virtually installed application executing in the virtual execution environment,

an agent process for the virtually installed application requests resources as a part of a plurality of sessions, the virtual execution environment:

17

associates resource requests of the plurality of sessions with a block to the virtually installed application,

associates the component of the stream-enabled application with the resource requests of the plurality of sessions,

generates a statistic comprising a frequency of usage of the component associated with the resource requests of the plurality of sessions in relation to the block, within at least one demographic group defined by a factor, the frequency depending on the association of the component with the resource requests of the plurality of sessions from the at least one demographic group, the statistic further comprising a percent coverage of the feature of the stream-enabled application by the component, and logs an identifier of the block (block ID) in association with a session of the plurality of sessions into the raw log;

an aggregator, wherein, in operation, the aggregator receives the raw log including the block ID, collates the block ID with a unique session identifier (unique session ID) associated with the session, and formats the block ID and the unique session ID into a formatted log, thereby logging the statistic into the formatted log.

2. The system of claim 1 wherein the raw log includes block requests received in accordance with a delta transmission protocol.

3. The system of claim 1 wherein the virtual execution environment executes on a streaming client of a streaming system, and the streaming client buffers the block ID and then transfers the block ID to a streaming server.

4. The system of claim 1 further comprising a component statistics engine wherein, in operation, the component statistics engine uses the formatted log to generate a report of popularity of the block within the at least one demographic group.

5. The system of claim 1 wherein the formatted log is formatted using a logical expression of a block-session grid.

6. The system of claim 1 wherein, in operation, the aggregator receives aggregation preferences and provides the formatted log in accordance with the aggregation preferences.

7. An apparatus comprising:
a processor and a memory;

18

a compilation tool, wherein, in operation, the compilation tool associates files, offsets, and lengths that correspond to a component of a stream-enabled application with a feature of the stream-enabled application based on a link map;

a component statistics and determination module, wherein, in operation, the component statistics and determination module:

receives block associations and a formatted log file comprising a block identifier (block ID) of a block associated with resource requests by an agent process in a plurality of sessions of the stream-enabled application executed as a virtually installed application,

receives a unique session identifier (session ID) associated with a unique session in which the agent process placed the resource requests, the block associated with the resource requests being associated with the component of the stream-enabled application,

generates a statistic comprising a frequency of usage of the component of the stream-enabled application in a plurality of sessions, within at least one demographic group defined by a factor, the frequency depending on an association of the component with the resource requests by the agent process in the plurality of sessions for the at least one demographic group, the statistic further comprising a percentage coverage of the feature of the stream-enabled application by the component, and

analyzes the block associations and formatted log file;

a report generation module, wherein, in operation, the report generation module receives report preferences and analysis from the component statistics and determination module and produces one or more reports, thereby logging the statistic into the one or more reports.

8. The system of claim 7 wherein the statistic comprises a popularity of the block within the at least one demographic group.

9. The system of claim 7 wherein the link map includes feature associations that are used to identify popularity of a feature, and the popularity is provided in the one or more reports.

10. The system of claim 7 wherein the statistic comprises a percent coverage of the stream-enabled application.

* * * * *