



(51) International Patent Classification:

H02K 33/02 (2006.01) A61C 17/34 (2006.01)

H02K 7/04 (2006.01)

(21) International Application Number:

PCT/IB2020/054131

(22) International Filing Date:

01 May 2020 (01.05.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

19172245.3 02 May 2019 (02.05.2019) EP

20163232.0 16 March 2020 (16.03.2020) EP

(71) Applicant: BRAUN GMBH [DE/DE]; Frankfurter Strasse 145, 61476 Kronberg (DE).

(72) Inventors: SCHAEFER, Norbert; Frankfurter Strasse 145, 61476 Kronberg (DE). SCHOBER, Uwe; Frankfurter Strasse 145, 61476 Kronberg (DE). SCHAEFER, Robert; Frankfurter Strasse 145, 61476 Kronberg (DE). PASCHOLD, Matthias; Frankfurter Strasse 145, 61476 Kronberg (DE). SCHWARZ, Tobias; Frankfurter Strasse 145, 61476 Kronberg (DE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA,

(54) Title: PERSONAL HYGIENE DEVICE




Fig. 1

(57) Abstract: The present disclosure is concerned with a personal hygiene device that extends in a 3-dimensional space that is spanned by a x-y-z coordinate system, having a drive unit having a support, a stator fixedly mounted at the support, an armature that is spring-mounted at the support for driven linear oscillating motion along a first longitudinal direction that is parallel to or coincides with the x-axis of the x-y-z coordinate system, the armature having a center of gravity located in rest at a coordinate $[x_a; y_a; z_a]$, and a drive shaft fixedly coupled with the armature, the drive shaft having a center of gravity located in rest at a coordinate $[x_d; y_d; z_d]$, a first treatment head assembly detachably connected to the drive shaft, the first treatment assembly having a center of gravity located in rest at a coordinate $[x_{t1}; y_{t1}; z_{t1}]$, and a secondary mass element

SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR,
TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

spring-mounted at the support for essentially linear oscillating motion along the first longitudinal direction, the secondary mass element having a center of gravity located in rest at a coordinate $[x_m; y_m; z_m]$, wherein at least the coordinate $[x_a; y_a; z_a]$ of the center of gravity of the armature has an offset in at least one of the y-direction and z-direction with respect to the coordinate $[x_d; y_d; z_d]$ of the center of gravity of the drive-shaft or with respect to the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the first treatment head assembly, i.e. $y_a \neq y_d$ and/or $y_a \neq y_{t1}$ and/or $z_a \neq z_d$ and/or $z_a \neq z_{t1}$, and the secondary mass element is designed such that the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element is aligned with the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity of the drive shaft, the first treatment head assembly and the armature in the at least one offset direction, i.e. $y_m = y_j$ and $z_m = z_j$, so that a line connecting the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element and the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity is parallel to or coincides with the x-axis.

PERSONAL HYGIENE DEVICE

FIELD OF THE INVENTION

The present disclosure is concerned with personal hygiene devices comprising a drive unit
5 having a stator-armature assembly where the armature is spring mounted at a support and a
secondary mass element that is spring mounted at the support.

BACKGROUND OF THE INVENTION

It is generally known that a personal hygiene device such as an electric toothbrush can be driven
10 by a resonant motor comprising a stator and an armature that is driven into a reciprocating
motion and is forced into its rest position by a restoring force (which restoring force may
typically be provided by at least one resilient element such as a leaf spring). Various designs of
such a resonant motor are known to the skilled person. The resonant motor may drive a drive
shaft into a linear reciprocating motion. The personal hygiene device may be equipped with a
15 secondary spring-mass resonator that is arranged to cancel vibrations that are produced by the
reciprocating armature of the resonant motor by generating a counter-cyclic motion and thus
generating vibrations having about the same amplitude, but a phase shifted by 180 degrees.
Document WO 2014/009916 A2 discloses one possible design of such a resonant motor.

20 There is a general need to optimize the vibrational behavior of personal hygiene devices
comprising a drive with a moving armature and a secondary mass element for cancelling the
vibrations generated by the moving armature.

SUMMARY OF THE INVENTION

In accordance with at least one aspect, a personal hygiene device, extending in a 3-dimensional
space that is spanned by a x-y-z coordinate system, comprising a drive unit having a support, a
stator fixedly mounted at the support, an armature that is spring-mounted at the support for driven
linear oscillating motion along a first longitudinal direction that is parallel to or coincides with the
x-axis of the x-y-z coordinate system, the armature having a center of gravity located in rest at a
coordinate $[x_a; y_a; z_a]$, and a drive shaft fixedly coupled with the armature, the drive shaft having a
center of gravity located in rest at a coordinate $[x_d; y_d; z_d]$, a first treatment head assembly
detachably connected to the drive shaft, the first treatment assembly having a center of gravity
located in rest at a coordinate $[x_{t1}; y_{t1}; z_{t1}]$, and a secondary mass element spring-mounted at the
support for essentially linear oscillating motion along the first longitudinal direction, the secondary

mass element having a center of gravity located in rest at a coordinate $[x_m; y_m; z_m]$, wherein at least the coordinate $[x_a; y_a; z_a]$ of the center of gravity of the armature has an offset in at least one of the y-direction and z-direction with respect to the coordinate $[x_d; y_d; z_d]$ of the center of gravity of the drive-shaft or with respect to the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the first treatment head assembly, i.e. $y_a \neq y_d$ and/or $y_a \neq y_{t1}$ and/or $z_a \neq z_d$ and/or $z_a \neq z_{t1}$, and the secondary mass element is designed such that the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element is aligned with the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity of the drive shaft, the first treatment head assembly and the armature in the at least one offset direction, i.e. $y_m = y_j$ and $z_m = z_j$, so that a line connecting the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element and the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity is parallel to or coincides with the x-axis.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure will be further elucidated by a detailed description of example embodiments and by reference to figures. In the figures

5

- Fig. 1 is a schematic depiction of a personal care device realized as an electric toothbrush;
- Fig. 2 is a cross section through an example personal hygiene device realized as an electric toothbrush;
- 10 Fig. 3 is a schematic depiction of the coupled masses of an example personal hygiene device as used for simulation;
- Fig. 4A first simulated results of vibration amplitudes at measurement points MP1, MP2, and MP3 as shown in Fig. 3; and
- Fig. 4B second simulated results of vibration amplitudes at measurement points MP1,
- 15 MP2, and MP3 as shown in Fig. 3.

DETAILED DESCRIPTION OF THE INVENTION

In the context of the present description “personal hygiene” shall mean the nurture (or care) of the skin and of its adnexa (i.e. hairs and nails) and of the teeth and the oral cavity (including the tongue, the gums etc.), where the aim is on the one hand the prevention of illnesses and the maintenance and strengthening of health (“hygiene”) and on the other hand the cosmetic treatment and improvement of the appearance of the skin and its adnexa. It shall include the maintenance and strengthening of wellbeing. This includes skin care, hair care, and oral care as

20

well as nail care. This further includes other grooming activities such as beard care, shaving, and depilation. A “personal hygiene device” thus means any device for performing such nurturing or grooming activity, e.g. (cosmetic) skin treatment devices such as skin massage devices or skin brushes; wet razors; electric shavers or trimmers; electric epilators; and oral care devices such as manual or electric toothbrushes, (electric) flossers, (electric) irrigators, (electric) tongue cleaners, or (electric) gum massagers. This shall not exclude that the proposed personal hygiene device may have a more pronounced benefit in one or several of these nurturing or device areas than in one or several other of these areas.

- 10 A personal hygiene device as proposed comprises a treatment head for providing a hygiene treatment. An electric toothbrush is one example of an electric personal hygiene device, particularly an example of the group of electric oral care devices.

- 15 In accordance with the present disclosure, the personal hygiene device has a drive unit that comprises a support, a stator fixedly mounted at the support and an armature that is spring-mounted at the support for driven linear oscillating motion along a first longitudinal direction that is parallel to or coincides with the x-axis of the x-y-z coordinate system. The armature has a center of gravity located in rest at a coordinate of the x-y-z coordinate system that is denoted by $[x_a; y_a; z_a]$, where x_a is the x-component, y_a is the y-component and z_a is the z-component, which denotation will be used in the following. The armature may be mounted at the support by at least one planar leaf spring, in particular by at least two planar leaf springs, which planar leaf springs extend at rest in a plane parallel to the y-z plane of the x-y-z coordinate system.

In accordance with the present disclosure, the personal hygiene device has a drive shaft that is fixedly coupled with the armature, the drive shaft has a center of gravity located in rest at a coordinate $[x_d; y_d; z_d]$. The personal hygiene device further has a first treatment head assembly that is detachably connected to the drive shaft. The first treatment assembly has a center of gravity located in rest at a coordinate $[x_{t1}; y_{t1}; z_{t1}]$. The personal hygiene device also comprises a secondary mass element that is spring-mounted at the support for linear oscillating motion along the first longitudinal direction, the secondary mass element having a center of gravity located in rest at a coordinate $[x_m; y_m; z_m]$. The secondary mass element may be mounted at the support by at least one planar leaf spring, in particular by at least two planar leaf springs, which planar leaf springs extend at rest in a plane parallel to the y-z plane of the x-y-z coordinate system.

In accordance with the present disclosure, at least the coordinate $[x_a; y_a; z_a]$ of the center of gravity of the armature has an offset in at least one of the y-direction and z-direction with respect to the coordinate $[x_d; y_d; z_d]$ of the center of gravity of the drive-shaft or with respect to the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the first treatment head assembly, i.e. $y_a \neq y_d$ and/or $y_a \neq y_{t1}$ and/or $z_a \neq z_d$ and/or $z_a \neq z_{t1}$. The secondary mass element is designed such that the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element is aligned with the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity of the drive shaft, the first treatment head assembly and the armature in the at least one offset direction, i.e. $y_m = y_j$ and $z_m = z_j$, so that a line connecting the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element and the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity is parallel to or coincides with the x-axis.

It is known that a system as described leads to low vibrations on the outer surface of the handle that is grasped by a user as the forces transmitted by the mounting spring or springs of the moving armature (together with the masses attached to the armature) and by the mountings spring or springs of the counter-oscillating secondary mass element to the support cancel each other, which was in particular achieved by making those masses close to each other or even making these masses identical and in particular adapting the mounting springs so that the resonance frequency of the spring-mounted secondary mass element is as close to the drive frequency as possible. WO 2014/009916 A2 discusses this in general. But it was found that a design as shown and discussed in WO 2014/009916 A2 still leads to remaining vibrations that a user can feel when holding the handle. It was found that such remaining vibrations can be associated with an offset between the joint center of gravity of armature, drive shaft and first treatment head assembly in the y-z plane and the center of gravity of the secondary mass element in the y-z plane, i.e. an offset in at least one of the y or z directions. In a design following the general description of WO 2014/009916 A2, an offset in z-direction is triggered due to the particular shape of the armature. Aligning the centers of gravity such that their y-components and their z-components have the same value, as is proposed herein, reduced the remaining vibrations. This means that aligning the centers of gravity such that the line connecting the two centers of gravity is parallel to (or coinciding with) the x-axis of the above defined x-y-z coordinate system reduces the vibrations felt at the handle – simulation results are discussed further below in connection with Figs. 4A and 4B.

The personal hygiene device as proposed may comprise a handle section having a handle housing that can be grasped by a user's hand. The support of the drive unit may itself be pivot mounted with respect to the handle housing. A resilient element such as a spring element may provide a

restoring force against any force that pivots the support around the pivot axis. The support may be coupled with a force sensor enabling to measure the force that acts on the support to pivot it. The personal hygiene device may comprise a replacement brush head that either itself forms a treatment head or that has a treatment head housing with respect to which the treatment head is mounted for driven motion. The treatment head housing may then be fixedly coupled with the support. The treatment head may be mechanically coupled with a motion transmitter to form a treatment head assembly.

The drive unit may comprise a periodic drive signal (e.g. an alternating current) that is used to drive the armature into a reciprocating motion. The drive frequency of the periodic drive signal may be chosen to lie in a range of between 100 Hz and 200 Hz, in particular in a range of between 120 Hz and 170 Hz, further in particular in a range of between 140 Hz and 150 Hz.

The armature may integrally comprise the drive shaft or the drive shaft may be detachably coupled with the armature. The drive shaft is used to transmit the motion provided by the armature to the driven treatment head. The drive shaft may be magnetically coupled with the treatment head assembly comprising the treatment head. The armature (together with any other masses connected with the armature) forms a resonant spring-mass system by virtue of the spring or springs by which the armature is mounted at the support. The armature may comprise at least one permanent magnet and the stator may comprise a coil that receives an alternating current at a drive frequency, where the drive frequency is chosen to lie at or close to the resonant frequency of the armature-spring system. The secondary mass system that is spring mounted at the support forms a further resonant spring-mass system that may be considered as being independent from the armature-spring system if the support can be assumed to be spatially fixed. The drive frequency may be chosen to lie at or as close as possible to the resonance frequency of the secondary mass element-spring system. The secondary mass element-spring system is arranged to be excited into a linear reciprocating motion by the vibrations of the support generated by the armature-spring system. The linear motion of the secondary mass element is phase shifted by 180 degrees with respect to the armature motion. The secondary mass element may be made from stacked metal sheets.

The personal hygiene device and the drive unit extend in three-dimensional space, which 3D space can be spanned by a Cartesian coordinate system so that each point in space can be defined by coordinates $[x; y; z]$. At rest, the various elements of the drive unit, in particular the armature, the secondary mass element, the drive shaft, and the treatment head assembly each have a center

of gravity that thus can be determined by respective coordinates as was already discussed, e.g. coordinate $[x_a; y_a; z_a]$ denotes the center of gravity of the armature, coordinate $[x_m; y_m; z_m]$ denotes the center of gravity of the secondary mass element, coordinate $[x_d; y_d; z_d]$ denotes the center of gravity of the drive shaft, and coordinate $[x_{t1}; y_{t1}; z_{t1}]$ denotes the center of gravity of the first treatment head assembly. Here, “first” is used to differentiate the first treatment head assembly being part of the personal hygiene device from a potential further (second) treatment head assembly. A personal hygiene kit may then comprise a personal hygiene device and at least one further replacement head comprising a second treatment head assembly. The mass and the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the second treatment head assembly may be chosen such that the two different replacement heads generate different vibration characteristics of the personal hygiene device.

Fig. 1 is a depiction of an example personal hygiene device 1 realized as an electric toothbrush. The personal hygiene device 1 comprises a handle section 20 and a first replacement head 10 that is detachably mounted at the handle section 20. The first replacement head 10 may comprise a first treatment head 11 mounted at a first treatment head housing 12 for driven motion relative to the first treatment head housing 12. A first motion transmitter may be coupled with the first treatment head 11 and may be disposed in a hollow of the first treatment head housing 12. The first treatment head 11 and the first motion transmitter together may then form a first treatment head assembly as will be discussed in more detail further below. The first replacement head 10 may be detached and replaced by a new, essentially identical replacement head when the first replacement head 10 is worn out or the first replacement head 10 may be complemented by at least a second replacement head that provides a different treatment or that is intended for usage by a different user. In the present case an electric toothbrush is shown and the first replacement head 10 is realized as a brush head that provides a first cleaning treatment of the teeth. A second brush head (i.e. second replacement head) may be provided that is different to the first brush head and that provides a different treatment effect, e.g. the second brush head may be structured for better tooth polishing effect or for a better gum massaging effect than the first brush head.

Fig. 2 is a cross sectional view of an example personal hygiene device 1A in accordance with the present disclosure, which personal hygiene device extends in Euclidian 3D space spanned by a Cartesian x-y-z coordinate system allowing to define absolute positions in space and relative distances. The Cartesian coordinate system is used here as an example of all possible coordinate systems that can be used to span the Euclidian 3D space. The personal hygiene device 1A is

realized as an electric toothbrush, which shall be considered as a non-limiting example, and comprises a handle section 20A and a first replacement head 10A. The first replacement head 10A comprises a first treatment head 110A and a first motion transmitter 111A that together form a first treatment head assembly 120A. The first treatment head 110A here comprises a carrier
5 element 1102A on which at least one treatment element 1101A is mounted, where in the shown example a plurality of filament tufts are mounted on the carrier element 1102A. The first treatment head 110A is here mounted at the first treatment housing 112A for driven oscillatory rotation M2 around a rotation axis R that is defined by an axle 1103A. The first motion transmitter 111A comprises a coupling portion 113A that is pivotably connected with the rest of
10 the first motion transmitter 111A. The first treatment head 110A is mounted at a first treatment head housing 112A. The first treatment head housing 112A is detachably connected with a treatment head adapter 235A of the handle section 20A.

The handle section 20A comprises a handle housing 220A and a support 210A that is pivotably
15 mounted with respect to the handle housing 220A so that the support 210A can pivot around a pivot axis P that is defined by an axle 211A. The support 210A carries a drive unit 230A that comprises a stator 231A fixedly mounted at the support 210A, an armature 232A and a secondary mass element 233A that are each spring mounted at the support 210A. The stator 231A may
20 comprise a coil and the armature 232A may comprise at least one permanent magnet as is generally known in the art so that the armature 232A can be driven into a linear reciprocating motion M1 when an alternating current is provided to the coil. The drive frequency of the alternating current may be chosen to be in a range of between 100 Hz and 200Hz. A drive shaft
234A is here fixedly connected with the armature 232A, which drive shaft extends along a longitudinal axis L that coincides with or is parallel to the x-axis of the Cartesian x-y-z
25 coordinate system (in the shown example, the longitudinal axis L is parallel to the x-axis of the shown Euclidian coordinate system). The front end of the drive shaft 234A may comprise a permanent magnet for coupling with another permanent magnet or magnetizable metal element provided at the coupling portion 113A of the first motion transmitter 111A. The treatment head
adapter 235A forms a front-end portion of the support 210A so that an external force F having a
30 component in positive z-direction applied at the first treatment head 110A leads to a pivoting motion of the support 210A around the pivot axis P. The support 210A may be spring mounted with respect to the handle housing 220A, so that a restoring spring force will act to bring the support 210A back into its rest position.

The personal hygiene device 1A may comprise a chassis element 240A that may carry an energy source 241A such as a battery or a rechargeable accumulator and a PCB 242A comprising the control electronics and potentially at least one sensor for, e.g., measuring the deflection of the support 210A relative to the handle housing 220A. The support 210A may in particular be

5 pivotably mounted at the chassis element 240A and the chassis element 240A may be fixedly secured at the handle housing 220A so that the chassis element 240A may be considered as a portion of the handle housing 220A.

The armature 232A has a center of gravity that has at rest coordinates $[x_a; y_a; z_a]$ (with respect to the centers of gravity it is also referred to Fig. 3). As can be seen in the shown embodiment, the armature 232A is offset from the longitudinal axis L. Hence, the z-coordinate z_a is in the shown embodiment offset from the longitudinal axis L, where the z-coordinate of the longitudinal axis is denoted as z_L . The secondary mass element 233A has a center of gravity that has at rest coordinates $[x_m; y_m; z_m]$. A skilled person may tend to select the positioning of the secondary

15 mass element such that the z-coordinate of the center of gravity of the secondary mass element 233A coincides with the longitudinal axis, $z_m = z_L$, in particular for reasons of sensible use of available construction volume. Further, the drive shaft 234A has a center of gravity that has at rest coordinates $[x_d; y_d; z_d]$. As the drive shaft 234A extends along the longitudinal axis L, the z-coordinate of the drive shaft 234A is in the shown example coinciding with the z-coordinate of the longitudinal axis L, i.e. $z_d = z_L$. And the first treatment head assembly 120A has a center of gravity that has in rest coordinates $[x_{t1}; y_{t1}; z_{t1}]$. Due to the particular design of the shown example first treatment head assembly 120A, the z-coordinate and the y-coordinate of the center of gravity of the first treatment head assembly 120A are offset from the longitudinal axis L.

20

25 In operation, the armature 233A is driven into a reciprocating longitudinal motion M1 and the armature 233A moves together with the drive shaft 234A and the first treatment head assembly 120A. Due to the general principle of the preservation of impulse, the impulse of the driven moving parts is in opposite direction transferred to the support 210A. The spring-mounted secondary mass element 233A will then be excited into a reciprocating linear motion M1' that is

30 shifted in phase by 180 degrees by the forces acting on the support. The mass M_a of the armature 233A, the mass M_d of the drive shaft 234A and the mass M_{t1} of the first treatment head assembly 120A add together to the joint mass M_j , $M_j = M_a + M_d + M_{t1}$, of the driven parts. It may be desirable to choose the mass M_m of the secondary mass element 233A so that it is essentially identical with the joint mass M_j of the driven moving parts and the spring constant of the spring

or springs mounting the secondary mass element 233A to the support may be chosen such that the secondary mass element 233A moves essentially in resonance at the drive frequency at which the armature 232A is driven into motion. By such a design, the forces transferred by the moving parts to the support 210A and from the support 210A to the handle housing 220A essentially
 5 cancel each other. But it had been found that some perceivable vibrations are still occurring at the handle housing 220B as was already generally discussed in a previous paragraph.

Fig. 3 shows a multibody block diagram indicating the various coupled masses and their motion constraints, joints and the applied forces that were used in a simulation program to understand the
 10 vibrations (i.e. amplitudes). m_1 is the mass representing the support 210B and the stator 231B; m_2 is the mass of the secondary mass element 233B that is spring mounted at the support 210B and that is constraint for linear motion due to the rigidity of the springs in the directions perpendicular to the longitudinal motion direction; m_3 is the mass of the armature 233B and of the drive shaft 234B that are spring mounted at the support 210B and that are likewise constraint
 15 into a linear motion, where further a periodically alternating force acts between the stator 231B and the armature 233b to drive the armature 233B into motion; m_{13} is the mass of the coupling portion 113B of the first treatment head assembly 120B, where it is assumed that the coupling portion 113B is fixedly connected with the drive shaft 234B; m_{11} is the mass of the rest of the motion transmitter 111B that is pivotably hinged at the coupling portion 113B; m_{12} is the mass
 20 of the first treatment head 110B that is pivotably mounted at the first treatment head housing 112B and the motion transmitter 111B is pivotably mounted at the first treatment head 110B; and finally m_{10} is the mass of the first treatment head housing 112B that is assumed to be fixedly connected with the support 210B. MP1, MP2, and MP3 are measurement points at which the resulting vibrations of the shown simplified model of the interacting parts are investigated. As is
 25 schematically indicated in Fig. 3, at rest the coordinate of the center of gravity of the armature 232B is $[x_a; y_a; z_a]$, the coordinate of the center of gravity of the drive shaft 234B is $[x_d; y_d; z_d]$, the coordinate of the center of gravity of the first treatment head assembly 120B is $[x_{t1}; y_{t1}; z_{t1}]$, and the coordinate of the center of gravity of the secondary mass element 233B is $[x_m; y_m; z_m]$. The Simscape™ Multibody™ software available from MathWorks, Natick, MA, USA can be
 30 used for such a simulation.

Figs. 4A and 4B show the simulation results of the effect of shifting the z coordinate and the y coordinate, respectively, of the center of gravity of the secondary mass element 233B of the discussed arrangement on the vibration amplitude A_v , where in Fig. 4A the vibration amplitudes

in z-direction are shown and in Fig. 4B the vibration amplitudes in y-direction are shown. In Figs. 4A and 4B, $z = 0$ and $y = 0$ represent a position on the longitudinal center axis of the drive shaft 234B. For the simulation shown in Fig. 4A, the y coordinate of the secondary mass element 233B was fixed at $y_m = 0$. For the simulation shown in Fig. 4B, the z coordinate of the secondary mass element 233B was fixed at $z_m = 0$. The vibration amplitudes show a minimum for a position of the center of gravity of the secondary mass element that is offset from the longitudinal axis. The effect is more prominent for the offset in z-direction and also more prominent for measurement point MP3 at the distal end tip of the first treatment head housing. In the simulations, the vibration amplitude A_v can be reduced to a level of well below 0.005 mm.

Hence, while the counter-oscillating masses M_m and M_j were already coinciding in an example as discussed in WO 2014/009916 A2 and while the motion of the secondary mass element 233B, the armature 232B, and of the drive shaft 234B are essentially confined to a linear motion, the vibrations that are generated by the moving masses at the support and at the first treatment head housing can be further reduced by optimizing the position of the center of gravity of the secondary mass element 233B. If a joint center of gravity of the armature 232B, the drive shaft 234B and of the first treatment head assembly 120B has at rest a coordinate $[x_j; y_j; z_j]$, then the coordinate $[x_m; y_m; z_m]$ of the coordinate of the center of gravity of the secondary mass element 233B at rest is best chosen to coincide with the coordinate of the joint center of gravity in y and z direction, i.e. $y_m = y_j$ and $z_m = z_j$.

The user of the personal hygiene device may be irritated when the personal hygiene device has only a very low perceivable vibration amplitude in operation. Thus, in some embodiments, at least one of the z or y coordinates of the center of gravity of the secondary mass element is misaligned by a distance in the range of between 1 μm and 200 μm , in particular of between 5 μm and 100 μm , with respect to the z coordinate or the y coordinate of the joint center of gravity. By such a measure, the user may experience a low vibration amplitude, which is still perceivable in a reassuring manner.

In some embodiments, the personal hygiene device comprises a second replaceable head. Once attached, the coordinate $[x_{t2}; y_{t2}; z_{t2}]$ of the center of gravity of the second replacement head is different in at least one of the y and z coordinates from the respective center of gravity $[x_{t1}; y_{t1}; z_{t1}]$ of the first replacement head. This allows to control the vibration amplitude felt by the user. E.g. in case the first replacement head has a regular cleaning function and the second

replacement head has a function that a user would relate to a higher power, e.g. a polishing function, then the higher vibration amplitude may convey the feeling of a higher power by means of a higher vibration amplitude. A similar effect can be achieved by different masses of the first and second treatment head assemblies. At least one of the two discussed measures may be used.

5

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as “40 mm” is intended to mean “about 40 mm.”

CLAIMS

What is claimed is:

1. A personal hygiene device, extending in a 3-dimensional space that is spanned by a x-y-z coordinate system, comprising:
 - a drive unit having
 - a support;
 - a stator fixedly mounted at the support;
 - an armature that is spring-mounted at the support for driven linear oscillating motion along a first longitudinal direction that is parallel to or coincides with the x-axis of the x-y-z coordinate system, the armature having a center of gravity located in rest at a coordinate $[x_a; y_a; z_a]$; and
 - a drive shaft fixedly coupled with the armature, the drive shaft having a center of gravity located in rest at a coordinate $[x_d; y_d; z_d]$;
 - a first treatment head assembly detachably connected to the drive shaft, the first treatment assembly having a center of gravity located in rest at a coordinate $[x_{t1}; y_{t1}; z_{t1}]$; and
 - a secondary mass element spring-mounted at the support for essentially linear oscillating motion along the first longitudinal direction, the secondary mass element having a center of gravity located in rest at a coordinate $[x_m; y_m; z_m]$;

wherein at least the coordinate $[x_a; y_a; z_a]$ of the center of gravity of the armature has an offset in at least one of the y-direction and z-direction with respect to the coordinate $[x_d; y_d; z_d]$ of the center of gravity of the drive-shaft or with respect to the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the first treatment head assembly, i.e. $y_a \neq y_d$ and/or $y_a \neq y_{t1}$ and/or $z_a \neq z_d$ and/or $z_a \neq z_{t1}$, and the secondary mass element is designed such that the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element is aligned with the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity of the drive shaft, the first treatment head assembly and the armature in the at least one offset direction, i.e. $y_m = y_j$ and $z_m = z_j$, so that a line connecting the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element and the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity is parallel to or coincides with the x-axis.
2. The personal hygiene device in accordance with claim 1, wherein the coordinate $[x_a; y_a; z_a]$ of the center of gravity of the armature has an offset in the y direction and in the z-direction with respect to the coordinate $[x_d; y_d; z_d]$ of the center of gravity of the drive-shaft, i.e. $y_a \neq y_d$ and $z_a \neq z_d$, or with respect to the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the first treatment head assembly, i.e. $y_a \neq y_{t1}$ and $z_a \neq z_{t1}$, and the secondary mass element is designed such that

the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element is aligned with the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity of the drive shaft, the first treatment head assembly and the armature in the y-direction and the z-direction, i.e. $y_m = y_j$ and $z_m = z_j$ so that a line connecting the coordinate $[x_m; y_m; z_m]$ of the center of gravity of the secondary mass element and the coordinate $[x_j; y_j; z_j]$ of the joint center of gravity is parallel to or coincides with the x-axis.

3. The personal hygiene device in accordance with claim 1 or claim 2, having a handle housing that can be grasped by a hand of a user and a first treatment head housing that is detachably attached to an attachment portion of the support.
4. The personal hygiene device in accordance with claim 3, wherein the support of the drive unit is mounted for a pivoting motion around a pivot axis with respect to the handle housing such that the pivot axis is generally parallel to the y-axis of the x-y-z coordinate system and a resilient element is arranged between the handle housing and the support to provide a restoring force against the pivoting motion and wherein a pressure or force applied at the first treatment head housing having a pressure or force component along a direction parallel to the z-axis of the x-y-z coordinate system leads to a pivoting motion of the support around the pivot axis against the restoring force of the resilient element.
5. The personal hygiene device in accordance with claim 4, wherein the support is coupled with a pressure sensor or force sensor for measuring the pressure or force applied at the first treatment head housing based on the deflection of the support with respect to the handle housing.
6. The personal hygiene device in accordance with one of claims 3 to 5, wherein the first treatment head assembly is movably mounted at the first treatment head housing and the first treatment head assembly and the first treatment head housing together form a first replacement head.
7. The personal hygiene device in accordance with claim 6, wherein the first treatment head assembly comprises a first motion transmitter that is detachably coupled with the drive shaft and with a first treatment head that is movably mounted at the first treatment head housing for driven oscillatory rotation around a rotation axis that is parallel to the z-direction.
8. The personal hygiene device in accordance with claim 7, wherein the motion transmitter and the drive shaft are coupled by a magnetic coupling.

9. The personal hygiene device in accordance with one of claims 6 to 8, wherein the drive unit is arranged to drive the first treatment head assembly with a frequency in the range of between 100 Hz and 200 Hz, in particular with a frequency in the range of between 120 Hz and 170 Hz, further in particular with a frequency in the range of between 140 Hz and 150 Hz.
10. The personal hygiene device in accordance with one of claims 1 to 9, wherein the weight of the support together with all parts mounted at the support and the weight of the handle with all parts mounted to the handle other than the support are designed to have a ratio of 0.2 or below.
11. The personal hygiene device in accordance with one of claims 1 to 10, wherein the alignment of the coordinates in the offset direction has a residual offset in the range of 5 μm to 100 μm .
12. The personal hygiene device in accordance with one of claims 1 to 11, wherein the secondary mass element is made from stacked metal sheets.
13. The personal hygiene device in accordance with one of claims 1 to 11, wherein the armature and the secondary mass element are mounted at the support by leaf springs that each extend at rest in a plane parallel to the y-z plane of the x-y-z coordinate system.
14. A personal hygiene device kit comprising a personal hygiene device in accordance with one of claims 6 to 13 and at least a second replacement head comprising a second treatment head housing and a second treatment head assembly, wherein in the attached state the center of gravity of the second treatment head assembly has a coordinate $[x_{t2}; y_{t2}; z_{t2}]$ that has an offset with respect to the coordinate $[x_{t1}; y_{t1}; z_{t1}]$ of the center of gravity of the first treatment head assembly in at least one of the y-direction or z-direction or where the first treatment head assembly has a weight that is different to the weight of the first treatment head assembly.

1 / 4




Fig. 1




Fig. 2






Fig. 3

4 / 4



INTERNATIONAL SEARCH REPORT

International application No
PCT/IB2020/054131

A. CLASSIFICATION OF SUBJECT MATTER

INV. H02K33/02 H02K7/04 A61C17/34
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

A61C H02K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	W0 2014/009916 A2 (BRAUN GMBH [DE]) 16 January 2014 (2014-01-16) cited in the application page 3, line 1 - line 7; figures 2, 5 page 3, line 33 - page 4, line 7 page 6, line 19 - line 21 page 9, line 31 - page 11, line 8 page 12, line 8 - line 12 page 14, line 13 - line 24 page 16, line 17 - line 20 -----	1-14
A	EP 2 790 309 A1 (PANASONIC CORP [JP]) 15 October 2014 (2014-10-15) paragraph [0021] - paragraph [0034]; figure 3 paragraph [0044] ----- -/--	1-14

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 July 2020

Date of mailing of the international search report

11/08/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Sollinger, Martin

INTERNATIONAL SEARCH REPORT

International application No

PCT/IB2020/054131

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2018/087631 A1 (KRAMP ANDREAS [DE] ET AL) 29 March 2018 (2018-03-29) paragraph [0038]; figure 8 paragraph [0043] -----	4,5
A	US 2017/079421 A1 (TAMMINGA STEPHANUS JACOB GERARDUS [NL] ET AL) 23 March 2017 (2017-03-23) paragraph [0063] -----	14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/IB2020/054131

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
W0 2014009916 A2	16-01-2014	CA 2878546 A1	16-01-2014
		CA 2971892 A1	16-01-2014
		CN 104471848 A	25-03-2015
		CN 104488176 A	01-04-2015
		DK 2873144 T3	26-11-2018
		EP 2685617 A1	15-01-2014
		EP 2873143 A2	20-05-2015
		EP 2873144 A2	20-05-2015
		ES 2681319 T3	12-09-2018
		ES 2693620 T3	13-12-2018
		ES 2693760 T3	13-12-2018
		JP 6030236 B2	24-11-2016
		JP 2015522241 A	03-08-2015
		PL 2685617 T3	31-01-2019
		PL 2873143 T3	31-10-2018
		PL 2873144 T3	28-02-2019
		US 2014015346 A1	16-01-2014
		US 2018019650 A1	18-01-2018
		WO 2014009915 A2	16-01-2014
		WO 2014009916 A2	16-01-2014
-----	-----	-----	-----
EP 2790309 A1	15-10-2014	CN 103959619 A	30-07-2014
		EP 2790309 A1	15-10-2014
		JP 5945814 B2	05-07-2016
		JP 2013118779 A	13-06-2013
		TW 201330463 A	16-07-2013
		WO 2013084438 A1	13-06-2013
-----	-----	-----	-----
US 2018087631 A1	29-03-2018	CA 3034787 A1	05-04-2018
		CN 109789007 A	21-05-2019
		EP 3300685 A1	04-04-2018
		US 2018087631 A1	29-03-2018
		WO 2018060790 A1	05-04-2018
-----	-----	-----	-----
US 2017079421 A1	23-03-2017	CN 106102516 A	09-11-2016
		EP 3119240 A1	25-01-2017
		JP 2017518146 A	06-07-2017
		RU 2016141250 A	23-04-2018
		US 2017079421 A1	23-03-2017
		WO 2015140340 A1	24-09-2015
-----	-----	-----	-----