



(51) International Patent Classification:

*C11D 17/00* (2006.01)    *C11D 1/835* (2006.01)  
*C11D 3/00* (2006.01)    *C11D 1/62* (2006.01)  
*C11D 3/37* (2006.01)

(21) International Application Number:

PCT/US2016/046176

(22) International Filing Date:

9 August 2016 (09.08.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/210,785    27 August 2015 (27.08.2015)    US

(71) Applicant: **S. C. JOHNSON & SON, INC.** [US/US];  
1525 Howe Street, Racine, Wisconsin 53403 (US).

(72) Inventor: **SAINT VICTOR, Marie-Esther**; 985 Skokie  
Ridge Drive, Glencoe, Illinois 60022 (US).

(74) Agents: **CARTER, Charles, G.** et al.; FOLEY & LARD-  
NER LLP, 3000 K. Street N.W., Suite 600, Washington,  
District of Columbia 20007-5109 (US).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,  
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,  
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,  
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,  
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,  
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,  
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,  
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,  
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,  
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,  
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,  
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,  
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,  
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, KM, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a  
patent (Rule 4.17(ii))

Published:

— with international search report (Art. 21(3))

(54) Title: CLEANING GEL WITH GLYCINE BETAINE AMIDE



(57) Abstract: Cleaning compositions, which commonly are self-adherent gels, are provided. The cleaning compositions include (a) adhesion promoter, (b) glycine betaine amide, and (c) water. The glycine betaine amide is a compound of formula (I); where R is an aliphatic group having 8 to 22 carbon atoms and X represents an inorganic or organic anion. The adhesion promoter includes at least one compound including one or more polyalkoxy groups. The adhesion promoter may also include polysaccharide and/or synthetic polymer resin. Gel forms of the cleaning compositions typically have a gel melt temperature of at least about 55 °C and a viscosity at 25 °C of at least about 150,000 cP.



WO 2017/034793 A1


## CLEANING GEL WITH GLYCINE BETAINE AMIDE

### BACKGROUND

[0001] It would be advantageous to have cleaning compositions, which may self-adhere to a hard surface, such as a toilet bowl or shower. In particular, it may be desirable to have such compositions in the form of a gel, in some instances with a high “hardness” property allowing them to be handled easily by a consumer without significant deformation. It may also be desirable for such gels to have a relatively low gel melt temperature, in order to facilitate processing of the gel composition during manufacturing. Additionally, such compositions may advantageously be transparent, have good foaming properties, and/or be compatible with a wide range of additional ingredients such as fragrance, dyes, surface-modifying polymers, antimicrobial agents, and other cleaning agent auxiliary ingredients.

### SUMMARY

[0002] The present application relates generally to the field of cleaning compositions and, in particular, cleaning compositions which may be especially useful for cleaning hard surfaces, such as the inside surface of a toilet bowl. The present application provides cleaning compositions, which may commonly self-adhere upon application to a hard surface, typically a vertical or inclined hard surface. The cleaning compositions include (a) an adhesion promoter, (b) a glycine betaine amide, and (c) water. Often, the adhesion promoter includes at least one compound including one or more polyalkoxy groups and the glycine betaine amide is a compound of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms and X<sup>-</sup> represents an inorganic or organic anion. Commonly, the composition is a gel. In some embodiments, the gel has a gel melt temperature of about 55-80 °C. The gel may have a viscosity at 25 °C of at least about 150,000 cP. In some embodiments, the gel may have a hardness of at least about 150 g.

[0003] The adhesion promoter may include at least one compound including one or more polyalkoxy groups. In some embodiments, the adhesion promoter may include an ethoxylated C<sub>12</sub>-C<sub>30</sub> aliphatic alcohol having an average of about 15 to 100 ethylene oxide units. In some

embodiments, the polyalkoxy group may include ethyleneoxide-propyleneoxide block copolymer. In some embodiments, the adhesion promoter may include polyethylene glycol. In some embodiments, the adhesion promoter may include at least one polysaccharide and/or synthetic polymer resin.


[0004] In some embodiments, the composition may include one or more of mineral oil, polyol humectant, an antimicrobial agent, and a fragrance component. Optionally, the composition may include a surfactant selected from nonionic, anionic, cationic, zwitterionic and/or amphoteric surfactants and mixtures thereof; where such surfactant is a different chemical compound from the adhesion promoter(s).

[0005] In another aspect, the present technology provides a composition for treating a hard surface that includes (a) at least one adhesion promoter, which includes at least one polyalkoxy group; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and (c) water. The composition is typically a gel, which has a gel melt temperature of about 55-80 °C and a viscosity at 25 °C of at least about 150,000 cP.

[0006] In another aspect, the present technology provides a composition for treating a hard surface including (a) at least one adhesion promoter, which includes at least one polyalkoxy group; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and (c) water; wherein the composition is a gel having a hardness of at least about 150 g and a gel melt temperature of about 55-80 °C.

[0007] In some embodiments, it may be advantageous to use a “crude” or “semi-purified” form of the glycine betaine amide. As used herein the term “crude” in reference to the glycine betaine amide is understood to mean the reaction product as formed from the reaction of glycine betaine with an aliphatic alcohol (typically a lower alkanol, such as n-butanol) in the

presence of an acid (typically methanesulfonic acid) and subsequent reaction of the intermediate reaction product (a glycine betaine ester) with an aliphatic amine, i.e., the final reaction product as is, and used without further treatment or purification. The terms “semi-pure” or “semi-purified” in reference to the glycine betaine amide are understood to mean that the reaction product formed is partly purified, i.e., residual glycine betaine, aliphatic alcohol and/or aliphatic amine are at least partially removed to provide a mixture which is still not a pure sample of the glycine betaine amide. Such “crude” or “semi-purified” glycine betaine amide components may be especially useful as surfactants in the present cleaning compositions. The “crude” and “semi-purified” glycine betaine amide components employed in the present cleaning compositions typically include at least 50 wt.% and, commonly, at least 60 wt.% of the glycine betaine amide.

**[0008]** In one embodiment, the cleaning compositions may include a mixture of a glycine betaine amide of Formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms and X<sup>-</sup> represents an inorganic or organic anion, and one or more of Me<sub>3</sub>N<sup>+</sup>-CH<sub>2</sub>-CO<sub>2</sub>H X<sup>-</sup> (“a glycine betaine salt”), an aliphatic amine RNH<sub>2</sub>, where R is as defined, or a salt thereof (e.g., RNH<sub>3</sub><sup>+</sup> X<sup>-</sup>) and an acid HX.

Typically, X<sup>-</sup> represents an alkanesulphonate anion, such as a methanesulphonate anion and the acid HX is an alkanesulphonic acid, such as a methanesulphonic acid. As used herein, the term “glycine betaine” refers to the zwitterionic compound Me<sub>3</sub>N<sup>+</sup>-CH<sub>2</sub>-CO<sub>2</sub>H X<sup>-</sup>, where X<sup>-</sup> represents a methanesulphonate anion. For example, a “crude” or “semi-purified” glycine betaine amide may include a glycine betaine amide of Formula (I) where R is a lauric group and one of more of methanesulphonic acid, lauric amine (RNH<sub>2</sub> where R is a lauric group) and a methanesulphonate salt of lauric amine.

**[0009]** In one aspect, a method for treating a hard surface using the self-adhering cleaning compositions described herein is also provided. The method includes applying a dose of the composition directly on the hard surface to be treated. When water is passed over the self-adhering composition and the hard surface, a portion of the self-adhering composition may be

released into the water that flows over the dose. The portion of the self-adhering composition that is released into the flowing water may provide a wet film on at least a portion of the hard surface. For example, the method may be used to treat the inside of a toilet bowl. A dose of the self-adhering composition may be applied directly on an inside surface of the toilet bowl.

[0010] Further, one of skill in the art will appreciate that, when used in conjunction with a metered dispenser, the dispenser may provide doses of the composition in any volume and/or size that is suitable for the intended application. Similarly, the shape of the dispenser may be any shape that is desired. For example, in an exemplary embodiment, a dispenser used to dispense the present gel composition may include a cylindrical body with the gel contained therein. Such a dispenser may include a guide member to push the gel composition through a dispenser mouth, which may be in any shape that is desirable for the intended purpose. Nonlimiting examples of cross-sectional shapes may be selected from: squares, circles, triangles, ovals, stars, ring-shaped, and the like.

#### DETAILED DESCRIPTION

[0011] In use, some of the compositions of the present technology may be applied directly on the hard surface to be treated, *e.g.* cleaned, such as a toilet bowl, shower or bath enclosure, drain, window, or the like, and self-adheres thereto, commonly through a plurality of flows of water passing over the self-adhering composition and surface, *e.g.* flushes, showers, rinses or the like. Each time water flows over the composition, a portion of the composition is released into the water that flows over the composition. The portion of the composition released onto the water covered surface provides a continuous wet film to the surface to in turn provide for immediate and long term cleaning and/or disinfecting and/or fragrancing or other surface treatment depending on the active agent(s) present in the composition. It is thought that the composition, and thus the active agents of the composition, may spread out from or are delivered from the initial composition placement in direct contact with the surface to coat continuously an extended area on the surface. Typically, the wet film acts as a coating and emanates from the self-adhering composition in all directions, *i.e.*, 360 degrees, from the composition, which includes in a direction against the flow of the rinse water. Motions of the surface of a liquid are coupled with those of the subsurface fluid or fluids, so that movements

of the liquid may produce stresses in the surface and vice versa. The composition may be especially useful in treating the surface of a toilet bowl since it allows for delivery and retention of a desired active agent on a surface above the water line in the bowl as well as below the water line.

[0012] In one aspect, the composition may be a composition for treating a hard surface that includes (a) an adhesion promoter, which comprises at least one compound including one or more polyalkoxy groups; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and X<sup>-</sup> represents an inorganic or organic anion; and (c) water; wherein the composition is self-adhering upon application to a hard surface. In some embodiments, the composition may include at least about 25 wt.% water or more preferably at least about 40 wt.% water.

[0013] Glycine betaine is a natural and inexpensive material derived from sugar beet molasses. The present glycine betaine amides may be derived from natural glycine betaine, providing a green (eco-friendly) and multifunctional material. Particularly of use is a glycine betaine amide of formula (I):



wherein R may be an aliphatic group having 8 to 22 carbon atoms and X<sup>-</sup> represents an inorganic or organic anion. Natural glycine betaine typically includes a methanesulfonate anion as the counterion, X<sup>-</sup>. The glycine betaine amide component of the present compositions may include one or more glycine betaine amides of formula (I). In some embodiments, R may be a linear or branched aliphatic group. In some embodiments, R may be a linear aliphatic group. In some embodiments, R may be an alkyl or an alkenyl group. In some embodiments, R may be an aliphatic group having 10 to 18 carbon atoms. In some embodiments, R may be a linear primary aliphatic group having 8 to 18 carbon atoms, *e.g.* an R group that is part of a fatty amine compound. In another embodiment, R may be an aliphatic group having 10 to 16 carbon atoms, such as the R group present in a C<sub>10</sub>-C<sub>16</sub> linear primary alkyl amine. The R

group may be a C<sub>8</sub>, C<sub>10</sub>, C<sub>12</sub>, C<sub>14</sub>, C<sub>16</sub>, and/or C<sub>18</sub> aliphatic group, e.g., a C<sub>8</sub>, C<sub>10</sub>, C<sub>12</sub>, C<sub>14</sub>, C<sub>16</sub>, and/or C<sub>18</sub> linear primary alkyl and/or alkenyl group. In some embodiments, R may be a C<sub>10</sub>, C<sub>12</sub>, C<sub>14</sub>, and/or C<sub>16</sub> aliphatic group. In some embodiments, R may be a lauric, myristic, palmitic, stearic, and/or oleic group. In certain embodiments, R may include a lauric and/or myristic group. In some embodiments, R may be a C<sub>12</sub> and/or C<sub>14</sub> alkyl and/or alkenyl group. Examples of suitable inorganic or organic anions which may be present as the counterion, X<sup>-</sup>, include halide, carboxylic acid, alkylcarbonate, alkylsulfonate, arylsulfonate, alkylsulfate, sulfate, nitrate, phosphate, and phosphite anions. In some embodiments, X<sup>-</sup> represents Cl<sup>-</sup>, Br<sup>-</sup>, I<sup>-</sup>, CH<sub>3</sub>CO<sub>2</sub><sup>-</sup>, CH<sub>3</sub>CH(OH)CO<sub>2</sub><sup>-</sup>, CH<sub>3</sub>SO<sub>3</sub><sup>-</sup>, ArSO<sub>3</sub><sup>-</sup>, CH<sub>3</sub>C<sub>6</sub>H<sub>4</sub>SO<sub>3</sub><sup>-</sup>, CH<sub>3</sub>OSO<sub>3</sub><sup>-</sup>, H<sub>2</sub>PO<sub>4</sub><sup>-</sup>, and/or H<sub>2</sub>PO<sub>3</sub><sup>-</sup> anion. X<sup>-</sup> may be a halide or alkylsulfonate anion. In some embodiments, X<sup>-</sup> may be a chloride or methanesulfonate anion. As noted above, in glycine betaine amides derived from natural glycine betaine, X<sup>-</sup> may commonly be a methane sulfonate anion.

**[0014]** In many embodiments of the present compositions, the glycine betaine amide may be present in combination with an aliphatic amine (*i.e.*, RNH<sub>2</sub>) and/or salt thereof, wherein R is as defined above. Often, aliphatic amine may be present as an unreacted starting material of the reaction used to produce the glycine betaine amide. In such cases, the “R group” of the aliphatic amine is commonly the same as the “R group” of the glycine betaine amide. The weight ratio of the glycine betaine amide to the aliphatic amine (or salt thereof) in the compositions may be about 20:1 to 1:5, more commonly about 10:1 to 2:1. In some embodiments, the weight ratio of the glycine betaine amide to the aliphatic amine (or salt thereof) may be about 10:1 to 1:2 or about 5:1 to 1:2. In some embodiments, the glycine betaine amide may include a mixture of glycine betaine amides having R groups with 12 to 14 carbon atoms. The composition may also include one or more fatty amines with 12 to 14 carbon atoms and/or salt thereof in combination with such a glycine betaine amide. In some embodiments, the glycine betaine amide component may be an unpurified reaction product, which also includes glycine betaine and/or salt thereof. In some embodiments, such an unpurified reaction product may include methanesulfonic acid and/or salt thereof. In addition to the glycine betaine amide, in some embodiments the composition may further include an aliphatic alcohol, *e.g.* aliphatic C<sub>8</sub>-C<sub>22</sub> alcohol, more typically a C<sub>8</sub>-C<sub>15</sub> alcohol such as a C<sub>8</sub>-C<sub>14</sub>

fatty alcohol. For example, the composition may include a linear aliphatic C<sub>8</sub>-C<sub>18</sub> alcohol in combination with the glycine betaine amide.

[0015] In some embodiments, in addition to the glycine betaine amide, the composition may also include a glycine betaine ester, *e.g.* a glycine betaine ester of formula (II):



wherein X<sup>-</sup> are as defined above. The “R” group may be an aliphatic group having 3 to 22 carbon atoms. In some embodiments, R may be an aliphatic group having 8 to 22 carbon atoms. In many embodiments, the composition may include the glycine betaine ester used as an intermediate to produce the glycine betaine amide, such as a glycine betaine ester produced by reaction of a lower alcohol(s) with glycine betaine (*e.g.*, glycine betaine ester where the R group is an n-butyl group).

[0016] In some embodiments, the composition may be a gel with a hardness about  $\geq 150$  g. In some embodiments, the gel hardness may be at least about 175 g or more preferably at least about 200 g. The compositions may have a gel hardness of at least about 175 g or at least about 185 g. In some embodiments, the gel hardness may range from about 150 g to 300 g. The gel hardness may range from about 175 g to 275 g or more preferably from about 185 g to 250 g. In one embodiment, the gel melt temperature may be at least about 40 °C, at least about 50 °C, or at least about 60 °C. The gel melt temperature may range from about 55 °C to 80 °C, from about 55 °C to 75 °C, or more desirably from about 60 °C to 70 °C. In another embodiment, the gel melt temperature may be no more than about 80 °C, no more than about 75 °C, or no more than about 70 °C. In some embodiments, the cleaning composition may be a gel and have viscosity at 25 °C of at least about 150,000 centipoise (cP). In another embodiment, the gel may have a viscosity from 200,000 to 1,100,000 cP, or about 250,000 to 800,000 cP. The composition may be a gel having a gel melt temperature of about 60-70 °C, and a viscosity at 25 °C of about 300,000 to 600,000 cP.

[0017] The adhesion promoter may include at least one compound including one or more polyalkoxy groups. In some embodiments, the composition may include about 15 wt.% to 40 wt.% of the adhesion promoter or more preferably about 15 wt.% to 35 wt.%. In some

embodiments, the adhesion promoter may include an ethoxylated C<sub>12</sub>-C<sub>30</sub> aliphatic alcohol having an average of about 15 to 100 ethylene oxide units. In some embodiments, the adhesion promoter may include an ethoxylated linear C<sub>14</sub>-C<sub>22</sub> primary aliphatic alcohol having an average of about 15 to 40 ethylene oxide units. In some embodiments, the composition may include about 15 to 40 wt.% of an ethoxylated C<sub>12</sub>-C<sub>30</sub> aliphatic alcohol having an average of about 15 to 100 ethylene oxide units or more preferably about 20 wt.% to about 35 wt.%. The composition may include about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 20-35 ethylene oxide unit.

**[0018]** In some embodiments, the adhesion promoter may include ethyleneoxide-propyleneoxide block copolymer. The ethylene oxide-propylene oxide block copolymer may include an EO-PO block copolymer, an EO-PO-EO block copolymer, a C<sub>8</sub>-C<sub>18</sub> alcohol EO-PO adduct, a C<sub>8</sub>-C<sub>18</sub> alcohol PO-EO adduct, and/or an EO-PO dialkyl ether. The total molecular weight of such ethylene oxide-propylene oxide block copolymers is typically in the range of about 2,000 to 8,000. In some embodiments, the composition may include up to about 20 wt.% or more preferably about 1 to 10 wt.% of the ethyleneoxide-propyleneoxide block copolymer.

**[0019]** In some embodiments, the adhesion promoter may further include one or more of a polysaccharide, polysaccharide derivative, and/or synthetic polymer resin. Nonlimiting examples include cellulose, sodium carboxymethyl cellulose, hydroxyethyl cellulose, hydroxypropyl cellulose, carob bean flour, and starch. In some embodiments, the adhesion promoter may further include a protein such as gelatin. In some embodiments, the composition may include about 0.1 wt.% to 5 wt.%, or more desirably about 0.1 wt.% to 3 wt.% of one or more of a polysaccharide, polysaccharide derivative, and/or synthetic polymer resin.

**[0020]** In some embodiments, the adhesion promoter may include polyethylene glycol. In some embodiments, the composition may include about 0.5 to 5 wt.% polyethylene glycol, about 1 to 5 wt.% polyethylene glycol, or more preferably about 1 to 3 wt.% polyethylene glycol. In some embodiments, the adhesion promoter may include a polywax.

**[0021]** In some embodiments, in addition to a polyalkoxy-based adhesion promoter the present gel compositions may also include an additive(s) which can function as a thickening

and/or co-hardening agent. Suitable examples of such additives include agent(s) having very low solubility in water, typically soluble in water at less than about 0.1 % by weight. Such additives may desirably have a low vapor pressure and include a high flash point hydrocarbon or hydrocarbon mixtures, such as mineral oil, naphthenic oil, or paraffin oil and/or polysiloxanes, such as silicone oils. Other suitable agents include low vapor pressure, high flash point oxygenated hydrocarbons having very low water solubility, such as esters, fatty or synthetic alcohols, or C<sub>10</sub>-C<sub>18</sub> alcohol ethoxylates with an average degree of ethoxylation of no more than about 2 and often about 1 mole of ethylene oxide per mole of alcohol. Examples of oxygenated hydrocarbons, suitable as co-hardening agents include alkyl esters of C<sub>10</sub>-C<sub>22</sub> fatty acids, such as isopropyl myristate, C<sub>10</sub>-C<sub>16</sub> aliphatic alcohols, and C<sub>10</sub>-C<sub>16</sub> alcohol aliphatic alcohol ethoxylates with no more than about 2 mole average degree of ethoxylation, often with no more than about 1 mole average degree of ethoxylation, and typically mono-ethoxylates, such as the mono-ethoxylate of lauryl alcohol. The gel compositions may include about 0.1 to 10 wt.%, commonly about 0.5 to 5 wt.% of the such agent(s). In many instances, the gel composition includes about 0.5 to 3 % of the co-hardening agent(s). The flash point of the co-hardening agent is generally about 90 °C or greater.

[0022] In some embodiments, the present adhesive cleaning composition may include an ethoxylated alcohol, glycine betaine amide, a polymeric alkylene oxide block copolymer, mineral oil, and water. The cleaning compositions may optionally include a polyol humectant, such as glycerin, sorbitol and/or other sugar alcohol. In some embodiments, the composition is a gel having a hardness of at least about 150 g and/or a gel melt temperature of about 50-80 °C. Often the cleaning compositions may include a fragrance component.

[0023] In another aspect, the cleaning composition may be an adhesive cleaning composition that includes a ethoxylated alcohol, which may be an ethoxylated C<sub>12</sub>-C<sub>30</sub> alcohol having an average of 15 to 50 ethylene oxide units; glycine betaine amide; ethyleneoxide-propyleneoxide block copolymer; mineral oil; and water. The composition may be self-adhering upon application to a hard surface.

[0024] In another embodiment, the cleaning composition may be an adhesive cleaning composition that includes about 15-40 wt.% of a first ethoxylated alcohol, which is an

ethoxylated C<sub>14</sub>-C<sub>30</sub> alcohol having an average of 20 to 50 ethylene oxide units; about 0.1-5 wt.% glycine betaine amide; about 1-15 wt.% ethyleneoxide-propyleneoxide block copolymer; about 0.5-10 wt.% mineral oil; and water. The cleaning composition may commonly also include an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of about 5 to 15 ethylene oxide units.

[0025] The present composition may optionally include a surfactant selected from nonionic, anionic, cationic, zwitterionic and/or amphoteric surfactants and mixtures thereof; wherein the surfactant is different from the adhesion promoter. In some embodiments, the composition may include up to about 20 wt.%, about 0.1 wt.% to 15 wt.%, about 0.5 to 10 wt.%, about 1 to about 5 wt.%, or about 10 to 20 wt.% of the surfactant. The surfactants may include one or more alkoxyated alcohols that are different from the adhesion promoter. The alkoxyated alcohol may include one or more ethoxylated alcohols. The ethoxylated alcohol may be linear or branched. In some embodiments, the ethoxylated alcohol may include a C<sub>8</sub>-C<sub>16</sub> alcohol having an average of 5 to 15 ethylene oxide units, more commonly 5 to 12 ethylene oxide units. Typically, when present, the ethoxylated alcohol includes a C<sub>9</sub>-C<sub>15</sub> linear and/or branched alcohol having an average of 5 to 12 ethylene oxide units. A non-limiting example is Genapol® X-100 (available from CLARIANT), which is a branched iso-C<sub>13</sub> alcohol ethoxylate having an average of 10 ethylene oxide units.

[0026] Other ethoxylated alcohols that may be present in the present cleaning compositions as a nonionic surfactant include linear or branched ethoxylated alcohols including a C<sub>5</sub>-C<sub>15</sub> alcohol having an average of 4 to 12 ethylene oxide units. Nonlimiting examples include Tomadol® 91-6 - a C<sub>9</sub>-C<sub>11</sub> ethoxylated alcohol having an average of 6 ethylene oxide units (available from Air Products and Chemicals, Inc.), LUTENSOL® AO-8 - a synthetic C<sub>13</sub>-C<sub>15</sub> ethoxylated oxo alcohol having an average of 8 ethylene oxide units (available from BASF), Genapol® LA 070S - an ethoxylated lauryl alcohol having an average of 7 ethylene oxide units (available from CLARIANT), and TERGITOL™ 15-S-7, a branched secondary ethoxylated alcohol with 7 ethylene oxide units (available from DOW Chemical). Other examples of suitable ethoxylated linear alcohols include ethoxylated linear alcohols having a C<sub>10</sub>-C<sub>15</sub> n-alkyl group, *e.g.*, having an average of 5 to 12 ethylene oxide units. Nonlimiting examples include

LUTENSOL® TDA 10 (available from BASF) - an ethoxylated tridecyl alcohol having an average of 10 EO groups.

[0027] Other nonionic surfactants which may be present include, but are not limited to, secondary ethoxylated alcohols, such as C<sub>11</sub>-C<sub>15</sub> secondary ethoxylated alcohols. Secondary ethoxylated alcohols suitable for use are sold under the tradename TERGITOL® (available from Dow Chemical). For example TERGITOL® 15-S, more particularly TERGITOL® 15-S-12 is a C<sub>11</sub>-C<sub>15</sub> secondary ethoxylate alcohol having an average of about 12 ethylene oxide groups.

[0028] Other exemplary useful nonionic surfactants include a variety of known nonionic surfactant compounds. Practically any hydrophobic compound having a carboxy, hydroxy, amido, or amino group with a free hydrogen attached to the nitrogen can be condensed with ethylene oxide or with the polyhydration product thereof, polyethylene glycol, to form a nonionic surfactant compound with varying degrees of water solubility - depending on the relative length of the hydrophobic and hydrophilic polyethylenoxy elements. Exemplary nonionic compounds include the polyoxyethylene ethers of alkyl aromatic hydroxy compounds, *e.g.*, alkylated polyoxyethylene phenols, polyoxyethylene ethers of long chain aliphatic alcohols (*e.g.*, ethoxylated alcohols), the polyoxyethylene ethers of hydrophobic propylene oxide polymers, and the higher alkyl amine oxides.

[0029] Further nonionic surfactants which may be optionally present in the compositions are alkyl polyglycosides (*e.g.* Glucopon® 425N). Suitable alkyl polyglycosides include known nonionic surfactants which are alkaline and electrolyte stable. Alkyl mono and polyglycosides are generally prepared by reacting a monosaccharide, or a compound hydrolyzable to a monosaccharide with an alcohol such as a fatty alcohol in an acid medium. The fatty alcohol may have from about 8 to 30 and typically 8 to 18 carbon atoms. Examples of such alkylglycosides include, APG 325 CS GLYCOSIDE which is reported to be a 50% C<sub>9</sub>-C<sub>11</sub> alkyl polyglycoside (commercially available from Henkel Corp, Ambler Pa.) and GLUCOPON® 625 CS which is reported to be a 50% C<sub>10</sub>-C<sub>16</sub> alkyl polyglycoside. In some embodiments, the nonionic surfactant may include an alkylpolyglycoside and/or an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of 5 to 12 ethylene oxide units.

[0030] Alkylpolyglycosides suitable for use in the present compositions may have the formula:



where R is a monovalent aliphatic radical containing 8 to 20 carbon atoms (the aliphatic group may be straight or branched, saturated or unsaturated), R' is a divalent alkyl radical containing 2 to 4 carbon atoms, preferably ethylene or propylene, x is a number having an average value of 0 to about 12, Z is a reducing saccharide moiety containing 5 or 6 carbon atoms, such as a glucose, galactose, glucosyl, or galactosyl residue, and n is a number having an average value of about 1 to 10. Some exemplary alkyl polyglycosides are sold under the name GLUCOPON® (where Z is a glucose moiety and x=0).

[0031] Additional suitable nonionic surfactants include linear alkyl amine oxides. Typical linear alkyl amine oxides include water-soluble amine oxides of the formula  $\text{R}^1\text{-N(R}^2\text{)(R}^3\text{)O}$  where  $\text{R}^1$  is typically a  $\text{C}_8\text{-C}_{18}$  alkyl moiety and the  $\text{R}^2$  and  $\text{R}^3$  moieties are typically selected from the group consisting of hydrogen,  $\text{C}_1\text{-C}_3$  alkyl groups, and  $\text{C}_1\text{-C}_3$  hydroxyalkyl groups. Quite often,  $\text{R}^1$  is a  $\text{C}_8\text{-C}_{18}$  n-alkyl and  $\text{R}^2$  and  $\text{R}^3$  are methyl, ethyl, propyl, isopropyl, 2-hydroxyethyl, 2-hydroxypropyl, and/or 3-hydroxypropyl. The linear amine oxide surfactants in particular may include linear  $\text{C}_{10}\text{-C}_{18}$  alkyl dimethyl amine oxides and linear  $\text{C}_8\text{-C}_{12}$  alkoxy ethyl di(hydroxyethyl) amine oxides. Particularly suitable amine oxides include linear  $\text{C}_{10}$ , linear  $\text{C}_{10}\text{-C}_{12}$ , and linear  $\text{C}_{12}\text{-C}_{14}$  alkyl dimethyl amine oxides. Other examples of amine oxide nonionic surfactants include alkyl amidopropyl amine oxides, such as lauryl/myristyl amidopropyl amine oxides (*e.g.*, lauryl/myristyl amidopropyl dimethylamine oxide).

[0032] Additional suitable nonionic surfactants include polyethoxylated fatty esters. These include, for example, polyethoxylated sorbitan monooleate, sorbitan monolaurate, sorbitan monopalmitate and/or sorbitan monostearate, and polyethoxylated castor oil. Specific examples of such surfactants are the products of condensation of ethylene oxide (*e.g.*, 10-25 moles) with sorbitan monooleate and condensation of ethylene oxide (*e.g.*, 20-40 moles) with castor oil.

**[0033]** The composition may further include one or more of mineral oil, polyol humectant, and adjuvants. In some embodiments, the composition may further include one or more of mineral oil, polyol humectant, an antimicrobial agent, and a fragrance component. In some embodiments, the composition may include up to about 10 wt.%, about 0.1 to 5 wt.%, or about 0.2 to 3 wt.% mineral oil.

**[0034]** Examples of suitable polyol humectants include glycerin, glycols, such as ethylene glycol, propylene glycol, diethylene glycol, dipropylene glycol, butylene glycol and the like, sugar alcohols such as sorbitol, xylitol, and maltitol, sugars such as glucose, galactose, or compounds with glucosyl or galactosyl residues, and mixtures thereof. In some embodiments, the composition may include 0 wt.% to about 20 wt.% of a polyol humectant or more preferably about 1 wt.% to 10 wt.%. In some embodiments, the composition may include about 1 wt.% to 10 wt.% or about 1 wt.% to 5 wt.% glycerin.

**[0035]** As used herein, adjuvants include components or agents, such as additional functional materials. In some embodiments, the functional materials may be included to provide desired properties and functionalities to the cleaning composition. For the purpose of this application, the term "functional materials" include a material that when dispersed or dissolved in a concentrate and/or use solution, such as an aqueous solution, provides a beneficial property in a particular use. The present compositions may optionally include other soil-digesting components, surfactants, disinfectants, detergent fillers, sanitizers, acidulants, complexing agents, biocides and/or antimicrobial agents, corrosion inhibitors, anti-redeposition agents, foam inhibitors, opacifying agents such as titanium dioxide, dyes, bleaching agents (hydrogen peroxide and other peroxides), enzymes, enzyme stabilizing systems, builders, thickening or gelling agents, wetting agents, dispersants, stabilizing agents, dispersant polymers, cleaning compounds, pH adjusting agents (acids and alkaline agents), stain preventers, and/or fragrances. In some embodiments, the composition may include 0 wt.% to about 10 wt.%, 1 wt.% to about 10 wt.%, or 0.1 wt.% to about 5 wt.% of a fragrance component.

**[0036]** In certain aspects, the present cleaning compositions may include adhesion promoter, such as an alkoxyated alcohol, the glycine betaine amide, polyol humectant, mineral oil, polyethyleneglycol and water. The aqueous-based composition may also include an anionic

surfactant (such as an ethoxylated fatty alcohol sulfate and/or sulfonate ester), fragrance and/or a C<sub>10</sub>-C<sub>15</sub> fatty alcohol. For example, cleaning composition may include ethoxylated alcohol, the glycine betaine amide, anionic sulfate ester (such as sodium laureth sulfate), glycerin, mineral oil, polyethyleneglycol and water. In an exemplary embodiment, the composition is an aqueous-based gel, which includes about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units; about 0.1-5 wt.% of the glycine betaine amide; about 2-10 wt.% glycerin; about 0.5-5 wt.% polyethyleneglycol; about 0.5-3 wt.% mineral oil; and at least about 40 wt.% water. Such aqueous-based compositions may also include about 1-10 wt.% of a fragrance component. These compositions may also include about 0.5 to 5 wt.% of an amine compound as a basic agent. In some embodiments, the compositions may also include about 0.05 – 0.5 wt.% of an inorganic basic material, such as sodium hydroxide.

[0037] In certain aspects, the present cleaning compositions may include adhesion promoter, such as an alkoxyated fatty alcohol, the glycine betaine amide, polyol humectant, a film forming polymer additive (e.g., hydrophilic polyacrylate copolymer), ethoxylated C<sub>10</sub>-C<sub>15</sub> alcohol nonionic surfactant, and water. The aqueous-based composition may also include fragrance, polyethyleneglycol and/or mineral oil. For example, cleaning composition may include ethoxylated alcohol (e.g., an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units), the glycine betaine amide, glycerin, an ethoxylated C<sub>10</sub>-C<sub>15</sub> alcohol having an average of 2 to 5 ethylene oxide units, an amphoteric polyacrylate copolymer containing pendent quaternary ammonium groups (e.g., MIRAPOL SURF S available from Rhodia), and water. In an exemplary embodiment, the composition is a gel, which includes about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units; about 0.1-5 wt.% of the glycine betaine amide; about 1-5 wt.% of the ethoxylated C<sub>10</sub>-C<sub>15</sub> alcohol; about 2-10 wt.% glycerin; about 0.5-2 wt.% of the amphoteric polyacrylate copolymer and at least about 40 wt.% water. Such compositions may also include about 1-10 wt.% of a fragrance component, about 0.5-5 wt.% polyethyleneglycol and/or about 0.5-3 wt.% mineral oil. These compositions may also include about 0.5 to 5 wt.% of an amine compound as a basic agent. In some embodiments, the compositions may also include about 0.05 – 0.5 wt.% of an inorganic basic material, such as sodium hydroxide, as the basic agent.

**[0038]** In certain aspects, the present cleaning compositions may include adhesion promoter, such as an alkoxyated fatty alcohol, the glycine betaine amide, polyol humectant, mineral oil, cationic surfactant, and water. Such aqueous-based compositions may also include a fragrance component and/or other additives. For example, cleaning composition may include ethoxylated alcohol (e.g., an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units), the glycine betaine amide, glycerin, mineral oil, a cationic surfactant such as an alkylpolyglucoside derivative having pendent quaternary ammonium groups, and water. In an exemplary embodiment, the aqueous-based composition is a gel (in the absence of the propellant) which includes about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units; about 0.5-3 wt.% mineral oil; about 2-10 wt.% glycerin; about 0.1-5 wt.% of the glycine betaine amide; about 1-5 wt.% of the alkylpolyglucoside derivative; and at least about 40 wt.% water. Such aqueous-based compositions may also include about 1-10 wt.% of a fragrance component. These compositions may also include about 0.5 to 5 wt.% of an amine compound as a basic agent. In some embodiments, the compositions may include about 0.05 – 0.5 wt.% of an inorganic basic material, such as sodium hydroxide, as the basic agent.

**[0039]** In certain aspects, the present cleaning compositions may include adhesion promoter, such as an alkoxyated fatty alcohol, the glycine betaine amide, an anionic surfactant (such as a ethoxylated fatty alcohol sulfate and/or sulfonate ester), polyol humectant, mineral oil, hydrophilic polyacrylate copolymer, and water. The aqueous-based composition may also include a fragrance component. For example, cleaning composition may include an ethoxylated alcohol (e.g., an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units), the glycine betaine amide, glycerin, mineral oil, an amphoteric polyacrylate copolymer containing pendent quaternary ammonium groups (e.g., MIRAPOL SURF S available from Rhodia), and water. Such compositions may also include an anionic sulfate ester (such as sodium laureth sulfate). In an exemplary embodiment, the aqueous-based composition is a gel (in the absence of the propellant) which includes about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of 15 to 40 ethylene oxide units; about 0.1-5 wt.% of the glycine betaine amide; about 0.1-3 wt.% of the amphoteric polyacrylate copolymer; about 2-10 wt.% glycerin; about 1-3 wt.% mineral oil; and at least about 40 wt.%

water. Such aqueous-based compositions may also include about 1-10 wt.% of a fragrance component. These compositions may also include about 0.5 to 5 wt.% of an amine compound as a basic agent. In some embodiments, the compositions may include about 0.05 – 0.5 wt.% of an inorganic basic material, such as sodium hydroxide, as the basic agent.

**[0040]** In certain aspects, the cleaning compositions include an alkoxyated alcohol (*e.g.*, ethoxylated alcohol), polymeric alkyleneoxide block copolymer (*e.g.*, a ethyleneoxide-propyleneoxide block copolymer), the glycine betaine amide, mineral oil, and water. In some embodiments, the cleaning compositions may include one or more additional components, such as a natural or synthetic polymer resin, a polyol humectant (such as glycerin, sorbitol, and/or other sugar alcohol), and/or an anionic and/or amphoteric surfactant and/or nonionic surfactant which is not an alkoxyated alcohol. Optionally, the cleaning compositions may also include one or more adjuvants, such as a fragrance, a complexing agent, and/or a bleaching agent. The alkoxyated alcohol component may include a mixture of ethoxylated alcohols having varying degrees of ethoxylation. For example, the ethoxylated alcohol component may include an ethoxylated C<sub>14</sub>-C<sub>30</sub> alcohol having an average of about 20 to 50 ethylene oxide units and an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of about 5 to 15 ethylene oxide units. In some embodiments, such compositions may be a gel having a hardness of at least about 150 g and/or a gel melt temperature of about 50-80 °C.

**[0041]** In another aspect, the cleaning composition may be an adhesive cleaning composition in which the adhesion promoter includes a ethoxylated alcohol, *e.g.*, an ethoxylated C<sub>12</sub>-C<sub>30</sub> alcohol having an average of 15 to 50 ethylene oxide units, ethyleneoxide-propyleneoxide block copolymer, the glycine betaine amide, mineral oil, and water. In some embodiments, the cleaning composition may include about 15-40 wt.% of a first ethoxylated alcohol, which is an ethoxylated C<sub>14</sub>-C<sub>30</sub> alcohol having an average of 20 to 50 ethylene oxide units; about 1-15 wt.% ethyleneoxide-propyleneoxide block copolymer; about 0.5-10 wt.% mineral oil; about 0.1-5 wt.% of the glycine betaine amide; and water. These compositions may also include about 0.5 to 5 wt.% of an amine compound as a basic agent. In some embodiments, the compositions may include about 0.05 – 0.5 wt.% of an inorganic basic material, such as sodium hydroxide, as the basic agent. The cleaning composition may often also include an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of about 5 to 15 ethylene oxide units.

**[0042]** In some embodiments, the present adhesive cleaning composition may include (a) about 0.1-5 wt.% of the glycine betaine amide; (b) about 15-40 wt.% of the adhesion promoter; (c) about 0.1-5 wt.% polyethylene glycol; (d) about 1-10 wt.% polyol humectant; (e) about 1-10 wt.% of a fragrance component; and (f) at least about 25 wt.% water. In some embodiments, the composition may include (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units; (b) about 0.1-5 wt.% of the glycine betaine amide; (c) about 1-10 wt.% ethyleneoxide-propyleneoxide block copolymer; (d) about 1-10 wt.% glycerin; (e) about 0.1-3 wt.% mineral oil; (f) 0 to about 10 wt.% of a fragrance component; and (g) at least about 40 wt.% water. The composition may include (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units; (b) about 0.1-5 wt.% of the glycine betaine amide; (c) about 0.5-5 wt.% of one or more ethoxylated linear primary alcohols, wherein each alcohol includes a carbon chain containing 9 to 15 carbons and from 2 to 12 ethylene oxide units; (d) about 1-10 wt.% glycerin; (e) 0 to about 3 wt.% mineral oil; (f) 0 to about 5 wt.% polyethylene glycol; (g) 0 to about 10 wt.% of a fragrance component; and (h) at least about 40 wt.% water. In some embodiments, the composition may include (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units; (b) about 0.1-5 wt.% of the glycine betaine amide; (c) about 0.1-3 wt.% mineral oil; (d) about 1-10 wt.% glycerin; (e) about 0.1-5 wt.% polyethylene glycol; (f) 0 to about 3 wt.% of one or more linear primary alcohols, wherein each alcohol includes a carbon chain containing 9 to 15 carbons; (g) 0 to about 10 wt.% of a fragrance component; and (h) at least about 40 wt.% water.

**[0043]** In another aspect, the cleaning composition may be an adhesive cleaning composition that includes a ethoxylated alcohol, which may be an ethoxylated C<sub>10</sub>-C<sub>30</sub> alcohol having an average of 8 to 50 ethylene oxide units and commonly about 15 to 50 ethylene oxide units; glycine betaine amide; ethyleneoxide-propyleneoxide block copolymer; mineral oil; and water. The composition may be self-adhering upon application to a hard surface.

**[0044]** In some embodiments, the cleaning composition may be an adhesive cleaning composition that includes about 15-40 wt.% of a first ethoxylated alcohol, which is an

ethoxylated C<sub>14</sub>-C<sub>30</sub> alcohol having an average of 20 to 50 ethylene oxide units; about 0.1-5 wt.% glycine betaine amide; about 1-15 wt.% ethyleneoxide-propyleneoxide block copolymer; about 0.5-10 wt.% mineral oil; and water. The cleaning composition may commonly also include an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of about 5 to 15 ethylene oxide units.

**[0045]** In another aspect, the present technology provides a composition for treating a hard surface that includes (a) at least one adhesion promoter, which includes at least one polyalkoxy group; (b) a glycine betaine amide of Formula I, wherein R is an aliphatic group having 8 to 22 carbon atoms; and (c) water; wherein the composition is a gel having a gel melt temperature of about 55-80 °C and a viscosity at 25 °C of at least about 150,000 cP.

**[0046]** In another aspect, the present technology provides a composition for treating a hard surface that includes (a) at least one adhesion promoter, which includes at least one polyalkoxy group; (b) a glycine betaine amide of Formula I, wherein R is an aliphatic group having 8 to 22 carbon atoms; and (c) water; wherein the composition is a gel having a hardness of at least about 150 g and a gel melt temperature of about 55-80 °C.

**[0047]** In some embodiments, the adhesion promoter may further include a hydrophilic polymer. In some embodiments, the composition may further include an active agent, wherein the active agent is one or more of a fragrance, germicide, antimicrobial, bleach, or deodorizer.

**[0048]** In some embodiments, the composition may be applied directly to a surface using any suitable applicator device, such as a pump or syringe-type device, manual, pressurized, or mechanized, aerosol, or sprayer. The consumer may activate the applicator for application of the composition directly to a surface without the need to touch the surface. In the case of a toilet bowl surface, this provides for a hygienic and easily accessible method of application. The amount and location(s) of the composition may be chosen by the user, *e.g.* one or more dollops or drops of composition, or one or more lines of composition. The composition may self-adhere to the hard surface to which it is applied, such as the ceramic side wall of a toilet bowl or shower wall. A surprising and unique feature not provided by conventional devices is that the composition may be delivered to surfaces located above the site of application of the composition.

[0049] Known applicators for gel-like substances may be used with the present compositions. For example, PCT Int. Pat. App. WO 03/043906 and WO 2004/043825 disclose exemplary dispensing devices. However, some users may find that the inability to provide consistent dosing associated with known applicators frustrating. A non-limiting exemplary dispenser that is capable of providing metered doses of a composition that may be compatible with the present compositions is described in U.S. Pat. App. No. 2007/0007302A1. When used in conjunction with a metered dispenser, the dispenser may provide doses of the composition in any volume and/or size and/or dose that is suitable for the intended application. Similarly, the shape of the dispenser may be any shape that is desired.

[0050] In one embodiment, a composition according to the present technology may be provided in a dispenser wherein the dispenser provides unitized doses. In a particular embodiment, the unitized dose may be from about 4 g/dose to about 10 g/dose. In another embodiment, the unitized dose may be from about 5 g/dose to about 9 g/dose. In yet another embodiment, the dispenser may provide from about 6 to about 8 g/dose unitized doses. In some embodiments, the dispenser may provide from about 3 to about 12 unitized doses. In some embodiments, the dispenser may be refilled with additional composition.

[0051] As used herein, "composition" refers to any solid, gel, and/or paste substance having more than one component.

[0052] As used herein, "self-adhering" or "self-adhesive" refers to the ability of a composition to stick onto a hard surface without the need for a separate adhesive or other support device. In one embodiment, a self-adhering composition does not leave any residue or other substance (*i.e.*, additional adhesive) once the composition is used up.

[0053] As used herein, "gel" refers to a disordered solid composed of a liquid with a network of interacting particles or polymers which has a non-zero yield stress.

[0054] As used herein, "fragrance" refers to any perfume, odor-eliminator, odor masking agent, the like, and combinations thereof. In some embodiments, a fragrance is any substance which may have an effect on a consumer, or user's, olfactory senses.

[0055] As used herein, "wt. %" refers to the weight percentage of an ingredient in the total formula. For example, an off-the-shelf commercial composition of Formula X may only contain 70% active ingredient X. Thus, 10 g of the off-the-shelf composition only contains 7 g of X. If 10 g of the off-the-shelf composition is added to 90 g of other ingredients, the wt. % of X in the final formula is thus only 7%.

[0056] As used herein, "hard surface" refers to any porous and/or non-porous surface. In one embodiment, a hard surface may be selected from the group consisting of: ceramic, glass, metal, polymer, stone, and combinations thereof. For the purposes of this application, a hard surface does not include silicon wafers and/or other semiconductor substrate materials. Nonlimiting examples of ceramic surfaces include: toilet bowl, sink, shower, tile, the like, and combinations thereof. A nonlimiting example of a glass surfaces includes: window and the like. Nonlimiting examples of metal surfaces include: drain pipe, sink, the like. Nonlimiting examples of a polymeric surface includes: PVC piping, fiberglass, acrylic, Corian®, the like. A nonlimiting example of a stone hard surface includes: granite, marble, and the like.

[0057] A hard surface may be any shape, size, or have any orientation that is suitable for its desired purpose. In one non-limiting example, a hard surface may be oriented in a vertical configuration. In another non-limiting example, a hard surface may be the surface of a curved surface, such as a ceramic toilet bowl. In yet another non-limiting example, a hard surface may be the inside of a pipe, which has vertical and horizontal elements, and also may have curved elements. It is thought that the shape, size and/or orientation of the hard surface will not affect the compositions of the present invention, because of the unexpectedly strong transport properties of the compositions under the conditions described infra.

[0058] As used herein, "surfactant" refers to any agent that lowers the surface tension of a liquid, for example water. Exemplary surfactants which may be suitable for use with the present invention are described infra. In one embodiment, surfactants may be selected from the group consisting of anionic, non-ionic, cationic, amphoteric, zwitterionic, and combinations thereof.

[0059] As used herein, “gel melt temperature” refers to the temperature at which the rigid gel composition abruptly transitions to a low viscosity flowable fluid having a viscosity of less than 5 Pa as the temperature of the gel is raised. To measure the gel melt temperature as defined herein a Brookfield temperature controlled Cone/Plate Viscometer (Brookfield Engineering Laboratories, Inc., Middleboro, Mass.) was used according to the manufacturer's specifications. The specific parameters used on the device are: Constant shear rate of 1/sec; C-25-1 Cone; 20 °C to 80 °C temperature ramp-up over 240 seconds.

[0060] As used herein, “gel hardness” refers to the hardness strength of a composition. The gel hardness values are determined by measurement at 22 °C using a Brookfield LFRA 1500 Texture Analyzer with TA41 probe (6 mm cylinder diameter, 35 mm length) with a trigger of 5.0 g, penetration distance of 3.0 mm, and a speed of 0.5 mm/sec, recorded as peak load values. In some embodiments, the present compositions may have a gel hardness of at least about 150 g. The compositions may have a gel hardness of at least about 175 g or at least about 185 g. The compositions may have a gel hardness of at least about 200 g. The compositions may have a gel hardness of at least about 250 g. In some embodiments, the gel hardness may range from about 150 g to 300 g. The gel hardness may range from about 175 g to 275 g or more commonly from about 185 g to 265 g. In some embodiments, the gel hardness may range from about 200 g to 250 g.

[0061] An assessment of the hardness of a gel can also be made using a Precision Penetrometer, manufactured by Precision Scientific, Co. equipped with a large diameter cone weighing 102.4 grams with a 23D angle and loaded with 150 grams of weight on the top of a spindle. The hardness is determined by measuring the penetration of the cone into the surface of a polymer or gel solid. Samples must be at least ¼ inch thick to be used with the setup parameters. The measurement is characterized in tenths of a mm penetration into the surface of the solid or gel.

[0062] As used herein, “viscosity” refers to the resistance to gradual deformation by shear stress or tensile stress of a composition. The viscosity may be measured at 25 °C using a TA AR 2000 rheometer equipped with a 4 cm stainless steel parallel plate and Peltier plate at a shear of 1 reciprocal second.

[0063] As used herein, “Force to Actuate” (FTA) refers to the force needed to dispense one dose of sample, i.e., the force required to actuate the product or force to push a dose of the product out of a dispensing device. FTA is measured using an IMADA force gauge, model MF-20, at 25 °C sample temperature. The force gauge is used to dispense one dose of sample. FTA should desirably be about 7-14 pounds of pressure. The dose weight is between 6-8 g with an average weight of dose of approximately 6.6 g.

[0064] As used herein, “adhesion” refers to the ability of a dose of gel to remain adhered on a vertical board with a tile surface. “Adhesion time” and “adhesion (in %)” are measured according to the following protocol. A board containing twelve 4.25" X 4.25" standard grade glossy ceramic tiles arranged in a 3 (in the y-direction) by 4 (in the x-direction) configuration bonded and grouted to a plexi-glass back is provided. Before each determination, the board is rinsed with warm (about 75 to a 85 °F) tap water using a cellulose sponge. The board is then re-rinsed thoroughly with warm tap water. A non-linting cloth saturated with isopropanol is then used to wipe down the entire tile board. The board is placed in a horizontal position (i.e., such that the plane of the board is flat on the floor or lab bench). A force gauge is used to dispense a dose of gel on the board. Samples approximately 1.5" in diameter and weighing from about 5.5 g to about 8.0 g are provided to the surface of the board such that the bottom of the sample touches the top-most, horizontally oriented (i.e., in the x-direction), grout line of the board. Samples are spaced approximately 2" apart from each other. A permanent marker is used to draw a straight line (parallel to the x-direction) approximately 0.75" below the top-most grout line. The board is then placed in a vertical position (i.e., such that the plane of the board is perpendicular with the floor or lab bench) in an environmental chamber. The chamber is maintained at a temperature of about 86 to a 90 °F and relative humidity of about 40% to 60%. High and low temperature and humidity is recorded for determination. The position of gels are checked every 24 hours until all samples have crossed the “fail line” or after specified time has elapsed. A camera is used to record pictures of the samples at time zero and at successive times. The time required for the sample to slide down the tile a distance of 1.5 times the diameter of the sample (circa 2.25") is measured, recorded as the "adhesion time" for a particular sample. The reported “adhesion time” is an average determined from the values

measured over three boards. The “adhesion” reported in percentage is the difference above or below the value determined for a control sample.

#### EXAMPLES

**[0065]** The following examples are intended to more specifically illustrate the present cleaning compositions according to various embodiments described above. These examples should in no way be construed as limiting the scope of the present technology.

**[0066]** A number of exemplary formulations of the cleaning compositions were prepared and are presented in Table 1 below. Table 2 presents several properties of the exemplary formulations including gel hardness, gel melt temperature, viscosity, adhesion, and adhesion time.

**Table 1**

Sample #	GB Surfactant	GB Surf (wt.%)	Glycerin	PEG 6000	Mineral oil	Genapol T 250	Imbentini AG/618G	Imbentini AG168S/300 SP	Takasago RU-2360/2
<i>Lab Standard</i>	<i>SLES</i>	16	5	1	0.5	0	15	12	5
<i>Marine</i>	<i>SLES</i>	16	5	1	0.9	0	15	12	5
<i>Aqua Pulse</i>	<i>SLES</i>	16	5	1	0.9	0	15	12	5
1D1	<i>C14 amide</i>	16	6	0.6	0.6	0	15	12	5
2D1	<i>C14 amide</i>	12	0	1.2	0.6	0	15	12	5
3D1	<i>C12 amide</i>	16	6	1.2	0	0	15	12	5
6D1	<i>C14 amide</i>	12	6	0.6	0.6	0	15	12	5
8D1	<i>C12 amide</i>	12	6	1.2	0	0	15	12	5
9D1	<i>C12 amide</i>	16	0	1.2	0.6	0	15	12	5
10D2	<i>C12 amide</i>	12	0	0.6	0.6	0	15	12	5
21D1	<i>C18 amide</i>	16	6	0.6	0.6	0	15	12	5
22D1	<i>C18 amide</i>	12	0	1.2	0.6	0	15	12	5
23D1	<i>C18 amide</i>	12	6	0.6	0.6	0	15	12	5
12D2	<i>C14 amide</i>	16	0	1.2	0	0	15	12	5
13D2	<i>C12 amide</i>	12	6	0.6	0	0	15	12	5
15D2	<i>C18 amide</i>	12	6	1.2	0	0	15	12	5

**Table 1 (Cont.)**

Sample #	GB Surfactant	GB Surf (wt.%)	Glycerin	PEG 6000	Mineral oil	Genapol T 250	Imbentim AG/618G	Imbentim AG168S/300 SP	Takasago RU-2360/2
<i>Lab Standard</i>	<i>SLES</i>	16	5	1	0.5	0	15	12	5
16D2	<i>C12 amide</i>	12	0	0.6	0	0	15	12	5
18D2	<i>C18 amide</i>	16	0	0.6	0	0	15	12	5
19D2	<i>C12 amide</i>	16	0	0.6	0.6	0	15	12	5
2D5	<i>C12 amide</i>	6	0	0.6	0	0	15	6	5
9D5	<i>C12 amide</i>	6	0	0.6	0	0	7.5	12	5
16D5	<i>C12 amide</i>	2	0	1.2	0	0	15	12	5
17D5	<i>C12 amide</i>	2	0	0	0	0	15	12	5
23D5	<i>C12 amide</i>	10	0	1.2	0	0	15	12	5
AA	<i>C12 amide</i>	12	0	0.6	0	0	15	12	5
AAA	<i>C12 amide</i>	12	6	0.5	0	0	15	12	5

**Table 2**

$\gamma_{CMC}$ (dyne/cm)	CMC (mg/l)	$C_{20}$ (mg/l)	$\delta\gamma/\delta C$	Maragoni Velocity	Adhesion	Adhesion Times (hours)	FTA	pH	Gel Point (°C)	Viscosity (cP x 10 <sup>3</sup> )	Sample #
				47	-	11.5	10.4	5.36	56.0	333.9	Lab Standard
				49.5	-	11.3			63.5	447.9	Marine
44.806	10	5.45	-1.10651	49.7	-	15.5	13.9		64.9	355.2	Aqua Pulse
				-	-22.50%	10.3	16.1	4.86	67.6	904.5	1D1
				106.3	112.50%	28.3	12.7	4.79	79.3	766.9	2D1
				102.85	-57.50%	5.7	17.3	5.71	48.2	766.9	3D1
				79.35	-26.25%	9.8	13.0	4.70	78.3	685.4	6D1
				75.7	-45.00%	7.3	14.2	5.50	60.0	681.4	8D1
				78.45	-51.90%	6.3	18.9	5.69	56.8	828.9	9D1
				82.85	-26.96%	9.3	17.1	5.40	73.8	833.9	10D2
				172.3	58.29%	17.5	21.6*		71.7	1087.5	21D1
				102.55	88.44%	20.8	14.0		80.3	463.5	22D1
				180.5	88.44%	24.3	15.7		85.7	480.7	23D1
				59.65	20.00%	15.3	8.3	4.84	70.1	309.7	12D2
				75.95	-34.78%	8.3	16.1	5.41	64.8	845.9	13D2

**Table 2 (Cont.)**

$\gamma_{CMC}$ (dyne/cm)	CMC (mg/l)	$C_{20}$ (mg/l)	$\delta\gamma/\delta C$	Maragoni Velocity	Adhesion	Adhesion Times (hours)	FTA	pH	Gel Point (°C)	Viscosity (cP x 10 <sup>3</sup> )	Sample #
				47	-	11.5	10.4	5.36	56.0	333.9	Lab Standard
				76.2	68.11%	20.5	12.0	4.49	77.9	378.6	15D2
				100.5	-35.17%	8.5	17.4		69.9	834.6	16D2
40.56	7	1.74	-0.92	53.6	79.24%	23.5	11.4		62.5	351.6	18D2
				102.45	28.39%	16.8	13.0		79.9	707.3	19D2
				110.5	-46.61%	7.0	20.9		61.6	898.9	2D5
41.86	15	11	-1.59786	120.15	18.38%	18.0	8.9	4.9	78.3	243.3	9D5
43.5	12	6.25	-1.62562	97.45	-69.85%	6.0	9.9	5.39	65.5	259.1	16D5
42.11	13.9	8.3	-1.3662	117.8	>238.97%	>48.0	11.0	4.51	79.7	340.8	17D5
43.88	12	10	1.28218	94.5	>238.97%	>48.0	13.5	4.74	80.0	318.5	23D5
				100.5		28.3				834.6	AA
				75.05		58.3				845.0	AAA

[0067] The composition of a number of additional exemplary glycine betaine amides which may be used in formulations of the present cleaning compositions are presented in Table 3 below.

**Table 3**

<b>Exemplary Crude GB Amide surfactants</b>				
	<b>Composition</b>			
	<b>GB amide*</b>	<b>GB butyl ester*</b>	<b>GB**</b>	<b>Ammonium salts***</b>
	Wt.%	Wt.%	Wt.%	Wt.%
<i>GB caprylic (C8) amide</i>	73.3	2.4	3.4	20.9
<i>GB caprylic/lauric (C8/C12) amide</i>	75.1	6.6	3.7	14.6
<i>GB lauric/myristic (C12/C14) amide</i>	79.9	2.5	2.4	15.2

\*\* GB = glycine betaine


\*\*\* Primarily methanesulfonate salt of amine corresponding to amide group

\* As methanesulfonate salt

### ILLUSTRATIVE EMBODIMENTS

[0068] Reference is made in the following to a number of illustrative embodiments of the subject matter described herein. The following embodiments describe illustrative embodiments that may include various features, characteristics, and advantages of the subject matter as presently described. Accordingly, the following embodiments should not be considered as being comprehensive of all of the possible embodiments or otherwise limit the scope of the methods, materials and compositions described herein.

[0069] In one aspect, the present technology provides a composition for treating a hard surface including (a) an adhesion promoter, which includes at least one compound including one or more polyalkoxy groups; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and X<sup>-</sup> represents an inorganic or organic anion; and (c) water; wherein the composition is self-adhering upon application to a hard surface. In some embodiments, the X<sup>-</sup> may represent a methanesulfonate anion. In some embodiments, the composition may be a gel having a gel melt temperature of about 55-80 °C. The composition may be a gel having a viscosity at 25 °C of at least about 150,000 cP. In some embodiments, the composition may be a gel having a hardness of at least about 150 g. In some embodiments, the composition may be a gel having a hardness of at least about 150 g, a gel melt temperature of about 55-80 °C, and a viscosity at 25 °C of at least about 400,000 cP.


[0070] In some embodiments, the adhesion promoter may include an ethoxylated alcohol. In some embodiments, the adhesion promoter may include an ethoxylated C<sub>12</sub>-C<sub>30</sub> aliphatic alcohol having an average of about 15 to 100 ethylene oxide units. In some embodiments, the adhesion promoter may include an ethoxylated linear C<sub>14</sub>-C<sub>22</sub> primary aliphatic alcohol having an average of about 20-35 ethylene oxide units. The composition may include about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 20-35 ethylene oxide units. In some embodiments, the adhesion promoter may include an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol. In some embodiments, the adhesion promoter may include an ethyleneoxide-propyleneoxide block copolymer. The ethyleneoxide-propyleneoxide block copolymer may include an EO-PO block copolymer, an EO-PO-EO block copolymer, a C<sub>8</sub>-C<sub>18</sub> alcohol EO-PO adduct, a C<sub>8</sub>-C<sub>18</sub> alcohol PO-EO adduct, and/or an EO-PO dialkyl ether. In some embodiments, the adhesion promoter may include polyethylene glycol. In some embodiments, the adhesion promoter may further include polysaccharide and/or synthetic polymer resin.

[0071] The composition may further include one or more of mineral oil, polyol humectant, an antimicrobial agent, and a fragrance component. In some embodiments, the composition may further include a surfactant selected from nonionic, anionic, cationic, zwitterionic, and/or amphoteric surfactants and mixtures thereof; wherein the surfactant is different from the

adhesion promoter. The nonionic surfactant may include an alkylpolyglycoside and/or an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of 5 to 12 ethylene oxide units.

[0072] In some embodiments, the composition may include: (a) about 0.1-5 wt.% of the glycine betaine amide; (b) about 15-40 wt.% of the adhesion promoter; (c) about 0.1-5 wt.% polyethylene glycol; (d) about 1-10 wt.% polyol humectant; (e) about 1-10 wt.% of a fragrance component; and (f) at least about 25 wt.% water. In some embodiments, the composition may include: (a) about 0.1-5 wt.% of the glycine betaine amide; (b) about 20-35 wt.% of the adhesion promoter; (c) about 0.5-2 wt.% polyethylene glycol; (d) about 1-10 wt.% glycerin; (e) about 1-10 wt.% of a fragrance component; and (f) at least about 25 wt.% water. In some embodiments, the composition may include: (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units; (b) about 0.1-5 wt.% of the glycine betaine amide; (c) about 1-10 wt.% ethyleneoxide-propyleneoxide block copolymer; (d) about 1-10 wt.% glycerin; (e) about 0.1-3 wt.% mineral oil; (f) 0 to about 10 wt.% of a fragrance component; and (g) at least about 40 wt.% water. In some embodiments, the composition may include: (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units; (b) about 0.1-5 wt.% of the glycine betaine amide; (c) about 0.5-5 wt.% of one or more ethoxylated linear primary alcohols, wherein each alcohol includes a carbon chain containing 9 to 15 carbons and from 2 to 12 ethylene oxide units; (d) about 1-10 wt.% glycerin; (e) 0 to about 3 wt.% mineral oil; (f) 0 to about 5 wt.% polyethylene glycol; (g) 0 to about 10 wt.% of a fragrance component; and (h) at least about 40 wt.% water. In some embodiments, the composition may include: (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units; (b) about 0.1-5 wt.% of the glycine betaine amide; (c) about 0.1-3 wt.% mineral oil; (d) about 1-10 wt.% glycerin; (e) about 0.1-5 wt.% polyethylene glycol; (f) 0 to about 3 wt.% of one or more linear primary alcohols, wherein each alcohol includes a carbon chain containing 9 to 15 carbons; (g) 0 to about 10 wt.% of a fragrance component; and (h) at least about 40 wt.% water.

[0073] In some embodiments, the R group of Formula I may be a C<sub>8</sub>, C<sub>10</sub>, C<sub>12</sub>, C<sub>14</sub>, C<sub>16</sub> and/or C<sub>18</sub> alkyl group and/or an oleic group. The R group of Formula I may be a lauric, myristic, palmitic, stearic and/or oleic group. In some embodiments, the glycine betaine amide may include a mixture of glycine betaine amides having R groups with 12 carbon atoms and 14 carbon atoms; and the composition may further include a mixture of amines (RNH<sub>2</sub>) and/or salt(s) thereof having R groups with 12 carbon atoms and 14 carbon atoms. In some embodiments, X<sup>-</sup> represents a methanesulfonate anion. The composition may further include a glycine betaine ester of formula (II):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and X<sup>-</sup> represents an inorganic or organic anion. In some embodiments, the X<sup>-</sup> may represent a methanesulfonate anion; the R group may include a lauric and/or myristic group; and the adhesion promoter may include an ethoxylated linear C<sub>14</sub>-C<sub>22</sub> primary aliphatic alcohol having an average of about 15 to 40 ethylene oxide units. The composition may be a gel having a gel melt temperature of about 60-70 °C and a viscosity at 25 °C of about 250,000 to 600,000 cP.

[0074] In one aspect, the present technology provides a composition for treating a hard surface that may include (a) at least one adhesion promoter, which includes at least one polyalkoxy group; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and (c) water; wherein the composition may be a gel having a gel melt temperature of about 55-80 °C and a viscosity at 25 °C of at least about 150,000 cP. In some embodiments, the gel may have a viscosity at 25 °C of about 250,000 to 500,000 cP. The composition may be self-adhering upon application to a hard surface.

[0075] In another aspect is provided a composition for treating a hard surface that includes (a) at least one adhesion promoter, which includes at least one polyalkoxy group; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms; and (c) water; wherein the composition may be a gel having a hardness of at least about 150 g and a gel melt temperature of about 55-80 °C. In some embodiments, the gel may have a viscosity at 25 °C of about 400,000 to 600,000 cP. The composition may be self-adhering upon application to a hard surface.

**[0076]** In one aspect is provided a composition for treating a hard surface that includes (a) at least one adhesion promoter, which includes an organic molecule including a polyalkoxy group; (b) at least one surfactant selected from the group consisting of: anionic, nonionic, cationic, amphoteric, zwitterionic, and combinations thereof; (c) the glycine betaine amide; (d) a blend of ethoxylated linear primary alcohols, wherein each alcohol of the blend includes a carbon chain containing 9 to 17 carbons; (e) at least one solvent, which includes glycerin; (f) a polyol humectant, such as mineral oil; and (g) water; where the composition is self-adhering upon application to a vertical hard surface. In some embodiments, the at least one adhesion promoter may further include a hydrophilic polymer. In some embodiments, the at least one surfactant may further include at least one cationic surfactant. In some embodiments, the at least one adhesion promoter may further include a polysaccharide. The composition may further include an active agent, wherein the active agent is one or more of a fragrance, germicide, antimicrobial, bleach, or deodorizer.

**[0077]** In some embodiments, the present composition includes the glycine betaine amide and may include about 0.5 to 3.5 wt.% mineral oil; about 1 to 12 wt.% glycerin; and about 18 to 27 wt.% ethoxylated alcohol. In some embodiments, the composition may include about 18 to 27 wt. % of an ethoxylated alcohol; about 0.5 to 3.5 wt.% mineral oil; about 5 to 10 wt.% glycerin; 0 to about 6 wt.% of a fragrance; and at least about 40 wt.% water. The ethoxylated alcohol may include a C<sub>16</sub>.C<sub>18</sub> ethoxylated alcohol including about 15 to 40 ethoxy groups.

**[0078]** In another aspect is provided a composition for treating a hard surface that includes: (a) about 18 to 27 wt.% of at least one adhesion promoter; wherein the at least one adhesion promoter includes an organic molecule with a hydrophilic residual and a hydrophobic residual;

(b) the glycine betaine amide; (c) at least one surfactant selected from the group consisting of: anionic, nonionic, cationic, amphoteric, zwitterionic, and combinations thereof; wherein the at least one surfactant includes at least about 7.5 wt.% based on the total weight of the composition of at least one nonionic surfactant, which can serve all or in part as the at least one adhesion promoter; (d) from greater than 0 to about 5 wt.% mineral oil; (e) at least about 25 wt.% water; (f) 0 to about 2.0 wt.% of a blend of linear primary alcohols, wherein each alcohol of the blend includes a carbon chain containing 9 to 17 carbons; and (g) optionally, at least one solvent; wherein the composition is self-adhering upon application to a vertical hard surface.

[0079] In one aspect is provided a self-adhesive composition that includes (a) at least one adhesion promoter; (b) a glycine betaine amide of formula (I):



wherein R is an aliphatic group having 8 to 22 carbon atoms and X<sup>-</sup> is an organic or inorganic anion; and (c) water. In some embodiments, R, is an alkyl and/or alkenyl group. In some embodiments, R may be C<sub>10</sub>-C<sub>18</sub> aliphatic group. In some embodiments, R may be a C<sub>8</sub>, C<sub>10</sub>, C<sub>12</sub>, C<sub>14</sub>, C<sub>16</sub>, and/or C<sub>18</sub> aliphatic group. In some embodiments, R may be a lauric, myristic, and/or oleic group. In some embodiments, R may be a C<sub>12</sub> and/or C<sub>14</sub> alkyl or alkenyl group. X<sup>-</sup> may be a methane sulfonate anion. In some embodiments, the composition may further include ROH and/or salt thereof, wherein R is as defined herein. In some embodiments, the composition may further include ROH and/or salt thereof, wherein R is an aliphatic C<sub>8</sub>-C<sub>18</sub> alcohol. The composition may further include methanesulfonic acid and/or salt thereof. In some embodiments, the adhesion promoter may be an alkoxyated alcohol. The alkoxyated alcohol may include one or more ethoxyated alcohols. In some embodiments, the one or more ethoxyated alcohols may include an ethoxyated C<sub>12</sub>-C<sub>30</sub> alcohol having an average of 15 to 50 ethylene oxide units. In some embodiments, the adhesion promoter may further include a polysaccharide.

[0080] It will be readily apparent to one skilled in the art that varying substitutions and modifications may be made to the methods and compositions disclosed herein without


departing from the scope and spirit of the invention. The terms and expressions which have been employed are used as terms of description and not of limitation, and there is no intention that in the use of such terms and expressions of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the invention. Thus, it should be understood that although the present invention has been illustrated by specific embodiments and optional features, modification and/or variation of the concepts herein disclosed may be resorted to by those skilled in the art, and that such modifications and variations are considered to be within the scope of this invention.

**[0081]** In addition, where features or aspects of the invention are described in terms of Markush groups or other grouping of alternatives, those skilled in the art will recognize that the invention is also thereby described in terms of any individual member or subgroup of members of the Markush group or other group.

**[0082]** Also, unless indicated to the contrary, where various numerical values are provided for embodiments, additional embodiments are described by taking any two different values as the endpoints of a range. Such ranges are also within the scope of the described invention.

**WHAT IS CLAIMED IS:**

1. A composition for treating a hard surface comprising
  - (a) adhesion promoter, which comprises at least one compound including one or more polyalkoxy groups;
  - (b) a glycine betaine amide having a formula:



wherein R is an aliphatic group having 8 to 22 carbon atoms; and X<sup>-</sup> represents an inorganic or organic anion; and

(c) water;

wherein the composition is self-adhering upon application to a hard surface.

2. The composition of claim 1, wherein the composition is a gel having a gel melt temperature of about 55-80 °C.
3. The composition of claim 1 or 2, wherein the composition is a gel having a viscosity at 25 °C of at least about 150,000 cP.
4. The composition of any of claims 1 to 3, wherein the composition is a gel having a hardness of at least about 150 g.
5. The composition of any of claims 1 to 4, wherein the adhesion promoter comprises an ethoxylated C<sub>12</sub>-C<sub>30</sub> aliphatic alcohol having an average of about 15 to 100 ethylene oxide units.
6. The composition of claim 5, wherein the composition comprises about 20-35 wt.% of an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 20-35 ethylene oxide units.

7. The composition of any of claims 1 to 6, wherein the adhesion promoter comprises ethyleneoxide-propyleneoxide block copolymer.
8. The composition of any of claims 1 to 7, wherein the adhesion promoter comprises polyethyleneglycol.
9. The composition of any of claims 1 to 8, further comprising one or more of mineral oil, polyol humectant, an antimicrobial agent and a fragrance component.
10. The composition of any of claims 1 to 9, wherein the adhesion promoter further comprises polysaccharide and/or synthetic polymer resin.
11. The composition of any of claims 1 to 10, further comprising a surfactant selected from nonionic, anionic, cationic, zwitterionic and/or amphoteric surfactants and mixtures thereof; wherein the surfactant is different from the adhesion promoter.
12. The composition of claim 11, wherein the nonionic surfactant comprises an alkylpolyglycoside and/or an ethoxylated C<sub>8</sub>-C<sub>15</sub> alcohol having an average of 5 to 12 ethylene oxide units.
13. The composition of any of claims 1 to 12 comprising:
  - (a) about 0.1-5 wt.% of the glycine betaine amide;
  - (b) about 15-40 wt.% of the adhesion promoter;
  - (c) about 0.1-5 wt.% polyethylene glycol;
  - (d) about 1-10 wt.% polyol humectant;
  - (e) about 1-10 wt.% of a fragrance component; and
  - (f) at least 25 wt.% water.
14. The composition of any of claims 1 to 12 comprising:
  - (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units

- (b) about 0.1-5 wt.% of the glycine betaine amide;
- (c) about 1-10 wt.% ethyleneoxide-propyleneoxide block copolymer;
- (d) about 1-10 wt.% glycerin;
- (e) about 0.1-3 wt.% mineral oil;
- (f) 0 to about 10 wt.% of a fragrance component; and
- (g) at least 40 wt.% water.

15. The composition of any of claims 1 to 12 comprising:

- (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units;
- (b) about 0.1-5 wt.% of the glycine betaine amide;
- (c) about 0.5-5 wt.% of one or more ethoxylated linear primary alcohols, wherein each alcohol includes a carbon chain containing 9 to 15 carbons and from 2 to 12 ethylene oxide units;
- (d) about 1-10 wt.% glycerin;
- (e) 0 to about 3 wt.% mineral oil;
- (f) 0 to about 5 wt.% polyethylene glycol;
- (g) 0 to about 10 wt.% of a fragrance component; and
- (h) at least 40 wt.% water.

16. The composition of any of claims 1 to 12 comprising:

- (a) about 15-35 wt.% of the adhesion promoter, which includes an ethoxylated C<sub>14</sub>-C<sub>22</sub> fatty alcohol having an average of about 15-40 ethylene oxide units;
- (b) about 0.1-5 wt.% of the glycine betaine amide;
- (c) about 0.1-3 wt.% mineral oil;
- (d) about 1-10 wt.% glycerin;
- (e) about 0.1-5 wt.% polyethylene glycol;
- (f) 0 to about 3 wt.% of one or more linear primary alcohols, wherein each alcohol includes a carbon chain containing 9 to 15 carbons;
- (g) 0 to about 10 wt.% of a fragrance component; and

(h) at least 40 wt.% water.


17. The composition of any of claims 1 to 16, wherein the R group is a C<sub>8</sub>, C<sub>10</sub>, C<sub>12</sub>, C<sub>14</sub>, C<sub>16</sub> and/or C<sub>18</sub> alkyl group and/or an oleic group.

18. The composition of any of claims 1 to 16, wherein the R group is a lauric, myristic, palmitic, stearic and/or oleic group.

19. The composition of any of claims 1 to 16, wherein the wherein the glycine betaine amide comprises a mixture of glycine betaine amides having R groups with 12 carbon atoms and 14 carbon atoms; and the composition further comprises a mixture of fatty amines (RNH<sub>2</sub>) having R groups with 12 carbon atoms and 14 carbon atoms.


20. The composition of any of claims 1 to 19, wherein the X<sup>-</sup> represents a methanesulfonate anion.

21. The composition of any of claims 1 to 20, further comprising a glycine betaine ester having a formula:



wherein R is an aliphatic group having 8 to 22 carbon atoms; and Y<sup>-</sup> represents an inorganic or organic anion.

22. The composition of any of claims 1 to 21, further comprising a glycine betaine ester having a formula:



wherein R is a butyl group; and Y<sup>-</sup> represents a methanesulfonate anion.

23. The composition of any of claims 1 to 22, wherein the X<sup>-</sup> represents a methanesulfonate anion; the R group comprises a lauric and/or myristic group; and the adhesion promoter comprises an ethoxylated linear C<sub>14</sub>-C<sub>22</sub> primary aliphatic alcohol having an average of about 15 to 40 ethylene oxide units.

24. The composition of claim 23 wherein the composition is a gel having a gel melt temperature of about 60 to 70 °C; and a viscosity at 25 °C of about 250,000 to 500,000 cP.

25. A composition for treating a hard surface comprising  
 (a) at least one adhesion promoter, which includes at least one polyalkoxy group;  
 (b) a glycine betaine amide having a formula:




wherein R is an aliphatic group having 8 to 22 carbon atoms; and

(c) water;

wherein the composition is a gel having has a gel melt temperature of about 55-80 °C and a viscosity at 25 °C of at least about 150,000 cP.

26. A composition for treating a hard surface comprising  
 (a) at least one adhesion promoter, which includes at least one polyalkoxy group;  
 (b) a glycine betaine amide having a formula:




wherein R is an aliphatic group having 8 to 22 carbon atoms; and

(c) water;

wherein the composition is a gel having a hardness of at least about 150 g and a gel melt temperature of about 55-80 °C.

27. The composition of claim 25 or 26, further comprising a glycine betaine ester having a formula:



wherein R is a butyl group; and Y<sup>-</sup> represents a methanesulfonate anion.

28. The composition of any of claims 1 to 27, wherein the adhesion promoter further comprises a hydrophilic polymer.

29. The composition of any of claims 1 to 28, further comprising an active agent, wherein the active agent is one or more of a fragrance, germicide, antimicrobial, bleach, or deodorizer.

30. The composition of any one of claims 1 to 29, further comprising a film forming polymer additive.

33. The composition of claim 30 wherein the film forming polymer additive comprises a hydrophilic polyacrylate copolymer.

INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2016/046176

A. CLASSIFICATION OF SUBJECT MATTER  
 INV. C11D17/00 C11D3/00 C11D3/37 C11D1/835 C11D1/62  
 ADD.  
 According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED  
 Minimum documentation searched (classification system followed by classification symbols)  
 C11D  
 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
 EPO-Internal, COMPENDEX, INSPEC, CHEM ABS Data, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 844 303 A2 (BUCK CHEMIE GMBH [DE]) 27 May 1998 (1998-05-27)  page 1, paragraph 1-3 page 2, paragraph 1-3 page 4, paragraph 3 - page 5, paragraph 1 page 8, paragraph 3 - page 9, paragraph 4; claims; example E2 page 5, paragraph 4-5 page 7, paragraph 2 page 14, last paragraph - page 15, paragraph 1 page 19, paragraph 4 ----- -/--	1-7, 9-11, 17-33

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

<p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier application or patent but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p>	<p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art</p> <p>"&amp;" document member of the same patent family</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Date of the actual completion of the international search  10 November 2016	Date of mailing of the international search report  17/11/2016
-----------------------------------------------------------------------------------	----------------------------------------------------------------------

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer  Marttin, Emmeline
----------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------

## INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2016/046176

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	<p>WO 2014/013234 A1 (RECKITT BENCKISER LLC [US]; RECKITT BENCKISER BRANDS LTD [GB]) 23 January 2014 (2014-01-23) page 1, paragraph 1 page 2, paragraph 2 - page 3, paragraph 3 page 4, paragraph 2-3 page 6, paragraph 2 - page 7, paragraph 1 page 9, paragraph 2-3 page 12, paragraph 2 - page 15, paragraph 1 page 22, last paragraph - page 23, paragraph 3 page 35, paragraph 2-3; claims; examples E11, E19-22; tables 1,2 page 25, line 10 page 40, last paragraph - page 41, paragraph 2</p> <p style="text-align: center;">-----</p>	1-33
Y	<p>US 2013/338227 A1 (SAINT VICTOR MARIE-ESTHER [US] ET AL) 19 December 2013 (2013-12-19) paragraphs [0058] - [0601], [0012] - [0018], [0031], [0047] - [0051], [0069] - [0073], [0076] - [0079], [0082] - [0088], [0094] - [0096]; examples V-VII; tables 1,2,9,10,14,18,19</p> <p style="text-align: center;">-----</p>	1-33

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/046176

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0844303	A2	27-05-1998	AT 294849 T 15-05-2005
			DE 19648788 A1 04-06-1998
			DE 59712296 D1 09-06-2005
			EP 0844303 A2 27-05-1998
-----			
WO 2014013234	A1	23-01-2014	AU 2013291737 A1 17-04-2014
			AU 2013291739 A1 29-01-2015
			CA 2851441 A1 23-01-2014
			CA 2878320 A1 23-01-2014
			EP 2760485 A1 06-08-2014
			EP 2872185 A1 20-05-2015
			JP 2015529704 A 08-10-2015
			JP 2015532658 A 12-11-2015
			PH 12015500105 A1 02-03-2015
			RU 2014122337 A 10-12-2015
			RU 2015105003 A 10-09-2016
			US 2014298577 A1 09-10-2014
			US 2015159358 A1 11-06-2015
			WO 2014013234 A1 23-01-2014
WO 2014013236 A1 23-01-2014			
-----			
US 2013338227	A1	19-12-2013	AR 091433 A1 04-02-2015
			US 2013338227 A1 19-12-2013
			US 2015275138 A1 01-10-2015
			WO 2013188508 A1 19-12-2013
-----			