



US007871414B2

(12) **United States Patent**
Hardin, Jr.

(10) **Patent No.:** **US 7,871,414 B2**
(45) **Date of Patent:** **Jan. 18, 2011**

(54) **LOOP TIP WIRE GUIDE WITH OUTER SLEEVE**

(75) Inventor: **David M. Hardin, Jr.**, Winston-Salem, NC (US)

(73) Assignee: **Wilson-Cook Medical Inc.**, Winston-Salem, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 319 days.

(21) Appl. No.: **11/966,497**

(22) Filed: **Dec. 28, 2007**

(65) **Prior Publication Data**

US 2009/0171367 A1 Jul. 2, 2009

(51) **Int. Cl.**
A61F 11/00 (2006.01)

(52) **U.S. Cl.** **606/108**; 600/585; 604/93.01; 604/164.01; 604/264; 604/272

(58) **Field of Classification Search** None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,107,852 A * 4/1992 Davidson et al. 600/585
5,333,620 A * 8/1994 Moutafis et al. 600/585
5,797,856 A * 8/1998 Frisbie et al. 600/585
2004/0106878 A1 6/2004 Skujins et al.

2004/0167442 A1 8/2004 Shireman et al.
2004/0199088 A1 * 10/2004 Bakos et al. 600/585
2005/0054952 A1 3/2005 Eskuri et al.
2006/0100545 A1 * 5/2006 Ayala et al. 600/585
2007/0135734 A1 6/2007 Reynolds et al.

FOREIGN PATENT DOCUMENTS

EP 1 346 747 A2 9/2003
EP 1 525 896 A2 4/2005
EP 1 847 289 A2 10/2007
WO WO 2005/014094 A1 2/2005
WO WO 2006/039217 A1 4/2006

OTHER PUBLICATIONS

PCT International Search Report for PCT/US2008/087112, filed Dec. 17, 2008.

PCT Written Opinion for PCT/US2008/087112, filed Dec. 17, 2008.

* cited by examiner

Primary Examiner—Todd E Manahan


Assistant Examiner—Naquan Ishman

(74) *Attorney, Agent, or Firm*—Brinks Hofer Gilson & Lione

(57) **ABSTRACT**

A wire guide has first and second portions with first and second diameters, respectively. The second portion is located distal of the first portion. A resilient loop positions a distal end of the wire guide adjacent another section of the wire guide. A closure member maintains the distal end in a fixed position relative to the remainder of the wire guide. An outer sleeve may be positioned around one or more parts of the wire guide. A radiopaque element may be secured to the outer sleeve.

23 Claims, 3 Drawing Sheets






FIG. 1




FIG. 2




FIG. 3




FIG. 6




FIG. 5




FIG. 4

1

LOOP TIP WIRE GUIDE WITH OUTER SLEEVE

FIELD OF THE INVENTION

The present invention relates to wire guides used in the placement of medical devices. More specifically, the present invention relates to a wire guide having a loop tip.

BACKGROUND OF THE INVENTION

Wire guides are elongate flexible members used to provide a path along which another medical device can be moved. The path provided by the wire guide can be used to navigate another medical device, such as a catheter, through a body vessel. The use of wire guides to define such a path is known in the art. Briefly, a wire guide is navigated through a body vessel toward a point of treatment. Once positioned within the vessel, a second medical device, frequently a cannula such as a catheter, is placed over the wire guide and moved along its length toward the point of treatment. Thus, the wire guide provides an established path for placing other devices, eliminating the need for performing delicate navigation procedures for each device passed into the body lumen.

During placement of a wire guide, an operator must navigate the wire guide through the body lumen. Often, the body lumen defines a tortuous path due to the presence of natural bends and/or curves, or unnatural impediments, such as tumors, build-ups, and/or strictures. The presence of a tortuous path may make navigation of a wire guide difficult. For example, the presence of an impediment may block the wire guide from navigating further into the body lumen. In addition, the presence of a tortuous path may make it difficult to determine the position of the wire guide within the body lumen.

There is an unmet need for a wire guide that can navigate a tortuous path having impediments in which the path and position of the wire guide can be reliably monitored during the navigation.

BRIEF SUMMARY OF THE INVENTION

In a first aspect, a wire guide capable of manipulation about at least one of a tortuous path and an impediment is provided. An elongate member having a first portion and a second portion is provided. The second portion is located distal of the first portion. A loop is provided having an interior space, wherein the loop is affixed to the second portion. An outer sleeve is disposed along at least a portion of the loop.

In a second aspect, a wire guide is capable of manipulation about at least one of a tortuous path and an impediment is provided. An elongate member having a first portion with a first diameter and a second portion with a second diameter smaller than the first diameter is provided. The second portion is located distal of the first portion. A loop having an interior space, wherein the loop is affixed to the second portion, is also provided. A neck portion has a third diameter at a widest point of the neck portion, the third diameter being greater than the second diameter and smaller than the first diameter. The neck portion is positioned between the first portion and the second portion. A first outer sleeve is disposed along a loop and a second outer sleeve is disposed along the neck portion.

In a third aspect, the loop of the wire guide comprises a radiopaque member disposed thereover. The radiopaque member provides the loop tipped wire guide with enhanced radiopacity and/or other properties.

2

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of a wire guide according to a first embodiment of the invention in which an outer sleeve is wrapped around the loop portion of the wire guide;

FIG. 2 is a side view of the outer sleeve shown as unbent;

FIG. 3 is a side view of a wire guide according to a second embodiment of the invention in which two outer sleeves are disposed over the distal end of the wire guide; and

FIGS. 4-6 are variants of a loop tip wire guide which may incorporate a first and a second outer sleeve.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 illustrates a wire guide 10 according to a first embodiment of the present invention. The wire guide comprises an elongate member 12 having a first portion 14 with a first diameter 16 and a second portion 18 with a second diameter 20. The second portion 18 is located distal of the first portion 14. The second diameter 20 is smaller than the first diameter 16. The elongate member 12 has an intermediate portion 21 that defines a taper from the first diameter 16 to the second diameter 20.

The elongate member 12 defines a loop 22 which is closed by closure member 29. In the presently preferred embodiment, the loop 22 comprises a section of the elongate member 12 bent back upon itself. As illustrated in FIG. 1, the second portion 18 preferably defines the entire loop 22. Alternatively, the second portion 18 may define only a portion of the loop 22, and an intermediate portion 21 defines at least a portion of the loop 22. The taper of the intermediate portion 21 provides additional flexibility to the wire guide 10, facilitating navigation of the loop 22 through the tortuous path.

Preferably, as illustrated in FIG. 1, the loop 22 comprises a curvilinear loop forming a generally ovoid shape. Also preferably, the loop 22 has a loop width 23 that is greater than the first diameter 16 of the first portion 14 of the elongate member 12. The term 'loop width' as used herein refers to the distance between the two outer most surfaces of the bent sleeve 80 (discussed below) disposed about the elongate member 12 at the widest portion of the loop 22.

The elongate member 12 has a distal end 26 and a distal tip 28. Preferably, the distal tip 28 tapers from the second diameter 20 to a smaller diameter, and preferably tapers to a point. As illustrated in FIG. 1, the loop 22 is preferably formed in a manner that positions the distal end 26 adjacent the intermediate portion 21. Preferably, this placement also positions the distal tip 28 adjacent the intermediate portion 21. Such placements provide a low profile over the portion of the elongate member 12 that has a double width (i.e., two sections of the elongate member 12). Other embodiments are contemplated in which the distal end 26 is positioned adjacent to the first portion 14 or the second portion 18 of the elongate member 12.

Any method of forming the loop 22 is contemplated. In one preferred embodiment, the closure member comprises a coil 29. More specifically, two sections of the elongate member 12 are wound about each other. Preferably, the distal end 26 is wound such that a low profile is achieved.

FIG. 1 shows an outer sleeve 80 slidably disposed along the loop 22. The term "sleeve" as used herein refers to any discrete structure adapted to be disposed about the loop 22, including but not limited to a coiled structure, a cylindrical structure, or a helical structure. The outer sleeve 80 may be sufficiently radiopaque so as to allow a physician or other operator to fluoroscopically observe the loop 22 as it is being navigated through a body lumen. The term "radiopaque" as

used herein refers to any type of material or structure that blocks radiation from being transmitted therethrough, thereby making the material or structure visible under x-rays.

FIG. 2 shows the outer sleeve **80** in an unbent configuration and unattached to the loop **22** of the wire guide **10**. The outer sleeve **80** comprises a first end **81**, a second end **82**, and a body portion **83** extending between the first and second ends **81** and **82**. Preferably, the outer sleeve **80** is slidably disposed over the entire loop **22**, as shown in FIG. 1, so as to increase the radiopacity of the entire loop **22**.

The inner diameter **84** (FIG. 2) of the outer sleeve **80** may be assembled onto the loop **22** as follows. The wire guide **10** is extended linearly out so as to create a single, tapered wire having a first diameter **16** at a first portion **14**, a second diameter **20** smaller than the first diameter **16** at a second portion **18**, and an intermediate portion **21** between the first diameter **16** and the second diameter **20**. The outer sleeve **80** may then be slid over the distal end of the wire guide **10** so as to position the outer sleeve **80** about the second portion **18**. With the outer sleeve **80** secured over the second portion **18**, the second portion **18** and the outer sleeve **80** are bent to create the loop **22** as shown in FIG. 1. The distal end **26** of the second portion **18** is then wound about the intermediate portion **21**. The distal tip **28** of the second portion **18** rests at the intermediate portion **21**. The inner diameter **84** of the outer sleeve **80** is less than the first diameter **16** of the first portion **14**. As a result, the outer sleeve **80** need not be further secured to the wire guide **10**. The first and second ends **81** and **82** of the outer sleeve **80** remain freely movable about the second portion **18**. Having the outer sleeve **80** slidably disposed about the second portion **18** maintains the flexibility of the loop **22** as the wire guide **10** encounters impediments along a tortuous body lumen.

Other means for securing the outer sleeve **80** onto the loop **22** are contemplated. For example, the sleeve **80** may be affixed onto the second portion **18** of the loop **22** by the use of adhesives, fusion bonding (i.e., annealing at elevated furnace temperatures as to create a solid bond), or soldering. Such securing means may alter the flexibility and resiliency of the loop **22** as needed. Other means for securing the sleeve **80** may be used as known to one of ordinary skill in the art.

The sleeve **80** may be made from any type of biocompatible material. In one embodiment, the material may be a suitable thermoplastic polymer such as high density polyethylene (HDPE), polytetrafluorethylene (PTFE), polyethylene ethyl ketone (PEEK), polymethylmethacrylate (PMMA), polyimide, Ethylene Tetrafluoroethylene (ETFE), and polyether block amides. For use with guide wires, the polymer layer has a thickness ranging from about 0.001 to about 0.01 inches, and more preferably about 0.002 to about 0.005 inches. Such a thickness allows the loop **22** to retain flexibility.

The outer sleeve **80** may comprise a radiopaque element **89** disposed along the body portion **83** (FIG. 2). The sleeve **80** and radiopaque element **89** may be formed from any number of suitable materials and possess any number of suitable structures. In a preferred embodiment, the outer sleeve **80** is formed from a tungsten coiled structure, and elemental gold is secured onto the outer sleeve **80** by electroplating the elemental gold onto the tungsten coiled structure. The term "secured" as used herein is intended to encompass any means by which a radiopaque element may be bounded to a sleeve, including but not limited to embedding, anchoring, chemically bonding, physically bonding, heat bonding, soldering, welding, impregnating, plating, and dip coating a radiopaque element to a sleeve **80**. The electroplating process involves using electrical current to deposit onto the tungsten coil a relatively thin layer of elemental gold. The current density,

which is determined by the ratio of the electroplating current and the surface area of the tungsten coil to be plated, may determine the deposition rate of the elemental gold, the electroplating adherence of the elemental gold, as well as the overall quality of the electroplating of the elemental gold. The plating of elemental gold onto the tungsten coil may provide enhanced fluoroscopic imaging.

In another plating process, the entire exterior of the tungsten coiled structure may be plated with the radiopaque material (e.g., elemental gold). Afterwards, the electroplated material is selectively removed from the sleeve **80** by laser ablation, chemical etching, mechanical abrasion or grinding. The thickness of the electroplating material may range from about 0.1 to about 30 microns. Alternatively, the above-described electroplating process may be performed so as to deposit bands of radiopaque material onto the tungsten coiled structure. Selected areas of the tungsten coiled structure are masked so as to prevent electroplating thereon.

Other radiopaque materials such as bismuth, platinum, tin, tantalum, iridium, barium and the like can be secured to the outer sleeve **80**. The radiopaque materials may be secured to any surface of the outer sleeve **80**.

Securing the radiopaque element **89** to the outer sleeve **80** may be achieved in other ways as well. For example, the radiopaque element **89** may be embedded into the sleeve **80**. A mandrel may be used to set the shape of the sleeve **80**. After establishing the shape of the sleeve **80**, the radiopaque element **89** is applied to the sleeve **80**. Alternatively, the radiopaque element **89** may lie over the sleeve **80** and suitable heat shrink material may be applied over the radiopaque element **89** and the sleeve **80**.

In yet another embodiment, the radiopaque element **89** may be formed from a shape memory material that is embedded or impregnated into the sleeve **80**. For instance, the radiopaque element **89** may be formed from NITINOL, which is a radiopaque nickel-titanium alloy. In one embodiment, the NITINOL may be a cylindrical band that is embedded within the sleeve **80** by utilizing the thermally induced deformation or recovery of the shape memory alloy. Initially, the cylindrical band would have an outer diameter substantially equal to or less than the outer diameter **85** of the sleeve **80**. The cylindrical band may then be cooled (e.g., by any conventional cooling method such as liquefied nitrogen) to a sufficiently low temperature below the shape recovering transition temperature so as to cause the shape forming material to become capable of physical deformation to an expanded diameter. While the cylindrical band is at the low temperature, it may be deformed into a deformed, expanded configuration that has a larger diameter than the original configuration. The larger diameter deformed cylindrical band may be obtained by applying a radial outward force to the inner surface of the band by, for example, a shaping rod through the center bore of the band. Once the band has been formed from its original configuration into its deformed configuration as represented by the deformed cylindrical band, the deformed band is positioned concentrically around the outer surface of the sleeve **80**.

Prior to raising the temperature of the NITINOL cylindrical band, a supporting mandrel is inserted through the passageway **88** (FIG. 2) of the sleeve **80** so as to extend longitudinally along the band beyond both ends **81** and **82** of the sleeve **80**. The temperature of the NITINOL band is then raised above its predetermined transition temperature using, for example, hot air. As the band is raised to a temperature above the shape transition temperature, the band begins to return to its smaller diameter original configuration by moving radially inward into contact with the outer radial surface

5

of the tubular sleeve **80**. Continued movement by the band radially inwardly causes the inner surface of the band to press against outer radial surface of the sleeve **80**. Simultaneously, the temperature of the band is high enough to soften and melt the sleeve **80** material immediately adjacent the band, thereby causing the band to sink into the material of the sleeve **80** until it reaches its original configuration. During the thermally induced deformation or shape recovery process into the original configuration, the support rod supports the inner radial surface of the sleeve against the radially inward force of band thereby maintaining the inner diameter **84** of the sleeve **80**. The support rod is then removed resulting in the NITINOL marker securely embedded into the material of the sleeve **80**.

Embedding the NITINOL band into the sleeve **80** is advantageous in that the cylindrical NITINOL band melts its way into embedded engagement with the sleeve **80** when moving into a physical rigid configuration, thereby not requiring any adhesives or other less dependable securing means for holding the band in place. Additionally, by sizing the band so that the outer diameter of the original configuration is no greater than the outer diameter of the sleeve **80**, the NITINOL marker band can be effectively attached to the sleeve **80** without increasing the sleeve's dimensional changes or creating transitions such as ridges on the outer surface of the sleeve **80**. Accordingly, a smooth outer radial surface of the sleeve **80** is maintained, thereby allowing easier navigation of the wire guide **10** through the body lumen.

Other means for embedding or impregnating radiopaque material into sleeve **80** include utilizing radiopaque inks, or the use of radiopaque shrink wrap or tubing over the sleeve **80** (e.g., radiopaque urethane). Alternatively, the sleeve **80** may be dipped into a solution of radiopaque polymer or loaded with radiopaque powder such as tungsten. In another embodiment, the inner diameter of a radiopaque element **89** is affixed to the outer diameter **85** of the sleeve **80** by a heat bond. The region of the sleeve **80** where the radiopaque element **89** is to be bonded is heated and slightly stretched down to enable slidably mounting the band onto the stretched down area.

In addition to the above-described structures for radiopaque element **89**, the radiopaque element **89** may possess other types of structures. In one embodiment, the radiopaque element **89** may take the form of ribbons, discrete bands, beads, or strips of foils embedded in the sleeve **80** or affixed to a surface of the sleeve **80**. The cross sectional shape of the radiopaque element **89** could be a rectangle, square, ovoid, circle, or the like. Alternatively, the radiopaque element **89** may be a cylindrical sleeve or a helical coil, both of which may be used without the sleeve **80**.

Prior to securing the sleeve **80** with the radiopaque element **89**, an electrically insulative material **99** is preferably disposed over the outer surface of the sleeve **80** comprising the radiopaque element **89**. Any electrically insulative material **99** may be utilized as known in the art. In a preferred embodiment, the electrically insulative material **99** comprises ethylene tetrafluoroethylene (ETFE). Preferably, the ETFE is extruded. The ETFE extrudate **99** may be disposed over the sleeve **80** in which the sleeve **80** preferably is a gold plated tungsten coil. The ETFE extrudate **99** serves as an electrical insulator which allows the material to be used with electro-surgical devices. ETFE is a thermoplastic copolymer derived from the polymerization of ethylene and tetrafluoroethylene monomers. The resin is abrasion resistant, possesses a relatively high dielectric strength compared to other plastics and has a relatively low coefficient of friction. Because of its high dielectric strength, the ETFE extrudate **99** is a suitable electrical insulator for use in wire guided applications in which an electrical medical device (e.g., cautery catheter) is advanced

6

over the wire guide **10**. The ETFE extrudate **99** as an electrical insulator may prevent electrical current from jumping onto the wire guide **10**. The ETFE extrudate **99** is preferably extruded over the outer sleeve **80** (e.g., preferably a tungsten coil) having a radiopaque element **89** in the form of elemental plated gold. In preferred embodiments, the thickness of the ETFE extrudate is between approximately 0.001 and 0.010 inches. In particularly preferred embodiments, the thickness of the extrudate is between approximately 0.001 and 0.005 inches. In still more preferred embodiments, the thickness of the extrudate is between approximately 0.001 and 0.002 inches. [David, please confirm. These preferred thicknesses provide suitable ETFE extrudate thicknesses while not adding significantly to the overall thickness of the device. Other fluoropolymers, polyurethanes, and other suitable electrically insulative materials as are known and used in the medical device arts may be utilized.

In another preferred embodiment, the radiopacity may be further enhanced by adding an additional radiopaque structure to the wire guide of FIG. 1. FIG. 3 shows that a second outer sleeve **90** has been added along the neck or intermediate portion **21**. The second outer sleeve **90** may comprise a radiopaque element **91**. Any radiopaque material may be used for the second outer sleeve **90**. Preferably, the second outer sleeve **90** is a platinum coil spring. The platinum coil spring is slidably disposed over the intermediate portion **21**. The platinum coil is positioned along the intermediate portion **21** so as to be adjacent to the first outer sleeve **80**, which preferably also possesses a radiopaque element **89**. The platinum coil has a first end **93** which is in close proximity to sleeve **80**. The platinum coil has a second end **92** which preferably extends proximally along the intermediate portion **21**. The platinum coil may cover the entire intermediate portion **21**, as shown in FIG. 3. Preferably, the platinum coil will have a length ranging from about 3 centimeters to about 5 centimeters.

The platinum coil has an inner diameter **95** which is larger than the outer diameter of the intermediate portion **21** at its widest point and smaller than the outer diameter (i.e., first diameter **16**) of the first portion **14**. Such a sized platinum coil enables it to remain entrapped along the intermediate portion **21** yet remain slidably disposed along the intermediate portion without reducing the flexibility of the wire guide **10**. The platinum coil may be assembled onto the intermediate portion **21** by introducing it from the proximal end of the wire guide **10**. The second outer sleeve may be formed from other radiopaque materials known to one of ordinary skill in the art besides platinum. Additionally, the second outer sleeve **90** may comprise various other structures besides a coiled structure.

Although sleeves **80** and **90** have been described with reference to the loop tip wire guide of FIG. 1, the radiopaque sleeves **80** and/or **90** may be secured to other variations of a loop tip wire guide. For example, FIGS. 4 and 5 represent other types of loop tip wire guides which may have sleeves **80** and **90** disposed therealong, in which the sleeves **80** and/or **90** may be radiopaque. For example, FIG. 4 shows a loop tip wire guide in which two sections of the elongate member **12** are welded or soldered together to form a loop **22**. Additionally, sleeve **80** may be configured about the loop **22** of FIG. 6, which shows the closure member **24** as a cannula closing the loop **22** and fixing the loop **22** in overall size. Sleeves **80** and **90** are shown disposed about the loop tip wire guide of FIG. 5. FIG. 5 shows a closure member having a molded bond **25** in which the loop **22** of the wire guide **10** is formed by molding two sections of the elongate member **12** together.

Any suitable material can be used for the elongate member **12**, and a variety of suitable materials are known to those

skilled in the art. The material chosen need only be biocompatible and able to be formed into the structures described herein. Examples of suitable materials include stainless steel and NITINOL. The elongate member **12** may comprise a wire, a tubular member or a sheet of material. Further, the elongate member **12** can be formed of a series of layers, or as a coated core structure. For example, in one embodiment, the elongate member **12** comprises a NITINOL core with a ETFE covering.

A variety of shapes and sizes of elongate members and loops can be used, and these can both be optimized based on particular applications. The dimensions of the elongate member **12** and loop **22** will depend upon various factors, including the intended use of the wire guide and the vessels into which the wire guide will be positioned. For a wire guide intended to cannulate the common bile duct, suitable dimensions include a first diameter **16** of between approximately 0.016 inches and approximately 0.038 inches, and preferably comprises a diameter of approximately 0.035 inches. The second diameter **20** of the wire guide preferably has a diameter of between approximately 0.003 inches and approximately 0.010 inches, and preferably comprises a diameter of approximately 0.006 inches. The intermediate portion of this wire guide defines a taper between the first diameter **16** and the second diameter **20**. The taper may be smaller or approximately the same size as the second diameter **20**. Preferably, the intermediate portion defines a taper from approximately 0.006 inches to approximately 0.016 inches. For this wire guide, the loop is preferably ovoid in shape with a length of between approximately 4 millimeters and approximately 5 millimeters, and a width of between approximately 2 millimeters and approximately 3 millimeters.

Also, the outermost surface of the wire guide **10**, may be treated with a hydrophilic coating or hybrid polymer mixture, such as those based on polyvinyl puroladine and cellulose esters in organic solvent solutions. These solutions make the wire guide particularly lubricious when in contact with body fluids, which aids in navigation.

As illustrated in the figures, the loop **22** is preferably formed by the elongate member **12**. As an alternative, a separate member defining the loop can be affixed to a substantially straight elongate member to form the wire guide of the present invention. This may be advantageous when it is desirable to form the loop and elongate member of different materials. For example, a nylon or silicon loop could be formed and attached, such as by a closure member, to an elongate member formed of NITINOL. Such an assembly could be associated with the outer sleeves **80** and/or **90** as described above, in which a radiopaque element **80** and **91** are secured to their respective outer sleeves **80**, **90** for enhanced radiopacity. Additionally, suitable heat shrink material, such as TEFLON, may be applied over a portion of the loop **22** to create a streamlined low profile.

As can be seen, utilizing outer sleeves **80** and/or **90**, which have radiopaque elements, ensures reliable monitoring of the position of the wire guide **10** during navigation within a body lumen to ensure that the wire guide **10** is advanced along the intended path.

While preferred embodiments have been described, it should be understood that the preferred embodiments are intended to be limiting in any way, and modifications may be made without departing from the invention. The scope of the invention is defined by the appended claims, and all devices that come within the meaning of the claims, either literally or by equivalence, are intended to be embraced therein. Furthermore, the advantages described above are not necessarily the only advantages of the invention, and it is not necessarily

expected that all of the described advantages will be achieved with every embodiment of the invention.

The invention claimed is:

1. A wire guide capable of manipulation about at least one of a tortuous path and an impediment comprising:
 - an elongate member having a first portion and a second portion, wherein the second portion is located distal of the first portion;
 - a loop defining an interior space, wherein the loop is affixed to the second portion; and
 - an outer sleeve movably disposed along at least a portion of the loop, wherein the first portion of the elongate member has a first diameter and the loop has a second diameter that is smaller than the first diameter.
2. The wire guide of claim 1, wherein the loop is closed by a closure member.
3. The wire guide of claim 1, wherein the outer sleeve is slidably disposed along the loop.
4. The wire guide of claim 1, wherein the outer sleeve comprises a first end and a second end and a body portion extending between the first end and the second end, the body portion being wound around the loop.
5. The wire guide of claim 1, wherein the outer sleeve comprises a radiopaque element.
6. The wire guide of claim 5, wherein the outer sleeve has an inner diameter, the inner diameter being smaller than the first diameter of the first portion of the elongate member and larger than the second diameter of the loop.
7. The wire guide of claim 5, wherein the outer sleeve is disposed within an electrically insulative material.
8. The wire guide of claim 7, wherein the electrically insulative material is formed from ethylene polytetrafluoroethylene (ETFE).
9. The wire guide of claim 5, further comprising a means for securing the radiopaque element to the outer sleeve.
10. The wire guide of claim 5, wherein the outer sleeve comprises tungsten, further wherein the outer sleeve comprises a coiled structure.
11. The wire guide of claim 10, wherein the outer sleeve is plated with elemental gold.
12. The wire guide of claim 11, wherein the outer sleeve wraps around the entire loop, such that the first end and the second end of the outer sleeve rests against an apex of the loop.
13. The wire guide of claim 5, wherein the radiopaque element comprises radiopaque beads, ribbons, discrete bands, strips of foils, or any combination thereof secured to the outer sleeve.
14. The wire guide of claim 5, wherein the outer sleeve imparts flexibility and resiliency to the loop.
15. The wire guide of claim 1, wherein the second portion of the elongate member is bent back upon itself to form the loop.
16. The wire guide of claim 1, further comprising a second outer sleeve, the second outer sleeve being disposed adjacent to the loop.
17. A wire guide capable of manipulation about at least one of a tortuous path and an impediment comprising:
 - an elongate member having a first portion with a first diameter and a second portion with a second diameter, the second diameter being smaller than the first diameter, wherein the second portion is located distal of the first portion;
 - a loop having an interior space, wherein the loop is affixed to the second portion;

9

a neck portion having a third diameter at a widest point of the neck portion, the third diameter being greater than the second diameter and smaller than the first diameter, the neck portion being positioned between the first portion and the second portion;

a first outer sleeve movably disposed along the loop; and a second outer sleeve fixedly disposed along the neck portion.

18. The wire guide of claim **17**, wherein an electrically insulative material is disposed about and substantially encloses each of the first and the second outer sleeves, the material being formed from ethylene polytetrafluoroethylene (ETFE).

10

19. The wire guide of claim **17**, wherein the second outer sleeve has a longitudinal length of about 5 centimeters.

20. The wire guide of claim **17**, wherein the loop comprises a first degree of radiopacity and the first outer sleeve comprises a second degree of radiopacity greater than the first degree of radiopacity.

21. The wire guide of claim **20**, wherein the second degree of radiopacity comprises gold plated on a tungsten coil.

22. The wire guide of claim **20**, wherein the second outer sleeve comprises a third degree of radiopacity greater than the first degree of radiopacity.

23. The wire guide of claim **22**, wherein the third degree of radiopacity comprises a platinum coil.

* * * * *