

A. ALVAREZ.
BLADE FOR SAFETY RAZORS.
APPLICATION FILED JULY 12, 1910.

991,594.

Patented May 9, 1911.

Fig. 1.




Fig. 2.




Fig. 3.



Fig. 4.





Fig. 5.



WITNESSES:

G. V. Rasmussen
John A. Wahlenbeck

INVENTOR
Alfonso Alvarez
BY
Briesen & Knautz
ATTORNEYS

UNITED STATES PATENT OFFICE.

ALFONSO ALVAREZ, OF NEW YORK, N. Y.

BLADE FOR SAFETY-RAZORS.

991,594.

Specification of Letters Patent.

Patented May 9, 1911.

Application filed July 12, 1910. Serial No. 571,577.

To all whom it may concern:

Be it known that I, ALFONSO ALVAREZ, a citizen of the United States, and resident of the borough of Manhattan, city, county, and State of New York, have invented certain new and useful Improvements in Blades for Safety-Razors, of which the following is a specification.

My invention relates to blades for safety razors and has for its object to provide a blade which may be readily stropped and honed if desired.

To this end my improved blade comprises two sections pivotally secured together and capable of being opened out so as to present one long substantially continuous edge to the strop or hone instead of two short edges as is the case in existing constructions.

My invention will be fully described hereinafter and the features of novelty will be pointed out in the appended claims.

Reference is to be had to the accompanying drawings in which—

Figure 1 is a horizontal section of a safety razor with my improved blade in position thereon; Fig. 2 is a plan view of the blade with the blade sections opened out; Fig. 3 is an edge view thereof; Fig. 4 is a face view of another form of blade; and Fig. 5 is a plan view of the blade showing a different form of recess.

In the drawings 10 represents the usual shank which carries the back plate 11 and is arranged to be detachably connected with the handle to secure the blade in position. The back plate 11 is provided with the customary studs 12 for preventing any lateral movement of the blade. In the form of my invention shown in Figs. 1, 2, and 3 the blade comprises two sections 13 and 14 pivotally secured together at one end as indicated at 15. The ends of each section 13 and 14 adjacent to the pivot 15 are preferably thinned down so as to secure a flush connection, the heads of the pivot 15 being also preferably made flush with the opposite surfaces of the sections 13 and 14. The free ends of each section 13 and 14 are adapted to overlap when the blade is in position in the holder and are hook shaped as indicated at 16 so as to extend partly around the one stud 12 and thus prevent the blade sections from accidentally spreading or opening apart. Each blade section is further formed at its inner edge with a recess 17 adapted to partly surround the other

stud 12 and a further central recess 18 arranged to partly surround the shank 10, as clearly shown in Fig. 1.

When it is desired to hone or strop the blade the same is removed from its support and opened up as indicated in Fig. 2. In this condition the cutting edges of the two sections are in alinement and form a substantially continuous cutting edge which is easily honed or stropped in the same manner as an ordinary razor, it being understood of course that the blade in its open condition is secured or clamped in a holder of suitable construction. If desired the said blade in its open or unfolded condition and while it is in this position in the holder may be used as an ordinary razor. When it is desired to again use the blade as a safety razor it is first folded as indicated in Fig. 1 and then again clamped in position on the studs 12 and the usual safety razor handle.

The form of blade shown in Fig. 4 differs from the one just described in that the blade sections 13 and 14 overlap at two intermediate points as 19 and 20. With this construction the blade sections extend farther around the studs 12 and shank 10 and are more firmly held against spreading when in operative position on the holder.

In both of my structures the blade sections are easily unfolded to present a relatively long cutting edge which is easy to strop and hone without necessitating the use of a complex and expensive stropping machine. The life of each blade is considerably increased as each individual user may readily and continuously keep said blades in proper working condition. It is of course to be understood that as shown in Fig. 5 the inner edges of said sections may be straight instead of recessed or may be otherwise shaped if desired.

Various modifications may be made within the scope of the claims without departing from the spirit of my invention.

I claim:

1. A blade for safety razors comprising two connected sections each having a cutting edge and so arranged that the cutting edges may lie adjacent each other or opposite each other.

2. A blade for safety razors comprising two pivotally connected sections each having a cutting edge and so arranged that the cutting edges may lie adjacent each other or opposite each other.

3. A blade for safety razors comprising two sections pivotally connected at one end and having their opposite ends free, each section having a cutting edge.
- 5 4. A blade for safety razors comprising two sections pivotally connected at one end and having their opposite ends free and hook shaped, each section having a cutting edge.
- 10 5. A blade for safety razors comprising two sections pivotally connected at one end and having their opposite ends arranged to overlap, each section having a cutting edge.
6. A blade for safety razors comprising two separate connected sections each having 15 a cutting edge and movable relatively to each other to form either separate cutting edges or a single substantially continuous cutting edge.
- In testimony whereof I have hereunto set 20 my hand in the presence of two subscribing witnesses.

ALFONSO ALVAREZ.

Witnesses:

JOHN A. KEHLENBECK,
M. H. LOCKWOOD.