




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B21D 5/04	A1	(11) International Publication Number: WO 96/04084 (43) International Publication Date: 15 February 1996 (15.02.96)
(21) International Application Number: PCT/EP95/02794 (22) International Filing Date: 17 July 1995 (17.07.95) (30) Priority Data: TO94A000635 29 July 1994 (29.07.94) IT (71) Applicant (for all designated States except US): SAPIM AMADA S.P.A. [IT/IT]; Viale Vicenza, 29, I-36045 Lonigo (IT). (72) Inventor; and (75) Inventor/Applicant (for US only): CODATTO, Antonio [IT/IT]; Via Venezia, 21, I-36045 Lonigo (IT). (74) Agents: SACONNEY, Piero et al.; Jacobacci & Perani S.p.A., Corso Regio Parco, 27, I-10152 Torino (IT).		(81) Designated States: CA, JP, SI, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published With international search report.

(54) Title: BENDING PRESS FOR SHEET METAL

(57) Abstract

The press comprises two tool holders facing each other (28a, 28b), capable of relative movement one towards the other and back again. Each tool holder carries a bending tool (40a, 40b) and a clamping tool (42a, 42b). The tool holders (28a, 28b) are in addition capable of relative movement between two working positions in one of which the rear edge (46a) of a tool holder (28a) is so positioned as to cooperate, in order to bend the sheet (L) in a first direction, with a front edge (44b) of the bending tool (40b) of the other tool holder (28b), and the clamping tool (42b) of the other tool holder (28b) is immediately opposite the tool of the first tool holder (28a) in order to cooperate with it through the interposed sheet (L). In the other working position, the functions of the edges of the bending tools and the functions of the clamping tools are reversed in order to carry out the bend in the other direction. The clamping tools (42a, 42b) are mounted in their tool holders in such a way that they retreat against the force of means of elastic repulsion (50a, 50b).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Bending press for sheet metal

The present invention relates to a bending press for sheet metal of the type defined in the preamble of Claim 1.

The invention has been designed for application in the bending of very thick sheet metal, for example 5-10 mm thick, but is not limited to this application.

The principle object of the invention is to produce a versatile bending press of simple design that can carry out bends in one direction or the other, as desired, relative to a plane in which the sheet lies, and that can carry out these bends at any angle within a range from 0 to 90°.

According to the invention this object is achieved by means of a press such as that claimed.

By virtue of this solution to the problem, the press can be selectively set in order to bend the sheet in one direction or the other simply by relatively displacing the tool holders, in the direction of introduction of the sheet, from one working position to the other. The angle of bending can be set simply by adjusting the relative working stroke of the tool holders in the direction normal to the plane in which the sheet lies.

The invention will be understood more clearly from the detailed description which follows of a preferred embodiment of the bending press, which description is given with reference to the appended drawings which are provided by way of nonlimiting example and in which:

- Figure 1 is a perspective view of the press,
- Figure 2 is a side view thereof on a larger scale and in partial cross-section,

- Figures 3a, 3b, 3c, 3d, 3e and 3f are side views on a reduced scale showing successive stages in a so-called "negative" bending operation, and
- Figures 4a, 4b, 4c, 4d, 4e and 4f are views similar to the preceding ones, showing successive stages in a so-called "positive" bending operation.

With reference to Figure 1, a bending press according to the invention is indicated overall by the reference numeral 10.

The press 10 is associated with a table 12 that feeds the sheets to said press.

The table 12 has a horizontal upper support surface 14 of the known type with balls 16. The upper surface 14 is divided up into various parts by longitudinal channels 18 and by a transverse channel 20.

Pushers 22 can move backwards and forwards within the longitudinal channels 18, in the direction of the double arrows X, so as horizontally to feed a sheet to be bent into the press 10 and correctly position it in the place where the bend is to be carried out.

The double arrows X also conventionally indicate the direction of introduction of the sheet to be bent in the press, details of which direction will be discussed below.

Abutment elements 24, that serve to centre the sheets transversely with respect to the press 10, can move towards one another and back again in the transverse channels. The direction of movement of the abutment elements 24 is indicated by the double arrows Y, which also conventionally indicate the direction parallel to the bends to be carried

out by the press 10. Details of the direction Y will also be discussed below.

The directions X and Y also define a horizontal plane in which the sheet to be bent lies.

Still with reference to Figure 1, the press 10 comprises a sturdy base 26 on which a first immovable lower tool holder 28a is fixed, which will be described in detail when referring to Figure 2.

The base 26 carries a slide in the form of clevis pads 30 that slide on the base 26 in the direction X of introduction of the sheet in the press. This direction X is again indicated by a double arrow. Associated with each clevis 30 are means for controlling its movements backwards and forwards in the direction X. Preferably, these control means take the form of hydraulic jacks 32, as illustrated.

A sturdy frame 34 is hinged about horizontal pins 35, which are parallel to the transverse direction Y, in the clevis pads 30 constituting the slide.

Control means, preferably in the form of hydraulic jacks 36, are interposed between the slide 30 and the frame 34.

A sturdy transverse plate 38 is fixed on that side of the frame 34 which faces the table 12 and is opposite the side with the pins 35. On its lower side the plate 38 carries a second movable upper tool holder 28b which faces the immovable lower tool holder 28a. The upper tool holder 28b will be described in greater detail below with reference to Figure 2.

For now, suffice it to say that the control means 36 are

able to cause the tool holder 28b to move back and forth in an upward and downward movement, substantially in the vertical direction indicated by the double arrow Z, so as to bend the sheets that are introduced into the press, in conjunction with the immovable lower tool holder 28a.

The vertical direction Z is normal to the horizontal plane in which the sheet lies and which is defined by the directions X and Y.

Reference will now be made to Figure 2, in order to describe various details of the lower 28a and upper 28b tool holders.

A sheet which is to be bent or is in the course of being bent is illustrated by dashed lines and is indicated by the reference L.

Each lower 28a and upper 28b tool holder carries a corresponding bending tool 40a, 40b and a corresponding clamping tool 42a, 42b. Each bending tool 40a, 40b is in the form of a tempered steel bar that extends in the transverse direction Y across the entire width of the press and has active edges at the front 44a, 44b and rear 46a, 46b, respectively, the terms "front" and "rear" referring to the direction X of introduction of the sheet.

Preferably, as illustrated, the edges 44a, 44b and 46a, 46b are rounded in order to facilitate the progressive bending of thick sheets.

Each clamping tool 42a, 42b is preferably made up, as illustrated, of a series of pads 48a, 48b evenly distributed across the width of the press 10, i.e. in the transverse direction Y.

The pads 48a of the lower tool holder 28a are also visible in Figure 1.

The clamping tools 42a, 42b formed by the series of pads 48a, 48b respectively, are mounted in the relevant tool holders 28a, 28b in such a way that they retreat against the force of means of elastic repulsion.

Preferably, these means of elastic repulsion are in the form of respective hydraulic piston-and-cylinder units 50a, 50b. In each of these units, the cylinder 52a, 52b is formed in the relevant tool holder 28a, 28b, while the piston 54a, 54b carries the relevant pad 42a, 42b at one of its projecting ends that faces the opposite tool holder.

Each piston 54a, 54b is under an opposing hydraulic pressure exerted, through the interposed sheet L, by the bending tool 40a or 40b immediately opposite it. This concept will be clarified below.

As a result of its being mounted on the pivoting frame 34 secured to the slide 30, which is in turn operated by the jacks 32 (Figure 1), the upper tool holder 28b can be moved in the direction of the arrow X between two working positions which, as will be seen, serve to produce a downward, so-called "negative", bend and an upward, so-called "positive", bend respectively, in a sheet L.

In Figure 2 the two tool holders 28a, 28b and their bending tools 40a, 40b and clamping tools 42a, 42b are shown in solid lines in the position which corresponds to a "negative" bend.

The sheet L is gripped between the lower bending tool 40a and the upper clamping tool 40b. The upper bending tool 40b

is in a retracted position (towards the inside of the press) with respect to the lower bending tool 40a. This position is such as to cause the front active edge 44b of the upper tool 46b to cooperate with the rear active edge 46a of the lower tool 40a during the bending operation.

The sheet L simply rests on the clamping tool 42a, above which there is no bending tool.

In order to carry out a "negative" bend, a programmer or other control system, by controlling the relevant jacks 36, causes the upper tool holder 28b to execute reciprocating strokes of increasing amplitude so as to produce the bend in a succession of strokes.

Thus, in the outward movement of a first reciprocating stroke, the sheet is bent through a certain angle according to the configuration indicated by L_1 ; in the outward movement of a second reciprocating stroke, the sheet is bent through a greater angle, according to the configuration indicated by L_2 ; in the outward movement of a final reciprocating stroke, the sheet is bent through an angle of 90° according to the configuration indicated by L_3 .

As will be understood, by programming the number and amplitude of the reciprocating working strokes (for example by employing a digital control system), it is possible to produce any desired angle of bending, the angle of the bend being proportional to the number and amplitude of the successive reciprocating strokes.

As will also be understood, on each downward stroke of the upper tool holder 28b, the upper sheet-clamping tool 42b retreats elastically, by virtue of the fact that the pistons 54b can withdraw back into the cylinders 52b, whilst

still maintaining, by virtue of the hydraulic pressure, the mechanical pressure which grips the sheet L between the pads 48b and the lower bending tool 40a.

The sequence of operations for bending the sheet downwards or "inversely" is more clearly illustrated in Figures 3a, 3b, 3c, 3d, 3e and 3f.

In Figure 3a, the upper tool holder 28b has been set in the position corresponding to this type of bending and illustrated in solid lines in Figure 2.

In Figure 3b, the upper tool holder 28b executes a first downward movement in the direction of the arrow Z_1 so as to bend the sheet L through a first angle.

In Figure 3c, the upper tool holder 28b is raised in the direction of the arrow Z_2 until the upper sheet-clamping tool 48b is no longer in contact with the sheet L; the sheet is then made to advance a short distance in the direction of the arrow X_1 with a view to continuing the bending according to a curved configuration.

In Figure 3d, the upper tool holder 28b is lowered once again in a second working stroke in the direction of the arrow Z_3 in order to continue the bending.

In Figure 3e, the upper tool holder 28b is raised once again in the direction of the arrow Z_4 and the sheet L is made to advance a short distance once again in the direction of the arrow X_2 with a view to completing a 90°-bend.

In Figure 3f, the upper tool holder 28b is lowered for a third time in the direction of the arrow Z_5 in order to complete the 90°-bend in the sheet L.

In order to carry out an upward or "positive" bend in the sheet L, the upper tool holder 28b is brought, via the jacks 32, into the other working position, partially illustrated in dot-and-dashed lines in Figure 2.

In this other working position the functions of the edges of the bending tools and the functions of the clamping tools are reversed: the sheet L is gripped between the upper bending tool 40b and the lower clamping tool 42a; the bending is carried out between the rear edge 46b of the upper bending tool 40b and the front edge 44a of the lower bending tool 40a; on each downward stroke of the upper tool holder 48b, the lower clamping tool 42a retreats elastically under the thrust of the upper bending tool 40b, whilst still maintaining the mechanical pressure which grips the sheet L between the two tools; the upper clamping tool 42b, which in this particular situation is found to the left (in Figure 2) of the lower clamping tool 42a, i.e. close to the table 12 of Figure 1, simply retreats, withdrawing into the tool holder 28b without deforming that part of the sheet between the support surface 14 of Figure 1 and the lower clamping tool 42a.

The sequence of operations for bending the sheet upwards or "positively" is more clearly illustrated in Figures 4a, 4b, 4c, 4d, 4e and 4f.

In Figure 4a, the upper tool holder 28b has been set in the position corresponding to this type of bending and illustrated in dashed lines in Figure 2.

In Figure 4b, the upper tool holder 28b executes a first downward movement in the direction of the arrow Z_1 so as to bend the sheet L through a first angle.

In Figure 4c, the upper tool holder 28b is raised in the direction of the arrow Z_2 until the upper tools 40b, 48b are no longer in contact with the sheet L; the sheet L is then made to advance a short distance in the direction of the arrow X_1 with a view to continuing the bending according to a curved configuration.

In Figure 4d, the upper tool holder 28b is lowered once again in a second working stroke in the direction of the arrow Z_3 in order to continue the bending.

In Figure 4e, the upper tool holder 28b is raised once again in the direction of the arrow Z_4 and the sheet L is made to advance a short distance once again in the direction of the arrow X_2 with a view to completing a 90°-bend.

In Figure 4f, the upper tool holder 28b is lowered for a third time in the direction of the arrow Z_5 in order to complete the 90°-bend in the sheet L.

The detailed description given above and with reference to the drawings refers to a preferred embodiment of the bending press according to the invention in which the plane in which the sheet lies is horizontal and the direction normal to this plane is approximately vertical, and in which the press comprises an upper tool holder which can move both vertically, in order to carry out the bending strokes, and horizontally, in order to pass from an upward bending action to a downward bending action, whilst the lower tool holder is immovable.

Naturally, the invention extends to any press of the type claimed in which the aforesaid plane in which the sheet lies is not horizontal and the direction normal to this plane is not approximately vertical. Similarly, either of

the tool holders could be movable whilst the other is immovable or, alternatively, both tool holders could be capable of relative movement; either of the two tool holders could be displaceable between the two working positions in order to bend the sheet in one direction or the other, and either of the tool holders could execute the bending stroke.

CLAIMS

1. Bending press for sheet metal, especially thick sheet metal, of the type that comprises a first and a second tool holder facing each other (28a, 28b), capable of relative movement one towards the other and back again in a direction (Z) normal to a plane in which the sheet to be bent lies, and bending tools (40a, 40b) and clamping tools (42a, 42b) extending parallel to the bend that is to be made and transversely to a direction in which the sheet (L) to be bent is introduced into the press,

characterised in that each tool holder (28a, 28b) carries a bending tool (40a, 40b) and a clamping tool (42a, 42b) of which, with reference to the direction (X) of introduction of the sheet (L), the bending tool (40a, 40b) is situated towards the rear and the clamping tool (42a, 42b) is situated towards the front, in that each bending tool (40a, 40b) is in the form of a bar that has active edges at the front (44a, 44b) and rear (46a, 46b) with reference to the aforesaid direction (X) of introduction of the sheet (L), in that the tool holders (28a, 28b) are capable of relative movement, in the direction (X) of introduction of the sheet (L), between two working positions in one of which the rear edge (46a) of the first tool holder (28a) is so positioned as to cooperate, in order to bend the sheet (L) in a first direction, with the front edge (44b) of the bending tool (40b) of the second tool holder (28b) and the clamping tool (42b) of the second tool holder (28b) is immediately opposite the bending tool (40a) of the first tool holder (28a) in order to cooperate with it through the interposed sheet (L) in the execution of the bend in the first direction, and in the other of which positions the front edge (46a) of the bending tool (40a) of the first tool holder (28a) is so positioned as to cooperate, in order to bend the sheet (L) in the opposite direction to the

first direction, with the rear edge (40b) of the bending tool (40b) of the second tool holder (28b) and the clamping tool (42a) of the first tool holder (28a) is immediately opposite the bending tool (40b) of the second tool holder (28b) in order to cooperate with it through the interposed sheet (L) in the execution of the bend in the second direction, and in that each clamping tool (42a, 42b) is mounted in its tool holder (28a, 28b) in such a way that it retreats against the force of means of elastic repulsion (50a, 50b) under the mechanical pressure exerted on it, through the interposed sheet (L), by the bending tool (40a, 40b) immediately opposite it.

2. Bending press according to Claim 1, characterised in that the active edges (44a, 46a, 44b, 46b) of the bending tools (40a, 40b) are rounded.

3. Bending press according to Claim 1 or 2, characterised in that each clamping tool (42a, 42b) is in the form of a series of pads (48a, 48b) which extends in the direction of extension of the bar forming the bending tool (40a, 40b) with which said clamping tool (42a, 42b) is to cooperate, and in that the means of repulsion (50a, 50b) of each clamping tool consist of hydraulic piston-and-cylinder units in which the cylinders (52a, 52b) are formed within their respective tool holders (28a, 28b) and in which the pistons (54a, 54b) carry the pads (48a, 48b), each piston (54a, 54b) being under a hydraulic pressure that opposes the mechanical pressure of the bending tool (40a, 40b) immediately opposite it.

4. Bending press according to any one of Claims 1 to 3, characterised in that it comprises means (36) for bringing about the respective movements of the two tool holders (28a, 28b), which are so programmed as to execute these

respective movements in the form of reciprocating strokes of increasing amplitude so as to produce a bend progressively in a succession of strokes, the angle of the bend being proportional to the number and amplitude of the successive reciprocating strokes.

5. Bending press according to any one of Claims 1 to 4, characterised in that one (28b) of the tool holders (28a, 28b) is movable in the direction (Z) normal to the plane in which the sheet (L) lies and the other tool holder (28a) is immovable in this direction.

6. Bending press according to any one of Claims 1 to 5, characterised in that one (28b) of the tool holders (28a, 28b) is movable in the direction (X) in which the sheet (L) is introduced and the other tool holder (28a) is immovable in this direction.


7. Bending press according to any one of Claims 1 to 4, characterised in that said direction (Z) normal to the plane in which the sheet lies is substantially vertical, the first tool holder (28a) is the lower tool holder and the second tool holder (28b) the upper, in that the upper tool holder (28b) is movable in both the direction (Z) normal to the plane in which the sheet (L) lies and the direction (X) in which the sheet (L) is introduced, and in that the lower tool holder (28a) is immovable.

8. Bending press according to Claim 7, characterised in that it comprises a base (26) on which the lower tool holder (28a) is fixed, a slide (30) capable of horizontal movement on the base (26), in the direction (X) in which the sheet is introduced, between the two abovementioned working positions, first operating means (32) interposed between the base (26) and the slide (30) to move the slide (30) be-

tween its two working positions, a movable frame (34) carried by the slide (30), which carries in turn the upper tool holder (28b) and is movable back and forth, to bring about bending, in such a way as to cause the upper tool holder (28b) to execute an approximately vertical reciprocating working movement, and second operating means (36) interposed between the slide (30) and the frame (34) to cause the frame (34) and the upper tool holder (28b) to execute the substantially vertical reciprocating working movement.

9. Bending press according to Claim 8, characterised in that the frame (34) is hinged on the slide (30) about a horizontal axis so as to pivot through an angle during the abovementioned reciprocating working movement.

FIG. 1



3/3

FIG. 3a




FIG. 3b




FIG. 3c




FIG. 3d




FIG. 3e




FIG. 3f




FIG. 4a




FIG. 4b




FIG. 4c




FIG. 4d




FIG. 4e





FIG. 4f



INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 95/02794

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B21D5/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B21D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP,A,0 490 828 (SAMAT S R L) 17 June 1992 see the whole document ---	1
P,A	DE,A,43 43 123 (ISING GERD) 22 June 1995 see the whole document ---	1
A	US,A,4 043 165 (BADGER DOUGLAS V ET AL) 23 August 1977 see the whole document -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

2 November 1995

Date of mailing of the international search report

21.11.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+ 31-70) 340-3016

Authorized officer

Ris, M

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/EP 95/02794

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP A-0490828	17-06-92	IT-B- 1242874 AT-T- 117922 DE-D- 69107185 DE-T- 69107185 ES-T- 2070477 JP-A- 5115924	18-05-94 15-02-95 16-03-95 07-09-95 01-06-95 14-05-93
DE-A-4343123	22-06-95	NONE	
US-A-4043165	23-08-77	CA-A- 1075575 DE-A- 2741001 FR-A- 2364709 GB-A- 1551543 JP-A- 53092364	15-04-80 23-03-78 14-04-78 30-08-79 14-08-78