

(51) International Patent Classification:
A47J 31/44 (2006.01)(21) International Application Number:
PCT/EP2015/065411(22) International Filing Date:
7 July 2015 (07.07.2015)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
14176238.5 9 July 2014 (09.07.2014) EP

(71) Applicant: NESTEC S.A. [CH/CH]; CT-IAM, Av. Nestlé 55, CH-1800 Vevey (CH).

(72) Inventors: LAGOUCHE, Laurent; 180 Chemin du Crêt Martin, F-74500 Saint-Paul en Chablais (FR). GUYON, Bertrand; Rue de la Rochette 16, F-25160 Saint Point Lac (FR). LARZUL, David; 45 rue Louis Aragon, F-69330 Meyzieu (FR).

(74) Agent: SCHNYDER, Frank; CT-IAM, Avenue Nestlé 55, 1800 Vevey (CH).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,

DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))
- of inventorship (Rule 4.17(iv))

Published:

- with international search report (Art. 21(3))

(54) Title: DEVICE FOR CONNECTING A BEVERAGE MACHINE TO A DISTRIBUTION NETWORK WITH SAFE MONITORING




Fig. 4

(57) Abstract: A connecting device (1) is configured for connecting a beverage machine (2) with an external liquid delivery system (3). The connecting device (1) has: an inlet (10) for a fluid connection to the external system (3); an outlet (13) for delivering liquid from the external system (3) via the inlet (10) to the beverage machine (2); a valve arrangement (12a, 12b) switchable between an open configuration for establishing a fluidic connection between the inlet (10) and the outlet (13) and a closed configuration for interrupting the fluidic connection; a control unit (14) for switching the valve arrangement (12a, 12b) between its open configuration and its closed configuration; and a sensor arrangement (15a, 15b) connected to the control unit (14) that is configured to switch the valve arrangement (12a, 12b) in response to a triggering signal from the sensor arrangement (15a, 15b). The outlet (13) is configured to deliver liquid from the external system (3) into a tank (20) of the machine (2) or of such connecting device (1). The sensor arrangement (15a, 15b) comprises: a low level sensor (15a) for detecting a low level (15a') of liquid in the tank (20) to generate a triggering signal for switching the valve arrangement (12a, 12b) to the open configuration so as to fill the tank (20) with liquid delivered by the outlet (13); and a high level sensor (15b) for detecting a high level (15b') of liquid in the tank (20) to generate a triggering signal for switching the valve arrangement (12a, 12b) to the closed configuration. The control unit (14) is also arranged to switch the valve arrangement (12a, 12b) into the closed configuration: when a predetermined period of time has lapsed after switching the valve arrangement (12a, 12b) into the open configuration; and/or when a further sensor (15c) provides a signal to the control unit (14) that indicates that the high level (15b') has been exceeded.

DEVICE FOR CONNECTING A BEVERAGE MACHINE TO A
DISTRIBUTION NETWORK WITH SAFE MONITORING

Field of the Invention

5 The present invention concerns the supply of liquid from a liquid distribution network, such as from a city water distribution network (typically the network supplying water to the tap valve in households), to a beverage preparation machine via a connecting device
10 having a safe monitoring.

For the purpose of the present description, a "beverage" is meant to include any liquid food, such as tea, coffee, hot or cold chocolate, milk, soup, baby food, etc... A "cartridge" is meant to include any pre-portioned
15 beverage ingredient, such as a flavouring ingredient, within an enclosing packaging of any material, in particular an airtight packaging, e.g. plastic, aluminium, recyclable and/or biodegradable packagings, and of any shape and structure, including soft pods or rigid
20 capsules containing the ingredient. The cartridge may contain an amount of ingredient for preparing a single beverage serving or a plurality of beverage servings.

Background Art

25 Beverage preparation machines have been known for a number of years. For example, US 5,943,472 discloses a water circulation system between a water reservoir and a hot water or vapour distribution chamber of an espresso machine. The circulation system includes a valve,
30 metallic heating tube and pump that are connected together and to the reservoir.

A beverage preparation machine typically includes a housing containing a beverage processing module and a water tank in fluid communication with the beverage
35 processing module. Examples of such beverage preparation machines are disclosed in EP 1 208 782, EP 1 267 687, EP 1 686 879, EP 1 731 065, EP 1 829 469, EP 1 864 598, EP 1 865 815, EP 1 867 260, EP 1 878 368, EP 2 222 210, EP 2 222 211, EP 2 222 212, EP 2 227 121, EP 2 227 122, US

2008/0006159, US 7,165,488, WO 2007/111884, WO 2009/074553, WO 2010/015427 and WO 2012/055767.

Usually the water tank is removable to be refilled by a user when empty. Some systems include a continuous
5 water supply by connecting the beverage machine directly to the city water distribution network, as for instance disclosed in CN201076369. This publication discloses a system that has a refillable water tank as well as an inlet for direct connection with the tap. Hence, beverage
10 preparation can be carried out either by using water directly from the tap or from the water tank.

Summary of the Invention

The invention thus relates to a connecting device
15 for connecting a beverage preparation machine with an external liquid delivery system, e.g. a water distribution network, to supply such liquid to the machine. Typically, liquid is supplied to the connecting device at a pressure above the atmospheric pressure, e.g.
20 in the range of 1.1 to 20 bar, typically 1.2 to 15 bar, such as 1.5 to 10 bar, for instance 2 to 6 bar.

For instance, the machine has a liquid storage tank, e.g. a tank with an upper opening, such as an opening delimited by a rim of the tank. The tank can be delimited
25 by a bottom part and a peripheral wall extending from and above the bottom part towards the opening. For instance, the tank has an outlet for dispensing liquid to a beverage processing and deliver unit of the machine. Such an outlet can be located at the bottom part of the tank.

30 The tank can be removable or fixed in the machine. The tank can be manually refillable (typically when not fitted with the connecting device).

Alternatively, the tank can be a buffer reservoir integrated in machine and/or in the connecting device,
35 e.g. not intended for manual refilling, the filling of which is controlled by the connecting device.

It is also possible that the machine is provided with a machine tank and the connecting device with a connecting device tank (different to the machine tank).

Examples of beverage preparation machines with suitable tanks are disclosed in EP 2 228 633, WO 2009/074550, WO 2010/046442, WO 2010/128109, WO 2011/083103, WO 2011/089210, WO 2011/144723, WO 2012/055767 and WO 2013/104643, which are hereby incorporated.

The connecting device has: an inlet for a fluid connection to the external system; an outlet for delivering liquid from the external system via the inlet to the beverage machine; a valve arrangement switchable between an open configuration for establishing a fluidic connection between the inlet and the outlet and a closed configuration for interrupting the fluidic connection, such as a valve arrangement comprising at least one valve; a control unit for switching the valve arrangement between its open configuration and its closed configuration; and a sensor arrangement connected to the control unit that is configured to switch the valve arrangement in response to a triggering signal from the sensor arrangement.

The outlet of the connecting device is configured to deliver liquid from the external system into a tank of the machine or a tank of the connecting device.

When the tank is integrated in the connecting device, the tank of the device can be directly connected to a liquid conduit of the machine. The machine may or may not be fitted with a further tank, e.g. for manual filling when the connecting device with its tank is removable from the machine so that the machine remains operable by filling the further tank.

The sensor arrangement comprises:

- a low level sensor for detecting a low level of liquid in the tank to generate a triggering signal for switching the valve arrangement to the open configuration so as to fill the tank with liquid delivered by the outlet; and
- a high level sensor for detecting a high level of liquid in the tank to generate a triggering signal for switching the valve arrangement to the closed configuration.

The low level sensor may either detect the presence of liquid in the tank, e.g. an amount of liquid that does not allow the (complete) preparation of a further serving, alternatively the low level sensor may simply detect the absence of liquid in the tank. The low level sensor may detect a level of liquid in the tank or at the tank outlet or in a fluid line in the beverage machine, e.g. a flowmeter in such a fluid line from which an absence of liquid in the tank can be inferred when no flow is measured by the flowmeter while a pump in the machine is activated to pump liquid from the tank along the machine's fluid line.

Hence, generally speaking, the connecting device may be connected to and use sensors that are integrated in the beverage machine to monitor the tank. Alternatively, the connecting device may be connected to and use sensors that are integrated to the connecting device.

The control unit can be arranged to switch the valve arrangement into the closed configuration:

- when a predetermined period of time has lapsed after switching the valve arrangement into the open configuration, the predetermined period of time being optionally user-adjustable, e.g. to adjust to a flow rate of liquid supplied from the external delivery system and/or to adjust to a maximum storage volume of the tank; and/or
- when a further sensor provides a signal to the control unit that indicates that the high level has been exceeded.

For instance, such a further sensor comprises:

- a further level sensor connected to the control unit and arranged to generate a triggering signal for switching the valve arrangement when a predetermined level above the high level is detected; and/or
- a flowmeter connected to the control unit and measuring a volume of liquid that is delivered via the outlet, the valve arrangement being switched into the closed configuration when the measured volume reaches a predetermined volume, the predetermined volume being

optionally user-adjustable, e.g. to adjust to a maximum storage volume of the tank.

Hence, when the high level sensor is somehow defective or the reading of the high level sensor by the control unit is defective, the connecting device is nevertheless provided with a safety arrangement for preventing such a malfunctioning of the connecting device that would lead to non-timely interruption of the filling of the liquid tank and finally overflow thereof. It follows that an isolated failure of a sensor or the time measuring system does not lead to an overflow of the tank.

For instance, the control unit is connected to at least one of: a power source via a power connector, such as an electric connector (e.g. plug or socket) to the mains with a voltage transformer and/or an electric connector (e.g. plug or socket) to the beverage machine with or without a voltage transformer; and a user interface such as an interface comprising a power and/or reset switch (such as an on/off switch and/or a switch for resetting the device, e.g. after an incident) and/or a control indicator e.g. a control light. The control indicator can for instance indicate: whether the device is on or off, and/or whether the valve arrangement are in the open or the closed configuration; and/or whether the device is properly functioning or malfunctioning; and/or whether the device is in a programming mode.

The control unit of the connecting device can be integrated in the control unit of the beverage machine, the electric powering of the connecting device being optionally supplied by the beverage machine. However, a dedicated control unit can be provided for the connecting device. In the latter instance, the control unit does not control other functions of to the beverage machine.

For instance, the sensor arrangement comprises at least one of an optical sensor, an electric sensor, e.g. a capacitive sensor, and a float sensor for sensing a float in the tank. The technical details of such sensors is well known in the field and are for instance discussed in EP 2 228 633 and US 8 387 455.

The valve arrangement may be connected to the inlet via a fluid connector, e.g. a fluid connector fixed to a frame portion of a body of the device.

5 In an embodiment, the valve arrangement comprises two or more valves that are in serial fluidic configuration between the inlet and the outlet.

10 Two such valves that that are in serial fluidic configuration can be controlled in parallel by the control unit to be both simultaneously open for establishing the fluidic connection between the inlet and the outlet or to be both simultaneously closed for interrupting the fluidic connection.

15 Two such valves that that are in serial fluidic configuration may be controlled separately so that: a first valve (e.g. a main or control valve) of such valves is open or closed for establishing or interrupting the fluidic connection between the inlet and the outlet as required for supplying liquid to the machine; and a
20 second valve (e.g. a backup or safety valve) of such valves is open as long as the first valve opens and closes as controlled by the control unit and is then closed when the first valve is malfunctioning (e.g. mechanical and/or electric failure so that it does not (fully) close anymore). For instance, at least one sensor,
25 e.g. a flowmeter and/or an overfill level sensor, is connected to the control unit for sensing an on-going flow of liquid via the inlet and the outlet after the control unit has attempted to switch the first valve into its closed configuration and for triggering the control
30 unit to switch the second valve into its closed configuration.

Hence, by providing a serial fluidic arrangement of a plurality of valves (e.g. two valves) that are
35 controlled in parallel (e.g. in the same manner) or separately, the possibility of mal-functioning of one valve, e.g. because of mechanical failure or electrical failure or lime clogging of this valve, does not prevent the other valve(s) from being closed and from interrupting the fluidic connection. It follows that a
40 malfunction of one valve (e.g. unable to fully interrupt the fluidic connection) does not lead to an overflow of the tank.

Optionally, the control unit is arranged to detect a malfunctioning of at least one valve to then indicate to a user such malfunctioning via an indicator and/or block the non-malfunctioning valve in its closed configuration with or without automatically switching-off such device.

The connecting device may further comprises an assembly arrangement for reversibly or irreversibly fixing such connecting device to the machine e.g. to the machine tank.

The connecting device is irreversibly fixed by the assembly arrangement when the disassembly requires a destruction of at least one part of the device (or the machine) or when the disassembly requires a special tool (e.g. a physical key) or knowledge (e.g. an intellectual key) possessed by specially trained maintenance personal but no by average consumers.

For instance, such device when reversibly fixed forms a user-removable accessory fixed to the tank so that the outlet is positioned for delivering liquid into the tank via an upper opening of the tank.

The assembly arrangement may include a mechanical connector, e.g. a hook, clip, snap, clamp, friction fastener, geometric connector, and/or a magnetic connector, and/or any connector that reversibly fixes the connecting device directly or indirectly to the machine's tank.

Hence, the connecting device may be fitted onto new or existing beverage machines (retrofitting) and does not alter the integrity of the machine. Hence, the connecting device can be removed from the machine so that beverage machine can be operated by manually refilling its tank. Alternatively, the connecting device may be fully integrated into the machine, in a manner which is not intended to be disassembled by an ordinary user.

When the connecting device is provided as a user-removable accessory, the connecting device can be fitted onto machines that can be operated without the connecting device or with the connecting device. The connecting device is provided as a separable unit that can be fitted by a user to a beverage machine having a liquid tank.

For instance, the assembly arrangement is configured for fixing such device to the tank so that the sensor arrangement extends inside the tank via an upper opening or is located adjacent a peripheral tank wall externally to the tank. Whether extending inside or located externally to the tank, the sensor arrangement is arranged so as to generate a triggering signal when the liquid reaches a predetermined level in the tank.

The connecting device can comprise a body and an overhanging arm arranged to extend over an opening of a machine's tank and optionally into the tank via the opening, the overhanging arm being formed of or holding at least one of the outlet and the sensor arrangement. The overhanging arm can comprise a connecting portion for connecting a cover member that is configured to cover the opening of the tank. Optionally the outlet and/or the sensor arrangement extend(s) through the connecting portion or form(s) the connecting portion or is/are integral with the connecting portion and the cover member.

Generally speaking, the connecting device can include a cover member that is configured to close a tank opening of the tank (e.g. to avoid contamination of the liquid in the tank by dust or other impurities that could otherwise enter the tank via its opening), the cover member delimiting a passage, such as a through hole, through which the outlet extends or through which the outlet can deliver liquid into the tank. Optionally, the sensor arrangement extends through the passage or through a different passage delimited by the cover member into the tank or is confined outside the tank.

The cover member can comprise an assembly arrangement for reversibly assembling the cover member to at least one of the tank, such as to a rim delimiting the tank opening, and/or to a main machine body of the beverage machine e.g. by being hooked to the main machine body. The assembling of the cover member to the tank and/or to machine's main machine body may be implemented in the manner by which ordinary tank covers are assembled thereto, e.g. as discussed in the references cited above.

The connecting device may include a device body and an assembly arrangement for reversibly assembling the

device body to the tank and/or to a main machine body of the beverage machine.

5 The assembly arrangement can include a lower assembly arrangement, such as a foot, for reversibly assembling the device body to a lower part of the tank and/or to a lower part of the main machine body, optionally the lower assembly arrangement comprising a platform projecting from a bottom part of the device body and/or extending under the outlet.

10 The assembly arrangement may have an upper assembly arrangement, such as a top, for reversibly assembling the device body to an upper part of the tank and/or to an upper part of the main machine body, optionally the upper assembly arrangement comprising an arm projecting from a top part of the device body and/or extending above the outlet, such as an arm forming or fixed to a cover member.

15 The assembly arrangement may comprise a first assembly arrangement, such as a lower assembly arrangement e.g. a foot, and a second assembly arrangement, e.g. an upper assembly arrangement, which can be reversibly or irreversibly fixed to the machine, e.g. to the tank and/or to the main machine body, by fastening the first and second arrangements to one another by a fixing arrangement.

25 The fixing arrangement may include any connector that reversibly or irreversibly fixes directly or indirectly the connecting device to the machine, e.g. a machine's tank and/or machine's main body, such as a mechanical or physical or chemical connector, e.g. one or more of hooks, clips, snaps, clamps, rivets, screws, 30 nails, friction fasteners, geometric fasteners, magnetic connectors, gluing areas and welding areas.

When fixed together the first and second arrangements can:

35 - extend over two extremities of the machine, e.g. over the tank and/or the main machine body, to form a clamp secured on the machine, e.g. on the tank and/or main machine body, the two extremities forming for instance a top and bottom part of the machine, e.g. of the tank and/or main machine body; and/or

40

- extend externally over and around the machine, e.g. externally over and around the tank and/or the main machine body, and optionally passing through an opening of said tank and/or main machine body; and/or
- 5 - delimit between them an opening for the external system to be connected to the inlet.

In an embodiment, the device body is made of a first part and a second part. The first part comprises the first assembly arrangement and the second part comprises
10 the second assembly arrangement. The first and second assembly arrangements are reversibly or irreversibly fixed to the machine by assembling the first and second parts together by the fixing arrangement.

For instance, at least one of the first and second
15 parts includes an outer housing by which it is assembled to the other part, e.g. each part having an outer housing whereby the parts are assembled together via their respective outer housings. For instance, one part of the first and second parts comprises the inlet, the outlet,
20 the valve arrangement and the control unit, optionally the inlet and/or the outlet extending through the other part of the first and second parts such as through an opening delimited by a housing of the other part e.g. an opening delimited by a housing of the first part and a
25 housing of the second part.

Hence, the connecting device can be mounted very easily onto the machine, for instance onto the machine's tank and/or main machine body. For instance, the connecting device is mounted onto the machine as a two
30 part arrangement and secured to the machine (e.g. tank and/or main machine body) by fastening the two parts of the connecting device together by the fixing arrangement.

The fastening of the two parts may be "accessible", i.e. easily unfastenable by a user without effort (e.g.
35 by using a user-toggle or lock), it can be "readily accessible", i.e. unfastenable by an untrained user without damaging the connecting device (e.g. by using screws). In general, the assembly arrangement resulting from such fastening, e.g. by using a corresponding fixing
40 arrangement, is considered to be reversibly.

Alternatively, the fastening is "not accessible", i.e. the unfastening involves a destruction of at least one part of the connecting device or of the fixing arrangement or it requires a special tool or key (e.g. not widely spread) or requires a special knowledge (provided by corresponding special training) of the connecting device and its structure to know how to disassemble it. In general, the assembly arrangement resulting from such fastening, e.g. by using a corresponding fixing arrangement, is considered to be irreversibly.

The connecting device may comprise a member bearing the sensor arrangement, optionally the member having one or more of the following features a) to d):

- a) the member extends in a generally upright direction and/or in a generally horizontal direction arranged to generally match a wall of the machine, such as a peripheral wall of the tank, along (a) corresponding direction(s), when such device is fixed to the tank;
- b) the member extends in a generally upright direction in a manner as to generally extend along the tank wall inside or outside the tank, when such device is fixed to the tank;
- c) the member forms a wall of a body of the device;
- d) the member is formed by a PCB which interfaces at least one or two sensor(s) of the sensor arrangement to the control unit.

Another aspect of the invention relates to a combination formed of a connecting device described above and a beverage machine. The device is arranged to connect the machine with an external liquid delivery system, e.g. a water distribution network, to supply such liquid to the machine. For instance, the machine has a liquid tank, such as a tank with an upper opening for supplying liquid into the tank, e.g. an opening delimited by a rim of the tank. Optionally, the tank is delimited by a bottom part and a peripheral wall extending from and above the bottom wall towards the opening and/or has a tank outlet for dispensing liquid to a beverage processing and delivery unit of the machine.

The machine can have an inlet for supplying an ingredient, such as an ingredient contained in a cartridge, to be processed with the liquid in the processing and delivery unit to prepare a beverage. The inlet usually has an ingredient passage with or without a loading device for transporting the ingredient at the inlet. Examples of such arrangements are disclosed in EP 1447034, WO 01/84993, WO 02/078499, WO 03/056987, WO 2012/072766, WO 2012/093107, WO 2012/126971, WO 2014/056821, WO 2014/056641 and WO 2014/056642.

The machine may have an outlet for delivering a beverage from the processing and delivery unit. Any outlet is contemplated. Examples of advantageous outlets are disclosed in WO 2006/050769, WO 2011/095502, WO 2012/055765, WO 2012/072758 and WO 2013/127907.

The outlet may be located above a support for placing a user-recipient, e.g. a cup or a mug, for collecting the beverage delivered by the outlet. Suitable examples of such supports are disclosed in EP 1943931, EP 1867260, EP 2189087, EP 2189088, EP 2189089, WO 2009/074557, WO 2011/154492, WO 2012/007313 and WO 2013/104636.

The machine may have an actuator, such as a handle or a motor, for actuating the beverage processing and delivery unit for receiving in and/or evacuating from the unit an ingredient, such as an ingredient contained in a cartridge. Suitable examples of such actuators and actuated beverage processing and delivery units are disclosed in US 8272319, WO 2004/071259, WO 2005/004683, WO2007/135136, WO 2009/043630, WO 2010/015427, WO 2012/025258, WO 2012/025259, WO 2013/127476, WO 2014/056810, WO 2014/056862, WO 2014/060370, WO 2014/096122 and WO 2014/096123.

The machine can have a pump for pumping the liquid from the tank to a beverage delivery outlet. Examples of suitable pumps and/or their integration in the fluid line of beverage preparation machines are disclosed in WO 2009/024500, WO 2009/150030, WO 2010/006953, WO 2011/107574, WO 2010/108700 and WO 2013/098173.

The machine may include a mixing chamber for mixing the liquid driven by the pump with an ingredient such as

an ingredient contained in a cartridge. Examples of mixing chambers can be found in the references listed in relation with the actuated beverage processing and delivery unit.

5 The machine may include thermal conditioner, such as a heater and/or a cooler, for thermally conditioning the liquid supplied from the tank, e.g. via a tank outlet. Examples of thermal conditioners and and/or their integration in the fluid line of beverage preparation
10 machines are disclosed in US 8646377, WO 01/54551, WO 2004/006742, WO 2006/029763, WO 2009/092746, WO 2009/043851, WO 2009/043865 and WO 2011/157675.

 The machine may include a machine control unit such as a control unit with a user-interface. Implementation
15 examples of control units and user-interfaces in beverage preparation machines are for example disclosed in WO 2008/138710, WO 2009/043865, WO 2009/135821, WO 2010/003932, WO 2010/037806, WO 2010/046442, WO 2011/020779, WO 2011/026853, WO 2011/029813, WO
20 2011/144719, WO 2011/144720, WO 2012/007260, WO 2012/032019 and WO 2012/072764.

 The machine can comprise an electric connector for supplying power via a power connector to the connecting device, e.g. as disclosed in WO 2009/074555.

25 The machine may have a removable tank lid for covering the tank. The tank lid may be compatible with the connecting device when the connecting device is used with the machine or the tank lid may be removed from the tank for using the connecting device. When the tank lid
30 is removed, the connecting device may comprise a cover member that replaces the tank lid and that allows the refilling of the tank via the connecting device (usually through the cover member). The tank lid (or the device's cover member) may be secured to the machine's main body
35 or to the tank or to both. An example of a tank lid (that can be modified for the connecting device, either as a part of the connecting device (as its cover member) or as part of the beverage machine or that can be used as such when the beverage machine is not combined with the
40 connecting device) is taught in WO 2011/089210.

The beverage preparation machine can be an in-home or out of home machine. The machine may be for the preparation of coffee, tea, chocolate, cacao, milk, soup, baby food, etc.... The machine may be arranged for preparing within a beverage processing module a beverage by passing hot or cold water or another liquid through a cartridge containing an ingredient, such as a flavouring ingredient, of the beverage to be prepared, such as ground coffee or tea or chocolate or cacao or milk powder.

The beverage preparation typically includes the mixing of a plurality of beverage ingredients, e.g. water and milk powder, and/or the infusion of a beverage ingredient, such as an infusion of ground coffee or tea with water. One or more of such ingredients may be supplied in loose and/or agglomerate powder form and/or in liquid form, in particular in a concentrate form. A carrier or diluents liquid, e.g. water, may be mixed with such ingredient to form the beverage. The liquid may be supplied manually and/or via the external delivery system.

For instance, a predetermined amount of beverage is formed and dispensed on user-request, which corresponds to a serving. The volume of such a serving may be in the range of 25 to 200 ml and even up to 300 or 400 ml, e.g. the volume for filling a cup, depending on the type of beverage. Formed and dispensed beverages may be selected from ristrettos, espressos, lungos, cappuccinos, latte macchiato, café latte, americano coffees, teas, etc... For example, a coffee machine may be configured for dispensing espressos, e.g. an adjustable volume of 20 to 60 ml per serving, and/or for dispensing lungos, e.g. a volume in the range of 70 to 150 ml per serving.

Brief Description of the Drawings

The invention will now be described with reference to the schematic drawings, wherein:

- Figure 1 illustrates a beverage preparation machine having a tank which can be fitted with a connecting device in accordance with an exemplary embodiment of the invention;

- Figures 2 and 3 show a perspective view and a side view, respectively, of such a connecting device;

- Figure 4 illustrates a beverage preparation machine fitted with such a connecting device; and

5 - Figure 5 is a cross-sectional view of part of a beverage machine fitted with such a connecting device.

Detailed description

10 Figures 1 to 3 illustrates a beverage preparation machine 2 that can be retrofitted with a connecting device 1 shown in Figs 2 to 4 in a manner illustrated in Fig. 5.

15 Exemplary machine 2 shown in Figs 1, 4 and 5 has a liquid storage tank 20, e.g. a water tank. For instance tank 20 has an upper opening 20a for supplying liquid into tank 20, such as an opening 20a delimited by a rim of tank 20. Optionally, tank 20 is delimited by a bottom part 20b and a peripheral wall 20c extending from and above bottom wall 20b towards opening 20a and/or having a
20 tank outlet 20d for dispensing liquid to a beverage processing and delivery unit 24,25 of machine 2.

25 Tank 20 can be removable or fixed in machine 2. Tank 20 can be manually refillable (typically when not fitted with the connecting device). Alternatively, the tank can be a buffer reservoir integrated in machine and/or in the connecting device, not intended for manual refilling, to which reservoir connecting device is connected.

30 When the tank is integrated in the connecting device, the tank of the device can be directly connected to a liquid conduit of the machine. The machine may or may not be provided with a further tank, e.g. for manual filling when the connecting device with its tank is removable from the machine so that the machine remains operable by filling the further tank.

35 Machine 2 may have an inlet 24 for supplying an ingredient, such as an ingredient contained in a cartridge, to be processed with the liquid from tank 20 in processing and delivery unit 24,25 so as to prepare a beverage.

Machine 2 typically includes an outlet 25 for delivering a beverage from processing and delivery unit 24,25, such as an outlet 25 located above a support 26 for placing a user-recipient, e.g. a cup or a mug, for
5 collecting the beverage delivered by outlet 25.

For instance, machine 2 has an actuator, such as a handle 23 or a motor, for actuating beverage processing and delivery unit 24,25 to receive in and/or evacuate from unit 24,25 an ingredient, such as an ingredient
10 contained in a cartridge.

Typically, machine 2 comprises a pump for pumping the liquid from tank outlet 20d to a beverage delivery outlet 25, optionally via a mixing chamber for mixing the liquid with an ingredient such as an ingredient contained
15 in a cartridge.

Machine 2 may also include a thermal conditioner, such as a heater and/or a cooler, for thermally conditioning the liquid supplied from tank 20, e.g. via tank outlet 20d.

20 Normally, machine 2 comprises a machine control unit such as a control unit with a user-interface 27, e.g. an on/off switch.

Optionally, machine 2 may also include an electric connector (not shown) for supplying power to an external
25 device, such as to connecting device 1, via a power connector 14c,14d of device 1.

Furthermore, tank 20 may have a (solid) tank lid 20' covering opening 20a, lid 20' being removable for filling tank 20. When connecting device 1 is fixed to tank 20,
30 lid 20' may be removed so that opening 20a remains open or is covered by a cover member 16d that is fixed to connecting device 1 and (re-)movable en bloc with device 1. Hence, tank 20 may nevertheless remain covered when (retro-)fitted with connecting device 1.

35 An exemplary connecting device 1 is illustrated in Figs 2 to 5, Figs 4 and 5 showing device 1 when mounted on a beverage preparation machine 2, typically of the type discussed above.

Connecting device 1 is arranged for connecting
40 machine 2 with an external liquid delivery system 3, e.g.

a pipe 3 of a water distribution network or a pipe 3 connected to such a network, to supply liquid from system 3 to machine 2.

Connecting device 1 typically has: an inlet 10 for a
5 fluid connection to external liquid delivery system 3; an
outlet 13 for delivering liquid from external system 3
via inlet 10 to beverage machine 2; a valve arrangement
12a,12b switchable between an open configuration for
10 establishing a fluidic connection between inlet 10 and
outlet 13 and a closed configuration for interrupting the
fluidic connection, such as a valve arrangement 12a,12b
connected to inlet 10 via a fluid connector 11 e.g. a
fluid connector 11 fixed to a frame portion 16a of a body
16 of such device 1, valve arrangement 12a,12b having for
15 instance at least one valve 12a,12b; a control unit 14
for switching valve arrangement 12a,12b between its open
configuration and its closed configuration; and a sensor
arrangement 15a,15b connected to control unit 14 that is
configured to switch valve arrangement 12a,12b in
20 response to a triggering signal from sensor arrangement
15a,15b.

Optionally, control unit 14 is connected to at least
one of: a power source via a power connector 14c,14d; and
a user interface 14a,14b such as an interface comprising
25 a and/or reset switch 14a (e.g. an on/off switch and/or a
switch for resetting device 1) 14a and/or a control
indicator e.g. a control light 14b. The power source may
be provided by beverage preparation machine 2 itself or
may be external to device 1 and to machine 2, for
30 instance the mains. Power connector 14c,14d may include
an electric cable 14c and a plug 14d. Power connector
14c,14d may include a voltage transformer, e.g. within
plug 14d or on control unit 14.

When the connecting device is integrated in the
35 machine, the control unit may be integrated in the
control unit of the machine or may be a separate control
unit dedicated to the connecting device. Likewise, the
user-interface of the connecting device may be part of
the user-interface of the machine (or at least located on
40 the machine).

Outlet 13 can be configured to deliver liquid from external system 3 into a tank 20 of machine 2 or of such connecting device 1.

Sensor arrangement 15a,15b may comprise a low level sensor 15a for detecting a low level 15a' of liquid in tank 20 to generate a triggering signal for switching valve arrangement 12a,12b to the open configuration so as to fill tank 20 with liquid delivered by outlet 13 and a high level sensor 15b for detecting a high level 15b' of liquid in tank 20 to generate a triggering signal for switching valve arrangement 12a,12b to the closed configuration. For instance, control unit 14 is arranged to switch valve arrangement 12a,12b into the closed configuration:

- when a predetermined period of time has lapsed after switching valve arrangement 12a,12b into the open configuration, the predetermined period of time being optionally user-adjustable, e.g. to adjust to a flow rate of liquid supplied from external delivery system 3 and/or to adjust to a maximum storage volume of tank 20; and/or
- when a further sensor 15c provides a signal to control unit 14 that indicates that high level 15b' has been exceeded.

Further sensor 15c can include a further level sensor connected to control unit 14 and arranged to generate a triggering signal for switching the valve arrangement when a predetermined level above high level 15b' is detected.

Further sensor 15c can comprise a flowmeter 15c connected to control unit 14 and measuring a volume of liquid that is delivered via outlet 13, the valve arrangement being switched into the closed configuration when the measured volume reaches a predetermined volume, the predetermined volume being optionally user-adjustable, e.g. to adjust to a maximum storage volume of tank 20.

Typically, control unit 14 is connected to at least one of: a power source via a power connector 14c,14d; and a user interface 14a,14b such as an interface comprising a and/or reset switch 14a (e.g. an on/off switch and/or a switch for resetting device 1) 14a and/or a control

indicator e.g. a control light 14b. The power source may be provided by beverage preparation machine 2 itself or may be external to device 1 and to machine 2, for instance the mains. Power connector 14c, 14d may include an electric cable 14c and a plug 14d. Power connector 14c, 14d may include a voltage transformer, e.g. within plug 14d or on control unit 14.

Sensor arrangement 15a, 15b may comprise at least one of an optical sensor, an electric sensor, e.g. a capacitive sensor, and a float sensor for sensing a float in tank 20.

Valve arrangement 12a, 12b can be connected to inlet 10 via a fluid connector 11 e.g. a fluid connector 11 fixed to a frame portion 16a of a body 16 of device 1.

Valve arrangement 12a, 12b may include two or more valves 12a, 12b that are in serial fluidic configuration between inlet 10 and outlet 13

At least two such valves 12a, 12b that are in serial fluidic configuration can be controlled in parallel by control unit 14 to be both simultaneously open for establishing the fluidic connection between inlet 10 and outlet 13 or both simultaneously closed for interrupting the fluidic connection.

At least two such valves 12a, 12b that are in serial fluidic configuration can be controlled separately by control unit 14. A first valve 12a (e.g. a main valve or a control valve) of such valves 12a, 12b can be opened or closed for establishing or interrupting the fluidic connection between inlet 10 and outlet 13 as required for supplying liquid to machine. A second valve 12b (e.g. a back-up or safety valve) of such valves 12a, 12b is typically open as long as first valve 12a opens and closes as controlled by control unit 14 and is closed when first valve 12a is malfunctioning. At least one sensor 15c, e.g. a flowmeter and/or an overfill level sensor, can be connected to control unit 14 for sensing an on-going flow of liquid via inlet 10 and outlet 13 after control unit 14 has attempted to switch first valve 12a into its closed configuration and for triggering control unit 14 to switch second valve 12b into its closed configuration.

Control unit 14 can be arranged to detect a malfunctioning of at least one valve 12a,12b to then indicate to a user such malfunctioning via an indicator 14b and/or block the non-malfunctioning valve in its closed configuration with or without automatically switching-off such device 1.

Connecting device 1 can further comprise an assembly arrangement 16c,16d for reversibly or irreversibly fixing connecting device 1 to machine 2 e.g. to machine tank 20. Device 1 may form a user-removable accessory 1 fixed to tank 20 so that outlet 13 is positioned for delivering liquid into tank 20 via an upper opening 20a of tank 20. Assembly arrangement 16c,16d may be configured for fixing such device 1 to tank 20 so that sensor arrangement 15a,15b extends inside tank 20 via a tank opening 20a or is located adjacent a peripheral tank wall 20c externally to tank 20, so as to generate a triggering signal when the liquid reaches a predetermined level 15a',15b' in tank 20.

The connecting device can be integrated in the beverage machine in a manner not intended to be disassemblable by a user.

The connecting device may be connected to and use sensors that are integrated in the beverage machine to monitor the tank.

Connecting device 1 may include a body 16 and an overhanging arm 16b arranged to extend over a tank opening 20a of tank 20 and optionally into tank 20 via opening 20a, overhanging arm 16 being formed of or holding at least one of the outlet 13 and sensor arrangement. Overhanging arm 16b can have a connecting portion 16e for connecting a cover member 16d that is configured to cover opening 20a of tank 20. Outlet 13 and/or the sensor arrangement may extend through connecting portion 16e or may form the connecting portion or may be integral with the connecting portion and cover member 16d.

Connecting device 1 can have a cover member 16d that is configured to close a tank opening 20a of tank 20, cover member 16d delimiting a passage 16e, such as a through hole, through which outlet 13 extends or through

which the outlet can deliver liquid into tank 20. Sensor arrangement 15a,15b may extend through this passage or through a different passage delimited by the cover member into the tank or may be confined outside the tank 20.

5 Cover member 16d may include an assembly arrangement 16f for reversibly assembling cover member 16d to at least one of tank 20, such as to a rim delimiting tank opening 20a, and/or to a main machine body 22 of beverage machine 2 e.g. by being hooked to main machine body 22.

10 Device 1 can have a device body 16 and an assembly arrangement 16c;16b,16d,16e,16f for reversibly or irreversibly assembling device body 16 to tank 20 and/or to a main machine body 22 of beverage machine 2.

15 The assembly arrangement can include a lower assembly arrangement 16c, such as a foot, for reversibly or irreversibly assembling the device body 16 to a lower part 20b of tank 20 and/or to a lower part of main machine body 22. For instance, lower assembly arrangement 16c has a platform projecting from a bottom part of
20 device body 16 and/or extends under outlet 13.

 The assembly arrangement may have an upper assembly arrangement 16b,16d,16e,16f, such as a top, for reversibly or irreversibly assembling device body 16 to an upper part 20a of tank 20 and/or to an upper part of
25 main machine body 22. For example, upper assembly arrangement 16b,16d,16e,16f includes an arm 16b projecting from a top part of device body 16 and/or extending above outlet 13, such as an arm forming or fixed to a cover member 20d.

30 The assembly arrangement may comprise a first assembly arrangement 16c, such as a lower assembly arrangement e.g. a foot, and a second assembly arrangement 16b,16d,16e,16f, e.g. an upper assembly arrangement, which can be reversibly or irreversibly
35 fixed to machine 2, e.g. to tank 20, by fastening first and second arrangements 16b,16c,16d,16e,16f to one another by a fixing arrangement 16bc. Fixing arrangement 16bc may include any connector that reversibly or irreversibly fixes directly or indirectly connecting
40 device 1 to machine 2, e.g. a machine's tank 20 and/or machine's main body 22, such as a mechanical or physical

or chemical connector, e.g. one or more of hooks, clips, snaps, clamps, rivets, screws, nails, friction fasteners, geometric fasteners, magnetic connectors, gluing areas and welding areas. For instance, when fixed together,
5 first and second arrangements 16b,16c,16d,16e,16f:

- extend over two extremities of machine 2, e.g. over tank 20 and/or main machine body 22, to form a clamp secured on machine 2, e.g. on tank 20 and/or main machine body 22, said two extremities forming for
10 instance a top and bottom part of machine 2, e.g. of tank 20 and/or main machine body 22; and/or
- extend externally over and around machine 2, e.g. externally over and around tank 20 and/or main machine body 22, and optionally passing through an
15 opening 20a of tank 20 and/or main machine body 22; and/or
- delimit between them an opening 16c' for external system 3 to be connected to inlet 10.

Device body 16 can be made of a first part 16' and a
20 second part 16'', first part 16' comprising first assembly arrangement 16c and second part 16'' comprising second assembly arrangement 16b,16d,16e,16f, first and second assembly arrangements 16c;16b,16d,16e,16f being reversibly or irreversibly fixed to machine 2 by
25 assembling first and second parts 16',16'' together by fixing arrangement 16bc.

At least one of first and second parts 16',16'' may include an outer housing 161',161'' by which it is assembled to the other part. For instance each part
30 16',16'' has an outer housing 161',161'' whereby parts 16',16'' are assembled together via their respective outer housings 161',161''.

One part 16'' of first and second parts 16',16'' can comprise inlet 10, outlet 13, valve arrangement 12a,12b
35 and control unit 14. For instance, inlet 10 and/or outlet 13 extend(s) through the other part 16' of first and second parts 16',16'' such as through an opening 16c' delimited by a housing 161' of other part 16', e.g. an opening delimited by a housing 161' of first part 16' and
40 a housing of the second part 16''.

Generally speaking, connecting device 1 may include a member 15 bearing sensor arrangement 15a,15b. Member 15 may have one or more of the following features a) to d):

- 5 a) member 15 extends in a generally upright direction 15' and/or in a generally horizontal direction 15'' arranged to generally match a wall 20c of machine 2, such as a peripheral wall 20c of tank 20, along (a) corresponding direction(s) 20c',20c'', when such device 1 is fixed to tank 20;
- 10 b) member 15 extends in a generally upright direction in a manner as to generally extend along tank wall 20c inside or outside tank 20, when device 1 is fixed to tank 20;
- c) member 15 forms a wall 15 of a body 16 of device 1;
- 15 d) member 15 is formed by a PCB which interfaces at least one or two sensor(s) 15a,15b of sensor arrangement 15a,15b to control unit 14.

CLAIMS

1. A connecting device (1) for connecting a beverage machine (2) with an external liquid delivery system (3),
5 e.g. a water distribution network, to supply such liquid to said machine (2), said connecting device (1) having:

- an inlet (10) for a fluid connection to said external system (3);

10 - an outlet (13) for delivering liquid from said external system (3) via the inlet (10) to said beverage machine (2);

15 - a valve arrangement (12a,12b) switchable between an open configuration for establishing a fluidic connection between the inlet (10) and the outlet (13) and a closed configuration for interrupting the fluidic connection, such as a valve arrangement (12a,12b) comprising at least one valve (12a,12b);

20 - a control unit (14) for switching the valve arrangement (12a,12b) between its open configuration and its closed configuration; and

25 - a sensor arrangement (15a,15b) connected to the control unit (14) that is configured to switch the valve arrangement (12a,12b) in response to a triggering signal from the sensor arrangement (15a,15b),

characterised in that the outlet (13) is configured to deliver liquid from said external system (3) into a tank (20) of said machine (2) or of such connecting device (1), and in that the sensor arrangement (15a,15b) comprises:

30 - a low level sensor (15a) for detecting a low level (15a') of liquid in said tank (20) to generate a triggering signal for switching the valve arrangement (12a,12b) to the open configuration so as to fill said tank (20) with liquid delivered by the outlet (13);
35 and

- a high level sensor (15b) for detecting a high level (15b') of liquid in said tank (20) to generate a triggering signal for switching the valve arrangement (12a,12b) to the closed configuration,

and in that the control unit (14) is also arranged to switch the valve arrangement (12a,12b) into the closed configuration:

- 5 - when a predetermined period of time has lapsed after switching the valve arrangement (12a,12b) into the open configuration, the predetermined period of time being optionally user-adjustable, e.g. to adjust to a flow rate of liquid supplied from said external delivery system (3) and/or to adjust to a maximum storage volume of said tank (20); and/or
- 10 - when a further sensor (15c) provides a signal to the control unit (14) that indicates that the high level (15b') has been exceeded.

2. The device of claim 1, wherein said further sensor
15 (15c) comprises:

- a further level sensor connected to the control unit (14) and arranged to generate a triggering signal for switching the valve arrangement when a predetermined level above the high level (15b') is detected; and/or
- 20 - a flowmeter (15c) connected to the control unit (14) and measuring a volume of liquid that is delivered via the outlet (13), the valve arrangement being switched into the closed configuration when the measured volume reaches a predetermined volume, the predetermined
25 volume being optionally user-adjustable, e.g. to adjust to a maximum storage volume of said tank (20).

3. The device of claim 1 or 2, wherein the control unit (14) is connected to at least one of: a power source via a power connector (14c,14d); and a user interface
30 (14a,14b) such as an interface comprising a power and/or reset switch (14a) and/or a control indicator e.g. a control light (14b).

4. The device of any preceding claim, wherein the sensor arrangement (15a,15b) comprises at least one of an
35 optical sensor, an electric sensor, e.g. a capacitive sensor, and a float sensor for sensing a float in said tank (20).

5. The device of any preceding claim, wherein the valve arrangement (12a,12b) is connected to the inlet (10) via
40 a fluid connector (11) e.g. a fluid connector (11) fixed

to a frame portion (16a) of a body (16) of such device (1).

6. The device of any preceding claim, wherein the valve arrangement (12a,12b) comprises two or more valves (12a,12b) that are in serial fluidic configuration between the inlet (10) and the outlet (13), optionally at least two such valves (12a,12b) that are in serial fluidic configuration are controlled:

- in parallel by the control unit (14) to be both simultaneously open for establishing the fluidic connection between the inlet (10) and the outlet (13) or both simultaneously closed for interrupting the fluidic connection; or
- separately by the control unit (14) so that a first valve (12a) of such valves (12a,12b) is open or closed for establishing or interrupting the fluidic connection between the inlet (10) and the outlet (13) as required for supplying liquid into said tank (20) and so that a second valve (12b) of such valves (12a,12b) is open as long as the first valve (12a) opens and closes as controlled by the control unit (14) and is closed when the first valve (12a) is malfunctioning, optionally at least one sensor (15c), e.g. a flowmeter and/or an overfill level sensor, may be connected to the control unit (14) for sensing an on-going filling of said tank (20) after the control unit (14) has attempted to switch the first valve (12a) into its closed configuration and for triggering the control unit (14) to switch the second valve (12b) into its closed configuration,

optionally the control unit (14) being arranged to detect a malfunctioning of at least one valve (12a,12b) to then indicate to a user such malfunctioning via an indicator (14b) and/or block the non-malfunctioning valve in its closed configuration with or without automatically switching-off such device (1).

7. The device of any preceding claim, which further comprises an assembly arrangement (16c,16d) for reversibly or irreversibly fixing said connecting device (1) to said machine (2) e.g. to said machine tank (20), optionally such device (1) forming a user-removable

accessory (1) fixed to said tank (20) so that the outlet (13) is positioned for delivering liquid into said tank (20) via an upper opening (20a) of said tank (20).

8. The device of claim 7, wherein the assembly arrangement (16c,16d) is configured for fixing such device (1) to said tank (20) so that the sensor arrangement (15a,15b) extends inside the tank (20) via a tank opening (20a) or is located adjacent a peripheral tank wall (20c) externally to the tank (20), so as to generate a triggering signal when the liquid reaches a predetermined level (15a',15b') in the tank (20).

9. The device of claim 7 or 8, which comprises a body (16) and an overhanging arm (16b) arranged to extend over a tank opening (20a) of said tank (20) and optionally into the tank (20) via the opening (20a), the overhanging arm (16) being formed of or holding at least one of the outlet (13) and the sensor arrangement.

10. The device of claim 9, wherein the overhanging arm (16b) comprises a connecting portion (16e) for connecting a cover member (16d) that is configured to cover the opening (20a) of said tank (20), optionally the outlet (13) and/or the sensor arrangement extending through the connecting portion (16e) or forming the connecting portion or being integral with the connecting portion and the cover member (16d).

11. The device of any one of claims 7 to 10, which comprises a cover member (16d) that is configured to close a tank opening (20a) of said tank (20), the cover member (16d) delimiting a passage (16e), such as a through hole, through which the outlet (13) extends or through which the outlet can deliver liquid into said tank (20), optionally the sensor arrangement (15a,15b) extending through said passage or through a different passage delimited by the cover member into said tank or being confined outside the tank (20).

12. The device of claim 10 or 11, wherein the cover member (16d) comprises an assembly arrangement (16f) for reversibly assembling the cover member (16d) to at least one of said tank (20), such as to a rim delimiting the tank opening (20a), and/or to a main machine body (22) of

said beverage machine (2) e.g. by being hooked to the main machine body (22).

13. The device of any one of claims 7 to 12, which has a device body (16) and an assembly arrangement (16c;16b,16d,16e,16f) for reversibly assembling the device body (16) to the tank (20) and/or to a main machine body (22) of said beverage machine (2), such as:

- a lower assembly arrangement (16c), such as a foot, for reversibly assembling the device body (16) to a lower part (20b) of the tank (20) and/or to a lower part of the main machine body (22), optionally the lower assembly arrangement (16c) comprising a platform projecting from a bottom part of the device body (16) and/or extending under the outlet (13); and/or
- an upper assembly arrangement (16b,16d,16e,16f), such as a top, for reversibly assembling the device body (16) to an upper part (20a) of the tank (20) and/or to an upper part of the main machine body (22), optionally the upper assembly arrangement (16b,16d,16e,16f) comprising an arm (16b) projecting from a top part of the device body (16) and/or extending above the outlet (13), such as an arm forming or fixed to a cover member (20d); and/or
- a first assembly arrangement (16c), such as a lower assembly arrangement e.g. a foot, and a second assembly arrangement (16b,16d,16e,16f), e.g. an upper assembly arrangement, which can be reversibly fixed to said machine (2), e.g. to said tank (20) and/or to said main machine body (22), by fastening the first and second arrangements (16b,16c,16d,16e,16f) to one another by a fixing arrangement (16bc) that may include any connector that reversibly or irreversibly fixes directly or indirectly such connecting device (1) to said machine (2), e.g. a machine's tank (20) and/or machine's main body (22), such as a mechanical or physical or chemical connector, e.g. one or more of hooks, clips, snaps, clamps, rivets, screws, nails, friction fasteners, geometric fasteners, magnetic connectors, gluing areas and welding areas, optionally when fixed together the first and second arrangements (16b,16c,16d,16e,16f):

- extending over two extremities of said machine (2), e.g. over said tank (20) and/or main machine body (22), to form a clamp secured on said machine (2), e.g. on said tank (20) and/or said main machine body (22), said two extremities forming for instance a top and bottom part of said machine (2), e.g. of said tank (20) and/or main machine body (22); and/or
- extending externally over and around said machine (2), e.g. externally over and around said tank (20) and/or said main machine body (22), and optionally passing through an opening (20a) of said tank (20) and/or main machine body (22); and/or
- delimiting between them an opening (16c') for said external system (3) to be connected to the inlet (10).

14. The device of any preceding claim, which comprises a member (15) bearing the sensor arrangement (15a,15b), optionally the member (15) having one or more of the following features a) to d):

- a) the member (15) extends in a generally upright direction (15') and/or in a generally horizontal direction (15'') arranged to generally match a wall (20c) of the machine (2), such as a peripheral wall (20c) of the tank (20), along (a) corresponding direction(s) (20c',20c''), when such device (1) is fixed to the tank (20);
- b) the member (15) extends in a generally upright direction in a manner as to generally extend along the tank wall (20c) inside or outside the tank (20), when such device (1) is fixed to the tank (20);
- c) the member (15) forms a wall (15) of a body (16) of said device (1);
- d) the member (15) is formed by a PCB which interfaces at least one or two sensor(s) (15a,15b) of the sensor arrangement (15a,15b) to the control unit (14).

15. A combination formed of a connecting device (1) as defined in any preceding claim and a beverage machine (2), the device (1) being arranged to connect the machine (2) with an external liquid delivery system (3), e.g. a water

distribution network, to supply such liquid to said machine (2), optionally the machine having one or more of:

- 5 - an inlet (24) for supplying an ingredient, such as an ingredient contained in a cartridge, to be processed with said liquid in the processing and delivery unit (24,25) to prepare a beverage;
- 10 - an outlet (25) for delivering a beverage from the processing and delivery unit (24,25) such as an outlet (25) located above a support (26) for placing a user-recipient, e.g. a cup or a mug, for collecting the beverage delivered by the outlet (25);
- 15 - an actuator, such as a handle (23) or a motor, for actuating the beverage processing and delivery unit (24,25) for receiving in and/or evacuating from the unit (24,25) an ingredient, such as an ingredient contained in a cartridge;
- 20 - a pump for pumping said liquid from the tank outlet (20d) to a beverage delivery outlet (25), optionally via a mixing chamber for mixing said liquid with an ingredient such as an ingredient contained in a cartridge;
- a thermal conditioner, such as a heater and/or a cooler, for thermally conditioning said liquid from the tank outlet (20d);
- 25 - a machine control unit such as a control unit with a user-interface (27);
- an electric connector for supplying power via a power connector (14c,14d) to the connecting device (1); and
- 30 - a removable tank lid (20'), such as a tank lid (20') replaceable by a cover member (16) comprised by the connecting device (1).

Fig. 1





Fig. 3




Fig. 2




Fig. 4




Fig. 5

INTERNATIONAL SEARCH REPORT

International application No

PCT/EP2015/065411

A. CLASSIFICATION OF SUBJECT MATTER
 INV. A47J31/44
 ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 A47J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 244 010 A1 (VERHEIJEN BV [NL]) 4 November 1987 (1987-11-04) column 3, line 37 - column 10, line 39; figures 1-7	1-15
Y	US 2011/212236 A1 (NGUYEN QUAN HOANG [US] ET AL) 1 September 2011 (2011-09-01) paragraph [0060] - paragraph [0061]; figure 9	1-15
Y	US 7 644 650 B2 (SUZUKI JUN [JP]) 12 January 2010 (2010-01-12) column 2, line 16 - column 3, line 16; figures 1-4	1-15
Y	EP 1 462 040 A1 (BRAVILOR HOLDING BV [NL]) 29 September 2004 (2004-09-29) paragraph [0018] - paragraph [0037]; figures 1-4	1-15



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

15 September 2015

Date of mailing of the international search report

23/09/2015

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040,
 Fax: (+31-70) 340-3016

Authorized officer

Klintebäck, Daniel

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2015/065411

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0244010	A1	04-11-1987	DE 3775608 D1 13-02-1992
		EP 0244010 A1	04-11-1987
		NL 8601122 A	01-12-1987
		US 4791860 A	20-12-1988

US 2011212236	A1	01-09-2011	AU 2011223792 A1 13-09-2012
		CA 2790679 A1	09-09-2011
		CN 102843937 A	26-12-2012
		EP 2542127 A2	09-01-2013
		JP 2013521059 A	10-06-2013
		KR 20130004910 A	14-01-2013
		NZ 602100 A	31-05-2013
		RU 2012141643 A	10-04-2014
		SG 183525 A1	27-09-2012
		US 2011212236 A1	01-09-2011
		WO 2011109443 A2	09-09-2011

US 7644650	B2	12-01-2010	EP 1759617 A1 07-03-2007
		JP 4781053 B2	28-09-2011
		JP 2007069626 A	22-03-2007
		US 2007051246 A1	08-03-2007

EP 1462040	A1	29-09-2004	AT 372076 T 15-09-2007
		AU 2004201243 A1	14-10-2004
		CN 1541602 A	03-11-2004
		DE 602004008690 T2	12-06-2008
		DK 1462040 T3	05-11-2007
		EP 1462040 A1	29-09-2004
		ES 2293155 T3	16-03-2008
		HK 1065694 A1	02-11-2007
		JP 2004290679 A	21-10-2004
		KR 20040084868 A	06-10-2004
		NL 1023023 C2	30-09-2004
		PT 1462040 E	22-11-2007
		TW I317797 B	01-12-2009
		US 2005072853 A1	07-04-2005
		ZA 200402365 A	05-10-2004
