



(51) International Patent Classification:

B01J 13/18 (2006.01) **A61K 9/50** (2006.01)
A01N 25/28 (2006.01) **C09B 67/02** (2006.01)

(21) International Application Number:

PCT/EP2016/075187

(22) International Filing Date:

20 October 2016 (20.10.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15191091.6 22 October 2015 (22.10.2015) EP

(71) Applicant: **BASF SE** [DE/DE]; Carl-Bosch-Str. 38, 67056 Ludwigshafen am Rhein (DE).

(72) Inventors: **WINKELMANN, Marion**; Behrensstr. 7, 67069 Ludwigshafen (DE). **MUELHEIMS, Kerstin**; Hinkelgasse 20, 67069 Ludwigshafen (DE). **TAUBER, Ralph**; Untergasse 18, 67229 Gerolsheim (DE). **FUCHS, Yannick**; Neulandstr. 6, 67346 Speyer (DE). **CETINKAYA, Murat**; Jacob Gillesstraat 20a, 2582 XZ Den Haag (NL). **SACHWEH, Bernd**; Großgasse 20a, 67149 Meckenheim (DE).

(81) Designated States (unless otherwise indicated, for every

kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every

kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: A PROCESS FOR PREPARING AN AQUEOUS DISPERSION OF MICROPARTICLES

(57) Abstract: The present invention relates to a process for preparing an aqueous dispersion of microparticles containing a water-insoluble, solid, non-polymeric, organic active or functional material (M) and an aminoplast resin (A) which surrounds or embeds material (M), which comprises the following steps: i) providing an aqueous slurry of the material (M) in the form of coarse particles; ii) subjecting the aqueous slurry to shear forces such that the coarse particles of the material (M) are comminuted and an aqueous suspension of fine particles of the material (M) is obtained; iii) performing a polycondensation of an aminoplast pre-condensate during step (ii) or in the aqueous suspension of the fine particles of the material (M) obtained in step (ii); wherein step (ii) is performed in the presence of at least one protective colloid and in the presence of at least a portion of the aminoplast pre-condensate subjected to the polycondensation of step (iii).



A process for preparing an aqueous dispersion of microparticles

The present invention relates to a process for preparing an aqueous dispersion of microparticles containing a solid non-polymeric, organic agriculturally active material M
5 and an aminoplast resin A which surrounds or embeds material M.

Background of Invention

10 Microparticles containing non-polymeric organic active materials, such as pesticides and pharmaceuticals, embedded or surrounded by a polymer material have often been described in the literature. The reasons for embedding or surrounding the active material in a polymer material, also termed microencapsulation, are manifold and include, e.g.

- enabling safe and practical handling of toxic or perishable substances;
- 15 - achieve steady, controlled release of material;
- prevent mixing of substances;
- modify surface properties,
- improving formulation stability, reduction of agglomeration or crystallization.

20 Microencapsulation of active organic material can be principally achieved by coacervation techniques, spray drying, fluidized-bed coating, electrostatic microencapsulation or in-situ polymerization. These techniques provide particles of the active or functional organic material, wherein the active compound is surrounded or embedded by a polymeric wall material.

25 The most common method for microencapsulation of pesticides is the interfacial polymerization. In this process, a first reactant, e.g. a polyfunctional isocyanate or acid chloride, is dissolved in the liquid pesticide ingredient or a solution thereof, which is then dispersed in water and subjected to polymerization by addition of a polyfunctional
30 compound having a complementary reactivity with regard to the first reactant, e.g. an diamine or diol. The polymerization occurring at the interface between the active substance and the aqueous phase completely encloses the fine droplets of pesticide substance with a thin membrane of polyurea or polyamide.

35 Modern techniques of microencapsulation active or functional organic material include the radical suspension polymerization of water-insoluble acrylate monomers with (meth)acrylic acid and optionally polyfunctional monomers in the presence of an o/w-emulsion of the active or functional organic material or the radical emulsion polymerization of an aqueous monomer emulsions, wherein the active or functional
40 organic material is dissolved or suspended in the monomer droplets.

A further in-situ polymerization technique includes microencapsulation of liquids by using aminoplasts, such as melamine formaldehyde resins (MF resins) or urea formaldehyde resins (UF resins) or melamine formaldehyde urea resins (MUF resins). The aminoplast resins are used in the form of their prepolymers or pre-condensates, which are added to an aqueous emulsion of the material to be encapsulated and cured by heating and/or altering the pH of the reaction mixture to effect polymerization of the prepolymers. Thereby, an aqueous suspension of the microcapsules are obtained, where the particles of the encapsulated material are surrounded by or embedded in an aminoplast polymer.

Microencapsulation of pesticides using in-situ polymerization of aminoplasts pre-condensates have been described several times. For example, US 4,557,755 describes the microencapsulation of water-insoluble pesticides by polymerizing an aminoplast pre-condensate, such as a melamine formaldehyde or melamine urea formaldehyde resin in an aqueous suspension of the pesticide compound in the presence of a cationic urea resin. The method is suggested for certain insecticides and fungicides.

US 5,462,915 describes an improved process for microencapsulation of water-insoluble pesticides, which comprises adding to a suspension of the pesticide a liquid aminoplast prepolymer and curing the prepolymer at temperatures of above 100°C. The method was applied for microencapsulation of water-insoluble salts of dicamba. A similar process is known from WO 00/27519, which was applied for microencapsulation of carbofuran.

WO 96/03041 describes a microcapsule composition of pesticides, wherein the microcapsules have an outer aminoplast layer and an inner wax coating deposited around pesticide compound.

Although microencapsulation of active organic compounds may be beneficial, it is often difficult to achieve, in particular in case of solid organic materials. When trying to microencapsulate a solid organic material in an aqueous suspension of the solid organic material by an in-situ-polymerization technique, the solid organic material tends to agglomerate thereby forming large particles of the organic material, which are embedded in the polymer matrix. A thus obtained suspension is usually no longer suitable for most uses.

The preparation of microparticles of water-insoluble, solid, active organic material usually requires providing an aqueous suspension of fine particles of the water-insoluble, solid organic material to be encapsulated, because most of the microencapsulating techniques are performed in an aqueous reaction medium. For

- this, the solid organic material must usually be comminuted before it is microencapsulated, as the water-insoluble, solid organic material is normally present as coarse solid particles, such as crystals, having particles sizes of 100 μm or higher, which are unsuitable for microencapsulation. Although one may comminute the coarse solid material in the dry state to a powder, this procedure is tedious and unsatisfactory, as the powder must be dispersed in water prior to microencapsulation and, hence, preparation of a powder requires an additional process step. Apart from that, organic powders are difficult to handle as they tend to agglomerate and bear an explosion risk.
- Although it is desirable to comminute the water-insoluble, solid active organic material to be encapsulated directly in an aqueous suspension of the material, one often encounters the problem that the suspension becomes highly viscous upon comminution and/or forms foam due to inclusion of air. This becomes particularly problematic for water-insoluble organic compounds bearing aromatic and other non-polar functional groups, as found in e.g. in pesticides or pharmaceuticals, because these non-polar moieties tend to reduce surface tension of water and stabilize gas bubbles in the aqueous continuous phase. Moreover, surfactants which are used to stabilize the fine particles in the suspension also favor foam formation. So far, large amounts of antifoam agents are required, in order to allow for efficiently comminuting such solid organic materials in an aqueous suspension. However, the presence of anti foaming agents in the final product is not always favorable and might interfere with the encapsulation procedure.

Summary of Invention

- It is an object to provide a process for microencapsulating solid, water-insoluble non-polymeric organic active materials, such as pesticides or pharmaceuticals, without the need for providing a powder of the materials prior to encapsulation. In particular, the process should be suitable for preparing aqueous suspensions of microparticles, especially of microparticles, which contain solid organic pesticide compounds, which usually are difficult to comminute in aqueous media without any anti foaming agents due to the presence of polar functional moieties.

- It was surprisingly found that solid, water-insoluble non-polymeric organic active materials, in particular solid organic pesticide compounds, can be efficiently microencapsulated, if the comminution of the coarse solid, water-insoluble non-polymeric organic active or functional materials to be encapsulated is performed in the presence of an aminoplast pre-condensate used for the microencapsulation of the solid, water-insoluble non-polymeric organic active materials and a protective colloid. Polycondensation of the aminoplast pre-condensate in the thus obtained aqueous suspension of the fine particles of said material yields an aqueous dispersion of

microparticles containing the water-insoluble, solid, non-polymeric, organic active material and an aminoplast resin A which surrounds or embeds the organic material.

Therefore, the present invention relates to a process for preparing an aqueous

5 dispersion of microparticles containing a water-insoluble, solid, non-polymeric, organic active material M, which is selected from the group consisting of agriculturally active compounds, and an aminoplast resin A which surrounds or embeds the material M, which comprises the following steps:

- i. providing an aqueous slurry of the material M in the form of coarse particles
- 10 ii. subjecting the aqueous slurry to shear forces, e.g. by milling or grinding, such that the coarse particles of the material M are comminuted and an aqueous suspension of fine particles of the material M is obtained;
- iii. performing a polycondensation of an aminoplast pre-condensate during step ii. or in the aqueous suspension of the fine particles of the material M obtained in step
- 15 ii.;

wherein step ii. is performed in the presence of at least one protective colloid and in the presence of at least a portion of the aminoplast pre-condensate subjected to the polycondensation of step iii.

20 The process of the invention allows for efficiently comminuting the coarse particles of the material M without significant formation of foam, even at high loadings of the slurry with the material M. Without being bound to theory, it is believed that the aminoplast pre-condensate acts as a defoamer, thereby reducing formation of foam and viscosity during the comminution process. Thereby conventional defoamers, which are normally

25 required during comminution can be avoided or their amount can be reduced significantly.

Detailed description of Invention

30 The expression "wt%" as used herein means "% by weight".

Here and throughout the specification, the terms "microparticles" and "microcapsules" are used synonymously and relate to particles which contain the agriculturally active compound and an aminoplast resin which surrounds or embeds the solid agriculturally

35 active compound. The terms "microparticles" and "microcapsules" indicates that the discrete particles having usually a particle size of less than 200 μm , in particular less than 100 μm , given as $d(0.9)$ value.

In the first step of the method of the present invention, an aqueous slurry of coarse

40 particles of the material M is provided. The term "coarse particle" means that the particles of the material M are bigger than the particles usually contained in a

suspension concentrate formulation, which means that the volume average diameter $d(0.5)$ of the particles of the material M generally exceeds 20 μm , and is in particular at least 30 μm or at least 50 μm and may range from 20 μm to 2000 μm , in particular in the range of 30 μm to 1000 μm or in the range of 50 μm to 500 μm . Moreover, the

5 $d(0.1)$ value of particles in the slurry is frequently at least 10 μm , i.e. the at most 10 volume % of the particles of the material M in the slurry have a diameter of above 10 μm .

The average particle diameter, as referred herein, is the volume average particle

10 diameter $d(0.5)$ or $d(v, 0.5)$, respectively, i.e. 50 vol.-% of the particles have a diameter which is above the value cited and 50 vol.-% of the particles have a diameter which is below the value cited. Therefore, average particle diameters are also termed "volume median diameters". Such average particle diameters can be determined by dynamic

15 light scattering (usually performed on diluted suspensions containing from 0.01 to 5% by weight of the material M). The $d(0.9)$ or $d(v, 0.9)$ value of particles indicates that 90 vol.-% of the particles are smaller than the value cited. The $d(0.1)$ or $d(v, 0.1)$ value of particles indicates that 10 vol.-% of the particles are smaller than the value cited.

The material M can be principally any active organic compound, such as a pesticide or

20 pharmaceutical compound, which is non-polymeric, i.e. which has a defined molecular structure, which is solid and which is essentially insoluble in water.

Solid means that the melting point of the material M is higher than ambient temperature. In particular the melting point of the material M is at least 50°C, in

25 particular at least 60 °C or at least 70°C and especially at least 80°C, e.g. from 50 to 300°C or from 60 to 300°C or from 70 to 300°C or from 80 to 300°C.

Essentially water insoluble means that the solubility of the material M in deionized water is at most 5 g/L at 22°C and 1 bar.

30 In particular, the material M bears at least one polar moiety, e.g. a heterocyclic moiety, in particular a heterocyclic moiety bearing one or more nitrogen atoms as ring memberes and/or one or more polar functional groups. Examples of heterocycles include in particular 5- or 6-membered, monocyclic hetaryl groups such as pyrazolyl,

35 imidazolyl, triazolyl, pyridyl, pyrimidinyl, pyridazinyl, pyrazinyl, triazinyl, 8 to 10 membered fused bicyclic hetaryl such as indolyl, isoindolyl, indazolyl, benzimidazolyl, benzothiazolyl, benzoxazolyl, quinolinyl, isoquinolinyl, phthalazinyl, pyrazolopyridinyl, pyrazolopyrimidinyl, imidazolylpyridinyl or imidazolylpyrimidinyl and the keto-analogues thereof such as imidazolin-2-onyl, pyrazol-3-onyl, pyridine-2-onyl, pyrimidine-2-onyl,

40 pyrimidine-4-onyl, pyrimidine-2,4-dionyl, pyridazin-3-onyl, isoindolin-5-only, quinolin-2-onyl, isoquinolin-1-onyl, phthalazin-3-only etc. Examples of polar functional groups

include are not limited to hydroxyl, amino, carbonyl group, including amide and carboxyl groups but also aldehyde or keto groups, imino groups, oxime groups etc.

According to the present invention the material M is an agriculturally active compound.

5

The term "agriculturally active compound" usually refers to any organic compound which is active against certain agriculturally relevant pests, such as plant pathogenous fungi, undesired vegetation or invertebrate pests such as insects, arachnids, slugs or worms. The term "pesticide compound" thus refers in particular to herbicide
10 compounds, fungicide compounds, insecticide compounds, compounds having acaricidal activity, i.e. acaricides, molluscicides and nematicides in particular to at least one organic active compound selected from the group of the fungicides, insecticides, nematicides, herbicides and biopesticides. Preferred pesticide compounds are fungicides, insecticides and herbicides. Especially preferred pesticide compounds are
15 herbicides. Mixtures of pesticides of two or more of the abovementioned classes may also be used. The skilled worker is familiar with such pesticides, which can be found, for example, in the Pesticide Manual, 17th Ed. (2015), The British Crop Protection Council, London. Suitable insecticides include e.g. insecticides from the class of the carbamates, organophosphates, organochlorine insecticides, phenylpyrazoles,
20 pyrethroids, neonicotinoids, spinosins, avermectins, milbemycins, juvenile hormone analogs, alkyl halides, organotin compounds nereistoxin analogs, benzoylureas, diacylhydrazines, METI acarizides, and insecticides such as chloropicrin, pymetrozin, flonicamid, clofentezin, hexythiazox, etoxazole, diafenthiuron, propargite, tetradifon, chlorofenapyr, DNOC, buprofezine, cyromazine, amitraz, hydramethylnon, acequinocyl,
25 fluacrypyrim, rotenone, or their derivatives. Suitable fungicides include e.g. fungicides from the classes of dinitroanilines, allylamines, anilinopyrimidines, antibiotics, aromatic hydrocarbons, benzenesulfonamides, benzimidazoles, benzisothiazoles, benzophenones, benzothiadiazoles, benzotriazines, benzyl carbamates, carbamates, carboxamides, carboxylic acid diamides, chloronitriles cyanoacetamide oximes,
30 cyanoimidazoles, cyclopropanecarboxamides, dicarboximides, dihydrodioxazines, dinitrophenyl crotonates, dithiocarbamates, dithiolanes, ethylphosphonates, ethylaminothiazolecarboxamides, guanidines, hydroxy-(2-amino)pyrimidines, hydroxyanilides, imidazoles, imidazolinones, inorganic substances, isobenzofuranones, methoxyacrylates, methoxycarbamates, morpholines, N-phenylcarbamates,
35 oxazolidinediones, oximinoacetates, oximinoacetamides, peptidylpyrimidine nucleosides, phenylacetamides, phenylamides, phenylpyrroles, phenylureas, phosphonates, phosphorothiolates, phthalamic acids, phthalimides, piperazines, piperidines, propionamides, pyridazinones, pyridines, pyridinylmethylbenzamides, pyrimidinamines, pyrimidines, pyrimidinonehydrazones, pyrroloquinolinones,
40 quinazolinones, quinolines, quinones, sulfamides, sulfamoyltriazoles, thiazolecarboxamides, thiocarbamates, thiophanates, thiophenecarboxamides, toluamides, triphenyltin compounds, triazines, triazoles. Suitable herbicides include e.g. herbicides from the classes of the acetamides, amides, aryloxyphenoxypropionates,

benzamides, benzofuran, benzoic acids, benzothiadiazinones, bipyridylum, carbamates, chloroacetamides, chlorocarboxylic acids, cyclohexanediones, dinitroanilines, dinitrophenol, diphenyl ether, glycines, imidazolinones, isoxazoles, isoxazolidinones, nitriles, N-phenylphthalimides, oxadiazoles, oxazolidinediones, oxyacetamides, phenoxycarboxylic acids, phenylcarbamates, phenylpyrazoles, phenylpyrazolines, phenylpyridazines, phosphinic acids, phosphoramidates, phosphorodithioates, phthalamates, pyrazoles, pyridazinones, pyridines, pyridinecarboxylic acids, pyridinecarboxamides, pyrimidinediones, pyrimidinyl(thio)benzoates, quinolinecarboxylic acids, semicarbazones, sulfonylaminocarbonyltriazolinones, sulfonylureas, tetrazolinones, thiadiazoles, thiocarbamates, triazines, triazinones, triazoles, triazolinones, triazolocarboxamides, triazolopyrimidines, triketones, uracils and ureas.

The term "agriculturally active compound" also includes pesticide safener compounds. The term "pesticide safener compound" principally includes any organic compound which provides plants from phytotoxic damage exerted by certain agriculturally relevant pesticide compounds.

The term "agriculturally active compound" also includes plant growth regulators.

Suitable pesticides include in particular the following compounds: herbicides, such as saflufenacil, pyroxasulfon, water-insoluble salts of dicamba, diuron, trifludimoxazin and pendimethalin; fungicides, such as pyrimethanil, pyraclostrobin and fluxapyroxad; insecticides, such as alpha cypermethrin and afidopyropen. The pesticide names are so called common names according to ISO 1750 and include the compounds as such, their salts and their derivatives, provided they are solid and essentially insoluble in water.

The material M may be crystalline or amorphous and is in particular at least partly or completely crystalline. In particular, the degree of crystallinity is at least 90 %.

A particular embodiment to the invention relates to microcapsules, wherein the material is saflufenacil, i.e. N'-(2-Chloro-4-fluoro-5-[1,2,3,6-tetrahydro-3-methyl-2,6-dioxo-4-(trifluoromethyl)pyrimidin-1-yl]benzoyl)-N-isopropyl-N-methylsulfamide. The saflufenacil used in the process of the invention may be any known form of solid saflufenacil, including amorphous saflufenacil and in particular crystalline saflufenacil, e.g. the crystalline anhydrate of saflufenacil as described in WO 08/043835 or a crystalline hydrate of saflufenacil as described in WO 08/043836.

Another particular embodiment to the invention relates to microcapsules, wherein the material M is pyrimethanil, i.e. 4,6-dimethyl-N-phenylpyrimidin-2-amine.

The slurry of the material M can be simply provided by suspending material M in water, which may or may not contain at least a portion of the protective colloid and/or at least a portion of the aminoplast precondensate used for encapsulation. Usually, the amount of solid material M is suspended such that the concentration of the material M in the slurry prior to step ii. is in the range of 5 to 40 % by weight, in particular in the range of 7 to 35 % of the total weight of the slurry.

According to the invention, step ii. is performed in the presence of the aminoplast pre-condensate used for encapsulation of the material M. During step ii. at least a portion or the total amount of aminoplast pre-condensate subjected to the polycondensation of step iii. may be present. It is also possible that a portion of the aminoplast pre-condensate subjected to the polycondensation of step iii. is added after step ii. has been performed. Usually, at least 20 %, in particular at least 50 %, especially at least 70 % or at least 90 % or the total amount of the aminoplast pre-condensate subjected to the polycondensation of step iii. will already be present during step ii.

The aminoplast pre-condensate present during step ii. may be added to the aqueous slurry of the material M provided in step i. or it may be added during step ii. Frequently, the major amount of aminoplast pre-condensate present during step ii. is added to the slurry before starting the comminution of step ii. In particular at least 20 %, in particular at least 50 %, especially at least 70 % or at least 90 % of the total amount of aminoplast pre-condensate subjected to the polycondensation of step iii. is added to the slurry of the material M before starting the comminution of step ii.

The concentration of the aminoplast pre-condensate in the slurry of step i. or during comminution of step ii. is frequently in the range of 0.5 to 20 % by weight, in particular in the range of 1 to 10 % by weight. Preferably, the aminoplast pre-condensate is present in the aqueous slurry of step i. or in the suspension of step ii. in an amount in the range of 1 to 50 % by weight, in particular in the range of 1 to 30 % by weight and especially in the range of 5 to 25 % by weight, based on the material M.

Suitable aminoplast pre-condensates are oligomeric or polymeric condensation products of one or more aldehydes, such as formaldehyde, acetaldehyde, propanal, glyoxal or glutaraldehyde, with one or more amino compounds having usually at least two primary amino groups, such as urea, thiourea, melamine, which may be wholly or partially etherified, cyanoguanamine (= dicyandiamide) and benzoguanamine. Upon applying curing conditions they form crosslinked aminoplast polymers. Aminoplast pre-condensates include, but are not limited to condensation products of melamine and formaldehyde (melamine-formaldehyde pre-condensates or MF pre-condensates), including wholly or partially etherified melamine-formaldehyde condensates, urea-

- formaldehyde pre-condensates (UF pre-condensates), thiourea-formaldehyde pre-condensates (TUF pre-condensates), pre-condensates of melamine, urea and formaldehyde (MUF pre-condensates), including wholly or partially etherified melamine-urea-formaldehyde condensates, pre-condensates of melamine, thiourea and formaldehyde (MTUF pre-condensates), including partially etherified melamine-thiourea-formaldehyde condensates, urea-glutaraldehyde pre-condensates, benzoguanamine-formaldehyde pre-condensates, dicyandiamide formaldehyde pre-condensates and urea-glyoxal pre-condensates.
- 10 Suitable aminoplast pre-condensates for microencapsulation are known and can be found, inter alia, in Kirk-Othmer, Encyclopedia of Chemical Technology, 3rd edition, Vol. 2, pp. 440-469, the prior art cited in the introductory part, US 4,918,317, EP 26914, EP 218887, EP 319337, EP 383,337, EP 415273, DE 19833347, DE 19835114 and WO 01/51197. Suitable pre-condensates are commercially available, e. g. Cymel
- 15 types, such as but not limited to Cymel® 303, 327, 328 or 385 (etherified melamine formaldehyde resins of Cytec), Maprenal® types, such as but not limited to Maprenal® MF 900w/95, MF 915/75IB, MF 920/75WA, MF 921w/85WA, (etherified melamine formaldehyde resins of Ineos), Kauramin® types of BASF SE, such as but not limited to Kauramin® 783, Kauramin® 792 or Kauramin® 753 (melamine formaldehyde resins),
- 20 Kauramin® 620 or Kauramin® 621 (melamine urea formaldehyde resins), Kaurit® types of BASF SE, such as but not limited to Kaurit® 210, 216, 217 or 220 (urea formaldehyde resins), Luracoll® types such as Luracoll® SD (etherified melamine formaldehyde resins), Luwipal® types such as but not limited to Luwipal® 063, Luwipal® 069 (etherified melamine formaldehyde resins), or Plastopal® types such as
- 25 but not limited to Plastopal® BTM, Plastopal® BTW (etherified urea formaldehyde resins).

In suitable urea-formaldehyde or thiourea-formaldehyde pre-condensates, the molar ratios of urea or thiourea to formaldehyde are generally in the range of 1:0.8 to 1:4, in particular in the range of 1:1.5 to 1:4, especially in the range of 1:2 to 1:3.5.

In suitable melamine-formaldehyde or melamine-(thio)urea-formaldehyde pre-condensates, the molar ratios of melamine to formaldehyde are generally in the range of 1:1.5 to 1:10, in particular in the range of 1:3 to 1:8 preferably in the range of 1:4 to 1:6.

In suitable melamine-formaldehyde or melamine-(thio)urea-formaldehyde pre-condensates, the molar ratios of melamine + urea or thiourea to formaldehyde are generally in the range of 1:0.8 to 1:9, in particular from 1:2 to 1:8 preferably in the range of 1:3 to 1:6. The molar ratio of urea or thiourea to melamine is usually in the range of 5:1 to 1:50 and in particular in the range of 30:1 to 1:30.

The pre-condensates may be used in the form of etherified pre-condensates of amino compound and aldehyde. In these etherified pre-condensates the methylol groups formed by the reaction of the amino groups with formaldehyde with an alkanol or an alkandiol, in particular with a C₁-C₄-alkanol, such as methanol, ethanol, n-propanol or n-butanol, in particular methanol, or a C₂-C₄-alkandiol, such as ethylene glycol. The degree of etherification of these resins can be adjusted by the molar ratio of amino groups to alkanol which is typically in the range of 10:1 to 1:10, preferably in the range of 2:1 to 1:5.

The pre-condensates are especially selected from the group consisting of melamine-formaldehyde pre-condensates, including wholly or partially etherified melamine-formaldehyde pre-condensates, and urea-formaldehyde pre-condensates and mixtures thereof. Especially, the pre-condensate is a wholly or partially etherified melamine-formaldehyde condensate, which may contain small amounts, e.g. 1 to 20 mol.-%, based on melamine, of urea.

According to the invention, step ii. is performed in the presence of a protective colloid. Usually, at least 20 %, in particular at least 50 %, especially at least 70 % or at least 90 % or the total amount of the protective colloid present in step iii. will also be present during step ii.

The protective colloid present during step ii. may be added to the aqueous slurry of the material M provided in step i. or it may be added during step ii. Frequently, the major amount of protective present during step ii. is added to the slurry before starting the comminution of step ii. In particular at least 20 %, in particular at least 50 %, especially at least 70 % or at least 90 % of the total amount of protective colloid present during step ii. will be added to the slurry of the material M before starting the comminution of step ii.

Protective colloids suitable for the process of the invention are principally any water-soluble polymers which are known to stabilize suspensions of water-insoluble material. Suitable protective colloids may be anionic, non-ionic or cationic.

Anionic protective colloids are water-soluble polymers, which contain a plurality of anionic groups, such as carboxylate groups, sulfonate groups, phosphonate groups, sulfate groups and/or phosphate groups. The anionic groups in these anionic polymers may be partially or fully neutralized. Suitable counter ions are alkalimetal ions, such as sodium, potassium, earth alkaline ions such as magnesium or calcium, and ammonium. In case of anionic polymeric surfactants having a sulfonate group, the anionic groups are preferably at least partly neutralized.

Suitable anionic protective colloids are e.g.

- anionically modified, water-soluble polysaccharides such as carboxymethylcellulose,
- 5 - lignin based sulfonic acids, such as liginosulfonic acid, ethoxylated liginosulfonic acid or oxidized liginins,
- arylsulfonic acid formaldehyde condensates and arylsulfonic acid formaldehyde urea condensates, such as naphthalene sulfonic acid formaldehyde condensates, phenol sulfonic acid formaldehyde condensates, cresol sulfonic acid formaldehyde condensates etc.,
- 10 - homo- and copolymers of ethylenically unsaturated monomers which frequently comprise at least 20% by weight, based on the total amount of the monomers, of at least one ethylenically unsaturated monomer which comprises at least one carboxy group, sulfonic acid group, and/or phosphonic acid group incorporated
- 15 within the polymer, and salts of these, in particular the alkali metal salts and ammonium salts. When the abovementioned anionic water-soluble polymers are in an aqueous medium, the sulfonic acid groups or phosphonic acid groups bonded to the main polymer chain are generally in the salt form, i.e. in the form of sulfonate groups, the phosphonic acid groups correspondingly being in the form of
- 20 phosphonate groups. The counterions are then typically alkali metal ions and alkaline earth metal ions, examples being sodium ions, and calcium ions, and ammonium ions (NH_4^+);

- Non-ionic protective colloids are water-soluble polymers, which contain a plurality non-
25 ionic polar moieties such as carbamoyl groups, i.e. $\text{C}(=\text{O})\text{NH}_2$ groups, lactam groups, such as pyrrolidin-2-on groups, polyethyleneoxide groups or hydroxyl groups.

- Suitable non-ionic protective colloids are e.g. water-soluble starches, starch derivatives, and cellulose derivatives, such as methylcellulose, hydroxypropylcellulose,
30 hydroxyethylcellulose, hydroxypropylmethylcellulose, and also polyvinyl alcohols, inclusive of partially hydrolyzed polyvinyl acetate with a degree of hydrolysis which is preferably at least 40%, in particular at least 60%, polyacrylamide, polyvinylpyrrolidone, polyethylene glycols, graft polymers of vinyl acetate and/or vinyl propionate onto polyethylene glycols, and polyethylene glycols mono- or bilaterally end-group-capped
35 with alkyl, carboxy, or amino groups.

- Preferably, the protective colloids are selected from anionic polymers having a plurality of sulfate or sulfonate groups, and neutral polymers having a plurality of hydroxyl groups, such as polyvinyl alcohols, inclusive of partially hydrolyzed polyvinyl acetate
40 with a degree of hydrolysis which is preferably at least 40%, in particular at least 60%.

In a preferred embodiment of the invention, the microparticle composition contains at least one anionic protective colloid, hereinafter also referred to as anionic polymeric surfactant A, which contains a plurality of anionic groups, especially sulfonate groups or sulfate groups.

5 Examples for polymeric surfactant A are the surfactants of the following groups A1 to A3, including the salts thereof:

- A.1 lignin based sulfonic acids, such as lignosulfonic acid, ethoxylated lignosulfonic acid or oxidized lignins;
- A.2 arylsulfonic acid formaldehyde condensates and arylsulfonic acid formaldehyde
10 urea condensates, such as naphthalene sulfonic acid formaldehyde condensates, phenol sulfonic acid formaldehyde condensates, cresol sulfonic acid formaldehyde condensates etc.;
- A.3 and homo- or copolymers of monoethylenically unsaturated monomers M1
15 having a sulfonic acid group optionally with one or more comonomers M2 different from monomers M1.

The anionic groups in these anionic polymeric surfactants A may be partially or fully neutralized. Suitable counter ions are alkalimetal ions, such as sodium, potassium, earth alkaline ions such as magnesium or calcium, and ammonium. In case of anionic
20 polymeric surfactants having a sulfonate group, the anionic groups are preferably at least partly neutralized.

The anionic polymeric surfactants A are in particular selected from groups A2. and A.3, especially from group A.3.

25 Preferably, the anionic polymeric surfactant A.3 is selected from homo- or copolymers made of

- i) at least one monoethylenically unsaturated monomer M1 having a sulfonic acid group, such as vinylsulfonic acid, allylsulfonic acid, styrene sulfonic acid,
30 vinyltoluene sulfonic acid, (meth)acrylate monomers having a sulfonic acid group, such as 2-acryloxyethylsulfonic acid, 2-acryloxypropylsulfonic or 4-acryloxybutylsulfonic acid, and (meth)acrylamide monomer having a sulfonic acid group, such as 2-acrylamidoethylsulfonic acid, 2-acrylamidopropylsulfonic acid or 2-acrylamido-2-methylpropane sulfonic acid
- 35 ii) optionally with one or more monoethylenically unsaturated comonomers M2 different from monomers M1, such as styrene, C₁-C₄-alkylacrylates, C₁-C₄-alkylmethacrylates, acrylamide, methacrylamide, acrylic acid, methacrylic acid, C₁-C₄-alkylacrylates, C₁-C₄-alkylmethacrylates.

In particular, groups of embodiments, the anionic polymeric surfactant A comprises or is selected from homo- or copolymers of group A.3, in particular from homo- or copolymers made of

- 5 i) monomers M1, which are selected from (meth)acrylate monomers having a sulfonic acid group, such as 2-acryloxyethylsulfonic acid, 2-acryloxypropylsulfonic acid or 4-acryloxybutylsulfonic acid, and (meth)acrylamide monomer having a sulfonic acid group, such as 2-acrylamidoethylsulfonic acid, 2-acrylamidopropylsulfonic acid or 2-acrylamido-2-methylpropane sulfonic acid,
- 10 ii) optionally with one or more monoethylenically unsaturated comonomers M2 different from monomers M1, such as styrene, C₁-C₄-alkylacrylates, C₁-C₄-alkylmethacrylates, acrylamide, methacrylamide, acrylic acid, methacrylic acid, C₁-C₄-alkylacrylates, C₁-C₄-alkylmethacrylates.

Especially, the polymeric surfactant A.3 comprises or is selected from homo- or copolymers of

- 15 i) monomers M1, which is 2-acrylamido-2-methylpropane sulfonic acid,
- ii) optionally with one or more monoethylenically unsaturated comonomers M2 different from monomers M1, such as styrene, C₁-C₄-alkylacrylates, C₁-C₄-alkylmethacrylates, acrylamide, methacrylamide, acrylic acid, methacrylic acid,
- 20 C₁-C₄-alkylacrylates, C₁-C₄-alkylmethacrylates.

In these preferred, particular preferred or especially preferred anionic polymeric surfactants A.3, the amount of monomers M1 is preferably at least 50% by weight, based on the total amount of monomers forming the polymeric surfactant. Even more preferred are polymeric surfactants A, which are homo- or copolymers of monomers M1, wherein the amount of monomers M1 is at least 90% by weight, based on the total amount of monomers forming the polymeric surfactant. These polymers are known and frequently commercially available e.g. from BASF SE.

30 In another particular groups of embodiments, the anionic polymeric surfactant A comprises or is selected from surfactants of group A.2, i.e. arylsulfonic acid formaldehyde condensates and arylsulfonic acid formaldehyde urea condensates, in particular from naphthalene sulfonic acid formaldehyde condensates.

35 Instead to the anionic polymeric surfactant A or in combination therewith a non-ionic protective colloid can be used. Then, the non-ionic protective colloid is preferably selected from the group consisting of neutral polymers having a plurality of hydroxyl groups, such as polyvinyl alcohols, inclusive of partially hydrolyzed polyvinyl acetate with a degree of hydrolysis which is preferably at least 40%, in particular at least 60%.


The amount of the protective colloid in the composition subjected to step ii. is preferably in the range of 0.1 to 50% by weight, in particular in the range of 2 to 40% by weight and most preferred in the range of 3 to 30% by weight, based on the total amount of material M to be encapsulated and aminoplast pre-condensate.

5

It was found beneficial, if the protective colloid is combined with one or more further anionic emulsifiers B different from the protective colloids. The anionic emulsifiers B provide for the stabilization of an aqueous formulation comprising the microparticles.

Suitable anionic emulsifiers B are surfactants having one anionic group, which is selected from phosphate or phosphonate groups and sulfate or sulfonate groups, the latter compounds being preferred. In contrast to the protective colloids, the molecular weight (number average) of these surfactants is generally lower and in particular at most 500 Dalton.

These anionic emulsifiers B will usually be included into the microparticle composition in the form of their salts, in particular the sodium, potassium or ammonium salts. Examples of anionic emulsifiers B include the salts of alkylsulfonates, alkylsulfates, alkylphosphates, semi-esters of alkoxyated alkanols with sulfuric acid or phosphoric acid, alkylarylsulfonates, alkylarylphosphates, semi-esters of alkoxyated alkylphenols with sulfuric acid or phosphoric acid and semi-esters of alkoxyated mono-, di- or tristyrylphenols with sulfuric acid or phosphoric acid. Amongst these anionic surfactants B, those of the formula I are preferred:



25 wherein

R is a hydrocarbon radical having from 8 to 40 carbon atoms and preferably from 12 to 30 carbon atoms and optionally one oxygen atom;

A is independently from one another 1,2-ethylene, 1,2-propylene or 1,3-propylene, especially 1,2-ethylene;

m is from 0 to 50, preferably from 0 to 30 and especially preferred from 0 to 20; and

X is SO_3M or PO_3M_2 with M being selected from H, alkaline metal ions, such as K and Na, alkaline earth metal ions, such as $\frac{1}{2}$ Ca and $\frac{1}{2}$ Mg and ammonium.

Preferably, M is an alkaline metal ion and especially sodium.

35

Examples of suitable hydrocarbon radicals R having from 8 to 40 carbon atoms are alkyl having from 8 to 40 and preferably from 12 to 30 carbon atoms, phenyl, which may be substituted with one or two alkyl radicals having from 4 to 20 carbon atoms, phenyl, which is substituted with a phenoxy radical, wherein phenyl and/or phenoxy may contain an alkyl radical having from 4 to 20 carbon atoms, tristyrylphenyl radical

40

etc. In a preferred embodiment of the present invention the radical R in formula I is a tristyrylphenyl radical.

Preference is given to anionic emulsifiers B, which are of the formula (I), wherein R, m

5 and X have the following meanings:

R is alkyl having from 8 to 30, in particular from 10 to 20 carbon atoms,

m is 0,

X is SO₃M with m being selected from alkaline metal ions, such as K and Na,
alkaline earth metal ions, such as ½ Ca and ½ Mg and ammonium. Preferably, M

10 is an alkaline metal and especially sodium.

If present, the amount of anionic emulsifiers B, in particular the surface-active compound of the formula I, is preferably in the range of 0.1 to 10% by weight, in particular from 0.3 to 7% by weight and most preferred in the range of 0.5 to 5% by

15 weight, based on the total amount of material M and aminoplast pre-condensate. If present, the amount of anionic emulsifier B, in particular the surface-active compound of the formula I, is preferably chosen such that the weight ratio of protective colloid to anionic emulsifier B is in the range of 1:1 to 20:1 in particular in the range of 2:1 to 10:1.

20 In step ii. of the process of the invention, the coarse particles of the material M are comminuted to the particle size required in the encapsulation step iii. Usually, comminution is performed such that less than 10 % by weight of the particles of the material M have a particle diameter of 40 µm or larger, i.e. the d(0.9) value is at most

25 40 µm, in particular at most 30 µm and especially at most 25 µm. Preferably, comminution is performed such that the volume average particle diameter d(0.5) of the material M is at most 25 µm or lower, e.g. in the range of 0.5 to 25 µm, in particular in the range of 0.5 to 15 µm and especially in the range of 0.5 to 10 µm.

30 Step ii. may be carried out by any physical comminution method suitable for achieving comminution of solid particles in an aqueous suspension, including grinding or milling techniques, respectively, i.e. wet grinding or wet milling, but also application of ultrasound or high pressure homogenization. In the instant application, the terms "grinding" and "milling" are synonymic. Preferably, comminution is achieved by

35 applying mechanical comminution methods, i.e. by subjecting the suspension to strong shear forces by mechanical means in a suitable comminution device. Suitable mechanical comminution methods are in particular wet grinding or wet milling techniques, such as wet grinding or wet milling in a milling device such as tumbling mills, including ball mills and rod mills, stirred media mills, including agitator bead mills, 40 rotor-stator mills and the like. Suitable mechanical wet grinding/milling methods and grinding devices are known, e.g. from Perry's Chemical Engineers' Handbook, 7th ed.

McGraw Hill 1997, 20-31 to 20-38, and commercially available, e.g. from Netzsch Feinmahltechnik, FHZ GmbH, Hosokawa-Alpine AG, Willy A. Bachofen AG Maschinenfabrik and Bühler GmbH.

- 5 In particular embodiments of the invention, step ii. is carried out in a stirred media mill, also termed agitated media mill. In other words, step ii. is performed by agitating the suspension together with a media of hard particles, which are harder than the particles of the material M, such that the particles of the material M and the hard particles collide, and the particles are broken in these collisions. The media of hard particles is
10 also referred to as grinding media.

In the stirred media mill, the grinding media is stirred in a closed or open milling chamber, preferably closed milling chamber. The preferred method of stirring is by means of a stirrer comprising a rotating shaft. The shaft may be provided with disks,
15 arms, pins, or other grinding devices. The stirred media mill may be operated in a batch or continuous mode. The stirred media mill may be operated in a vertical or horizontal position, the latter being preferred.

Preferably, the stirred media mill is operated in a continuous mode in which the
20 suspension is recirculated to the inlet of the mill. Recirculation of the product can be driven by conventional means, such as by employing a peristaltic pump. Preferably, the product is recirculated as quickly as possible to achieve a high number of turnovers. The required residence time for achieving the desired fineness will depend on several factors, such as the energy impact, the hardness of the material, the design of the
25 milling apparatus and other features of the milling process, mentioned above. However, a skilled person will be readily in the position to evaluate the required residence time by routine experiments.

Suitable grinding media for the practice of the present invention include metal beads
30 and ceramic beads. Suitable metal beads include beads of carbon steel and beads of stainless steel. Preferred ceramic beads include beads of zirconium oxide, beads of yttrium or cerium stabilized zirconium oxide, beads of zirconium silicate, and beads of alumina. The preferred grinding media for the purpose of the invention are beads of yttrium stabilized zirconium oxide.

35

The grinding media used for particle size reduction are preferably spherical. The grinding media for the practice of the present invention preferably have an average size ranging from about 50 to 2000 microns (0.05 to 2.0 mm), more preferably from about 200 to 1000 microns (0.2 to 1.0 mm).

40

Preferably the grinding media load measured as a volume percent of the mill chamber

volume is 60 to 90%, more preferably 70 to 85 %.

Stirred media mills are operated at tip speeds in the range of 3 to 15 m/s. Preferably in the range of 8 to 12 m/s.

5

Suitable agitated media mills are commercially available, e.g. from Netzsch Feinmahltechnik, Willy A. Bachofen AG Maschinenfabrik and Bühler GmbH.

Step ii. may be performed by using a single comminution device. However, it is also possible to combine two or more comminution devices in series.

10

According to the invention, step ii. is performed in the presence of a protective colloid. The amount of the protective colloid in the composition subjected to step ii. is frequently from 0.1 to 50% by weight, in particular from 2 to 40% by weight and most preferred from 3 to 30% by weight, based on the total amount of material M to be encapsulated and aminoplast pre-condensate. The concentration of the protective colloid in the suspension subjected to step ii. is usually in the range of 0.1 to 10 %, in particular from 0.2 to 8 % and especially from 0.3 to 5 %, based on the total weight of the suspension subjected to step i.

15
20

According to the invention, step ii. is performed in the presence of an aminoplast pre-condensate. During step ii. the concentration of the aminoplast pre-condensate in the suspension subjected to step ii. is frequently in the range of 0.5 to 30 % by weight, in particular from 1 to 10 % by weight, based on the total weight of the suspension.

25

The concentration of the material M in the suspension subjected to step ii. is frequently in the range of 5 to 40 % by weight, in particular in the range of 7 to 35 % by weight, based on the total weight of the suspension.

If present, the concentration of the surfactant B in the suspension subjected to step ii. is frequently in the range of 0.001 % by weight to 2 % by weight, in particular from 0.01 to 1 % by weight, based on the total of the suspension.

30

Preferably, step ii. is performed at a temperature, which is below the melting point of the material M, in particular at a temperature which is at least 10°C, in particular at least 20°C below the melting point of the material M.

35

The polycondensation of the aminoplast pre-condensate can be effected or initiated in a well-known manner, e.g. by heating the aqueous suspension obtained in step ii. to a certain reaction temperature, at a pH, where the polycondensation at the reaction temperature occurs. During the polycondensation, the aminoplast pre-condensate is

40

converted into a water-insoluble aminoplast resin, which precipitates from the aqueous phase and deposits preferably on the surface of the solid particles material M, thereby embedding or surrounding the material M.

- 5 Preferably, the polycondensation of the aminoplast is performed at pH of less than pH 6, in particular at a pH of at most pH 5, especially at a pH of at most pH 4, e.g. in the range of pH 0 to 6, more particularly in the range from pH 1 to 5 or in the range from pH 2 to 4.
- 10 The pH of the aqueous suspension is usually adjusted by addition of suitable amounts of an organic or inorganic acid, such as sulfuric acid, hydrochloric acid, phosphoric acid, a carboxylic acid including alkanolic acids, alkanedioic acids or hydroxycarboxylic acids, such as formic acid, acetic acid, propionic acid, oxalic acid, malic acid or citric acid, and alkyl or arylsulfonic acids, such as methanesulfonic acid or toluenesulfonic acid.
- 15 It is preferred, but not mandatory, if at least a portion, in particular the majority of the acid is present in the aqueous suspension, before the aqueous suspension is heated to the reaction temperature.

- Preferably, the polycondensation of the aminoplast pre-condensate is performed at
- 20 elevated temperature, in particular at a temperature of at least 40°C, in particular at least 50°C, e.g. at a temperature in the range of 40 to 100°C, in particular in the range of 45 to 95°C or in the range of 50 to 90°C. It may be possible to effect the start of the polycondensation of the aminoplast at a comparatively low temperature, e.g. a temperature in the range of 40 to 65°C or 45 to 60°C and then complete the
- 25 polycondensation reaction at a higher temperature of e.g. 50 to 100°C or 60 to 90°C. The time for completing the polycondensation may vary, depending on the reactivity of the pre-condensate, the temperature and the pH of the aqueous suspension and may take from 1 h to 24 h, in particular from 2 to 12 h. Preferably, the polycondensation reaction is at least partly performed at temperatures of at least 50°C, in particular at
- 30 least 60°C, e.g. for 1 to 8 h at a temperature in the range from 50 to 100°C, in particular 60 to 90°C.

- It is possible to perform steps ii. and iii. successively. It is, however also possible to combine steps ii. and iii., i.e. to perform polycondensation while still performing step ii.
- 35

- If steps ii. and iii. are performed successively, one will perform step ii. first, until the desired particle size of the material M is achieved, and then perform step iii. by effecting the polycondensation of the aminoplast pre-condensate as described above. Then, steps ii. and iii. are frequently performed in separate vessels, i.e. step ii. is
- 40 performed in a suitable device for comminution of the particles of the material M, such as an agitated media mill, and then the obtained suspension of the material M is

transferred into a reaction vessel, where the polycondensation is effected as described above.

If steps ii. and iii. are combined in a single step, polycondensation of step iii. is performed while still performing comminution step ii. It is not necessary to start polycondensation together with comminution. Rather, one will preferably start with step ii. and continue step ii. while starting the polycondensation of step iii. In particular, the slurry of step i. is subjected to step ii. until a certain fineness of the particles in the suspension is achieved and then polycondensation is started by lowering pH and/or by increasing the temperature, while still further performing means for comminuting the particles. For example, the slurry of step i. is transferred to a milling device, e.g. an agitated media mill and subjected to comminution, until the $d(0.9)$ value is below 40 μm , in particular below 30 μm or below 20 μm , and then, the suspension is heated, e.g. to a temperature of at least 50°C or at least 60°C and the pH of the suspension is lowered, e.g. to a pH of at most 5.0, in particular at most 4.0 while further subjecting the suspension to comminution in the milling device, e.g. agitated media mill. It is also possible, for example, to transfer the slurry of step i. to a milling device, e.g. an agitated media mill and subjected to comminution, until the $d(0.9)$ value is below 40 μm , in particular below 30 μm or below 20 μm , discharging the suspension from the milling device, followed by effecting the conditions for polycondensation, e.g. by heating the suspension, e.g. to a temperature of at least 50°C or at least 60°C, and lowering the pH of the suspension, e.g. to a pH of at most 5.0, in particular at most 4.0, and then recharging the suspension to the milling device and subjecting the suspension to comminution in the milling device.

The microcapsules/microparticles obtained by the process of the present invention are discrete particles having usually a particle size of less than 200 μm , frequently less than 100 μm and in particular less than 50 μm , given as $d(0.9)$ value. Preferably, the particle size of the microcapsule particles, i.e. their diameter, will not exceed 40 μm , in particular not exceed 35 μm and especially not exceed 30 μm . The particle size given is the so called $d(0.9)$ -value as defined above. The microcapsule particles frequently have an average particle diameter, herein also termed $d(0.5)$ -value, ranging from 0.5 to 25 μm , in particular from 0.5 to 20 μm , especially from 0.5 to 10 μm .

The concentration of the material M in the suspension obtained in step iii. is frequently in the range of 3 to 40 % by weight, in particular in the range of 5 to 35 % by weight, based on the total weight of the suspension.

The thus obtained aqueous dispersion of the microparticles or microcapsules, respectively, may be neutralized by the addition of a base. Preferably, the pH of the dispersion is adjusted to a pH of at least 6, e.g. a pH in the range of pH 6 to 10, in

particular in the range of pH 6.5 to 9.0.

From the aqueous suspension obtained by the process as described herein, the microparticles can be isolated, e.g. by filtration or centrifugation, or the aqueous suspension may be spray-dried, granulated or freeze-dried, to obtain a solid composition in the form of a powder or granules. The solid composition may be re-dispersed or formulated by using formulation auxiliaries as described below.

Customary formulation auxiliaries include, e.g. viscosity-modifying additives (thickeners), antifoam agents, preservatives, buffers, inorganic dispersants, etc., which are usually employed in aqueous formulations. Such auxiliaries may be incorporated into the aqueous suspension, after step iii) of the preparation process described herein has been carried out. The amount of additives will generally not exceed 10% by weight, in particular 5% by weight of the total weight of the aqueous suspension.

Suitable inorganic dispersants, also termed anticaking agents, for preventing agglutination of the microparticles, are silica (such as, for example Sipernat® 22 from Degussa), alumina, calcium carbonate and the like. In the context of the present invention silica is a preferred inorganic dispersant. The concentration of inorganic dispersants in the final suspension will generally not exceed 2% by weight, based on the total weight of the final suspension, and, if present, it is preferably in the range from 0.01 to 2% by weight, in particular from 0.02 to 1.5% by weight and especially from 0.1 to 1% by weight, based on the total weight of the final formulation.

Suitable thickeners are compounds which affect the flow behavior of the suspension concentrate and may assist in stabilizing the aqueous suspension of the microparticles against caking. Mention may be made, in this connection, for example, of commercial thickeners based on polysaccharides, such as methylcellulose, carboxymethylcellulose, hydroxypropylcellulose (Klucel® grades), Xanthan Gum (commercially available e.g. as Kelzan® grades from Kelco or Rhodopol® grades from Rhodia), synthetic polymers, such as acrylic acid polymers (Carbopol® grades), polyvinyl alcohol (e.g. Mowiol® and Poval® grades from Kuraray) or polyvinyl pyrrolones, silicic acid or phyllosilicates, such as montmorillonite and bentonites, which may be hydrophobized, (commercially available as Attaclay® grades and Attaflow® grades from BASF SE; or as Veegum® grades and Van Gel® grades from R.T. Vanderbilt). The concentration of thickeners in the aqueous suspension will generally not exceed 2% by weight, based on the total weight of the aqueous suspension, and is preferably in the range from 0.01 to 2% by weight, in particular from 0.02 to 1.5% by weight and especially from 0.1 to 1% by weight, based on the total weight of the aqueous suspension or the final formulation, respectively.

Antifoam agents suitable for the compositions according to the invention are, for example, silicone emulsions (such as, for example, Silicone SRE-PFL from Wacker or Rhodorsil® from Bluestar Silicones), polysiloxanes and modified polysiloxanes including polysiloxane blockpolymers such as FoamStar® SI and FoamStar® ST products of
5 BASF SE, long-chain alcohols, fatty acids, organofluorine compounds and mixtures thereof.

Suitable preservatives to prevent microbial spoiling of the compositions of the invention include formaldehyde, alkyl esters of p-hydroxybenzoic acid, sodium benzoate,
10 2-bromo-2-nitropropane-1,3-diol, o-phenylphenol, thiazolinones, such as benzisothiazolinone, 5-chloro-2-methyl-4-isothiazolinone, pentachlorophenol, 2,4-dichlorobenzyl alcohol and mixtures thereof. Commercially available preservatives that are based on isothiazolinones are for example marketed under the trademarks Proxel® (Arch Chemical), Acticide® MBS (Thor Chemie) and Kathon® MK (Rohm &
15 Haas).

If appropriate, the compositions according to the invention, in particular the aqueous suspensions, may comprise buffers to regulate the pH. Examples of buffers are alkali metal salts of weak inorganic or organic acids such as, for example, phosphoric acid,
20 boric acid, acetic acid, propionic acid, citric acid, fumaric acid, tartaric acid, oxalic acid and succinic acid.

In addition, the compositions according to the invention, in particular the aqueous suspensions, can be formulated with conventional binders, for example aqueous
25 polymer dispersions, water-soluble resins, for example water-soluble alkyd resins, or waxes.

The aqueous dispersions of microcapsules obtainable by the process as defined herein contain an agriculturally active compound. Consequently, they can be used for
30 controlling harmful organisms, such phytopathogenic fungi, undesired plants, undesired insect or mite, and/or for regulating the growth of plants, depending on the type of agriculturally active compound. Hence, the invention also relates to the use of an aqueous dispersion of microcapsules obtainable by a process as defined herein for controlling phytopathogenic fungi and/or undesired plant growth and/or undesired
35 insect or mite attack and/or for regulating the growth of plants.

The aqueous dispersions can be applied as such or in formulated form in a customary manner. Therefore, the invention also relates to a method of controlling
phytopathogenic pests, in particular for controlling phytopathogenic fungi and/or
40 undesired plant growth and/or undesired insect or mite attack, wherein the aqueous dispersion of microcapsules obtainable by a process as defined herein is allowed to act

on the respective pests, their environment or the crop plants to be protected from the respective pest, on the soil and/or on undesired plants and/or on the crop plants and/or on their environment. The invention also relates to a method for regulating the growth of plants, wherein the aqueous dispersion of microcapsules obtainable by a process as defined herein is allowed to act on the crop plants the crop plants and/or on their environment.

When employed in plant protection, the amounts of active compound applied are, depending on the kind of desired effect, from 0.001 to 2 kg per ha, preferably from 0.005 to 2 kg per ha, more preferably from 0.05 to 0.9 kg per ha, in particular from 0.1 to 0.75 kg per ha. In treatment of plant propagation materials such as seeds, e. g. by dusting, coating or drenching seed, amounts of active compound of from 0.1 to 1000 g, preferably from 1 to 1000 g, more preferably from 1 to 100 g and most preferably from 5 to 100 g, per 100 kilogram of plant propagation material (preferably seed) are generally applied. When used in the protection of materials or stored products, the amount of active compound applied depends on the kind of application area and on the desired effect. Amounts customarily applied in the protection of materials are 0.001 g to 2 kg, preferably 0.005 g to 1 kg, of active compound per cubic meter of treated material.

Depending on the type of active compound, the dispersion of the microcapsules or a formulation thereof may be used for the purposes of treatment of plant propagation materials, particularly seeds. The dispersions in question give, after two-to-tenfold dilution, active compound concentrations of from 0.01 to 20% by weight, preferably from 0.1 to 15% by weight, in the ready-to-use preparations. Application can be carried out before or during sowing. Methods for applying the dispersion on to plant propagation material or treating the plant propagation material therewith, especially seeds, include dressing, coating, pelleting, dusting, soaking and in-furrow application methods of the propagation material. Preferably, the respective dispersion or a formulation thereof, is applied on to the plant propagation material by a method such that germination is not induced, e. g. by seed dressing, pelleting, coating and dusting.

Various types of oils, wetters, adjuvants, fertilizer, or micronutrients, and other pesticides (e.g. herbicides, insecticides, fungicides, growth regulators, safeners) may be added to the respective dispersion or a formulations thereof as premix or, if appropriate not until immediately prior to use (tank mix). These agents can be admixed with the compositions according to the invention in a weight ratio of 1:100 to 100:1, preferably 1:10 to 10:1.

The user applies the respective dispersion or a formulation thereof usually from a predosage device, a knapsack sprayer, a spray tank, a spray plane, or an irrigation

system. Usually, the respective dispersion or a formulation thereof is made up with water, buffer, and/or further auxiliaries to the desired application concentration and the ready-to-use spray liquor or the agrochemical composition according to the invention is thus obtained. Usually, 20 to 2000 liters, preferably 50 to 400 liters, of the ready-to-use
5 spray liquor are applied per hectare of agricultural useful area.

Examples of suitable crop plants are cereals, for example wheat, rye, barley, triticale, oats or rice; beet, for example sugar or fodder beet; pome fruit, stone fruit and soft fruit, for example apples, pears, plums, peaches, almonds, cherries, strawberries,
10 raspberries, currants or gooseberries; legumes, for example beans, lentils, peas, lucerne or soybeans; oil crops, for example oilseed rape, mustard, olives, sunflowers, coconut, cacao, castor beans, oil palm, peanuts or soybeans; cucurbits, for example pumpkins/squash, cucumbers or melons; fiber crops, for example cotton, flax, hemp or jute; citrus fruit, for example oranges, lemons, grapefruit or tangerines; vegetable
15 plants, for example spinach, lettuce, asparagus, cabbages, carrots, onions, tomatoes, potatoes, pumpkin/squash or capsicums; plants of the laurel family, for example avocados, cinnamon or camphor; energy crops and industrial feedstock crops, for example maize, soybeans, wheat, oilseed rape, sugar cane or oil palm; maize; tobacco; nuts; coffee; tea; bananas; wine (dessert grapes and grapes for vinification);
20 hops; grass, for example turf; sweetleaf (*Stevia rebaudania*); rubber plants and forest plants, for example flowers, shrubs, deciduous trees and coniferous trees, and propagation material, for example seeds, and harvested produce of these plants.

The term crop plants also includes those plants which have been modified by breeding,
25 mutagenesis or recombinant methods, including the biotechnological agricultural products which are on the market or in the process of being developed. Genetically modified plants are plants whose genetic material has been modified in a manner which does not occur under natural conditions by hybridizing, mutations or natural recombination (i.e. recombination of the genetic material). Here, one or more genes
30 will, as a rule, be integrated into the genetic material of the plant in order to improve the plant's properties. Such recombinant modifications also comprise posttranslational modifications of proteins, oligo- or polypeptides, for example by means of glycosylation or binding polymers such as, for example, prenylated, acetylated or farnesylated residues or PEG residues.

35

I. Analytics:

Particle size Distribution (PSD) was determined by statistic laser scattering using a Malvern Mastersizer 200 according to European norm ISO 13320 EN. The data were
40 treated according to the Mie-Theory by software using a "universal model" provided by

Malvern Instruments. Important parameters are the d_n -values for $n = 10, 50$ and 90 , the d_{10} , d_{50} and d_{90} .

5 Solid content of the final dispersion was measured by evaporating the volatiles of small probe of the aqueous suspension in an oven at 105°C for 2 hours. The value indicated for the examples is an average value from three parallel experiments.

II. Ingredients:

10	Protective colloid 1:	20% aqueous solution of poly(2-acrylamido-2-methylpropane sulfonic acid) sodium salt with pH 2.5-4;
	Protective colloid 2:	Naphthalenesulfonic acid formaldehyde condensate Sodium salt
	Surfactant 1:	15% aqueous solution of sodium dodecyl sulfate
15	Pre-condensate P1:	70% w/w aqueous solution of etherified melamine formaldehyde pre-condensate (Luracoll® SD of BASF SE);
	Thickener:	Viscalex HV 30® (30% aqueous solution of an acrylic polymer; BASF SE)
	Saflufenacil:	Anhydrate, purity 98.8%
20	Pyrimethanil:	Crystalline, purity > 98%

For the following experiments a MicroCer® bead mill of Netzsch Feinmahltechnik GmbH, Germany having an internal volume of 80 mL and a ZETA® agitator of Netzsch Feinmahltechnik GmbH was used. A sieve (200 μm) was installed inside the mill at the
 25 outlet. The mill was connected with a vessel and operated in a circuit mode.

Example 1

The stirred media mill was filled with zircon oxide grinding media with an average
 30 diameter of 0.6 – 0.8 mm. Filling degree was 62.5 % of the internal volume.

150 g crystalline saflufenacil anhydrate was mixed with 790.4 g water, 20 g protective colloid 2, 2.7 g surfactant 1 and 36.9 g aminoplast pre-condensate P1 in a stirred vessel until a homogenous suspension was obtained.

35 The above slurry was subjected to milling. The mill was operated at a tip speed that averaged 12 m/s. The suspension was passed through the mill by circuit mode. After 2 hours of grinding the average particle size, by volume $d(0.5)$, was reduced to 1.6 μm and 90 % of the particles had sizes of less than 4.0 μm .

40 The thus obtained suspension was stable for several hours and could be processed in the following encapsulation step.

The suspension was transferred into a reaction vessel equipped with a stirrer. Then the suspension was warmed to 30 °C and 41 g of a 10 % aqueous formic acid with stirring. Stirring was continued for further 1 h at 30°C at 250 rpm. Then, the reaction vessel was slowly heated within 60 min to 80°C and the temperature was kept at 80°C for further 120 min with stirring. Then the reaction vessel was cooled to 22°C.

The obtained aqueous suspension had a content of saflufenacil of 15.0 % by weight. The d(0.5) value was 1.7 µm, d(0.9) was 4.4 µm.

10

Example 2

Composition: 230 g saflufenacil anhydrate, 20 g protective colloid 2, 2,7 g surfactant 1 and 36.9 g aminoplast condensate P1, 710,4 g water

15

Apparatus settings and parameters for the mixing and milling were chosen according to Example 1. After milling particle size by volume d(0.5), was reduced to 1.6 µm and 90 % of the particles had sizes less than 3.8 µm. The polymerization was performed under the conditions of Example 1.

20

The obtained aqueous suspension had a content of saflufenacil of 23 % by weight. The d(0.5) value was 12.1 µm, and d(0.9) was 63.9 µm.

Example 3

Composition: 300 g saflufenacil anhydrate, 20 g protective colloid 2, 2,7 g surfactant 1 and 36.9 g aminoplast pre-condensate P1, 710,4 g water

Apparatus settings and parameters for the mixing and milling were chosen according to Example 1. After milling particle size by volume d(0.5), was reduced to 1.3 micron and 90 % of the particles had sizes less than 3.0 µm. The polymerization was performed under the conditions of Example 1.

30

The obtained aqueous suspension had content of saflufenacil of 30 % by weight. The d(0.5) value was 7.4 µm and d(0.9) was 190.0 µm.

Example 4

Composition: 240 g saflufenacil anhydrate, 29 g protective colloid 2, 17 g surfactant 1, 55 g aminoplast pre-condensate P1, 659 g water.

40

Apparatus settings and parameters for the mixing and milling were chosen according to Example 1. The polymerization was performed under the conditions of Example 1.

5 The obtained aqueous suspension had content of saflufenacil of 24 % by weight. The d(0.5) value was 2.4 μm and d(0.9) was 4.9 μm .

Example 5

10 Composition: 160.2 g saflufenacil anhydrate, 11.9 g surfactant 1, 57.84 g protective colloid 1, 36.36 g aminoplast pre-condensate P1, 382.24 g water.

Apparatus settings and parameters for the mixing and milling were chosen according to Example 1. The polymerization was performed under the conditions of Example 1.

15 The obtained aqueous suspension had a content of saflufenacil of 24 % by weight. The d(0.5) value was 3.1 μm .

Example 6

20 Composition: 227 g Pyrimethanil, 164 g protective colloid 1, 17 g surfactant 1, 51 g aminoplast pre-condensate P1, 519 g water.

Apparatus settings and parameters for the mixing and milling were chosen according to Example 1. The polymerization was performed under the conditions of Example 1.

25 The obtained aqueous suspension had a content of pyrimethanil of 23 % by weight. The d(0.5) value was 8.4 μm and d(0.9) was 14.0 μm .

Example 7

30 Composition: 100 g Pyrimethanil, 72 g protective colloid 1, 8 g surfactant 1, 15, 23 g aminoplast pre-condensate P1, 797 g water.

35 The above composition was subjected to milling. Milling parameters during milling were chosen according to Example 1. After having milled the suspension for 2 hours in the presence of the aminoplast pre-condensate, the tip speed of the mill was reduced from 12 m/s to 3.6 m/s and the vessel was heated until the milled suspension had a temperature of 80 °C. Once the temperature was reached, formic acid was added into the vessel during constantly stirring the suspension in the vessel and the suspension
40 was pumped through the stirred media mill until a pH of 3.5 was achieved. Thereafter,

the suspension was milled for 2 further hours at 3.6 m/s in circuit mode at a temperature of 80 °C and the pH of 3.5.

5 The obtained aqueous suspension had a solid content of 7 % by weight. The d(0.5) value was 8.4 µm, the d(0.9) was 32.7 µm.

Example 8

10 Composition: 100 g Pyrimethanil, 72 g protective colloid 1, 8 g surfactant 1, 23 g aminoplast pre-condensate P1, 797 g water.

15 The above composition was subjected to milling. Milling parameters were chosen according to Example 1, with the exception, that the temperature of the slurry was adjusted to 80 °C before the milling was started. Once the temperature of 80 °C was reached, the suspension was pumped through the mill by circuit mode and comminuted with 12 m/s stirrer tip speed. After the milling had been started, formic acid was added into the vessel in an amount that a pH of 3.5 was obtained. The sample was milled for further 2 hours at a tip speed of 12 m/s and a temperature of 80 °C.

20 The obtained aqueous suspension had a solid content of 7 % by weight. The d(0.5) value was 13.9 µm, the d(0.9) was 30.0 µm.

Example 9

25 Composition: 66.7 g saflufenacil, 5.0 g surfactant 1, 24.1 g protective colloid 1, 15.2 g aminoplast pre-condensate P1, 539 g deionised water.

30 The above composition was subjected to milling. Milling parameters were chosen according to Example 1, with the exception, that the temperature of the slurry was adjusted to 80 °C, before the milling was started. Once the temperature of 80 °C was reached, the suspension was pumped through the mill by circuit mode and comminuted with 12 m/s stirrer tip speed. After the milling had been started, formic acid was added into the vessel until a pH of 3.5 was obtained. The sample was milled for further 2 hours at a tip speed of 12 m/s and a temperature of 80 °C.

35 The obtained aqueous suspension had a content of saflufenacil of 10 % by weight. The d(0.5) value was 19 µm.

We claim:

1. A process for preparing an aqueous dispersion of microcapsules containing a solid organic material, selected from agriculturally active compounds, and an aminoplast resin which surrounds or embeds the solid material, which comprises the following steps:
 - i. providing an aqueous slurry of a solid material in the form of coarse particles,
 - ii. subjecting the aqueous suspension to shear forces in order to comminute the coarse particles, whereby an aqueous suspension of fine particles of the solid organic material is obtained;
 - iii. performing a polycondensation of an aminoplast pre-condensate in the aqueous suspension obtained in step ii.;wherein the milling of step ii. is performed in the presence of at least one protective colloid and at least a portion of the aminoplast pre-condensate subjected to the polycondensation of step iii.
2. The process of claim 1, wherein the aminoplast pre-condensate is selected from the group consisting of melamine formaldehyde pre-condensates and urea formaldehyde pre-condensates and mixtures thereof.
3. The process of claim 2, wherein the aminoplast pre-condensate comprises an etherified melamine formaldehyde pre-condensate.
4. The process of any of the preceding claims, wherein at least 50 % of the aminoplast pre-condensate subjected to the polycondensation of step iii. is present in the aqueous suspension during the milling.
5. The process of any of the preceding claims, wherein the aminoplast pre-condensate is present in the aqueous suspension of step ii. in an amount from 1 to 30 % by weight and especially from 5 to 25 % by weight, based on solid material to be encapsulated.
6. The process of any of the preceding claims, wherein the protective colloid is an anionic polymer having a plurality of sulfate or sulfonate groups.

7. The process of claim 6, wherein the protective colloid is selected from homo- or copolymer of a (meth)acrylate monomer or a (meth)acrylamide monomer having a sulfonic acid group and arylsulfonic acid formaldehyde condensates, and mixtures thereof.
- 5
8. The process of any one of the preceding claims, where the aqueous suspension of step ii. additionally contains at least one anionic emulsifier different from the protective colloid.
- 10
9. The process of any one of the preceding claims, where the coarse particles of the solid material are milled to a volume average particle diameter $d(0.5)$ in the range from 0.5 to 25 μm , as determined by dynamic light scattering.
- 15
10. The process of any one of the preceding claims, where the comminution in step ii. is performed by grinding.
11. The process of claim 10, where the comminution in step ii. is performed in a stirred media mill.
- 20
12. The process of any one of the preceding claims, where the concentration of the solid material in the aqueous slurry of step i. is from 5 to 40 % by weight.
- 25
13. The process of any one of the preceding claims, where the solid material is selected from organic compounds having a melting point above 50°C.
- 30
14. The process of any one of the preceding claims, where at least 50 % of the aminoplast pre-condensate subjected to the polycondensation of step iii. and at least 50 % of the protective colloid are contained in the aqueous suspension of the solid material prior to the comminution.
- 35
15. The process of any one of the preceding claims, where the aqueous suspension of the solid material has a pH of at least pH 6 during the comminution in step ii.
16. The process of any one of the preceding claims, where the polycondensation of the aminoplast pre-condensate in the aqueous suspension obtained in step ii. is performed at a pH of at most pH 5, e.g. at a pH in the range from pH 1 to pH 4.

17. A method of controlling phytopathogenic fungi and/or undesired plant growth and/or undesired insect or mite attack and/or for regulating the growth of plants, wherein the aqueous dispersion of microcapsules obtainable by a process as defined in any of claims 1 to 16 is allowed to act on the respective pests, their
5 environment or the crop plants to be protected from the respective pest, on the soil and/or on undesired plants and/or on the crop plants and/or on their environment.
18. The use of an aqueous dispersion of microcapsules obtainable by a process as
10 defined in any of claims 1 to 16 for controlling phytopathogenic fungi and/or undesired plant growth and/or undesired insect or mite attack and/or for regulating the growth of plants.

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/075187

A. CLASSIFICATION OF SUBJECT MATTER

INV. B01J13/18 A01N25/28 A61K9/50 C09B67/02
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B01J A01N A23P A61K C09B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2012/095436 A1 (BASF SE [DE]; TARANTA CLAUDE [DE]; BORK THOMAS [DE]; SCHROEDER-GRIMONP) 19 July 2012 (2012-07-19) claims 1, 13, 15 page 6, line 37 - line 38 -----	17,18
A	WO 95/13698 A1 (ZENECA LTD [GB]) 26 May 1995 (1995-05-26) claims 17, 25 page 4 -----	1-18
A	WO 2008/155097 A2 (SYNGENTA PARTICIPATIONS AG [CH]; SYNGENTA LTD [GB]; PEDRONI DOMINGOS []) 24 December 2008 (2008-12-24) the whole document ----- -/-	1-18



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

14 December 2016

Date of mailing of the international search report

21/12/2016

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Tarallo, Anthony

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2016/075187

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 2007/072046 A2 (SYNGENTA LTD [GB]; MULQUEEN PATRIC JOSEPH [GB]; WALLER ANNE [GB]; SHIR) 28 June 2007 (2007-06-28) the whole document -----	1-18
A	WO 96/33611 A2 (ZENECA LTD [GB]) 31 October 1996 (1996-10-31) the whole document -----	1-18
A	US 2013/287844 A1 (TARANTA CLAUDE [DE] ET AL) 31 October 2013 (2013-10-31) the whole document -----	1-18
A	WO 2011/064312 A1 (BASF SE [DE]; JUNG MARC RUDOLF [DE]; KOPLIN TOBIAS JOACHIM [DE]; KRAPP) 3 June 2011 (2011-06-03) the whole document -----	1-18
A	WO 2009/098232 A1 (BASF SE [DE]; LEVY TATJANA [DE]; JUNG MARC RUDOLF [DE]; BERGHAUS RAINE) 13 August 2009 (2009-08-13) the whole document -----	1-18

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2016/075187

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2012095436	A1	19-07-2012	
		AU 2012206618 A1	25-07-2013
		BR 112013017684 A2	12-07-2016
		CA 2823105 A1	19-07-2012
		CN 103298338 A	11-09-2013
		EA 201300811 A1	30-12-2013
		EP 2663182 A1	20-11-2013
		JP 5852673 B2	03-02-2016
		JP 2014501775 A	23-01-2014
		KR 20140043326 A	09-04-2014
		US 2013287844 A1	31-10-2013
		WO 2012095436 A1	19-07-2012
WO 9513698	A1	26-05-1995	
		AT 167980 T	15-07-1998
		AU 678074 B2	15-05-1997
		AU 8111094 A	06-06-1995
		BG 62591 B1	31-03-2000
		BG 100562 A	31-12-1996
		BR 9408051 A	24-12-1996
		CA 2176513 A1	26-05-1995
		CN 1135160 A	06-11-1996
		CZ 9601396 A3	12-02-1997
		DE 69411583 D1	13-08-1998
		DE 69411583 T2	18-02-1999
		DK 0730406 T3	28-06-1999
		EP 0730406 A1	11-09-1996
		ES 2119354 T3	01-10-1998
		HU 221738 B1	28-12-2002
		IL 111626 A	22-09-1999
		JP 3848676 B2	22-11-2006
		JP H09505074 A	20-05-1997
		NO 961963 A	14-05-1996
		NZ 275848 A	29-01-1997
		PL 314424 A1	02-09-1996
		RO 118617 B1	29-08-2003
		RU 2159037 C2	20-11-2000
		SI 9420069 A	31-12-1996
		US 6015571 A	18-01-2000
		WO 9513698 A1	26-05-1995
		ZA 9409019 B	17-07-1995
WO 2008155097	A2	24-12-2008	
		AU 2008266495 A1	24-12-2008
		BR PI0813124 A2	30-12-2014
		CA 2690070 A1	24-12-2008
		CN 101765368 A	30-06-2010
		EA 201000005 A1	30-06-2010
		EP 2166839 A2	31-03-2010
		JP 2010530394 A	09-09-2010
		KR 20100031686 A	24-03-2010
		US 2010267563 A1	21-10-2010
		WO 2008155097 A2	24-12-2008
		ZA 200908655 B	25-08-2010
WO 2007072046	A2	28-06-2007	
		AT 528988 T	15-11-2011
		AU 2006327936 A1	28-06-2007
		AU 2006327942 A1	28-06-2007
		BR PI0620371 A2	08-11-2011
		BR PI0620458 A2	08-11-2011
		CA 2631394 A1	28-06-2007

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2016/075187

Patent document cited in search report	Publication date	Patent family member(s)	Publication date	
		CA 2632154 A1	28-06-2007	
		CN 101404880 A	08-04-2009	
		CN 101466263 A	24-06-2009	
		CY 1112515 T1	09-12-2015	
		DK 1965638 T3	23-01-2012	
		EA 200870114 A1	28-04-2009	
		EA 200870115 A1	30-06-2009	
		EP 1965637 A2	10-09-2008	
		EP 1965638 A2	10-09-2008	
		ES 2375642 T3	02-03-2012	
		IL 191747 A	30-07-2015	
		IL 191754 A	30-07-2015	
		JP 5329972 B2	30-10-2013	
		JP 2009520795 A	28-05-2009	
		JP 2009520796 A	28-05-2009	
		JP 2014024863 A	06-02-2014	
		KR 20080078674 A	27-08-2008	
		KR 20080078839 A	28-08-2008	
		NZ 595675 A	28-03-2013	
		NZ 597029 A	28-09-2012	
		PT 1965638 E	17-11-2011	
		RS 52059 B	30-04-2012	
		SG 170076 A1	29-04-2011	
		SG 170077 A1	29-04-2011	
		SI 1965638 T1	31-01-2012	
		UA 95269 C2	25-07-2011	
		UA 95270 C2	25-07-2011	
		US 2009226496 A1	10-09-2009	
		US 2009269382 A1	29-10-2009	
		WO 2007072046 A2	28-06-2007	
		WO 2007072052 A2	28-06-2007	
		ZA 200804922 B	27-05-2009	
		ZA 200805058 B	27-05-2009	

WO 9633611	A2	31-10-1996	AP 873 A	11-09-2000
			AR 003681 A1	09-09-1998
			AT 195216 T	15-08-2000
			AU 711892 B2	21-10-1999
			AU 5340996 A	18-11-1996
			BG 63522 B1	30-04-2002
			BG 101990 A	30-04-1998
			BR 9604990 A	06-04-1999
			CA 2219001 A1	31-10-1996
			CN 1185090 A	17-06-1998
			CO 5040219 A1	29-05-2001
			CZ 9703401 A3	17-06-1998
			DE 69609712 D1	14-09-2000
			DE 69609712 T2	29-03-2001
			DK 0824313 T3	18-12-2000
			EG 20936 A	28-06-2000
			EP 0824313 A2	25-02-1998
			ES 2148749 T3	16-10-2000
			GR 3034610 T3	31-01-2001
			HU 9900466 A2	28-05-1999
			JP 3961021 B2	15-08-2007
			JP H11504030 A	06-04-1999
			JP 2007039468 A	15-02-2007
			NO 974947 A	22-12-1997

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2016/075187

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		NZ 305421 A	28-01-1999
		OA 10530 A	13-03-2001
		PE 44197 A1	16-10-1997
		PL 323051 A1	02-03-1998
		PT 824313 E	28-09-2001
		RO 120446 B1	28-02-2006
		SK 145697 A3	05-08-1998
		TR 9701259 T1	21-02-1998
		TW 299223 B	01-03-1997
		US 5846554 A	08-12-1998
		US 6077522 A	20-06-2000
		US 6149843 A	21-11-2000
		WO 9633611 A2	31-10-1996
		ZA 9603303 B	17-12-1996

US 2013287844	A1	31-10-2013	
		AU 2012206618 A1	25-07-2013
		BR 112013017684 A2	12-07-2016
		CA 2823105 A1	19-07-2012
		CN 103298338 A	11-09-2013
		EA 201300811 A1	30-12-2013
		EP 2663182 A1	20-11-2013
		JP 5852673 B2	03-02-2016
		JP 2014501775 A	23-01-2014
		KR 20140043326 A	09-04-2014
		US 2013287844 A1	31-10-2013
		WO 2012095436 A1	19-07-2012

WO 2011064312	A1	03-06-2011	
		BR 112012012875 A2	08-09-2015
		CN 102724869 A	10-10-2012
		EP 2506708 A1	10-10-2012
		JP 2013512224 A	11-04-2013
		KR 20120113221 A	12-10-2012
		US 2012283104 A1	08-11-2012
		WO 2011064312 A1	03-06-2011

WO 2009098232	A1	13-08-2009	
		BR PI0906673 A2	26-07-2016
		CA 2712454 A1	13-08-2009
		CN 101939090 A	05-01-2011
		EA 201001233 A1	29-04-2011
		EP 2240267 A1	20-10-2010
		IL 207017 A	21-04-2016
		JP 5665547 B2	04-02-2015
		JP 2011510959 A	07-04-2011
		US 2010323892 A1	23-12-2010
		WO 2009098232 A1	13-08-2009
