

(12) STANDARD PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 2016201918 B2**

(54) Title
Package for a surgical mesh

(51) International Patent Classification(s)
B65D 81/20 (2006.01) **B65B 31/00** (2006.01)
A61B 17/00 (2006.01) **B65D 81/24** (2006.01)
A61F 2/00 (2006.01)

(21) Application No: **2016201918** (22) Date of Filing: **2016.03.29**

(30) Priority Data

(31) Number	(32) Date	(33) Country
15305621.3	2015.04.23	EP

(43) Publication Date: **2016.11.10**

(43) Publication Journal Date: **2016.11.10**

(44) Accepted Journal Date: **2020.07.02**

(71) Applicant(s)
Sofradim Production

(72) Inventor(s)
Ferrand, Rebecca;Vail, Thomas;Grepinet, Barbara


(74) Agent / Attorney
Spruson & Ferguson, GPO Box 3898, Sydney, NSW, 2001, AU

(56) Related Art
WO 2005120395 A2
US 4798292 A
US 6889839 B1
US 4203520 A

PACKAGE FOR A SURGICAL MESH

ABSTRACT

A package (1) for a surgical mesh (100), the package (1) comprising a receiving member (2) configured and dimensioned to receive a surgical mesh (100), and a covering member (3) configured and dimensioned to cover the said at least one surgical mesh (100) maintaining with the receiving member (2) the said surgical mesh (100) in a substantially flat position, and a gas channelling network interposed between the said receiving member (2) and the said covering member (3) configured to channel a sterilization gas within the surgical mesh (100).



PACKAGE FOR A SURGICAL MESH

FIELD

[0001] The present invention relates generally to a package for a surgical mesh.

BACKGROUND

[0002] Surgical meshes used for wall reinforcement, for example for the abdominal wall, are widely used in surgery. These surgical meshes are intended to treat, for example, hernias by temporarily or permanently filling a tissue defect. These surgical meshes are made generally from a surgical biocompatible textile and can have a number of shapes, for example rectangular, circular or oval, depending on the anatomical structure to which they are to adapt. The surgical mesh is generally flat and may vary in dimensions, from for example 5 X 10 cm up to 30 X 50 cm, depending on the size of the defect to be treated.

[0003] Before being packaged as a commercial product and shipped to hospitals or end-users, the surgical mesh has to be sterilized to prevent contamination to the patient body in which it is intended to be implanted.

[0004] Gas sterilization is commonly used in the medical field and surgical meshes are usually sterilized by means of ethylene oxide (EtO) gas.

[0005] The sterilization process generally requires the immersion of the surgical mesh in ethylene oxide for a time sufficient for the gas to sterilize the surgical mesh.

[0006] For handling purposes, the surgical mesh is usually inserted into a handling pouch before being submitted to the sterilization process.

[0007] The handling pouch is provided with a window made of a material which is impervious to contamination by microorganisms, bacteria and/or a biologically active substance which may come into contact with the pouch while it is being handled, while at the same time remaining permeable to a sterilization gas such as for example ethylene oxide. Such a material is for example a nonwoven made of filaments of a high density polyethylene bound together by heat and pressure, such as a product sold by the Du Pont de Nemours under the trademark

“Tyvek®”. The surgical mesh to be sterilized is therefore humidified by exposure to water vapor, inserted into a “Tyvek®” pouch and submitted to ethylene oxide gas for sterilization.

[0008] However, it may happen, in particular for large surgical meshes, that the ethylene oxide gas may not reach the entire surface of the surgical mesh and/or does not diffuse in the surgical mesh a sufficiently efficient manner when the surgical mesh is first packaged in a pouch with a “Tyvek®” window. This proves to be a problem as it is desirable that sterilization is completed to a high degree on the entire surface of the surgical mesh.

[0009] Furthermore, in order to proceed to ethylene oxide sterilization, the surgical mesh must be previously humidified. The larger the mesh, the more humid the mesh will be after the sterilization step. In addition, because of its intrinsic nature, the surgical mesh is subject to moisturization. Moisturization has to be avoided during transportation and storage so as to maintain optimal dry conditions of the surgical mesh at the moment of its use.

OBJECT OF THE INVENTION

[0010] It is an object of the present invention to substantially overcome or at least ameliorate one or more of the above disadvantages.

SUMMARY OF THE INVENTION

[0011] In this technical context, it would be desirable to provide a packaging for a surgical mesh allowing an efficient ethylene oxide gas sterilization of all surgical meshes, whatever their size, that would prevent humidity of ambient air to permeate through the packaging, and that would also favour drying of the surgical mesh during storage and transportation.

[0011a] In accordance with the present invention, there is provided a package for a surgical mesh, the package comprising:

a receiving member configured and dimensioned to receive a at least one surgical mesh, the receiving member including transverse resting ribs and longitudinal resting ribs protruding from an inner wall of the receiving member and dividing the inner wall of the receiving member into diffusing compartments, the receiving member further comprising at least one first groove; and

a covering member configured and dimensioned to cover the said at least one surgical mesh maintaining with the receiving member, the said at least one surgical mesh in a substantially flat position, the covering member comprising at least one second groove defining with the at least one first groove of the receiving member at least one channel configured for a sterilising gas to flow within the at least one surgical mesh

[0012] The present invention in at least an embodiment relates to a package for a surgical mesh, the package comprising:

a receiving member configured and dimensioned to receive a surgical mesh;

a covering member configured and dimensioned to cover the said at least one surgical mesh maintaining with the receiving member the surgical mesh in a substantially flat position; and

a gas channelling network interposed between the said receiving member and the said covering member configured to channel a sterilization gas within the surgical mesh.

[0013] Thus, the invention in at least an embodiment may make it possible to maintain a surgical mesh in a substantially flat position and to bring a sterilizing gas in the entire surface of the mesh. This proves to be a great advantage for large surgical meshes, which tend to be partially sterilised using prior art sterilizing techniques.

[0014] In an embodiment of the invention, the receiving member and the covering member define at least one gas diffusing compartment connected to the said gas channelling network.

[0015] In an embodiment of the invention, the covering member includes at least one cut off portion allowing a large exposure to a sterilizing gas and a large exposure for humidity absorption by a desiccant agent.

[0016] In an embodiment, the receiving member comprises a resting rib and an inner wall configured to receive the at least one surgical mesh and the covering member comprises at least one resting rib and an inner wall configured to maintain the at least one surgical mesh between the said resting ribs and to define the at least one gas diffusing compartment for a sterilizing gas.

[0017] In an embodiment, the receiving member comprises at least one groove and the covering member comprises at least one groove defining with at least one groove of the receiving member a channel for a sterilizing gas.

[0018] In an embodiment, the receiving member and/or the covering member comprise at least one transverse resting ribs forming at least two diffusing compartments.

[0019] In an embodiment, the receiving member and the covering member include peripheral rim provided with at least one locking pin and at least one corresponding locking opening.

[0020] In an embodiment, the peripheral rim includes a series of locking toothing.

[0021] In an embodiment, at least one of the receiving member and of the covering member includes a cavity configured to receive a capsule of desiccant material.

[0022] In an embodiment, the receiving member and the covering member have a substantially rectangular shape.

[0023] In an embodiment, the covering member includes at least two cut off portions.

[0024] In an embodiment, the covering member includes a central portion and two lateral portions extending from the central portion.

[0025] In an embodiment, the covering member includes a hinge allowing access to the surgical mesh.

[0026] In an embodiment, the hinge is formed by a weakened line.

[0027] In an embodiment, the hinge is positioned at the junction the central portion and the lateral portion.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] Preferred embodiments of the present invention will now be described, by way of example only, with reference to the accompanying drawings wherein:

[0029] Fig. 1 includes a perspective view of a package according to an embodiment of the invention;

[0030] Fig. 2 includes a perspective view of a receiving member of the embodiment of Fig. 1;

[0031] Fig. 3 includes a perspective view of the receiving member with a surgical mesh;

[0032] Fig. 4 and 5 include perspective views of a covering member;

[0033] Fig. 6 includes an exploded view of another embodiment of the invention.

DETAILED DESCRIPTION

[0034] Reference will now be made to the drawings wherein like structures are provided with like reference designations.

[0035] Turning to Fig. 1, a package 1 for a substantially rectangular mesh is shown in an perspective view.

[0036] Package 1 includes a receiving member 2 and a covering member 3. In the illustrated embodiment of Fig. 1, the package 1 is shown as rectangular; however, the package 1 may be of any suitable shape for receiving a surgical mesh.

[0037] The surgical mesh 100 can be seen in Figs. 1 or 3.

[0038] The receiving member 2 has a generally planar shape. In the illustrated embodiment, the receiving member 2 comprises a series of resting ribs 4 protruding from an inner panel 5.

[0039] As depicted on Fig. 2, the receiving member 2 is thus provided with transverse ribs 4 and longitudinal ribs 4 which divide the inner panel 5 into diffusing compartments 8 as will be explained later.

[0040] In the embodiment of Figs. 1 and 2, the receiving member 2 is provided with four transverse resting ribs 4 and two longitudinal resting ribs 4, which define three diffusing compartments 8.

[0041] The resting ribs 4 include at least one groove 9. In the embodiment of Figs. 1 to 3, the resting ribs 4 are provided with a series of grooves 9 spaced out at regular intervals.

[0042] In embodiments, the inner wall 5 can be provided with strengthening ribs 11.

[0043] The receiving member 2 further includes a peripheral rim 12.

[0044] Along each length of the receiving member 2, the peripheral rim 12 includes a series of locking toothing 13.

[0045] Along each width of the receiving member 2, the peripheral rim 12 is provided with a locking pin 14 and a locking opening 15. The peripheral rim 12 can also include one or more grooves 16.

[0046] Turning to Figs. 4 and 5, a covering member 3 is shown.

[0047] The covering member 3 has a generally planar shape. The covering member 3 has a substantially planar shape and is comprised of a central portion 20 and of two lateral portions 30

extending from the central portion 20 forming substantially a H. As can be seen on Fig. 4, the covering member 3 includes two symmetrical cut off portions 40.

[0048] In the illustrated embodiment, the covering member 3 comprises a series of resting ribs 4 protruding from an inner panel 5.

[0049] As depicted on Fig. 5, the covering member 3 is thus provided with transverse ribs 4 and longitudinal ribs 4, which define with the inner panel 5 diffusing compartments 8.

[0050] In the embodiment of Figs. 4 and 5, the covering member 3 is provided with two transverse resting ribs 4 and two longitudinal resting ribs 4, which define a diffusing compartment 8 in each lateral portion 30.

[0051] The resting ribs 4 include at least one groove 9. In the embodiment of Figs. 4 and 5, the resting ribs 4 are provided with a series of grooves 9 spaced out at regular intervals.

[0052] In embodiments, the inner wall 5 can be provided with strengthening ribs 11.

[0053] The covering member 3 further includes a peripheral rim 12.

[0054] Along each length of the covering member 3, the peripheral rim 12 includes a series of locking tothing 13.

[0055] Along each width of the receiving member 3, the peripheral rim 12 is provided with a locking pin 14 and a locking opening 15. The peripheral rim 12 can also include one or more grooves 16.

[0056] The central portion 20 can include a cavity 22 provided with three retaining tabs 23.

[0057] In an embodiment, the covering member 3 includes two weakened line 25 to form a hinge at the junction of the central portion 20 with each of the lateral portions 30.

[0058] The surgical mesh 100 is placed onto the receiving member 2 as can be seen on Fig.3. The surgical mesh 100 seats on the resting ribs 4 and is surrounded by the peripheral rib 12.

[0059] The covering member 3 is placed above the receiving member 4 and is locked onto the receiving member 2. The locking pins 14 of the covering member 3 are engaged into the corresponding openings 15 of the receiving member 2. The locking toothing 13 of the receiving member 2 engage into the locking toothing of the covering member 3.

[0060] The surgical mesh 100 is thus interposed between the receiving member 2 and the covering member 3 and is maintained in a substantially flat position. The surgical mesh 100 is maintained between the resting ribs 4 of the receiving member 2 and the resting ribs 4 of the covering member 3.

[0061] It can be noted that, within the package 1, the gap between the resting ribs 4 of the receiving member 2 and the resting ribs 4 of the covering member 3 can be in the area of 1 mm while the surgical mesh 100 thickness can be in the area of 0.6 mm.

[0062] When positioned in the package 1, the surgical mesh 100 is thus maintained along the resting ribs 4; the part of the surgical mesh 100 which is not directly interposed between the resting ribs 4 of the receiving member 2 and of the covering member is received in the diffusing compartments 8 where the surgical mesh 100 is free from contact with the package.

[0063] The surgical mesh 100 positioned in the package 1 may then be sterilized by immersion in a sterilizing solution of gas including ethylene oxide.

[0064] The sterilizing gas can flow within the package 1 and diffuses into the surgical mesh 100 through the cut off portion 40 and through the grooves 9 provided in the resting ribs 4. The entire surface of the surgical mesh 100 is thus exposed to the sterilizing gas.

[0065] After sterilization, the package 1 can be hermetically sealed in a suitable envelope like container (not shown) to be stored for a later use.

[0066] The central cavity 22 can receive a capsule of a desiccant material to ensure that the any moisture within the surgical mesh 100 is captured. The desiccant capsule is maintained in position by the tabs 23. The cut off portions 40 provide a significant exposure to the action of the desiccant capsule.

[0067] It can be appreciated that the receiving portion 2 and the covering member 3 are devoid of sharp angles or sharp edges thus limiting the risk of damaging the container.

[0068] When needed on an operating room, the package 1 can be presented to the medical staff.

[0069] One of the lateral portions 30 of the covering member 3 may be lifted and may be folded along the weakened line 25 thereby giving access to the surgical mesh 100.

[0070] Figs. 6 depicts another embodiment of the invention. In this embodiment of the invention, the receiving member 2 and the covering member 3 are identical.

[0071] A surgical mesh 100 is positioned onto a receiving member 2 such as the receiving member 2 illustrated on Fig. 2 and a covering member 3. The covering member 3 is structurally identical to the receiving member 2. However, the covering member 3 further includes a cavity 22 for a desiccant capsule.

[0072] The package described herein may be made of any material suitable for sterilization such as plastic, foils, combination thereof and laminates thereof and may be formed using any suitable molding process.

CLAIMS


1. A package for a surgical mesh, the package comprising:
a receiving member configured and dimensioned to receive at least one surgical mesh, the receiving member including transverse resting ribs and longitudinal resting ribs protruding from an inner wall of the receiving member and dividing the inner wall of the receiving member into diffusing compartments, the receiving member further comprising at least one first groove; and
a covering member configured and dimensioned to cover the said at least one surgical mesh maintaining with the receiving member, the said at least one surgical mesh in a substantially flat position, the covering member comprising at least one second groove defining with the at least one first groove of the receiving member at least one channel configured for a sterilising gas to flow within the at least one surgical mesh.
2. The package according to claim 1, wherein the receiving member and the covering member define at least one gas diffusing compartment connected to the at least one channel.
3. The package according to either one of claim 1 or 2, wherein the covering member includes at least one cut off portion.
4. The package according to any one of claims 1 to 3, wherein the covering member comprises at least one resting rib and an inner wall configured to maintain the surgical mesh between the resting ribs and to define the at least one gas diffusing compartment for a sterilising gas.
5. The package according to claim 4, wherein the covering member comprises at least one transverse resting rib forming at least two diffusing compartments.
6. The package according to any one of claims 1 to 5, wherein the receiving member and the covering member include a peripheral rim provided with at least one locking pin and at least one corresponding locking opening.
7. The package according to claim 6, wherein the peripheral rim includes a series of locking toothing.


8. The package according to any one of claims 1 to 7, wherein at least one of the receiving member and of the covering member includes a cavity configured to receive a capsule of desiccant material.
9. The package according to any one of claims 1 to 8, wherein the receiving member and the covering member have a substantially rectangular shape.
10. The package according to any one of claims 3 to 9, wherein that the covering member includes at least two cut off portions.
11. The package according to claim 10, wherein the covering member includes a central portion and two lateral portions extending from the central portion.
12. The package according to one of claims 1 to 11, wherein the covering member includes at least one hinge allowing access to the at least one surgical mesh.
13. The package according to claim 12, wherein the at least one hinge is formed by a weakened line.
14. The package according to claim 13, wherein the at least one hinge is positioned at the junction the central portion and the lateral portion.
15. The package according to any one of claims 1 to 14, wherein the inner wall of the receiving member further includes strengthening ribs.
16. The package according to any one of claims 1 to 15, wherein the covering member comprises transverse resting ribs and longitudinal resting ribs protruding from an inner wall of the covering member and dividing the inner wall of the covering member into diffusing compartments.
17. The package according to claim 16, wherein the inner wall of the covering member further includes strengthening ribs.


2016201918 12 Jun 2020

18. The package according to any one of claims 8 to 17, wherein the cavity further comprises retaining tabs which maintain the capsule of desiccant material within the cavity.

Sofradim Production
Patent Attorneys for the Applicant/Nominated Person
SPRUSON & FERGUSON










Fig. 4





Fig. 5.



6.
Li-9