

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
8 February 2007 (08.02.2007)

PCT

(10) International Publication Number
WO 2007/015795 A2

(51) International Patent Classification:
H04B 7/00 (2006.01)

(21) International Application Number:
PCT/US2006/027628

(22) International Filing Date: 17 July 2006 (17.07.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/700,799 20 July 2005 (20.07.2005) US
11/444,846 31 May 2006 (31.05.2006) US

(71) Applicant (for all designated States except US): **INTER-DIGITAL TECHNOLOGY CORPORATION** [US/US];
3411 Silverside Road, Concord Plaza, Suite 105, Hagley Building, Wilmington, Delaware 19810 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SHAHEEN, Kamel, M.** [EG/US]; 429 Ashton Drive, King Of Prussia, Pennsylvania 19406 (US).

(74) Agent: **BALLARINI, Robert, J.; VOLPE AND KOENIG, P.C.**, United Plaza, Suite 1600, 30 S. 17th Street, Philadelphia, Pennsylvania 19103 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND SYSTEM FOR SUPPORTING AN EVOLVED UTRAN



(57) Abstract: A method and system for supporting an evolved universal mobile telecommunication systems (UMTS) terrestrial radio access network (E-UTRAN) are disclosed. The system includes a wireless transmit/receive unit (WTRU), a UTRAN and an E-UTRAN. The UTRAN sends to the WTRU a list of available radio access technologies in a coverage area of the UTRAN. The list includes information related to the E-UTRAN. The WTRU receives the list and may initiate a handoff based on the list. The WTRU then sends its multi-mode/multi-RAT capability information including the E-UTRAN capability to the UTRAN. The UTRAN then sends a measurement capability message to the WTRU. The measurement capability message includes parameters necessary for performing measurements on an E-UTRAN channel. The WTRU performs measurements based on the measurement capability message and reports measurement results to the UTRAN. The UTRAN may initiate a handoff to the E-UTRAN based on the measurement results.

WO 2007/015795 A2

[0001] METHOD AND SYSTEM FOR SUPPORTING AN EVOLVED UTRAN

[0002] FIELD OF INVENTION

[0003] The present invention is related to wireless communication systems. More particularly, the present invention is related to a method and system for supporting an evolved universal mobile telecommunication systems (UMTS) terrestrial radio access network (E-UTRAN).

[0004] BACKGROUND

[0005] Different types of wireless access systems have been developed to provide different types of services and capabilities. Some examples of wireless access systems include wireless local area networks (WLANs), (such as IEEE 802-based networks), and cellular networks, (such as UMTS terrestrial radio access network (UTRAN), a global system for mobile communication (GSM)/enhanced data rate for GSM evolution (EDGE) radio access network (GERAN), or the like). Each of these networks have been developed and tailored to provide specific applications.

[0006] Proposals for an E-UTRAN (Long Term Evolution for UTRAN and evolved Node-B (E-Node-B)) have been made to improve wireless system capacity and enhance performance. The E-UTRAN will provide significant advantages over existing wireless communication systems and additional services may be available through the higher bit rate and lower latency provided by the E-UTRAN. Figure 1 shows a conventional integrated wireless communication system 100 including an E-UTRAN 114. The system 100 includes an access system stratum 110, a network stratum 120 and a multimedia stratum 130. The access system stratum 110 includes a plurality of radio access networks (RANs) 111-115, a core network (CN) 116 and an evolved CN 117. The RANs 111-115 include a generic access network (GAN) 111, a GERAN 112, a UTRAN 113, an E-UTRAN 114 and an interworking wireless local area network (I-WLAN) 115. The RANs 111-115 are connected to the CN 116 or the evolved CN 117 to provide services, (such as multimedia services from an Internet protocol (IP) multimedia

subsystem (IMS) 131), to one or more WTRUs while interacting with an authentication, authorization and accounting (AAA) server 121, a mobile IP (MIP) server 122, or other network entities in the network stratum 120 via a gateway general packet radio services (GPRS) support node (GGSN) 118 or a packet data gateway (PDG) 119.

[0007] Currently, multimode wireless transmit/receive units (WTRUs) configured to support multiple wireless communication systems are available. The capabilities of each of the WTRUs may vary. For example, some WTRUs may support only UMTS, while other WTRUs may support multiple mode of operations such as I-WLAN, GERAN, and/or E-UTRAN. The WTRUs that are capable of supporting E-UTRAN will also be available in the future.

[0008] Therefore, it would be desirable to provide a method and system for supporting an E-UTRAN such that the WTRUs may receive and utilize such additional E-UTRAN capabilities and services.

[0009] SUMMARY

[0010] The present invention is related to a method and system for supporting an E-UTRAN. The present invention extends conventional methods and procedures for supporting multimode operations within UMTS-based wireless communication system, (i.e., UTRAN), in order to support the addition of the new technology, (i.e., E-UTRAN), to the system. The conventional procedures are specified in third generation partnership project (3GPP) standards (e.g., TS25.331). The system, herein, includes a WTRU, a UTRAN and an E-UTRAN. A conventional UTRAN sends to the WTRU a list of available radio access technologies (RATs) in a coverage area of the UTRAN. The list includes information related to the existing RAT attributes such as technology type, bit rate, bandwidth, or the like. The present invention introduces the information related to E-UTRAN to this list. The WTRU receives this list during initial access or during handoff procedures. Upon receiving the list, an E-UTRAN capable WTRU may configure/reconfigure the WTRU to receive E-UTRAN services based on the list through handoff procedures or system reselection

procedures. The E-UTRAN capable WTRU may send its multi-mode/multi-RAT capability information including the E-UTRAN capability to the UTRAN during the initial access, (i.e., attach procedures), or when requested by a system. During a normal handoff procedure, the UTRAN sends a measurement capability message to the WTRU. The measurement capability message includes parameters necessary for performing measurements on an E-UTRAN channel. The WTRU performs measurements based on the measurement capability message and reports measurement results to the UTRAN. The UTRAN may initiate a handoff to the E-UTRAN based on the measurement results. In idle operation, the WTRU may decide to re-select to the E-UTRAN based on the capability information received earlier from the UTRAN. The WTRU uses this information to configure the transmitter and receiver bandwidth, bit rate, frequency band, or the like.

[0011] BRIEF DESCRIPTION OF THE DRAWINGS

[0012] A more detailed understanding of the invention may be had from the following description of a preferred embodiment, given by way of example, and to be understood in conjunction with the accompanying drawings, wherein:

[0013] Figure 1 is a diagram of a conventional wireless communication system;

[0014] Figure 2 shows a wireless communication system configured in accordance with the present invention; and

[0015] Figure 3 is a flow diagram of a process for supporting E-UTRAN in accordance with the present invention.

[0016] DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] When referred to hereafter, the terminology "WTRU" includes but is not limited to a user equipment, a mobile station, a fixed or mobile subscriber unit, a pager, or any other type of device capable of operating in a wireless environment.

[0018] The features of the present invention may be incorporated into an integrated circuit (IC) or be configured in a circuit comprising a multitude of interconnecting components.

[0019] Figure 2 shows a wireless communication system 200 configured in accordance with the present invention. The system 200 includes a plurality of RANs 210a, 210b, deployed under different RATs, and a core network 220 which may be an all Internet protocol (IP) network (AIPN). The core network 220 is connected to other networks, such as a public switching telephone network (PSTN) 230, the Internet 240, or the like. Each of the RANs 210a, 210b may be a GAN, a GERAN, a UTRAN, an E-UTRAN, an IEEE-based I-WLAN, or any type of wireless access network.

[0020] In order to optimize mobility among diverse RANs 210a, 210b, the core network 220 provides open interfaces for mobility management (MM) 222 that allow the operator of the core network 220 to direct WTRUs 250 towards the most suitable RANs 210a, 210b. The core network 220 also provides open interfaces that allow the WTRUs 250 to access other AIPN services, such as session control (SC) 224, authentication, authorization and accounting (AAA) 226 and a policy control 228.

[0021] A WTRU 250 is a multi-mode WTRU equipped with at least two radio units configured to support communication with at least two different RATs. For example, the WTRU 250 may include one radio unit for communicating with an E-UTRAN and the other radio unit for communication with an I-WLAN. The WTRU 250 establishes a connection with one of the RANs and may perform a handoff to a target RAN if handoff criteria is met by the target RAN.

[0022] A handoff may be initiated manually or automatically in the system 200. In the manual handoff process initiated by a user of the WTRU 250, the user knows the existence of alternative RATs, (such as E-UTRAN), in its current geographic location and switches between them, (e.g., between the UTRAN and the E-UTRAN). The automatic handoff process may be initiated by the WTRU 250, or by the RAN 210a, 210b or the core network 220.

[0023] In the WTRU-initiated handoff, the WTRU 250 detects the existence of alternative RATs, (such as an E-UTRAN), and initiates a handoff process, (e.g., to the E-UTRAN), based on the preference of the user of the WTRU 250. The WTRU 250 receives necessary information, (such as handoff policies, resource status, or the like), from the network, (e.g., a RAN 210b or the core network 220). The WTRU 250 tracks the locations of coverage areas of the RANs 210a, 210b and initiates the handoff process based on predetermined handoff criteria.

[0024] In a system initiated handoff, the core network 220, (or the RAN 210a, 210b), recognizes that the WTRU 250 is capable of supporting multiple RATs, (including E-UTRAN), and requests necessary information, (such as power measurements), from the WTRU 250. The core network 220, (or the RAN 210a, 210b), tracks the location of the WTRU 250 and initiates the handoff procedures based on a set of criteria, (such as the mobility of the WTRU 250, requested bandwidth, applications, load balancing, subscriber's profile, the measurement reports provided by the WTRU 250, or the like), once the WTRU 250 is within the coverage area of a target RAN.

[0025] Figure 3 is a flow diagram of a process for supporting an E-UTRAN in accordance with the present invention. A WTRU 352 listens to a channel, (e.g., a broadcast control channel (BCCH)), on the UTRAN 354 (step 302). The UTRAN 354 sends, (or indicates), a list of available RATs, (such as E-UTRAN 356 RAT), within the coverage area of the UTRAN 354 to the WTRU 352 (step 304). The list of available RATs is preferably sent via a UTRAN cell information list message. However, the list may be sent via any type of messages.

The UTRAN cell information list message contains information on intra-frequency cells, inter-frequency cells and inter-RAT cells. The conventional UTRAN cell information list message is modified to include new information elements (IEs) for the E-UTRAN 356. The E-UTRAN 356 may be based on orthogonal frequency division multiplexing (OFDM), or any other type of air interface. In OFDM case, the UTRAN cell information list may include OFDM selection and reselection information, base transceiver station identity code (BSIC), system specific measurement information, or the like. The system

specific measurement information enumerates supported frequencies, bandwidths, output power, or the like. Table 1 shows an exemplary UTRAN cell information list message including new IEs (shown in bold fonts) in accordance with the present invention.

Information Element/Group name	Need	Multi	Type and reference	Semantics description
Intra-frequency cell info	OP	1..<maxCellMeas>		
>CHOICE <i>position status</i>	MP			
>>Occupied				
>>>Cell info	MP		Cell info 10.3.7.2	
>>Vacant				No data
Inter-frequency cell info	OP	1..<maxCellMeas>		
>CHOICE <i>position status</i>	MP			
>>Occupied				
>>>Frequency info	MP		Frequency info 10.3.6.36	
>>>Cell info	MP		Cell info 10.3.7.2	
>>Vacant				No data
Inter-RAT cell info list	OP			
>Inter-RAT cell info	OP	1..<maxCellMeas>		
>>CHOICE <i>position status</i>	MP			
>>>Occupied				
>>>>CHOICE <i>Radio Access Technology</i>				
>>>>>GSM				
>>>>>>Cell selection and re-selection info	MP		Cell selection and re-selection info for SIB11/12 10.3.2.4	

Table 1 – Part 2 of 2

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>>>>>>BSIC	MP		BSIC 10.3.8.2	
>>>>>>BCCH ARFCN	MP		Integer (0..1023)	
>>>>>>IS-2000				
>>>>>>>System specific measurement info			enumerated (frequency, timeslot, colour code, output power, PN offset)	For IS-2000, use fields from TIA/EIA/IS-2000.5, subclause 3.7.3.3.2.27, <i>Candidate Frequency</i>

Information Element/Group name	Need	Multi	Type and reference	Semantics description
				<i>Neighbour List Message</i>
>>>>>OFDM				
>>>>>OFDM selection and re-selection info	MP			
>>>>>BSIC	MP			
>>>>>System Specific measurement info	MP		enumerated (frequency, bandwidth, output power)	
>>>Inter-RAT cell info indicator	OP		Integer (0..3)	
>>Not present				No data

Table 1 – Part 2 of 2

[0026] Referring again to Figure 3, the WTRU 352 receives the list and stores it (step 306). Based on preset user preference, the WTRU 352 sends its multi-mode/multi-RAT capability information to the UTRAN 354 (step 308). The multi-mode/multi-RAT capability information indicates a support of E-UTRAN and/or other RATs. For example, the multi-mode/multi-RAT capability information may indicate a support of OFDM, a support of E-UTRAN to UTRAN handoff, OFDM radio frequency (RF) capability, OFDM measurement capability, or the like. The support of OFDM may enumerate the supported OFDM channel bandwidth, (e.g., 1.25 MHz, 2.5 MHz, 5 MHz, 10 MHz, 15 MHz, 20 MHz). The support of E-UTRAN to UTRAN handoff is preferably a Boolean value indicating such capability of the WTRU.

[0027] The OFDM RF capability and OFDM measurement capability indicate OFDM RF and measurement capabilities of the WTRU to the UTRAN. An OFDM channel may have different bandwidth depending of system configuration and the desired bit rate and delay associated with certain services. For example, in order to achieve the highest bit rate allowed, (e.g., 100 Mbps), the E-UTRAN must transmit and receive using the highest bandwidth allowed, (e.g. 20 MHz). The E-UTRAN may run several combinations of these services (different bandwidths for different WTRUs). Therefore, the handoff to the E-UTRAN should be triggered based on the OFDM RF capabilities of the WTRU. During handoff, when the WTRU performs measurements, the WTRU is

preferably tuned and configured to a certain channel frequency and a specific bandwidth for the measurements. When the WTRU reports the measurements to the UTRAN, the UTRAN correlates the measurements with the physical attributes of the E-UTRAN channels. This guarantees that the handoff is done accurately to the correct target E-UTRAN channel that supports the desired bit rate and delay requirements.

[0028] The multi-mode/multi-RAT capability information may be sent via a conventional UTRAN WTRU multi-mode/multi-RAT capability message, WTRU radio access capability message, WTRU radio access capability extension message, or any other type of message. Tables 2-4 show an exemplary UTRAN WTRU multi-mode/multi-RAT capability message, a WTRU radio access capability message and a WTRU radio access capability extension message, respectively, including new IEs (shown in bold fonts) in accordance with the present invention.

Information Element/Group name	Need	Multi	Type and Reference	Semantics description
Multi-RAT capability				
Support of GSM	MP		Boolean	
Support of multi-carrier	MP		Boolean	
Multi-mode capability	MP		Enumerated (TDD, FDD, FDD/TDD)	
Support of UTRAN to GERAN NACC	CV- <i>not_iRAT_HoInfo</i>		Boolean	
Support OFDM	MP		Enumerated(1.25 M, 2.5M, 5M, 10M, 15M, 20MHz, or range)	
Support E-UTRAN to UTRAN handoffs			Boolean	

Table 2

Information Element/Group name	Need	Multi	Type and reference	Semantics description
Access stratum release indicator	MP		Enumerated(R99)	Indicates the release of the UE. The IE also indicates the release of the RRC transfer syntax supported by the UE..
	CV- <i>not_rrc</i>		Enumerated(REL-4,	13 spare values are needed.

Information Element/Group name	Need	Multi	Type and reference	Semantics description
	<i>_connectionSetupComplete</i>		REL-5 REL-6)	
DL capability with simultaneous HS-DSCH configuration	OP		Enumerated(32kbps, 64kbps, 128kbps, 384kbps)	
PDCP capability	MP		PDCP capability 10.3.3.24	
RLC capability	MP		RLC capability 10.3.3.34	
Transport channel capability	MP		Transport channel capability 10.3.3.40	
RF capability FDD	OP		RF capability FDD 10.3.3.33	
RF capability TDD	OP		RF capability TDD 10.3.3.33b	One "TDD RF capability" entity shall be included for every Chip rate capability supported.
		1 to 2		
RF capability OFDM (E-UTRAN)	OP		OFDM RF capability x.x.x	
Physical channel capability	MP		Physical channel capability 10.3.3.25	
UE multi-mode/multi-RAT capability	MP		UE multi-mode/multi-RAT capability 10.3.3.41	
Security capability	MP		Security capability 10.3.3.37	
UE positioning capability	MP		UE positioning capability 10.3.3.45	
Measurement capability	<i>CH-fdd_req_sup</i>		Measurement capability 10.3.3.21	

Table 3

Information Element/Group name	Need	Multi	Type and reference	Semantics description
Frequency band specific capability list	MP	1 to <maxFrequencyBandsFDD>		
>Frequency band	MP		Enumerated(Band I, Band II, Band III, Band VI, Band IV, Band V, OFDM band)	One spare value is needed

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>Frequency band 2	OP		Enumerated(Extension Indicator OFDM band)	This IE indicates the supported frequency bands beyond Band VIII (yet to be defined) Fifteen spare values are needed
>RF capability FDD extension	MD		RF capability FDD extension 10.3.3.33a	the default values are the same values as in the immediately preceding IE "RF capability FDD extension"; the first occurrence is MP
>Measurement capability extension	MP		Measurement capability extension 10.3.3.21a	
>RF capability OFDM	MD		RF capability OFDM	
>Measurement capability OFDM	MP		Measurement capability OFDM	

Table 4

[0029] Referring again to Figure 3, the UTRAN 354 receives the WTRU multi-mode/multi-RAT capability message (step 310). The UTRAN 354 then sends a measurement capabilities message to the WTRU 352 (step 312). The measurement capability message defines the parameters necessary for the measurements. New IEs for the E-UTRAN are included in the conventional measurement capability message and the measurement capability extension message for the E-UTRAN parameters, (e.g., OFDM measurement parameters for each frequency bands). Each IE in the measurement capability message and the measurement capability extension message is a Boolean value indicating whether downlink or uplink compressed mode is required to perform measurements on each frequency band.

[0030] Tables 5 and 6 show an exemplary UTRAN measurement capability message and a measurement capability extension message, respectively. The new IEs introduced in accordance with the present invention are shown in bold font.

Information Element/Group name	Need	Multi	Type and reference	Semantics description
--------------------------------	------	-------	--------------------	-----------------------

Information Element/Group name	Need	Multi	Type and reference	Semantics description
Need for downlink compressed mode				
FDD measurements	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on FDD
3.84 Mcps TDD measurements	CV- <i>3.84_Mcps_tdd_sup</i>		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 3.84 Mcps TDD
1.28 Mcps TDD measurements	CV- <i>1.28_Mcps_tdd_sup</i>		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 1.28 Mcps TDD
GSM measurements	CV- <i>gsm_sup</i>			
>GSM 900	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on GSM 900
>DCS 1800	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on DCS 1800
>GSM 1900	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on GSM 1900
Multi-carrier measurement	CV- <i>mc_sup</i>		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on multi-carrier
OFDM E-UTRAN measurements				
>1.25 MHz	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 1.25 MHz OFDM
>2.5 MHz	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 2.5 MHz OFDM
>5 MHz	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 5 MHz OFDM
>10 MHz	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 10 MHz OFDM

Table 5 – Part 1 of 3

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>15 MHz	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 15 MHz OFDM
>20 MHz	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 20 MHz OFDM
Need for uplink compressed mode				
FDD measurements	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on FDD
3.84 Mcps TDD measurements	CV- <i>3.84_Mcps_tdd_sup</i>		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 3.84 Mcps TDD
1.28 Mcps TDD measurements	CV- <i>1.28_Mcps_tdd_sup</i>		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 1.28 Mcps TDD
GSM measurements	CV- <i>gsm_sup</i>			
>GSM 900	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on GSM 900
>DCS 1800	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on DCS 1800
>GSM 1900	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on GSM 1900
Multi-carrier measurement	CV- <i>mc_sup</i>		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on multi-carrier
OFDM E-UTRAN measurements				
>1.25 MHz	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 1.25 MHz OFDM
>2.5 MHz	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 2.5 MHz OFDM
>5 MHz	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 5 MHz OFDM

Table 5 – Part 2 of 3

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>10 MHz	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 10 MHz OFDM
>15 MHz	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 15 MHz OFDM
>20 MHz	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 20 MHz OFDM

Table 5 – Part 3 of 3

Information Element/Group name	Need	Multi	Type and reference	Semantics description
FDD measurements	MP	1 to <maxFreqBandsFDD>		
>FDD Frequency band	MD		Enumerated(Band I, Band II,	The default value is the same as indicated in the IE "Frequency band" included in the IE " UE radio access capability extension". One spare value is needed
			Band III, Band VI, Band IV, Band V)	
>FDD Frequency band 2	MD		Enumerated(Extension Indicator)	The default value is the same as indicated in the IE "Frequency band 2" included in the IE " UE radio access capability extension"., if the IE "FDD Frequency band" above is not included. The default value is the same as the IE "FDD Frequency band", if the IE "FDD Frequency band" is included. Fifteen spare values are needed

Table 6 – Part 1 of 4

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on the FDD frequency band indicated by the IE "FDD Frequency band"
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on the FDD frequency band indicated by the IE "FDD Frequency band"
TDD measurements	CV- <i>tdd_s</i> <i>up</i>	1 to <maxFr eqBand sTDD>		
>TDD Frequency band	MP		Enumerated(a, b, c)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on TDD frequency band indicated by the IE "TDD Frequency band"
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on TDD frequency band indicated by the IE "TDD Frequency band"
GSM measurements	CV- <i>gsm_</i> <i>sup</i>	1 to <maxFr eqBand sGSM>		
>GSM Frequency band	MP		Enumerated(GSM450, GSM480, GSM850, GSM900P, GSM900E, GSM1800, GSM1900)	Nine spare values are needed.
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on GSM frequency band indicated by the IE "GSM Frequency band"

Table 6 – Part 2 of 4

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on GSM frequency band indicated by the IE "GSM Frequency band"
Multi-carrier measurement	CV- mc_s up			
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on multi-carrier
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on multi-carrier
OFDM E-UTRAN measurements				
> 1.25 MHz band	MP		Enumerated(x, y, z)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements on 1.25 MHz OFDM
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 1.25 MHz OFDM
>> 2.5 MHz band	MP		Enumerated(x, y, z)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements 2.5 MHz OFDM
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 2.5 MHz OFDM
>> 5 MHz band	MP		Enumerated(x, y, z)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements 2.5 MHz OFDM
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 5 MHz OFDM

Table 6 – Part 3 of 4

Information Element/Group name	Need	Multi	Type and reference	Semantics description
>> 10 MHz band	MP		Enumerated(x, y, z)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements 10 MHz OFDM
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 10 MHz OFDM
>> 15 MHz band	MP		Enumerated(x, y, z)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements 15 MHz OFDM
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 15 MHz OFDM
>> 20 MHz band	MP		Enumerated(x, y, z)	
>Need for DL compressed mode	MP		Boolean	TRUE means that the UE requires DL compressed mode in order to perform measurements 20 MHz OFDM
>Need for UL compressed mode	MP		Boolean	TRUE means that the UE requires UL compressed mode in order to perform measurements on 20 MHz OFDM

Table 6 – Part 4 of 4

[0031] Referring again to Figure 3, the WTRU 352 receives the measurement capabilities message. The WTRU 352 then performs measurements on the E-UTRAN signals 315 on E-UTRAN channels indicated in the measurement capabilities message and reports measurement results to the UTRAN 354 (step 314). The UTRAN 354 may initiate a handoff to the E-UTRAN 356 based on the measurement reports.

[0032] Embodiments.

[0033] 1. A method for supporting an E-UTRAN in a wireless communication system including a WTRU, a UTRAN and the E-UTRAN.

[0034] 2. The method of embodiment 1 comprising the step of the WTRU listening to a UTRAN channel.

[0035] 3. The method of embodiment 2 comprising the step of the UTRAN sending a list of available RATs in a coverage area of the UTRAN via the

UTRAN channel, the list including information related to the E-UTRAN.

[0036] 4. The method of embodiment 3 comprising the step of the WTRU receiving the list, whereby the WTRU receives E-UTRAN services based on the list.

[0037] 5. The method as in any embodiments 3-4, wherein the list is sent via a BCCH.

[0038] 6. The method as in any embodiments 3-5, wherein the list is included in a cell information list message.

[0039] 7. The method as in any embodiments 3-4, wherein the list is sent via a dedicated channel.

[0040] 8. The method as in any embodiments 3-7, wherein a RAT of the E-UTRAN is OFDM.

[0041] 9. The method as in any embodiments 3-8, wherein the E-UTRAN information includes at least one of OFDM selection and reselection information, BSIC, and system specific measurement information.

[0042] 10. The method of embodiment 9, wherein the system specific measurement information enumerates at least one of supported frequency, bandwidth, and output power.

[0043] 11. The method as in any embodiments 1-10 comprising the step of the WTRU sending a multi-mode/multi-RAT capability of the WTRU to the UTRAN.

[0044] 12. The method of embodiment 11 comprising the step of the UTRAN receiving the multi-mode/multi-RAT capability of the WTRU.

[0045] 13. The method as in any embodiments 11-12, wherein the multi-mode/multi-RAT capability indicates an E-UTRAN capability of the WTRU.

[0046] 14. The method of embodiment 13, wherein the E-UTRAN capability includes an OFDM capability.

[0047] 15. The method as in any embodiments 11-14, wherein the multi-mode/multi-RAT capability includes at least one of an indication of OFDM support, an indication of a support of handoff between the UTRAN and the E-UTRAN, OFDM radio frequency capability, and OFDM measurement capability.

[0048] 16. The method of embodiment 15, wherein the indication of OFDM support enumerates supported frequencies and bandwidths.

[0049] 17. The method as in any embodiments 11-16, wherein the multi-mode/multi-RAT capability is sent via at least one of a WTRU multi-mode/multi-RAT capability message, a WTRU radio access capability message, and a WTRU radio access capability extension message.

[0050] 18. The method as in any embodiments 11-17, wherein the multi-mode/multi-RAT capability is sent during an attach procedure.

[0051] 19. The method as in any embodiments 11-17, wherein the multi-mode/multi-RAT capability is sent upon request by the UTRAN.

[0052] 20. The method as in any embodiments 1-19, comprising the step of the UTRAN sending a measurement capability message to the WTRU, the measurement capability message including parameters necessary for performing measurements on an E-UTRAN channel.

[0053] 21. The method of embodiment 20 comprising the step of the WTRU performing measurements based on the measurement capability message.

[0054] 22. The method of embodiment 21 comprising the step of the WTRU reporting measurement results to the UTRAN.

[0055] 23. The method of embodiment 22 comprising the step of the UTRAN initiating a handoff of the WTRU to the E-UTRAN based on the measurement results.

[0056] 24. The method as in any embodiments 20-23, wherein the measurement capability message includes parameters for OFDM measurements.

[0057] 25. The method as in any embodiments 3-24, comprising the step of the WTRU initiating a handoff from the UTRAN to the E-UTRAN based on the list.

[0058] 26. The method of embodiment 25 wherein the handoff is triggered by a user of the WTRU.

[0059] 27. The method of embodiment 25 wherein the handoff is

triggered automatically.

[0060] 28. A wireless communication system supporting an E-UTRAN.

[0061] 29. The system of embodiment 28 comprising an E-UTRAN.

[0062] 30. The system of embodiment 29 comprising a UTRAN configured to send a list of available RATs in a coverage area of the UTRAN, the list including information related to the E-UTRAN.

[0063] 31. The system of embodiment 30 comprising a WTRU configured to receive the list and receive E-UTRAN services based on the list.

[0064] 32. The system as in any embodiments 30-31, wherein the UTRAN sends the list via a BCCH.

[0065] 33. The system as in any embodiments 30-32, wherein the UTRAN includes the list in a cell information list message.

[0066] 34. The system as in any embodiments 30-31, wherein the UTRAN sends the list via a dedicated channel.

[0067] 35. The system as in any embodiments 30-34, wherein an RAT of the E-UTRAN is OFDM.

[0068] 36. The system as in any embodiments 30-35 wherein the E-UTRAN information includes at least one of OFDM selection and reselection information, BSIC, and system specific measurement information.

[0069] 37. The system of embodiment 36 wherein the system specific measurement information enumerates at least one of supported frequency, bandwidth, and output power.

[0070] 38. The system as in any embodiments 31-37, wherein the WTRU is configured to send its multi-mode/multi-RAT capability to the UTRAN.

[0071] 39. The system of embodiment 38 wherein the multi-mode/multi-RAT capability includes E-UTRAN capability.

[0072] 40. The system of embodiment 39 wherein the E-UTRAN capability includes an OFDM capability.

[0073] 41. The system as in any embodiments 38-40, wherein the multi-mode/multi-RAT capability includes at least one of an indication of OFDM support, an indication of a support of handoff between the UTRAN and the E-

UTRAN, OFDM radio frequency capability, and OFDM measurement capability.

[0074] 42. The system of embodiment 41, wherein the indication of OFDM support enumerates supported frequencies and bandwidths.

[0075] 43. The system as in any embodiments 38-42, wherein the multi-mode/multi-RAT capability is sent via at least one of a WTRU multi-mode/multi-RAT capability message, a WTRU radio access capability message, and a WTRU radio access capability extension message.

[0076] 44. The system as in any embodiments 38-43, wherein the multi-mode/multi-RAT capability is sent during an attach procedure.

[0077] 45. The system as in any embodiments 38-43, wherein the multi-mode/multi-RAT capability is sent upon request by the UTRAN.

[0078] 46. The system as in any embodiments 31-45, wherein the UTRAN is configured to send a measurement capability message to the WTRU, the measurement capability message including parameters necessary to perform measurements on an E-UTRAN channel, and the WTRU is configured to perform measurements based on the measurement capability message and report measurement results to the UTRAN.

[0079] 47. The system of embodiment 46, wherein the UTRAN is configured to initiate a handoff to the E-UTRAN based on the measurement results.

[0080] 48. The system as in any embodiments 46-47, wherein the measurement capability message includes parameters for OFDM measurements.

[0081] 49. The system as in any embodiments 31-48, wherein the WTRU is configured to initiate a handoff of the WTRU from the UTRAN to the E-UTRAN based on the list.

[0082] 50. The system of embodiment 49 wherein the handoff is triggered by a user of the WTRU.

[0083] 51. The system of embodiment 49 wherein the handoff is triggered automatically.

[0084] Although the features and elements of the present invention are described in the preferred embodiments in particular combinations, each feature or element can be used alone without the other features and elements of the preferred embodiments or in various combinations with or without other features and elements of the present invention.

*

*

*

CLAIMS

What is claimed is:

1. In a wireless communication system including a wireless transmit/receive unit (WTRU), a universal mobile telecommunication systems (UMTS) terrestrial radio access network (UTRAN) and an evolved UTRAN (E-UTRAN), a method for supporting the E-UTRAN, the method comprising:

the WTRU listening to a UTRAN channel;

the UTRAN sending a list of available radio access technologies (RATs) in a coverage area of the UTRAN via the UTRAN channel, the list including information related to the E-UTRAN; and

the WTRU receiving the list, whereby the WTRU receives E-UTRAN services based on the list.

2. The method of claim 1 wherein the list is sent via a broadcast control channel (BCCH).

3. The method of claim 2 wherein the list is included in a cell information list message.

4. The method of claim 1 wherein the list is sent via a dedicated channel.

5. The method of claim 1 wherein a RAT of the E-UTRAN is orthogonal frequency division multiplexing (OFDM).

6. The method of claim 5 wherein the E-UTRAN information includes at least one of OFDM selection and reselection information, base transceiver identity code (BSIC), and system specific measurement information.

7. The method of claim 6 wherein the system specific measurement information enumerates at least one of supported frequency, bandwidth, and output power.

8. The method of claim 1 further comprising:
the WTRU sending a multi-mode/multi-RAT capability of the WTRU to the UTRAN; and
the UTRAN receiving the multi-mode/multi-RAT capability of the WTRU.

9. The method of claim 8 wherein the multi-mode/multi-RAT capability indicates an E-UTRAN capability of the WTRU.

10. The method of claim 9 wherein the E-UTRAN capability includes an orthogonal frequency division multiplexing (OFDM) capability.

11. The method of claim 10 wherein the multi-mode/multi-RAT capability includes at least one of an indication of OFDM support, an indication of a support of handoff between the UTRAN and the E-UTRAN, OFDM radio frequency capability, and OFDM measurement capability.

12. The method of claim 11 wherein the indication of OFDM support enumerates supported frequencies and bandwidths.

13. The method of claim 8 wherein the multi-mode/multi-RAT capability is sent via at least one of a WTRU multi-mode/multi-RAT capability message, a WTRU radio access capability message, and a WTRU radio access capability extension message.

14. The method of claim 8 wherein a multi-mode/multi-RAT capability is sent during an attach procedure.

15. The method of claim 8 wherein the multi-mode/multi-RAT capability is sent upon request by the UTRAN.

16. The method of claim 8 further comprising:

the UTRAN sending a measurement capability message to the WTRU, the measurement capability message including parameters necessary for performing measurements on an E-UTRAN channel;

the WTRU performing measurements based on the measurement capability message; and

the WTRU reporting measurement results to the UTRAN.

17. The method of claim 16 further comprising:

the UTRAN initiating a handoff of the WTRU to the E-UTRAN based on the measurement results.

18. The method of claim 16 wherein the measurement capability message includes parameters for orthogonal frequency division multiplexing (OFDM) measurements.

19. The method of claim 1 further comprising:

the WTRU initiating a handoff from the UTRAN to the E-UTRAN based on the list.

20. The method of claim 19 wherein the handoff is triggered by a user of the WTRU.

21. The method of claim 19 wherein the handoff is triggered automatically.

22. A wireless communication system supporting an evolved universal mobile telecommunication systems (UMTS) terrestrial radio access network (E-UTRAN), the system comprising:

an E-UTRAN;

a UTRAN configured to send a list of available radio access technologies (RATs) in a coverage area of the UTRAN, the list including information related to the E-UTRAN; and

a wireless transmit/receive unit (WTRU) configured to receive the list and receive E-UTRAN services based on the list.

23. The system of claim 22 wherein the UTRAN sends the list via a broadcast control channel (BCCH).

24. The system of claim 23 wherein the UTRAN includes the list in a cell information list message.

25. The system of claim 22 wherein the UTRAN sends the list via a dedicated channel.

26. The system of claim 22 wherein a RAT of the E-UTRAN is orthogonal frequency division multiplexing (OFDM).

27. The system of claim 26 wherein the E-UTRAN information includes at least one of OFDM selection and reselection information, base transceiver identity code (BSIC), and system specific measurement information.

28. The system of claim 27 wherein the system specific measurement information enumerates at least one of supported frequency, bandwidth, and output power.

29. The system of claim 22 wherein the WTRU is configured to send its multi-mode/multi-RAT capability to the UTRAN.

30. The system of claim 29 wherein the multi-mode/multi-RAT capability includes E-UTRAN capability.

31. The system of claim 30 wherein the E-UTRAN capability includes an orthogonal frequency division multiplexing (OFDM) capability.

32. The system of claim 31 wherein the multi-mode/multi-RAT capability includes at least one of an indication of OFDM support, an indication of a support of handoff between the UTRAN and the E-UTRAN, OFDM radio frequency capability, and OFDM measurement capability.

33. The system of claim 32 wherein the indication of OFDM support enumerates supported frequencies and bandwidths.

34. The system of claim 29 wherein the multi-mode/multi-RAT capability is sent via at least one of a WTRU multi-mode/multi-RAT capability message, a WTRU radio access capability message, and a WTRU radio access capability extension message.

35. The system of claim 29 wherein the multi-mode/multi-RAT capability is sent during an attach procedure.

36. The system of claim 29 wherein the multi-mode/multi-RAT capability is sent upon request by the UTRAN.

37. The system of claim 29 wherein the UTRAN is configured to send a measurement capability message to the WTRU, the measurement capability message including parameters necessary to perform measurements on an E-

UTRAN channel, and the WTRU is configured to perform measurements based on the measurement capability message and report measurement results to the UTRAN.


38. The system of claim 37 wherein the UTRAN is configured to initiate a handoff to the E-UTRAN based on the measurement results.

39. The system of claim 37 wherein the measurement capability message includes parameters for orthogonal frequency division multiplexing (OFDM) measurements.

40. The system of claim 22 wherein the WTRU is configured to initiate a handoff of the WTRU from the UTRAN to the E-UTRAN based on the list.

41. The system of claim 40 wherein the handoff is triggered by a user of the WTRU.

42. The system of claim 40 wherein the handoff is triggered automatically.



1/3

FIG. 1
PRIOR ART




FIG. 2




FIG. 3