



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C10L 5/00	A1	(11) International Publication Number: WO 92/02601 (43) International Publication Date: 20 February 1992 (20.02.92)
(21) International Application Number: PCT/US91/05506 (22) International Filing Date: 8 August 1991 (08.08.91) (30) Priority data: 564,909 9 August 1990 (09.08.90) US (71) Applicant: MOBIL OIL CORPORATION [US/US]; 3225 Gallows Road, Fairfax, VA 22037-0001 (US). (72) Inventors: ABRAMO, Guy, Paul ; 13184 Ladybank Lane, Herndon, VA 22071 (US). AVERY, Noyes, Latham ; 1026 Rock Creek Road, Bryn Mawr, PA 19010 (US). TREWELLA, Jeffery, C. ; 8 Morgan Road, Flemington, NJ 08822 (US).		(74) Agent: MURPHY, Gerald, M., Jr.; Birch, Stewart, Ko- lasch & Birch, 301 North Washington Street, P.O. Box 747, Falls Church, VA 22046-3487 (US). (81) Designated States: AT (European patent), AU, BE (Euro- pean patent), CH (European patent), DE (European pat- ent), DK (European patent), ES (European patent), FR (European patent), GB (European patent), GR (Euro- pean patent), IT (European patent), JP, KR, LU (Euro- pean patent), NL (European patent), SE (European pat- ent). Published <i>With international search report.</i>
(54) Title: DEPOSIT CONTROL ADDITIVES AND FUEL COMPOSITIONS CONTAINING THE SAME (57) Abstract A fuel additive having detergency, solubility and thermal stability which is a mixture of a polyalkenyl succinimide, a poly- alkylene, i.e., polyisobutylene or polypropylene, an ester and a polyether; namely a polybutylene oxide, polypropylene oxide or polybutylene/polypropylene oxide copolymer, and an optional amount of a mineral oil or synthetic oil.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	ES	Spain	MG	Madagascar
AU	Australia	FI	Finland	ML	Mali
BB	Barbados	FR	France	MN	Mongolia
BE	Belgium	GA	Gabon	MR	Mauritania
BF	Burkina Faso	GB	United Kingdom	MW	Malawi
BG	Bulgaria	GN	Guinea	NL	Netherlands
BJ	Benin	GR	Greece	NO	Norway
BR	Brazil	HU	Hungary	PL	Poland
CA	Canada	IT	Italy	RO	Romania
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU ⁺	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark				

⁺ It is not yet known for which States of the former Soviet Union any designation of the Soviet Union has effect.

DEPOSIT CONTROL ADDITIVES AND FUEL
COMPOSITIONS CONTAINING THE SAME

BACKGROUND OF THE INVENTION

Technical Field

The invention relates to deposit control additives for fuels. Specifically, the invention relates to a fuel additive comprising a combination of a polyalkylene-substituted succinimide as a detergent/dispersant and a carrier fluid which is a combination of a polymeric component, an ester and a polyether, and optionally a mineral oil or synthetic oil.

Related Art

During operation of an internal combustion engine, fuel and lubricant deposits accumulate and bake onto the intake valves and intake ports of the fuel system. These deposits restrict the flow of air and fuel entering the combustion chamber which can cause stalling and hesitation, especially during "cold-start" operation.

Conventional polyalkenyl succinimides as gasoline detergent additives are described as effective in providing carburetor cleanliness and port fuel injector cleanliness. However, the polyalkenyl succinimides alone offer little intake valve cleanliness performance.

SUMMARY OF THE INVENTION

The present invention offers a gasoline additive which can be used in a minor effective amount as a carburetor, port fuel injector and intake valve cleanliness additive which limits the amount of deposit formation. The components of the additive synergistically clean the fuel system of a spark ignition internal combustion engine, when added to a fuel in an amount of at least 10 to 100, at most 200 to 500 pounds of additive per 1,000 barrels of fuel (lbs/MB). All the fuel system components, particularly the carburetor, fuel lines, fuel injectors, port fuel injectors and intake valves are cleaned by exposure to small amounts of the additive combination in solution with the fuel. The additive formulation of the present invention, when used in minor concentrations, limits the amount of deposit formation.


An advantage of the invention is that it is effective in both high quality premium unleaded as well as regular unleaded gasolines thus providing effective detergency properties for all kinds of vehicles.

The invention is directed to an additive for normally liquid fuels having detergency, solubility and thermal stability comprising a combination of a

polyalkenyl succinimide which is the reaction product of a polyalkenyl succinic anhydride and a polyalkylene polyamine, a polymer or copolymer of an olefinic hydrocarbon, an ester and a polyether and fuel compositions containing the additive and methods of making the same.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The additive contains a range of from at least 10 to 20 to at most 50 to 80 wt. %, based on the total weight of the additive, of an N-substituted polyalkenyl succinimide. The N-substituted polyalkenyl succinimide is made by reacting a polyalkenyl succinic anhydride with a polyamine. The polyalkenyl succinic anhydride has the structural formula:




in which R¹ is a polyalkenyl radical having a weight average molecular weight from at least 600 to 900 to at most 1,500 to 3,000. The polyalkenyl radical contains at least about 40 to 60 carbon atoms, at most 100 to 300 to carbon atoms. The alkenyl

groups are polyolefins made from olefins, typically 1-olefins, containing 2 to 10 carbon atoms. Representative examples of suitable olefins include ethylene, propylene, butylene, isobutylene, pentene, hexene, octene, decene and higher olefins or copolymers thereof. When the polyalkenyl radical is a homopolymer of polyisobutenyl, it contains at least 10 to 20 isobutenyl groups, at most 30 to 60 isobutenyl groups.

10 The ratio of succinic anhydride groups to alkylene groups ranges from at least 0.5 to 1 to at most 1.1 to 3.5 of succinic anhydride groups to each equivalent weight of substituent groups. Such alkenyl succinic anhydrides are made by known techniques. The polyolefins are made by catalytic
15 oligomerization of the olefin. The polyalkenyl succinic anhydride is made from a mixture of polyolefins and maleic anhydride which are heated to a temperature of from 150° to 250°C, optionally,
20 with the use of a catalyst such as chlorine or peroxide. Approximately one mole of maleic anhydride is reacted per mole of polyalkylene such that the resulting polyalkenyl succinic anhydride has about 1 succinic anhydride group per
25 polyalkylene substituent, preferably 0.8 to 0.9 succinic anhydride groups for each polyalkylene

substituent. Another method of making the polyalkenyl succinic anhydrides is described in U.S. Patent No. 4,234,435 which is incorporated herein by reference in its entirety which discloses the polyalkenyl succinic anhydride characterized by the presence within its structure of at least 1.3 succinic anhydride groups for each equivalent weight amount of the polyalkylene substituent. The reaction equilibrium is such that approximately 80 to 90% of the polyalkenyl succinic anhydride can be together in solution with 10 to 20% of unreacted polyolefin.

The polyalkenyl succinimide is derived from a polyalkylene polyamine having the structural formula:



in which R_2 is a hydrogen or a low molecular weight alkyl radical. Typically, the low molecular weight alkyl radicals have from at least 1 to 2 carbon atoms and at most 3 to 6 carbon atoms and n is an integer ranging from at least 1 to 2 and at most 4 to 6. Representative examples of R_2 alkyl groups include methyl, ethyl, propyl or butyl. Representative examples of suitable polyamines

include ethylene diamine, propylene diamine, butylene diamine, diethylene triamine, triethylene tetramine, tetraethylene pentamine, pentaethylene hexamine, dipropylene triamine and tripropylene tetramine. The polyalkylene polyamine can also be
5 a polymer or copolymer of any one of the foregoing polyamines ranging in molecular weight of at least 1004 to at most 600.

The alkylene succinic anhydride and the
10 polyamine combine stoichiometrically such that one equivalent of the succinic anhydride reacts with 0.5 - 1.0 molecular equivalent amounts of the polyamine.

The procedure for making the polyalkenyl
15 succinimide is described in U.S. Patent No. 3,219,666 and U.S. Patent No. 4,098,585, which are both herein incorporated by reference in their entirety.

The additive formulation also contains a
20 carrier fluid which is a mixture having low temperature fluidity and solvency. The components of the carrier fluid are known to provide a moderate amount of intake valve cleanliness when mixed with fuels. However, although the components
25 alone provide a moderate level of intake valve detergency/cleanliness, they do not provide

carburetor and port fuel injector detergency/cleanliness. Yet, it was discovered that when used in the present additive formulation, these fluids together in combination with the polyalkenyl succinimides provide superior intake valve detergency as well as port fuel injector and carburetor detergency.

The carrier fluid contains less than 80 wt. %, i.e., at least 10 to 25% to at most 70 to 80%, preferably 20 to 50%, by weight of the total weight of the additive, of a polymer or copolymer of an olefinic hydrocarbon. The polymer has a weight average molecular weight of at least 600 to 900 to at most 1,500 to 3,000. The polymer, typically, has a viscosity ranging from 200 SUS at 100°C and about 20,000 SUS at 100°C. The polymer is prepared from a monoolefin, diolefin or polyolefin. The olefin can have 1 to 2 ethylenically unsaturated double bonds which are conjugated or unconjugated. The polymer contains at least about 40 to 60 carbon atoms, at most about 100 to 300 carbon atoms. Representative examples of suitable olefins from which the polymers or copolymers are derived include, but are not limited to, ethylene, propylene, 1-butylene, 2-butene, isobutylene, pentene, hexene, butadiene, octene, isoprene and

decene or higher olefins. Mixtures of the foregoing, such as a 1 to 1 mixture of isobutylene and 1-butylene are also used. Olefinic copolymers derived from any of these olefins are also suitable. Polyisobutylene, as an example of a suitable polymer for use in this invention, contains at least 10 to 20 isobutylene groups, at most 30 to 60 isobutylene groups. The polymeric component is used in an additional amount and is considered independent from any unreacted polymeric components which may be present in the final additive mixture from the reaction of the anhydride.

The carrier fluid also contains an ester which is made by known techniques or is readily available from commercial sources. The amount of the ester is from 1 to 80 wt. % based on the entire weight of the additive, more specifically, 2 to 60 wt. % or, even more specifically, 5 to 20 wt. %.


The ester is based on an ester of aliphatic or aromatic carboxylic acids, i.e., a mono-, di-, tri- or tetra-carboxylic acid. The aromatic ester can contain over 22 carbon atoms and can have a molecular weight ranging from 300 to 1,500, specifically, 400 to 1,200. To make the aromatic or aliphatic ester, a carboxylic acid substituted

benzene or aliphatic compound is reacted with a linear alcohol containing at least 4 to 8 to at most 16 to 20 carbon atoms or a branched Oxo-alcohol containing at least 6 to 8, at most 16 to 20 carbon atoms. Representative examples of the alcohols from which the ester is derived include monohydric alcohols such as n-butanol, i-butanol, t-butanol, isopentyl alcohol and Oxo alcohols, which are prepared by the Oxo process. The Oxo process involves reacting olefins with carbon monoxide and hydrogen at temperatures of about 150° to 200°C and pressures of about 30 to 400 atmospheres in the presence of a suitable catalyst. Examples of Oxo alcohols are those alcohols having 6 to 20 carbon atoms such as 2-methyl pentanol, 2-ethylhexanol, isodecanol, dodecanol and tridecanol. The foregoing alcohols are also readily available from commercial sources.

There are other ways to make the ester which are known in the art. These methods, which are best described in Kirk-Othmer "Encyclopedia of Chemical Technology," Vol 9, pages 291-309, John Wiley and Sons, New York, 1980, include direct synthesis by reacting an organic alcohol and the carboxylic acid substituted benzene with elimination of water (see Kirk-Othmer "Encyclopedia

of Chemical Technology" Volume 9, pages 306-307,
John Wiley & Sons, New York, 1980). Additionally,
a method for making the esters is described in U.S.
Patent No. 4,032,550 and in U.S. Patent No.
5 4,032,304 which are both incorporated by reference
in their entirety.

The carrier fluid also contains a polyether.
The amount of the polyether is about 1 to 80 wt. %
based on the entire weight of the additive, more
10 specifically, 2-60 wt. % or 5-20 wt. %. The
polyether is derived from an alkylene oxide such as
an epoxide having the structural formula:



15

Where R^3 , R^4 , R^5 and R^6 are independently hydrogen
atoms or lower hydrocarbyl radicals having 1 to 20
carbon atoms. Representative examples of the oxide
include polymers or copolymers of ethylene oxide,
20 propylene oxide, butylene oxide, pentene oxide,
hexene oxide, octene oxide and decene oxide and
isomers thereof. A representative example of a
suitable copolymer is a polypropylene/polybutylene
oxide. Mixtures of any of the foregoing oxides are

also suitable. The alkylene oxide is initiated by monofunctional or polyfunctional alcohols or amines ranging in molecular weight from 20 - 400 or an alkyl phenol ranging in molecular weight from 100 to 3,000, preferably 500-1,000. The alcohols are represented by the structures $R'(OH)_n$ and $R'(C_6H_5OH)_n$, respectively, in which R' is a substantially saturated aliphatic hydrocarbon radical containing 4 to 20 carbon atoms and n is an integer ranging from 1 to 3. The polyethers have a molecular weight of at least 500, specifically, 600 to 3000.

In another, similar, embodiment, the ester and polyether components of the present carrier fluid are described in German patent application publication DT-OS 38 38 918 which is incorporated by reference in its entirety. The foregoing publication describes suitable esters having a minimum viscosity of 2 centistokes at 100°C. The esters are polyol esters based on neopentyl glycol, pentaerythritol or trimethylolpropane with corresponding monocarboxylic acids, oligomer esters and polymer esters such as those based on dicarboxylic acid, polyol and monoalcohol. Certain named esters are the adipates, phthalates, isophthalates, terephthalates and trimellitates of

iso-octanol, iso-nonanol, iso-decanol and
iso-tridecanol and mixtures thereof. The
polyethers are derived from aliphatic and aromatic
mono-, di-, or polyalcohols, amines and
5 alkylphenols. The polyether starting materials
named in the publication include hexanediol,
iso-tridecanol, iso-nonylphenol, isododecylphenol
and iso-tridecylamine.

The carrier fluid can optionally contain at
10 least 1 to 10% or 5 to 30%, at most 50 to 80% of a
mineral oil or synthetic oil which is used in
addition to the polymeric, ester or polyether
carrier fluid components. Representative of a
suitable mineral oil is a solvent refined,
15 naphthenic mineral oil or a hydrotreated naphthenic
mineral oil or a paraffinic mineral oil of at least
100 SUS at 100°C, more specifically at least 300 to
500 SUS to at most 900 to 1200 SUS at 100°C.
Representative of synthetic oils are polyolefins
20 such as those derived from ethylene, propylene,
1-butene, hexene, octene, decene and dodecene and
the like and copolymers of the foregoing.

The additive is blended in a concentration of
from at least 10 to 100 to at most 200 to 500
25 pounds of additive per 1000 barrels (lb/MB) of
fuel. The liquid fuel can be a liquid hydrocarbon

fuel or an oxygenated fuel or mixtures thereof. Other fuels are contemplated as well, such as diesel oils and aviation fuels.

Specifically, however, the fuel compositions
5 contemplated include gasoline base stocks such as a mixture of hydrocarbons boiling in the gasoline boiling range which is from about 90°F (32°C) to about 450°F (232°C). This base fuel may consist of straight chain or branched chain hydrocarbons,
10 paraffins, cycloparaffins, olefins, aromatic hydrocarbons, or mixtures thereof. The base fuel can be derived from among others, straight run naphtha, polymer gasoline, natural gasoline or from catalytically cracked or thermally cracked
15 hydrocarbons, alkylate and catalytically cracked reformed stock. The composition and octane level of the base fuel are not critical, and any conventional motor fuel base can be employed in the practice of this invention. However, the invention
20 is best employed in premium unleaded and regular unleaded gasolines, although it is also effective in leaded gasolines. The fuels may be gasoline containing up to 50% alcohol or ethers. Further, the fuel may be an alcohol- type fuel containing
25 over 50% to little or no hydrocarbon. Typical of such fuels are methanol, ethanol and mixtures of

methanol and ethanol. Further examples of alcohol fuels are propanols, butanols, pentanols, and higher alcohols. The ether fuels can be methyl tert butyl ether, ethyl tert butyl ether, di-isobutyl ether, tert amyl methyl ether and the like. The fuels which may be treated with the additive included gasohols which may be formed by mixing 90 to 95 volumes of gasoline with 5 - 10 volumes of ethanol or methanol. A typical gasohol may contain 90 volumes of gasoline and 10 volumes of absolute ethanol.

The fuel compositions of the instant invention may additionally comprise any of the additives generally employed in fuel compositions. Thus, the compositions of the instant invention may contain solvents, co-detergents, anti-knock compounds such as tetraethyl lead, anti-icing additives, upper cylinder and fuel pump lubricity additives, antistatic agents, corrosion inhibitors, antioxidants, water scavengers, lead scavengers, dyes, lead octane appreciators, anti-smoke additives and the like.

° Along with having excellent detergency properties, the additive packages are effective corrosion inhibitors and provide excellent water shedding and filtration performance.

The following Table I illustrates the relative proportions in which the additive components were mixed to formulate the fuel additive packages of the present invention.

<u>Example No.</u>	<u>Component</u>	<u>lb Additive/ MB Gasoline</u>
1	i) Polyisobutenyl (PIB) succinimide (MW PIB=920)	40
ii)	Polyisobutylene (PIB) (MW=600)	36
iii)	Commercial Ester/polyether mixture	57
2	i) Polyisobutenyl (PIB) succinimide (MW PIB=920)	40
ii)	Polyisobutylene (PIB) (MW=600)	36
iii)	Commercial Ester/polyether mixture	18
iv)	Mineral Oil (solvent refined naphthenic 500 SUS)	46

A single cylinder intake valve cleanliness test was used to determine the effectiveness of the additive formulation of the present invention. In the test, premium unleaded gasoline containing various quantities of a polyisobutenyl succinimide, polyisobutylene, and a commercial ester/polyether

mixture (a BASF Co. product sold under the trademark PLURADYNE CF-14), in which the ester/polyether components were of the kind described herein in accordance with Example 1 was
5 evaluated in a single-cylinder engine (using a 10W-30 mineral oil lubricant). After 40 hours of operation at 1100 rpm and 10-12 inches manifold vacuum, the intake valve was removed, its combustion chamber side cleaned and the gross
10 weight was determined. Deposits were then removed mechanically and the tare weight of the valve was measured in order to calculate the net weight of the deposits.

Table II, below, presents the results of
15 several test runs with premium unleaded gasoline containing the various additive package components indicated as well as the specific formulation of Example 1.

Table IICLR Intake Valve Cleanliness Test Results

-----Concentration (lb/MB)-----

<u>Run</u>	<u>Polyisobutenyl Succinimide</u>	<u>Ester/Ether</u>	<u>Polyisobutylene</u>	<u>ITV Deposit Wt.,mg</u>	<u>% Deposits vs Base</u>
A	-	-	-	298	-
B	50	-	-	561	188
C	-	100	-	165	55
D 10	-	-	100	109	37
E	40	36	57	47	16

As the results in Table II show, the use of a polyisobutenyl-succinimide alone at a concentration of 50 lb/MB (Run B) increased intake valve (ITV) deposits 188% as compared to the base fuel alone (Run A). A concentration of 100 lb/MB of the commercial ester/polyether mixture reduced deposits to 55% (Run C) as compared to the base fuel alone (Run A). The polyisobutylene alone at a concentration of 100 lb/MB (Run D) reduced deposits to 37% as compared to the base fuel alone (Run A). However, in Run E, using an additive package of the kind described herein, an unexpectedly large reduction in deposits was observed. The additive package of Example 1, in a concentration of 133 lb

of additive per 1,000 barrels of fuel, decreased deposits to 16% (Run E) as compared to the base fuel alone (Run A).

As demonstrated by the results of Table II, although the ester/polyether mixture and polyalkylenes such as polyisobutylene can improve intake cleanliness to some degree (Runs C and D, respectively), these hydrocarbons provide no carburetor or port fuel injector detergency, and therefore cannot be used alone to provide full deposit control. However, full deposit control is obtained when the components are blended together in a synergistic additive package.

CLAIMS:

1. An additive for normally liquid fuels having detergency, solubility and thermal stability comprising a combination of

- i. a polyalkenyl succinimide which is the reaction product of a polyalkenyl succinic anhydride and a polyalkylene polyamine;
- ii. a polymer or copolymer of an olefinic hydrocarbon;
- iii. an ester; and
- iv. a polyether.

2. The additive of claim 1 in which the relative proportions of the components are in an amount of 10 to 80 wt. % of the polyalkenyl succinimide, 10 to 80 wt. % of the polymer or copolymer, 1 to 80 wt. % of the ester and 1 to 80 wt. % of the polyether based on the total weight of the additive.

3. The additive of claim 1 in which the polyalkenyl succinimide has a molecular weight of 600 to 3,000 and the polymer or copolymer has a molecular weight of 600 to 3,000.

4. The additive of claim 1 in which the alkylene group of the polyalkenyl succinimide is a polyolefin made from 1-olefins which are 1-ethylene, 1-propylene, 1-butylene, 1-isobutylene, 1-pentene, 1-hexene, 1-octene, 1-decene or higher 1-olefins or copolymers thereof.

5. The additive of claim 1 in which the polyalkylene polyamine is ethylene diamine, propylene diamine, butylene diamine, diethylene triamine, triethylene tetramine, tetraethylene pentamine, pentaethylene hexamine, dipropylene triamine or tripropylene tetramine.

6. The additive of claim 1 in which the olefinic hydrocarbon of (ii) is ethylene, propylene, butylene, 2-butylene, isobutylene, pentene, hexene, butadiene, isoprene, octene or decene.

7. The additive of claim 1 in which the ester is an aromatic ester derived from a mono-, di-, tri- or tetra-carboxylic acid substituted benzene compound and a linear alcohol containing at least four carbon atoms or a branched oxo-alcohol containing at least six carbon atoms.

8. The additive of claim 1 in which the esters are adipates, phthalates, isophthalates, terephthalates and trimellitates of iso-octanol, iso-nonanol, iso-decanol or iso-tridecanol or mixtures thereof, polyol esters of neopentyl glycol, pentaerythritol or trimethylolpropane with corresponding monocarboxylic acids, oligomer and polymer esters of dicarboxylic acid, polyol and monoalcohol.

9. The additive of claim 1 in which the polyether is a polymer or copolymer of ethylene oxide, propylene oxide, butylene oxide, pentene oxide, hexene oxide, octene oxide, decene oxide or isomer thereof.

10. The additive of claim 1 in which the polyether has a molecular weight of 500 to 3,000.

11. The additive of claim 1 in which the additive further comprises a mineral oil or synthetic oil.

12. A normally liquid fuel composition comprising a major amount of a normally liquid fuel and an additive having detergency, solubility and

thermal stability, the additive comprising a combination of

- i. a polyalkenyl succinimide which is the reaction product of a polyalkenyl succinic anhydride and a polyalkylene polyamine;
- ii. a polymer or copolymer of an olefinic hydrocarbon;
- iii. an ester; and
- iv. a polyether.

13. The composition of claim 12 in which the relative proportions of the components of the additive are in an amount of 10 to 80 wt. % of the polyalkenyl succinimide, 10 to 80 wt. % of the polymer or copolymer, 1 to 80 wt. % of the ester and 1 to 80 wt. % of the polyether based on the total weight of the additive.

14. The composition of claim 12 in which the polyalkenyl succinimide has a molecular weight of 600 to 3,000 and the polymer or copolymer has a molecular weight of 600 to 3,000.

15. The composition of claim 12 in which the alkylene group of the polyalkenyl succinimide is a polyolefin made from 1-olefins which are 1-ethylene, 1-propylene, 1-butylene, 1-isobutylene, 1-pentene, 1-hexene, 1-octene, 1-decene or higher olefins or copolymers thereof.

16. The composition of claim 12 in which the polyalkylene polyamine is ethylene diamine, propylene diamine, butylene diamine, diethylene triamine, triethylene tetramine, tetraethylene pentamine, pentaethylene hexamine, dipropylene triamine or tripropylene tetramine.

17. The composition of claim 12 in which the olefinic hydrocarbon of (ii) is ethylene, propylene, butylene, 2-butene, isobutylene, pentene, hexene, butadiene, isoprene, octene or decene.

18. The composition of claim 12 in which the ester is an aromatic ester derived from a mono-, di-, tri- or tetra-carboxylic acid substituted benzene compound, and a linear alcohol containing at least four carbon atoms or a branched oxo-alcohol containing at least six carbon atoms.

19. The composition of claim 12 in which the esters are adipates, phthalates, isophthalates, terephthalates and trimellitates of iso-octanol, iso-nonanol, iso-decanol or iso-tridecanol or mixtures thereof, polyol esters of neopentyl glycol, pentaerythritol or trimethylolpropane with corresponding monocarboxylic acids, oligomer and polymer esters of dicarboxylic acid, polyol and monoalcohol.

20. The composition of claim 12 in which the polyether is a polymer or copolymer of ethylene oxide, propylene oxide, butylene oxide, pentene oxide, hexene oxide, octene oxide, decene oxide or isomer thereof.

21. The composition of claim 12 in which the polyether has a molecular weight of 500 to 3,000.

22. The composition of claim 12 in which the additive further comprises a mineral oil or synthetic oil.

23. The composition of claim 12 in which the fuel is a liquid hydrocarbon or liquid oxygenated fuel or mixture of liquid hydrocarbon and liquid oxygenated fuels in which the additive is used in a concentration of from 10 to 500 pounds of additive per 1000 barrels of fuel.

24. A method of making a normally liquid fuel composition comprising blending a major proportion of a normally liquid fuel or lubricant and an additive having detergency, solubility and thermal stability, the additive comprising a combination of

- i. a polyalkenyl succinimide which is the reaction product of a polyalkenyl succinic anhydride polyalkylene polyamine;
- ii. a polymer or copolymer of an olefinic hydrocarbon;
- iii. an ester; and
- iv. a polyether.

INTERNATIONAL SEARCH REPORT

International Application No. PCT/US91/05506

CLASSIFICATION OF SUBJECT MATTER

According to International Patent Classification (IPC) and to both National Classification and IPC
 IPC(5): C10L 5/00; US Cl.: 44/398; 585/12; 44/347

FIELDS SEARCHED

Minimum Documentation Searched

Classification Symbol

Classification Symbols

U.S.

44/347; 44/398; 585/12

Documentation Searched other than Minimum Documentation
 to the extent that such Documents are included in the Fields Searched

DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No. 1
Y	US, A, 4,098,585 (VARTANIAN) 04 JULY 1978 See entire document.	1-24
Y	US, A, 3,419,365 (STREETS) 31 DECEMBER 1968 See entire document.	1-24
Y	US, A, 4,032,304 (DORER ET AL.) 28 JUNE 1972 See entire document.	1-24
Y	DE, A, 3,838,918 (BASF) 23 MAY 1990 See entire document.	1-24

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"A" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

Date of Mailing of this International Search Report

25 OCTOBER 1991

25 NOV 1991

International Searching Authority

ISA/US

Signature of Authorized Officer

NGUYEN NGOC-HO

INTERNATIONAL DIVISION

Maria Nuzzolillo