




(86) Date de dépôt PCT/PCT Filing Date: 2013/03/19
(87) Date publication PCT/PCT Publication Date: 2013/09/26
(45) Date de délivrance/Issue Date: 2019/09/24
(85) Entrée phase nationale/National Entry: 2014/09/18
(86) N° demande PCT/PCT Application No.: GB 2013/000118
(87) N° publication PCT/PCT Publication No.: 2013/140115
(30) Priorités/Priorities: 2012/03/19 (GB1204797.3);
2012/12/10 (GB1222120.6)

(51) Cl.Int./Int.Cl. *E04H 12/22*(2006.01),
E01F 13/02(2006.01)
(72) Inventeur/Inventor:
HIGGS, PHILIP MAURICE, GB
(73) Propriétaire/Owner:
KEE SAFETY LIMITED, GB
(74) Agent: FETHERSTONHAUGH & CO.

(54) Titre : SYSTEME DE RAIL DE SECURITE MODULAIRE
(54) Title: MODULAR SAFETY RAIL SYSTEM



(57) Abrégé/Abstract:

A support foot (10) for a vertical member (48) of a safety rail system comprises an upper body section (14) which defines an upper surface region of the support foot and a lower body section (15) which defines a lower surface region, the two bodies having at least in part a substantially common outer periphery and each body section having extending therethrough a plurality of location formations (25) for supporting one or more vertical members (48) of the safety rail system.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(10) International Publication Number

WO 2013/140115 A1

(43) International Publication Date
26 September 2013 (26.09.2013)

WIPO | PCT

(51) International Patent Classification:
E04H 12/22 (2006.01) *E01F 13/02* (2006.01)

(21) International Application Number:
PCT/GB2013/000118

(22) International Filing Date:
19 March 2013 (19.03.2013)

(25) Filing Language:
English

(26) Publication Language:
English

(30) Priority Data:
1204797.3 19 March 2012 (19.03.2012) GB
1222120.6 10 December 2012 (10.12.2012) GB

(71) Applicant: **KEE SAFETY LIMITED** [GB/GB]; Cradley Business Park, Overend Road, Cradley Heath, West Midlands B64 7DW (GB).

(72) Inventor: **HIGGS, Philip Maurice**; 34 Armour Hill, Tilehurst, Reading, Berkshire RG31 6JP (GB).

(74) Agent: **BADGER, John Raymond**; J. R Badger & Co, 6 Simpson Road, Sutton Coldfield, West Midlands, B72 1EP (GB).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: MODULAR SAFETY RAIL SYSTEM



(57) Abstract: A support foot (10) for a vertical member (48) of a safety rail system comprises an upper body section (14) which defines an upper surface region of the support foot and a lower body section (15) which defines a lower surface region, the two bodies having at least in part a substantially common outer periphery and each body section having extending therethrough a plurality of location formations (25) for supporting one or more vertical members (48) of the safety rail system.

FIG. 1

MODULAR SAFETY RAIL SYSTEM

This invention relates to a support foot for a modular type safety rail system and in particular, though not exclusively, to a support foot for a modular safety rail system suitable for use in providing free-standing roof edge protection.

Modular type safety rail systems are well known and typically comprise safety rail sections formed from lengths of metal tubing or panels which are inter-connected at ground level by connectors which, for example, facilitate construction of two, three or four way inter-connections of safety rail sections.

Tubes serving as vertical posts of a safety rail section conventionally are supported by and secured to cast iron metal base plates. The base plates generally need to be of a robust, heavy construction thereby to provide firm support and location for the vertical posts. Many different designs of base plates have been proposed, but different designs suffer different disadvantages. Thus some are relatively expensive to manufacture whilst others do not lend themselves to ease of use, for example ease of securing the vertical posts to the base plates and/or ease of securing toe boards of different sizes or in different orientations. Other designs do not lend themselves readily to being stacked safely in a manner which is inherently adapted to resist toppling of the stacked assembly.

Furthermore, in general the known designs of base plates are not entirely satisfactory for manufacturing from recycled non-ferrous or other metallic material, for example by moulding of recycled polymeric materials such as polyvinyl chloride. Such materials commonly either lack the stiffness of cast iron or do not have sufficient strength for enabling them to be provided with satisfactory screw-threaded formations such as may be necessary in order that a safety rail can be secured properly to the base plate.

The present invention seeks to provide an improved support foot for a modular safety rail system in which at least some of the aforescribed disadvantages of known base plates are mitigated or overcome. The invention seeks also to provide a safety rail assembly comprising a plurality of said support feet and safety rail sections.

In accordance with one aspect of the present invention there is provided a support foot for a modular safety rail system, said support foot being adapted to provide location for a vertical member of a safety rail section and comprising:

a support body assembly having upper and lower surface regions and an outer periphery;

a plurality of location formations positioned inwards of said outer periphery and each extending into the support body assembly from said upper surface for location of a vertical member of a safety rail section;

said support foot comprising two bodies to provide said support body assembly, one of said bodies being an upper body section which defines said upper surface region, the other of said bodies being a lower body section which defines said lower surface region, the two bodies having at least in part a common outer periphery and said location formations each extending through at least that material that defines the upper body section,

at least one of said location formations having associated therewith a retention means for securing a vertical member of a safety rail section against removal from the support foot, and

said retention means comprising a retainer which is held captive within the assembly of the two support foot body sections.

Preferably the location formations each extend through the upper body section and at least a part of the thickness of the lower body section.

A location formation may be in the form of a socket of circular or other cross-sectional shape. Preferably the cross-sectional shape and size of the socket is substantially the same as that of the cross-sectional shape and size of the vertical member which is to be located within the socket when constructing a safety rail assembly.

The location formations may extend through the whole thickness of the lower body section but more preferably terminate at a position spaced from said lower surface region whereby, in use, the lower end of a vertical member is prevented from contacting and thus potentially damaging a support surface such as that of a roof on which the support foot is positioned.

Confronting surfaces of the two bodies may be provided with one or a plurality of inter-engaging formations whereby, on assembly of the two bodies in contact with one another, the two bodies become located in a predetermined alignment. One of the confronting surfaces may be provided with a plurality of protrusion each engagable with a respective one or a plurality of recesses in the other of the confronting surfaces or each of the surfaces may be provided with a combination of recesses and protrusions.

The inter-engaging formations may be of a type which resist relative sliding movement of the two body sections in a plane substantially perpendicular to the direction in which the location formations extend through the support body assembly.

Said inter-engaging formations may serve also to resist tilting movement of the upper body section relative to the lower body section. For that purpose the inter-engaging formations preferably comprise confronting formation surfaces at least one of which extends in a direction substantially perpendicular to the direction in which the inter-engaging formations restrain relative sliding movement of the two body sections.

One or each of the confronting surfaces of the two body sections may be provided with at least one protrusion in the form of a substantially cylindrical boss for engagement within, as a close fit, the wall of a recess formed in the other of the two confronting surfaces of the body sections. Said wall also may be of a substantially cylindrical shape but that is not an essential feature for resisting toppling movement, it being sufficient that the protrusion is a close fit against one or more surface regions of a recess. Thus, in general, the present invention teaches that relative tilting of the two body sections may be inhibited by providing respective confronting surfaces of the two body sections with inter-engaging formations which are a close fit or which come into contact with one another following an initial tilting movement and thereby inhibit further relative tilting movement.

Connectors may be provided for securing together the two body sections.

Each of the bodies may be provided with a plurality of apertures which align with apertures in the other body for the purpose of locating connectors, such as bolts, whereby the two bodies may be secured relative to one another. Accordingly said connectors may be employed to inhibit relative tilting movement of the two body sections and also to prevent lifting of the upper body section away from the lower body section.

Preferably at least said lower surface region, as defined by the lower body portion, is provided with recesses aligned with the apertures for the purpose of accommodating ends of connectors, such as bolt heads or nuts, to ensure that, in use, those ends do not apply point loading to the support surface on which the support foot is positioned.

Particularly suitable materials for forming the bodies include polymeric materials, including recycled polymeric materials such as polyvinyl chloride. Alternatively however, the bodies may be formed from metallic materials such as cast iron. The bodies may be formed, for example, by casting or injection moulding techniques.

The support foot may be provided with one or more slots each for location of a toe board. Side faces of a slot may be defined solely by the upper body section or they may be defined by both of the upper and the lower body sections. The lower body section may define slot sides which do not extend fully to the lower surface of the lower body section such that, in use, material defining the lower surface acts to maintain the lower edge of a toe board spaced slightly above the support surface on which the support foot is positioned.

Preferably each location formation has associated therewith a retention means whereby a vertical member of a safety rail section may be secured against upwards removal from the support foot. Said retention means may comprise a retention means aperture which extends from the location formation in an outwards direction towards the outer periphery of the support foot in the manner in which said aperture is accessible for enabling vertical member to be secured in position subsequent to insertion of the vertical member into the location formation.

In the case of a support foot having one or more slots for a toe board, preferably a said slot is aligned with a location formation such that the retention means aperture extends to, and is accessible at, that end of the slot which lies innermost from the outer periphery of the support foot.

The retention means aperture may be a screw threaded aperture and may be provided with a retention screw, such as a grub screw, which may be brought into firm engagement with the surface of a vertical member of a safety rail section thereby to prevent ready removal of the safety rail section from the support foot. More preferably, however, and to avoid the need to form a screw thread in either of the upper and lower body sections, the retention means aperture may provide access to a retainer which is captive within the assembly of the two support foot body sections.

A captive retainer may be in the form of a tubular sleeve which is provided within the support foot at a position co-axial with a longitudinal axis of the location formation, the sleeve having an internal profile slightly greater than external profile of the vertical member such that in the assembly the sleeve surrounds the vertical member.

The sleeve may be provided with a screw threaded aperture for a screw, such as a grub screw, which can be brought to bear firmly against the vertical member such that the captive retainer acts to hold the vertical member captive relative to the support foot.

The sleeve may have a formation such as a boss which surrounds the screw threaded aperture and extends radially outwards from the sleeve whereby the boss co-operates with abutments defined by the support body to retain the screw threaded aperture of the sleeve aligned with the retention means aperture. The retention means aperture of the support body may be defined by either or each of the body sections and may be in the form of a recess provided in a said confronting surface of one or each of the body sections. Particularly if the retention means aperture is not screw threaded, the retention means aperture may be defined in part by each of the upper and lower body sections of the support foot.

The support foot may be provided with a pair of openings and/or the lower surface region may be provided with a pair of recesses to serve as handles for enabling the support foot readily to be lifted for transportation.

The upper and lower surface regions of the support body assembly may comprise inter-engagable formations whereby when one support foot is stacked upon a second support foot said inter-engaging formations resist relative sliding movement of one support foot relative to the other. Said formations may be positioned close to the outer periphery of the support body assembly whereby they serve to resist toppling of the superimposed support foot relative to the underlying support foot. More preferably said formations inter-engage in a manner substantially similar to the

aforedescribed inter-engaging formations of the upper and lower body sections whereby tilting of the superimposed support foot relative to the underlying support foot is inhibited.

The present invention provides also a modular safety rail assembly comprising two safety rail sections each supported by a support foot of a type in accordance with the present invention.

The present invention further teaches provision of at least one safety rail section tie such that two said safety rail sections may be secured to one another at a position remote from the support body, preferably within the upper 30% of the height of the safety rail sections. The tie may be of a kind which merely limits relative movement of the upper regions of adjacent support rail sections or the tie may be rigidly secured to at least one of the safety rail sections whereby it inhibits relative movement of the safety rail sections.

Embodiments of the present invention will now be described, by way of example only, with reference to the accompanying diagrammatic drawings in which:-

Figure 1 is an exploded perspective view of a support foot in accordance with an embodiment of the present invention;

Figure 2 is a perspective view of the support foot of Figure 1 in an assembled condition;

Figures 3 to 5 are respectively plan and side elevations of the support foot of Figure 2;

Figure 6 is a perspective view of an upper body section of the support foot of Figure 2;

Figures 7 to 9 are respectively plan and side elevations of the support body section of Figure 6;

Figure 10 is a perspective view of the lower body section of the support foot of Figure 2;

Figures 11 to 13 are respectively plan and side elevations of the support body section of figure 10;

Figure 14 is a perspective view of a safety rail section retainer sleeve;

Figure 15 is a perspective view of the support foot of Figure 1 in an assembled condition and showing the lower surface of the lower body section;

Figure 16 is a perspective view of part of a safety rail assembly in accordance with the present invention, and

Figure 17 is a perspective view of a safety rail assembly in accordance with another embodiment of the present invention.

A support foot 10 (see Figures 2 to 5) for a modular safety rail system comprises a two-part body having substantially planar upper and lower surfaces 11,12 which each define a substantially square outer periphery 13.

The upper surface 11 is defined by an upper body section 14 (see Figures 1 and 6 to 9) and the lower surface 36 is defined by a lower body section 15 (see figures 1 and 10 to 13). Each body section is formed by injection moulding of recycled polyvinyl chloride, in this embodiment the material having a density of approximately 1.65 g/cm³.

The support foot is formed with eight apertures 16 arranged two near to each edge 17 of the support foot. Bolts 18 (see Figure 1) are provided to extend through the apertures to secure together the two body sections.

The upper and lower surfaces 11,12, of the support foot are provided with recesses 19 aligned with each aperture 16 to locate bolt heads and associated nuts and washers, in particular such that the nuts and /or bolts do not protrude beneath general plane of the lower surface 12 and impose, in use, any potentially damaging point loads on a roof or other such support surface.

To assist in ensuring alignment of the apertures when the two body sections are connected together by the bolts the lower body section 15 is provided with protrusions 20 in the form of bosses which extend from that surface 21 which in the assembly confronts a surface 22 of the upper body section. The confronting surface 22 of the upper body section is formed with recesses (not shown) in which the protrusions 20 are a close fit.

The protrusions 20 each comprise a cylindrical surface which extends in a direction substantially perpendicular relative to the body section surface from which it depends and accordingly, by virtue of being a close fit in a corresponding protrusion in the other body section, relative tilting movement of the two body sections is inhibited.

The support foot is formed with four uniformly spaced location sockets 25 positioned near to but spaced from the centre of the upper surface 11 and extending substantially perpendicular relative to the plane of that surface, each for location of a vertical post extending from and typically forming part of a safety rail section. Each socket extends through the upper body section and into the lower body section. Opposite sockets 25 are aligned with a line extending between opposite corners 26 of the support foot.

The support foot additionally is formed with four uniformly spaced slots 27 each for location of a toe board. Each slot extends from a corner position 26 of the support body to a position near to but spaced from one of the sockets 25. The lower body section 15 is shaped to define a passage 28 which lies adjacent the confronting surface 21 of that section, the passage extending in the form of a surface recess between the slot 27 and the nearest socket 25.

A portion of the socket 25 defined by the lower body section has a cross-sectional shape greater than that of the portion of the socket defined by the upper body section 14 thereby to provide an annular space for location of a tubular retention sleeve 30 (see Figure 1 and 14) defined by the upper body section 14. The sleeve 30 has a radially outwardly extending boss 31 that locates in the aforescribed passage 28 such that the sleeve is thereby prevented from rotation within the socket. The socket formation in the lower body section 15 is of a stepped diameter, reducing in diameter firstly to provide an annular shoulder 32 on which the sleeve may rest, and closest to the lower surface 12, an annular shoulder 33 which serves as a end stop for abutment by the lower end of a post inserted into the socket.

A screw threaded aperture 34 is formed in the boss and extends through the boss such that it is aligned with and accessible from the passage 28. Accordingly, in use, a grub screw in the sleeve aperture 34 may be tightened to bear firmly against a vertical post positioned in the socket. Because the socket portion as defined by the upper body section has a diameter less than the diameter of the retention sleeve 30 the post is held captive against vertical removal from and rotation relative to the socket.

Two opposite sides of the support foot are formed with openings 40 each aligned with recesses 41 in the lower surface to act as handle positions for lifting of the support body.

The upper surface 11 of the upper body section 14 and the lower surface 36 of the lower body section comprise respective protrusions and depressions whereby when one support foot is stacked on top of another support foot relative sliding movement is resisted. In this embodiment the upper surface 11 comprises upwardly extending rib formations 37 aligned with the toe board slots 27 and the lower surface 36 comprises depressions in the form of channel-like recesses 38 (see Figure 15).

An assembly 45 comprising two support rail sections 46 is shown in Figure 16. Each support rail section has a downwardly extending post region 48 secured in a respective one of two of the support body sockets 25. Near to the upper regions of the support rail sections a tie bar 47 is secured firmly to each of the rail sections to inhibit relative movement of the two sections.

Accordingly any sideways load imposed on one of the support rail sections 46 is transmitted in part to an adjacent support rail section and any tendency for undue sideways movement is resisted by the support bodies in which the or each of said adjacent support rail sections is located.

Another form of assembly is shown in Figure 17. In this assembly 50 the horizontally extending rails 51 are secured together either by in-line connectors 52 or right angle connectors 53, thereby obviating the need to provide the tie bars 47 described in the context of the assembly 45 of Figure 16. In the assembly of Figure 17, in which each support foot is of the type described above with reference to Figures 1 to 15, connector bolts 18 optionally are provided in each end support foot 55 but are omitted from each intervening support foot 56, each support foot 56 being constrained against relative tilting movement of the upper and lower body sections of the support foot by virtue of the configuration of the assembly 50.

CLAIMS

1. A support foot for a modular safety rail system, said support foot being adapted to provide location for a vertical member of a safety rail section and comprising:

a support body assembly having upper and lower surface regions and an outer periphery;

a plurality of location formations positioned inwards of said outer periphery and each extending into the support body assembly from said upper surface for location of a vertical member of a safety rail section;

said support foot comprising two bodies to provide said support body assembly, one of said bodies being an upper body section which defines said upper surface region, the other of said bodies being a lower body section which defines said lower surface region, the two bodies having at least in part a common outer periphery and said location formations each extending through at least that material that defines the upper body section,

at least one of said location formations having associated therewith a retention means for securing a vertical member of a safety rail section against removal from the support foot, and

said retention means comprising a retainer which is held captive within the assembly of the two support foot body sections.

2. A support foot according to claim 1 wherein the location formations each extend through the upper body section and at least a part of a thickness of the lower body section.

3. A support foot according to claim 2 wherein at least some said location formations terminate at positions spaced from said lower surface region of the support body assembly whereby, in use, the lower end of a vertical member of a safety rail section is prevented from contacting a support surface on which the support foot is positioned.
4. A support foot according to any one of claims 1 to 3 wherein each of the two bodies defines a surface which confronts the other of the two bodies and said confronting surfaces are each provided with a formation which in the assembly of the two bodies inter-engages with a complementary formation in the other of the two bodies.
5. A support foot according to claim 4 wherein said inter-engaging formations maintain the two bodies in alignment when in contact with one another.
6. A support foot according to claim 4 or claim 5 wherein said inter-engaging formations resist relative sliding movement of the two body sections in a direction perpendicular to the direction in which the location formations extend through the support body assembly.
7. A support foot according to any one of claims 4 to 6 wherein the inter-engaging formations of said confronting surfaces of the two body sections comprise confronting surfaces which, in use, resist tilting of the upper body section relative to the lower body section.
8. A support foot according to any one of claims 4 to 7 wherein at least one of the confronting surfaces of the inter-engaging formations extends parallel with the direction in which the location formations extend through the support body assembly.

9. A support foot according to claim 7 wherein said at least one the confronting surfaces of the inter-engaging formations extends in a direction perpendicular to one of said body section confronting surfaces.
10. A support foot according to any one of claims 1 to 9 and comprising connectors for securing together the upper and lower body sections.
11. A support foot according to claim 10 wherein each of the bodies is provided with a plurality of location connector apertures which align with apertures in the other body for the purpose of locating connectors for securing the two bodies relative to one another.
12. A support foot according to claim 11 wherein said lower surface region is provided with a recess aligned with a location connector aperture for the purpose of accommodating an end of a connector.
13. A support foot according to any one of claims 1 to 12 and comprising at least one slot for location of a toe board.
14. A support foot according to claim 13 wherein side faces of the slot are defined solely by the upper body section.
15. A support foot according to claim 13 wherein a slot is defined by both of the upper and lower body sections.
16. A support foot according to claim 15 wherein the lower body section defines slot sides which do not extend fully to the lower surface of the lower body section.

17. A support foot according to any one of claims 1 to 16 wherein said retention means comprises a retention means aperture which extends from the location formation in an outwards direction towards the outer periphery of the support foot.
18. A support foot according to claim 17 when dependent on any one of claims 8 to 11 wherein the retention means aperture extends to and is accessibly at an end of a slot which lies innermost from the outer periphery of the support foot.
19. A support foot according to claim 17 or claim 18 wherein a retention means aperture is defined by one of the body sections.
20. A support foot according to claim 17 or claim 18 wherein a retention means aperture is defined in part by each of the upper and lower body sections of the support foot.
21. A support foot according to any one of claims 1 to 20 wherein the captive retainer is a tubular sleeve provided within the support foot at a position co-axial with a longitudinal axis of the location formation and through which a vertical member of a safety rail section may extend.
22. A support foot according to claim 21 wherein the tubular sleeve is provided with a screw threaded aperture for a screw which, in use, may be brought to bear firmly against a vertical member of a safety rail section to hold the vertical member captive relative to the support foot.
23. A support foot according to claim 22 wherein the tubular sleeve comprises a boss which surrounds the screw threaded aperture and extends radially outwards from the sleeve to co-operate with abutments defined by the support body and thereby retain the screw threaded aperture of the sleeve aligned with the retention means aperture.

24. A support foot according to any one of claims 1 to 23 wherein said upper and lower surface regions of the support body assembly respectively comprise inter-engagable formations whereby when one support foot is stacked superimposed on another support foot said formations resist at least one of sliding movement, toppling movement or tilting movement of the superimposed support foot relative to the underlying support foot.
25. A modular safety rail assembly comprising two safety rails or safety rail sections each supported by a support foot of a type in accordance with any one of claims 1 to 24.
26. A modular safety rail assembly according to claim 25 wherein two safety rail sections are inter-connected by a said support foot and a tie, said tie being positioned remote from the support body.
27. A modular safety rail assembly according to claim 26 wherein the safety rail sections have height dimensions and said tie is positioned within the upper 30% of the height of the safety rail sections.
28. A modular safety rail assembly according to claim 26 or claim 27 wherein the tie is rigidly secured to at least one of the safety rail sections.

1/7




FIG. 1




FIG. 2




FIG. 3




FIG. 4








FIG. 5

3/7






FIG. 10




FIG. 11




FIG. 12




FIG. 13

5/7




FIG. 14




FIG. 15

6/7




FIG. 16

7/7




FIG. 17

