

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/011989 A1

(51) International Patent Classification⁷: G02C 7/04

(21) International Application Number: PCT/EP2003/008058

(22) International Filing Date: 23 July 2003 (23.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/398,485 24 July 2002 (24.07.2002) US

(71) Applicant (for all designated States except AT, US): NOVARTIS AG [CH/CH]; Lichtstrasse 35, CH-4056 Basel (CH).

(71) Applicant (for AT only): NOVARTIS PHARMA GMBH [AT/AT]; Brunner Strasse 59, A-1235 Vienna (AT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): LINDACHER, Joseph, Michael [US/US]; 1115 Eagle Pointe Drive, Lawrenceville, GA 30044 (US). HALL, Jordan, William [US/US]; 170 5th Street N.W., Atlanta, GA 30313 (US).


(74) Agent: GRUBB, Philip; Novartis AG, Corporate Intellectual Property, CH-4002 Basel (CH).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LT, LU, LV, MA, MD, MK, MN, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SE, SG, SK, SY, TJ, TM, TN, TR, TT, UA, US, UZ, VC, VN, YU, ZA, ZW.

(84) Designated States (regional): Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

[Continued on next page]

(54) Title: TRANSLATING CONTACT LENS HAVING A RAMPED RIDGE



(57) Abstract: The present invention provides a translating contact lens having a central axis, an anterior surface and an opposite posterior surface. The anterior surface includes an optical zone and a tamped ridge zone capable of controlling contact lens position on an eye in primary gaze and/or translating amount across the eye when the eye changes from gazing at an object at a distance to gazing at an object at an intermediate distance or at a nearby object. The tamped ridge zone is disposed below the optical zone and includes an upper edge, a lower tamped edge, a latitudinal ridge that extends outwardly from the anterior surface, and a ramp that extends downwardly from the lower tamped edge and has a curvature or slope that ensures a varying degree of interaction between the tamped ridge zone and the lower eyelid depending on where the lower eyelid strikes the tamped ridge zone. The lower eyelid of the eye is engaged with at least some portion of the tamped ridge zone at all times.

WO 2004/011989 A1



Published:

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Translating contact lens having a ramped ridge

This invention is related to contact lenses. In particular, the present invention is related to translating contact lenses each having a ramped ridge zone on the lower portion of the anterior surface that is able to control lens position on the eye in primary gaze and/or translation amount across the surface of the eye when the eye changes from gazing at an object at a distance to gazing at a nearby object.

Contact lenses are widely used for correcting many different types of vision deficiencies. These include defects such as near-sightedness and far-sightedness (myopia and hypermetropia, respectively), and defects in near range vision usually associated with aging (presbyopia). Presbyopia occurs as a person ages when the lens of eye begins to crystallize and lose its elasticity, eventually resulting in the eye losing the ability to focus at near distances, such as the normal reading distance, and in some cases at intermediate distances. Some presbyopic persons have both near vision and far vision defects, requiring bifocal or multifocal lenses, instead of single vision lenses, to properly correct their vision.

A typical single vision contact lens has a focus, which is the point on which parallel rays of light focus when the lens is placed perpendicular to the parallel rays, and an optical axis, which is an imaginary line drawn from the focus to the center of the lens. A posterior surface fits against the cornea and an opposite anterior surface has a vision surface that focuses light to correct the eye's vision. In the case of a typical spherical lens, the vision surface has a single radius of curvature that is the distance from any point on the vision surface to a point on the optical axis referred to as the center of curvature.

A bifocal lens has at least two vision surfaces on the anterior surface of the lens: a distance vision surface, for gazing at far off objects, and a near vision surface, for gazing at close objects (e.g., while reading). Generally, bifocal contact lenses are concentric or segmented in configuration. In a conventional bifocal contact lens of the concentric type, a first, centrally located, circular correction zone constitutes either distant or near vision correction, while a second annular correction zone surrounding the first zone provides the corresponding near or distance vision correction, respectively. In a conventional bifocal contact lens of the segmented or translating type, the lens is divided into two optical zones. Usually the upper zone is for distance vision correction, whereas the lower zone is for near vision correction.

- 2 -

With such a translating lens, the distance portion (upper zone) of the lens is in front of the pupil of the eye in straight-ahead gaze, while in downward gaze, the add power or near portion (lower zone) of the lens is over the pupil.

Effective use of bifocal contact lens requires translation of the eye between vision surfaces when the eye changes from grazing at an object at a distance to grazing a nearby object. In such a situation, the pupil must move from being subtended by the distance vision surface to being subtended by the near vision surface.

Additionally, with the increasing use of computers, more and more people utilize a computer at work and at home. It is desirable that a translating contact lens could have one or more intermediate vision surfaces in addition to the near and distant vision surfaces. Such a translating contact lens may have to have an ability to control the translation amount of the eye in a manner that the pupil can be subtended by one of near vision surface, intermediate vision surfaces, and distant vision surface.

While there are many designs for hard bifocal translating contact lenses, soft contact lenses have difficulty in translating across the surface of the eye when the visual direction of the eye changes from horizontal gaze (distance vision) to down gaze (near vision). There are several lens designs reported for soft bifocal translating lenses (see, for example, U.S. Patent Nos. 4,618,277, 5,071,244, 5,371,976, 6,109,749). However, there are some disadvantages associated with those designs in the prior art. Bifocal translating contact lenses in the prior art are not comfortable to be worn. Furthermore, bifocal translating contact lenses in the prior art would be unable to control the translating amount of a contact lens across the surface of the eye.

Therefore, there is a need for a soft translating multi-focal contact lens that is capable of translating across the surface of the eye when the eye changes position from distance vision to near vision and providing wearer's comfort. There is also a need for a soft translating multi-focal contact lens that can control the amount of translation across the surface of the eye when the eye changes position from distance vision to an intermediate vision or to near vision.

SUMMARY OF THE INVENTION

The disadvantages of the prior art are overcome by the present invention which, in one aspect, is a translating contact lens having a central axis, an anterior surface and an opposite posterior surface. The posterior surface has an optical zone. The anterior surface includes an optical zone and a ramped ridge zone capable of controlling contact lens position on an eye in primary gaze and/or translating amount across the eye when the eye changes from gazing at an object at a distance to gazing at an object at an intermediate distance or at a nearby object. The ramped ridge zone is disposed below the optical zone and includes an upper edge, a lower ramped edge, a latitudinal ridge that extends outwardly from the anterior surface, and a ramp that extends downwardly from the lower ramped edge and has a curvature or slope that provides a varying degree of interaction between the ramped ridge zone and the lower eyelid depending on where the lower eyelid strikes the ramped ridge zone. The lower eyelid of the eye is engaged with at least some portion of the ramped ridge zone at all times.

In a preferred embodiment, at least one of the optical zones of the anterior and posterior surfaces includes a first portion to provide distant vision correction for the eye and a second portion disposed beneath the first portion to provide near vision correction for the eye.

In another preferred embodiment, at least one of the optical zones of the anterior and posterior surfaces has a top edge, a lower edge, a distance vision zone and a near vision zone.

The distance vision zone provides distance vision correction and has a first area that is sufficient to overlay a substantial portion of a pupil of an eye and is disposed in a first position within the optical zone so that the pupil is substantially subtended by the distance vision zone when the eye is gazing at a substantially horizontal point.

The near vision zone is substantially concentric with the central axis and extends radially outward from the distance vision zone. The near vision zone provides near vision correction and has a second area that is sufficient to overlay a substantial portion of a pupil of an eye. The near vision zone is disposed in a second position within the optical zone so that the pupil

is substantially subtended by the near vision zone when the eye is gazing at a near vision point below the substantially horizontal point.

In another preferred embodiment, at least one of the optical zones of the anterior and posterior surfaces has a top edge, a lower edge, a distant vision zone, an intermediate vision zone, and a near vision zone. An optical zone including three vision zones can provide distance vision correction (e.g., driving), intermediate vision correction (e.g., working on computer), and near vision correction (e.g., reading books or newspapers). The intermediate vision zone is located between the distant vision zone and the near vision zone. The intermediate vision zone provides intermediate vision correction and has an area that is sufficient to overlay a substantial portion of the pupil and disposed in a position within the optical zone so that the pupil is substantially subtended by the intermediate vision zone when gazing at an intermediate vision point below the substantially horizontal point. Preferably, the intermediate vision zone is a progressive power zone having an optical power that continuously changes from distant vision to near vision.

In another preferred embodiment, at least one of the optical zones of the anterior and posterior surfaces has a top edge, a lower edge, and a cylindrical optical surface, or power, to correct for a wearer's astigmatism.

In another preferred embodiment, the anterior surface further comprises a ridge-off zone extending outwardly from the top edge of the optical zone of the anterior surface, a transition zone, and a lenticular zone. The ridge-off zone extends outwardly from the top edge of the optical zone. The transition zone extends from the lower edge of the optical zone to the upper edge of the ramped ridge zone and provides a smooth transition from the ramped ridge zone to the optical zone. The lenticular zone extends radially outward from the ridge-off zone and the lower ramped edge of the ramped ridge zone, that tapers to a narrow end (edge) where the posterior and anterior surfaces meet each other.

In another preferred embodiment, the entire ramped ridge zone is continuous in first derivative and/or in second derivative.

In another preferred embodiment, the latitudinal ridge in the ramped ridge zone is defined by one or more mathematical functions, preferably a conic or spline-based mathematical

function, or is made of several different surface patches, and has a non-uniformly varying elevation profile. For example, the elevation heights at both ends of the latitudinal ridge are higher than the elevation heights in the middle of the latitudinal ridge. More preferably, the latitudinal ridge has a mirror symmetry with respect to a plan which cut the latitudinal ridge in the middle into two equal parts and contains the central axis of the contact lens. Such latitudinal ridge may provide increased wearer's comfort since the stress on the lower eyelid may be more uniformly distributed to the lens-interacting portion of the eyelid during lens translation.

The invention, in another aspect, provides a method for producing a translating contact lens. The method comprises the steps of shaping a contact lens by a manufacturing means to have a central axis, an anterior surface and an opposite posterior surface, wherein the posterior surface has an optical zone, wherein the anterior surface includes an optical zone and a ramped ridge zone capable of controlling contact lens position on an eye in primary gaze and/or translating amount across the eye when the eye changes from gazing at an object at a distance to gazing at an object at an intermediate distance or at a nearby object. The ramped ridge zone is disposed below the optical zone and includes an upper edge, a lower ramped edge, a latitudinal ridge that extends outwardly from the anterior surface, and a ramp that extends downwardly from the lower ramped edge and has a curvature or slope that provides a varying degree of interaction between the ramped ridge zone and the lower eyelid depending on where the lower eyelid strikes the ramped ridge zone. The lower eyelid of the eye is engaged with at least some portion of the ramped ridge zone at all times.

These and other aspects of the invention will become further apparent from the following detailed description of the presently preferred embodiments, read in conjunction with the accompanying figures. The detailed description and figures are merely illustrative of the invention and do not limit the scope of the invention, which is defined by the appended claims and equivalents thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A is a front elevational view of a preferred embodiment of the invention.

- 6 -

FIG. 1B is a cross-sectional view, exaggerated along the horizontal axis, of the preferred embodiment shown in FIG. 1A, taken along line 1B-1B.

FIG. 1C is a detail view of a portion of FIG. 1B.

FIG. 2 schematically depicts the relationship between the ramp slope and the radius of a blending curve according to a preferred embodiment of the invention.

FIGs. 3A-3E schematically illustrate a translating contact lens having a ramped ridge zone including a flattened lower ramp edge and a flattened latitudinal ridge according to a preferred embodiment of the invention.

FIGs 3F-3J schematically show a translating contact lens having a ramped ridge zone including two bumps at the two ends of a latitudinal ridge according to a preferred embodiment of the invention.

FIG. 4A is a front elevational view of an optical zone having horizontal distance vision and near vision zones.

FIG. 4B is a front elevational view of an optical zone having a non-circular distance vision zone.

FIG. 4C is a front elevational view of an optical zone having circular distance vision and near vision zones.

FIG. 5 is a schematic representation of a optical power profile of an optical zone having progressive optical powers.

Repeat use of reference characters in the present specification and drawings is intended to represent same or analogous features or elements of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference now will be made in detail to the embodiments of the invention. It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope or spirit of the invention. For instance, features illustrated or described as part of one embodiment, can be used on another embodiment to yield a still further embodiment. Thus, it is intended that the present invention cover such modifications and variations as come within the scope of the appended claims and their equivalents. Other objects, features and aspects of the present invention are disclosed in or are obvious from the following detailed description. It is to be understood by one of ordinary skill in the art that the present discussion is a description of exemplary embodiments only, and is not intended as limiting the broader aspects of the present invention.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Generally, the nomenclature used herein and the laboratory procedures are well known and commonly employed in the art. Conventional methods are used for these procedures, such as those provided in the art and various general references. Where a term is provided in the singular, the inventors also contemplate the plural of that term. The nomenclature used herein and the laboratory procedures described below are those well known and commonly employed in the art.

As shown in FIG. 1A and FIG. 1B, a preferred embodiment of the invention is a contact lens **100** having a top **108**, a bottom **109**, a central axis **102**, a posterior surface **104** and an opposite anterior surface **106**. The anterior surface **106** includes an optical zone **110**, a transition zone **140**, a ramped ridge zone **150**, a ridge-off zone **160** and a lenticular zone **170**. The optical zone **110** has a lower edge **114** and includes a distance vision zone **120** and a near vision zone **130**.

The distance vision zone **120** provides distance vision correction for the user. The area of the distance vision zone **120** is sufficient to overlay a substantial portion of a pupil **106a** of a user. The distance vision zone **120** is disposed so that the user's pupil **106a** is substantially

subtended by the distance vision zone **120** when the user is gazing at a substantially horizontal point. Typically, the distance vision zone **120** will be offset from the central axis **102**. But its curvature center is on or very close to the central axis **102**. Preferably, the prism effect caused by the decentralization of the curvature center from the central axis is less or equal to 1 prism diopter. The distance **a** from the center **102** to the bottom of the distance vision zone **120** should be the minimum distance that allows the pupil **106a** to be substantially subtended by the distance vision zone **120** when gazing at the horizon. This may result in the distance vision zone **120** having an oval shape.

The near vision zone **130** is substantially concentric with the central axis **102** and extends radially outward from the distance vision zone **120**. The near vision zone **130** provides near vision correction for the user. The area of the near vision zone **130** is sufficient to overlay a substantial portion of the pupil **106b**. The near vision zone **130** is disposed so that the user's pupil **106b** is substantially subtended by the near vision zone **130** when the user is gazing at a near vision point below the substantially horizontal point (e.g., while reading). Both the distance vision zone **120** and near vision zone **130** could be placed either on the posterior surface **104** or the anterior surface **106** of the lens **100**.

The transition zone **140** provides a smooth transition from the ramped ridge zone **150** to the optical zone **110**. The transition zone **140** extends from the lower edge **114** of the optical zone **110** to the upper edge of the ramped ridge zone **156**.

The lens **100** can also include a ridge-off zone **160**, which extends outwardly from the top edge **112** of the optical zone **110**, the first side edge **152** of the ramped ridge zone **150** and the second side edge **154** of the ramped ridge zone **150**. The ridge-off zone **160** adds lens rotational stability and improves the comfort of the lens **100**. For added comfort and better corneal coverage, the lens **100** may also include a lenticular zone **170**, extending radially outward from the ridge-off zone **160** and the lower ramped edge **158** of the ramped ridge zone **150**, that tapers to a narrow end **172**.

The ramped ridge zone **150** provides vertical translation support for the lens **100**. The ramped ridge zone **150** is disposed below the optical zone **110**. The ramped ridge zone **150** has an upper edge **156**, a lower ramped edge **158**, a first side edge **152**, a second side edge

154, a latitudinal ridge **159** extends outwardly from the anterior surface **106**, and a ramp **180** that extends downwardly from the lower ramped edge to the lenticular zone **170**. When the eye **107** moves in a downward direction, the user's lower eyelid **105** can engage gradually first with the ramp **180**, then the lower ramp edge **158** and finally the latitudinal ridge **159**, thereby allowing translation of the lens **100** across the surface of the eye **107**.

The transition from the lenticular zone **170** to the ramped ridge zone **150** is continuous in first derivative (tangent to each other), preferably continuous in second derivative. The ramp **180** has a curvature or slope that provides a varying degree of interaction between the ramped ridge zone and the lower eyelid depending on where the lower eyelid strikes the ramped ridge zone. With such ramp, the lower eyelid of the eye is engaged with at least some portion of the ramped ridge zone at all times and thereby effect the lens position on the eye in primary gaze (horizontal gaze) and/or lens translating amount across the surface of an eye when the eye changes from the horizontal (primary) gaze (distant vision) to a down gaze (intermediate or near vision).

One advantage of incorporating a ramp in the ramped ridge zone is that it can provide a smooth transition zone for the eyelid to "ramp up" the ridge. This gradual engagement will benefit the wearer by increasing comfort and reducing lens sensation in the eye because the ridge will always be engaged.

Another advantage of incorporating a ramp in the ramped ridge zone is that, since the ramp slope can determine lens position on an eye in primary gaze (horizontal), a lens design for a desired visual performance can be reliably implemented in the production of translating contact lenses.

The ramp can be composed of one or more curved surfaces that ensure a continuous transition (continuous in first or second derivative) from the lenticular zone to the ramp and to the latitudinal ridge. For example, a ramp is composed of a simple curvature as shown in FIG. 2. The slope of a ramp depends on the radius of the curvature. Where a blending curvature has a large radius, ramp is longer and steep. Where a blending curvature has a small radius, the ramp is shorter and flat.

- 10 -

For a bifocal translating contact lens having a design identical with or similar to that shown in FIG. 1A and FIG. 1B, the curvature of a ramp can have a radius of between 0.1 to 1.0 mm, preferably a radius of between 0.2 to 0.6 mm, to provide a desired lens position on the eye in the primary gaze.

In a preferred embodiment of the invention, the entire ramped ridge zone of a translating contact lens of the invention has a continuity in first derivative and/or in second derivative. Such ramped ridge zone can be a continuous surface defined by one or more mathematical functions, preferably by a conic or spline-based mathematical function, or is made of several different surface patches.

“Surface patches” refer to combinations of curvatures and lines that are continuous in first derivative, preferably in second derivative, from each other.

In another preferred embodiment, the lower ramp edge and the latitudinal ridge is morphed into a shape that will both help translation and improve comfort, for example, as shown in FIGs. 3A-3E and FIGs. 3F-3J.

FIGs. 3A-3E illustrate schematically a translating contact lens having preferred ramped ridge zone of the invention including a flattened lower ramp edge and a latitudinal ridge of a preferred ramped ridge zone. This preferred ramped ridge zone of the invention may accommodate better to the lower eyelid of the eye, and may distribute more uniformly translating stress over the entire lens-interacting portion of the lower eyelid. Therefore, with such ramped ridge, a translating contact lens may improve wearer's comfort.

FIGs. 3F-3J show schematically a translating contact lens 300 having a top 308, a bottom 309, a central axis 302, a posterior surface 304 and an opposite anterior surface 306. The anterior surface 306 includes an optical zone 310, a transition zone 340, a ramped ridge zone 350, a ridge-off zone 360 and a lenticular zone 370.

The ramped ridge zone 350 has an upper edge, a lower ramp edge, a latitudinal ridge extends outwardly from the anterior surface 306, and a ramp. The elevation height of the latitudinal ridge are higher at the both ends than in the middle (FIG. 3F-3J). Two bumps (391, 392) forms at the two ends of the latitudinal ridge. The latitudinal ridge has a mirror

symmetry with respect to a plan, which cuts the latitudinal ridge in the middle into two equal part and contains the central axis. Such latitudinal ridge can improve wearer's comfort, since translating stress may be uniformly distributed over the entire lens-interacting portion of the lower eyelid. Such a preferred feature of a ramped ridge zone can be achieved by using a continuous surface defined by a conic or spline-based mathematical function or made of several different surface patches.

As will be readily appreciated by those of skill in the art, many different shapes of vision zones are possible with the present invention. Three illustrative examples of such shapes are shown in FIGS. 4A-4C.

As also will be readily appreciated by those of skill in the art, the above-described bifocal optics can be replaced with a trifocal or a multi-focal optics to make a multi-focal translating contact lens. A "multi-focal translating contact lens" refers to a translating contact lens that comprises bifocal, trifocal or multi-focal optics.

The optical zone of at least one of the anterior and posterior surfaces of a multi-focal translating contact lens can include a distant vision zone, an intermediate vision zone, and a near vision zone, from the top to the bottom of the contact lens. The multi-focal translating contact lens of the invention has a ramped ridge zone of the invention on the lower portion of the anterior surface of the contact lens. The ramped ridge zone interacts with the lower eyelid to influence lens motion relative to the cornea and thereby the translating amount across the surface of the eye. The multi-focal translating contact lens can provide distant vision correction at a primary gaze (e.g. driving), intermediate vision correction at a half-down-gaze (e.g. work on computer) and near vision correction at full-down-gaze (e.g. read books and newspaper).

A preferred embodiment of the optical zone of at least one of the anterior and posterior surfaces of a multi-focal translating contact lens of the invention has a distant vision zone, an intermediate vision zone extending radially outward from the distance vision zone, and a near vision zone extending radially outward from the intermediate vision zone. The distance vision zone provides distance vision correction and having a first area that is sufficient to overlay a substantial portion of the pupil of the eye and disposed in a first position within the optical zone so that the pupil is substantially subtended by the distance vision zone when

gazing at a substantially horizontal point. The intermediate vision zone provides intermediate vision correction and having a second area that is sufficient to overlay a substantial portion of the pupil and disposed in a second position within the optical zone so that the pupil is substantially subtended by the intermediate vision zone when gazing at an intermediate vision point below the substantially horizontal point. The near vision zone provides near vision correction and having a third area that is sufficient to overlay a substantial portion of the pupil and disposed in a third position within the optical zone so that the pupil is substantially subtended by the near vision zone when gazing at a near vision point below the intermediate vision point. When the eye changes position from distance vision (e.g. driving) to an intermediate vision (e.g. working on computer) or to near vision (e.g., reading books or newspapers), the amount of translation across the surface of the eye is controlled by the ramped ridge zone on the lower portion of the anterior surface of the multi-focal translating contact lens.

A preferred embodiment of the intermediate vision zone in a multi-focal translating lens of the invention is a progressive power zone, which has an optical power that continuously changes from the distant vision to the near vision (FIG. 5).

Effective use of a trifocal contact lens or a multi-focal translating contact lens having a progressive power zone requires varying amounts of translation across the surface of the eye when the eye changes from gazing at an object at a distance (primary gaze) to gazing at an object at an intermediate distance (partially-down or half down gaze) or to gazing at a nearby object (fully-down gaze). Such requirement related to varying amounts of translation can be achieved by varying the curvature or slope of the ramp in the ramped ridge zone, since degrees of eyelid interaction depend upon the curvature or slope of the ramp and upon the looseness of the lower eyelid of an eye. A correlation between amounts of translation and the curvature or slope of the ramp for a give individual can be established empirically by a person skilled in the art. Preferably, a correlation between amounts of translation and the curvature or slope of the ramp is derived from population studies.

As will be readily appreciated by those of skill in the art, a ramped ridge zone of the invention can be incorporated in a toric soft contact lens that has a cylindrical optical surface, or power, to correct for the wearer's astigmatism. A toric contact lens requires features that provide a predetermined orientation on the eye. A preferred embodiment of the invention is

to provide a toric soft contact lens, which comprises a posterior surface and an opposite anterior surface. The anterior surface includes an optical zone and a ramped ridge zone on the lower portion of the anterior surface, wherein the first derivative of the anterior surface is continuous from the center to the edge. Preferably, the second derivative of the anterior surface is continuous from the center to the edge.

A translating contact lens of the invention typically would be made from a soft contact lens material, such as a silicon hydro-gel or HEMA. It will be understood that any lens described above comprising any soft contact lens material would fall within the scope of the invention.

A translating contact lenses of the invention may be produced by any convenient means, for example, such as lathing and molding. Preferably, contact lenses are molded from contact lens molds including molding surfaces that replicate the contact lens surfaces when a lens is cast in the molds. For example, an optical cutting tool with a numerically controlled lathe may be used to form a metallic optical tool incorporating the features of the anterior surface of a translating contact lens of the invention. The tool is then used to make anterior surface molds that are then used, in conjunction with posterior surface molds, to form the lens of the invention using a suitable liquid lens-forming material placed between the molds followed by compression and curing of the lens-forming material.

Preferably, a contact lens having complicated surface feature or the optical tool to be used for making the same is fabricated by using a numerically controlled lathe, for example, such as Optoform ultra-precision lathes (models 30, 40, 50 and 80) having Variform piezo-ceramic fast tool servo attachment from Precitech, Inc, according to a method described in co-pending U.S. Patent Application No. , entitled Method for Manufacturing a contact lens, herein incorporated by reference in its entirety.

As an illustrative example, production of a translating contact lens having a ramped ridge zone shown in FIG. 3F is described as follows.

First, an user defines a set of parameters, such as a surface tolerance, a concentricity tolerance, orientation of the lens design, the number of spokes to be generated for each of the anterior and posterior surfaces, creating zero point at 0,0, orientation of Z-axis, and type of lens surface (concave or convex surface) to be converted into a geometry.

A "surface tolerance" refers to the allowed position-deviation of a projected point from an ideal position on a surface of a lens design. The deviation can be in the direction either parallel or perpendicular to the central axis of a lens design.

A "concentricity tolerance" refers to the allowed deviation of a point from a given arc.

A "spoke" refers to a ray radiating outwardly from the central axis and is perpendicular to the central axis.

A "semi-diameter spoke" refers to a line segment from the central axis to the edge of a lens design.

"Evenly-spaced semi-diameter spokes" means that all semi-diameter spokes radiate outwardly from the central axis and separate from each other by one equal angle.

A "point spacing" refers to a distance between two points along the semi-diameter spoke.

Second, an user determines the number of points to be projected onto the a surface of the lens design (for example, the anterior surface) along each of the number of evenly-spaced semi-diameter spokes in a direction parallel to the central axis. A semi-diameter spoke at an azimuthal angle, at which one of the two bumps of the anterior surface is located, is selected as the semi-diameter probing spoke. Evenly-spaced points are projected along the semi-diameter probing spoke, in which each pairs of points are separating by a point spacing of 10 microns. Then, all of the projected points are divided into a series of groups, each group composed of three consecutive points, a first point, a middle point and a third point. Each of the points can belong to either one group or two groups. One group at a time from the central axis to the edge or from the edge to the central axis, the curvature of the surface at the middle point of the group is analyzed by comparing a distance between the middle point and a line linking the first point and the third point of the corresponding group with the predetermined surface tolerance. If the distance between the middle point and the line linking the first and third points of the group is larger than the predetermined surface tolerance, the curvature of the surface at that point is sharp and an additional point is projected between the first and the middle points in that group. The point spacing between the first and additional points is equal to point spacing between the additional and middle points. After adding an additional point, all of the points included the newly added point is regrouped again and the curvature of the surface at the middle point of each of the series of groups is analyzed. Such iterative procedure is repeated until the distance between the

middle point of each of the series of groups and the line linking the first and the third points of corresponding group along the probing spoke is equal to or less than the predetermined surface tolerance. In this way, the number of the points to be projected onto the surface of the lens design along each of the desired number of evenly-spaced semi-diameter spokes and point spacings for a series of pairs of neighboring points are determined.

The above-determined number of points are projected onto the anterior surface of the lens design shown in FIG. 3F along each of 96 semi-diameter spokes. For each of the semi-diameter spokes, a semi-meridian which is continuous in first derivative is generated. The semi-meridian includes a series of arcs and optionally straight lines, wherein each arc is defined by fitting at least three consecutive points into a spherical mathematical function within a desired concentricity tolerance. Each of the straight lines is obtained by connecting at least three consecutive points. Preferably, arc fitting routine is started from the central axis to the edge.

Similarly, conversion of the posterior surface of the lens design shown in FIG. 3F into a geometry can be carried out according to the above described procedure.

After converting the lens design shown in FIG. 3F to a geometry of a contact lens to be produced in a manufacturing system, a mini-file containing both the information for the header and the information about the geometry of the lens is generated. This mini-file also contains a zero semi-meridian that is based on the average height of each of the other meridians at each of radial locations and that gives the Variform a zero position on which it can base its oscillation calculations. In this mini-file, all semi-meridians have the same number of zones. This is accomplished by copying the last zone of a semi-meridian for a number of time to equalize the numbers of zones for all meridians. After the mini-file is complete, it is loaded into an Optoform ultra-precision lathe (models 30, 40, 50 or 80) having Variform piezo-ceramic fast tool servo attachment and run to produce a translating contact lens.

In another embodiment, the present invention provides a method for producing a translating contact lens of the invention. The method comprises the steps of shaping a contact lens by a

manufacturing means to have a central axis, an anterior surface and an opposite posterior surface, wherein the posterior surface has an optical zone, wherein the anterior surface includes an optical zone and a ramped ridge zone capable of controlling contact lens position on an eye in primary gaze and/or translating amount across the eye when the eye changes from gazing at an object at a distance to gazing at an object at an intermediate distance or at a nearby object, wherein the ramped ridge zone is disposed below the optical zone and includes an upper edge, a lower ramped edge, a latitudinal ridge that extends outwardly from the anterior surface, and a ramp that extends downwardly from the lower ramped edge and has a curvature or slope that provides a varying degree of interaction between the ramped ridge zone and the lower eyelid depending on where the lower eyelid strikes the ramped ridge zone. The lower eyelid of the eye is engaged with at least some portion of the ramped ridge zone at all times.

The invention has been described in detail, with particular reference to certain preferred embodiments, in order to enable the reader to practice the invention without undue experimentation. A person having ordinary skill in the art will readily recognize that many of the previous components, compositions, and/or parameters may be varied or modified to a reasonable extent without departing from the scope and spirit of the invention. Furthermore, titles, headings, example materials or the like are provided to enhance the reader's comprehension of this document, and should not be read as limiting the scope of the present invention. Accordingly, the invention is defined by the following claims, and reasonable extensions and equivalents thereof.

What is claimed is:

1. A translating contact lens having a central axis, an anterior surface and an opposite posterior surface having a first optical zone, the anterior surface comprising:
 - a second optical zone having a top edge and a lower edge; and
 - a ramped ridge zone capable of controlling contact lens position on an eye in primary gaze and/or translating amount across the eye when the eye changes from gazing at an object at a distance to gazing at an object at an intermediate distance or to gazing at a nearby object,
 - wherein the ramped ridge zone is disposed below the second optical zone and includes an upper edge, a lower ramped edge, a latitudinal ridge that extends outwardly from the anterior surface, and a ramp that extends downwardly from the lower ramped edge to surrounding surface and has a curvature or slope that provides a varying degree of interaction between the ramped ridge zone and the lower eyelid depending on where the lower eyelid of the eye strikes the ramped ridge zone, and
 - wherein the lower eyelid of the eye is engaged with at least some portion of the ramped ridge zone at all times.
2. A translating contact lens of claim 1, wherein at least one of the first and second optical zones includes:
 - a distance vision zone for distance vision correction, the distance vision zone having a first area that is sufficient to overlay a substantial portion of the pupil of the eye and disposed in a first position within the optical zone so that the pupil is substantially subtended by the distance vision zone when gazing at a substantially horizontal point; and
 - a near vision zone for near vision correction, the near vision zone extending radially outward from the distance vision zone and having a second area that is sufficient to overlay a substantial portion of the pupil and disposed in a second position within the optical zone so that the pupil is substantially subtended by the near vision zone when gazing at a near vision point below the substantially horizontal point.
3. A translating contact lens of claim 2, wherein the anterior surface further comprises:
 - a ridge-off zone extending outwardly from the top edge of the second optical zone;

a transition zone extending from the lower edge of the second optical zone to the upper edge of the ramped ridge zone, wherein the transition zone provides a smooth transition from the ridge zone to the second optical zone; and
a lenticular zone, extending radially outward from the ridge-off zone and the lower ramped edge of the ramped ridge zone, that tapers to a narrow end where the posterior and anterior surfaces meet each other.

4. A translating contact lens of claim 3, wherein the curvature center of the distance vision zone is on or very close to the central axis.
5. A translating contact lens of claim 4, wherein prism effect caused by the deviation of the curvature center of the distance vision zone from the central axis is less or equal to 1 prism diopter.
6. A translating contact lens of claim 3, wherein the distance vision zone has an oval shape.
7. A translating contact lens of claim 3, wherein the ramped ridge zone comprises a first side edge and a second side edge, wherein the ridge-off zone extends outwardly from the top edge of the second optical zone, first side edge of the ramped ridge zone and the second side edge of the ramped ridge zone, and wherein the ridge-off zone has sufficient area so that the ridge-off zone, the second optical zone, the ramped ridge zone and the transition zone cover substantially all of the cornea of the eye.
8. A translating contact lens of claim 7, wherein the ramp is made of a curved surface having a radius of between 0.1 to 1.0 mm.
9. A translating contact lens of claim 8, wherein the radius is between 0.2 to 0.4 mm.
10. A translating contact lens of claim 2, wherein the entire ramped ridge zone is continuous in first derivative and/or in second derivative.
11. A translating contact lens of claim 10, wherein the ramped ridge zone is defined by a spline-based mathematical function or made of several different surface patches.

12. A translating contact lens of claim 2, wherein the anterior surface is continuous in first derivative and/or in second derivative from center to edge.
13. A translating contact lens of claim 2, wherein the latitudinal ridge has a non-uniformly varying elevation profile.
14. A translating contact lens of claim 13, wherein the latitudinal ridge has a mirror symmetry with respect to a plan which cut the latitudinal ridge in the middle into two equal parts and contains the central axis.
15. A translating contact lens of claim 2, wherein the contact lens is a soft contact lens.
16. A translating contact lens of claim 1, wherein at least one of the first and second optical zones includes:
a distance vision zone for distance vision correction, the distance vision zone having a first area that is sufficient to overlay a substantial portion of the pupil of the eye and disposed in a first position within the optical zone so that the pupil is substantially subtended by the distance vision zone when gazing at a substantially horizontal point; an intermediate vision zone for intermediate vision correction, the intermediate vision zone extending radially outward from the distance vision zone and having a second area that is sufficient to overlay a substantial portion of the pupil and disposed in a second position within the optical zone so that the pupil is substantially subtended by the intermediate vision zone when gazing at an intermediate vision point below the substantially horizontal point; and
a near vision zone for near vision correction, the near vision zone extending radially outward from the intermediate vision zone and having a third area that is sufficient to overlay a substantial portion of the pupil and disposed in a third position within the optical zone so that the pupil is substantially subtended by the near vision zone when gazing at a near vision point below the intermediate vision point.
17. A translating contact lens of claim 16, wherein the anterior surface further comprises:
a ridge-off zone extending outwardly from the top edge of the second optical zone;

a transition zone extending from the lower edge of the second optical zone to the upper edge of the ramped ridge zone that provides a smooth transition from the ridge zone to the second optical zone; and
a lenticular zone, extending radially outward from the ridge-off zone and the lower edge of the ridge zone, that tapers to a narrow end where the posterior and anterior surfaces meet each other.

18. A translating contact lens of claim 17, wherein the ramped ridge zone comprises a first side edge and a second side edge, wherein the ridge-off zone extends outwardly from the top edge of the second optical zone, first side edge of the ramped ridge zone and the second side edge of the ramped ridge zone, and wherein the ridge-off zone has sufficient area so that the ridge-off zone, the second optical zone, the ramped ridge zone and the transition zone cover substantially all of the cornea of the eye.
19. A translating contact lens of claim 16, wherein the entire ramped ridge zone is continuous in first derivative and/or in second derivative.
20. A translating contact lens of claim 19, wherein the ramped ridge zone is defined by a spline-based mathematical function or made of several different surface patches.
21. A translating contact lens of claim 16, wherein the anterior surface is continuous in first derivative and/or in second derivative from center to edge.
22. A translating contact lens of claim 16, wherein the latitudinal ridge has a non-uniformly varying elevation profile.
23. A translating contact lens of claim 22, wherein the latitudinal ridge has a mirror symmetry with respect to a plan which cut the latitudinal ridge in the middle into two equal parts and contains the central axis.
24. A translating contact lens of claim 16, wherein the contact lens is a soft contact lens.

25. A translating contact lens of claim 16, wherein the intermediate vision zone is a progressive power zone having an optical power that continuously changes from distant vision to near vision.
26. A translating contact lens of claim 1, wherein at least one of the first and second optical zones includes a cylindrical optical surface to correct astigmatism.
27. A translating contact lens of claim 26, wherein the anterior surface further comprises:
 - a ridge-off zone extending outwardly from the top edge of the second optical zone;
 - a transition zone extending from the lower edge of the second optical zone to the upper edge of the ramped ridge zone that provides a smooth transition from the ridge zone to the second optical zone; and
 - a lenticular zone, extending radially outward from the ridge-off zone and the lower ramped edge of the ramped ridge zone, that tapers to a narrow end where the posterior and anterior surfaces meet each other.
28. A translating contact lens of claim 27, wherein the ramp is made of a curved surface having a radius of between 0.1 to 1.0 mm.
29. A translating contact lens of claim 27, wherein the entire ramped ridge zone is continuous in first derivative and/or in second derivative.
30. A translating contact lens of claim 29, wherein the ramped ridge zone is defined by a spline-based mathematical function or made of several different surface patches.
31. A translating contact lens of claim 27, wherein the anterior surface is continuous in first derivative and/or in second derivative from center to edge.
32. A translating contact lens of claim 27, wherein the latitudinal ridge has a non-uniformly varying elevation profile.
33. A translating contact lens of claim 32, wherein the latitudinal ridge has a mirror symmetry with respect to a plan which cut the latitudinal ridge in the middle into two equal parts and contains the central axis.



34. A translating contact lens of claim 27, wherein the contact lens is a soft contact lens.
35. A translating contact lens of claim 1, wherein at least one of the first and second optical zones includes a first portion for distant vision correction and a second portion beneath the first portion for near vision correction.
36. A translating contact lens of claim 2, wherein the second portion is disposed beneath the central axis.
37. A translating contact lens of claim 35, wherein the anterior surface further comprises:
 - a ridge-off zone extending outwardly from the top edge of the second optical zone;
 - a transition zone extending from the lower edge of the second optical zone to the upper edge of the ramped ridge zone that provides a smooth transition from the ridge zone to the second optical zone; and
 - a lenticular zone, extending radially outward from the ridge-off zone and the lower ramped edge of the ramped ridge zone, that tapers to a narrow end where the posterior and anterior surfaces meet each other.
38. A translating contact lens of claim 37, wherein the entire ramped ridge zone is continuous in first derivative and/or in second derivative.
39. A translating contact lens of claim 38, wherein the ramped ridge zone is defined by a spline-based mathematical function or made of several different surface patches.
40. A translating contact lens of claim 37, wherein the anterior surface is continuous in first derivative and/or in second derivative from center to edge.
41. A translating contact lens of claim 37, wherein the latitudinal ridge has a non-uniformly varying elevation profile.
42. A translating contact lens of claim 41, wherein the latitudinal ridge has a mirror symmetry with respect to a plan which cut the latitudinal ridge in the middle into two equal parts and contains the central axis.

43. A translating contact lens of claim 37, wherein the contact lens is a soft contact lens.
44. A translating contact lens of claim 35, wherein at least one of the first and second optical zones includes a first portion for distant vision correction, a second portion beneath the first portion for intermediate vision correction, and a third portion beneath the second portion for near vision correction.
45. A translating contact lens of claim 44, wherein the second portion has an optical power that continuously changes from distant vision to near vision.
46. A method for producing a translating contact lens, comprising the steps of shaping a contact lens by a manufacturing means to have a central axis, an anterior surface and an opposite posterior surface, wherein the posterior surface has an optical zone, wherein the anterior surface includes an optical zone and a ramped ridge zone capable of controlling contact lens position on an eye in primary gaze and/or translating amount across the eye when the eye changes from gazing at an object at a distance to gazing at an object at an intermediate distance or at a nearby object, wherein the ramped ridge zone is disposed below the optical zone and includes an upper edge, a lower ramped edge, a latitudinal ridge that extends outwardly from the anterior surface, and a ramp that extends downwardly from the lower ramped edge and has a curvature or slope that provides a varying degree of interaction between the ramped ridge zone and the lower eyelid depending on where the lower eyelid strikes the ramped ridge zone.
47. A method of claim 46, wherein the anterior surface is continuous in first derivative and/or in second derivative from center to edge.
48. A method of claim 47, wherein the latitudinal ridge has a non-uniformly varying elevation profile.
49. A method of claim 48, wherein the latitudinal ridge has a mirror symmetry with respect to a plan which cut the latitudinal ridge in the middle into two equal parts and contains the central axis.

- 24 -

50. A method of claim 46, wherein said manufacturing means is a numerically controlled lathe or molds.

1 / 8

**Fig. 1A****Fig. 1B****Fig. 1C**

2 / 8




Fig. 2

Fig. 3A
















Fig. 3B**Fig. 3C****Fig. 3D****Fig. 3E**

Fig. 3F


6 / 8

Fig. 3G***Fig. 3H******Fig. 3I******Fig. 3J***

7 / 8

***Fig. 4A******Fig. 4B******Fig. 4C***

Progressive power profile

**Fig. 5**

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/08058

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G02C7/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G02B G02C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2002/021410 A1 (YE MING ET AL) 21 February 2002 (2002-02-21) the whole document ----	1-50
A	US 5 764 339 A (HORTON JOSEPH A) 9 June 1998 (1998-06-09) column 3, line 55 - line 64 figures ----	1-50
A	US 4 573 775 A (BAYSHORE CHARLES A) 4 March 1986 (1986-03-04) abstract; figures ----	1-50
A	US 4 618 229 A (JACOBSTEIN BENJAMIN L ET AL) 21 October 1986 (1986-10-21) abstract; figures ----	1-50
	-/-	

Further documents are listed in the continuation of box C.

Patent family members are listed in annex.

° Special categories of cited documents :

- °A° document defining the general state of the art which is not considered to be of particular relevance
- °E° earlier document but published on or after the international filing date
- °L° document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- °O° document referring to an oral disclosure, use, exhibition or other means
- °P° document published prior to the international filing date but later than the priority date claimed

- °T° later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- °X° document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- °Y° document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- °&° document member of the same patent family

Date of the actual completion of the international search

24 November 2003

Date of mailing of the international search report

03/12/2003

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Ward, S

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 03/08058

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 874 234 A (WICHTERLE OTTO) 17 October 1989 (1989-10-17) abstract; figures ---	1-50
A	US 6 109 749 A (BERNSTEIN PAUL R) 29 August 2000 (2000-08-29) cited in the application column 3, line 57 - line 67 column 4, line 1 - line 13 figures ---	1-50
A	US 5 071 244 A (ROSS RICHARD M) 10 December 1991 (1991-12-10) cited in the application abstract; figures ---	1-50
A	US 4 618 227 A (BAYSHORE CHARLES A) 21 October 1986 (1986-10-21) cited in the application abstract; figures -----	1-50

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 03/08058

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 2002021410	A1	21-02-2002	AU	8980901 A		25-02-2002
			CA	2418060 A1		21-02-2002
			WO	0214929 A1		21-02-2002
			EP	1311896 A1		21-05-2003
			NO	20030703 A		13-02-2003
US 5764339	A	09-06-1998	AU	4895097 A		24-04-1998
			WO	9814820 A1		09-04-1998
US 4573775	A	04-03-1986	AT	60453 T		15-02-1991
			AU	559190 B2		26-02-1987
			AU	1812983 A		23-02-1984
			BR	8304473 A		27-03-1984
			CA	1228756 A1		03-11-1987
			DE	3382135 D1		28-02-1991
			DK	377383 A , B,		20-02-1984
			EP	0102223 A2		07-03-1984
			ES	282306 U		01-05-1985
			GR	81367 A1		11-12-1984
			IE	56747 B1		04-12-1991
			JP	7044368 U		14-11-1995
			JP	59053812 A		28-03-1984
			MX	157390 A		18-11-1988
			NZ	205166 A		10-09-1986
			ZA	8306111 A		27-03-1985
US 4618229	A	21-10-1986	CA	1251667 A1		28-03-1989
US 4874234	A	17-10-1989	CS	8404634 A1		13-11-1985
			AU	587192 B2		10-08-1989
			AU	4374485 A		02-01-1986
			DE	3521745 A1		19-12-1985
			FR	2566142 A1		20-12-1985
			GB	2160677 A , B		24-12-1985
			JP	61083518 A		28-04-1986
US 6109749	A	29-08-2000	AU	748228 B2		30-05-2002
			AU	1379499 A		24-05-1999
			CA	2309168 A1		14-05-1999
			EP	1029255 A1		23-08-2000
			JP	2001522065 T		13-11-2001
			WO	9923527 A1		14-05-1999
US 5071244	A	10-12-1991		NONE		
US 4618227	A	21-10-1986		NONE		