



(43) International Publication Date
8 September 2017 (08.09.2017)

(51) International Patent Classification:

B07B 7/02 (2006.01) *B02C 23/32* (2006.01)
B02C 23/12 (2006.01) *B02C 15/00* (2006.01)

(21) International Application Number:

PCT/EP2017/054658

(22) International Filing Date:

28 February 2017 (28.02.2017)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15/055,981 29 February 2016 (29.02.2016) US

(71) Applicant: **GENERAL ELECTRIC TECHNOLOGY GMBH** [CH/CH]; Brown Boveri Strasse 7, CH-5400 Baden (CH).

(72) Inventors: **BIANCA, Joseph David**; 58 Gilbert Road, Southampton, Massachusetts 01073 (US). **CHAPMAN, Paul John**; 50 Somerset Drive, Windsor, Connecticut 06095 (US).

(74) Agent: **FOSTER, Christopher Michael**; General Electric Technology GmbH, Global Patent Operation - Europe, Brown Boveri Strasse 7, CH-5400 Baden (CH).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,

[Continued on next page]

(54) Title: SYSTEM, METHOD AND APPARATUS FOR CONTROLLING THE FLOW DISTRIBUTION OF SOLID PARTICLES




FIG. 4

(57) Abstract: A turret includes a generally frusto-conical shaped body and a plurality of static straightening vanes arranged interior to the body, the vanes dividing the body into a plurality of substantially equal sections. The vanes are configured to straighten a swirling flow of solid particles as they enter the body, and to divide the swirling flow into a plurality of straightened flows that are communicated to a plurality of coal outlet pipes.



LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, **Published:**

SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, — *with international search report (Art. 21(3))*
GW, KM, ML, MR, NE, SN, TD, TG).

SYSTEM, METHOD AND APPARATUS FOR CONTROLLING THE FLOW DISTRIBUTION OF SOLID PARTICLES

CROSS REFERENCE TO RELATED APPLICATION

This application claims the priority benefit of U.S. Application No. 15/055981, the entire contents of which are incorporated herein by reference.

BACKGROUND

TECHNICAL FIELD

[0001] Embodiments of the invention relate to pulverized coal boilers and, more particularly, to a system, method and apparatus for controlling the flow distribution of coal between outlet pipes of a pulverizer.

DISCUSSION OF ART

[0002] Coal fired boilers utilize pulverizers to grind coal to a desired fineness so that it may be used as fuel for burners. In a typical pulverized coal boiler, coal particulate and primary air flow from the pulverizers to the burners through an array of coal pipes leading from the pulverizers to the burners. Typically, raw coal is fed through a central coal inlet at the top of the pulverizer and falls by gravity to the grinding area at the base of the mill. Once ground using one or more of a variety of known methods, the pulverized coal is transported upwards using air as the transport medium. The pulverized coal passes through classifier vanes within the pulverizer. These classifier vanes may vary in structure, but are intended to establish a swirling flow within the classifier and rejects cone to prevent coarse coal particles from flowing into the discharge turret of the pulverizer. The centrifugal force field set up in the rejects cone forces the coarse coal particles to drop back down onto the grinding surface to be reground until the desired fineness is met. Once the coal is ground finely enough, it is discharged from the pulverizer and distributed among multiple pulverized coal outlet pipes and into respective fuel conduits where it is carried to the burners.

[0003] With reference to FIG. 1, in a conventional coal pulverizer 10, raw coal is fed into a coal inlet pipe and by force of gravity falls through a centrally located coal chute 12 until it reaches a grinding platform 14 where a grinding mechanism 16 grinds the coal into fine pieces. Air flows into an air inlet port 18, feeding primary air into the pulverizer 10. This creates a

stream of air that carries the particles of pulverized coal upward from the grinding platform 14 where they enter classifier vanes 20 of a classifier 22 that establish a swirling flow within the classifier reject cone 24. The centrifugal force set up in the reject cone 24 prevents coarse pieces of coal from entering the discharge turret 26, as discussed above. The coarse pieces of coal fall by force of gravity back into the grinding platform 14, to be reground by the grinding mechanism 16 until they reach a desired degree of fineness. The pulverized coal that is not too coarse, however, is directed by the swirling flow of air upwards through a deflector ring 28 of the classifier 22, and into the discharge turret 26 located above the deflector ring 28. Once the pulverized coal enters the discharge turret 26 it is distributed between the multiple pulverized coal outlet pipes 30 (FIG. 1 shows seven pulverized coal outlet pipes at the top of the turret 26). The pulverized coal is then carried by connected fuel conduits (not shown) to a boiler where it is burned as fuel.

[0004] While the swirling flow of pulverized coal is efficient in preventing coarse coal particles from being carried upward to the coal pipes, such swirling flow has also been known to create an imbalance in coal flow distribution between the coal pipes 30. As illustrated by the particle tracking diagrams of FIGS. 2-4, the swirling flow created in the classifier 22 also extends into the deflector ring 28 and the turret 26, leading to an imbalanced distribution of coal between the various pipes 30. In particular, as shown in FIGS. 2 and 3, the trajectory 32 of coal particles within the deflector ring 38 has a substantially horizontal component, and only a slight vertical component. The same is true for the trajectory 34 of coal particles within the turret 26. This has been shown to lead to a greater distribution of coal into some of the pipes as compared to others (see, e.g., FIG. 3, where the coal pipe at the bottom right receives a lesser flow of coal particles as compared to the others).

[0005] This unbalanced distribution of coal among the coal outlet pipes can adversely affect the performance of each burner and the boiler as a whole and can lead to decreased combustion efficiency, increased potential for tube fouling, furnace slagging, and non-uniform heat release within the combustion chamber. In addition, unbalanced distribution of coal can also result in the inability to control individual burner stoichiometry (i.e., the air-to-coal ratio), which can lead to elevated emissions of nitric oxides, carbon monoxide and the like.

[0006] In view of the above, there is a need for a system and method for ensuring a more uniform distribution of coal between the various outlet pipes of a pulverizer in order to improve overall system efficiency and performance.

BRIEF DESCRIPTION

[0007] In an embodiment, a turret is provided. The turret includes a generally frusto-conical shaped body and a plurality of static straightening vanes arranged interior to the body, the vanes dividing the body into a plurality of sections. The vanes are configured to straighten a swirling flow of solid particles as they enter the body, and to divide the swirling flow into a plurality of straightened flows that are communicated to a plurality of coal outlet pipes.

[0008] In another embodiment, a method for controlling the output of coal in a plurality of coal outlet pipes in a coal pulverizer is provided. The method includes the steps of modifying, or retrofitting, a portion of a coal pulverizer with a turret, the turret comprising a generally frusto-conical shaped body and a plurality of static straightening vanes arranged interior to the body, the vanes dividing the body into a plurality of sections.

[0009] In yet another embodiment, a coal pulverizer is provide. The pulverizer includes a grinding mechanism configured to transform raw coal into pulverized coal, a classifier configured to receive the pulverized coal from the grinding platform and to generate a swirling flow of coal, the classifier being further configured to reject coarse particles of the pulverized coal from the swirling flow, a turret arranged generally above the classifier, the turret having a generally frusto-conical body and a plurality of static straightening vanes arranged interior to the body, the straightening vanes dividing the body into a plurality of sections, and a plurality of coal outlet pipes in fluid communication with the interior of the turret. The straightening vanes within the turret are configured to straighten the swirling flow of coal as it enters the turret, and to divide the swirling flow into a plurality of straightened flows that are communicated to the coal outlet pipes.

DRAWINGS

[00010] The present invention will be better understood from reading the following description of non-limiting embodiments, with reference to the attached drawings, wherein below:

[00011] FIG. 1 is a perspective view of a coal pulverizer or mill of the prior art.

[00012] FIG. 2 is a detail, perspective view of an upper portion of the coal pulverizer of FIG. 1, showing the travel of coal particles.

[00013] FIG. 3 is a detail, perspective view of a classifier and turret of the coal pulverizer of FIG. 1, showing the travel of coal particles within the classifier, turret and outlet pipes.

[00014] FIG. 4 is a perspective view of a coal pulverizer or mill according to an embodiment of the invention.

[00015] FIG. 5 is a detail, perspective view of a turret section of the coal pulverizer of FIG. 4.

[00016] FIG. 6 is a detail, perspective view of an upper portion of the coal pulverizer of FIG. 4, showing the travel of coal particles within the turret.

[00017] FIG. 7 is another detail, perspective view of an upper portion of the coal pulverizer of FIG. 4, showing the travel of coal particles within the turret and outlet pipes.

DETAILED DESCRIPTION

[00018] Reference will be made below in detail to exemplary embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference characters used throughout the drawings refer to the same or like parts. While embodiments of the invention are directed to systems and methods for controlling the flow distribution of pulverized coal in a pulverizer and, in particular, for controlling the flow distribution of coal to burner coal pipes on front and rear fired boilers, embodiments of the invention may be also applicable to controlling the flow distribution of coal to burner coal pipes on any type of boiler, and to controlling the flow of solid particles, generally.

[00019] As used herein, "operatively coupled" refers to a connection, which may be direct or indirect. The connection is not necessarily being a mechanical attachment. As used herein, "fluidly coupled" or "fluid communication" refers to an arrangement of two or more features such that the features are connected in such a way as to permit the flow of fluid between the features and permits fluid transfer.

[00020] Embodiments of the invention relate to a system and method for controlling the flow distribution of solid particles, namely coal, in a pulverizer or mill for a coal fired boiler. As illustrated in FIG. 4, a pulverizer 100 according to an embodiment of the present invention is generally similar in configuration to pulverizer 10 described above, where like reference numerals designate like parts. The pulverizer 100 includes a coal chute 12 configured to receive a supply of raw coal and to feed the coal, by force of gravity, to a grinding platform or table 14. At the grinding platform 14, a grinding mechanism 16 of any known type and configuration is

operable to grind the raw coal into fine particles. Arranged above the grinding platform 14 is a classifier 22 having a plurality of vanes 20 arranged in an annular ring above a reject cone 24. As illustrated in FIG. 4, the classifier 22 also includes a deflector ring 28 defining an annular or cylindrical body concentrically arranged within the annular ring of vanes 20 and through which the coal chute 12 extends. A turret 26 is fluidly coupled to the classifier 22 (through the passageway defined by the deflector ring 28) and is positioned thereabove. The turret 26 defines a generally conical shaped or frusto-conical shaped body having a plurality of outlets 36 at the top thereof. The outlets 36 are in fluid communication with a corresponding number of outlet pipes, such as coal outlet pipes 30, that lead to fuel conduits (not shown) configured to carry pulverized coal to the burners of the boilers for combustion. The coal chute 12 extends through the turret 26 to allow raw coal to pass therethrough to the grinding platform 14.

[00021] In an embodiment, the classifier 22 is a static classifier. In other embodiments, the classifier 22 may be a dynamic classifier. In an embodiment, the vanes 20 of the classifier 22 may be selectively adjustable in order to control the relative fineness or coarseness of coal particles according to system operating parameters. For example, one or more of the vanes 20 may be pivotable about a vertical axis.

[00022] As illustrated in FIGS. 4 and 5, the turret 26 includes a plurality of flow straightening vanes 110 arranged therein that divide the interior of the turret 26 into a plurality of sections of equal size. The vanes 110 extend radially outward from a peripheral surface of the coal chute 12 to the interior walls of the turret 26, and have a height that is substantially equal to a height of the deflector ring turret 26. As illustrated, the outer edge of each vane 110 is tapered so as to mate with the tapered sidewalls of the turret 26. In an embodiment, the height of each of the vanes 110 is approximately 25% of the turret height.

[00023] In an embodiment, the vanes 110 are static vanes, meaning that they are in fixed position within the turret 26 and unable to rotate about any axis. In an embodiment, the number of vanes 110 and sections defined by the vanes 110 corresponds to the number of outlets 36 and coal pipes 30 fluidly coupled to the turret 26. For example, as illustrated in FIG. 4 and 5, the turret 26 may include seven straightening vanes 110 that divide the interior of the turret 26 into seven frusto-conical, wedge-shaped sections corresponding to the seven outlets 36 in the turret 26. While seven vanes 110 are illustrated in FIG. 4, it is envisioned that the number of vanes 110 (and thus sections) within the turret 26 will be dictated by the number of outlets 36 in the turret 26, which may vary between applications or installations.

[00024] In operation, raw coal is fed into the coal inlet pipe and by force of gravity falls through the centrally located coal chute 12 until it reaches the grinding platform 14 where the grinding mechanism 16 grinds the coal into fine pieces. Air flows into an air inlet port (not shown) below the grinding platform 14, feeding primary air into the pulverizer 100. This creates a stream of low-velocity air that carries the particles of pulverized coal upward from the grinding platform 14 where they enter the classifier vanes 20 of the classifier 22. These vanes 20 establish a swirling flow within the reject cone 24. The centrifugal force field set up in the classifier and reject cone 24 prevents coarse pieces of coal from entering the discharge turret 26. In particular, coarse pieces of coal fall by force of gravity back into the grinding platform 14, to be reground by the grinding mechanism 16 until they reach a desired degree of fineness. The pulverized coal that is not too coarse, however, is carried by the swirling flow of air upwards through the deflector ring 28 of the classifier 22 and into the turret 26. In particular, the pulverized coal that is not rejected passes upwards into the sections of the turret 26 defined by the vanes 110, and into the coal outlet pipes 30 associated with each section. The pulverized coal may then be fed to one or more burners where it is combusted.

[00025] As best shown in FIGS. 6 and 7, the vanes 110 within the turret 26 function to uniformly divide or partition the swirling flow of coal into a plurality of equal flows (e.g., coal flows 120) within each section, and to somewhat straighten the flow of coal through the turret 26 and into the respective coal outlet pipes 30. In particular, the vanes 110 serve to transition the swirling flow within the reject cone 24 and classifier 22 (having a substantially horizontal trajectory in many cases) into substantially vertical flows 120 within the sections of the turret 26 defined by the vanes 110 that then enter the coal pipes 30, as best shown in FIG. 7. This straightening of the coal flow (i.e., bringing it back within a controllable and predictable range) and the even distribution of the flow to the outlets 36 via use of static vanes 110 within the turret 26 (see FIGS. 6 and 7) is an improvement over the prior art, where flow control of the pulverized coal has proven difficult because of the swirling within the deflector ring and turret, and which has heretofore contributed to an imbalance between the respective coal pipes 30 (see FIGS. 2 and 3).

[00026] In an embodiment, the use of static flow straightening vanes 110 within the turret 26 may improve pipe-to-pipe coal flow balance to approximately +/- 10% or better, as compared to a pipe-to-pipe imbalance of over 30% in some cases with existing systems. As indicated above, by uniformly distributing the flow of coal among each of outlets 36 in the turret 26

utilizing static, tapered flow straightening vanes 110 within the turret 26, fouling and slagging may be minimized, combustion efficiency increased and emissions decreased, which leads to improved boiler efficiency and better overall performance as compared to existing systems.

[00027] Referring back to FIG. 5, in an embodiment, the vanes 110 may each include a plurality of sections that are selectively retractable and extendable in a vertical direction, which allows the total height of the vane(s) 110 to be adjusted (the vanes 110 are all fixed in the horizontal direction and are not pivotable about a vertical axis or horizontal axis). For example, as illustrated in FIG. 5, each vane 110 may include four sections including a first section 112, a second section 114, a third section 116 and a fourth section 118. While four sections are illustrated, the vanes 110 may have more or fewer than four sections without departing from the broader aspects of the present invention. The sections 112, 114, 116, 118 are operatively connected to one another and are slidable relative to one another such that a total height of each vane 110 may be selectively adjusted. For example, in an embodiment, each of the vanes 110 may include a mechanism that allows for adjustment of the vertical height of each of the vanes 110. The mechanism may include a plurality of linkages (not shown), a linear screw (not shown), a rack and pinion, and/or other mechanism or device that allow one or more of the sections 112, 114, 116, 118 to be moved vertically with respect to at least one other section 112, 114, 116, 118 in order to selectively decrease or increase the height of the vane 110. In an embodiment the height is adjustable between a minimum height, corresponding to a height of the tallest section, and a maximum height, corresponding approximately to the combined height of each of the sections 112, 114, 116, 118. As indicated above, in an embodiment, the maximum height is approximately 25% of the turret height.

[00028] This ability to adjust the vertical height of each of the vanes 110 by extending or retracting the sections 112, 114, 116, 118 allows for additional control of the flow distribution of coal in the event that flow distribution between the coal pipes is still not uniform due to, for example, other variables within the system downstream from the pulverizer (such as, for example, differences in pipe lengths and numbers and types of elbows in each fuel line). In particular, in certain instances, even with the flow straightening vanes 110, downstream configurations and conditions may result in certain pressure imbalances between the coal pipes, which can lead to some remaining coal flow imbalance. The height of one or more of the vanes 110, however, may be adjusted in order to compensate for or remedy this imbalance. In an embodiment, the height of one or more of the vanes 110 may be adjusted in dependence upon a

measured flow of coal within a coal outlet pipe or fuel line or in dependence upon, for example, measured emissions of a respective burner or boiler.

[00029] In an embodiment, the pulverizer 100 may be manufactured with the turret 26 having the vanes 110 installed therein. In other embodiments, the turret 26 having vanes 110 may be manufactured as a separate component that may be retrofit into existing pulverizers. In yet other embodiments, existing pulverizers, and turrets thereof, may be retrofit with static flow straightening vanes 110 for improving the flow distribution of coal to the outlet pipes connected thereto. In this respect, the invention can be integrated into new power plant installations, as well as retrofit into the pulverizers of existing power generation systems. As a result, improved boiler efficiencies and decreased emissions may be realized, regardless of whether a new plant is being brought online, or an existing plant updated or upgraded.

[00030] In an embodiment, a turret is provided. The turret includes a generally frusto-conical shaped body and a plurality of static straightening vanes arranged interior to the body, the vanes dividing the body into a plurality of substantially equal sections. The vanes are configured to straighten a swirling flow of solid particles as they enter the body, and to divide the swirling flow into a plurality of straightened flows that are communicated to a plurality of coal outlet pipes. In an embodiment, the number of straightening vanes is equal to the number of coal outlet pipes in the pulverizer. In an embodiment, each of the straightening vanes is selectively extendable and retractable in a vertical direction for adjusting a height of each of the vanes. In an embodiment, the height of each straightening vane is designed to be individually adjusted. In an embodiment, each of the straightening vanes includes four segments. In an extended position the height of a respective vane is substantially equal to a combined height of the four segments. In a retracted position the height of a respective vane is substantially equal to a height of a single segment. In an embodiment, a feed pipe extends through the body, the feed pipe and the body being substantially concentric, wherein each of the straightening vanes extends radially from the feed pipe to an inner peripheral wall of the body. In an embodiment, the plurality of straightening vanes is seven straightening vanes. In an embodiment, the solid particles are pulverized coal particles.

[00031] In another embodiment, a method for controlling the output of coal in a plurality of coal outlet pipes in a coal pulverizer is provided. The method includes the steps of modifying, or retrofitting, a portion of a coal pulverizer with a turret, the turret comprising a generally frusto-conical shaped body and a plurality of static straightening vanes arranged interior to the

body, the vanes dividing the body into a plurality of substantially equal sections. In an embodiment, the turret is positioned in an upper portion of the pulverizer above a classifier of the pulverizer and is in fluid communication with the classifier. In an embodiment, the method may also include the steps of, within the classifier of the pulverizer, generating a swirling flow of coal, within the turret, dividing the swirling flow of coal into a plurality of flows equal in number to the number of sections within the turret, and, within each of the sections of the turret, straightening the flows of coal. In an embodiment, the method may also include transporting the plurality of flows of coal into the plurality of coal outlet pipes associated with each of the section, wherein the plurality of flows of coal are generally vertical through the turret. In an embodiment, the number of straightening vanes is equal to the number of coal outlet pipes in the pulverizer. In an embodiment, the method may also include the step of adjusting a height of at least one of the straightening vanes in dependence upon a detected coal flow imbalance between the coal outlet pipes. In an embodiment, each of the straightening vanes includes four segments. In an extended position the height of a respective vane is substantially equal to a combined height of the four segments. In a retracted position the height of a respective vane is substantially equal to a height of a single segment. In an embodiment, a feed pipe extends through the turret, the feed pipe and the body of the turret being substantially concentric, wherein each of the straightening vanes extends radially from the feed pipe to an inner peripheral wall of the turret.

[00032] In yet another embodiment, a coal pulverizer is provide. The pulverizer includes a grinding mechanism configured to transform raw coal into pulverized coal, a classifier configured to receive the pulverized coal from the grinding platform and to generate a swirling flow of coal, the classifier being further configured to reject coarse particles of the pulverized coal from the swirling flow, a turret arranged generally above the classifier, the turret having a generally frusto-conical body and a plurality of static straightening vanes arranged interior to the body, the straightening vanes dividing the body into a plurality of substantially equal sections, and a plurality of coal outlet pipes in fluid communication with the interior of the turret. The straightening vanes within the turret are configured to straighten the swirling flow of coal as it enters the turret, and to divide the swirling flow into a plurality of straightened flows that are communicated to the coal outlet pipes. In an embodiment, the classifier includes a reject cone that is configured to receive the coarse particles rejected by the classifier and to transport the rejected coal particles to a grinding platform of the pulverizer. In an embodiment, each of the

straightening vanes is selectively extendable and retractable in a vertical direction for adjusting a height of each of the straightening vanes. In an embodiment, each of the straightening vanes includes four segments. In an extended position the height of a respective straightening vane is substantially equal to a combined height of the four segments. In a retracted position the height of a respective straightening vane is substantially equal to a height of a single segment.

[00033] It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-described embodiments (and/or aspects thereof) may be used in combination with each other. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from its scope. While the dimensions and types of materials described herein are intended to define the parameters of the invention, they are by no means limiting and are exemplary embodiments. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are used as the plain-English equivalents of the respective terms “comprising” and “wherein.” Moreover, in the following claims, terms such as “first,” “second,” “third,” “upper,” “lower,” “bottom,” “top,” etc. are used merely as labels, and are not intended to impose numerical or positional requirements on their objects. Further, the limitations of the following claims are not written in means-plus-function format and are not intended to be interpreted based on 35 U.S.C. § 112, sixth paragraph, unless and until such claim limitations expressly use the phrase “means for” followed by a statement of function void of further structure.

[00034] This written description uses examples to disclose several embodiments of the invention, including the best mode, and also to enable one of ordinary skill in the art to practice the embodiments of invention, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the invention is defined by the claims, and may include other examples that occur to one of ordinary skill in the art. Such other examples are intended to be within the scope of the claims if they have structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

[00035] As used herein, an element or step recited in the singular and proceeded with the word “a” or “an” should be understood as not excluding plural of said elements or steps, unless

such exclusion is explicitly stated. Furthermore, references to “one embodiment” of the present invention are not intended to be interpreted as excluding the existence of additional embodiments that also incorporate the recited features. Moreover, unless explicitly stated to the contrary, embodiments “comprising,” “including,” or “having” an element or a plurality of elements having a particular property may include additional such elements not having that property.

[00036] Since certain changes may be made in the above-described system and method without departing from the spirit and scope of the invention herein involved, it is intended that all of the subject matter of the above description or shown in the accompanying drawings shall be interpreted merely as examples illustrating the inventive concept herein and shall not be construed as limiting the invention.

WHAT IS CLAIMED IS:

1. A turret for a pulverizer, comprising:
a generally frusto-conical shaped body; and
a plurality of static straightening vanes arranged interior to the body, the vanes dividing the body into a plurality of sections;
wherein the vanes are configured to straighten a swirling flow of solid particles as they enter the body, and to divide the swirling flow into a plurality of straightened flows that are communicated to a plurality of coal outlet pipes.
2. The turret of claim 1, wherein:
the number of straightening vanes is equal to the number of coal outlet pipes in the pulverizer.
3. The turret of claim 1 or 2, wherein:
each of the straightening vanes is selectively extendable and retractable in a vertical direction for adjusting a height of each of the vanes.
4. The turret of any one of claims 1 to 3, wherein:
the height of each straightening vane is designed to be individually adjusted.
5. The turret of any one of claims 1 to 4, wherein:
each of the straightening vanes includes four segments;
wherein in an extended position the height of a respective vane is substantially equal to a combined height of the four segments; and
wherein in a retracted position the height of a respective vane is substantially equal to a height of a single segment.
6. The turret of any one of claims 1 to 5, wherein:
a feed pipe extends through the body, the feed pipe and the body being substantially concentric;

wherein each of the straightening vanes extends radially from the feed pipe to an inner peripheral wall of the body.

7. The turret of any one of claims 1 to 6, wherein:
the plurality of straightening vanes is seven straightening vanes.
8. The turret of any one of claims 1 to 7, wherein:
the solid particles are pulverized coal particles.
9. A method for controlling the output of coal in a plurality of coal outlet pipes in a coal pulverizer, the method comprising the steps of:
modifying, or retrofitting, a portion of a coal pulverizer with a turret, the turret comprising:
a generally frusto-conical shaped body; and
a plurality of static straightening vanes arranged interior to the body, the vanes dividing the body into a plurality of sections.
10. The method according to claim 9, wherein:
the turret is positioned in an upper portion of the pulverizer above a classifier of the pulverizer and is in fluid communication with the classifier.
11. The method according to claim 10, further comprising the steps of:
within the classifier of the pulverizer, generating a swirling flow of coal;
within the turret, dividing the swirling flow of coal into a plurality of flows equal in number to the number of sections within the turret; and
within each of the sections of the turret, straightening the flows of coal.
12. The method according to claim 11, further comprising the step of:
transporting the plurality of flows of coal into the plurality of coal outlet pipes associated with each of the section;
wherein the plurality of flows of coal are generally vertical through the turret.

13. The method according to any one of claims 9 to 12, wherein:
the number of straightening vanes is equal to the number of coal outlet pipes in the pulverizer.
14. The method according to any one of claims 9 to 13, further comprising the step of:
adjusting a height of at least one of the straightening vanes in dependence upon a detected coal flow imbalance between the coal outlet pipes.
15. The method according to any one of claims 9 to 14, wherein:
each of the straightening vanes includes four segments;
wherein in an extended position the height of a respective vane is substantially equal to a combined height of the four segments; and
wherein in a retracted position the height of a respective vane is substantially equal to a height of a single segment.
16. The method according to any one of claims 9 to 15, wherein:
a feed pipe extends through the turret, the feed pipe and the body of the turret being substantially concentric; and
wherein each of the straightening vanes extends radially from the feed pipe to an inner peripheral wall of the turret.
17. A coal pulverizer, comprising:
a grinding mechanism configured to transform raw coal into pulverized coal;
a classifier configured to receive the pulverized coal from the grinding platform and to generate a swirling flow of coal, the classifier being further configured to reject coarse particles of the pulverized coal from the swirling flow;
a turret arranged generally above the classifier, the turret having a generally frusto-conical body and a plurality of static straightening vanes arranged interior to the body, the straightening vanes dividing the body into a plurality of sections; and
a plurality of coal outlet pipes in fluid communication with the interior of the turret;

wherein the straightening vanes within the turret are configured to straighten the swirling flow of coal as it enters the turret, and to divide the swirling flow into a plurality of straightened flows that are communicated to the coal outlet pipes.

18. The pulverizer of claim 17, wherein:

the classifier includes a reject cone that is configured to receive the coarse particles rejected by the classifier and to transport the rejected coal particles to a grinding platform of the pulverizer.

19. The pulverizer of claim 17 or 18, wherein:

each of the straightening vanes is selectively extendable and retractable in a vertical direction for adjusting a height of each of the straightening vanes.

20. The classifier of any one of claims 17 to 19, wherein:

each of the straightening vanes includes four segments;

wherein in an extended position the height of a respective straightening vane is substantially equal to a combined height of the four segments; and

wherein in a retracted position the height of a respective straightening vane is substantially equal to a height of a single segment.

1/7




FIG. 1
PRIOR ART

2/7




FIG. 2
PRIOR ART

3/7




FIG. 3
PRIOR ART

4/7




FIG. 4

5/7




FIG. 5

6/7




FIG. 6




FIG. 7

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2017/054658

A. CLASSIFICATION OF SUBJECT MATTER

INV. B07B7/02 B02C23/12 B02C23/32 B02C15/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

F23K B65G B02C B07B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 2 500 647 A2 (BABCOCK POWER SERVICES INC [US]) 19 September 2012 (2012-09-19) paragraphs [0001], [0003], [0024] - [0028]; figures 2-5 -----	1,2, 6-13, 16-19
X	US 2015/056024 A1 (RATH JOHN [US] ET AL) 26 February 2015 (2015-02-26) paragraphs [0019] - [0027]; claims 1,8; figures 1-3 -----	1-20
A	JP S63 271019 A (HITACHI LTD; BABCOCK HITACHI KK) 8 November 1988 (1988-11-08) abstract; figures 1,3,4,13,14,15 -----	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

6 June 2017

Date of mailing of the international search report

20/06/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Iuliano, Emanuela

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2017/054658

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 2500647	A2	19-09-2012	CN	102705856 A		03-10-2012
			EP	2500647 A2		19-09-2012
			JP	6016395 B2		26-10-2016
			JP	2012192404 A		11-10-2012
			US	2012237304 A1		20-09-2012

US 2015056024	A1	26-02-2015	CA	2861833 A1		18-07-2013
			US	2015056024 A1		26-02-2015
			US	2017122558 A1		04-05-2017
			WO	2013106727 A1		18-07-2013

JP S63271019	A	08-11-1988	JP	H0526093 B2		15-04-1993
			JP	S63271019 A		08-11-1988
