



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A61G 7/02	A1	(11) International Publication Number: WO 93/12751 (43) International Publication Date: 8 July 1993 (08.07.93)
--	----	---

(21) International Application Number: PCT/US91/09818


(22) International Filing Date: 27 December 1991 (27.12.91)

(71)(72) Applicant and Inventor: MacSANZ, Jossy [US/US];
6815 1/2 Fishburn Avenue, Bell, CA 90201 (US).(74) Agent: WARE, Paul, H.; 8910 - 2nd Avenue, Inglewood,
CA 90305 (US).(81) Designated States: AT, AU, BB, BG, BR, CH, DE, DK, FI,
GB, HU, JP, KP, KR, LK, LU, MG, MW, NL, NO, RO,
RU, SD, SE, US, European patent (AT, BE, CH, DE,
DK, ES, FR, GB, GR, IT, LU, MC, NL, SE), OAPI pa-
tent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN,
TD, TG).

Published

With international search report.

(54) Title: AUTOMATIC INVALID RELIEF FACILITY



(57) Abstract

The object of the invention is to provide a facility that permits invalids and other movement-restricted persons to independently attend to the business of the elimination of body wastes and without the necessity of being removed from the vehicle of confinement, be it a bed, wheelchair or other structure. The facility has a waste receptacle (48) that may be moved into registry with an annular aperture (20) in a mattress (12) so as to receive body wastes in the receptacle. The facility also has a plug (14) that may be moved into position into said annular aperture for the comfort of the user. Both the mattress and the plug are provided with cleanable, removable covers (15 and 202).

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

Description

Automatic Invalid Relief Facility

Technical Field

This invention relates to automatic facilities for the independent use of invalids and other movement-restricted persons or any other user conventionally needing the assistance of hospital or home-care personnel whenever the person so movement-restricted finds it necessary to answer a call of nature in the elimination of body wastes. In the operation of such facilities, it is essential that the body wastes, of whatever nature, be either automatically removed to sewage outlets as soon as possible after the invalid or other movement-restricted person has made a deposit of such waste matter, or that an attendant be alerted immediately to the need to dispose of such body wastes. It is also important that the process of body waste elimination be carried out cleanly and with a minimum of discomfort to the user.

Background Art

The prior art includes United States Patent number 127,070, to C. G. Kuhn for Improvement in Invalid-Bedsteads, issued May 21, 1872. The device described in the Kuhn patent provides what the specification calls "...a false underbottom ... sufficient to contain and conceal the mechanism of the apparatus." Kuhn further provides an inclined footrest that allows a movable part of the bottom to swing past it into the configuration shown in Figure 1 thereof. Much of the mechanism is employed to manually raise and lower a headboard or back for the user's comfort. The manually operated mechanism

also arranges the positioning of a commode by means of a "vibrating arm" into and out of registry with a commode-opening, which opening is provided with a yielding cushion which acts as a cover to close the commode when it is brought under the cushion.

Another prior art device is described in the United States Patent number 1,100,303, granted to Hooper for Bed Attachment, issued June 16, 1914. The main object is recited to provide "... a device ... which will eliminate the necessity of the patient being removed from the bed during the period of defecation." Hooper provides a carriage on wheels, completely removable from the bed, which carriage carries a chamber-pot, registrable beneath an opening in the mattress and having a sleeve and collar arrangement. The opening may be covered by means of a countersunk handle insertable from above the mattress.

Yet another prior art device has been illustrated in the United States Patent number 1,869,036, granted to Zink and issued July 26, 1932, for Sanitary Bedpan. The primary object recited in the specification is stated "... to provide a bed pan connected with a sewer or standpipe whereby water may be supplied to the bed pan for flushing the same and carrying the waste matter from the pan to the sewer." In this innovation, the bed pan rests on the surface of the bed when in use and swivels outwardly therefrom when not being used.

United States Patent number 2,418,259, granted to Harmanson for Hospital Bed Construction and issued April 1, 1947, describes another prior art device offering relief to invalids and other bedridden persons. The device makes use of bed slats to support a closet bowl that has a flange arranged to rest on the slats. Inlet water is provided from the water supply system of the building for the purpose of flushing and connection

is made to the sewer system for the disposal of waste material.

Patentee St. Jean's United States Patent number
5 4,096,594, for Mattress Device, granted June 27, 1978, while applicable both to a bed and a chair, appears to contemplate relief in no other cases than urination. The "mesh material" supports the weight of the incontinent person and permits "... liquid to flow therethrough."

10

A final prior art patent discovered in applicant's pre-examination novelty search is United States Patent number 4,631,762, and was granted to Fugett on December 30, 1986, for Hospital Bed with Toilet Facility. The
15 patent describes a facility that provides powered means to laterally slide a central mattress section aside and then to raise a waste-receiving receptacle into position for an invalid to use. After use, the system may be flushed and returned to its not-in-use position.

20

These prior art devices are commendable and show a creative spirit for their times. The inventors and their inventions have contributed remarkably to the technology involved. However, these prior art structures do not
25 include those combined elements of the instant invention that provide greater facility of use and ingenious arrangement of components and that make the instant invention the high culmination in the art.

30 **Disclosure of Invention**

In accordance with the instant invention, there is provided a facility by means of which an invalid or other movement-restricted or confined person may independently
35 attend to the necessary elimination of body wastes without leaving the vehicle of confinement whether it be bed, wheel chair or other vehicle. In the

accomplishment of the aims and objects of the invention, a first easily movable embodiment includes a means of detection and provides an alarm signal giving notice that the facility has been used for the deposit of waste matter. The waste matter may then be removed by an attendant upon discovery of the alarm signal. Stained or otherwise soiled covers may be removed for cleaning and replaced with pre-cleaned covers. In another, more elaborate yet non-transportable embodiment, the device is autonomous in providing for the removal of the waste matter through an existing sewer system by means of the cooperation of the elements of the system itself.

Brief Description of Drawings

Further advantages and features of the instant invention will be more fully apparent to those skilled in the art to which the invention pertains from the ensuing detailed description thereof, regarded in conjunction with the accompanying drawings wherein like reference numerals refer to like parts throughout and in which:

Figure 1 is a side elevational view of the invention in its more elaborate form including means for disposal of the deposited waste matter into a sewer, the device being shown in configuration for use to deposit body wastes by an invalid or other movement restricted person.

Figure 2 is a fragmentary, enlarged, cross-sectional view taken along the sight lines 2 - 2 of Figure 1.

Figure 3 is a side elevational view of the invention much like Figure 1 except in the configuration shown, the device is depicted in its normal or not-in-use configuration.

Figure 4 is a side elevational view of the device in its simpler form wherein, after use, provision must be made to indicate that such use has occurred and that attendance is required for the disposal of deposited body wastes.

Figure 5 is an exploded perspective view of the embodiment shown in Figure 4.

Figure 6 shows the simpler embodiment of the invention in its in-use configuration, applied to a wheelchair as the vehicle of confinement of an invalid or other movement-restricted person.

Figure 7 is a fragmentary representation, much like Figure 6, however, shown in the not-in-use configuration.

Figure 8 is a perspective view showing the cover that may be removed for purposes of cleaning and showing the opening intended to communicate with the waste disposal facility.

Figure 9 is an enlarged, detailed view taken along the sight lines 9 - 9 of Figure 8.

Figure 10 is an enlarged, detailed view taken along the sight lines 10 - 10 of Figure 9.

Figure 11 is a fragmentary view of the removable cleanable cover applied to an element of the device.

Best Mode for Carrying Out the Invention

Referring to the drawing and to Figures 1 through 4 with greater particularity, the Automatic Invalid Relief Facility is denoted generally by the numeral 10

and comprises a mattress 12 having a substantially central annular aperture 20 that may be in the form of a modified frustum of a cone. Said modified frustum may be so modified or shaped as to form an elongated, ovate opening having an upper circumferential contour of smaller dimensions than its lower, likewise symmetrically shaped circumferential contour. Said central annular aperture thus forming an opening into which a vertically movable plug 14, which is a solid surface in the form of a like-shaped, modified frustum of a cone, may be inserted, said plug 14 being of such dimensions as to fit snugly into said central annular aperture. The plug 14 may be covered by means of a suitable removable, washable or otherwise cleanable cover 15 having a means of securing that may be simply an elastic band 15' (Figure 11). The plug 14, which may be fabricated of a suitable resilient material, rests on a solid base 22 which in turn is connected to and rests upon a horizontally movable carriage 18 by means of the rod and sleeve 56 and 54 respectively. Rod and sleeve structure 56 and 54 operate to maintain the orientation and the vertical positional integrity of plug 14. The plug base 22 is also attached by way of threaded shaft 37, one end of which is connected to a reversible electric motor 30 mounted within a bracket 34. The other end of said threaded shaft 37 is secured to said plug base 22 by means of a nut 24. Reversible electric motor 30, acting through threaded shaft 37, serves to vertically raise and lower said plug 14 up into and out of positional agreement with said aperture 20. The whole assembly just described is supported upon horizontally movable carriage 18 which is itself supported upon journal rods 62 which move horizontally upon linear bearings 38. Horizontally movable carriage 18 is caused to move horizontally by means of reversible electric motor 26 which drives threaded shaft 36 through nut 32 so as to place waste matter receptacle 48 into and out of horizontal registry

with annular aperture or hole 20. The whole assembly just described, is supported by frame 16. A first limit switch 40 restricts and controls the extent of horizontal travel enjoyed by horizontally movable carriage 18 and arrests its leftward movement at the location of the limit switch as shown in Figures 1, 3 and 4. A second limit switch 28 serves a like purpose to restrict and control the extent of horizontal travel enjoyed by horizontally movable carriage 18 and to arrest its rightward movement at the location of the limit switch, also as shown in Figures 1, 3 and 4. The vertical travel of plug 14 is likewise controlled in extent by limit switches. A third limit switch 46 restricts and controls the extent of vertically upward travel allowed to plug 14, while a fourth limit switch 52 restricts and controls the extent of vertically downward travel of plug 14. Thus first and second limit switches 40 and 28 respectively restrict and control the extent of horizontal travel of horizontally movable carriage 18, while third and fourth limit switches 46 and 52 respectively restrict and control the extent of the vertical travel of plug 14 into and out of annular aperture 20.

Figures 8, 9 and 10 depict a removable, cleanable mattress cover 202 within the general contemplation of a specialized bed sheet or the like, to be applied to the mattress 12. The cover for the mattress 12 is denoted generally by the numeral 200 and comprises a mattress cover 202 having a substantially central opening 204 which may be fashioned by forming a double slit so as to form an "X" in the fabric of the cover thus forming flaps 206, 207, 208 and 209 which may be pulled back so as to create the opening 204. Said opening 204 is designed to permit communication with annular aperture or opening 20 in the mattress 12. Means to secure said flaps 206, 207, 208 and 209 from the opening 204 may be implemented

through the employment of snap fasteners 211, 212, 213 and 214, for example, as illustrated in Figure 9. Means to create the opening as at numeral 204 and to secure the fabric of the mattress cover are deemed to be within the spirit, scope and contemplation of the invention. Reinforcement stitching is denoted generally by the numeral 216. Enlarged detail of the folding back of a representative flap 206 is shown in Figure 10 wherein flap 206 has been shown folded back from opening 204 and fastened underneath mattress cover 202. As portrayed in the Figure, the flap 206 is folded back at the opening 204 and is secured underneath mattress cover 202 by means of the snap fastener system comprising female snap fastener element 12', which is secured to mattress 12, and male snap fastener element 211. Said fastener element 12' being mated with male snap fastener element 211 which is shown secured to flap 206. Reinforcement stitching 216 may be applied to a turn or foldunder 218 in the fabric of mattress cover 202. Such additional reinforcement stitching or other reinforcement measures should be considered to be within the spirit, scope and contemplation of the invention.

In the embodiment of the invention illustrated by Figures 1 and 3, the receptacle 48 is connected to a domestic water supply by means of telescoping water inlet pipe assembly comprising the telescoping pipes 64 and 66 by means of suitable pressure-reducing and flushing valves, not shown because such water supply and flushing arrangements are well known in the art and do not form an inventive part of the instant invention. In like manner, the receptacle 48 has a bottom outlet opening and is connected to telescoping tubes 58 and 60 through a trap 68 and thence to a domestic sewer inlet not shown. As in the water supply arrangement, telescoping tubes for the purpose of sewage disposal are old in the art and are not to be regarded as inventive elements in the instant

invention.

In the embodiment shown in Figures 4 and 5, receptacle 48 is transparent, removable and is carried by receptacle holder 70 upon horizontally movable carriage 18. A photoelectric cell 42 is sensitive to a light 44 and through this sensitivity, causes an alarm signal, not shown because such alarm systems are well known in the art and do not form an inventive part of the instant invention, to become energized and active whenever a deposit has been made in receptacle 48. An electric control cable 50 having a forward/reverse switch is included to indicate that movement within and of the assembly is intended to be within the control of the invalid user. Such user operated control systems are well known and implemented in the prior art. An additional linear bearing 72 is shown in Figure 5 at the opposite end of carriage 18 from linear bearing 38.

Attention is now invited to Figures 6 and 7 showing the Automatic Invalid Relief Facility applied to a wheelchair. The wheelchair is identified generally by the numeral 110 having a back portion 113, a seat portion 112, an inclined leg-rest portion 158 and a foot rest portion 160. The seat portion 112 includes an annular aperture 120 of the same nature as the annular aperture 20 of Figure 1. The same general type of covering is expected to be applied as has been depicted in Figures 8, 9 and 10. An associated plug 114 serves the same purpose, bears the same description and enjoys the same relationship as the plug 14 bears to the aperture 20 in Figure 1. Again, the same general type of covering is expected to be applied as has been depicted in Figure 11. In like manner, the plug 114 is supported by plug base 122 which is supported by a nut 124 attached to threaded shaft 137 which is driven by reversible motor 130 so as to vertically raise and lower said plug 114 within the

constraints imposed by limit switches 146 and 152 and into and out of union with aperture 120. Sleeve and rod assembly comprising sleeve 154 and rod 156 provide vertical positional integrity for the plug and plug base 114 and 122 respectively. The reversible electric motor 130 is maintained in position by bracket 134. A receptacle or pot 148 is positioned by means of a receptacle or pot holder 170 from which the pot 148 can be removed by an attendant when circumstances warrant. A reversible electric motor 126 provides horizontal motion to a movable carriage 118 by driving threaded shaft 136 within the constraints imposed by limit switches 140 and 128 for the purpose of moving the receptacle 148 into and out of registry with aperture 120. A linear bearing 138 provides support and facilitates horizontal movement of the assembly. The supporting wheelchair frame is denoted by the numeral 116. The same photoelectric alarm system as has been described with respect to Figures 4 and 5 is expected to be a part of the system just described.

Industrial Applicability

The present invention finds application wherever invalids and other movement-restricted persons receive care, either from a care provider other than the invalid or where such care is provided independently by the invalid.

Claims

1. An automatic invalid relief facility for the independent use of invalids and other movement-restricted persons and other users, comprising:

a mattress having a central annular aperture;

5 a removable mattress cover having a substantially central opening, said opening adapted to communicate with said annular aperture in said mattress;

a transparent, removable waste receptacle registrable with said central annular aperture for
10 receiving body waste deposits from a user;

a waste receptacle holder for receiving and supporting said waste receptacle;

a vertically movable plug of such dimensions as to be inserted and to fit snugly into said central annular
15 aperture;

a cleanable cover securable over said plug;

a horizontally movable carriage for moving said waste receptacle and said plug into and out of registry with said central annular aperture;

20 horizontal motive means for moving said horizontally movable carriage;

vertical motive means for moving said vertically movable plug into and out of said central annular aperture when said vertically movable plug has been
25 placed in registry therewith by said horizontal motive

means;

sensing and alarm signal means for alerting attendant personnel that a deposit has been made by a user into said body waste receptacle; and

5 user operated control means for operating said motive means.

2. The device of claim 1 in which said horizontal motive means comprises:

journal rods supporting said horizontally movable carriage;

5 linear bearings supporting and retaining said journal rods and providing low-friction travel for said horizontally movable carriage along said journal rods;

10 a first limit switch operable to arrest the horizontal travel of said horizontally movable carriage in one horizontal direction along said journal rods;

a second limit switch operable to arrest the horizontal travel of said horizontally movable carriage in the opposite horizontal direction along said journal rods;

15 a threaded shaft drivingly attached to said horizontally movable carriage;

20 a reversible electric motor for driving said threaded shaft in said one horizontal direction and in said opposite horizontal direction along said journal rods.

3. The device of claim 1 in which said vertical motive means comprises:

a sleeve attached at one end to said vertically movable plug;

5 a rod situated longitudinally within said sleeve and attached at one of its ends to said horizontally movable carriage;

a threaded shaft attached at one end to said vertically movable plug; and

10 a reversible electric motor attached to the other end of said threaded shaft for driving said threaded shaft in one vertical direction and in the opposite vertical direction so as to move said plug in said vertical directions.

4. An automatic invalid relief facility for the independent use of invalids and other movement-restricted persons and other users, comprising:

a mattress having a central annular aperture;

5 a removable mattress cover having a substantially central opening, said opening adapted to communicate with said annular aperture in said mattress;

a waste receptacle having a bottom outlet opening registrable with said central annular aperture for
10 receiving body waste deposits from a user;

water supply means for supplying water from a domestic water system to flush waste from said waste

receptacle through said bottom outlet opening;

15 sewer inlet means communicating with said bottom
outlet opening for receiving said body wastes into a
domestic sewer facility;

a vertically movable plug of such dimensions as to
be inserted and to fit snugly into said central annular
aperture;

20 a cleanable, removaable cover securable over said
plug;

a horizontally movable carriage for moving said
waste receptacle and said plug into and out of registry
with said central annular aperture;

25 horizontal motive means for moving said horizontally
movable carriage;

vertical motive means for moving said vertically
movable plug into and out of said central annular
aperture when said vertically movable plug has been
30 placed in registry therewith by said horizontal motive
means;

user operated control means for operating said
motive means.

5. The device of claim 4 wherein:

said water supply means includes telescoping tubes;

said sewer inlet means includes telescoping tubes;

and in which said horizontal motive means comprises:

15

5 journal rods supporting said horizontally movable carriage;

 linear bearings supporting and retaining said journal rods and providing low-friction travel for said horizontally movable carriage along said journal rods;

10 a first limit switch operable to arrest the horizontal travel of said horizontally movable carriage in one horizontal direction along said journal rods;

 a second limit switch operable to arrest the horizontal travel of said horizontally movable carriage
15 in the opposite horizontal direction along said journal rods;

 a threaded shaft drivingly attached to said horizontally movable carriage; and

 a reversible electric motor for driving said
20 threaded shaft in said one horizontal direction and in said opposite horizontal direction along said journal rods.

6. The device of claim 4 in which said vertical motive means comprises:

 a sleeve attached at one end to said vertically movable plug;

5 a rod situated longitudinally within said sleeve and attached at one of its ends to said horizontally movable carriage;

 a threaded shaft attached at one end to said vertically movable plug; and

10 a reversible electric motor attached to the other end of said threaded shaft for driving said threaded shaft in one vertical direction and in the opposite vertical direction so as to move said plug in said vertical directions.

7. An automatic invalid relief facility applied to a wheelchair for the independent use of invalids and other movement-restricted persons and other users, comprising:

5 a seat portion of said wheelchair having a central annular aperture;

10 a removable cover having a substantially central opening, said opening adapted to communicate with said central annular aperture in said seat portion of said wheelchair;

 a transparent, removable waste receptacle registrable with said central annular aperture for receiving body waste deposits from a user;

15 a waste receptacle holder for receiving and supporting said waste receptacle;

 a vertically movable plug of such dimensions as to be inserted and to fit snugly into said central annular aperture;

20 a cleanable, removable cover securable over said plug;

 a horizontally movable carriage for moving said waste receptacle and said plug into and out of registry with said central annular aperture;

horizontal motive means for moving said horizontally
25 movable carriage;

vertical motive means for moving said vertically
movable plug into and out of said central annular
aperture when said vertically movable plug has been
placed in registry therewith by said horizontal motive
30 means;

sensing and alarm signal means for alerting
attendant personnel that a deposit has been made by a
user into said body waste receptacle; and

user operated control means for operating said
35 motive means.

8. The device of claim 7 in which said horizontal
motive means comprises:

journal rods supporting said horizontally movable
carriage;

5 linear bearings supporting and retaining said
journal rods and providing low-friction travel for said
horizontally movable carriage along said journal rods;

a first limit switch operable to arrest the
horizontal travel of said horizontally movable carriage
10 in one horizontal direction along said journal rods;

a second limit switch operable to arrest the
horizontal travel of said horizontally movable carriage
in the opposite horizontal direction along said journal
rods;

15 a threaded shaft drivingly attached to said
horizontally movable carriage;

20 a reversible electric motor for driving said threaded shaft in said one horizontal direction and in said opposite horizontal direction along said journal rods.

9. The device of claim 7 in which said vertical motive means comprises:

a sleeve attached at one end to said vertically movable plug;

5 a rod situated longitudinally within said sleeve and attached at one of its ends to said horizontally movable carriage;

a threaded shaft attached at one end to said vertically movable plug; and

10 a reversible electric motor attached to the other end of said threaded shaft for driving said threaded shaft in one vertical direction and in the opposite vertical direction so as to move said plug in said vertical directions.

10. An improved automatic invalid relief facility of the type having a mattress, said mattress having a central annular aperture;

5 a waste receptacle registrable with said central annular aperture in said mattress and a waste receptacle holder for receiving and supporting said waste receptacle;

a horizontally movable carriage for moving said waste receptacle horizontally;

10 horizontal motive means for moving said carriage; and user operated control means for operating said horizontal motive means;

wherein the improvement comprises:

15 a removable mattress cover having a substantially
central opening, said opening adapted to communicate with
said annular aperture in said mattress;

a transparent, removable waste receptacle
registrable with said central aperture for removing body
wastes from a user;

20 a vertically movable plug of such dimensions as to
be inserted and to fit snugly into said central annular
aperture;

a cleanable cover securable over said plug;

25 vertical motive means for moving said vertically
movable plug into and out of said central annular
aperture when said vertically movable plug has been
placed in registry therewith by said horizontal motive
means; and

30 sensing and alarm signal means for alerting
attendant personnel that a deposit has been made by a
user into said body waste receptacle.

1/5












Fig. 1.







5/5



INTERNATIONAL SEARCH REPORT

International Application No. PCT/US91/09818

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) *

According to International Patent Classification (IPC) or to both National Classification and IPC
IPC (5): A61G 7/02

II. FIELDS SEARCHED

Minimum Documentation Searched *

Classification System

Classification Symbols

U.S. 5/604,605,463
 297/192
 4/450,465,480,483

Documentation Searched other than Minimum Documentation
 to the extent that such Documents are included in the Fields Searched *

III. DOCUMENTS CONSIDERED TO BE RELEVANT *

Category *	Citation of Document, ** with indication, where appropriate, of the relevant passages **	Relevant to Claim No. **
Y	US, A, 4,571,759 (SASAKI ET AL.) 25 February 1986 See the entire document.	1,4,7,10
Y	US, A, 3,922,735 (KATO) 02 December 1975 See the entire document.	1,3,4,6,7,9,10
Y	US, A, 4,011,610 (PARKER, III) 15 March 1977 Note the mattress cover and plug cover.	1,4,7,10
Y	US, A, 2,591,850 (MITCHELL) 08 April 1952 Note teaching of transparent bedpan.	1,7,10
Y	US, A, 557,614 (SCHMITT) 07 April 1896 Note teaching of equivalent bedpan and plug in wheelchair and bed.	7
Y	US, A, 4,631,762 (FUGETT) 30 December 1986 See Figure 9.	4
Y	US, A, 5,008,964 (DEAN ET AL.) 23 April 1991 See entire document.	1,7,10

* Special categories of cited documents: ¹⁰

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

14 May 1992

Date of Mailing of this International Search Report

11 JUN 1992

International Searching Authority

ISA/US

Signature of Authorized Officer

Michael F. Trettel
 Michael F. Trettel

FURTHER INFORMATION CONTINUED FROM THE SECOND SHEET

A US, A, -2,699,772 (BEEM ET AL.) 18 January 1955

A US, A, 3,943,583 (ISHIKAWA) 16 March 1976

V ☐ OBSERVATIONS WHERE CERTAIN CLAIMS WERE FOUND UNSEARCHABLE¹

This international search report has not been established in respect of certain claims under Article 17(2) (a) for the following reasons:

1. ☐ Claim numbers _____, because they relate to subject matter ¹² not required to be searched by this Authority, namely:
2. ☐ Claim numbers _____, because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out ¹³, specifically:
3. ☐ Claim numbers _____, because they are dependent claims not drafted in accordance with the second and third sentences of PCT Rule 6.4(a).

VI. ☐ OBSERVATIONS WHERE UNITY OF INVENTION IS LACKING²

This International Searching Authority found multiple inventions in this international application as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims of the international application.
2. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims of the international application for which fees were paid, specifically claims:
3. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claim numbers:
4. ☐ As all searchable claims could be searched without effort justifying an additional fee, the International Searching Authority did not invite payment of any additional fee.

Remark on Protest

- ☐ The additional search fees were accompanied by applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.