




US 20130204352A1

(19) **United States**(12) **Patent Application Publication**
BROWN(10) **Pub. No.: US 2013/0204352 A1**(43) **Pub. Date: Aug. 8, 2013**(54) **LONGITUDINALLY FLEXIBLE
EXPANDABLE STENT**(71) Applicant: **Boston Scientific Scimed, Inc.**, Maple
Grove, MN (US)(72) Inventor: **Brian J. BROWN**, Hanover, MN (US)(73) Assignee: **BOSTON SCIENTIFIC SCIMED,
INC.**, Maple Grove, MN (US)(21) Appl. No.: **13/830,723**(22) Filed: **Mar. 14, 2013****Related U.S. Application Data**(63) Continuation of application No. 13/332,283, filed on
Dec. 20, 2011, which is a continuation of application
No. 13/195,581, filed on Aug. 1, 2011, now aban-
doned, which is a continuation of application No.
10/800,572, filed on Mar. 15, 2004, now Pat. No.
8,114,146, which is a continuation of application No.
10/705,273, filed on Nov. 10, 2003, now Pat. No.
7,988,717, said application No. 10/800,572 is a con-tinuation of application No. 09/197,278, filed on Nov.
20, 1998, now Pat. No. 7,204,848, said application No.
10/705,273 is a continuation of application No.
09/197,278, filed on Nov. 20, 1998, now Pat. No.
7,204,848, which is a continuation-in-part of applica-
tion No. 08/511,076, filed on Aug. 3, 1995, now Pat.
No. 6,818,014, which is a continuation-in-part of
application No. 08/396,569, filed on Mar. 1, 1995, now
abandoned.**Publication Classification**(51) **Int. Cl.**
A61F 2/88 (2006.01)(52) **U.S. Cl.**
CPC **A61F 2/88** (2013.01)
USPC **623/1.22**(57) **ABSTRACT**Segmented articulatable stent of open structure comprised of
end-connected struts of first and second lengths making up
first and second segments with angular interconnects between
adjacent first and second segments.




FIG. 1a




FIG. 1b





FIG. 2






FIG. 4a




FIG. 4b




FIG. 5a




FIG. 5b




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15

LONGITUDINALLY FLEXIBLE EXPANDABLE STENT

[0001] This application is a Continuation of application Ser. No. 13/332,283 filed Dec. 20, 2011, which is a Continuation of application Ser. No. 13/195,581 filed Aug. 1, 2011, which is a Continuation of application Ser. No. 10/705,273 filed Nov. 10, 2003, which is a Continuation of Application Ser. No. 09/197,278 filed Nov. 20, 1998, and issued as U.S. Pat. No. 7,204,848 on Apr. 17, 2004, which is a Continuation-in-Part of application Ser. No. 08/511,076 filed Aug. 3, 1995, and issued as U.S. Pat. No. 6,818,014 on Nov. 16, 2004, which is a Continuation-in-Part of application Ser. No. 08/396,569, abandoned, filed Mar. 1, 1995, the disclosures of which are hereby incorporated by reference.

[0002] Further, application Ser. No. 13/195,581 is a Continuation of application Ser. No. 10/800,572 filed Mar. 15, 2004, which is a Continuation of application Ser. No. 09/197,278 filed Nov. 20, 1998, and issued as U.S. Pat. No. 7,204,848 on Apr. 17, 2004, which is a Continuation-in-Part of application Ser. No. 08/511,076 filed Aug. 3, 1995, and issued as U.S. Pat. No. 6,818,014 on Nov. 16, 2004, which is a Continuation-in-Part of application Ser. No. 08/396,569, abandoned, filed Mar. 1, 1995, the disclosures of which are hereby incorporated by reference.

FIELD OF THE INVENTION

[0003] This invention relates to an endoprosthesis device for implantation within a body vessel, typically a blood vessel. More specifically, it relates to a tubular expandable stent of improved longitudinal flexibility.

BACKGROUND OF THE INVENTION

[0004] Stents are placed or implanted within a blood vessel for treating stenoses, strictures or aneurysms therein. They are implanted to reinforce collapsing, partially occluded, weakened, or dilated sections of a blood vessel. They have also been implanted in the urinary tract and in bile ducts.

[0005] Typically, a stent will have an unexpanded (closed) diameter for placement and an expanded (opened) diameter after placement in the vessel or the duct. Some stents are self-expanding and some are expanded mechanically with radial outward force from within the stent, as by inflation of a balloon.

[0006] An example of the latter type is shown in U.S. Pat. No. 4,733,665 to Palmaz, which issued Mar. 29, 1988, and discloses a number of stent configurations for implantation with the aid of a catheter. The catheter includes an arrangement wherein a balloon inside the stent is inflated to expand the stent by plastically deforming it, after positioning it within a blood vessel.

[0007] A type of self-expanding stent is described in U.S. Pat. No. 4,503,569 to Dotter which issued Mar. 12, 1985, and discloses a shape memory stent which expands to an implanted configuration with a change in temperature. Other types of self-expanding stents not made of shape memory material are also known.

[0008] This invention is directed to stents of all these types when configured so as to be longitudinally flexible as described in detail hereinbelow. Flexibility is a desirable feature in a stent so as to conform to bends in a vessel. Such stents are known in the prior art. Examples are shown in U.S. Pat. No. 4,856,516 to Hillstead; U.S. Pat. No. 5,104,404 to Wolff; U.S. Pat. No. 4,994,071 to MacGregor; U.S. Pat. No. 5,102,

417 to Palmaz; U.S. Pat. No. 5,195,984 to Schatz; U.S. Pat. No. 5,135,536 to Hillstead; U.S. Pat. No. 5,354,309 to Shepp-Pesch et al.; EPO Patent Application 0 540 290 A2 to Lau; EPO Patent Application No. 0 364 787 B1 to Schatz, and PCT Application WO 94/17754 (also identified as German Patent Application 43 03 181).

[0009] Generally speaking, these kinds of stents are articulated and are usually formed of a plurality of aligned, expandable, relatively inflexible, circular segments which are interconnected by flexible elements to form a generally tubular body which is capable of a degree of articulation or bending. Unfortunately, a problem with such stents is that binding, overlapping or interference can occur between adjacent segments on the inside of a bend due to the segments moving toward each other and into contact or on the outside of a bend the segments can move away from each other, leaving large gaps. This can lead to improper vessel support, vessel trauma, flow disturbance, kinking, balloon burst during expansion, and difficult recross for devices to be installed through already implanted devices and to unsupported regions of vessel.

[0010] A diamond configuration with diagonal connections between each and every diamond of each segment is also known but such closed configurations lack flexibility.

[0011] It is an object of this invention to provide a longitudinally flexible stent of open configuration that avoids these problems and exhibits improved flexibility (radially and longitudinally) in the stent body segments thereof rather than in flexible joints between the segments.

[0012] It is a further object of the present invention to provide a stent that is flexible yet also allows for side branch access.

SUMMARY OF THE INVENTION

[0013] It is a goal of the present invention to provide a flexible stent formed of interconnected bands which provides for side branch access and which further avoids the problem of pinching or overlap between adjacent bands. Pinching or overlap is avoided where peaks and troughs of adjacent bands are circumferentially displaced relative to each other. The stents of the present invention accomplish this goal by having different bands characterized by different wavelengths over the length of the stent and/or disposing the interconnecting members in such a way that after expansion of the stent, the phase relationship between adjacent bands is altered with the peaks and troughs displaced circumferentially relative to each other.

[0014] The inventive expandable stents are formed of a plurality of interconnected band-like elements characterized by alternating peaks and troughs. The ends of the interconnecting members which join adjacent bands are circumferentially offset and optionally, longitudinally offset. Peaks and troughs in adjacent bands are circumferentially offset as well so that the stent, in an expanded state, will have minimal overlap of peaks and troughs.

[0015] To this end, the invention provides a tubular, flexible, expandable stent, comprising a plurality of undulating band-like elements of a selected wavelength or wavelengths. The band-like elements have peaks and troughs and are aligned on a common longitudinal axis to define a generally tubular stent body. The peaks and troughs take a generally longitudinal direction along the stent body. Adjacent band-like elements may be in phase or out of phase with each other. The inventive stents further comprise a plurality of intercon-

necting elements having first ends and second ends. The first and second ends extend from adjacent band-like elements and are displaced from one another in a longitudinal direction and in a radial direction along the stent. Desirably, upon expansion of the stent, at least some of the peaks and troughs of a given band-like element are displaced relative to each other about the periphery of the stent to accommodate longitudinal flexing of the stent within the band-like elements and without interference between adjacent band-like elements.

[0016] In one embodiment, two different types of band-like elements are present in the stent, first band-like elements with a first selected wavelength and second band-like elements with a second selected wavelength exceeding the first selected wavelength. The first and second band-like elements preferably alternate over the length of the stent. Although the terminology of 'first band-like element' and 'second band-like element' is used, it is not intended to convey the relative order of appearance of the elements in the inventive stents.

[0017] In another embodiment, two different types of band-like elements are present, first and second band-like elements, each of which has peaks and troughs. The first band-like elements have more peaks (or troughs) than the second band-like elements. Similarly, the invention is also directed to embodiments having first and second band-like elements with peaks and troughs where the peaks (or troughs) of the first band-like elements are spaced closer together than the peaks (or troughs) of the second band-like elements.

[0018] In another embodiment in which band-like elements of only one wavelength are present, adjacent bands are about 180° out of phase with one another. Interconnecting elements extend at an oblique angle relative to the longitudinal axis from a peak to a trough on an adjacent band.

[0019] In another embodiment in which band-like elements of only one wavelength are present, peaks from which interconnecting elements emanate are elongated relative to the peaks which are not connected to troughs and similarly, the troughs from which interconnectors emanate are elongated relative to troughs which are not connected to peaks. Further, each interconnecting element extends from the side of a peak to the side of a trough on an adjacent band.

[0020] In yet another embodiment in which band-like elements of only one wavelength are present, adjacent bands are about 90° out of phase with one another. Each interconnecting element extends between a peak and a trough and the ends of the interconnecting member are circumferentially offset from one another and, optionally, longitudinally offset.

[0021] The invention further provides a tubular, flexible, expandable stent having a longitudinal axis, comprising one or more cylindrical shaped first segments having first struts, the first segment being defined by a member formed in an undulating pattern of interconnected paired first struts and in which adjacent pairs of first struts in a given first segment are interconnected at opposite ends and one or more cylindrical shaped second segments defined by a member formed in an undulating pattern of interconnected paired second struts and in which adjacent pairs of second struts in a given second segment are interconnected at opposite ends. The first struts are shorter than the second struts. The first segments are formed of a number of first struts and the second segments are formed of a number of second struts with the number of first struts in a first segment exceeding the number of second struts in a second segment. The first and second segments, present and desirably alternating along the stent body, are aligned on a common longitudinal axis to define a generally tubular stent

body. Adjacent first and second segments are connected by a plurality of interconnecting elements, each interconnecting element extending from an end of paired first struts on a first segment to an end of paired second struts on an adjacent second segment. The ends of interconnecting elements are circumferentially offset relative to each other, and optionally, longitudinally offset. Desirably, upon expansion of the stent, the paired struts of the adjacent segments are displaced relative to each other about the periphery of the stent body to accommodate longitudinal flexing of the stent within the segments and without interference between adjacent segments.

BRIEF DESCRIPTION OF THE FIGURES

[0022] FIG. 1a shows a band-like element used in the inventive stents.

[0023] FIG. 1b shows a schematic of a peak region which contains a double peak and a trough region containing a double trough.

[0024] FIG. 2 shows a flat view of a stent configuration according to the invention.

[0025] FIG. 3 shows the pattern of FIG. 2 in a tubular stent.

[0026] FIG. 4a shows a flat view of a stent configuration according to the invention.

[0027] FIG. 4b shows a flat view of a stent configuration according to the invention.

[0028] FIG. 5a shows a flat view of a stent configuration according to the invention.

[0029] FIG. 5b shows a flat view of a stent configuration according to the invention.

[0030] FIG. 6 shows a flat view of a stent configuration according to the invention.

[0031] FIG. 7 shows a flat view of a stent configuration according to the invention.

[0032] FIG. 8 shows a flat view of a stent configuration according to the invention.

[0033] FIG. 9 shows a flat view of a stent configuration according to the invention.

[0034] FIG. 10 shows a flat view of a stent configuration according to the invention.

[0035] FIG. 11 shows a flat view of a stent configuration according to the invention.

[0036] FIG. 12 shows a flat view of a stent configuration according to the invention.

[0037] FIG. 13 shows the pattern of FIG. 12 in a tubular stent.

[0038] FIG. 14 shows an expanded stent of the configuration shown in FIG. 12.

[0039] FIG. 15 shows a flat view of an alternate stent configuration according to the invention.

DETAILED DESCRIPTION OF THE INVENTION

[0040] While this invention may be embodied in many different forms, there are described in detail herein specific preferred embodiments of the invention. This description is an exemplification of the principles of the invention and is not intended to limit the invention to the particular embodiments illustrated.

[0041] For the sake of consistency, the terms 'peak' and 'trough' shall be defined with respect to the proximal and distal ends of the stent. Each of the stents has a proximal end 91 and a distal end 93 and a longitudinal axis 95, as seen in FIG. 1a. Peaks 36 are generally concave relative to the proxi-

mal end of the stent and generally convex relative to the distal end of the stent. Troughs **40**, on the other hand, are generally convex relative to the proximal end of the stent and generally concave relative to the distal end of the stent. Notwithstanding this definition, the term peak is also intended to extend to regions **48** that are generally peak-like which may, nevertheless, contain trough-like regions within the peak-like region as seen in FIG. **1b**. Similarly the term trough is also intended to extend to regions **52** that are generally trough-like which may, nevertheless, contain peak-like regions within the trough-like region as seen in FIG. **1b**.

[0042] Corresponding to each peak **36** is an inner diameter peak **38** where the inner diameter of the band-like element reaches its peak. The set of points on a given band-like element which are distal to inner diameter peak **38** is denoted peak region **48**. Similarly, corresponding to each trough **40** is an inner diameter trough **42** where the inner diameter of the band-like element reaches its trough. The set of points on a given band-like element which are proximal to inner diameter trough **42** is denoted trough region **52**. For the sake of clarity, unless otherwise indicated, analogous portions of stents will be similarly labeled, using three digit reference numerals to distinguish among the various embodiments shown.

[0043] Also included within this definition of peak regions and trough regions are peak regions which are comprised of multiple peaks as well as trough regions which are comprised of multiple troughs such as those shown schematically in FIG. **1b**. Peak **36** is seen to consist of two sub-peaks **36a,b** and trough **40** is similarly seen to consist of two sub-troughs **40a,b**. In the case of peaks containing sub-peak and troughs containing sub-troughs, the peak region **48** includes all of the points along the band-like element between the sub-peaks that make up the peak and similarly, the trough region **52** includes all of the points along the band-like element between the sub-troughs that make up the trough.

[0044] The inventive stents may incorporate one or more bands of a chosen wavelength. In some embodiments, the inventive stents include one or more small amplitude, short wavelength bands to provide for flexibility and one or more large amplitude, long wavelength bands to give side branch access or to provide for sections of alternative strengths such as soft and/or stiff sections.

[0045] Turning to the Figures, FIG. **2** shows a flat view of a stent configuration and FIG. **3** shows the stent of FIG. **2** in tubular form. That is, the stent is shown for clarity in FIG. **2** in the flat and may be made from a flat pattern **110** (FIG. **2**) which is formed into a tubular shape by rolling the pattern so as to bring edges **112** and **114** together (FIG. **2**). The edges may then be joined as by welding or the like to provide a cylindrical configuration such as that shown generally at **115** in FIG. **3**.

[0046] A more preferred method of manufacture begins with a thin walled tube which is then laser cut to provide the desired configuration. It may also be chemically etched or EDM'd (electrical discharge machined) to form an appropriate configuration.

[0047] The configuration can be seen in these Figures to be made up of one or more spaced first band-like elements **120**. First band-like elements have a generally serpentine configuration to provide continuous waves to the first band-like elements. The waves are characterized by a plurality of peaks **124** and troughs **128** taking a generally longitudinal direction along the cylinder such that the waves in first band-like ele-

ments **120** open as the stent is expanded from an unexpanded state having a first diameter to an expanded state having a second diameter.

[0048] The stent further comprises a plurality of spaced second band-like elements **132** having a generally serpentine configuration to provide continuous waves to the second band-like elements. The waves are characterized by a plurality of peaks **136** and troughs **140** taking a generally longitudinal direction along the cylinder such that the waves in the second band-like elements open as the stent is expanded from an unexpanded state having a first diameter to an expanded state having a second diameter. First and second band-like elements are characterized by respective wavelengths and amplitudes with the wavelength and amplitude of the second band-like elements exceeding the wavelength and amplitude of the first band-like elements.

[0049] Adjacent first band-like elements **120** and second band-like elements **132** are interconnected via a plurality of interconnecting elements **144**. The ends of interconnecting element are circumferentially offset from each other.

[0050] In an embodiment, as shown in FIGS. **2** and **3**, first band-like elements **120** and second band-like elements **132** alternate over the length of the stent. Optionally, as shown in FIGS. **2** and **3**, each end **152** of the stent may terminate in a first band-like element. The invention also, however, contemplates each end terminating in a second band-like element, or further, one end terminating in a first band-like element and the other end terminating in a second band-like element.

[0051] While a minimum of one connecting element is required to join adjacent band-like elements, two or more interconnecting elements are preferred. In one embodiment, as shown in FIGS. **2** and **3**, adjacent first and second band-like elements **120** and **132** are connected with three interconnecting elements **144**. Further, in one embodiment, adjacent interconnecting elements **144** extending from peaks **136** on a first band-like element **120** are spaced five peaks apart on the first band-like element while adjacent interconnecting elements **144** extending from troughs **140** on a second band-like element **132** are spaced three troughs apart on the second band-like element.

[0052] It is a further feature of the present invention that peaks **124** on first band-like elements **120** are circumferentially displaced on the periphery of the stent from troughs **140** on adjacent second band-like elements **132**. It is desirable that peaks and troughs be displaced in the expanded state of the stent to minimize the possibility of pinching or overlap between adjacent band-like elements.

[0053] Although the stent of FIG. **2** is comprised of two different wavelength band-like elements, the invention contemplates stents with a plurality of different wavelength band-like elements. As such, other stents may have three, four or more different wavelength band-like elements.

[0054] In another embodiment, the inventive stent is comprised of band-like elements of a single wavelength, interconnected by interconnecting elements. Turning to FIGS. **4a** and **4b**, band-like elements **220a,b** are interconnected by interconnecting elements **244a,b**. Adjacent band-like elements **220a,b** are 180° out of phase with one another. In the compressed state, the band-like elements consist of a plurality of peaks **236a,b** and troughs **240a,b**. Peak region **248a,b** and trough region **252a,b** have been shaded in one instance for illustrative purposes.

[0055] In the embodiment shown in FIG. **4a**, each interconnecting element **244a** extends between a peak region **248a**

and a trough region **252a**. Rectilinear interconnecting elements **244a** consist of a first shank **280a**, a second shank **284a** and a link **288a** disposed in-between the first and second shanks **280a** and **284a**. First shank **280a** extends in a longitudinal direction from peak region **248a** and is substantially perpendicular to link **288a**. Second shank **284a** extends in a longitudinal direction from trough region **252a** and is perpendicular to link **288a**.

[0056] In the embodiment shown in FIG. **4b**, the stent differs from the embodiment of FIG. **4a** in that interconnecting element **244b** extending between a peak region **248b** and a trough region **252b** is curvilinear rather than rectilinear.

[0057] In both FIGS. **4a** and **4b**, the interconnecting elements are seen to emanate from the middle of the peak and trough regions.

[0058] In another embodiment, as shown in FIG. **5a**, the inventive stent is comprised of band-like elements **320a** of a single wavelength, interconnected by interconnecting elements **344a**. Adjacent band-like elements **320a** are 180° out of phase with one another. The band-like elements consist of a plurality of peaks **336a** and troughs **340a**. Interconnecting elements **344a** extend between a peak region **348a** and a trough region **352a**. The peak regions **348a** and trough regions **352a** from which interconnecting elements **344a** emanate on a given band-like element **320a** are seen to extend longitudinally beyond adjacent peak regions **348a'** and trough regions **352a'** from which no interconnecting elements extend. The extension is such that at least a portion of peak regions **348a** overlap longitudinally along the stent with at least a portion of trough region **352a** on an adjacent band-like element **320a'**. Of course, the overlap is limited to the longitudinal direction and not to the circumferential direction.

[0059] In another embodiment, as shown in FIG. **5b**, interconnecting elements **344b** extend between peak region **348b** and a second closest trough region **352b** on an adjacent band-like element. Interconnecting elements **344b** are seen to be perpendicular to the longitudinal axis. As in the stent of FIG. **5a**, peak regions **348b** from which interconnecting elements **344b** extend and trough regions **352b** from which interconnecting elements **344b** extend may extend beyond adjacent peak regions **348b'** and trough regions **352b'** from which no interconnecting elements **344b** emanates.

[0060] In another embodiment, as shown in FIG. **6**, adjacent band-like elements **420** are in phase with each other. As in previous Figs, band-like elements **420** are of a single wavelength, interconnected by interconnecting elements **444**. The band-like elements consist of a plurality of peaks **436** and troughs **440**. Interconnecting elements **444** extend at an oblique angle relative to the longitudinal axis of the stent between a peak region **448** and a trough region **452**. As such, ends of interconnecting elements **444** are circumferentially offset relative to each other. The exact angle will, of course, depend on the region from which the interconnecting elements extend, as well as on whether interconnecting elements interconnect nearest peaks and troughs, next nearest peaks and troughs or peaks and troughs that are further separated.

[0061] In FIGS. **5a**, **5b** and **6**, the interconnecting elements are seen to emanate from the sides of the peak and trough regions.

[0062] Although for the embodiments of FIGS. **1-6**, the interconnecting elements extend from peak regions on band-like elements to trough regions on adjacent band-like elements, the invention further contemplates interconnecting elements extending from a position between a peak region

and an adjacent trough region on a band-like element to a position intermediate a trough region and a peak region on an adjacent second band-like element as in FIG. **7**.

[0063] In the embodiment of FIG. **7**, interconnecting elements are seen to extend from a region between the peak region and the trough region on a band-like element. The stent is formed of adjacent band-like elements **520** which are 180° out of phase with one another. Interconnecting elements **544** extend from a region intermediate a peak region **548** and a trough region **552** on a band-like element to a region intermediate a peak region **548** and a trough region **552** on an adjacent band-like element. Interconnecting elements **544** consist of a first shank **560**, a second shank **564**, and an intermediate member **568** disposed in-between first and second shanks **560** and **564**. First shank **560** and second shank **564** are substantially perpendicular to intermediate member **568** which extends in the longitudinal direction. Although not depicted, the region from which interconnecting elements **544** emanate may be midway between peaks and troughs.

[0064] The embodiment of FIG. **7** also differs from the embodiments of FIGS. **2-6** in the orientation of the interconnecting elements. Whereas the interconnecting elements in FIGS. **2-6** are all similarly oriented, in the embodiment of FIG. **7**, the orientation of interconnecting elements alternates between adjacent pairs of adjacent band-like elements. Specifically, second shanks **564'** of interconnecting elements **544'** are seen to be displaced in a clockwise circumferential direction along the stent relative to first shanks **560'**, and second shank **564''** of interconnecting elements **544''** are seen to be displaced in a counterclockwise circumferential direction along the stent relative to while first shank **560''**.

[0065] This feature is also seen in the embodiment of FIG. **8** in which adjacent in-phase band-like elements **620** are interconnected by interconnecting elements **644**. Interconnecting elements **644** extend at an oblique angle relative to the longitudinal axis of the stent between a peak region **648** and a trough region **652**. As in FIG. **7**, the orientation of interconnecting elements alternates between adjacent pairs of adjacent band-like elements. Specifically, the distal ends of interconnecting elements **644'** are seen to be oriented in a counterclockwise circumferential direction along the stent relative to the proximal end of the interconnecting elements while the distal ends of interconnecting elements **644''** are seen to be displaced in a clockwise circumferential direction along the stent relative to the proximal ends.

[0066] Although in the embodiments of FIGS. **2-8**, adjacent bands are connected by five interconnecting elements, additional or fewer interconnecting elements may be used. Further, while interconnecting elements are shown spaced three peaks apart and three troughs apart, other separations are contemplated as well.

[0067] In the embodiment of FIG. **9**, each band-like element **720** is seen to comprise peaks **736** of more than one amplitude and troughs **740** of more than one amplitude. Large amplitude peaks **736a** and small amplitude peaks **736b** alternate as do large amplitude troughs **740a** and small amplitude troughs **740b**. As in the previous embodiments, the interconnecting elements are oriented at an oblique angle relative to the longitudinal axis **795** of the stent. More generally, the invention is directed at stents comprising band-like elements whose amplitude varies along the band-like element.

[0068] In another embodiment of the invention, as shown in FIG. **10**, each band-like element **820** is seen to comprise peaks **836** of more than one amplitude and troughs **840** of

more than one amplitude, however, peaks of the same amplitude are grouped together within a band-like element as are troughs of the same amplitude. It is further noted that in the embodiment of FIG. 10, the location of a group of peaks of given amplitude in a band-like element varies circumferentially along the length of the stent. Interconnecting elements **844** connect peaks **836** and troughs **840** in adjacent band-like elements **820**. Where several peaks of different amplitudes are present in a band-like element, the invention further contemplates the possibility of interconnecting elements extending from the large peaks **836a** to large troughs **840a** as in FIG. 9 as well as the possibility of interconnecting elements extending from large peaks to small troughs or from small peaks **836b** to large troughs **840a** as in FIG. 10. Further, the interconnecting elements between any two adjacent band-like elements may be of different lengths from one another as seen in FIG. 10 and commence at different longitudinal positions within a band-like element and terminate at different longitudinal positions within a band-like element. Interconnecting element **844a** is seen to be longer than interconnecting element **844b**. As in the previous embodiments, the interconnecting elements are oriented at an oblique angle relative to the longitudinal axis **895** of the stent. In the embodiment of FIG. 10, interconnecting element **844a** is seen to be oriented at a smaller oblique angle relative to the longitudinal axis of the stent than interconnecting element **844b**. As is apparent from FIG. 10, the invention is also directed to stents comprised of band-like elements whose wavelength varies along a given band-like element. Region **898** and region **899** of band-like element are characterized by different wavelengths.

[0069] It is also noted that in the embodiment of FIG. 10, all of the troughs **840a, b** in a given band-like element **820** are aligned longitudinally along the stent and differ only in their circumferential position along the stent.

[0070] It is further noted in the embodiment of FIG. 10, the stent comprises a first group of interconnecting elements **844a** and a second group of interconnecting elements **844b**. The interconnecting elements of the first group are all parallel to one another and disposed at a different oblique angle relative to the longitudinal axis than the members of the second group which are all parallel to one another. As such, the invention contemplates stents having several different groups of obliquely disposed interconnecting elements where the oblique angle differs from group to group.

[0071] In another embodiment of the invention, as shown in FIG. 11, each band-like element **920** is seen to comprise peaks **936a, b** of different amplitudes and troughs **940** of different amplitudes, however, peaks of the same amplitude are grouped together within a band-like element as are troughs of the same amplitude. It is further noted that in the embodiment of FIG. 11 the location of groups of peaks of given amplitude in a band-like element varies circumferentially along the length of the stent. Interconnecting elements **944** connect large amplitude peaks **936a** and small amplitude troughs **940b** in adjacent band-like elements **920**. Similarly, interconnecting elements **944** also connect small amplitude peaks **936b** and large amplitude troughs **940a**.

[0072] The invention also contemplates stents similar to that shown in FIG. 11 in which interconnecting elements extend from large peaks **936a** to large troughs **940a**, as in FIG. 9. Similarly, interconnecting elements may extend from small peaks **936b** to small troughs **940b**.

[0073] Further, the interconnecting elements between any two adjacent band-like elements may be of different lengths from one another and disposed at different oblique angles.

[0074] As is apparent from FIG. 11, the invention is also directed to stents comprised of band-like elements whose wavelength varies along a given band-like element. Region **998** and region **999** of band-like element **920** are characterized by different wavelengths.

[0075] It is also noted that in the embodiment of FIG. 11 the large amplitude portions **999** of band-like element **920** are symmetrically disposed about the center **1001** of the band-like element as are the small amplitude portions **998**. The center **1001** of the band-like element is defined as a ring that runs along a path that is midway between the large peaks **936a** and large troughs **940a** of the band-like element. This feature may also be seen in the embodiment of FIG. 9.

[0076] The invention is also directed to a tubular, flexible, expandable stent having a longitudinal axis, comprising one or more cylindrical shaped first segments. Cylindrical shaped first segments **20** as seen in FIG. 1, have first struts **23** having first **25** and second **27** ends. First segments **20** are defined by a member formed in an undulating pattern of interconnected paired first struts **23**, in which adjacent pairs of first struts **29'** and **29''** in a given first segment **20** are interconnected at opposite ends **31'** and **31''**, respectively. Adjacent segments are interconnected.

[0077] The stent may be seen more clearly in FIGS. 2-8. As shown, the stent of FIG. 3, in addition to comprising first segments **120** which are defined by an undulating pattern of interconnected paired first struts **123** in which adjacent pairs of first struts **129'** and **129''** in a given first segment **120** are interconnected at opposite ends **131'** and **131''**, respectively, the stent further comprises one or more cylindrical shaped second segments **132**, each second segment being defined by a member formed in an undulating pattern of interconnected paired second struts **135** and in which adjacent pairs of second struts **137'** and **137''** in a given second segment **132** are interconnected at opposite ends **139'** and **139''**, respectively. First struts **123** are shorter than second struts **135**. First segments **120** are formed of a number of first struts **123** and second segments **132** formed of a number of second struts **135**, the number of first struts in a first segment exceeding the number of second struts in a second segment. First and second segments **120** and **132** are aligned on a common longitudinal axis **195** to define a generally tubular stent body, shown generally at **115**. First and second segments **120** and **132** alternate along the stent body. Adjacent first and second segments **120** and **132** are connected by a plurality of interconnecting elements **144**. Each interconnecting element **144** extends from an end **131''** of paired first struts on a first segment **120** to an end **139''** of paired second struts on an adjacent second segment **132**. The ends of interconnecting elements **144** are circumferentially offset relative to each other.

[0078] Desirably, upon expansion of stent **115**, paired struts **129''** and **137''** of adjacent segments **120** and **132** are displaced relative to each other about the periphery of the stent body to accommodate longitudinal flexing of the stent within the segments and without interference between adjacent segments.

[0079] In the embodiments as shown in FIGS. 4a, b, cylindrical shaped segments **220a, b** are formed of interconnected struts **223a, b** having first **225** and second **227** ends. Adjacent pairs of struts **229a, b'** and **229a, b''** in a given segment **220a, b** are interconnected at opposite ends **231a, b'** and **231a, b''**,

respectively. Adjacent segments are connected by a plurality of interconnecting elements **244a,b**. Each interconnecting element **244a,b** extends from an end of paired struts **231a,b** on a segment to an end of paired struts **231a,b** on an adjacent segment. First end **245a,b** and second end **247a,b** of interconnecting elements **244a,b** are seen to be circumferentially displaced along the stent.

[0080] Similar structure, denoted by similar reference numerals may be found in the stents of FIGS. **5a,b**, and **6-8**.

[0081] In particular, in the embodiment as shown in FIG. **8**, cylindrical shaped segments **620** are formed of interconnected struts **623**, having first **625** and second **627** ends. Segments **620** are defined by a member formed in an undulating pattern of interconnected paired struts **623** in which adjacent pairs of struts **629'** and **629"** in a given segment **620** are interconnected at opposite ends **631'** and **631"**, respectively. Segments **620** are aligned on a common longitudinal axis **695** to define a generally tubular stent body. Adjacent segments are connected by a plurality of interconnecting elements **644** (and **644'**) having first **645** (**645'**) and second **647** (**647'**) ends, each interconnecting element **644** (**644'**) extending from an end of paired struts **631'** on a segment to an end of paired struts **631"** on an adjacent segment. First end **645** (**645'**) and second end **647** (**647"**) are seen to be circumferentially displaced along the stent.

[0082] Additional embodiment of the stents are shown in FIGS. **12-15**. FIG. **12** and FIG. **13** show a fragmentary flat view of an unexpanded stent configuration and the actual tubular stent (unexpanded), respectively. That is, the stent is shown for clarity in FIG. **12** in the flat and may be made from a flat pattern **1110** (FIG. **12**) which is formed into a tubular shape by rolling the pattern so as to bring edges **1112** and **1114** together (FIG. **12**). The edges may then joined as by welding or the like to provide a configuration such as that shown in FIG. **13**.

[0083] The configuration can be seen in these Figures to be made up of a plurality of adjacent segments generally indicated at **1116**, each of which is formed in an undulating flexible pattern of substantially parallel struts **1118**. Pairs of struts are interconnected at alternating end portions **1119a** and **1119b**. As is seen in FIG. **12**, the interconnecting end portions **1119b** of one segment are positioned opposite interconnecting end portions **1119a** of adjacent segments. The end portions as shown are generally elliptical but may be rounded or square or pointed or the like. Any configuration of end portions is acceptable so long as it provides an undulating pattern, as shown. When the flat form **1110** is formed into an unexpanded tube as shown in FIG. **13**, the segments are cylindrical but the end portions **1119** of adjacent segments remain in an opposed position relative to each other.

[0084] A more preferred method of manufacture begins with a thin walled tube which is then laser cut to provide the desired configuration. It may also be chemically etched or EDM'd (electrical discharge machined) to form an appropriate configuration.

[0085] Interconnecting elements **1120** extend from one end portion **1119** of one segment **1116** to another end portion **1119** of another adjacent segment **1116** but not to an oppositely positioned end portion **1119** of an adjacent segment **1116**. There are at least three struts included between the points on each side of a segment **1116** at which an interconnecting element **1120** contacts an end portion **1119**. This results in the interconnecting elements **1120** extending in an angular direction between segments around the periphery of

the tubular stent. Interconnecting elements **1120** are preferably of the same length but may vary from one segment to the other. Also, the diagonal direction may reverse from one segment to another extending upwardly in one case and downwardly in another, although all connecting elements between any pair of segments are substantially parallel. FIG. **12**, for example shows them extending downwardly, right to left. Upwardly would extend up left to right in this configuration.

[0086] As a result of this angular extension of the interconnecting elements **1120** between adjacent segments and loops, upon expansion of the stent as seen in FIG. **14**, the closest adjacent end portions **1119** between segments **1116** are displaced from each other and are no longer opposite each other so as to minimize the possibility of binding or overlapping between segments, i.e., pinching

[0087] The number of interconnecting elements **1120** may vary depending on circumstances in any particular instance. Three per segment are satisfactory for the configuration shown and at least three will be used typically.

[0088] The alternate design shown in FIG. **15** includes longer struts **1118a** in the two end segments **1116a** than in the intermediate segments **1116**. This allows the end segments (**1116a**) to have less compression resistance than the intermediate segments (**1116**), providing a more gradual transition from the native vessel to the support structure of the stent. Otherwise, the configuration is the same as that shown in FIG. **12**.

[0089] As indicated in the Figures, the invention contemplates a variation of interconnecting element shapes ranging from rectilinear to curvilinear. The invention further contemplates embodiments in which all interconnecting elements are similarly oriented as well as embodiments in which adjacent sets of interconnecting elements extending between adjacent pairs of segments are oppositely oriented (e.g., FIGS. **7** and **8**). The invention also contemplates the use of interconnecting elements which extend from a range of positions along the segments, ranging from various positions in the area in which paired struts are interconnected to other positions along the struts.

[0090] The invention also contemplates the possibility of interconnecting elements extending at an oblique angle relative to the longitudinal axis of the stent and connecting adjacent peaks and troughs on adjacent segments as well as peaks and troughs on adjacent segments which are separated by one or more peaks and/or troughs.

[0091] The invention also contemplates reversing the orientation of interconnecting elements as shown in FIGS. **7** and **8**.

[0092] Finally, there are preferably at least three interconnecting elements joining adjacent first and second segments although fewer or additional interconnecting elements are also contemplated.

[0093] It is understood that the peaks and troughs of the present invention need not be rounded, as shown in the Figures. The peaks and troughs may be bulbous, triangular, square, pointed, or otherwise formed of interconnected straight sections.

[0094] As already indicated, this invention is applicable to self-expanding configurations, mechanically expandable configurations and to a wide variety of materials, including both metal and plastic and any other material capable of functioning as an expandable stent. For example, the stent may be of metal wire or ribbon such as tantalum, stainless

steel or the like. It may be thin-walled. It may be of shape memory alloy such as Nitinol or the like, etc. The interconnecting elements may be formed integrally with the band-like elements (or segments) or may be bonded thereto via such methods as adhesive bonding, welding or any other known method of bonding.

[0095] The above Examples and disclosure are intended to be illustrative and not exhaustive. These examples and this description will suggest many variations and alternatives to one of ordinary skill in this art. All these alternatives and variations are intended to be included within the scope of the attached claims. Those familiar with the art may recognize other equivalents to the specific embodiments described herein which equivalents are also intended to be encompassed by the claims attached hereto.

What is claimed is:

1. A stent comprising: a plurality of contiguous filaments arranged to form:

- (i) a plurality of first helical segments, each first helical segment consisting of a plurality of substantially S-curved undulations alternating with a plurality of connection elements, each S-curved undulation defined as a contiguous filament segment extending between two consecutive connection elements, and each connection element including a substantially linear strut angled with respect to a longitudinal axis of the stent; and
- (ii) a second helical segment consisting of a plurality of undulations alternating with a plurality of the connection elements, each undulation defined as a contiguous filament segment extending between two consecutive connection elements and having a circumferential length larger than a circumferential length defined by each substantially S-curved undulation,

wherein each undulation consists of five linear segments connected together by curved portions; the first and second helical segments having different pitches and crossing each other at the connection elements that are integral portions of the first and second helical segments.

2. The stent of claim **1** wherein each of the substantially S-curved undulations includes a plurality of linear filament segments that are substantially parallel to a longitudinal axis of the stent.

3. A stent having an a generally cylindrical shaped body, comprising:

- a first repetitious pattern of contiguous filament segments consisting of a plurality of substantially S-shaped undulations alternating with a plurality of connection elements propagating generally helically through the body, the first repetitious pattern having a first pitch and each S-shaped undulation defined as a contiguous filament segment spanning between two consecutive connection elements; and

- a second repetitious pattern consisting of the connection elements alternating with a plurality of undulations, each undulation spanning between two consecutive connection elements and defining a length greater than a length of each substantially S-shaped undulation,

wherein each undulation consists of five linear segments connected together by curved portions, and wherein the second repetitious pattern propagates helically through the body and has a second pitch that is different than the first pitch.

4. The stent of claim **3** wherein each of the substantially S-shaped undulations includes a plurality of linear filament segments that are substantially parallel to a longitudinal axis of the stent.

5. The stent of claim **4** wherein the connection element includes a substantially linear strut angled with respect to a longitudinal axis of the stent.

6. A stent comprising:

- a plurality of filament segments arranged to form a plurality of first repetitious patterns, each first repetitious pattern consisting of substantially S-shaped segments and connection elements advancing substantially helically along a longitudinal axis of the stent,

wherein each S-shaped segment is connected to exactly two connection elements, and each connection element includes a substantially linear strut angled with respect to a longitudinal axis of the stent;

wherein the connection elements are staggered to form a second repetitious helical pattern with a plurality of undulations, each undulation having a longer length than a length of each of the substantially S-shaped segments, and wherein each undulation is connected to exactly two connection elements.

7. The stent of claim **6** wherein at least a portion of the first repetitious pattern is generally sinusoidal.

8. The stent of claim **6** wherein the connection elements forming the second pattern are not contiguous.

9. The stent of claim **6**, wherein the first and second repetitious helical patterns have opposing pitches.

10. The stent of claim **9**, wherein the first and second repetitious helical patterns share common filament segments.

11. The stent of claim **6**, wherein each of the substantially S-shaped segments includes a plurality of linear filament segments that are substantially parallel to the longitudinal axis of the stent.

12. A stent comprising:

- a plurality of first substantially repeating patterns formed by a plurality of filament segments, each first substantially repeating pattern consisting of substantially S-shaped segments and interconnecting elements coursing angularly along the periphery of said stent, between the proximal end of the stent and the distal end of the stent, and having a common longitudinal axis,

wherein each substantially S-shaped segment is connected to exactly two interconnecting elements, and each interconnecting element extends in an angular direction with respect to said common longitudinal axis;

wherein the interconnecting elements are staggered to form a second substantially repeating pattern with a plurality of undulations coursing angularly along the periphery of said stent, each undulation having a longer length than a length of each of the substantially S-shaped segments, and wherein each undulation is connected to exactly two connection elements.

13. The stent of claim **12**, wherein the interconnecting elements forming the second substantially repeating pattern are not contiguous.

14. The stent of claim **12**, wherein the first and second substantially repeating patterns have opposing pitches.

15. The stent of claim **12**, wherein the first and second substantially repeating patterns share common filament segments.

16. The stent of claim **12**, wherein each of the substantially S-shaped segments includes a plurality of struts that are substantially parallel to the longitudinal axis of the stent.

* * * * *