US 20110246898A1

(19) **United States**

(12) **Patent Application Publication**

Imes et al.

(10) **Pub. No.: US 2011/0246898 A1**

(43) **Pub. Date: Oct. 6, 2011**

(54) **MOBILE ENERGY MANAGEMENT SYSTEM**

(76) Inventors: **Kevin R. Imes**, Austin, TX (US); **James Hollister**, Round Rock, TX (US); **John Frederick Cottrell**, Austin, TX (US)

(21) Appl. No.: **13/165,887**

(22) Filed: **Jun. 22, 2011**

Related U.S. Application Data

(63) Continuation of application No. 13/080,705, filed on Apr. 6, 2011, which is a continuation-in-part of application No. 12/840,142, filed on Jul. 20, 2010, which is a continuation-in-part of application No. 12/840,169, filed on Jul. 20, 2010, said application No. 12/840,142 is a continuation-in-part of application No. 12/840,059, filed on Jul. 20, 2010, said application No. 13/080,705 is a continuation-in-part of application No. 12/893,230, filed on Sep. 29, 2010, which is a continuation-in-part of application No. 12/893,327, filed on Sep. 29, 2010, which is a continuation-in-part of application No. 12/948,889, filed on Nov. 18, 2010, which is a continuation-in-part of application No. 12/948,806, filed on Nov. 18, 2010, which is a continuation-in-part of application No. 12/948,208, filed on Nov. 17, 2010, which is a continuation-in-part of application No. 12/839,854, filed on Jul. 20, 2010.

(60) Provisional application No. 61/255,678, filed on Oct. 28, 2009, provisional application No. 61/235,798, filed on Aug. 21, 2009.

(30) **Foreign Application Priority Data**

Jul. 20, 2010 (WO) PCTUS1042589

Publication Classification

(51) **Int. Cl.**


G06F 15/177 (2006.01)

G06F 3/01 (2006.01)

(52) **U.S. Cl.** **715/735**

(57) **ABSTRACT**

According to an aspect of the disclosure, a mobile energy management system and method includes controlling at least one network device at a site using the proximity detection of a mobile device which may be based upon the detection of a plurality of zones. Various features may be presented on a graphical user interface of the mobile device including a proximity control feature for enabling and disabling proximity detection, a set location setting for associating the current location of the mobile device with the location of the site, a set travel distance feature enabling the user to enter a travel distance within the graphical user interface, and a map which may present the location of the site, the current location of the mobile device, and the plurality of zones. The network device may be a thermostat associated with the HVAC system of the site or other energy consuming appliances.





100
104
Energy Source 102
128
Server 120
122
124
126
Site 1 106
Site 2 108
Site 3 110
DEG Asset 112
VCG Asset 114
DEG Asset 116
VCG Asset 118
EMI 130

FIG. 1




200
202
Site
DEG Asset 214
Smart Appliance(s) 212
TSAT 208
Mobile Device 210
AMI / Gateway 242
Controller 216
Gateway 218
242
244
248
206
Server
Site Interface 220
Processor 222
Memory 226
Database 224
Mobile Client Interface 226
Energy Pricing Monitor
Demand Response Module
Efficiency Rating
Proximity Detection Module
Scheduling Module
Energy Savings
Messaging Module
204
228
230
232
234
236
238
240
Information Network 240
Smart Metering Device 250

FIG. 2

FIG. 3


Begin
300
Network Established ?
302
Yes
No
Detect AMI Network?
304
Yes
Join AMI Network
306
No
Detect WIFI Network
308
Yes
Initiate WIFI Network
310
No
Establish Energy Network
312
Detect Network Device
314
Obtain Profile
316
Join Network Device
318
Proceed to Block 322
320
Proximity Enabled ?
322
Yes
Receive Location Report
344
No
Detect User Schedule
324
Yes
Identify Event
356
No
Schedule Event ?
326
Yes
Schedule Event
328
No
Detect Location Change ?
346
Yes
Detect Distance
350
Detect Direction
352
No
Proceed to Block 322
350
Alter Operating Condition
348
Yes
Intiate Control Action
354
No
Generate Control Action
330
Output Control Action to Home Energy Network
332
Alter Operating Condition
334
Proceed to Block
340
Generate Site
338
Obtain Network Device Data
336



400
Power Supply 412
Broadband Device 414
Information Network Interface 416
Wireless Information Network Device 418
External Bus Interface 420
Bus
406
Memory 404
Processor 402
Bus 410
Network Device Profile Module 432
Device Profiles 442
Profile Modifiers 448
Security Module 434
User Profiles 444
Home Profiles 446
Controller Module 436
Proximity Detection Module 438
Application Program Interface 440
OS 450
Support / Updates 428
Bus 408
Zigbee 422
WIFI 424
AMI 426
Communication Interface 430

FIG. 4

FIG. 5A



500
Mobile Device
Memory
504
I/O Device
506
Display
508
Processor
502
Energy Management Application
510
Wireless Data Network
522
Location Reporting Device
512
Proximity Detection Module
524
Network Interface
514
WIFI
516
Bluetooth
518
ZigBee
520

FIG. 5B




530
Energy Management User Interface
532
User Name
Location
Energy Provider
Energy Personality
534
Current Readings
(Inside,Outside, Proximity, Alerts)
536
Current Settings (TSTAT 1, TSTAT 2)
Proximity Detection (On/Off)
Demand Response (On/Off)
538
Current Savings

FIG. 6A


600
602
604
638
642
Zone 1
Zone 2
Site
HVAC 630
TSAT 628
Controller 626
640
644
External Data Source 612
Network Location 618
Mobile Device 632
614
620
624
636
Server
Database 608
Exernal Data Source Interface 610
Network Interface 616
Site Interface 622
Mobile Client Interface 634
Processor 606
Scheduling Module
Scheduling Tool Module
Scheduling Templates Module
Control Action Report Module
Site Data Report Module
Efficiency Rating Module
Setpoint Update Module
Proximity Detection Module
Zone Update Module
Current Readings Module
Demand Response Module
Energy Savings Module
Message Module
Interaction Detection Module
Energy Personality Detection Module
Mobile Client Module
648
650
652
654
656
658
660
662
664
666
668
670
672
674
678
680



12:00
Current Reading
in:78°out:95°
530
Thermostat Set-Point
Map View
77° | 78° | 79°
Main
Your Name
1234 Your Street
Your Town, Your
City 12345
Set Location
633
Mode: A/C | Heater Status: ON
Proximity Detection
Auto
On
Off
667
651
The Maximum Distance
I Will Be Traveling Today
is:
4 Miles
5 Miles
10 Miles
665
632

FIG. 6B



12:00
Current Reading
in:78°out:95°
530
Back
Map View
663
You Are Currently Outside Zone 182
651
659
653
649
74°
76°
655
657
661
632

FIG. 6C



642
604
638
643
645
637
641
639

FIG. 6D



700
702
704
706
708
710
712
714
716
718
720
722
724
726
728
730
732
734
736
738
User Information
User 1 | User 2
User Name
Residential Site Address
Mobile Phone Number
Current Energy Provider
Current Best Rate
Advertiesment
edit details
Current Readings
Date / Time
65
inside
outside
67
TSTAT 1
65
Energy Savings:
Low
Main | 2 | 3
Demand Response :
ON | OFF | TEXT ME
Proximity Detection:
ON | OFF
Energy Usage / Savings
Current Annual Savings
$235.37
2.3 MWH
Current Monthly Savings
$35.33
350 kWH
Demand Reponse Savings
$175.00
1250kWH
view more data

FIG. 7



800
802
804
806
808
810
812
814
816
818
820
822
824
Energy Usage / Savings
Current Annual Savings
$235.37
2.3 MWH
Current Monthly Savings
$35.33
350 kWH
Demand Reponse Savings
$177.00
1.25 MWH
Estimated Annual Savings
Graph of Managed vs. Unmanaged Energy Consumption
Comparitive Consumption Graph
Community | State | National
Sunday July 25, 2010
Current Daily Usage /Savings Graph
(click to enlarge)
Su| M | T | W | Th | F | Sa
June 2010
Monthly Usage / Savings Graph
view annual

FIG. 8



900
902
904
906
908
910
912
914
916
918
920
922
924
926
928
930
932
934
User Information
User 1 | User 2
+ ADD USER
User Name
Energy Personality Type
Indicia
Add to Social Networks
Site Address
Mobile Number
Energy Text Message Alerts:
ON | OFF
Proximity Detectio n
ON | OFF
Access Privileges
Current Energy Provider: Centerpoint Energy
Current Rate Plan: Fixed Rate ($0.30/kWh)
Best Available Rate Plan for CenterPoint Energy
- Tiered Rate ($0.28/kWh)
Best Local Rate: EnergyOne: Usage Plan ($0.25/kWh)
Calculate Annual Savings
User 1 | User 2
My Energy Blogs | Green Energy Reviews | Markets
My Energy Savings Have Been Huge!
april 25, 2010
author: User 1
Edit | Publish
Today's Best Energy Savings Advice...
april 22, 2010
author: Allure Energy Expert
+ ADD

FIG. 9



1000
1002
1004
1006
1008
1010
1012
1014
1016
1018
1020
1022
1024
1026
1028
1030
1032
1034
1036
1038
1040
1042
1044
1046
Sun, July 25, 2010
9:40 AM
T-STAT Main | 2 | 3
TSTAT 1
68
Savings Selector
L M H
Estimated Savings
Monthly: $28.00
Annual: $273.00
Summer | Winter Schedule
(A/C) (Heater)
USER 1 (active) | USER 2 | Vacation | Lake House + ADD
Current Inside: 67 Outside: 85
SUN MON TUES WED THUR FRI SAT
12am - 5am
5am - 8am
8am - 10am
10am - 5pm
5pm - 9pm
65 68 74
68 68 68 68 68 68
80 80 80 82 82 82
75 72 72 72 72 72
adapt?
adapt?
+ Add Additional Time Span
View Templates
Proximity : ON | OFF
Vacation Mode: ON | OFF
Leave Date
Return Date
Text Energy Alerts: YES | NO

FIG. 10

FIG. 11




1100
Wireless Thermostat
1102
Outside Temp: 75
1104
Partly Cloudy: 20% Rain
Todays Hl: 90 Lo: 73
1108
1112
1110
-
76
+
1106
Inside Temp: 77
1116
1120
Off --- Heat -- A/C -- Fan
Proximity -- Vacation -- SE
1114
1118

FIG. 12


1200
Temperature / Humidity Sensors 1202
I/O Sensor 1204
Power /Control Interface 1206
Bus Interface 1208
Processor 1210
Control Relays 1212
Wireless Device 1214
Memory 1216
Display Interface 1218
PMU 1220
Display 1222
Profile Module 1224



1300
1302
1304
Information Network 1332
Site
Controller
Application Program Interface 1306
Communication Interface(s) 1306
Network Device 1330
Wireless Device 1308
Wireless Device 1310
Wireless Device 1312
Network 1 1314
Network 2 1318
Network 3 1322
TSTAT 1320
Mobile Device
1330
1328
Smart Meter / AMI 1316
Utility Network 1328
Information Network 1326

FIG. 13



1400
1404
Database
1406
Site Data
1408
User Profile
1410
Performance Data
External Data Source 1412
Capacity Buyer / Auction 1414
Server
1402
Monitor 1416
Mobile Device 1 1422
Client Interface 1418
Site Interface 1420
Site 1 1428
Mobile Device 2 1424
Client System 1426
Site 3 1432
Site 2 1430

FIG. 14



1500
1504
Database
1506
Site Data
1508
Site Schedule
1510
Performance Data
External Data Source 1512
Utility Scheduling Interface 1514
Server
1502
Aggregate Demand Module 1516
Mobile Device 1 1522
Client Interface 1518
Site Interface 1520
Site 1 1528
Mobile Device 2 1524
Client System 1526
Site 3 1532
Site 2 1530

FIG. 15



Begin
1600
Detect Aquisition Interval
1602
Acqusition Interval Updated?
1604
Yes
Obtain Updated Interval
1606
No
Acquire Device Data
1608
Translate Device Data
1610
Detect Report Interval
1612
Report Interval Updated?
1614
Yes
Obtain Updated Interval
1616
No
Generate Report Data
1618
Generate / Update Site Report
1620
Initiate Network Connection
1622
Network Location Available?
1624
Yes
Initiate Transfer of Site Report
1630
Initiate Processing of Site Report Data at Network Location
1632
No
Store Site Report
1626
Control Action Available?
1634
Yes
Receive Control
1636
No
Interval(s) Updated?
1638
Yes
Update Interval(s)
1640
No
Updates Available?
1642
Yes
Recieve Update(s)
1644
Process Update(s)
1646
Disconnect from Network Location
1648
Process Control Action
1650
Detect Control Action Data
1652
Process Control Action Data
1654
Generate Network Device Data
1656
Output Network Device Data
1658
Proceed to Block 1602
1660

FIG. 16

MOBILE ENERGY MANAGEMENT SYSTEM

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of co-pending U.S. Ser. No. 13/080,705 entitled "Mobile Energy Management System," filed on Apr. 5, 2011, which was a continuation-in-part of co-pending U.S. application Ser. No. 12/840,142 entitled an "Energy Management System and Method," filed on Jul. 20, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/840,169 entitled an "Energy Management System and Method," filed on Jul. 20, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/840,059 entitled an "Energy Management System and Method," filed on Jul. 20, 2010," and a continuation-in-part of co-pending U.S. application Ser. No. 12/893,230 entitled an "Energy Management System and Method," filed on Sep. 29, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/893,327 entitled an "Energy Management System and Method," filed on Sep. 29, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/948,889 entitled an "Energy Management System and Method," filed on Nov. 18, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/948,806 entitled an "Energy Management System and Method," filed on Nov. 18, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/948,208 entitled an "Energy Management System and Method," filed on Nov. 17, 2010, and a continuation-in-part of co-pending U.S. application Ser. No. 12/839,854 entitled an "Energy Management System and Method," filed on Jul. 20, 2010, and a continuation-in-part of co-pending PCT Application Serial No. WO2011/011404 entitled an "Congestion Detection, Curtailment, Storage, and Dispatch Module," filed on Jul. 20, 2010 which all claim the benefit of U.S. Provisional Patent Application Ser. No. 61/255,678, entitled a "Proximity Based Home Energy Management System and Method" and filed on Oct. 28, 2009, as well as U.S. Provisional Patent Application Ser. No. 61/235,798 entitled an "Alternative Energy Asset Management System with Intelligent Data Framework Capabilities", filed on Aug. 21, 2009.

FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to home systems, and more particularly to an energy management system and method.

BACKGROUND

[0003] Current energy management systems take a passive role to residential energy management. For example, consumers lack energy awareness and are typically left with having to evaluate a monthly bill to determine how much energy was consumed. Additionally, consumers lack transparency into what the leading causes of energy consumption are at their residences. Some utility companies are providing energy display only technologies that will allow consumers to see what the current price of energy may be. However, such displays take a passive role to conservation, and leaving it up to the consumer to manually curtail their use.

[0004] In certain regions, information infrastructure is lacking to enable utility companies and customers to access real-time energy consumption. For example, some regions have smart meters that are capable measuring and reporting consumption data. However, there is a lack of communication and analytical infrastructure to allow utility companies to analyze future demand and schedule energy production. For example, some utilities are providing demand response systems that react to load levels, and force curtailment on residential, industrial, and commercial customers. Such programs have not been well received as they typically inconvenience the end user.

BRIEF DESCRIPTION OF THE DRAWINGS

[0005] It will be appreciated that for simplicity and clarity of illustration, elements illustrated in the Figures have not necessarily been drawn to scale. For example, the dimensions of some of the elements are exaggerated relative to other elements. Embodiments incorporating teachings of the present disclosure are shown and described with respect to the drawings presented herein, in which:

[0006] FIG. **1** illustrates a block diagram of an energy management system and energy transmission system according to an aspect of the disclosure;

[0007] FIG. **2** illustrates a energy management system operable to manage energy at a site according to an aspect of the disclosure;

[0008] FIG. **3** illustrates a flow diagram of a method of managing energy at a site according to an aspect of the disclosure;

[0009] FIG. **4** illustrates a block diagram of a controller according to an aspect of the disclosure;

[0010] FIG. **5**A illustrates a block diagram of a mobile device operable to be used with an energy management system according to another aspect of the disclosure;

[0011] FIG. **5**B illustrates a block diagram of an energy management user interface according to another aspect of the disclosure;

[0012] FIG. **6**A illustrates a block diagram of an energy management system according to another aspect of the disclosure;

[0013] FIG. **6**B illustrates an energy management user interface according to an aspect of the disclosure;

[0014] FIG. **6**C illustrates an energy management user interface according to another aspect of the disclosure;

[0015] FIG. **6**D illustrates a diagram of a plurality of zones defined by an energy management system according to another aspect of the disclosure;

[0016] FIG. **7** illustrates an energy management user interface according to an aspect of the disclosure;

[0017] FIG. **8** illustrates an energy management system interface operable to report energy usage and savings information according to a further aspect of the disclosure;

[0018] FIG. **9** illustrates an energy management system interface operable to access and edit user and site information according to a further aspect of the disclosure;

[0019] FIG. **10** illustrates an energy management scheduling user interface operable to schedule energy use at a residential site according to a further aspect of the disclosure;

[0020] FIG. **11** illustrates an wireless thermostat user interface operable according to an aspect of the disclosure;

[0021] FIG. **12** illustrates a block diagram of a wireless thermostat according to a further aspect of the disclosure;

[0022] FIG. **13** illustrates a block diagram of an energy network bridge according to a further aspect of the disclosure;

[0023] FIG. **14** illustrates a block diagram of a demand response system according to a further aspect of the disclosure;

[0024] FIG. **15** illustrates a block diagram of a aggregate demand schedule system according to a further aspect of the disclosure; and

[0025] FIG. **16** illustrates a flow diagram of a method of managing energy use at a residence according to a further aspect of the disclosure.

[0026] The use of the same reference symbols in different drawings indicates similar or identical items.

DETAILED DESCRIPTION OF THE DRAWINGS

[0027] The following description in combination with the Figures is provided to assist in understanding the teachings disclosed herein. The following discussion will focus on specific implementations and embodiments of the teachings. This focus is provided to assist in describing the teachings and should not be interpreted as a limitation on the scope or applicability of the teachings. However, other teachings can certainly be utilized in this application. The teachings can also be utilized in other applications and with several different types of architectures such as distributed computing architectures, client/server architectures, or middleware server architectures and associated components.

[0028] Devices or programs that are in communication with one another need not be in continuous communication with each other unless expressly specified otherwise. In addition, devices or programs that are in communication with one another may communicate directly or indirectly through one or more intermediaries.

[0029] Embodiments discussed below describe, in part, distributed computing solutions that manage all or part of a communicative interaction between network elements. In this context, a communicative interaction may be intending to send information, sending information, requesting information, receiving information, receiving a request for information, or any combination thereof. As such, a communicative interaction could be unidirectional, bidirectional, multi-directional, or any combination thereof. In some circumstances, a communicative interaction could be relatively complex and involve two or more network elements. For example, a communicative interaction may be "a conversation" or series of related communications between a client and a server—each network element sending and receiving information to and from the other. The communicative interaction between the network elements is not necessarily limited to only one specific form. A network element may be a node, a piece of hardware, software, firmware, middleware, another component of a computing system, or any combination thereof.

[0030] For purposes of this disclosure, an energy management system, network device, or any combination thereof can include any instrumentality or aggregate of instrumentalities operable to compute, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize any form of information, intelligence, or data for business, scientific, control, entertainment, or other purposes. For example, an energy management system, network device, or any combination thereof can include any combination of a personal computer, a PDA, a consumer electronic device, a media device, a smart phone, a cellular or mobile phone, a smart utility meter, an advanced metering infrastructure, a smart energy device, an energy display device, a home automation controller, an energy hub, a smart energy gateway, a set-top box, a digital media subscriber system, a cable modem, a fiber optic enabled communications device, a media gateway, a home media management system, a network server or storage device, an energy substation, a vehicle charging station, a renewable energy production device, a renewable energy control device, an energy storage management system, a smart appliance, an HVAC system, a water pump, a heat pump, a hot water heater, a thermostat, an energy controller, an irrigation system, a lighting system, an alarm system, a smart power outlet, an energy detection device, a power measurement device, a power measurement unit (PMU), an air handler, a wireless air damper, a humidity control system, a heat and motion sensing device, a smart power outlet, a switch router, wireless router, or other network communication device, or any other suitable device or system, and can vary in size, shape, performance, functionality, and price.

[0031] According to an aspect, an energy management system can include memory, one or more processing resources or controllers such as a central processing unit (CPU) or hardware or software control logic. Additional components of the energy management system can include one or more storage devices, one or more wireless, wired or any combination thereof of communications ports to communicate with external devices as well as various input and output (I/O) devices, such as a keyboard, a mouse, pointers, controllers, and display devices. The energy management system can also include one or more buses operable to transmit communications between the various hardware components, and can communicate using wireline communication data buses, wireless network communication, or any combination thereof.

[0032] As used herein, a wireless energy network can include various types and variants of wireless communication configurable to manage energy at a site, including associated protocols or enhancements thereto including, but not limited to, any combination or portion of, IEEE 802.15-based wireless communication, Zigbee communication, INSETEON communication, X10 communication protocol, Z-Wave communication, Bluetooth communication, WIFI communication, IEEE 802.11-based communication, WiMAX communication, IEEE 802.16-based communication, various proprietary wireless communications, or any combination thereof.

[0033] As described herein, a flow charted technique, method, or algorithm may be described in a series of sequential actions. Unless expressly stated to the contrary, the sequence of the actions and the party performing the actions may be freely changed without departing from the scope of the teachings. Actions may be added, deleted, or altered in several ways. Similarly, the actions may be re-ordered or looped. Further, although processes, methods, algorithms or the like may be described in a sequential order, such processes, methods, algorithms, or any combination thereof may be operable to be performed in alternative orders. Further, some actions within a process, method, or algorithm may be performed simultaneously during at least a point in time (e.g., actions performed in parallel), can also be performed in whole, in part, or any combination thereof.

[0034] As used herein, the terms "comprises," "comprising," "includes," "including," "has," "having" or any other variation thereof, are intended to cover a non-exclusive inclusion. For example, a process, method, article, system, or apparatus that comprises a list of features is not necessarily limited only to those features but may include other features not expressly listed or inherent to such process, method, article, system, or apparatus. Further, unless expressly stated

to the contrary, "or" refers to an inclusive-or and not to an exclusive-or. For example, a condition A or B is satisfied by any one of the following: A is true (or present) and B is false (or not present), A is false (or not present) and B is true (or present), and both A and B are true (or present).

[0035] Also, the use of "a" or "an" is employed to describe elements and components described herein. This is done merely for convenience and to give a general sense of the scope of the invention. This description should be read to include one or at least one and the singular also includes the plural, or vice versa, unless it is clear that it is meant otherwise. For example, when a single device is described herein, more than one device may be used in place of a single device. Similarly, where more than one device is described herein, a single device may be substituted for that one device.

[0036] Unless otherwise defined, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this invention belongs. Although methods and materials similar or equivalent to those described herein can be used in the practice or testing of embodiments of the present invention, suitable methods and materials are described below. All publications, patent applications, patents, and other references mentioned herein are incorporated by reference in their entirety, unless a particular passage is cited. In case of conflict, the present specification, including definitions, will control. In addition, the materials, methods, and examples are illustrative only and not intended to be limiting.

[0037] To the extent not described herein, many details regarding specific materials, processing acts, and circuits are conventional and may be found in textbooks and other sources within the computing, electronics, and software arts.

[0038] In accordance with an aspect of the disclosure, an energy management system is disclosed. The energy management system can include a database configured to store site report data received from a plurality of residential sites using a wireless home energy network at each site. According to an aspect, each residential site can include a thermostat accessible to the wireless home energy network. The energy management system can also include a processor operably coupled to the database and configured to access the site report data, detect a current temperature set-point of the thermostat at a first residential site, and detect a first seasonal profile of the thermostat. The processor can also detect a current operating mode of a HVAC system operably coupled to the thermostat, and determine a thermostat schedule of the thermostat using the first seasonal profile and the current operating mode of the HVAC system.

[0039] FIG. **1** illustrates a block diagram of an energy management system, illustrated generally at **100**, according to an aspect of the disclosure. Energy management system **100** can include an energy source **102** configured to generate energy that can be coupled to an energy transmission system **104** to satisfy a load or demand at a first site **106**, second site **108**, third site **110**, or any combination thereof. Energy transmission system **104** can be configured to be coupled to one or more of first site **106**, second site **108**, third site **110**, or any combination thereof.

[0040] According to an aspect, first site **106** can include a distributed energy generation (DEG) asset **112**. DEG asset **112** can include various types of energy producing assets such as a natural gas generator, fuel cell generator, solar array, solar concentrator, wind turbine generator, battery array, electric vehicle, hydro-power generator, any type of generator, or any combination thereof capable of outputting energy to energy transmission system **104**.

[0041] According to a further aspect, second site **108** can include a virtual capacity generation (VCG) asset **114**. VCG **114** can include an energy consumption device configured to reduce energy consumption or load placed on energy transmission system **104** during various periods. For example, VCG asset **108** can include equipment located a commercial facility, industrial facility and the like. According to another aspect, second site **102** can include a retail center having energy consuming devices that can be managed to reduce energy consumption. In other forms, second site **108** can include a residential site having VCG assets that include energy consuming devices such as an HVAC system, heat pump, hot water heater, lighting systems, entertainment systems, refrigerators, or any type of electricity consuming device or system, or any combination thereof. According to a further aspect, third site **110** can include a combination of a assets such as DEG asset **116** and a VCG asset **118**.

[0042] According to another aspect, first site **106** can be coupled to server **120** using an Internet or broadband connection **122**. Second site **108** can be coupled to server **120** using a second Internet or broadband connection **124**. Third site **110** can be coupled to server **120** using a third Internet or broadband connection **126**. Various other types of connections can also be deployed by energy management system **100** as needed or desired.

[0043] According to another aspect, portions or combinations of energy transmission system **104** can be used within one or more markets such as ERCOT, Southwest Power Pool (SPP), California Independent system operator (CAISO), Western Electric Coordinating Council (WECC), other grids or markets, future national or regional grids, operators, councils, or any combination or portions thereof can be accessed using energy management system **100**.

[0044] According to a further aspect, energy management system **100** can utilize energy management information (EMI) to manage energy production, consumption, curtailment, load shedding, purchase decisions, demand response decisions, or any combination thereof. For example, EMI can include any combination of data sources such as real-time congestion data, energy transmission line operating conditions, syncrophasor data, firm owned alternative energy generator operating status, non-firm owned alternative energy generator operating status, locational marginal pricing data, congestion revenue rights data, energy storage capacity, stored energy output capacity, real time energy pricing data, historical energy pricing data, real time nodal demand data, historical nodal demand data, real time zonal demand data, historical zonal demand data, external market demand data, historical external market demand data, nodal price data, real time energy price data, real time energy demand data, historical energy demand data, historical energy price data, firm owned alternative energy generator data, non-firm owned alternative energy generator data, est. firm owned alternative energy generator output schedule, estimated non-firm owned alternative energy generator output schedule, macro environmental data, micro environmental data, real-time grid congestion data, historical grid congestion data, renewable energy credit information, carbon credit cap and trade pricing information, fixed and variable costs for operating alternative energy generators, production tax credit (PTC) pricing information, investment tax credit (ITC) information, federal grant

information, credit-to-grant comparison analysis data, PTC to ITC analysis data, interest/finance data for alternative energy generators, asset depreciation schedules, available solar and wind output capacity, distributed energy production scheduling data, feed-in tariff data, baseline energy generator data, load utilization data, transmission efficiency data, congestion right revenue data, priority dispatch data, federal renewable portfolio standard (RPS) data, state renewable portfolio standard (RPS) data, net-metering data, current or forecasted % coal production data, current or forecasted % natural gas production data, current or forecasted % green house gas production data, current or future coal pricing data, current or future natural gas pricing data, current or future oil pricing data, current or future energy transmission pricing data, forecasted transmission price setting events, virtual capacity data, historical site performance data, seasonal weather and performance data, aggregate scheduling demand data, collaborative demand response data, historical device consumption data, forecasted device consumption data, or any combination thereof.

[0045] FIG. **2** illustrates an energy management system, illustrated generally at **200** and configured to be used at a site **202** according to an aspect of the disclosure. Site **202** can include a residential site, and industrial site, a manufacturing site, a commercial site, or any combination thereof. According to an aspect, energy management system **200** can include a server **204** located at a remote location that can be communicatively coupled to a network **206**. According to a further aspect, site **202** can include a controller **216** capable of connecting to a wireless thermostat (TSTAT) **208**, an associated mobile device **210**, one or more smart appliances **212**, a distributed energy generating asset **214**, or any combination thereof. In a form, controller **216** can establish a wireless energy network **242** using a wireless communication described herein. Various combinations of networks and variants thereof can also be deployed by controller **216** to establish wireless energy network **242**.

[0046] According to a further aspect, mobile device **210** can communicate with controller **216** using a WIFI or 802.11 based communication, Bluetooth communication, Zigbee communication, or various other wireless communication, or any combination thereof. According to a further aspect, mobile device **210** an communicate with an information network **240** using a subscriber based wireless data communication network such as a 3G network, 4G network, EDGE network, a cellular network, WiMAX, other wireless data communication, or any combination thereof. According to a further aspect, site **202** can include a gateway **218** configured as a broadband gateway such as a DSL gateway, cable system gateway, fiber optic gateway, or any combination thereof.

[0047] According to another aspect, energy management system **200** can include an advanced metering infrastructure (AMI) gateway **242** configured to communicate with a smart metering device **250**. Smart metering device **250** can include a utility or power company owned metering device and can be configured to communicate using a wireless network such as a cellular network, a mesh network, WiMAX network, or any combination thereof. According to an aspect, controller **216** can communicate with AMI gateway **242** using an AMI network **248** communicated by AMI gateway **242**.

[0048] According to a further aspect, energy management system **200** can include server **204** configurable to include various energy management logic, modules, interfaces, database sources, or various combinations thereof to manage energy use at site **200**. Server **204** can also include a processor **222** that can be configured as multiple processors having one or more processing cores as needed or desired, one or more databases **224** that can be internal or external to server **204**, and memory **226** configurable to store data. According to an aspect, server **204** can be located in a single location however multiple locations, and server configurations including cloud computing, distributed computing, dedicated computing, or any combination thereof can be deployed. According to an aspect, controller **216** can include portions or all of server **204** and can deploy some or all of the capabilities of server **204**.

[0049] According to another aspect, server **204** can include a site interface **220** operable to be coupled to network **206** and gateway **218** to communicate data between site **202** and server **204**. Server **204** can also include a mobile client interface **226** that can be coupled to a wireless telecommunications communication gateway such as a WAP gateway and the like. According to an aspect, mobile client interface **226** can communicate with one or more mobile devices **210**, using information network **240** or another data network provided by a wireless telecommunications provider. Mobile client interface **226**, mobile device **210**, an information network **240**, or various combinations thereof can include secure connection capabilities such as SSL connections or other carrier supported secure connection capabilities. Server **204** can also include an energy price monitor **228**, a demand response module **230**, an efficiency rating module **232**, a proximity detection module **234**, a scheduling module **236**, an energy savings module **238**, a messaging module **240**, or any combination thereof.

[0050] According to an aspect, energy price monitor **228** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to monitor energy pricing of site **202**.

[0051] According to an aspect, demand response module **230** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to manage demand response preferences and capabilities of site **202**.

[0052] According to an aspect, efficiency rating module **232** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to determine an efficiency rating, thermal response, virtual capacity capabilities, performance data, or various other of site **202**.

[0053] According to an aspect, proximity detection module **234** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to detect a location of mobile device **210** relative to site **202**, and modify operating conditions of site **202** based on a proximity of mobile device **210** to site **202**.

[0054] According to an aspect, scheduling module **236** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to schedule energy use or operations of one or more energy consuming devices at site **202**.

[0055] According to an aspect, energy savings module **238** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to determine a past or forecasted energy savings of site **202**. In a form, server **204** can include user account login information at a utility company or energy provider that can enable a user to gain access to meter data. As such, energy savings module **238** can pull EMI data stored at a third party website, and output past or forecasted energy savings of site **202**.

[0056] According to an aspect, messaging module **240** can be deployed by processor **222** and can access EMI stored within database **224** or a remote data source to communicate messages. For example, messaging module **240** can use an email address, mobile device identifier, SMS gateway data, network device identifier data, IP address of controller **216**, IP address of gateway **218**, IP address of AMI gateway **242**, or any combination thereof to communicate messages or other energy management information.

[0057] According to a further aspect, energy management system **200** and controller **216** can access consumption data at site **202** using AMI gateway **242**. For example, controller **216** can include a wireless communication module (not expressly illustrated in FIG. **2**) such as a Zigbee communication module (e.g. 802.15.4), WIFI module, Bluetooth module or various other wireless modules, or any combination thereof. Controller **216** can include one or more profiles stored within a memory device (not expressly illustrated in FIG. **2**) configured to include data that will enable controller **216** to join AMI gateway **242**. For example, a profile can include various attributes to initiate or establish communication using one or more security levels as needed or desired.

[0058] According to a further aspect, energy management system **200** can be used with an energy management application accessible or deployed by mobile device **210** or other computing device. For example, the energy management application can be used to control TSTAT **208**, one or more smart appliances **212** or various other devices at site **202**. A user can access the energy management application using mobile device **210** or other computing device and read the current settings, operating conditions, or various other types of energy management information associated with site **202**. For example, a user can view if TSTAT **208** and an associated HVAC system (not expressly illustrated in FIG. **2**) is on or off, a mode such as heat, A/C, or fan, or any combination thereof. In other forms, the user can use the energy management application to access multiple thermostats or zones at site **202**. According to this form, the energy management application may access multiple thermostats of different manufacturers. Although the energy management application has been described in the context of accessing TSTAT **208**, it should be understood that other network devices, smart appliances, lighting systems, or any other energy consuming or network accessible device or any combination thereof can be accessed using the energy management application.

[0059] According to a further aspect, mobile device **210** can include a mobile device application that can upload location data to server **204**, controller **216**, TSTAT **210**, smart appliances **212**, various other devices capable of receiving location data, or any combination thereof. For example, in a particular form mobile device **210** can report a current location using a location application program interface (API) of mobile device **210**, and can upload location data to server **204** using mobile client interface **226**. Server **204** can then deploy proximity detection module **234** to determine whether one or more operating conditions should be altered at site **202**. For example, proximity detection module **234** can include rules based logic to determine if an operating condition of a resource at site **202** should be altered. For example, if a user is greater than two miles away from site **202**, and is moving away from site **202**, server **204** can generate a control action report to be communicated to site **202**. For example, a control action report can include adjusting TSTAT **208** up a specific number of degrees relative based on the distance and direction a user may be from site **202**.

[0060] According to a particular aspect, a user may have previously established an upper setting limit a user would like an internal temperature to reach at site **202** without having an associated HVAC unit turning on. The upper setting limit can be sent to TSTAT **208** based on how far a user may be from site **202**. A lower limit can be established for a heating unit as well. These limits can be entered using mobile device **210**, a web-based user interface, or any combination thereof.

[0061] According to another aspect, server **204** can characterize site **202** to determine operating characteristics and performance data of site **202** and associated energy consuming devices at site **202**. For example, server **204** can use efficiency rating module **232** to monitor performance data at site **202**. Performance data can include measured performance data detected by controller **216**, performance specifications of an energy consuming device that can be based on a model number or other identification data of the device, the size or square footage of site **202**, efficiency improvements or specifications of site **202**, various other EMI data, or any combination thereof. As performance of an energy consuming device may be detected, an energy alert can be sent using messaging module **240**. In another form, an energy alert can be sent to a third party to initiate a service call at site **202**. For example, one or more third parties may subscribe to a service to buy leads based on an energy consuming devices performance eroding. Server **204** can include a lead generation module (not expressly illustrated in FIG. **2**) that can be communicated using messaging module **240** to a subscriber such as a service company, appliance provider, and the like.

[0062] In another form, performance data can be used to determine when to adjust an operating condition of an energy consuming device based on a schedule, proximal location of the user and mobile device, in response to a demand response event, in response to a consumer setting of a desired operating condition based on an energy savings mode (e.g. low, med, high), or any combination thereof.

[0063] According to a particular aspect, controller **216** can be configured as a plug-device that can be plugged directly to a wall socket or other power receptacle and can include various components (not expressly shown in FIG. **2**). Controller **216** can also include a network interface or Ethernet port, one or more USB interfaces or mini-USB interfaces, an SDIO slot, additional data or plug interfaces, or any combination thereof. Controller **216** can include an internal or external AC, DC, AC to DC converter power module, or any combination thereof to power controller **216**. According to an aspect, controller **216** can be provided as a small form factor unit to allow for easy installation, use, and discretionary placement. For example, controller **216** can include a plug computer based on Marvell Corporation's Kirkwood® microprocessor, Part Number 6281 and associated components. In another form, controller **216** can include a plug computer including specifications described in "Sheeva Plug Development Kit Reference Design", version 1.1, and previous versions which are herein incorporated by reference. Other processors having various other speeds and supporting components can also be used. According to an aspect, controller **216** can include various buses that can be used to install one or more wireless modules. For example, controller **216** can include a UART bus interface that can be used to interface a Zigbee module, WIFI module, Bluetooth Module, various other modules or combinations thereof. Various other buses can also be used

including but not limited to a USB bus, a SPI bus, an SDIO bus, a mini-USB bus, or any combination thereof. Controller **216** can include buses that can be located internal or external to a housing of controller **216**.

[0064] According to an aspect, energy management system **200** can include one or more network devices, such as TSTAT **208**, smart appliances **212**, or various other network devices installed at a residential site such as a home or residence. Controller **216** can establish a wireless energy network **242** capable of communicating with a network device at site **202**. Energy management system **200** can also include server **204** disposed remotely from site **202** and capable of generating a control action report to control the network device. Controller **216** can also be located at site **202** including a residential site. Controller **202** can be in communication with server **204**. According to an aspect, controller **202** can establish initiate a plurality of operating status requests of the network device, and receive device data in response to at least one of the operating status requests. Controller **202** can further generate a site report including the device data, and initiate a communication of the site report to server **204**. During the communication of the site report from controller **202** to server **204**, controller **202** can detect an availability of a control action report at server **202** in conjunction with the communication of the site report. As such, a secure connection can be initiated from site **202** to communicate site reports and receive control action reports without having to have server **204** initiate a communication with site **202**.

[0065] According to another aspect, server **202** can generate control action report prior to a site report upload, in association with a site report upload, or any combinations thereof. For example, one or more control action reports can be generated and queued in advance of a site report upload. In other forms, a control action report can be generated during a site report upload. In yet another form, a control action report can be generated in response to information uploaded within the site report. As such, various combinations of control action report generation techniques can be deployed as needed or desired.

[0066] According to an aspect, energy management system **200** can be used to generate a control action report in response to a distance mobile client **210** may be from site **202**. For example, site **202** can include a network device, such as TSTAT **208**, joined to wireless energy network **242**. According to an aspect, controller **216** can be configured to establish wireless energy network **242** using a wireless mesh network and initiate a plurality of operating status requests. For example, controller **216** can access TSTAT **208** using wireless energy network **242** at a first operating status request interval. Controller **216** can be used to generate a site report that can include device data of TSTAT **208** at a site report interval. According to an aspect, a site report interval can be the same interval as the first operating status request interval. In other forms, each interval can be different. For example, the first operating status report request interval can be set to thirty seconds and the site report interval can be set to sixty seconds. As such, two cycles of data can be acquired. Various combinations of intervals can be used as desired.

[0067] According to a further aspect, controller **216** can initiate a communication of site report to a remote server such as server **204** using gateway **218**. For example, gateway **218** can include a residential broadband connection **206** capable of establishing a secure gateway connection between site **202** and server **204** using a public communication network. According to an aspect, residential broadband connection **206** does not include a cellular communications based network.

[0068] In another form, control data can be provided in response to a detection of a travel direction and a distance between mobile device **210** having location reporting device, and site **202**. For example, as a user of mobile device **210** is moving away from site **202**, server **204** can detect a direction and distance mobile device **210** may be from residential site **202**. Server **204** can then determine if a control action should be generated. For example, as mobile device **210** moves away from residential site **202**, TSTAT **208** setting can be adjusted up during a warm or summer season (or down during a cold or winter season) to reduce energy consumption. Other network devices can also be adjusted as needed or desired.

[0069] According to a further aspect, energy management system **200** can use energy pricing monitor **228** to generate a control action report. For example, energy pricing monitor **228** can be configured to detect energy pricing within an energy market, and initiate curtailing use of a network device, such as TSTAT **208**, smart appliance **212**, other network devices at site **202**, or any combination thereof. For example, energy pricing monitor **228** can output a control action report in response to an unfavorable pricing condition, and further upon the detection of a travel direction and a distance between mobile device **210** and site **202**. In another form, energy pricing monitor **228** can also initiate use of one or more network devices at site **202** in response to a favorable pricing condition, and a detection of a travel direction and a distance between mobile device **210** and residential site **202**. In this manner, a user's travel direction, distance, and current energy pricing within a market can be used to determine how energy consumption can occur at site **202**.

[0070] According to a further aspect, energy management system **200** can also use demand response module **230** to detect a demand response condition and respond accordingly. For example, demand response module **230** can be used to detect a grid condition favorable to a demand response event and detect a profile preference setting of an user or site manager of site **202**. For example, a user or site manager can set a profile to always participate, not participate, or have a request sent to collaborate on whether to participate. Other profile settings can also be used such as determining an economic or monetary value to a user or site manager if participating in a demand response event. For example, a favorable grid condition can include an increase in the price of energy due to an undersupply of energy within an energy transmission system or market (not expressly illustrated in FIG. **2**). In another form, a favorable condition can include an oversupply of energy purchased by an energy provider of site **202**. Additionally, a high demand period can be detected and the oversupply of energy can be increased using a demand response event. In another form, a favorable grid condition can include a time interval when transmission pricing to use an energy transmission system may be determined. As such, an energy provider would receive an economic benefit from reducing load when the transmission rate or rate for using transmission lines would be determined. Various combinations of favorable grid conditions can be detected as needed or desired in association with determining a demand response event to curtail energy use at site **202**.

[0071] According to an aspect, energy management system **200** can use demand response module **230** configured to detect an energy capacity of site **202** having a residence. For

example, demand response module **230** can detect a grid condition favorable to a demand response event, and can also detect a preference of an resident or owner of the residence to participate in demand response events. Demand response module **230** can also determine an energy capacity of site **202** using historical device consumption data received in a site report, and forecasted device consumption data. Control data can then be generated to alter an operating condition of the network device in response to the grid condition and the preference of the owner and the energy capacity of site **202**.

[0072] According to a further aspect, server **204** can determine an energy capacity of site **202** using device data received in association with site reports received from site **202**. For example, site report data can be used with efficiency rating module **232** to determine a virtual generation capacity or energy reduction capacity of site **202**. Upon detecting an available capacity, demand response module **230** can output a curtailment action to be used within a control action report to be communicated to site **202**. For example, a curtailment action can include an updated control data to alter a current operating condition of one or more network devices connected to wireless energy network **242** at site **202**.

[0073] According to a further aspect, controller **216** can be configured to detect a new set-point value within a control action report, and identify TSTAT **208** to be adjusted to the new set-point value. In some forms, multiple wireless thermostats can be accessed via wireless energy network **242** and adjusted as desired. Controller **216** can communicate a different set-point values to each of the wireless thermostats. Controller **216** can initiate an outputting of new set-point values to TSTAT **208** and others using wireless energy network **242**.

[0074] According to an aspect, energy management system **200** can use proximity detection module **234** to detect a distance mobile device **210** may be from site **202** including a residential site. For example, proximity detection module **234** can access location data stored within database **224** and provided by mobile device **210** using mobile client interface **226**. Proximity detection module **234** can further detect mobile device **210** within a first zone (e.g. less than one (1) mile from the site, less than three (3) miles from site, greater than five (5) miles from site, etc.). Proximity detection module can further detect a current thermostat setting of TSTAT **208**, and an indoor temperature detected at site **202** and communicated within a site data report communicated from site **202**. Proximity detection module **234** can then determine a percentage adjustment to adjust a current setting of TSTAT **208**, and output the percentage adjustment as a new set-point value to be used within a control action report. For example, if mobile device **210** can be detect as being greater than three (3) miles from site **202**, TSTAT **208** can be adjusted to within 75% of the maximum setting in a summer season, or minimum setting in a winter season. As such, a site **202** can be managed based on a user's proximity to a site, which zone a user may be located in, and current seasonal schedule or setting being used at a site **202**.

[0075] According to another aspect, energy management system **200** can include TSTAT **208** configured as a wireless thermostat capable of joining wireless energy network **242** operable as a wireless home energy network. According to an aspect, TSTAT **208** can be configured to not include an enabled local programming schedule configured to control an HVAC system of site **202**. For example, TSTAT **208** can include sufficient memory to store a set-point value, but may be not include scheduling capabilities at TSTAT **208**. As such, a simplified user interface of TSTAT **208** can be deployed. For example, if TSTAT **208** includes a scheduling feature, energy management system **200** can be used to disable the scheduling feature located at TSTAT **208**. As such, TSTAT **208** can be considered a non-programmable thermostat capable of connecting to wireless energy network **242**, and set-point values or other control actions can be received using wireless energy network **242**. In this manner, scheduling use of TSTAT **208** can be provided using on-line or web application based scheduling tool.

[0076] According to a further aspect, controller **216** can be further configured to initiate joining TSTAT **208** to wireless energy network **242** using a unique identifier of TSTAT **208**. A unique identifier of TSTAT **208** can be received from server **204** and a local schedule and or scheduling capabilities of TSTAT **208** can be disabled. In this manner, an overall design complexity of a thermostat can be reduced and scheduling capabilities can be provided using a schedule created within a network environment and output by controller **216**, server **204**, mobile device **210**, or any combination of sources capable of providing schedule information or control action data to TSTAT **208**.

[0077] According to another aspect, energy management system **200** can also use scheduling module **236** to schedule use of a network device located at site **202** and capable of connecting to wireless energy network **242**. Additionally, multiple user schedules can be stored within database **224** and used by site **202**. For example, scheduling module **236** can be used to detect a first user schedule accessible to controller **216**. The first user schedule can include a first schedule event configured to alter an operating condition of a network device such as TSTAT **208**, smart appliance **212**, or other energy consuming network devices. According to an aspect, the first user schedule can be operably linked to mobile device **210** having a location detection device. The first user schedule can be used or not used based on a distance mobile device **210** may be from residence **202**. In this manner, as user returns to residential site **202**, a user schedule can be activated and used.

[0078] According to another aspect, energy management system **200** can include a second user schedule accessible to controller **216**. For example, a second user schedule can include scheduling data to schedule a second schedule event configured to alter an operating condition of a network device at site **202**. The second user schedule can be operably linked to a second mobile device having a location reporting device (not expressly illustrated in FIG. **2**). For example, the second user schedule can be used or not used based on a distance a second mobile device may be from site **202**. In another form, mobile device **210** may not be located at site **202**, but a second mobile device may located be at site **202**. In this form, a second user schedule may be based on detecting the second mobile device located at site **202**. According to an aspect, the second user schedule can be disabled when the second user leaves the site **202** and a proximity mode can be enabled. According to a further aspect, a second user schedule may not be operably linked to any mobile device. As such, controller **216** can use a second user's schedule to schedule events in response to a detection of mobile device **210** being a distance away from residential site **202**. In this manner, multiple user schedules and proximity control of energy use can be deployed at a common site.

[0079] According to an aspect, energy management system **200** can also include controller **242** capable of detecting

advanced metering infrastructure (AMI) wireless network **248** output by smart metering device **250**. For example, smart metering device **250** can include, or can be coupled to, AMI/Gateway **242** capable of outputting AMI wireless network **248**. In other forms, smart metering device **250** can be configured to output AMI wireless network **248** directly.

[0080] According to another aspect, controller **216** can be configured with a communication interface (not expressly illustrated in FIG. **2**) to enable joining AMI wireless network **248**. In this manner, controller **216** can gain access to AMI wireless network **248** to receive AMI data. In a further aspect, controller **216** can use the AMI data to alter an operating condition of a network device at site **202**, output AMI data using a display of a network device, communicate AMI data to server **204**, or any combination thereof. According to a further aspect, controller **216** can communicate the AMI data with site report data as a site report to server **204**. As such, AMI data and site report data can be used at server **204**.

[0081] According to a further aspect, controller **216** can connect to AMI wireless network **248** at a first security level, and alter an operating condition of a network device connected to wireless energy network **242** at a second security level. According to an aspect, wireless energy network **242** can be deployed at the same security level as AMI wireless network **248**, can be deployed at a different security level than AMI wireless network **248**, or any combination thereof.

[0082] According to a further aspect, a user or site profile can be used to enable use of control actions initiated or received by AMI wireless network **248**. For example, a site manager or user can establish a profile setting to enable or disable a utility company to alter an operating condition of a network device at a residence. As such, controller **216** can access a profile setting prior to connecting to AMI wireless network **248**, enabling use of a control action received using the AMI wireless network **248**, or any combination thereof. In other forms, controller **216** can access server **204** to detect profile settings.

[0083] According to another aspect, energy management system **200** can also include controller **216** configured to communicate using a Zigbee network and a WIFI network. For example, controller **216** can include a ZigBee enabled communication device (not expressly illustrated in FIG. **2**) capable of initiating wireless energy network **242** at site **202** that includes a residential site. Controller **242** can also include a WIFI enabled communication device (not expressly illustrated in FIG. **2**) capable of initiating WIFI network **244** operable to be coupled to mobile device **210** that may be WIFI enabled, or other WIFI enabled devices, systems, or any combination thereof.

[0084] According to a further aspect, controller **216** using WIFI network **244** can be used to alter an operating condition at site **202** in response to detecting mobile device establishing or losing a WIFI connection to WIFI network **244**. For example, a user schedule can be enabled when a WIFI connection of mobile device **210** can be detected, and an operating condition of one or more network devices connected to wireless energy network **242**. As mobile device **210** leaves site **202**, an operating condition of one or more network devices can be altered upon a detection of a WIFI connection of mobile device **210** to WIFI network **244** being lost.

[0085] According to an aspect, mobile device **210** can communicate with controller **216** to access site data, site reports, control action data, AMI data, or various other types of EMI data available using WIFI network **244**. According to an aspect, mobile device **210** can initiate control actions, control action reports, or combinations thereof that can alter an operating condition of a network device coupled to wireless energy network **242**. According to a further aspect,

[0086] According to another aspect, controller **216** configured with a WIFI communication device can enable a connection to a home computer system, laptop computer, Netbook, home server, IPAD®, home automation system, router, or other WIFI enabled system or devices (not expressly illustrated in FIG. **2**), or any combination thereof. For example, a user can use an IPAD to access controller **216**. Using WIFI network **244** and wireless energy network **242**, a user can receive operating status information, initiate control actions of network devices, schedule energy use, or various other energy management activities. In some forms, controller **216** may not have access to network **206**. Controller **216** can include portions or all of the capabilities of server **204** to schedule energy use, generate scheduling data, access site data, generate control action data, or any combination thereof. As such, in some instances network **206** may not be established (e.g. in a new construction site, etc.), or if a network failure or an absence of network availability occurs, a user can access network devices at site **202** and manage energy use.

[0087] According to another aspect, controller **216** can detect when mobile device **210** connects to WIFI network **244** and alter an operating condition of a network device coupled to wireless energy network **242**. For example, as mobile device **210** moves or transitions away from site **202**, controller **216** can detect a signal loss and alter an operating condition at site **202**. According to an aspect, controller **216** can include control action data to be used upon detecting a signal loss. In other forms, controller **216** can report the signal loss to server **204** within, or external to a site report. Server **204** can then determine a control action (if any) in response to a reporting of the WIFI signal being lost.

[0088] According to a further aspect, server **204** can initiate a text message using messaging module **240** to be sent to mobile device **210**. User of mobile device **210** can then view the text message and respond to alter an operating condition at site **202**. For example, a user can place site **202** in proximity mode which will enable an energy efficiency schedule associated with the user. In other forms, a user can access an energy management application accessible to mobile device **210** and alter an operating condition at site **202**. Various combinations of messaging communications (e.g. SMS text, email, social network messaging, social network postings, etc.), message content, and various combinations thereof can be used to inform a user of mobile device **210** that an operating condition can be altered in response to mobile device **210** not being connected to a WIFI signal at site **202**, a detection of mobile device **210** being a distance from site **202** using location detection, or any combination thereof.

[0089] According to another aspect, controller **216** can also connect to mobile device **210** using WIFI network **244** and communicate information using mobile device **210** and information network **240**. For example, mobile device **210** can connect to information network **240** which can be a wireless subscriber based information network. Mobile device **210** can receive energy management information from an information source accessible to information network **240**. According to an aspect, mobile device **210** can include a mobile energy management application that can be used to access server **204** or other information source(s). Mobile

device **210** can be used to upload information such as a site report, network device data, operating statuses, or various other types of information that can be obtained at site **202** using wireless energy network **242**. According to a further aspect, mobile device **210** can receive information such as control action reports, control data, environmental data, scheduling data, user profile data, network device profile data, Zigbee based profile data, WIFI data, configuration data, network device data updates or firmware updates, controller data updates or firmware updates, or various other types of EMI data or any combination thereof that can be communicated to mobile device **210** using information network **240**. Mobile device **210** can then communicate received information to controller **216** using WIFI network **244**. Controller **216** can use the received information to manage energy use at site **202**.

[0090] According to a further aspect, controller **216** can be configured to request profile data, profile updates, network device updates, or any combination thereof of a network device using WIFI network **244**, wireless AMI network **248**, network **206**, or any combination thereof. For example, controller **216** can detect a Zigbee enabled network device at site **202**. Controller **216** can identify unique identifier of the Zigbee enabled network device, and request a profile of the Zigbee enabled network using WIFI network **244**. For example, mobile device **210** can request a Zigbee profile using information network **240**. In another form, a home computer, laptop computer, IPAD® etc. can request the Zigbee profile using network **206**. In another form, controller **216** can access wireless AMI network **248** to request a Zigbee profile. As such, controller **216** can be configured to request profile data, profile updates, network device updates, various other types of information to manage network device, or any combination thereof of a network device using one or more networks accessible to controller **216**.

[0091] According to a further aspect, controller **216** can be incorporated into a network device. For example, controller **216** and TSTAT **208** can be combined into the same unit. Controller **216** can also include an 802.15.4 based wireless communication device (not expressly shown in FIG. **2**) operable to establish wireless energy network **242**. Controller **216** can also include an 802.11 based wireless communication device (not expressly shown in FIG. **2**) operable to communicate with mobile device **210**. Using the 802.11 based wireless communication device, controller **216** can communicate with gateway **218** having a residential broadband wireless router capable of establishing an 802.11 based wireless communication network at site **202**. In this manner, combining controller **216** and TSTAT **208** can lead to a reduction in the number of separate devices deployed at site **202**.

[0092] According to a further aspect, controller **216** can include a processor (not expressly illustrated in FIG. **2**) configured to deploy a web server capable of enabling web services. For example, controller **216** can connect to WIFI network **244** and a computer system at site **202**. The computer system can include a browser configured to access an IP address of the web server of controller **216** to manage one or more network devices coupled to wireless energy network **242**. In a particular form, controller **216** can include a scheduling tool configured to be output by the web server and accessible using WIFI network **244**. According to a further aspect, controller **216** can be coupled to mobile device **210** and controller **216** can be configured to enable access to a subscriber based wireless information network **240** using a connection to the 802.11 based wireless communication device of controller **216**.

[0093] FIG. **3** illustrates a method of managing energy at a site according to an aspect of the disclosure. Portions or all of the method of FIG. **3** can be used with portions or all of the energy management systems, devices, or apparatuses disclosed herein, or any other type of system, controller, device, module, processor, or any combination thereof, operable to employ all, or portions of, the method of FIG. **3**. Additionally, the method can be embodied in various types of encoded logic including software, firmware, hardware, or other forms of digital storage mediums, computer readable mediums, or logic, or any combination thereof, operable to provide all, or portions, of the method of FIG. **3**.

[0094] The method begins generally at block **300**. At decision block **302**, the method detects whether an energy network has been established. For example, a wireless energy network can be established and can include one or more networks that can be used to manage energy use at a site. According to an aspect, a wireless energy network can be established using a wireless enabled controller located at a residence. At decision block **302**, a detection of an energy network, AMI enabled network, WIFI enabled network, Zigbee enabled network, WiMAX network, or any other type of energy network, or any combination thereof can be detected. If at decision block **302**, one or more networks may not be detected, the method can proceed to decision block **304**. At decision block **304**, the method can detect if there is an AMI network available. If at decision block **304** there is an AMI network available, the network can proceed to block **306** and the AMI network can be joined. For example, the AMI network can include a specific protocol and security level to establish communication or allow a joining of the network. For example, the AMI network may require an encryption key-based security that can require specific keys, certificates, etc. to enable access. According to another aspect, the AMI network may include a smart grid based security described in Smart Grid standards. As such, various combinations of joining the AMI network can be deployed. Upon joining the AMI network, the method can proceed to decision block **308**.

[0095] In some forms, an AMI network may be available and the method can be modified to determine whether to join the AMI network. If at decision block **304**, an AMI network may not be detected (or may not be joined), the method can proceed to decision block **308**. At decision block **308**, the method can detect if a WIFI network (e.g. 802.11 based network) may be available. If a WIFI network is not detected or is not available, the method can proceed to block **310** and a WIFI network can be established. For example, a controller, network device, smart appliance, or various other types of energy consuming devices can include a WIFI communication device capable of initiating a WIFI network. As such, at block **310** a WIFI network can be established and the method can proceed to block **312**. If at decision block **308** a WIFI network exists, or if a WIFI network should not be established, the method can proceed to block **312**. In some forms, an additional WIFI network can be established at block **310** and the method can be modified to allow a bridging between the two WIFI networks.

[0096] According to an aspect, at block **312** an energy network can be established to manage one or more network devices. For example, an energy network can include a wireless energy network that is based on a Smart Grid standards

and protocols such as a Zigbee based protocol. Various other types of communication can also be used to establish an energy network. An energy network can be established by outputting a wireless network at a site to enable a network device to join the energy network.

[0097] Upon establishing an energy network, the method can proceed to block **314** a network device capable of connecting to the energy network can be detected. For example, a network device can include a Zigbee enabled communication device capable of joining a Zigbee enabled energy network. A unique identifier of the network device can be detected and a profile can be obtained at block **316**. In some forms, a unique identifier can be previously obtained by a controller deploying the energy network. For example, a unique identifier can be obtained from a server accessible to a controller, via a WIFI or other network accessible to a controller, or any combination thereof. In other forms, an external information source can be capable of providing a unique identifier, or a list of unique identifiers to identify a valid network device that can be joined to the energy network. A controller can then use the unique identifier, and the profile, to establish or join the network device to the energy network.

[0098] In another form, a profile of a network device may not be immediately available, or may have been revised. As such, a profile can be obtained using a WIFI network, an AMI network, an Internet or broadband network, or any combination thereof. For example, a unique identifier, a model number, a serial number, a device class identifier, or any combination thereof that can be communicated to an external source or information network to obtain a profile can be used. A profile can then be identified and used to join the network device to the energy network.

[0099] According to a further aspect, obtaining a profile at block **316** can include initiating a request using a controller and an information network accessible to a mobile device capable of communicating with a WIFI network at a site. For example, a profile can be provided by connecting a mobile device to a wireless information network such as a 3G data network, 4G data network, or other subscriber based wireless information network. The mobile device and then communicate the profile to the controller using the WIFI network at the site. The controller can then receive the profile and use at least a portion of the profile within the energy network.

[0100] According to an aspect, upon obtaining a profile, the method can proceed to block **318** and the network device can be joined to the energy network. For example, the network device can be joined at a security level that is different than required by an AMI network, or other secure network. In some forms, the network device can be joined to multiple networks or combination of networks while joined to the energy network. In other forms, the network device can be joined to only the energy network. In still other forms, an AMI network connection can be established to enable an AMI network to access the network device, and the network device can unjoin or disconnect the AMI network and join the energy network. In another form, information received from the AMI network can be used to alter an operating condition of the network device using the energy network. Various other permutations of joining a network device to an energy network or other networks can also be realized as needed or desired.

[0101] According to a further aspect, a network device can join the energy network using a standardized profile, such as a Zigbee profile. In addition, a network device can be joined using a profile modifier that can extend the functionality of the Zigbee profile associated with a specific network device. For example, a controller establishing the energy network can access profile modifiers to enhance use of a specific network device.

[0102] According to a further aspect, an AMI network can be joined during a period of time, and then the energy network can be joined during a separate time period. As such, various combinations of joining a network device to one or more networks can be used as needed or desired to manage energy use of a network device. Additionally, the method can be modified to join additional network devices to one or more networks as needed or desired. Upon joining one or more network devices, the method can proceed to block **320** and then to decision block **322**.

[0103] At decision block **322**, the method can detect whether a proximity mode associated with a site and energy network is enabled or disabled. For example, proximity mode can include associating a mobile device with a residential site, and automatically controlling a network device based on detecting a location the mobile device may be from the residential site. One or more mobile devices associated with a site can include a location reporting device capable of outputting a location report. The location reporting device can use various technologies to report location including GPS, GPRS, cell tower triangulation, or various other location reporting technologies. In another form, a location reporting device of a mobile device can also include a WIFI radio capable of being connected to a WIFI network. As such, a mobile device can be connected to a WIFI network at the site using a WIFI connection, and as a WIFI connection is established or lost, a proximity mode can be enabled and disabled accordingly.

[0104] According to an aspect, at block **322** if proximity mode is enabled, the method can proceed to block **344** as described below. If at decision block **322** proximity mode may not be enabled, the method can proceed to decision block **324** to detect if a user schedule is available. For example, a user schedule can include an event schedule to control one or more network devices. According to an aspect, one or more user's can create a schedule that can be accessed by a controller, and used to control one or more wireless thermostats or other network devices that can be joined to the energy network. According to a further aspect, a user schedule can be linked to a mobile device of the user. In some forms, the mobile device can include a location detection device configured to report locations of the mobile device.

[0105] According to an aspect, if a user schedule may not be detected, the method can proceed to block **356** and an event can be identified. For example, an event can include one or more programmed events that can be created and accessed at a specific time, date, period, or other to alter an operating condition of a network device. For example, a user may not have provided a user schedule to schedule energy use of a hot water system at a residence. As such, a default schedule can be accessed to identify an event and schedule or manage use of the hot water heater. For example, an event can include decreasing a hot water heater ten (10) degrees at midnight. Another event can include increasing a hot water heater fifteen (15) degrees at five (5) A.M. In another form, a network device can include a wireless thermostat that can be used to control an HVAC system based on a time of day or other attribute. For example, a weather forecast can be determined, and an event can be scheduled to adjust a wireless thermostat accessible to the energy network. Various other environmental conditions, grid conditions, user profiles, device profiles,

energy pricing, or any combination of energy management information can be used to schedule or create an event.

[0106] Upon identifying an event, the method can proceed to decision block **326** and detect whether to schedule the event. For example, if an event is configured to be scheduled at a specific time of day, the method can detect the event at decision block **326**. If an event may not be detected, the method can proceed to decision block **322** and repeats.

[0107] According to an aspect, if at decision block **326** an event should be scheduled, the method can proceed to block **328** and the event can be scheduled. For example, a network device can be identified, an operating condition to be altered can be identified, a time of day to alter the operating condition can be identified, a period of time to alter an operating condition can be identified, a device profile can be used, or any combination of data that can be used to schedule an event can be used. According to another aspect, the method can include initiating a scheduled event at block **328** using a portion of a programming schedule stored within a memory of the controller associated with the energy network. For example, portions of event data can be communicated from a remote server to the controller, and used with a programming schedule stored within the controller to schedule an event. In this manner, one or more sources can be used alone or in combination to schedule events.

[0108] According to a further aspect, upon scheduling the event, the method can proceed to block **330** and a control action can to be communicated to a network device. For example, a control action can include control action data or device data sufficient to alter an operating condition of a network device. In some forms, data formatted according to a standard profile, such as a Zigbee Home Automation profile, Zigbee Energy Profile, and the like. In other forms, control action data can include a device identifier, a message format to output a message, a parameter or feature of a network device to alter, an updated set-point or operating condition of the network device, a network or security key, a date and time, or any combination thereof.

[0109] According to an aspect, the method can proceed to block **332** and the control action can be output to the energy network as an outgoing message and received by the network device as an incoming message. For example, the network device can detect the outgoing message communicated within the energy network using a unique identifier of the network device.

[0110] At block **334**, upon the network device receiving the incoming message, a control action can be extracted from the incoming message and the operating condition at the network device can be altered using the control action data. For example, an dishwasher may be turned on, a clothes washer or dryer turned on, lights within a home can altered, a thermostat can be adjusted, a hot water hear can be adjusted, or various other types of control actions can be initiated as needed or desired.

[0111] At block **336**, network device data can be obtained from the network device using the energy network. For example, a network device can receive a request to output operating status information as network device data to the energy network. In other forms, the network device can be enabled to periodically publish status information to the energy network and received by the controller. Upon outputting the network device data, the method can then proceed to block **338** and a site report can be generated. For example, a site report can include network device data received from one or more network devices accessible to the home energy network. Site report data can be stored locally to the controller, and processed to confirm an updating of the control action. The site report data can be stored within a site report and communicated to a remote server configurable to receive and process the site report data within a site report. According to an aspect, a site report can be communicated to a remote server configurable to receive site reports from the controller using a broadband connection initiated by the controller. Other forms of communication can also be used to communicate a site report as needed or desired. Upon generating a site report, the method can proceed to decision block **302**.

[0112] According to an aspect, if at decision block **322** proximity detection may be enabled, the method can proceed to block **344** and a location report can be received. For example, a location report can include location data output from a location reporting device such as a mobile device. In other forms, a location report can be generated in response to a detection that a mobile device having a WIFI radio may be within range, or out of range, of the WIFI network at the site. As such, the method can be used to alter an operating condition of the network device using the energy network in response to detecting the location reporting device establishing or losing a WIFI connection to the WIFI network.

[0113] According to an aspect, the method can proceed to decision block **346** and can detect if a location change has occurred. If a location change has not occurred, the method can proceed to block **348** and detects whether to alter an operating condition. If an operating condition of one or more network devices may not be altered, the method can proceed to block **350**, and to block **322**.

[0114] According to another aspect, if at decision block **346** a location change may be detected, the method can proceed to block **350** and detects a distance a location reporting device may be from an associated site. The method can then proceed to block **352** and detects the direction of the mobile device. For example, if the distance has increased from a previous location reported, the method can detect that a user may be moving away from a site. In other forms, a detected direction can include moving toward a site, moving away from a site, or not moving at all.

[0115] Upon detecting a direction, the method can proceed to decision block **348** and detects whether to alter an operating condition of a network device. For example, in addition to detecting a distance and direction a user may be from a residence, various other types of information can also be used to alter an operating condition. For example, data such as real time velocity data, average velocity data, estimated length of time a user may take to return to a site, thermostat scheduling data, network device scheduling data, site report data, real-time weather condition data, traffic condition data, user driving pattern data, daily driving pattern data, GPS mapping data, home energy efficiency ratings, demand response data, curtailment data, energy pricing data, grid condition data, various other types of EMI, or any combination thereof.

[0116] Upon detecting an operating condition to alter, the method can proceed to block **354** and initiates a control action. For example, a server remote to a site can be used to generate a control action that can be included within a control action report and communicated to the controller at the site. In a form, the control action report can be communicated in association with an upload of a site report. According to another aspect, a control action can be generated by the controller. For example, a location and direction of a mobile

device can be identified and communicated to the controller. The controller can then determine whether to generate a control action using the location data and direction data, and possible other data as needed or desired. The method can then proceed to block **328** as generally described above. If at decision block **348** an operating condition of a network device should not be altered, the method can proceed to block **350** and to block **322**.

[0117] According to an aspect, the method can be provided to detect a distance between the location reporting device and the site using a previously stored location of the residence and a new location of the location reporting device. At decision block **354** altering an operating condition can include altering an operating condition of the network device in response to detecting the location reporting device is traveling away from the residence. Further, altering an operating condition of the network device in response to detecting the location reporting device is traveling toward the residence.

[0118] According to another aspect, the method can be provided to detect a location reporting device at a first distance at block **350**, and at decision block **348** initiate a control action. As the location reporting device may be detected at a second distance, a second control action can be initiated. For example, a control action can include setting a first temperature set-point of a thermostat in response to detecting the first distance. The method can further be provided to detect the location reporting device at a second distance different from the first distance, and set the temperature set-point to a second value.

[0119] According to a further aspect, the method can be modified to detect an upper and lower thermostat set-point limits of a network device. For example, an upper set-point limit can include a maximum a temperature that should be reached within a site during a warm season. A set-point of a thermostat can then be determined by determining the difference between a previous set-point and the maximum set-point. In some forms, a percentage adjustment, such as 30%, 50%, 75%, etc. of the resulting difference between a maximum set-point and a base set point can be used to determine a new set-point. For example, if a thermostat is set to seventy (70) degrees and has a maximum set-point of eighty (80) degrees, the delta between the two being ten (10) degrees. A new set-point can then be generated by multiplying this delta by a percentage, such as 50%, and adding it to the current set point. In this example, a new setting of seventy five (75) degrees would be the resulting set-point. In other forms, the method can use the maximum and minimum set-points, resulting or current set-points, in association with a time of day, a distance or distances a user may be from a site, or various other data that can be used to determine a set-point using maximum and minimum set-point values.

[0120] FIG. **4** illustrates a block diagram of an energy management apparatus, illustrated generally as controller **400**, according to an aspect of the disclosure. Controller **400** can include a processor **402** and memory **404** configurable to store data. Memory **404** can be configured as on-board memory of processor **402**, or in other forms can also include expandable memory such as DDR memory, Flash Memory, EPROM, ROM, or various other forms, or any combination thereof generally illustrated as memory **404**.

[0121] According to an aspect, controller **400** can include buses **406**, **408**, **410** configured to couple data and signals to various components within controller **400**. Although illustrated as multiple buses **406**, **408**, **410**, controller **400** can include a single bus, multiple buses, or any combination thereof. Various types of bus configurations can be used as needed or desired including, but not limited to, any combination or portion of a serial bus, a parallel bus, a serial parallel bus, a universal serial bus, industry standard bus, controller area network bus, a serial peripheral bus, a universal asynchronous receiver transmitter bus, a control bus, standard digital input output bus, or any combination thereof.

[0122] According to an aspect, controller **400** can also include a communication interface **430**, an information network interface **416**, an external bus interface **420**, an application program interface **440**, or any combination thereof configurable to be coupled to one or more of buses **406**, **408**, **410** or any combination thereof. According to an aspect, any combination of interfaces **430**, **416**, **420**, **440** can be configured in any combination of hardware, software, or firmware, and can include any combination or portion of a serial bus interface, a parallel bus interface, a serial-parallel bus interface, a universal serial bus interface, industry standard bus interface, controller area network bus interface, a serial peripheral interface, a universal asynchronous receiver transmitter interface, a control bus interface, standard digital input output interface, or any combination thereof.

[0123] According to a further aspect, controller **400** can also include a power supply **412** capable of providing power to controller **400**. Power supply **412** can be an internal power supply and in other forms can be provided external to controller **400**. Controller **400** can also include a broadband device **414** configured to be coupled to a broadband network. For example, broadband device can include an Ethernet communication module, a Cable or coaxial-based communication module, and can include communication logic to receive and transmit data between controller **400** and an information network such as a LAN, WAN, local network, the Internet, and the like. Broadband device **414** can include TCP/IP communication capabilities and can also be security enabled to transmit SSL data between controller **400** and an information network.

[0124] According to a further aspect, controller **400** can also include an information network interface **416**, a wireless information network device **418**, and an external bus interface **420**. Controller **400** can also include a Zigbee enabled communication device **422**, a WIFI device **424**, an Advanced Metering Infrastructure device **426**, a support and updates module **428**, and a communication interface **430**. Controller **400** can also include an operating system **450** that can be executed by processor **402**.

[0125] According to an aspect, controller **400** can be configured to use any type or combination of wireline or wireless communication to manage energy use at a site, including, but not limited to, power-line communication, wire line communication, wireless communication, Zigbee based communication, INSETEON based communication, X10 based communication, Z-Wave based communication, WiMAX based communication, Bluetooth based communication, WIFI based communication, 802.11-based communication, 802.15-based communication, 802.16-based communication, proprietary communication, other communications described herein, or any combination thereof.

[0126] According to a further aspect, controller **400** can include a network device profile module **432**, a security module **434**, a controller module **436**, and a proximity detection module **438**. Controller **400** can also include device profiles **442**, user profiles **444**, home profiles **446**, and profile modi-

fiers **448**. One or more of the modules, profiles, or any combination thereof can be provided as encoded logic such as a ROM, PROM, EPROM, EEPROM, or various combinations thereof and accessible to processor **402** as needed or desired. In other forms, one or more of the modules, profiles, or any combination thereof can be stored within a memory device such as memory **404**, within a removable flash drive (not expressly illustrated in FIG. **4**), an external data storage device (not expressly illustrated in FIG. **4**), or any combination thereof.

[0127] According to further aspect, controller **400** can include processor **402** operable to manage energy use at a site. Processor **400** can be configured to convert an incoming message received from a wireless energy network (not expressly illustrated in FIG. **4**) into XML enabled output data. Processor **400** can also format an outgoing message to be output to a wireless energy network using XML enabled input data. According to an aspect, XML enabled input data includes a network device identifier of a network device accessible using a wireless energy network. Controller **400** can also include communication interface **430** configurable to enable access to communication device, such as Zigbee device **422**, WIFI device **424**, AMI device **426**, or any other device accessible to controller **400** and having access to a wireless energy network. According to an aspect, communication interface **430** can be configured to detect an outgoing message formatted by processor **402** and configure the outgoing message to a message bus format that can be coupled to bus **408** and a communication device such as Zigbee device **422**. For example, outgoing message can include network device data configured to be output to a wireless energy network, but processed into a message bus format prior to outputting to a communication device. Communication interface **430** can then convert the outgoing message from a message bus format to a format that can be output by a specific communication device. For example, if the outgoing message was intended to be output using WIFI device **424**, communication interface can detect that the message was to be sent on a WIFI network and can convert the outgoing message from a message bus format to a WIFI device format. Communication interface **430** can then output the WIFI device formatted message to WIFI device **424**.

[0128] According to a further aspect, communication interface **430** can be configured to detect an incoming message received from a wireless energy network using a communication device such as Zigbee device **422**, WIFI device **424**, AMI device **426**, or any other device accessible to controller **400** and having access to a wireless energy network. Incoming message can include incoming network device data received from a network device. Communication interface **430** can convert an incoming message from a communication device format to access an incoming network device data received from a network device, and output the incoming network device data using a message bus format that can be used by processor **402**.

[0129] According to another aspect, controller **400** can include a wireless data module, such as Zigbee device **422**, WIFI device **424**, AMI device **426**, or any other device accessible to controller **400** and having access to a wireless energy network. A wireless data module can be accessible to processor **402** and configured to generate profile data to be used with an outgoing message. For example, processor **402** can access network device profile module **434** and use a network device profile of a network device accessible to the wireless energy network to output a message receivable by a specific network device. Network device data can be formatted using a network device profile of a specific network type of the wireless energy network. In some forms, a network device profile may not include information sufficient to output network device data. As such, profile modifiers **448** can be provided and can include profile modification data of the network device not available within the network device profiles **442** that can be used to communicate with a network device coupled to an energy network accessible to controller **400**.

[0130] For example, device profiles **442** can include a Zigbee thermostat device profile having home automation profile data and smart energy profile data. Profile modification data **448** can be used to access additional profile information to format an outgoing Zigbee message and access a Zigbee enabled thermostat coupled to a wireless energy network accessible to controller **400**. In this manner, additional features and functionality that may not exist within Zigbee profile standards can be accessed by using profile modifier data **448**. As such, functionality of a Zigbee enabled device can be expanded beyond a standard Zigbee profile.

[0131] According to another aspect, controller **400** can include a first user profile stored within user profiles **444** and accessible to processor **402**. For example, a first user profile can include a first time schedule to operate a network device and a control setting to control the network device. User profiles **444** can also include a first user identifier to identify a first user and can also be include a network device identifier to identify the network device to control or alter.

[0132] According to another aspect, controller **400** can include a second user profile within user profiles **444** and accessible to processor **402** that is different than the first user profile. A second user profile can include a second time schedule to operate a network device and at least one control setting to control the network device. The second user profile can also include a second user identifier to identify the second user and a network device identifier to identify the network device.

[0133] According to a further aspect, processor **402** can determine when to use a first user profile or a second user profile. For example, processor **402** can access user profiles **444** to detecting the user profiles, and initiate outputting an outgoing message using the first user schedule or the second user schedule. Processor **402** can then be used to monitor when to alter the operating condition provided by the first user schedule, to an operating condition of a second user schedule. In this manner, multiple user schedules can be used by controller **400** to control a network device.

[0134] According to a further aspect, processor **402** can be used to detect an input to a network device as a user schedule is being used, and store a new setting of the network device in association with the deployed user schedule. For example, processor **402** can detect a current user profile being used, and further detect an interaction with a network device during use of a first user schedule. Upon detecting an interaction, processor **402** can initiate an update to the first user profile in response to detecting the interaction.

[0135] According to an aspect, processor **402** can be used to convert data received using broadband device **414** to a format that can be output to a wireless energy network. Also, processor **402** can also be configured to convert data received from the wireless energy network to a format that can be used by broadband device **414**. For example, processor **402** can include a Linux enabled processor configured to convert an

incoming message received from Zigbee device **422** to an XML enabled output data. Additionally, processor **402** can format XML enabled input data received from broadband device **414** to an outgoing Zigbee message that can be output using Zigbee device **422**.

[0136] According to a further aspect, controller **400** can be configured as a server and can deploy several processes of applications that can be used, including, but not limited to Ubuntu Version 9.04, Java SE Version 6, "lighttpd HTTP Server", Servlets, FastCGI, Apache log4j, Eclipse, Apache Ant, or any equivalent operating environments or software, or any combination thereof.

[0137] According to an aspect, processor **402** using a Java operating environment can initiate generation of a Java output object using XML enabled input data received from broadband device **414**. The Java output object can include network device data of a ZigBee enabled network device accessible to a wireless energy network and Zigbee device **422**. Processor **402** can further initiate generation of XML enabled output data from an incoming message received from Zigbee device **422** using a Java input object configured to accesses network device data using a network device profile stored within device profiles **422**, and a profile modifiers **448** as needed or desired.

[0138] According to an aspect, controller **400** can use communication interface **430** and API **440** to enable access to ZigBee device **422** operably coupled to bus **408** and accessible to API **440**. As such API **440** can be used by processor **402** during use of one or more modules to access Zigbee device **422**, WIFI device **424**, AMI device, **426** or any combination thereof to communicate network data using a wireless energy network. As such, processor **402** can make API calls to API **440** to access various functions of one or more communication devices **422**, **424**, **426**.

[0139] According to another aspect, controller **400**, can be used to coordinate a wireless energy network, and use data within the wireless energy network that was received from an external information source accessible to controller **400**. For example, broadband device **414** can be coupled to an information network. Broadband device **414** can further be coupled to information network interface **416** operable to access external data sources that can be communicatively coupled to broadband device **414**. Controller **400** can initiate coordinating a wireless energy network, and initiate outputting XML enabled output data as site report data to information network interface **416** to be communicated to an external data source using broadband device **414**. Site report data can include a portion or representation of network device data received by Zigbee device **422**, or other device accessing the wireless energy network. According to an aspect, controller **400** can also receive control action report data using broadband device **414**. For example, control action report data can include XML enabled input data that can be output as network device data using the wireless energy network.

[0140] According to a further aspect, controller **400** can be configured to access a wireless energy network at more than one security level. For example, processor **402** can use security module **434** configured to initiate supporting coordinating a wireless energy network at a first security level and enable access to a network device at a first security level. For example, processor **402** can initiate receipt of an incoming message using Zigbee device **422** at the first security level. Upon gaining access and communicating device data, processor **402** can disconnect the network device. In another form, security module **434** and processor **402** can then initiate access to a second network device at a second security level using Zigbee device **422**, and enable access to the second network device using the second security level. Processor **402** can initiate receipt of a second incoming message at the second security level, and upon receipt of device data disable access to the second network device. As such, controller **400** can use a single Zigbee device **422** to access multiple network devices using more than one security level.

[0141] According to an aspect, controller **400** can be used to access more than one wireless energy network. For example, processor **402** can initiate using a first wireless communication device, such as Zigbee device **422**, to coordinate a first wireless energy network. Processor **402** can also initiate using a second wireless communication device, such as a second Zigbee device (not expressly illustrated in FIG. **4**), or other wireless device, to coordinate a second wireless energy network. As such, processor **402** can access one or more network devices coupled to one or more wireless energy networks. According to another aspect, a second Zigbee device, or other wireless device can be used to join a second wireless energy network instead of coordinating the second wireless energy network. For example, the second wireless energy network can include an advanced metering infrastructure (AMI) enabled network operably associated with an AMI enabled smart meter. AMI device **426** can include a second ZigBee device, or other wireless communication device, capable of joining an AMI enabled network of an AMI enabled smart meter (not expressly illustrated in FIG. **4**). As such, smart meter data can be accessed by controller **400** as needed or desired. For example, AMI data or smart meter data can be obtained on a periodic basis and communicated in association with a site report having network device data. As such, broadband device **414**, wireless information network device **418**, or other information network devices can be used to site report data that can include AMI data acquired using controller **400**.

[0142] According to another aspect, controller **400** can use AMI device **426** to access an AMI enabled smart meter to alter an operating condition of a network device accessible to controller **400** using Zigbee device **422**. For example, AMI device **426** can include an advanced metering infrastructure (AMI) enabled interface capable of initiating access to an AMI enabled smart meter. Controller **400** can use AMI device **426** to receive AMI data from an AMI enabled smart meter. Processor **402** can be used to initiate altering an operating condition of a network device in response to detecting AMI data received from the AMI enabled smart meter. Processor **402** can further be used to detect a smart energy control request output by an AMI enabled smart meter, and initiate using the smart energy control request at the network device.

[0143] In some forms, a control request may be obviated by controller **400** by not allowing an AMI initiated control request to be enabled. For example, processor **402** can access home profiles **446** and determine whether a control action initiated by an AMI enabled smart meter should be enabled or disabled. As such, controller **400** can be used to monitor control actions being output by an AMI enabled smart meter or other utility provided system, and alter the request as desired. For example, a user may create a home profile **446** that would not allow for a curtailment action of a network device. In other forms, home profile **446** may enable a curtailment action over a period or schedule, and disable a curtailment action over another period or schedule. As such,

controller **400** can determine a valid period or schedule to enable and disable a curtailment action initiated by an AMI enabled smart meter.

[0144] According to a further aspect, controller **400** can reset an operating condition in the event an AMI enabled smart meter alters an operating condition of a network device. For example, an AMI enabled smart meter may be able to control a network device. Controller **400** can monitor an operating condition of the network device, and in the event an operating condition has been altered to a setting that is not scheduled by controller **400**, controller **400** can respond to the operating condition by notifying a user, or automatically altering the operating condition to a preferred setting.

[0145] According to another aspect, controller **400** can be used to access an information network outside of the wireless home energy network. For example, information network interface **416** can be configured to access an information network using broadband device **414**, wireless information network device **418**, external bus interface **420**, or any combination thereof. According to an aspect, wireless information network device **418** can include a subscriber based network device, or in other forms can include a WIFI network access device, or various combinations thereof. According to an aspect, wireless information network device **418** can include WIFI device **424** that can be used to access an information network. As such, WIFI device **424** can be used to access an information network, an wireless energy network, a local wireless information network, or any combination thereof.

[0146] According to an aspect, controller **400** can use WIFI device **424** to be coupled to a WIFI enabled communication device such as a mobile device, smart phone, home computer, laptop computer, Netbook, or any other WIFI enabled device capable of connecting to a WIFI network. Communication interface **430** and processor **402** can be used to enable a WIFI enabled communication device to access network device data, site data, or any combination of data accessible using the wireless energy network. Control actions can also be requested using the WIFI enabled communication device and connection to control a network device coupled to the wireless energy network accessible by controller **400**. For example, a mobile device access a WIFI network can be used to access a wireless energy network having a network device. In other forms, controller **400** can include a web server capable of communicating web services that can be accessed by a mobile device (or other system or device), via a web based environment. For example, controller **400** can output portions or all of a graphical user interface as described in FIGS. **7-10** herein, or other graphical user interfaces that can be output by a web server. As such, a user having a WIFI enable communication device can be coupled to controller **400** using WIFI device **424** and monitor, create and manage operating conditions, home profiles, user profiles, device profiles, user schedules, proximity detection, demand response preferences, energy savings preferences, other control settings, view site data, or any combination thereof. Other settings and operating conditions can be accessed, monitored, or managed as needed or desired.

[0147] According to another aspect, controller **400** can include proximity detection module **438** that can be accessed by processor **402** to enable and disable proximity control at a site. For example, proximity detection module **438** and processor can be used to detect a distance between a mobile device having a location reporting device and the site. Processor **402** can be used to identify a current operating condition of a network device, and identify an updated operating condition of the network device in response to the detected distance. Processor **402** can be used to initiate generation of an outgoing message to include an updated operating condition in response to the distance. According to a further aspect, controller **400** can be configured to receive location data using an information network having a server configured to communicate location data associated with a mobile device having a location reporting device that is associated with a site. Location data can be stored within memory **404** and used to monitor a distance and direction between a site and the mobile device. As such, controller **400** can initiate control actions using the location data, and the location data need not be stored in a server remotely located to a site. Various control actions can be generated using various types of conditions including detecting a distance, determining a control zone having a distance or interval, travel pattern of a mobile device, monitoring current and future weather data, monitoring real-time traffic data, monitoring energy pricing data, monitoring home efficiency data, or using any combination of energy management information in association with providing proximity control of a site.

[0148] According to an aspect, controller **400** can include a plug computer employing a Linux based server configured to manage energy use at a site. For example, controller **400** can include a Java enabled processor as processor **402**, memory **404** configured to store incoming and outgoing wireless energy network messages, Zigbee device **422** capable of accessing a wireless energy network, and information network interface **416** capable of initiating communication with an information network. Controller **400** can also include communication interface **430** operably coupled to bus **408** and Zigbee device **422** coupled to bus **408**. Through utilizing a Java enabled processor and Linux operating system, controller **400** can deploy a web server (not expressly illustrated in FIG. **4**) and a Java environment to handle and convert XML data received using a web server into Java objects that can be used to communicate network device data and various other types of data.

[0149] For example, processor **400** can be used to convert an incoming message received from a wireless energy network using the Zigbee device **422** into XML enabled output data. Processor **402** can format an outgoing message to be output to a wireless energy network using XML enabled input data that includes a network device identifier of a network device accessible using a wireless energy network. Communication interface **430** can be configured to detect the outgoing message formatted by processor **402** to be output using the wireless energy network, and configure the outgoing message to a message bus format to be output to communication bus **408**. In some forms, the outgoing message can include network device data configured to be output to a wireless energy network. Communication interface **430** can further detect an incoming message received from a wireless energy network that includes incoming network device data. Communication interface **430** can be used to convert the incoming message accessed from bus **408** from the message bus format to detect incoming network device data that can be output to processor **402**. Processor **402** can then be used to generate site data including the network device data, and a site report that can be communicated using information network interface **416**.

[0150] FIG. **5**A illustrates a block diagram of a mobile device, generally illustrated at **500**, according to an aspect of the disclosure. Mobile device **500** can be configured as a smart phone or handheld computer, tablet, and the like such as an I-Phone® device, a Blackberry® device, an Android® device, an IPad® or various other devices or systems. Mobile device **500** can include a processor **502**, a memory **504**, an I/O device **506** such as a keypad, touch screen, function buttons, a mini qwerty board, or any other type of input device capable providing control of mobile device **500** or any combination thereof. I/O devices **506** can also include a speaker for outputting sound, and a microphone for detecting sound. Mobile device **500** can also include a display **508** such as color LCD display, touch screen display, or any combination thereof. According to a further aspect, one of more of I/O devices **506** can be displayed within display **508** having touch screen capabilities, such as selectable GUI elements that can be used to control features, functions, or various other application of mobile device **500**. As such, mobile device **500** can be configured to use numerous applications that output graphical elements configurable to control mobile device **500** and applications accessible by mobile device **500**.

[0151] According to a further aspect, mobile device **500** can also include an energy management application **510** accessible to processor **502** and configured to enable a user to manage energy use of at a site in a mobile environment. Mobile device **500** can also include a location reporting device **515**, such as GPS technology, cell tower location technology, triangulation technology, geofencing technology, significant change technology, distance filter technology, IP based WIFI location technology such as location over WIFI, or any combination thereof. Portions of location reporting device **515** can be located within mobile device **500** however in other forms, a wireless network can include functionality that can be selectively accessed to detect a location of mobile device **500**.

[0152] According to a further aspect, mobile device **500** can also include a network interface **514** configurable to enable access to a WIFI device **516**, a Bluetooth device **518**, a ZigBee device **520**, or any combinations thereof. According to a further aspect, mobile device **500** can also include a wireless data network device **522** that can be configured with one or more RF radios capable of connecting to one or more wireless networks such as a 3G network, 4G network, PCS network, EDGE network, cellular network, or any combination thereof.

[0153] As illustrated in FIG. **5**B and FIG. **5**C, mobile device **500** can also include an energy management user interface **530** capable of being displayed within display **508**. Energy management user interface **530** can include a user information section **532** that can display various types of user data such as a location of a site being managed, an energy provider providing energy to the site being managed, an energy personality of the user based on the user's interaction with energy use at the residential site, or various other types of user profile information.

[0154] According to a further aspect, energy management user interface **530** can include a current readings section **534** configured to display a current readings and operating conditions of a site. For example, current readings can include a current inside temperature, outside temperature, proximity setting, energy alert setting, savings rate, status of network devices being managed such as lights, HVAC system, hot water heater system, sprinkler system, refrigerator system, washing machine system, distributed energy generation system such as a solar array, battery storage device, fuel cell, wind turbine generator, or any combination thereof. Other network devices can also be managed as needed or desired. Current readings section **534** can include a selectable graphical element that can be selected to access additional site information. Site information displayed within current readings **534** can be accessed from a remote server capable of managing or storing site reports that include site data and device data. In other forms, site information, current reading, operating conditions, or any combination thereof can be accessed using a WIFI device **516** of mobile device **500**.

[0155] According to a further aspect, energy management user interface **530** can include a current settings section configured to enable a user to alter an operating condition of a network device being managed. For example, current settings section **536** can include current setting of one or more thermostats at a site, settings of any other network device being managed at a site. Current settings section **536** can also include general settings to manage a site. For example, a general setting can include a proximity detection setting, a set location setting, a set travel distance setting, a demand response setting, an energy alerts settings, a savings setting, schedules, calendars, events, a vacation setting to enable a vacation schedule, or any other type of setting that can be used to manage energy consumption or network devices at a site, or any combination thereof. Current settings section **536** can also include a graphical element that can be selected to access additional settings as needed or desired.

[0156] According to a further aspect, energy management user interface **530** can include a current savings section **538** configured to enable a user to access energy savings information and adjust as needed or desired. For example, an energy savings amount obtained at a site can be realized. A user may also be able to access an energy saving selector (not expressly illustrated in FIG. **5**B) to modify an energy savings level. For example, a user can change a savings level to low, medium, high, or various other savings metrics. According to another aspect, a user may access a vacation mode (not expressly illustrated in FIG. **5**B) and alter an operating condition of a site by selecting a vacation mode using mobile device **500**. As such, various energy savings settings can be selected as needed or desired.

[0157] According to a further aspect, mobile device **500** can provide proximity updates, site report requests, site control commands, configuration data, settings, scheduling data, text messages such as SMS, MMS and others, and various other types of information or data or any combination thereof that can be used with an energy management system. According to another aspect, mobile device **500** may not have full functionality or capabilities of a smart phone or other device capable of running an application. For example, a mobile device such as a cell phone may not be capable of loading an application such as an energy management application. However, the mobile device may have sufficient functionality to allow an energy management system to contact the mobile device. For example, an adverse operating condition may be detected at a site (e.g. temperature set-point of thermostat is out of range, lights are left on, etc.). As such, the energy management system can identify the mobile device and send a message, such as a text message, an email message, or any combination thereof, capable of being received and displayed by the mobile device. In some forms, a user can receive the message and respond to the message, enabling the user to

control the operating condition of the network device at the site. For example, the user can respond to the message via a text message, an email message, or another messaging application accessible to the mobile device. As such, a mobile device that may not be able to run energy management application **510** can be used to control an operating condition at an associated site.

[0158] During operation, a user can access operating status and generate control actions to control a network device (not expressly illustrated in FIG. **5**A or **5**B) at a site. For example, mobile device can receive and send messages, such as text messages, HTTP enabled messages, XML enabled messages, email messages, data, or any combination thereof. For example, if an outside temperature at a site is increasing or forecasted to increase, and the price of energy is increasing or scheduled to increase, mobile device **500** can receive a message to inform the user of the condition. The user can respond to the message as desired. In other forms, a suggestion can be sent to the user. For example, a suggestion to increase a thermostat or indoor temperature by three degrees can be received by mobile device **500**. Upon receiving the message, the user can respond to the message using a text or other messaging technology. In other forms, a user can access energy management application **510** and initiate a control action to adjust the thermostat to different set-point. In this manner, a user can become aware of a current operating or forecasted condition in a mobile environment, and respond as needed or desired.

[0159] According to another aspect, mobile device **500** can include a portion or all of energy management application **510** running in the background, in the foreground, or any combination thereof. According to an aspect, energy management application **510** can be launched automatically when a message or energy alert may be received by mobile device **500**.

[0160] According to a further aspect, energy management application **510** can be operable to work with an energy management system to update a control action field within a database. For example, mobile device **500** and energy management application **510** can initiate updating a control field within a database to identify a control action. Energy management application **510** can further update a new set-point within the database. As such, an energy management system can generate a control action report or data during a site upload. In this manner, a user of mobile device **500** can update control setting using a remote server or energy management system, and control actions can be generated to alter an operating condition at a site.

[0161] According to another aspect, energy management application **510** can output recommendation settings of a network device to the user. For example, a user can select a low savings, medium savings, or a high savings at a residential site using current settings **536**. A user can select a savings level, and mobile device **500** can communicate a message to an energy management system associated with the site and mobile device **500** to generate a control action to alter an operating condition at a site based on a savings level setting. For example, an energy management system can calculate new settings of one or more network devices, intervals to set the network devices, start and stop times, and the like. In some instances, settings can be determined based on a forecasted weather, forecasted energy pricing, forecasted energy availability, proximity of mobile device **500** from a site, or various other types of data. Settings can be stored within a database and control actions can be initiated as needed or desired.

[0162] According to a further aspect, an energy alert message received by mobile device **500** can be used to alter or display an energy status icon, alter an application icon, alter a status within a social network, or various combinations thereof. For example, a user can then select the energy status icon using mobile device **500** and an associated application can be presented to a user to allow a user to alter an operating condition as desired. In some forms, a user's election to reduce energy consumption during peak times or other times can be fed into their social network as an energy savings message or update. A user's energy personality can also be output from mobile device or associated web service to be updated within a social network as needed or desired.

[0163] According to a further aspect, mobile device **500** can include proximity detection module **524** operably associated with energy management application **510** and location reporting device **512**. Proximity detection module **524** can be provided as a part of energy management application **510**, location reporting device **512**, may be provided as a separate module, or any combination thereof. According to an aspect, proximity detection module **524** can be used with location reporting device **512** to detect a distance mobile device **500** may be from an associated site. For example, proximity detection module **524** can be operated as a background process that periodically requests a location from location reporting device **512**. Location reporting device **512** can use various location reporting methods (e.g. GPS, triangulation, etc.) to detect a current location, and an associated API of location reporting device **512**. According to an aspect, proximity detection module **524** can request an accuracy of a location to be provided by location reporting device **512**, and a response time. For example, if a GPS signal may not be available to mobile device **500**, location reporting device **512** can be requested by proximity detection module **524** to detect a location using a triangulation technique or other technique within 500 milliseconds. In another form, proximity detection module **524** can alter reporting parameters of location reporting device **512** in response to a relative location mobile device **500** may be from an associated site. For example, mobile device **500** may be greater than five (5) miles from an associated site, and location reporting device **524** can alter a distance accuracy, response time, method used, or various other location reporting parameters that can be selected.

[0164] According to another aspect, proximity detection module **524** can be used to initiate altering an operating condition of an associated site in response to a location of mobile device **500**. For example, proximity detection module **524** can be used to detect mobile device **500** being greater than two miles away from an associated site, and a direction that is moving away from an associated site. Proximity detection module **524** can output a location and direction to energy management application **510**, and energy management application **510** can detect whether to initiate a control action at an associated site.

[0165] According to a further aspect, proximity detection module **524** can be used to detect a location at a modifiable interval (e.g. one (1) minute, five (5) minutes, etc.) to reduce the amount battery drain or power consumption of mobile device **500**. For example, as mobile device **500** may be moving away from an associated site, and an interval to access location data using location reporting device **512** can be increased (e.g. set from one (1) minute to three (3) minutes).

In another form, as mobile device **500** moves closer to an associated site, proximity detection module **524** request at location from location reporting device **512** at a shorter interval (e.g. set from five (5) minutes to (1) minute). Various combinations of intervals can be deployed as needed or desired. In other forms, energy pricing at a period of time can also be used to alter reporting of a location reporting device **512**. Various other combinations of using data to alter reporting of a location can also be used as needed or desired to reduce battery consumption or other operating conditions of mobile device **500**.

[0166] According to a further aspect, proximity detection module **524**, energy management application **510**, or another portion of mobile device **500**, or any combination thereof can be used as an energy management system. For example, an energy management system, such as energy management system **200** illustrated in FIG. **2**, energy management system **600** illustrated in FIG. **6**, an energy management system located at a site, hosted within a network, a apparatus or device capable of energy management, or any combination thereof can be used. According to an aspect, an energy management system can receive location data reported by location reporting device **512**, and alter an operating condition of mobile device **500** based on a relative location mobile device **500** may be from an associated site. As such, an energy management system can be used to alter an operating condition of mobile device **500**.

[0167] According to another aspect, sampling of location reporting device **512** can be updated using energy management application **510**, an energy server operably associated with mobile device **500**, or any combination thereof. For example, mobile device **500** can be detected by an energy management system as being between three and five miles from a site. An energy management system or application can further detect mobile device **500** traveling away from an associated site. As such, access to location reporting device **512** can be reduced thereby reducing energy consumption of mobile device **500**.

[0168] According to a further aspect, a user of mobile device **500** may enter a building where a location based signal, such as a GPS signal, may not be able to be accessed or have limited access. As such, a sampling interval of location reporting device **512** may be altered to conserve energy. Upon a user exiting a building and a location of mobile device **500** being detected, a sampling interval can be returned to a previous value or a new value as needed or desired. According to further aspect, a sampling interval can be sent to mobile device **500** from another source such as an energy management system. In other forms, updated sampling intervals can be stored within mobile device **500** and accessed as needed or desired. In other forms, a distance from a site, a sampling interval, direction, or various combinations of data can be communicated to mobile device **500** to be used to alter access to location reporting device **512**.

[0169] According to another aspect, mobile device **500** can include software trap routines to be used when a location may go undetected. For example, energy management application **510** can use proximity detection module **524** that accesses location reporting device **512** to obtain a location. However, if a location is not obtained, or invalid, or any combination thereof, a software trap routine can be used to keep the proximity module, or background process from exiting. In this manner, energy management application **510** and various modules, associated processes, or any combination thereof can be continuously run without having to receive valid location data, and terminating the background process.

[0170] According to a further aspect, mobile device **500** can incorporate various portions or functionality of energy management system **200**, controller **300**, energy management system **600**, wireless thermostat **1200**, or various other systems, apparatuses, modules, GUI's or any combination thereof described herein as needed or desired to manage energy use in a mobile environment using mobile device **500**. Additionally, mobile device **500** can use various types of data accessible to mobile device **500** including, but not limited to EMI data disclosed herein. According to an aspect, an application icon (not expressly illustrated in FIG. **5**B) can be provided in a association with energy management application **510**. For example, an icon can be used to access energy management application **510** can in some forms, can be altered to display energy consumption information, settings information or various other types of information without a user having to launch energy management application **510**. For example, energy management application **510** can alter text information (e.g. device settings, current readings, lights on/off, etc.). An example can include displaying a current thermostat setting of a thermostat at a site, altering a color of an icon based on an energy savings or consumption level, alter a color based on proximity information, display a current temperature within a site, or various combinations thereof. As such, a user need not launch an energy management application **510** to EMI data associated with a site.

[0171] FIG. **6**A illustrates a block diagram of an energy management system, generally illustrated at **600**, according to another aspect of the disclosure. Energy management system **600** can include a server **602** operable to be coupled a site **604**. Server **602** can include a processor **606** and a database **608**. Server **602** can include an external data source interface **610** that can be coupled to an external data source **612** using a network connection **614**. External data source **612** can include one or more data sources capable of providing access to EMI data, various other types of data, or any combination thereof. According to a further aspect, external data source **612** can also include third party sources. For example, an external data source **612** can include subscription based, non-subscription based, or any combination thereof of data having weather conditions, traffic conditions, grid operating conditions, wholesale energy prices, real-time energy pricing, dynamic pricing information, fixed pricing information, forecasted energy pricing, forecasted energy consumption, forecasted energy production, alternative energy production, distributed alternative energy production, zonal demand or operating conditions, nodal demand or operating conditions, or other EMI data that can be accessed using a third party.

[0172] According to a further aspect, server **602** can also include a network interface **616** that can be coupled to a network location **618** using a network connection **620**. Network location **618** can be used to access to EMI data, various other types of data, or any combination thereof. Server **602** can also use network interface **620** to access a public network, a private network, a semi-private network or any combination thereof. According to an aspect, network interface **616** can include a network communication device (not expressly illustrated in FIG. **6**) and a web server operable to enable access to the Internet or other communication network. Server **602** can also include a site interface **622** that can be coupled to site **604** using a network connection **624** operable to be coupled to a home controller **626**. According to an aspect, site interface

622 can be realized as a web services based application configured to receive information initiated by site 604.

[0173] According to an aspect, site 604 can also include a wireless thermostat, TSTAT 628, operably coupled to NVAC system, HVAC 630. Site 604 can further include a mobile device 632 associated with site 604. Mobile device 632 can be coupled to a mobile client interface 634, such as a WAP or other mobile device gateway capable of communicating using a mobile information network 636. According to an aspect, energy management system 600 can be operable to provide a first zone 638 having a first distance 640, and a second zone 642 having a second distance 644. First zone 638 and second zone 642 can be used to control TSTAT 628 and HVAC 630. For example, first zone 638 and second zone 642 can be provided as a boundary that can be determined in various ways to control one or more energy consuming devices at site 604. As shown in FIG. 6D, the energy management system 600 can also be operable to detect a first boundary 643 of the site 604 having a first boundary distance 639 and a second boundary 645 of the site 604 having a second boundary distance 641 that is different than the first boundary distance 639. The energy management system 600 can initiating a change to the operating condition of an energy consuming device at the site 604 in response to detecting a change in the distance of the mobile device 632 relative to the first boundary 643 and the second boundary 645. The energy management system 600 may detect a plurality of zones including, an on-site zone 637 including an area within the first boundary 643, a first zone 638 including an area beyond the first boundary 643 and within the second boundary 645, and a second zone 642 including an area beyond the second boundary 645. The energy management system 600 may initiate a change to the operating condition of the network device at the site 604 in response to detecting the change in the distance of the mobile device 632 relative to the on-site zone 637, the first zone 638, and the second zone 642. The mobile device 632 can be determined to be within the on-site zone 637 when the distance of the mobile device 632 relative to the site 604 is less than or equal to the first boundary distance 639. The energy management system 600 may initiate an on-site operating condition of the network device at the site 604 in response to detecting the mobile device 632 within the on-site zone 637. The mobile device 632 can be determined to be within the first zone 638 when the distance of the mobile device 632 relative to the site 604 is greater than the first boundary distance 639 and less than or equal to the second boundary distance 641. The energy management system 600 may initiate a first zone operating condition of the network device at the site 604 in response to detecting the mobile device 632 within the first zone 638. The mobile device 632 can be determined to be within the second zone 642 when the distance of the mobile device 632 relative to the site 604 is greater than the second boundary distance 641. The energy management system 600 may initiate a second zone operating condition of the network device at the site 604 in response to detecting the mobile device 632 within the second zone 642.

[0174] According to another aspect, server 602 and processor 606 can include one or more processors having one or more core processors. Server 602 can also use any combination of software modules, firmware, encoded logic, or any combination thereof to manage energy use. For example, server 602 can use a scheduling module 648, a scheduling tool module 650, a scheduling templates module 652, a control action report module 654, a site data report module 656, an efficiency rating module 658, a set-point update module 660, a proximity detection module 662, a zone update module 664, a current readings module 666, a demand response module 668, an energy savings module 670, a message module 672, an interaction detection module 674, an energy personality module 678, or any combination thereof.

[0175] According to an aspect, database 608 can be configured to store EMI data, control action data, site report data or any combination thereof. For example, database 608 can store data received from one or more residential sites associated with server 602. For example, site 604 can access TSTAT 628 using a wireless energy network deployed at site 604. Processor 606 can be configured to access site report data stored within database 608. Processor 606 can detect a current temperature set-point within the site data and an associated date and time of TSTAT 628 at site 604. Processor 606 can detect a current temperature reading at site 604, and can further detect seasonal settings stored within database 608. For example, a seasonal profile can include seasonal settings that can include settings of a winter schedule, a summer schedule, or various combinations of seasons and settings. According to an aspect, processor 606 can detect a current operating mode of HVAC 630 operably coupled to TSTAT 628, and determine a thermostat schedule to be used with TSTAT 628. For example, if HVAC 630 may be in an A/C mode, a summer profile, schedule and the like can be deployed which can include temperature settings that can be different than a winter profile. For example, scheduling module 648 can be used to determine a date, a time or time interval, thermostat setting, operating mode, or any combination thereof, and store a schedule within database 608.

[0176] According to another aspect, server 602 can also generate control action reports using control action report module 654. For example, processor 606 can initiate generation of a control action report to communicate to site 604. A control action report can be generated in various ways with various types of data and settings to control an operating environment at site 604. For example, a control action report can be generated by setting a control action field within database 608.

[0177] According to a further aspect, energy management system 600 can use seasonal settings to control HVAC 630. For example, energy management system 600 can detect an operating mode of HVAC 630 and alter a set-point in using the detected operating mode and an associated seasonal profile. For example, an updated temperature set-point can include a value between a current temperature set-point and a minimum seasonal set-point in response to the current operating mode of HVAC 630 being in a heating mode. An updated temperature set-point can also have a value between a current temperature set-point and a maximum seasonal set-point in response to the current operating mode of HVAC 630 being in a cooling mode. Server 602 can generate a control action report that can also includes settings or data generated in response to an efficiency rating of site 604, an estimated time period to generate an updated temperature reading, an updated temperature set-point, a current energy price, and a future energy price or any combination thereof.

[0178] According to another aspect, server 602 can be used to generate a control action report using proximity detection module 662. For example, processor 606 can detect a distance between a location reporting device, such as mobile device 632 and site 604. As shown in FIG. 6B, the location of the site 604 may be set using the mobile device 632. In response to

users selection of the set location setting **633** within the user interface **530** of the mobile device **632**, the processor **606** can detect the current location of the mobile device **632** and associate that location as the location of the site **604**. The processor **606** can use the location of the site **604** to calculate the distance of the mobile device relative to the site. Processor **606** can further detect a zone, such as first zone **638**, second zone **642** or additional zones as desired. The at least one of the zones may be determined using geofencing and the zones may stored in the memory **404** of the mobile device **632**. Using a detected zone, processor **606** can initiate generation of a control action report to be communicated to site **604** in response to a current zone. In this manner, various network devices (not expressly illustrated in FIG. **6**A) at site **604** can be automatically controlled on a zone by zone basis as mobile device **632** moves away from, or towards, site **604**. For example, the energy management system **600** may initiating a change to the operating condition of one or more network devices in response to detecting a change in the distance of the mobile device relative to the site **604** and the proximity setting. According to another aspect, the control of multiple devices may not be mutual exclusive wherein the energy management system **600** may alter the operating condition of one network device and not alter the operating condition of another network device. Referring to FIG. **6**C, a map **651** can be displayed within the user interface **530**. The Map **649** may include a graphic presenting the site location **651**, the first zone **653**, and the second zone **655**. The graphic may further presents the boundary of the first zone **657** and the boundary of the second zone **659**. The map **649** may also include a graphic presenting the current location **661** of the mobile device **632** and a reference **663** to the location of the mobile device **632** with respect to the zones **638**, **642**.

[0179] According to another aspect, one or more of the zones **638**, **642**, additional zones (not expressly illustrated in FIG. **6**A), or any combination thereof can be updated automatically using updated conditions. For example, processor **606** can use a zone update module **664** on a periodic basis to update zones using various types of data. For example, processor **606** can detect an efficiency rating of site **604**, detect an external temperature at site **604** from an external data source **612** or other sources, determine a real-time travel time between mobile device **632** having location reporting capabilities and site **604**. As shown in FIG. **6**B, the processor **606** can also update the zones in response to the user entering a travel distance **665** within the user interface **530**. Processor **606** can modify distance **640**, **644**, or any combination thereof. For example, the zones **638**, **642** can be automatically scaled in response to a change in the setting of the travel distance wherein at least one of the zones is enlarged in response to an increase in the travel distance. According to another example, the boundary of the first zone **638** may be defined by a first distance **640** being less than half the travel distance **665** with the second zone **642** defined by a second distance **644** being greater than half the travel distance **665**. According to another example, an efficiency rating of site **604**, external temperature at site **604**, estimated real-time travel time to or from site **604**, various other EMI, or any combination thereof can be used. Although illustrated as being sequential, zones **638**, **642** can be modified independently, together, or any combination thereof.

[0180] According to another aspect, server **602** can use proximity detection module **662** to detect when mobile device **632** may be moving away from site **604**, and adjust HVAC **630** using thermostat **628**. For example, processor **606** can detect mobile device **632** moving away from site **604**. Processor **606** can further detect a percentage change value associated with a current zone, and further detect a base set-point of TSTAT **628**. Processor **606** can further determine a difference between the base set-point, and a minimum seasonal set-point in response to a current operating mode of the HVAC **630**. For example, if the HVAC **630** is in a heating mode a percentage change can be determined to adjust use of a heating unit. The energy management system **600** may also alter the temperature set-point of TSTAT **628** in response to the location of the mobile device **632** with respect to the one or more zones **637**, **638**, **642**. The energy management system **600** may alter the temperature set-point of TSTAT **628** to an on-site temperature set-point corresponding to the on-site zone **637** in response to detecting the mobile device in the on-site zone **637**. The energy management system **600** may alter the temperature set-point of TSTAT **628** to a first zone temperature set-point corresponding to the first zone **638** in response to detecting the mobile device in the first zone **638** where the first zone temperature set-point is different from the on-site temperature set-point. The energy management system **600** may alter the temperature set-point of TSTAT **628** to a second zone temperature set-point corresponding to the second zone **642** in response to detecting the mobile device in the second zone **642** where the second zone temperature set-point is different from the on-site temperature set-point and the first zone temperature set-point.

[0181] According to a further aspect, server **602** can determine a difference between a base set-point and a maximum seasonal set-point in response to a current operating mode of the HVAC being in a cooling mode. As such, processor **606** can determine an updated thermostat set-point as a percent change based on the determined difference. Processor **606** can initiate generation of a control action report including an updated thermostat set-point to be used at site **604**.

[0182] According to another aspect, server **602** can be used to generate an aggregated demand schedule. For example, processor **606** can determine energy demand of a plurality of residences in a region using scheduling module **648**. For example, processor **606** can identify a group of residential sites within a specified region (not expressly illustrated in FIG. **6**) and access thermostat schedules of each of the residential sites within the group. Processor **606** can also aggregate scheduling data using thermostat schedules, and initiate an outputting of the aggregated scheduling data. Aggregated scheduling data can include time intervals, settings, etc. and in some forms can also include an estimate of energy consumption based on an efficiency rating of residential sites, consumption profiles, location data, or various other site attributes that can be used to calculate an aggregated demand. According to an aspect, aggregated data can be used to forecast load, energy production, virtual capacity, demand response capacity, grid congestion, or any combination of grid attributes that can use aggregated scheduling data.

[0183] According to another aspect, energy management system **600** can also include a web services enabled scheduling tool to schedule energy use at a residential site. For example, processor **606** can use scheduling tool module **650** to generate a web based or network based graphical user interface that includes a scheduling tool. FIG. **8**A-D illustrate examples of a web services enabled scheduling tool and user interfaces that can be output using scheduling tool module **650**. For example, processor **606** can output a thermostat

selector configurable to enable selection of one or more wireless thermostats located at site **604**. An event scheduler operably associated with the thermostat selector and configurable to enable a user to graphically select a utilization schedule of the one or more wireless thermostats can also be output by processor **606**. Processor **606** can also be used to update a utilization schedule to include a time of day and temperature setting. Scheduling tool module **650** can be used to control the one or more network devices that can include wireless thermostats, smart appliances and the like. Scheduling tool module **650** can be used to output an energy savings preference selector configured to graphically modify the utilization schedule, and display a resulting energy savings, a weather forecasting tool, and various other types of tools or scheduling features to assist in managing or scheduling use of a network device.

[0184] According to another aspect, server **602** can also use interaction detection module **674** to detect when a user may alter an operating mode of a network device. For example, interaction detection module **674** can detect when a user may adjust a thermostat at a specific time of the day, and suggest a modification of a utilization schedule to a user during a user access to scheduling tool output using scheduling tool module **650**. A user can then elect to have the utilization schedule updated to include the suggestion as needed or desired.

[0185] According to another aspect, server **602** and scheduling tool module **650** can be used to enable additional features and functions. As shown in FIG. **6**B, a scheduling tool can be used to display a proximity control selector **651** configured to enable and disable proximity control of a residential site, a demand response selector configured to enable and disable participation in demand response event, a vacation mode selector to enable and disable a vacation schedule, an auto update selector configured to enable an automatic update of the utilization schedule in response to a detection of a user interaction with the one or more network device, or various other controls that can be used to manage energy use at a site, or any combination thereof. According the embodiment shown in FIG. **6**B, the proximity control selector **651** may be configured to provide an automatic (AUTO) setting **667** selectable on the user interface **530**. When the AUTO setting **667** is selected, proximity detection of the mobile device **632** is automatically enabled in response to the mobile device **632** leaving the site **604**. The mobile device **632** may be detected as having left the site **604**, thus enabling proximity detection, when the distance between the mobile device **632** and the site **604** exceeds the first boundary distance **639**.

[0186] According to another aspect, server **602** and scheduling tool module **650** can be used to enable and disable demand response capabilities. For example, a scheduling tool can used to provide a demand response selector (not expressly illustrated in FIG. **6**) operable to be displayed with a scheduling tool. A demand response selector can include several settings such as an always participate selection configured to always enable a curtailment of an HVAC system in response to a demand response event, a never participate selection configured to not allow a curtailment of the HVAC system in response to a demand response event, a request participation selection configured to initiate a communication, such as an email, text message, instant message, social network message, or various combinations thereof to the user to request participation in a demand response event. A demand response selector can be operably associated with demand response module **668** to initiate demand response inquiries, analyses, and deployments.

[0187] According to another aspect, server **602** can also use scheduling template module **652** to generate utilization templates that a user can access and modify to schedule energy use. For example, a plurality of energy templates can be accessed by a scheduling tool. Templates can include a predetermined utilization schedule selectable by the user based on a user's scheduling profile. A selected predetermined utilization schedule can be modifiable by a user using a scheduling tool module **650**, and saved as needed or desired. According to an aspect, server **602** can output an on-line questionnaire or survey that a user can participate in to determine an energy template to use.

[0188] According to a further aspect, server **602** can also use energy personality detection module **678** to detect an interaction profile of a user. For example, a user may be an urban professional having a long work commute which may result in a first portion of a utilization schedule. Upon arriving at a residential site, a user may interact with their thermostat to which will result in a different portion of a utilization schedule. For example, a user may like an indoor temperature to be colder when going to bed. As such, a personality of the user while away and while at home can be used to automatically generate a user's schedule. According to another aspect, an energy personality indicia or character can be generated and output with a user's on-line scheduling tool, within a user's social network, or any combination thereof. For example, processor **606** can detect an interaction of a user with a wireless thermostat, and display of an energy personality indicia in response to the interaction. A user can then enable or disable display of the energy personality indicia within a social network such as Facebook®, MySpace®, etc. In other forms, processor **606** can be used to modify the indicia based on an overall energy savings a user has accomplished at their residential site. For example, processor **606** can use energy savings module **670** to determine an energy savings of the individual and alter the energy personality indicia accordingly. In another form, a user can set up a messaging service or account using Twitter® and the like to output energy savings updates to a subscriber base in response to an energy saving initiate, participating in demand response events, alter energy use, or various other forms. According to a further aspect, a Twitter® account or other messaging service can be used on a community basis to inform a group of individuals of energy management events. For example, an "energy action day" or "energy alerts" can be posted using a Twitter® account to subscribers and a subscriber can curtail energy use using energy management system **600** or various other energy management systems as needed or desired. Other forms of messaging or any combination thereof can be used as needed or desired.

[0189] According to another aspect, server **602** can be used to determine a sample size of residential sites and corresponding schedules to forecast energy consumption over an interval. For example, processor **606** can be used to determine a random sample size of residential sites in connection with estimating an energy consumption of a specific region such as a zip code, street or series of streets, substations supporting residential sites, node-to-node, or any combination thereof or other methods of determining a region. Upon identifying a sample size of a region, residential sites can be identified within the region. For example, processor **606** can then deter-

mine associated thermostat schedules of residential sites within the specified region using scheduling module **648**. Server **602** can output thermostat scheduling data of the plurality of sites in connection with scheduling or forecasting energy use.

[0190] According to another aspect, server **602** can also be used to enable a demand response initiated at site **604**. For example, processor **606** can use demand response module **668** to detect an enabled demand response setting of site **604**. Processor **606** can further detect a demand response event condition and enable a curtailment action of HVAC **630** if a user of site **604** has selected participation in a demand response event. An energy reduction capacity of site **604** can be determined using efficiency rating module **658**, scheduling module **648**, proximity detection module **662**, or various other modules, data sources, or any combination thereof.

[0191] According to another aspect, server **602** can also use demand response module **668** to contact individuals prior to curtailing energy use at site **604**. For example, processor **606** can initiate a demand response event request communication to communicate to the users of a plurality of sites. Processor **606** can detect a user response level to participate in a demand response event, and enable a curtailment of a corresponding HVAC system or other energy consuming devices at a site of a user electing to participate in the demand response event. In this manner, user's may not be forced to participate in demand response events but can have real-time election capabilities to participate as needed or desired.

[0192] According to an aspect, server **602** can send a text message that includes a request to participate in a demand response event. In some forms, a text message can include an agreement to pay the user to participate in a demand response event. Payment can take various forms such as credits, cash, rewards, points, contribution to education funds, discounts on energy rates, or any combination thereof. Server **602** can receive a response from using mobile client interface **634** and process the response using message module **672** to determine a desire to participate or not.

[0193] According to another aspect, server **602** can be used with scheduling module **648** to determine an aggregate capacity to reduce energy consumption. For example, processor **606** can be used to identify a group of residences within the plurality of residences and determine an energy reduction capacity of each of the residences within the group using an efficiency rating of each of the residences within the group. Upon determining an efficiency rating of each residence, processor **606** can detect other data to be used to determine an available capacity. For example, current weather conditions at each residential site can be detected, a user's energy schedule or thermostat schedule can be used, a response to text messages or emails electing to participate can be determined, grid conditions can be used, or any combination thereof. Upon estimating an available capacity, an aggregate energy reduction capacity based on the energy reduction capacity of each of the residences within the group can be determined.

[0194] According to another aspect, server **602** can use an aggregate energy reduction capacity in association with an auction. For example, processor **606** can initiate an auction of virtual energy capacity to retail energy providers electing to bid an available energy capacity. In other forms, a third party can host an auction and energy management system **600** can output an available capacity in association with an upcoming auction event, peak demand period, transmission rate determination period, or any combination thereof. For example, processor **606** can initiate an auction process to sell the aggregate energy reduction capacity to a third party, and detect a sale of the aggregate energy reduction capacity in connection with the auction process. Upon a sale occurring, processor **606** can initiate a curtailment of an HVAC system, other energy consuming devices, or any combination thereof, at each of the residences within the group.

[0195] According to another aspect, energy management system **600** can include mobile client interface **634** operable to be coupled to mobile device **632** associated with site **604**. For example, mobile client interface **634** can include a WAP gateway or other mobile client gateway to enable server **602** access to mobile device **632**. Mobile client interface **634** can be provided as a part of server **602**, however in other forms, portions or all of mobile client interface **634** can be provided by a specific wireless network provider. As such, mobile client interface **634** can be configured to communicate with a specific carrier having a WAP gateway. Mobile client interface **634** can be used to communicate EMI or control data between WAP gateway and server **602** using any combination wireless or terrestrial communication technologies. Additionally, WAP gateway can also include logic or modules that can provide mobile device users access to EMI data or control data generated by mobile device **632**, server **602**, energy management system **600**, or any portions and combinations thereof.

[0196] According to an aspect, mobile client interface **632** can receive a site readings request of site **604** from mobile device **632**. For example, processor **606** can detect the site reading request and initiate access to database **608** to retrieve site report data of site **604**. Processor **606** can format the site report data as mobile device data, and output the mobile device data to mobile device **632** using mobile device network **636**.

[0197] According to another aspect, mobile client interface **634** can receive a request from mobile device **632** to modify a current temperature set-point of HVAC system **630**. For example, processor **606** can process a received request from mobile device **632** and initiate generation of a control report using control action report module **654**. The control action report can include a reference to an updated temperature set-point communicated from mobile device **632** to mobile client interface **634**. Processor **606** can set a variable or field within database **608** to alter a set-point. Upon site **604** initiating access to server **602**, processor **606** can access a variable or field associated with site **604**, and generate a control action report or control data to be communicated to site **604** using site interface **622**. As such, upon a temperature set-point being updated at site **604**, home controller **626** can communicate a control action confirmation data, site report, status information, or various combinations thereof to confirm the updated temperature set-point. Processor **606** can output a confirmation of the updated temperature set-point to the mobile client interface **634** upon receiving a confirmation, and can output an updated temperature set-point to mobile device **632**.

[0198] According to another aspect, mobile device **632** can be used to enable and disable operating modes of one or more network devices located at site **604**. For example, mobile device **632** can include a mobile application loaded on mobile device **632** that can be used to control settings at site **604**. FIGS. **5**A and B illustrate examples of energy management application and functionality that can be used by mobile device **632** although other applications and functions can also

be deployed using mobile device **632** as needed or desire. According to another aspect, mobile device **632** can access a web based application associated with server **602** using a web browser of mobile device **632** to enable and disable operating modes or conditions at site **602**. For example, mobile device **632** can alter a proximity setting, alter one or more environmental control zones, access current readings, modify a vacation setting, modify energy use schedules, or various other operating modes or data associated with controlling or maintaining operating modes of network devices located at site **604** as needed or desired.

[0199] According to another aspect, energy management system **600**, can be used to send messages to mobile device **632** in connection with an altered operating condition at site **634**. For example, processor **606** can access site data received from site **604**, and further detect a manual input condition provided at TSTAT **628**. For example, a user may have decreased a temperature set-point of TSTAT **628**. Processor **606** can detect whether a user is at home using location data received from mobile device **632** and proximity detection module **660**. Upon detecting the condition, processor **606** can determine if it should initiate a text message indicating the manual input condition. For example, processor **606** can use message module **672** to format and output a text message indicating the condition change of TSTAT **628**, and output the text message using mobile client interface **634**. A user can then alter the condition using mobile device **632** as desired. In other forms, an email message or other electronic message can also be sent to a user. For example, a message can be displayed within a window of a computer system associated with the user. In other forms, a text message can be sent to multiple mobile devices associated with site **604**. Various other combinations of alerting a user of site **604** of a manual change to an operating condition can be used as needed or desired.

[0200] FIG. **7** illustrates an energy management user interface (EMUI), illustrated generally at **700**, according to an aspect of the disclosure. In some forms, EMUI **700** can be accessed using a mobile device, desktop computer, Netbook, laptop computer, smart phone, a energy display device, a smart thermostat, a home automation control terminal, and IPad® or any combination of devices capable of displaying energy management user interfaces.

[0201] According to an aspect, EMUI **700** can include a user information section **702** configured to display one or more user names **704**, a residential site address **706**, a mobile phone number **708** associated with residential site address **706**. User information section **702** can further display a current energy provider **710** associated with residential site address **705**, and a current best rate **712** of a third party energy provider available at residential site address **706**. An advertisement **714** section can also be displayed, and an edit details link **716** can be displayed to enable a user to access, edit, modify, delete, manage, etc. information displayed within user information section **702**. FIG. **9** described herein includes an example of a user interface that can be used to edit user information displayed within user information section **702**. User information section **702** can also display an energy personality **740** associated with hers name **704**. Energy personality **740** can also be linked to one or more social networks as needed or desired.

[0202] According to a further aspect, a current readings section **718** can be displayed within EMUI **700**. Current readings section **718** can include, for example, a current date and time section **720** with a current inside temperature and outside temperature at a residential site. Current readings section **718** can further include a current thermostat set-point **722** of a thermostat located at a residential site. More than one thermostat can be deployed at a residential site and current thermostat set-point **722** can include references such as "Main", "2", "3" or some other indicia configured to enable access to current thermostat readings of multiple thermostats at a residential site. A user can also modify the name or number of a thermostat, zone, etc. using an edit feature of thermostat set-point **722**.

[0203] According to a further aspect, a current readings section **718** can also include an energy savings level **724** configured to indicate a savings level that relates to current thermostat set-point **722**. For example, as current thermostat set-point **722** is set to a low set-point, an air conditioner unit may run more frequently and cause a low energy savings. As such, a visual indication of an energy savings can be displayed in association with a current set-point giving a user feedback on energy consumption based on a thermostat set point. In some forms, a user can adjust a thermostat set-point up or down, and an energy savings level can be altered in near real-time based on the users selection. For example, various programming languages such as DHTML, AJAX, Flash, HTML 5, and the like can be used to show a near real-time update of one or more fields within EMUI **700**.

[0204] According to a further aspect, EMUI **700** can also include a demand response notification selector **726** configured to enable participation in demand response events, disable participation in demand response events, and enable a text message (or other messages) to be sent to a user to request participation in a demand response event. According to a further aspect, EMUI **700** can also include a proximity detection selector **728** configured to enable proximity detection of one or more mobile devices associated with a residential site.

[0205] According to another aspect, EMUI **700** can also include an energy usage/savings section **730** that can display a current annual savings **732**, a current monthly savings **734**, a demand response savings **736**, and a view more data link **738**. According to an aspect, view more data link **738** can be operably associated with accessing portions or all of EMUI **800** described in FIG. **8**.

[0206] FIG. **8** illustrates an energy management user interface operable to report energy usage and savings information, illustrated generally as EMUI **800**, according to a further aspect of the disclosure. According to an aspect, EMUI **800** can include an energy usage/savings section **802**, operable to display a current annual savings **804**, a current monthly savings **808**, and a current demand response savings **808** realized by a user participating in demand response events. EMUI **800** can also include an estimated annual savings section **810**, a managed vs. unmanaged energy consumption graph **812**, and a comparative consumption graph **814**. According to an aspect, a user can select a comparison graph that includes a community graph configured to compare a user's energy consumption to others in a residential community, a state comparison graph configured to compare a user's energy consumption to others within a state, and a national graph configured to compare a user's energy consumption to a current national average.

[0207] According to a further aspect, EMUI **800** can also include a daily usage graph **816** configured to indicate energy consumption and savings on an hour-by-hour basis. For example, if a user selects a medium energy savings settings,

daily usage graph can display a daily savings in dollars, KWh or any combination thereof. Daily usage graph **816** can further include a graph indicated what the consumption would have been if energy use was left unmanaged. According to a further aspect, daily usage graph **816** can also include a day selector **818** configured to enable a user to select a day of the week to view energy consumption and savings.

[0208] According to another aspect, EMUI **800** can also include a monthly usage and savings graph section **820** configurable to output monthly energy usage and savings information of each day of the month. For example, a monthly graph can include a daily, weekly, or other pairing bar graph configured to display a monthly energy usage and savings at a residential site. A user can navigate between a month using month selector **822** and a specific month's consumption and savings graph can be displayed. In some instances, only a portion of a specific month's data may be available to be displayed. As such, only a portion of a graph may be displayed as desired. According to a further aspect, monthly usage and savings graph section **820** can also include an link to access annual savings as needed or desired.

[0209] According to another aspect, EMUI **800** can further be used to access and display performance data of an adjacent home, a similar sized home, one or more of the same or similar energy consuming devices (e.g. HVAC, hot water heater, other smart appliances), or any combination thereof. EMUI **800** can compare performance of each of the other residences and devices, and provide feedback to a user about the user's relative performance. For example, EMUI **800** can output a visual indication of power consumed, such as a graph, chart, etc. In other forms, a comparable residential site can also be displayed using EMUI **800**. For example, a same or similar sized home can be used as a baseline comparison.

[0210] In other forms, EMUI **800** can be used to enable a user access to energy efficient devices and systems, and a user can forecast energy reduction and savings through use of an energy efficient system. As such, energy consuming devices that may be introduced and have a greater efficiency rating can be identified and communicated to a consumer. According to another form, EMUI **800** can display a click-through or micro-site to allow a user to access third party product energy efficient offerings. In other forms, EMUI **800** can enable access to a "green energy" marketplace that will enable a user to review energy efficient products and services. Such products and services can be selected by a user and associated XML data, meta data, and the like can be fed into EMUI **800**. EMUI **800** can be configured to use the third party data and refresh data displayed within EMUI **800** to display an estimated saving if used at the user's residential site. As such, EMUI **800** can determine an estimate of what energy savings may be for their residential site, allowing a user to make an informed purchase decision. For example, a user may wish to add a solar array or other type of energy producing system to their residential site. EMUI **800** can be used to estimate the amount of energy that may be saved based on a user's actual historical energy use. As such, a payback period associated with purchasing can be displayed to a consumer.

[0211] FIG. **9** illustrates an energy management user interface (EMUI) operable to access and edit user and site information, illustrated generally at **900**, according to a further aspect of the disclosure. EMUI **900** can include a user profile **902** configured to display and enable a user to edit changes to user information. User profile **902** can include a user selector **904** configurable to add and remove user's associate with a site, a user name field **906**, an energy personality type field and/or indicia **908**, a social network selector **910**, a residential site address **912**, and a mobile number **914** associated with a residential site address **912**. According to a further aspect, user profile **902** can also include an energy text message alert selector **916**, a proximity detection selector **918**, and a current HVAC provider information field **920**.

[0212] According to an aspect, user selector **904** can be configured to enable a user to select a user data to edit. For example, multiple users can be associated with a residential site and a user's information can be accessed by selecting user selector **904**. In other forms, a user can log into a web site or other application and may only be able to have limited access to user specific data associated with a residential site. According to another aspect, user information selector **904** can be used to add additional users to be associated with a residential site. As such, a master user or administrator login can form (not expressly illustrated in FIG. **9**) can be provided to manage user information. In some aspects, a user profile **902** can include pre-populated information to reduce the amount of information a user may need to input. Additionally, information associated with the residential site can be accessed and used with the additional user as needed or desired.

[0213] According to a further aspect, EMUI **900** can also include an energy provider section **922** which can include retail, utility, or third party energy information. For example, a current energy provider can be displayed and a current energy rate and plan currently being used can also be displayed. Energy provider section **922** can also indicate a best rate plan at a current provider, and a best local rate available through another provider. Energy provider section **922** can also include a savings calculator element **934** capable of initiating a savings calculation of the residential site using a best available rate of a current provider, other providers, or any combination thereof. Savings calculator element **9434** can also use historical site data, scheduling data of the residential site, forecasted energy consumption, future energy pricing, or various other EMI or any combination thereof to determine annual savings. Site consumption can then be used to determine what an overall cost of energy would be when using a given rate plan. Other intervals (e.g. monthly, weekly, daily, etc.) can also be calculated as needed or desired. As such, a user can identify a plan that would align with usage habits and scheduling data at a residential site.

[0214] According to a further aspect of the disclosure, EMUI **900** can also include a user posting and reviews section **924**. User posting and reviews section **926** can include a content selector **926** capable of selecting energy blogs, green energy reviews, markets and the like. For example, as a user selects 'My Energy Blogs,' a list of energy blog titles can be displayed including a user energy blog **928** configured to enable a user to edit and publish their own energy blog. A user can publish their energy blog to an energy blog websites, social networks, third party sites, content providers, or any combination thereof. A third party energy blog **930** can also be listed within user posting and reviews section **926** allowing third party bloggers, articles, content providers, RSS feeds, Twitter® Feeds, or any combination thereof, to provide content. According to an aspect, a user can add a blog, news feed, social network, Twitter® account, etc. to user posting and reviews section **926** as desired. User selector within user posting and reviews section **924** can allow a user can to select between user content associated with a site and read/write/access privileges can be enabled and disabled accordingly.

[0215] According to a further aspect, user posting and reviews section **926** can also include a 'Green Energy Reviews' section configured to review energy saving products, environmentally friendly products, green energy producing systems, or any combination thereof. User posting and reviews section **926** can also include a 'Markets' section configured to enable a user to access green energy product websites or marketplaces having green energy products. For example, a marketplace can be used to consolidate available green energy products, such as smart appliances, and further identify third party pricing and websites selling green energy products. As such, a user can read reviews of new energy saving products and access the energy products using user posting and reviews section **926**. In some instances, EMUI **900** can be used to enable E-commerce between a posting site within markets section, green energy reviews section, retail energy providers, etc. allowing a firm hosting EMUI **900** to be paid a portion of revenue resulting from a sale.

[0216] FIG. **10** illustrates an energy management user interface (EMUI) operable to schedule energy use at a residential site, illustrated generally as EMUI **1000** according to a further aspect of the disclosure. EMUI **1000** may be illustrated in association with managing one or more user schedules, thermostats, HVAC systems, zones, sites or any combination thereof. In other forms, EMUI **1000** can be modified to schedule energy use of various energy consumption devices at a site as needed or desired. Additionally, portions or all of EMUI **1000** can be accessed using a computer system capable of accessing the Internet, can be configured as mobile application that can be used with a smart phone or handheld computer, tablet, and the like such as an I-Phone® device, a Blackberry® device, an Android® device, an IPad® or various other devices or systems, or any combination thereof.

[0217] According to an aspect, EMUI **1000** includes a thermostat display **1002** configured to enable a user to adjust a temperature of one or more thermostats located at a residential site. Thermostat display **1002** can include a date and time display, a thermostat selector **1004**, and a thermostat controller **1006**. EMUI **1000** can also include a savings selector **1008** configured to enable a user to select a low savings level, a medium savings level, or a high savings level. Savings selector **1008** can be operably associated with an estimated savings display **1010** and a scheduling tool **1012**. For example, a user can select a low savings using savings selector **1008** and an estimated savings can be calculated and displayed within estimated savings display **1010**. According to a further aspect, a user can select a savings level using savings selector **1008**. As such, resulting thermostat settings can be displayed within scheduling tool **1012** thereby providing a user a visual indication of a resulting temperature setting. According to a further aspect, savings selector **1008** can also be operably associated with scheduling tool **1012** to display more than one temperature setting at a time. For example, a low savings may result in a temperature setting of sixty-five degrees, a medium savings may result in a temperature setting of sixty-eight degrees, and a high savings level may result in a temperature setting of seventy-four degrees. Various combinations of values and display techniques can be used as needed or desired.

[0218] According to a further aspect, scheduling tool **1012** can include a seasonal schedule capable of allowing a user to schedule energy use based on a season (e.g. spring, summer, fall, winter). For example, a first site may be located in a hot climate and a second site may be located in a cold climate. As such, an air conditioner may be used more frequently during the summer months in a hot climate and can be associated with a schedule being displayed. A user can select between a seasonal schedule using scheduling tool **1012**, and a schedule can be updated accordingly to display a winter schedule. Various other seasonal schedules can be added and removed as needed or desired. In other forms, scheduling tool **1012** can be used to access a current operating mode of an HVAC system and display a seasonal schedule in response to detecting an operating mode. For example, if an HVAC system may be operating in a heat mode, a winter schedule can be displayed. Other seasonal schedules can also be displayed within scheduling tool **1012** as needed or desired.

[0219] According to a further aspect, scheduling tool **1012** can include a current inside and outside temperature display **1014**, and a schedule selector **1016** capable of displaying a user schedule of a first user, a second user, a vacation schedule, or any combination of schedules. For example, a user may use scheduling tool **1012** to schedule energy use at multiple sites. As such, scheduling tool can display a second site associated with a specific user. Additional schedules can be added as needed or desired, and access privileges also can be set by a current user using user information profile such as user profile **902** illustrated in FIG. **9** or any other privileges or logic capable of setting access privileges.

[0220] According to a further aspect, scheduling tool **1012** can also include a weekly schedule display section **1018**, and a time span display section **1020** configured within a schedule **1022**. Weekly schedule display **1018** can also be configured to show current dates or a series of dates, and can further include forecasted weather conditions of each day. A user can navigate to another week by selecting tab **1024** configurable to enable a subsequent weekly schedule to be displayed as desired. According to further aspect, schedule **1022** includes a plurality of cells generally illustrated at scheduled events **1026** that can be modified as desired to schedule energy use. Schedule events **1026** can include a time interval and setting of a network device, such as a thermostat, being scheduled. A cell can also include an indicator, such as 'adapt?' indicator **1028** to identify an auto-schedule suggestion detected by an energy management system operably associated with EMUI **1000**. For example, when a user may be at a site, a user may desire to have a temperature decreased to seventy eight degrees on Saturday prior to nine (9) P.M. As such, an auto-schedule suggestion can be detected and an adapt? indicator **1028** can be displayed to enable a user to have a schedule adapted automatically. Adaption suggestions can be provided to users in other ways and need not be limited to being displaying within schedule **1022**.

[0221] According to a further aspect, EMUI **1000** can also provide access to view templates selector **1030** that can be used to schedule energy use. For example, view templates selector **1030** can be used to display predetermined schedules within scheduling tool **1012**. A user can then modify portions of a selected template to their preference as needed or desired. In other forms, a series of questions can be asked to a user to determine a template to display. For example, scheduling tool **1012** can enable access to a short questionnaire to detect a user's day-to-day schedule. For example, a user can be an urban professional, a housewife, a single parent, a soccer mom, an empty nester, or various other demographics. As such, EMUI **1000** can be adapted to hide scheduling tool **1012** until a survey or series of questions is completed, and then display a resulting schedule within scheduling tool **1012**.

[0222] According to a further aspect, EMUI **1000** can be adapted to display a list of selectable templates and can allow a user to select and display each template. Upon identifying a template, a user can then save an identified template as a user schedule. In some forms, a user's site location can be determined in advance and templates can be generated based on a location of a site (e.g. warm climate vs. cold climate). As such, view templates can be generated based on a site profile, a user profile, user characteristics, site data, or various other types of data capable of being used to generate a template that can be used by a user.

[0223] According to a further aspect, scheduling tool **1012** can also include an add addition time span selector **1034** configured to enable a user to add an additional time span within time span display section **1020**. Scheduling tool **1012** can also include a view additional time slot selector **1032** configured to enable a user to scroll to additional time slots that may be output using scheduling tool **1012**. For example, a user can select additional time slot selector **1032** and scheduling tool **1012** can be updated to display scheduled events of each day simultaneously. In this manner, a user can scroll additional time slots and days of the week as needed or desired.

[0224] According to a further aspect, EMUI **1000** can also include a proximity detection selector **1036**. For example, a user may enable proximity detection using proximity detection selector **1036**, and energy use at a site may be altered based on a users distance to the site. A user's mobile device number can be associated with a site and can allow a user to enable and disable proximity detection selector **1036**. In some forms, proximity detection selector **1036** can be hidden, displayed, selectable, or any combination thereof in response to a user having a mobile device capable of being detected when a user is at or away from a site.

[0225] According to another aspect, EMUI **1000** can a energy alert text message selector **1038** configured to enable a text message to be sent to a user's mobile device. For example, during a high energy use day, an energy action day may be identified and a utility company or other entity may publish a warning indicating that a high energy use day may be occurring. As such, a user can receive a text message indicating the situation. In some forms, a can respond to the text message and alter their energy use schedule. For example, a user can respond to a request to alter their energy savings setting from a medium to a high. As such, scheduling tool **1012** can be modified to initiate a high energy savings schedule at a user's site. In other forms, energy alert text message selector **1038** can be used to enable a user to receive demand response requests via a text message. For example, a demand response request can include a requested time interval, new temperature setting, estimated savings, other demand response data, or any combination thereof within a text message. A user can then respond to the text message to participate, not participate, partially participate, or any combination thereof. Upon responding, a user's schedule can be modified as needed or desired.

[0226] According to a further aspect, EMUI **1000** can also include a vacation mode settings **1040** to enable a user to initiate use of a vacation mode or schedule. For example, vacation mode settings **1040** can include a vacation mode selector **1042** to turn a vacation mode on or off. Vacation mode settings can also include a schedule leave date selector **1044** and a schedule return date selector **1046**. A calendar (not expressly illustrated in FIG. **10**) can be displayed to enable a user to select an interval of dates when they will be on vacation. As such, reduced energy use can be realized by altering a temperature setting. For example, a schedule can be increased to a high energy saving mode in association with the vacation mode being selected. In other forms, a user may have input or selected a vacation schedule to be used when vacation mode may be selected. Various combinations can be used as needed or desired.

[0227] During use, upon a user accessing EMUI **1000**, EMUI **1000** can display a current date and time, and can further highlight a current cell within scheduling tool **1012** that corresponds to a current data and time. A user can select a thermostat to adjust using thermostat selector **1004**, and a schedule of a selected thermostat can be displayed within scheduling tool **1012**. A user can adjust a current set-point using thermostat controller **1006**, and a corresponding temperature within a current cell can be adjusted accordingly. In another form, a user can select a cell to be modified. For example, a user may want to modify a temperature setting or scheduled event set for Tuesday, between eight (8) A.M and five (5) P.M. As such, a user can select the appropriate cell and further adjust a temperature up or down using thermostat controller **1006**. A new setting can be displayed within the selected cell. According to a further aspect, a user can use savings selector **1008** to adjust a savings to be realized on a specific day. As such, a resulting temperature setting can be displayed within a selected cell.

[0228] In other forms, a user can select a time span cell to adjust. For example, a user can modify a current time span cell by selecting a specific cell. Upon selection of a specific cell, scheduling tool **1012** can highlight which cells may be affected by modifying a time interval. A user can then modify an interval accordingly as needed or desired.

[0229] According to a further aspect, a user can select a day of the week to modify. For example, a user can select 'MON' and a background color can be altered to indicated that each of the MON cells can be modified. In a form, a user can update each cell as desired, can alter one or more, or all MON cells using savings selector **1008** as needed or desired.

[0230] According to another aspect, EMUI **1000** can be used to activate a one or more schedules. For example, a first user schedule can be activated over a period of time and then a second user schedule can be activated over another period of time. A user can also activate a vacation schedule that include an scheduled events to optimize energy savings when nobody is present at a site. In other forms, a first user schedule can be compared to a second user schedule, and events at a site can be scheduled accordingly. For example, a first user schedule may be active during an evening time and may override a second user schedule. In other forms, a second user schedule may be activated in the morning to accommodate an individual that may remain at home during the day. As such, EMUI **1000** can be used to generate multiple schedules to automatically control energy use at a site as needed or desired.

[0231] According to an aspect, portions or all of EMUI **1000** can be provided as a hosted application that can allow a user to access site reports, historical consumption data, real-time consumption data, operating status of energy consuming devices, control interface to control energy consuming devices, a scheduling interface to schedule utilization and consumption of energy, an inventory tool that will show real-time and historic energy consumption of each energy consumption device within the home, or any combination thereof.

[0232] According to a further aspect, portions of all of EMUI **1000** can include a user interface that can report a current operating condition, and can further include control logic capable of providing a user access to a smart appliance or control system at a site. For example, if a demand response condition may be detected within an energy transmission system, EMUI **1000** can be used to output the condition to a user. A user can then alter an operating status of one or more energy consuming devices at a site.

[0233] According to another aspect, a site can include multiple users that can access and control settings at a site using EMUI **1000**. Additionally, a site can include multiple thermostats that can be managed remotely and controlled by a user. For example, a thermostat in the upper portion of a home can be displayed via a web browser or application on an mobile device such as a Blackberry®, I-Phone®, Android®, I-Pad® and the like. A user can select a thermostat using thermostat selector **1004**, and adjust the thermostat to a first setting. In some forms, the thermostat settings may have a different effect on the actual temperature within various portions of the home. As such, a user may want to select the desired temperature within at a site, and EMUI **1000** can be used to calculate thermostat settings to achieve the desired temperature. In another form, EMUI **1000** can be used with an energy management system such as energy management system **600** in FIG. **6**, or other systems. A thermal response of a zone, room, site, or any portion thereof can be determined and setting of one or more thermostats can be automatically determined to achieve a desired temperature.

[0234] In other forms, EMUI **1000** can be used in association with various types of EMI data. For example, various EMI data such as current and forecasted weather data, grid conditions, real-time pricing data, grid congestions conditions, forecasted demand, or any combination thereof of EMI data can be used to determine a setting recommendation that a user can select. In this manner, a user's lifestyle and preferences can be aligned with the real-time and forecasted conditions allowing a user to make informed energy consumption decisions.

[0235] FIG. **11** illustrates a diagram of a network device, illustrated generally as wireless thermostat **1100**, according to an aspect of the disclosure. Wireless thermostat **1100** can be used in association with an energy management system, mobile device, energy management user interface, or various other devices, systems, or any combination thereof.

[0236] Wireless thermostat **1100** can include a outside temperature display **1102**, a weather forecast display **1104**, and an inside temperature display **1106**. Wireless thermostat **1100** can also include a thermostat setting display **1108**, a temperature increase input **1110**, and a temperature decrease input **1112**. Various type of display technology having single color, multicolor, or any combination thereof can be used with wireless thermostat **1100**, including, but not limited to LED displays, TFT displays, OLED displays, LCD displays, flexible lighting displays, or any combination thereof.

[0237] According to an aspect, wireless thermostat **1100** can also include a mode switch **1114** and indicators **1116** configured to identify a mode. For example, mode switch **1114** can be placed off, heat mode, air condition model, or fan mode. An associated indicator above each mode within setting display **1116** can be illuminated in connection with an operating mode setting. In other forms, indicators **1116** can be placed behind an associated text and illuminated to indicate a current mode. For example, wireless thermostat **1100** can include a thin material that can allow a backlight, such as LED lighting to illuminate and show text. In another form, mode switch **1114** can include a push button or toggle switch to enable a back light to display and select a mode. Various other input and display methods or combinations thereof can be used.

[0238] According to a further aspect, wireless thermostat **1100** can also include a smart thermostat settings **1118**. Smart thermostat settings **1118** can be programmable settings that can display a proximity mode **1122**, a vacation mode **1124**, and a smart energy mode **1126**. Smart thermostat settings **1118** can be displayed based on a capability of a site, a current operating mode of wireless thermostat **1100**, a setting within a energy management user interface such as EMUI **1100** and the like, an operating mode of a mobile device, a location of a mobile device, an operating mode of another network device accessible to an energy network, or various other combinations of operating modes or settings accessible to wireless thermostat **1118**. For example, a user may want to activate proximity detection to control wireless thermostat **1100** (and possible other network devices) using proximity mode **1122**. As such, a user can activate proximity mode accordingly. In other forms, a user may be going on vacation and can activate vacation mode **1122**. In another form, a user may activate a smart energy mode **1126**, and an energy schedule provided by EMUI **1100**, associated settings, and the like can be deployed.

[0239] According to another aspect, wireless thermostat **1100** can include a housing **1130** can having a material that can detect when a user touches wireless thermostat **1100**. For example, housing **1130** can be operably coupled to a heat sensor, capacitive sensor, and the like configured to detect when a user touches a portion of housing **1130**. Upon detecting a user contacting housing **1130**, one or more displays or indicators of wireless thermostat **1100** may illuminate. In this manner, energy consumed by wireless thermostat **1100** can be realized by changing one or more displays from a sleep state to a display state. According to a further aspect, a portion or all of housing **1130** can include a material such as a concealing material that can include characteristics such as transparency, translucency, semi-transparency, semi-translucency, opaqueness, other types of light altering material, or any combination thereof capable of hiding one or more displays or indicators of wireless thermostat **1100**. For example, a backlight or LED can illuminate at a surface of wireless thermostat **1100** giving an appearance of having the display at or near a front surface of housing **1130**. As such, housing **1130** with a concealing material can be mounted on a wall or other location without having readings or settings persistently being displayed using a display or other indicators.

[0240] According to an aspect, temperature control mechanisms **1110** and **1112** can include a mechanism (not expressly illustrated in FIG. **11**) that can allow housing **1130** to rock or shift left and right as a user contacts mechanisms **1110** or **1112**. Other orientations can also be used. For example, wireless thermostat **1100** can mounted to a wall surface (not expressly illustrated in FIG. **11**), and a user can contact a temperature increase mechanism **1110**. Housing **1130** would rock slightly to the right. In another form, at least a portion of housing **1130** can include a switch mechanism similar to a mouse of a computer system that provides a clicking sound or a mechanical feedback when temperature control mechanisms **1110** or **1112** are engaged or touched. As such, a user can realize a visual change of display **1108**, and can further be

provided a mechanical feedback of a switching mechanism upon activation of a switching mechanism. Various other orientations to rotate housing (e.g. up/down, left/right, etc.) can be realized as needed or desired.

[0241] FIG. **12** illustrates a block diagram of a network device, illustrated generally as a wireless thermostat **1200**, according to another aspect of the disclosure. Wireless thermostat **1200** be used with wireless thermostat **1100** illustrated in FIG. **11** above or various other devices, systems, or any combination thereof described herein. Wireless thermostat **1200** can include a temperature and humidity sensors **1202**, and one or more I/O devices **1204** to allow a user to provide an input to wireless thermostat **1200**. For example, I/O device **1204** can enable a user can to select a mode (e.g. off, A/C, Heat, Fan, etc.), a smart energy mode (e.g. proximity, vacation, smart schedule, etc.), or various other features or combinations of features. Wireless thermostat **1200** can also include a power interface **1206**, and a bus interface **1208**. Wireless thermostat **1200** can also include a processor or controller **1210**, and one or more control relays **1212** to control a remote unit such as an HVAC unit, heat pump, other appliances, or any combination thereof.

[0242] According to a further aspect, wireless thermostat **1200** can also include a one or more wireless devices **1214** capable of communicating with one or more associated wireless networks, a memory **1216**, and a display interface **1218**. Display interface **1218** can be configured to engage one or more LCD displays, touch screens, one or more LEDs, or various other display technologies illustrated generally as display **1222**. Wireless thermostat **1200** can also include a precision measurement unit (PMU) **1220** configured to measure consumed by an associated network device, and a profile module **1224** that can include network protocol configuration data, user profile data, device data, seasonal profile data, or various other types of data that can be accessed during use of wireless thermostat **1200**. According to an aspect, wireless thermostat **1200** is a non-programmable thermostat that does not include an enabled programmable thermostat scheduling feature accessible by a user engaging wireless thermostat **1200**. As such, a limited amount of scheduling functionality is needed or desired within wireless thermostat **1200** and a user can use a scheduling tool such as EMUI **1000** or various other features provided herein to enable and disable use of wireless thermostat **1200**.

[0243] FIG. **13** includes a block diagram of an energy management system, illustrated generally at **1300**, according to a further aspect of the disclosure. Energy management system **1300** can be deployed at residential site **1302** and can include an energy management apparatus or controller **1302**. Controller **1302** can include portions or all of controller **400** described in FIG. **4** or any other type of system, device, apparatus, or any combination thereof capable of deploying controller **1302**.

[0244] According to an aspect, controller **1302** can include an application program interface **1306** operably coupled to a processor or logic (not expressly illustrated in FIG. **13**) of controller **1302**. Controller **1302** can include a communication interface **1306** a wireless device **1308** configured to access a first network **1314**, a wireless device **1310** configured to access a second network **1318**, and a wireless device **1312** configured to access a third network **1322**. Controller **1302** can also include a network device **1330** such as an Ethernet or other wireline communication device capable of access an information network such as a LAN, WAN, the Internet, and the like.

[0245] According to a further aspect, first network **1314** can be communicatively coupled to a smart meter/AMI device **1316**. According to another aspect, second network **1318** can be communicatively coupled to a wireless thermostat (TSTAT) **1320**. According to a further aspect, third network **1322** can be coupled to a mobile device **1324**. According to an aspect, mobile device **1324** can include a smart phone device such as a Blackberry®, I-Phone®, Android® and the like, a laptop computer system, a Netbook, an IPad®, or any other type of mobile device.

[0246] During use, controller **1302** can be used to communicate information from various networks to a wireless energy network to manage one or more network device connected to a wireless energy network. For example, second network **1318** can be configured as a wireless energy network capable of enabling communication with a network device such as TSTAT **1320**. Information can be received from information network **1332**, and processed by controller **1302** and output to TSTAT **1320** using API **1306** and communication interface **1306**. In other forms, information can be communicated from mobile device **1324** to controller **1302** using third network **1322** that may be different from second network **1318**. Controller **1302** can detect information communicated from mobile device **1324** and output information to TSTAT **1320** using second network **1318** to TSTAT **1320**. As such, controller **1302** can provide a network bridge to enable information communicated between various different types of networks.

[0247] According to an aspect, controller **1302** can include application program interface **1306** configured to use at least a portion of an incoming message communicated from an information network, an information network, a utility network or any combination thereof. For example, an incoming message can include at least a portion of a user energy management schedule. Controller **1302** can initiate altering use of a resource in response to detecting a portion of the first user energy management schedule. For example, a schedule can include altering a thermostat, lights, smart appliances, etc. Communication interface **1306** can further be operably coupled to application program interface **1306** and configured to communicate information using a wireless device.

[0248] For example, communication interface **1306** can communicate with wireless device **1310** capable of accessing a second network **1318** operable as a wireless energy network. Although illustrated as a single communication interface, communication interface can be provided as multiple communication interfaces, a single communication interface, as a multi-network communications interface, or any combination thereof. As such, multiple networks can be accessed and communicated with as needed or desired. For example, wireless device **1312** can be configured to communicate using a WIFI enable communication protocol and wireless device **1310** can be configured to communicate using a Zigbee enabled communication protocol.

[0249] According to an aspect, controller **1302** can include wireless device **1312** configured as a WIFI enabled communication device operably coupled communication interface **1306** and third network **1322** operable as a WIFI network. Application program interface **1306** can be configured to receive an energy management schedule communicated using an incoming message received from third network **1322**

as an incoming WIFI message. As such, an energy management schedule or other EMI data can be communicated from a WIFI enabled device, such as mobile device **1324** or other devices. Controller **1302** can then use application program interface **1306** to process the energy management schedule and initiate control actions to a network device accessible to an energy network.

[0250] According to another aspect, controller **1302** can receive an first energy management schedule using a first network, and receive a second energy management schedule using a second network. For example, a first energy schedule can be received using network device **1330** and can include a first user energy schedule data. A second energy schedule can be received using third network **1322** operable as a WIFI network. For example, a user of mobile device **1324** can provide scheduling data, control data, or various other energy management scheduling data. Controller **1302** can then use portions of each schedule as needed or desired, and initiate control actions using second network **1318** operable as a wireless home energy network. For example, second network **1318** can be configured as a Zigbee enabled network. As such, multiple networks having scheduling information can be accessed and scheduling data of multiple users can be used to control network devices accessible to an energy network.

[0251] According to an aspect, controller **1302** can include output control actions that have been received from more than one network to control a network device accessible to an energy network. For example, wireless device **1312** can be configured to receive control action data from third network **1322** operable as a WIFI enabled network. Control action data can be provided in association with a first user schedule using mobile device **1324**. Controller **1302** can further receive a second control action data from associated with a second user schedule, such as a utility schedule. Second control action data or a second user energy management schedule can be communicated using first network **1314** configured as an AMI enabled network and smart meter/AMI interface **1316**. Controller **1302** can then detect whether to use the second control action prior to the first control action.

[0252] According to another aspect, control action data of multiple user schedules can be communicated using communication interface **1306** provided as multiple communication interfaces. For example, wireless device **1312** can include a communication interface accessible to application program interface **1306**. Additionally, wireless device **1310** can include a communication interface accessible to application program interface **1306**. As such multiple communication interfaces can be deployed to communicate control action data of one or more user energy management schedule.

[0253] According to a further aspect, application program interface **1306** can be used to initiate use of a first control action of a first user energy management schedule prior to using a first control action of a second user energy management schedule prior to the first user energy management schedule. For example, a second user energy management schedule can include one or more control action that can have a higher priority that a first user energy management schedule. As such, controller **1302** and application program interface **1306** can initiate a control action as needed or desired based on a priority.

[0254] According to a further aspect, controller **1302** can initiate a control action or energy management schedule in response to a distance an associated mobile device **1324** may be from site **1304**. For example, a first user energy management schedule may be deployed as a first user having mobile device **1324** may be located at or near site **1302**. As mobile device **1324** moves away from site **1302** (e.g. one mile, three miles, etc.), a second user energy management schedule can be initiated and used by controller **1302**. In this manner, proximity detection of mobile device **1324** can be used to initiate a second user energy schedule.

[0255] According to another aspect, mobile device **1324** can output scheduling data, control action data, energy management data, and the like using third network **1322** configured as a WIFI enabled network. For example, mobile device **1324** can include a application or scheduling logic capable of initiating a user energy management schedule. Mobile device **1324** can encode or output control action data, and communicate the control action data, scheduling data, and the like using a WIFI protocol and messaging format.

[0256] According to an aspect, controller **1302** can include detect when mobile device **1324** may be connected to third network **1322** and modify operation of a network device accessible to controller **1302**. For example, mobile device **1324** can be coupled to third network **1322** operable as a WIFI network, or other network capable of being deployed at site **1304**. As mobile device **1324** moves away from site **1304** and a network connection to third network **1322** may be altered, controller **1302** can detect a change in connectivity (e.g. weak signal, signal is lost, connection switches to another hub, station, controller, and the like) to third network **1322**, a connection status of wireless device **1312** can be output to communication interface **1306** and accessed by application program interface **1306**. As such, controller **1302** can detect whether to alter use of a resource or network device accessible to controller **1302**. For example, mobile device **1324** may be connected to third network **1322** using a WIFI connection. As a WIFI connection is altered, controller **1302** can initiate altering an operating condition of a resources such as TSTAT **1320**, one or more wireless devices **1308**, **1310**, **1312**, or various other resources accessible to controller **1302**. For example, if a second user may be located at site **1304**, a second user energy management schedule that may be different from the first user energy management schedule can be deployed. For example, a first portion of a second energy management schedule of a second user can be enabled in response to the operating status of the resource,

[0257] According to another aspect, wireless device **1312** that may have been configured to be coupled to third network **1322** can be placed in a reduced operating condition to save power consumed by controller **1302**. In another form, proximity detection of mobile device **1324** can be initiated to detect a location of mobile device **1324** when a WIFI connection or other connection is altered. Additionally, mobile device **1324** may also alter an operating condition by disabling a WIFI connection to third network **1322**. Mobile device **1324** can also initiate location reporting of mobile device **1324**, and controller **1302** can alter an operating condition of a network device or resource in response to mobile device **1324** being at a distance from site **1304**.

[0258] According to another aspect, mobile device **1324** may be configured to enable access to TSTAT **1320** using a network connection **1330** that can include one or more wireless communication protocols. For example, a network device such as TSTAT **1320** can be coupled to mobile device **1324** using a WIFI connection, Bluetooth connection, or various other forms of wireless communication. Upon connecting to TSTAT **1320**, mobile device **1324** can be used to alter

and operating condition of TSTAT **1320**. As such, mobile device **1324** having energy management capabilities can be used to alter an operating condition of TSTAT **1320**, various other network devices at site **1304**, or any combination thereof. For example, mobile device **1324** can include an energy management scheduling tool, such as portions or all of EMUI **1000** described in FIG. **10**, to provide control inputs and scheduling data directly to TSTAT **1320**. As such, controller **1302** may not be available to output control actions (e.g. a network connection may be lost, etc.), or mobile device **1324** may have priority over controller **1302** to provide control inputs or energy managing scheduling information to TSTAT **1320**.

[0259] According to a further aspect, TSTAT **1320** can receive an input and communicate status information, operating conditions, control actions, or any combination thereof to a network resource, controller **1302**, mobile device **1423**, smart meter/AMI **1316**, or any other device, system, or apparatus, or any combination thereof. According to an aspect, TSTAT **1302** can detect is a user altered an operating condition (e.g. change mode, altered smart energy settings, etc.) and can communicate an operating status change. In another form, TSTAT **1320** can alter an operating status of another network device in response to an input to TSTAT **1320**. For example, a user may place TSTAT **1320** in a vacation operating mode. As such, TSTAT **1320** can output an updated status to another network device, controller **1302**, mobile device **1324**, or other network devices. For example, a second TSTAT may be located at site **1304** (not expressly illustrated in FIG. **13**), and placed in a vacation operating mode using a signal output by TSTAT **1320**. In other forms, controller **1302**, mobile device **1324**, or any combination thereof can be used to alter the operating condition of the second TSTAT as needed or desired.

[0260] FIG. **14** illustrates a collaborative demand response system (CDRS), illustrated generally at **1400**, according to an aspect of the disclosure. CDRS **1400** can include a server **1402** operably coupled to an information source such as a database **1404**. According to a further aspect, server **1402** can include portions or all of server **602** illustrated in FIG. **6**, or any other server capable of being deployed with CDRS **1400**. According to further aspect, database **1404** can include site data **1406**, user profile data **140**, performance data **1410**, or various other types of EMI data that can be used in association with CDRS **1400** as needed or desired. According to another aspect, CDRS **1400** can also include access to one or more external data source **1412**. CDRS **1400** can also interface with an energy buyer/auction **1414** capable of buying available capacity of CDRS **1400**.

[0261] According to a further aspect, CDRS **1402** can include a monitor **1416**, a client interface **1418**, and a site interface **1420**. According to an aspect, client interface **1418** can be coupled to a first mobile device **1422**, a second mobile device **1424**, a client system **1426**, or any combination thereof. For example, client interface **1418** can be configured as a mobile client interface operable to communicate information using a mobile network. In other forms, client interface **1418** can be coupled to a client system **1426** using an information network such as the Internet.

[0262] According to another aspect, CDRS **1402** can include site interface **1420** configured to interface with multiple sites. For example, site interface **1420** can be operably associated with first site **1428** and mobile device **1422**. In other forms, site interface **1420** can be operably associated with second site **1430** and mobile device **1424**. Site interface **1420** can also be operably associated with third site **1423** and client system **1426**. Various other combinations can also be used with CDRS **1400**.

[0263] During use, CDRS **1400** can be used to determine a desire by an owner of a site to participate in a demand response event. Server **1402** and monitor **1416** can detect a current or future demand response initiative to be deployed at a specific time. Server **1402** can detect an availability of capacity in a specific region, and initiate an inquiry with a site owner, user, administrator, etc. According to an aspect, a text message, email message or other form of electronic or wireless messaging can be initiated to detect a desire by a user to participate. Server **1402** can access site data **106** associated with a specific site to detect if a user may have a default setting to participate. In other forms, a user a user may have set a preference to be contacted via email or text message. As such, server **1402** can initiate a message and detect a desire by one or more users to participate.

[0264] According to a further aspect, server **1402** can access performance data of each site elected to participate in a demand response event. For example, historical site data of a site can be stored within database **1404**, and performance of a participating site can be determined as performance data **1410**. According to an aspect, other EMI data can be accessed from database **1404**, external data source **1412**, or any combination thereof and used to determine performance of a site. For example, current and future weather conditions can be used to determine performance of a site. Taking weather conditions into consideration, along with a thermal response or characteristic of a site, a capacity to reduce energy can be determined on a site by site basis. The overall or aggregate capacity and desire to participate can be sold to a third party, monetized by an owner of CDRS **1400**, or any combination thereof.

[0265] FIG. **15** illustrates a demand scheduling system (DDS), illustrated generally at **1500**, according to an aspect of the disclosure. DSS **1500** can include a server **1502** operably coupled to an information source such as a database **1504**. According to a further aspect, server **1502** can include portions or all of server **602** illustrated in FIG. **6**, or any other server capable of being deployed with DDS **1500**. According to an aspect, database **1504** can include site data **1506**, site schedule data **1508**, performance data **1510**, or various other types of EMI data that can be used in association with DSS **1500** as needed or desired. According to another aspect, DSS **1500** can also include access to one or more external data sources **1512**. DSS **1500** can also interface with an utility company, COOP, retail energy provider, or various other energy providers, or any combination thereof, using one or more utility schedule interface **1514**. According to an aspect, utility scheduling interface **1514** can be a standard interface however in other forms, utility scheduling interface **1514** can include a custom interface configurable to engage an existing energy company's information network, infrastructure, database, or various other components that can be used by an energy provider to access DDS **1500**.

[0266] According to a further aspect, DSS **1502** can include an aggregate demand module **1516**, a client interface **1518**, a site interface **1520**, or any combination thereof. According to an aspect, client interface **1518** can be coupled to a first mobile device **1522**, a second mobile device **1524**, a client system **1526**, or any combination thereof. For example, client interface **1518** can be configured as a mobile client interface

operable to communicate information using a mobile network. In other forms, client interface **1518** can be coupled to a client system **1526** using an information network such as the Internet.

[0267] According to another aspect, DSS **1502** can include site interface **1520** configured to interface with multiple sites. For example, site interface **1520** can be operably associated with a first site **1528** that can be associated with mobile device **1522**. In other forms, site interface **1520** can be operably associated with a second site **1530** and mobile device **1524**. Site interface **1520** can also be operably associated with third site **1532** and client system **1526**. Various other combinations can also be used with DSS **1502**.

[0268] During use, server **1502** can use EMI data to forecast energy use at sites **1528**, **1530**, and **1532**. For example, each site can include site schedule data **1508** stored within database **1504**. For example, EMUI **1000** or another scheduling tool can be used to schedule energy use at a site. Site **1508** schedule data can be used to determine what energy use may be on a site-by-site basis. An aggregate demand of a specific region, zip code, substation, grid location, etc. can also be detected. Aggregate demand module **1516** can then detect what an aggregate level of demand and scheduled demand can then be communicated to a utility company as needed or desired. In this manner, scheduling data that may not have been traditionally accessible on a site by site basis can be used to detect energy demand and schedule energy production. For example, residential sites traditionally use non-programmable and programmable thermostats that do not allow for determining schedules on a site by site basis. DSS **1500** can enable access to scheduling data of each residential site to determine an aggregate demand schedule.

[0269] According to an aspect, server **1502** can access performance data of each site to determine scheduled energy demand. For example, historical site data of a site can be stored within database **1504**, and performance of a participating site can be determined as performance data **1510**. According to an aspect, other EMI data can be accessed from database **1504**, external data source **1512**, or any combination thereof and used to determine performance of a site. For example, current and future weather conditions can be used to determine performance of a site. Taking weather conditions into consideration, along with a thermal response or characteristic of a site, a capacity to reduce energy can be determined on a site by site basis. The overall or aggregate demand can be used by the owner of DSS **1500** or communicated to a third party on a contractual basis as needed or desired.

[0270] FIG. **16** illustrates a method of managing energy at a site according to an aspect of the disclosure. Portions or all of the method of FIG. **16** can be used with portions or all of the energy management systems, devices, or apparatuses disclosed herein, or any other type of system, controller, device, module, processor, or any combination thereof, operable to employ all, or portions of, the method of FIG. **16**. Additionally, the method can be embodied in various types of encoded logic including software, firmware, hardware, or other forms of digital storage mediums, computer readable mediums, or logic, or any combination thereof, operable to provide all, or portions, of the method of FIG. **16**.

[0271] The method begins generally at block **1600**. At block **1602**, an acquisition interval to acquire network device data can be detected. For example, network device data can be acquired using a wireless energy network having one or more network devices accessible to the wireless energy network. For example, a wireless energy network can include various types of wireless networks configured to communicated information to manage energy use of a network devices accessible to the wireless network. For example, a wireless energy network can include one or more of any combination or portion of, IEEE 802.15-based wireless communication, Zigbee communication, INSETEON communication, X10 communication protocol, Z-Wave communication, Bluetooth communication, WIFI communication, IEEE 802.11-based communication, WiMAX communication, IEEE 802.16-based communication, various proprietary wireless communications, or any combination thereof.

[0272] At decision block **1604**, the method can detect whether an acquisition interval may be updated. For example, an acquisition interval can be set to a first interval (such as 1 minute, 2 minutes, 10 minutes etc.), and can then be altered to another interval. According to an aspect, an acquisition interval can be altered in response to a distance a mobile device may be from a site. For example, as a user moves away from a site, an acquisition interval can be increased (e.g. changed from 1 minute to 3 minutes). Similarly, as a mobile device move towards a site, an acquisition interval can be decreased (e.g. changed from 3 minutes to 1 minute). Various combinations of intervals can be used as needed or desired. If at decision block **1604** an acquisition interval has been updated, the method can proceed to block **1606** and an updated interval can be obtained. If at decision block **1604** an acquisition interval has not been changed, the method can proceed to block **1608**.

[0273] According to an aspect, at block **1608**, device data can be acquired. For example, device data can be obtained by sending a request to one or more network devices joined to a wireless energy network. For example, multiple devices can be accessed at an acquisition interval to obtain device data. Device data can be provided in various forms and types of information. According to an aspect, device data can include a device identifier, a network identifier, operation data, security data, various other types of data that can be used to manage energy use, or any combination thereof. According to a further aspect, device data can be formatted based on a wireless communication protocol (e.g. Zigbee, WIFI, WiMax, etc.) being deployed as the wireless energy network.

[0274] According to another aspect, the method can be modified to detect an availability of one or more network devices. For example, a first network device may be accessible to a wireless energy network and may use a first device profile to communicate information using the wireless energy network. Additionally, a second network device may be accessible to the wireless energy network and may use a second device profile that may be different from the first.

[0275] Upon acquiring device data from one or more network devices, the device data can be translated at step **1610**. For example, the device data may be formatted using a device profile, communication protocol, or various other formats to communicate device data using a wireless energy network. At block **1610**, device data can be translated into another format to use by another system, process, device, etc. other than the wireless energy network. For example, Zigbee formatted data can be translated into XML encoded data. According to another aspect, device data can be translated to an data object, such as a Java object and the like. Various other translations can also be used.

[0276] The method can then proceed to block **1612** and a report interval can be detected. According to an aspect, a

report interval can include an interval that may be the same as the acquisition interval, greater than the acquisition interval, or less than the acquisition interval. According to a particular aspect, the report interval can be twice as long as the acquisition interval. As such, exact timing of when to acquire device data can be obviated as at least one data acquisition may be available to generate a report.

[0277] At decision block **1614**, if a report interval should not be updated, the method can proceed to block **1618** as described below. If a report interval should be updated, the method can proceed to block **1616** and an updated report interval may be obtained. According to an aspect, a report interval can be provided using a data acquisition interval. For example, a report interval can be updated in association with an acquisition interval being updated. In other forms, a report interval can be provided and updated without an acquisition interval being updated. Various combinations of updating a report interval, acquisition interval, or any combination thereof can be used. Upon updating a report interval, the method can proceed to block **1618**.

[0278] According to an aspect, at block **1618** report data can be generated. For example, report data can include data that can be provided within a site report and can be formatted in various ways. For example, report data can include a XML encoded data, Java objects, textual data or various combinations thereof. According to an aspect, network device data can be converted to a binary representation. For example, to reduce the amount of information to be communicated, a binary representation can include one or more binary bits within a data field that can represent portions or all of the network device data. According to a further aspect, report data can be stored on a device basis until a site report can be generated.

[0279] Upon generating report data, the method can proceed to block **1620** and generates a site report. For example, a site report can include data received from one or more network devices. In another form, site report data can include data from another source, device, network, or any combination thereof capable of providing data that can be used within a site report. For example, a home controller may include a data and time setting based on a current time zone. A network device may not have a current or updated date and time stamp provided with the network device data. As such, a current date and time stamp can be provided with the site report data. In other forms, data obtained from another source (e.g. WIFI network, AMI network, WiMax network, etc.) can be provided within a site report. For example, a site report can include network device data that includes a thermostat or HVAC system being placed in an 'on' condition. Additionally, an AMI network can be accessed to detect a current energy consumption level, rate, price, savings or various other types of information that can be provided using an AMI network. The AMI network data can be combined with the network device data within a site report. As such, subsequent processing of site reports can include additional information that can be processed into a rite report to manage and report energy use at a site. Other types and combinations of EMI data from various network locations can be included within a site report as needed or desired.

[0280] Upon generating a site report, the method can proceed to block **1622** and a network connection can be initiated. For example, a rested web services approach to making a network connection can be deployed to realize increased network security at a site. For example, a home controller can be used to initiate a network connection using a LAN, broadband network, wireless data network, WiMax network, WIFI network, or various other networks or combinations of networks. A specific network location can be accessed on a secure basis using SSL or other encryption methods. At decision block **1624**, if a network may not be available, the method can proceed to block **1626** and store the site report until the network may become available. The method can then proceed to block **1608** as described herein. If at decision block **1624** a network location may be available, the method can proceed to block **1630** and initiates a transfer of a site report. According to an aspect, if multiple site reports are available, the method can initiate a transfer of the multiple site reports.

[0281] Upon initiating transfer of the site reports, the method can proceed to block **1632** and can initiate processing site report data at a network location. For example, a network location can include a server configured to process site report data and store site report data within a database. Additional processing of the data can be realized as needed or desired. For example, server **602** described in FIG. **6** includes several modules that can be used to process site report data. The server **602** may detecting the availability of a first network location and a second network location, wherein the second network location is different than the first network location. The server **602** can initiate access of the first network location to detect the operating condition of the network device and initiate access to a second network location to store the distance of the mobile device **632** relative to the site **604**. Communication of a control action to the first network location can be initiated to alter the operating condition of the network device. The server **602** can also initiate access to the second network location to detect a distance of the first mobile device relative to a distance of a second mobile device associated with the site **604**. Access to the first network location can be initiated to alter the operating condition of the network device if the first mobile device is closer to the site **604** than the second mobile device. The server **602** may then initiate an update of the operating condition at the first network location.

[0282] Upon initiating processor of site report data, the method can processed to decision block **1634** to detect if a control action may be available. For example, a control action field or flag associated with a specific site and one or more network devices can be provided within a database or other storage location. In another form, one or more binary values can be used to indicate if control action data be available. If control action may be available, the method can proceed to block **1636** and a control action can be received. For example, a control action can be communicated during a session and can include one or more actions associated with a network device accessible at a site. According to an aspect, a control action can be encoded based on a profile, (e.g. Zigbee Profile, Smart Energy Profile, Home Automation, etc.). In other forms, a control action can be formatted as XML encoded data, HTML encoded data, proprietary data format, or any combination thereof.

[0283] Upon receiving a control action at block **1636**, or if a control action may not be available, the method can proceed to decision block **1638** and detects if an interval should be updated. For example, a acquisition interval, report interval, or any combination thereof can be available. If an interval should be updated, the method can proceed to block **1640** and one or more intervals can be received and updated. According to an aspect, if an interval may be updated, an update flag can

be set to indicate a new or updated interval can be used. In other forms, a current interval field can be updated with a new interval value. If at decision block **1638**, an interval may not be updated, the method can proceed to decision block **1642** as described below.

[0284] According to an aspect, at decision block **1642** the method can detect if an update may be available. For example, an update can include one or more new or updated profiles that can be used at a site in association with an energy network. In another form, a software or firmware update can be available to update a network device, home controller, or various other systems, apparatuses, methods, devices, or any combination thereof that can be used at a site. If an update may be available, the method can proceed to block **1644** and a method can be received and processed at block **1646** as needed or desired. According to an aspect, an update may be available at another network location. As such, the method can be modified to include an update available flag or data, and another network location can be accessed to receive an update. If at decision block **1642** an update may not be available, the method can proceed to block **1648** as needed or desired.

[0285] According to an aspect, at block **1648**, the method can disconnect from a network location and proceed to block **1650**. If a control action may have been received, the method can processor the control action data, and proceed to block **1652** to detect a control action within the control action data. According to an aspect, a control action can include various combinations of actions such as obtaining or reading an operating status or value of one or more network device attributes, altering an operating condition of network device, updating an operating schedule of a network device, or various other control actions as needed or desired. In another form, control action data can be stored within a memory and deployed based on a schedule. As such, a period of time (e.g. twelve hours, twenty four hours, etc.) can be stored and deployed in the event of a information network failure at a site.

[0286] Upon detecting control action data, the method can proceed to block **1654** and can process control action data. For example, if control action data should be stored, the method can store control action data and deploy at a later time. In another form, control action data can be processed into a format that can be used to output network device data. For example, control action data can be processed into one or more JAVA objects, XML files, or other formats to include a received control action data of a specific device. According to an aspect, a network device can include a specific profile to access features of a network device. As such, control action data can be processed based on a specific profile.

[0287] Upon processing control action data, the method can proceed to block **1656** and the processed control action data can be generated into network device data. For example, a network may be deployed to provide an energy network at a site. As such, a protocol to communicate device data as network device data can be deployed. In other forms, a communication device can be coupled to a USB port, UART port, SPI port, other buses, or combinations thereof. As such, control action data can be formatted into a format that can be communicated using a specific bus having a wireless network device or module coupled to a bus. For example, for example. At block **1656** network device data can be formatted to be communicated using a USB bus having Zigbee communication module coupled to the USB bus. In other forms, a network device, such as a wireless WIFI device can be coupled to a UART bus and accessed to output control action data. Upon generating network device data, the method can proceed to block **1658** and the network device data can be output to a communication module that can output the control action data to the network device. The method can then proceed to block **1660**, and to block **1602** as needed or desired.

[0288] According to another aspect, the present disclosure and include an installation system and method configured to install a system at a site. For example, FIG. **6** described herein includes controller **626** and thermostat **628** installed at a site **604**. Installation can include controller **626** including a serial number (not expressly illustrated in FIG. **6**), or other unique identifier. Thermostat **628** can also include a serial number (not expressly illustrated in FIG. **6**) or other unique identifier. Upon a user or agent installing controller **626**, an identifier of controller **626**, thermostat **628**, or any combination thereof, can be communicated to server **602** to authenticate site **604** and enable energy management at site **604**.

[0289] According to another aspect, an installation can include controller **626** requesting a list of valid identifiers of one or more network devices that can be installed at site **604**. For example, controller **626** can receive a list of one or more valid network devices that may be installed at site **604**, and can validate one or more installed devices. For example, controller **626** can detect a network device accessible using an energy network deployed at site **604**. A network device can communicate an identifier and controller **626** can detect whether the communicated identifier may be within the list communicated by server **602**. As such, an agent that may have an inventory of network devices, controllers, or any combination thereof can install a controller and a network device without having to determine a valid serial number.

[0290] According to a further aspect, an installation can include using a mobile device including installation logic, one or more applications, settings, or any combination thereof. For example, mobile device **632** illustrated in FIG. **6** or other mobile devices or systems can be used to install portions or all of an energy management system at site **604**. For example, a user can deploy an energy management application on mobile device **632** and can input a serial number or other identifier to into an energy management application. In this manner, a user may modify network devices installed at site **604** by for example, adding new devices, updating new devices, deleting current devices, receiving software updates using a serial number of an installed device, or various combinations thereof. According to a further aspect, an installation, settings, and the like can include prompting a user to use a GPS location in connection with an installation and site **604**. As such, a user need not type in an address and can just select a current location to associate mobile device **632** and site **604**.

[0291] According to another aspect, an installation can include using RFID, bar code, network scan, or various other hands-free identification processes. For example, mobile device **632** can include an energy management application that can include an installation or set-up that includes reading a bar code label of controller **626**, TSTAT **628**, various other network devices, or any combination thereof. For example, a user can scan a barcode that can include a unique identifier of controller **626**, TSTAT **628**, or any combinations thereof. According to an aspect, a bar code label can be affixed to a portion of a housing (not expressly illustrated in FIG. **6**). In other forms, a bar code can be accessed using a display, such as a display of TSTAT **626** or other network devices or systems that can display one or more bar codes (e.g. outputting

multiple at a single system, network device, installation sheet or stickers, etc.). Upon a user scanning a bar code label, the installation process can use a network connection, such as WIFI or other wireless data networks to communicate unique data and authenticate a system. An server, such as server **602** can authenticate the data and activate a user's account. According to an aspect, a user can also set a location using a current GPS location of mobile device **632** at site **604**. In this manner, and installation process that can include authenticating or activating software on a mobile device, a home controller, a network device, and a server account can be coordinated in an efficient manner thereby reducing the need to have an installation technician or other third party activate an account. Various combinations of associating devices, systems, controllers, mobile devices, etc. can be used to activate portions or all of an energy network using hands-free RF, optical scanning devices, or any combination thereof. According to a further aspect, an installation can be modified to allow a third party technician install a system and can include scanning one or more bar codes that may be affixed to a network device, controller, etc. In other forms, a third party technician can scan bar code labels or other devices and affix the labels to a device, controller, system, etc. in association with an installation. As such, inventory management can also be maintained in association with installing a controller, network device, system, etc.

[0292] Note that not all of the activities described above in the general description or the examples are required, that a portion of a specific activity may not be required, and that one or more further activities may be performed in addition to those described. Still further, the order in which activities are listed are not necessarily the order in which they are performed.

[0293] The specification and illustrations of the embodiments described herein are intended to provide a general understanding of the structure of the various embodiments. The specification and illustrations are not intended to serve as an exhaustive and comprehensive description of all of the elements and features of apparatus and systems that use the structures or methods described herein. Many other embodiments may be apparent to those of skill in the art upon reviewing the disclosure. Other embodiments may be used and derived from the disclosure, such that a structural substitution, logical substitution, or another change may be made without departing from the scope of the disclosure. Accordingly, the disclosure is to be regarded as illustrative rather than restrictive.

[0294] Certain features are, for clarity, described herein in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features that are, for brevity, described in the context of a single embodiment, may also be provided separately or in any sub combination. Further, reference to values stated in ranges includes each and every value within that range.

[0295] Benefits, other advantages, and solutions to problems have been described above with regard to specific embodiments. However, the benefits, advantages, solutions to problems, and any feature(s) that may cause any benefit, advantage, or solution to occur or become more pronounced are not to be construed as a critical, required, or essential feature of any or all the claims.

[0296] The above-disclosed subject matter is to be considered illustrative, and not restrictive, and the appended claims are intended to cover any and all such modifications, enhancements, and other embodiments that fall within the scope of the present invention. Thus, to the maximum extent allowed by law, the scope of the present invention is to be determined by the broadest permissible interpretation of the following claims and their equivalents, and shall not be restricted or limited by the foregoing detailed description.

[0297] Although only a few exemplary embodiments have been described in detail above, those skilled in the art will readily appreciate that many modifications are possible in the exemplary embodiments without materially departing from the novel teachings and advantages of the embodiments of the present disclosure. Accordingly, all such modifications are intended to be included within the scope of the embodiments of the present disclosure as defined in the following claims. In the claims, means-plus-function clauses are intended to cover the structures described herein as performing the recited function and not only structural equivalents, but also equivalent structures.

What is claimed is:

1. A method of managing a site in a mobile environment, comprising:

detecting an availability of at least one network device at a site wherein the at least one network device has an operating condition;

detecting at least one boundary of the site;

presenting a proximity control selector within a user interface of a mobile device associated with the site, wherein the proximity control selector has a setting that can be toggled to enable and disable proximity detection using the mobile device;

detecting a distance of the mobile device relative to the site in response to enabling proximity detection on the mobile device; and

initiating a change to the operating condition of the network device in response to detecting a change in the distance of the mobile device relative to the at least one boundary of the site and the setting of the proximity control selector.

2. The method of claim **1** further comprising:

detecting a first boundary of the site having a first boundary distance;

detecting a second boundary of the site having a second boundary distance that is different than the first boundary distance; and

initiating the change to the operating condition of the energy consuming device at the site in response to detecting the change in the distance of the mobile device relative to the first boundary and the second boundary.

3. The method of claim **2** further comprising:

detecting a plurality of zones including,

an on-site zone including an area within the first boundary,

a first zone including an area beyond the first boundary and within the second boundary, and

a second zone including an area beyond the second boundary; and

initiating the change to the operating condition of the network device at the site in response to detecting the change in the distance of the mobile device relative to the on-site zone and the first zone and the second zone.

4. The method of claim **3** further comprising:
detecting the mobile device within the on-site zone in response to the distance of the mobile device relative to the site being less than or equal to the first boundary distance; and,
initiating an on-site operating condition of the network device at the site in response to detecting the mobile device within the on-site zone.

5. The method of claim **3** further comprising:
detecting the mobile device within the first zone in response to the distance of the mobile device relative to the site being greater than the first boundary distance and less than or equal to the second boundary distance; and
initiating a first zone operating condition of the network device at the site in response to detecting the mobile device within the first zone.

6. The method of claim **3** further comprising:
detecting the mobile device within the second zone in response to the distance of the mobile device relative to the site being greater than the second boundary distance; and
initiating a second zone operating condition of the network device at the site in response to detecting the mobile device within the second zone.

7. The method of claim **3** wherein the operating condition of the network device is a temperature set-point of a thermostat at the site further comprising the steps of:
initiating altering an on-site temperature set-point corresponding to the on-site zone;
initiating altering the on-site temperature set-point to a first zone temperature set-point corresponding to the first zone that is different from the on-site temperature set-point; and
initiating altering the on-site temperature set-point to a second zone temperature set-point corresponding to the second zone that is different from the on-site temperature set-point and the first zone temperature set-point.

8. The method of claim **3** further comprising:
detecting a new distance of the mobile device;
comparing the new distance to at least one of the plurality of zones;
detecting if a zone change has occurred;
initiating communication of a control message if the zone change has occurred; and
not initiating a communication of a control message if the zone change has not changed.

9. The method of claim **1** further comprising:
detecting an availability of a first thermostat of a first manufacturer;
detecting an availability of a second thermostat of second manufacturer; and
enabling proximity control of the first and second thermostat using the same mobile application accessible by a user of the mobile device.

10. The method of claim **1** further comprising;
detecting the availability of a first network location and a second network location, wherein the second network location is different than the first network location;
initiating access of the first network location to detect the operating condition of the network device;
initiating access to a second network location to store the distance of the mobile device relative to the site; and
initiating a communication of a control action to the first network location to alter the operating condition of the network device.

11. The method of claim **1** further comprising:
detecting an availability of a WIFI network including a device connected to the WIFI network;
accessing the device using the WIFI network to detect an operating condition of the device; and
initiating an altering of the operating condition of the network device using the WIFI network.

12. The method of claim **1** further comprising:
detecting an availability of at least one network device at a site wherein the at least one network device has an operating condition;
presenting a set location setting within a user interface of the mobile device;
detecting a selection of the set location setting;
detecting a current location of the mobile device in response to selection of the set location setting;
associating the current location of the mobile device with the site;
detecting a new location of the mobile device;
detecting a distance of the mobile device relative to the site by calculating a distance between the current location and the new location of the mobile device; and
initiating a change to the operating condition of the network device in response to detecting a change in the distance of the mobile device relative to the site.

13. A method of managing energy use in a mobile environment comprising:
displaying a graphical user interface (GUI) including a set location setting;
determining a site location in response to a selection of the set location setting;
storing the site location within a memory of the mobile device;
detecting a location change of the mobile device relative to the site location; and
altering the operating condition of the network device in response to a detection of the location change of the mobile device.

14. The method of claim **13** further comprising:
enabling a user to set a travel distance within the GUI;
determining a plurality of zones using the travel distance including a first zone and a second zone;
detecting when the mobile device changes between the first zone and the second zone; and
altering the operating condition of the network device in response to detecting the mobile device changing zones.

15. The method of claim **14** further comprising:
detecting a setting of the travel distance; and
displaying the plurality of zones as a graphic within the GUI.

16. The method of claim **15** further comprising:
displaying a map within a GUI, wherein the map includes a graphic presenting the site location and the plurality of zones disposed about the site location;
detecting the current location of the mobile device;
displaying a graphic within the map presenting the current location of the mobile device; and
wherein at least one of the zones is determined using geofencing.

17. The method of claim **15** further comprising:
detecting a change in the setting of the travel distance;

automatically scaling the plurality of zones in response to the change in the setting of the travel distance wherein at least one of the zones is enlarged in response to an increase in the travel distance; and

storing the zones within the memory of mobile device.

18. The method of claim **15** further comprising:

detecting a first distance defining a boundary of the first zone;

displaying a graphic presenting the first zone and the boundary of the first zone within the GUI;

detecting a second distance defining a boundary of the second zone;

displaying a graphic presenting the second zone and the boundary of the second zone within the GUI;

detecting a location of the mobile device with respect to the first or second zone; and

displaying within the GUI a reference to the location of the mobile device with respect to the first or second zone.

19. The method of claim **15** further comprising:

detecting a first distance defining a boundary of the first zone;

detecting a second distance defining a boundary of the second zone;

displaying a graphic presenting the first zone, the second zone, and a site location within the GUI; and

wherein the first distance and the second distance is less than the setting of the travel distance.

20. The method of claim **15** further comprising:

determining a boundary of the first zone as being less than half the travel distance; and

determining a boundary of the second zone as being greater than half the travel distance.

* * * * *