



(56)

References Cited

U.S. PATENT DOCUMENTS

6,784,705 B2	8/2004	Kamata	7,554,377 B1	6/2009	Guan	
6,794,856 B2	9/2004	Fernald	7,679,412 B2	3/2010	Ogiwara et al.	
6,858,917 B1	2/2005	Ranucci	7,679,957 B2	3/2010	Ma et al.	
6,901,012 B2	5/2005	Ikehashi et al.	7,710,783 B2	5/2010	Ning	
6,933,770 B1	8/2005	Ranucci	7,715,236 B2	5/2010	Hyde	
7,116,088 B2	10/2006	Tran et al.	7,732,945 B2	6/2010	Gotoh et al.	
7,116,240 B2	10/2006	Hyde	8,183,926 B2*	5/2012	Degoirat	330/288
7,119,526 B2	10/2006	Fernald	2007/0210923 A1	9/2007	Butler et al.	
7,133,269 B2	11/2006	Lundberg	2007/0290660 A1	12/2007	Yamazaki	
7,161,338 B2	1/2007	Jiang et al.	2008/0106416 A1	5/2008	Sullivan et al.	
7,429,854 B2*	9/2008	Kimura	2008/0180249 A1	7/2008	Butler et al.	
7,436,732 B2	10/2008	Hirobe	2008/0189567 A1	8/2008	Goodnow et al.	
7,471,143 B2	12/2008	Kim	2009/0146729 A1*	6/2009	Nishimori	327/539
			2009/0289776 A1	11/2009	Moore et al.	
			2011/0298540 A1*	12/2011	Sheng et al.	330/130

\* cited by examiner




Fig. 1  
Prior Art




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 4




Fig. 3




Fig. 5




Fig. 6




Fig. 7



900 ↗




Fig. 9




Fig. 11




Fig. 10




Fig. 12




Fig. 13




Fig. 14




Fig. 15

- 1. IF PORB\_THRUSH LOW = OUT LOW
- 2. PORB\_THRUSH HIGH
  - 2.1 BOTH A, B HIGH → OUT HIGH
  - 2.2 BOTH A, B LOW → OUT LOW
  - 2.3 ONE OF A OR B HIGH → OUT HIGH




Fig. 16




Fig. 18




Fig. 17




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 26




Fig. 25





Fig. 27



3008 GUARANTEED VOLTAGE IR<sub>3</sub>

Fig. 29




Fig. 28

3100 ↗




Fig. 30  
Prior Art




Fig. 31  
Prior Art





Fig. 32  
Prior Art




Fig. 33




Fig. 35




Fig. 36




Fig. 34




Fig. 37A  
Prior Art




Fig. 37B  
Prior Art




Fig. 38

4000  
↙




Fig. 39




Fig. 40

# GENERATION OF VOLTAGE SUPPLY FOR LOW POWER DIGITAL CIRCUIT OPERATION

## CROSS REFERENCE TO RELATED PATENT APPLICATIONS

The present invention claims priority from U.S. Provisional Patent Application Ser. No. 61/495,634 filed Jun. 10, 2011, and is related to U.S. patent applications Ser. Nos. 13/490,254, filed Jun. 6, 2012, entitled DYNAMIC POWER CLAMP FOR RFID POWER CONTROL, 13/490,115, filed Jun. 6, 2012, entitled POWER-ON SEQUENCING FOR AN RFID TAG, 13/490,267, filed Jun. 6, 2012, entitled ANALOG DELAY CELLS FOR THE POWER SUPPLY OF AN RFID TAG, 13/490,236, filed Jun. 6, 2012, entitled BANDGAP READY CIRCUIT, 13/490,285, filed Jun. 6, 2012, entitled DYNAMIC ADJUSTING RFID DEMODULATION CIRCUIT, and 13/490,296, filed Jun. 6, 2012, entitled SHUNT REGULATOR CIRCUIT HAVING A SPLIT OUTPUT, the disclosures of which are herein specifically incorporated by this reference in its entirety.

## BACKGROUND OF THE INVENTION

### 1. Field of the Invention

The invention relates, in general, to the field of radio frequency identification (RFID) tags and systems. More particularly, the invention relates to numerous circuit improvements for the RFID tag for optimizing performance.

### 2. Discussion of the Related Art

As is well known in the art, a basic RFID system includes three components: an antenna or coil; a transceiver with decoder, i.e., RFID reader; and a transponder, i.e., RFID tag, programmed with unique information.

RFID tags are categorized as either active or passive. Active RFID tags are powered by an internal battery and are typically read/write, i.e., tag data can be rewritten and/or modified. Passive RFID tags operate without a separate external power source and obtain operating power generated from the reader.

An example of a typical passive RFID tag is shown in FIG. 1. Tag **100** includes an antenna **102** that is coupled to an analog front end circuit **104**, which is in communication with a digital and memory circuit **106** through receive (RX) and transmit (TX) paths. Most passive RFID tags today use some sort of electrically erasable programmable read-only memory (EEPROM) such as flash memory.

While EEPROM memory has served in passive RFID tag applications to date, the demands for greater data throughput into and out of the RFID are increasing. This can be seen for example in factory environments, and in collecting highway tolls. The EEPROM based passive RFID tags, are slow and may not be suited for the higher throughput applications. Alternative, faster memories technologies such as FRAM ("Ferroelectric Random Access Memory") memory exist that are ideally suited for these new higher speed RFID applications. However, the RFID environment is extremely challenging for FRAM based integrated circuits, not only for the normal challenges such as the variation in process corners, temperature, and the constraints of low power operation but also for intermittent contact with the RFID reader leading to interruptions with the available power supply on the RFID tag.

What is desired, therefore, are circuit improvements for an RFID tag that will provide robust operation in a challenging RFID environment while exploiting the advantages of FRAM memory.

## SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a power supply for low power operation of digital circuitry for an RFID application that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

According to the present invention, a low power voltage regulator includes an output node for providing a regulated output voltage, a first diode-connected transistor of a first polarity type (P-channel transistor) in series with a second diode-connected transistor of a second polarity type (N-channel transistor) coupled between the output node and ground, and a bias current having a value for biasing the first and second diode-connected transistors in a sub-threshold mode of operation for very low power design or in higher current mode for higher performance design. The low power voltage regulator further includes a buffer amplifier or emitter (or source) follower stage to provide a low impedance regulated voltage. The bias current may be generated from a bandgap circuit to provide a low value current source capable of providing the sub-threshold or normal mode of operation, or other current source design.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles of the invention.

In the drawings:

FIG. 1 is a block diagram of a prior art EEPROM based passive RFID tag;

FIG. 2A is an overall block diagram of a FRAM memory based passive RFID tag according to the present invention;

FIG. 2B is a more detailed block diagram of a first portion of the FRAM memory based passive RFID tag referred to in FIG. 2A;

FIG. 2C is a more detailed block diagram of a second portion of the FRAM memory based passive RFID tag referred to in FIG. 2B;

FIG. 3 is a schematic diagram of the low power voltage regulator and a buffer stage according to the present invention;

FIG. 4 is a schematic diagram of the low power voltage regulator and an emitter follower stage according to the present invention;

FIG. 5 is a graph of  $V_{DD\_REG}$  vs  $I_{Load}$  showing the operation of the low power voltage regulator according to the present invention;

FIG. 6 is a schematic diagram of a transistor identifying voltage and currents used in the graph of FIG. 7;

FIG. 7 is a graph of the sub-threshold operation for a transistor such as the ones used in the low power voltage regulator according to the present invention;

FIG. 8 is a detailed transistor-level schematic of an embodiment of the low power voltage regulator according to the present invention;

FIG. 9 is a schematic diagram of a clamping circuit for an RFID tag according to the present invention;

FIG. 10 is a timing diagram of an overshoot transient in the VDDR power supply for an RFID due to a slow clamping circuit according to the prior art;

FIG. 11 is a timing diagram of the VDDR response to a fast RF rise with both active and dynamic clamping according to the present invention;

FIG. 12 is a schematic diagram of a power-on sequencing circuit for an RFID tag according to the present invention;

FIG. 13 is a timing diagram associated with the circuit of FIG. 12;

FIG. 14 is a schematic diagram of a power-on reset circuit according to the present invention;

FIG. 15 is a timing diagram associated with the circuit of FIG. 14;

FIG. 16 is a block diagram of a state machine according to the present invention;

FIG. 17 is a timing diagram associated with the state machine of FIG. 16;

FIG. 18 is a timing diagram associated with the power-on reset circuit of FIG. 14;

FIG. 19 is a schematic diagram of a first delay circuit embodiment for use with a power supply of an RFID tag according to the present invention;

FIG. 20 is a timing diagram associated with the delay circuit of FIG. 19;

FIG. 21 is a schematic diagram of a second delay circuit embodiment for use with a power supply of an RFID tag according to the present invention;

FIG. 22 is a timing diagram associated with the delay circuit of FIG. 21;

FIG. 23 is a schematic diagram of a third delay circuit embodiment for use with a power supply of an RFID tag according to the present invention;

FIG. 24 is a timing diagram associated with the delay circuit of FIG. 23;

FIG. 25 is a schematic diagram of a cascaded delay circuit embodiment according to the present invention;

FIG. 26 is a timing diagram associated with the cascaded delay circuit of FIG. 26;

FIG. 27 is a schematic diagram of a bandgap ready circuit according to the present invention;

FIG. 28 is a schematic diagram of a logic circuit for use with the bandgap ready circuit of FIG. 27;

FIG. 29 is a timing diagram associated with the bandgap ready circuit of the present invention;

FIG. 30 is a schematic diagram of a prior art demodulation circuit.

FIG. 31 is a timing diagram associated with the prior art demodulation circuit of FIG. 30;

FIG. 32 is a timing diagram associated with the prior art demodulation circuit of FIG. 30;

FIG. 33 is a schematic diagram of a dynamic adjusting RFID demodulation circuit according to the present invention;

FIGS. 34-36 are timing diagrams associated with the dynamic adjusting RFID demodulation circuit according to the present invention;

FIGS. 37A and 37B are schematic diagrams of a prior art shunt regulator;

FIG. 38 is a schematic diagram of a shunt regulator driven from a rectifier circuit output having a split output according to the present invention; and

FIGS. 39 and 40 are timing diagrams associated with the shunt regulator of FIG. 38.

#### DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS

Referring now to FIG. 2A, a passive RFID tag 200 according to the invention includes an antenna 202, an analog front end 204, and a digital portion 206 that includes digital control circuitry and FRAM memory and communicates with the analog front end 204 using the RX and TX paths.

Referring to FIG. 2B, a more detailed block diagram of a first portion 208 of the RFID tag 200 includes a rectifier 210, a split output 212 including two diodes described in further detail below, an active clamp 214, and a dynamic clamp 218 coupled to the VDDR power supply, which is also described in further detail below. The rectifier output is also coupled to a demodulator 216 for providing a digital output, which is also described in further detail below.

Referring to FIG. 2C, a more detailed block diagram of a second portion 220 of the RFID tag 200 includes a slew filter 224 and a bandgap circuit 222 both coupled to the VDDR power supply, and both described in further detail below. The output of the slew filter is coupled to a VDDM regulator 226 for providing a VDDM supply voltage. In turn, a VDDD regulator 228 is coupled to the VDDM supply voltage, as well as delay circuits 232 and 234. The purpose and nature of these circuits is described in further detail below. A VDDMPOK circuit 238 receives the VDDM, VBG, and DLY2 signals and provides a VDDMPOK signal. A delay circuit 240 receives the VDDMPOK signal and provides a GEN2POK signal. A reset circuit 242 receives the GEN2POK and VDDMPOK signals to provide a RESET signal. Finally, circuit 236 receives the VDDMPOK, GEN2POK, and PORBTHRESH signals to provide a VDDD\_PORB signal. The nature of all of these further signals and circuits is explained in further detail below. Circuit 230 monitors the VDDD threshold.

Referring now to FIG. 3 a low power voltage regulator 300 includes an output node for providing a regulated output voltage (VDD\_REG), a first diode-connected transistor Q1 of a first polarity type (P-channel) in series with a second diode-connected transistor Q2 of a second polarity type (N-channel) coupled between the output node and ground. A bias current  $I_{BIAS}$  has a value for biasing the first and second diode-connected transistors in a sub-threshold mode of operation as is explained in further detail below. The  $I_{BIAS}$  current can be generated using a bandgap circuit or other bias current circuits as are known in the art. A buffer amplifier 302 is coupled to the output node to provide a low impedance regulated output voltage.

Referring now to FIG. 4 a low power voltage regulator 400 includes an output node for providing a regulated output voltage (VDD\_REG), and a first diode-connected transistor Q1 of a first polarity type (P-channel) in series with a second diode-connected transistor Q2 of a second polarity type (N-channel) coupled between the output node and ground. A diode D3 is provided to compensate for the voltage drop seen in Q3 to the regulated voltage VDD\_REG. A bias current  $I_{BIAS}$  has a value for biasing the first and second diode-connected transistors in a sub-threshold mode (or other mode) of operation as is explained in further detail below, as well as diode D3. An emitter follower stage transistor Q3 is coupled to the output node (through diode D3) to provide a low impedance regulated output voltage.

Referring now to FIG. 5, it is important to note that the total voltage across transistors Q1 and Q2 is not a constant voltage, even though the bias current, labeled  $I_{BIAS}$ , may be. Thus, the

5

circuit of FIG. 4 is not a constant voltage generator. At lower temperatures a higher total voltage  $V_2$  results given a constant bias current. At higher temperatures a lower total voltage  $V_1$  results given the same constant bias current. Thus, the total voltage decreases with increased temperature change. The voltage VDD\_REG is a temperature compensated voltage, which helps to provide stable circuit performance. A higher VDD\_REG voltage is provided to compensate for relatively slower transistors, which occurs at lower temperatures. A lower VDD\_REG voltage is provided to compensate for relatively faster transistors, which occurs at higher temperatures. The level of  $I_{BIAS}$  also sets the operating mode of Q1 and Q2 as sub-threshold or higher power mode.

Referring now to FIG. 6, a transistor is shown identifying the drain-source current ( $I_{DS}$ ), drain-source voltage ( $V_{DS}$ ), and the gate-source voltage ( $V_{GS}$ ) thereof.

Referring now to FIG. 7, a graph is shown plotting the drain-source current of a transistor in response to the gate-source voltage. A threshold voltage  $V_{THRESHOLD}$  is shown. Above the threshold voltage, the transistor operates in the "Square Law" mode of operation. Below the threshold voltage, the transistor operates in an exponential mode of operation, with the leakage current of the device forming a current floor level. In the circuit of FIG. 4, the bias current through transistors Q1 and Q2, as well as serially connected diode D3, is constrained to operate those transistors in the sub-threshold mode of operation for very low power operation. This insures that the circuit of FIG. 4 operates a low power mode, which is of critical importance in an RFID tag, as the available energy for circuit operation is extremely limited. With larger  $I$  a higher power, higher performance circuit operation is obtained.

Referring now to FIG. 8, a detailed transistor-level schematic of an embodiment of the low power voltage regulator 800 is shown. Low power voltage regulator 800 includes a first diode-connected transistor Q1 of a first polarity type (P-channel) in series with a second diode-connected transistor Q2 of a second polarity type (N-channel) coupled between the output node and ground. A bias current generator  $I_1$  is used to bias the first and second diode-connected transistors in a sub-threshold mode of operation. A third diode-connected transistor (Q3, N-channel) is coupled between the bias current  $I_1$  and the first and second diode-connected transistors Q1 and Q2. A buffer amplifier (Q4, Q5,  $I_2$ ,  $I_3$ ) is coupled to the third transistor Q3 for providing a regulated output voltage VDD\_REG. The buffer amplifier includes an input transistor Q4 (N-channel) having its gate forming the input of the buffer, and its source forming the output of the buffer for providing the regulated output voltage. A feedback transistor Q5 (P-channel) is also included having a gate coupled to the drain of the input transistor, a source for coupling to a power supply voltage, and a drain coupled to the source of the input transistor Q4. A first buffer bias current  $I_2$  is coupled to the drain of the input transistor Q4 and a second buffer bias current  $I_3$  is coupled to the source of the input transistor Q4. The value of the second bias current  $I_3$  is greater than the value of the first bias current  $I_2$ . Representative values of the bias currents for the voltage regulator 800 in very low power operation are as follows:  $I_1$  is 20 nA,  $I_2$  is 20 nA, and  $I_3$  is 40 nA.

A clamp circuit 900 for an RFID tag is shown in FIG. 9 including a VDDR power supply node (clamped power supply voltage provided by the RFID rectifier circuit, not shown in FIG. 9), a dynamic clamp 902 coupled between the power supply node and ground, and an active clamp 904 also coupled between the power supply and ground, holding the

6

power supply VDDR at a maximum steady state clamped value when the RF supplied power exceeds an operating minimum.

The dynamic clamp 900 includes a capacitor divider circuit including capacitors C91 and C92 coupled between the VDDR rail and ground. A resistor R91 is coupled to the capacitor divider circuit at center tap node 906. An N-channel transistor Q91 has a gate coupled to the capacitor divider circuit at center tap node 906. The drain of transistor Q91 is coupled to the VDDR rail and the source is coupled to ground.

The active clamp includes a differential amplifier 906 having a first input coupled to a resistor divider including resistors R92 and R93 at center tap node 908, a second input for receiving a reference voltage VREF, and an output coupled to a P-channel transistor Q92 for providing the clamped VDDR voltage. The differential amplifier 906 can be an operational amplifier. The gate of transistor Q92 is coupled to the output of differential amplifier 906, the clamped VDDR voltage is provided at a source of the transistor, and the drain of the transistor is tied to ground. A holding capacitor C93 is attached between VDDR and ground. The clamped VDDR is also referred to as 'VDD' in the following section.

Referring now to FIG. 10, the overshoot transient in the VDD clamped supply voltage is shown due to the undesirably slow response of a prior art clamping circuit. The power supply voltage waveform 1002 attains a desirably final VDD voltage level only after experiencing a significant overshoot that may adversely affect downstream circuitry.

Referring now to FIG. 11, the prior art VDD voltage waveform 1102 including the undesirable overshoot is shown along with the VDD voltage waveform 1104 clamped with the active and dynamic clamping according to the present invention. Note that the voltage waveform 1104 has a much reduced overshoot.

Thus, a clamping method for an RFID tag according to the present invention includes providing a power supply voltage from an RFID rectifier having an overshoot in an unclamped condition, and clipping excess energy harvested by the RFID rectifier during an overshoot time period to prevent the overshoot and to prevent overdriving subsequent RFID circuitry. This method is provided by using a dynamic clamp in cascade with an active clamp. The dynamic clamp includes an NMOS transistor for shunting fast rising initial energy from the RFID rectifier output, and further includes a leakage path for turning off the NMOS transistor after the overshoot time period. Stated another way, a clamping method for an RFID tag according to the present invention includes removing energy harvested by an RFID rectifier from a fast rising RF field that would generate an overshoot condition for a predetermined initial time period to prevent overshoot and to prevent overdriving subsequent RFID circuitry.

Referring now to FIG. 12, circuit 1200 provides sequencing control for an RFID tag according to the present invention. The voltage at input node (1) is the raw power supply voltage VDDR supplied by the dynamically and actively clamped output of the rectifier, Power VDDR in FIG. 2B. The circuit 1200 can be realized in a one-chip or two-chip solution. Circuit block 1202 is a normal bandgap circuit, coupled to the bandgap ready circuit 1204 at node (2). Bandgap ready circuit 1204 is explained in further detail below. Circuit block 1206 is a slew filter that is explained in further detail below. The output of the slew filter is shown as node (3), coupled to filter capacitor 1208. Circuit block 1210 is an LDO regulator generating power for the memory circuit block 1224, for the digital voltage regulator circuit block 1212. It also provides a divided down signal to circuit block 1214, a comparator, where it is compared to the bandgap voltage to generate signal

VDDMPOK explained further below. The “memory VDDM” voltage means the VDD voltage provided to the memory. Note FRAM memory block **1224** is coupled to the VDDM line. Circuit block **1212** is a second regulator for providing the regulated VDDD voltage to the digital circuitry on the chip designated by block **1226** at node (5). Circuit block **1214** is a comparator. Three inputs are shown, which include a positive input, a negative input, and an enable input. The outputs of comparator **1214** are VDDMPOK, and the inverted VDDMPOK signals. The VDDMPOK signal node is labeled (6A). The VDDMPOK signal designation means “VDDM Power is OK”. Blocks **1216** and **1218** are delay circuits that are explained in further detail below. Circuit block **1220** is also a delay circuit. Delay circuit **1220** can be a simple analog delay using a current source and a capacitor, and is used to generate the GEN2POK signal at node (6B) as shown. Block **1222** is a voltage monitor, and is described in further detail below. Finally, a reset signal generating block **1228** is shown for generating a reset signal at node **1808**.

FIG. **13** is a timing diagram associated with FIG. **12**, wherein the node waveforms for nodes (1), (2), (3), (4), and (5) are shown. The corresponding waveforms are designated **1302**, **1304**, **1306**, **1308**, and **1310**. One of the most important functions associated with the circuit of FIG. **12** is to protect the FRAM memory from any loss of contents by shutting down the memory properly. That is, a new memory access is prevented when the memory voltage is below a certain value. Memory operation is only possible when VDDM is above a first threshold value, and maintains that value. Memory operation is discontinued when VDDM drops below a second threshold value.

Referring now to FIG. **14**, a voltage monitor circuit is shown including a transistor **Q1402**, a capacitor **1404**, and a digital circuit including inverters **1406** and **1408**, and an OR gate **1410** for generating a POR signal.

Referring now to FIG. **15**, a waveform **1502** is shown that is associated with the monitor circuit of FIG. **14**.

Referring now to FIG. **16**, a state machine **1600** is shown that receives all of the various timing inputs and generates the VDDD\_PORB signal. State machine **1600** operates according to the following rules:

If PORB\_THRESH is low, the output of the state machine is low.

If PORB\_THRESH is high, then:

If the other two input signals are high, then the output is high.

If the other two input signals are low, then the output is low.

If only one of the two input signals are high, the output is high.

Referring now to FIG. **17**, a timing diagram is shown associated with the state machine of FIG. **16**. In particular, the fall edge delay with respect to the VDDMPOK signal **1702**, and the GEN2POK signal **1704** is shown, which is in the range of about 2 to 6 microseconds.

Referring now to FIG. **18**, a timing diagram associated with the overall sequencing circuit of FIG. **12** is shown including the input VDDRAW voltage, the VDDMPOK signal **1804**, the GEN2POK signal **1806**, and the discharge pulse **1808**.

Referring now to FIG. **19**, a first delay circuit **1900** for use with a power supply in an RFID tag includes a power supply input VDD\_IN and a power supply output VDD\_OUT. A passive circuit **1902**, **1904** is coupled between the power supply input VDD\_IN and ground. A transistor **Q1906** has a current path coupled between the power supply input VDD\_IN and the power supply output VDD\_OUT, and a control node coupled to an intermediate node **1908** of the passive circuit. The passive circuit includes a capacitor **1902**

and a resistor **1904** in series connection. The capacitor **1902** is coupled between the power supply input VDD\_IN and the intermediate node **1908**. The resistor **1904** is coupled between the intermediate node **1908** and ground. Transistor **Q1906** is a P-channel transistor.

Referring now to FIG. **20**, the response of the delay circuit **1900** is shown. The VDD\_IN typically supplied by a diode rectifier on the RFID tag and has an overshoot indicated by waveform **2002**. The VDD\_OUT waveform **2004** after being processed by first delay circuit **1900** has no overshoot, and is delayed by a predetermined delay time period determined by the time constant of the passive circuit including capacitor **1902**, resistor **1904**.

Referring now to FIG. **21**, a second delay circuit **2100** for use with a power supply in an RFID tag includes a power supply input VDD\_IN and a power supply output VDD\_OUT. A ramp circuit **2102**, **2104** is coupled between the power supply input VDD\_IN and ground. A transistor **Q2106** has a current path coupled between the power supply input VDD\_IN and the power supply output VDD\_OUT, and a control node coupled to an intermediate node **2108** of the ramp circuit. The ramp circuit includes a capacitor **2102** and a current source **2104** in series connection. The current source can be a temperature stabilized current source provided from a bandgap circuit if desired. The capacitor **2102** is coupled between the power supply input VDD\_IN and the intermediate node **2108**. The current source **2104** is coupled between the intermediate node **2108** and ground. Transistor **Q2106** is a P-channel transistor.

Referring now to FIG. **22**, the response of the second delay circuit **2100** is shown. The VDD\_IN typically supplied by a diode rectifier on the RFID tag and has an overshoot indicated by waveform **2202**. The VDD\_OUT waveform **2204** after being processed by second delay circuit **2100** has no overshoot, and is delayed by a predetermined delay time period determined by the ramping speed of the ramp circuit including capacitor **1902**, resistor **1904**. The predetermined delay time includes a first delay time DLY1, which is determined by the current source turning on and a second delay time DLY2, which is determined by transistor **Q2106** turning on. The bandgap waveform **2206** is also shown in FIG. **22**.

Referring now to FIG. **23**, a third delay circuit **2300** for use with a power supply in an RFID tag includes a power supply input VDD\_IN and a power supply output VDD\_OUT. A current mirror circuit **Q2302**, **Q2304** has an input coupled to a current source **2306**, an output coupled to the power supply output VDD\_OUT, and a power node coupled to the power supply input VDD\_IN. A capacitor **2308** ( $C_{LARGE}$ ) is coupled between the power supply output VDD\_OUT and ground. The current mirror circuit comprises a simple two-transistor current mirror with a P-channel MOS input transistor **Q2302** and a P-channel MOS mirror transistor **Q2304**. Other more complicated current mirror circuits as are known in the art can also be used. Current source **2306** can be a temperature stabilized current source from bandgap circuit if desired.

Referring now to FIG. **24**, the response of the third delay circuit **2300** is shown. The VDD\_IN typically supplied by a diode rectifier on the RFID tag and has an overshoot indicated by waveform **2402**. The VDD\_OUT waveform **2404** after being processed by first delay circuit **1900** has no overshoot, and is delayed by a predetermined delay time period determined by  $I_{REF}$  turning on. The slew rate of the output waveform **2404** is defined by the values of the current source **2306** and the capacitor **2308** until a stable final output voltage value is reached.

A cascaded delay circuit providing power to a regulator **2600** for an RFID tag is shown in FIG. **25** including a power

supply input VDD\_IN and a power supply output VDD\_OUT and two delay circuits **2602**, **2604** in cascade connection between the power supply input and the power supply output. Different combinations of cells and numbers can be used. For example, delay cell **2602** can be the delay cell **1900** shown in FIG. **19** or the delay cell **2100** shown in FIG. **21**. The delay cell **2604** can be the slew filter **2300** shown in FIG. **23**. The regulator **2606** can be any known voltage regulator such as an LDO, shunt, or source follower regulator.

Delay cell **2602** can comprise delay circuit **1900** or delay circuit **2100** as discussed above coupled between a local power supply input (VDD\_IN) and a local power supply output **2610**.

Slew filter **2604** can comprise delay circuit **2300** as discussed above coupled between a local power supply input **2610** and a local power supply output **2612**.

Voltage regulator **2606** can comprise any known voltage regulator as discussed above coupled between a local power supply input **2612** and a local power supply output VDD\_OUT.

Referring now to FIG. **26**, a number of response waveforms are shown in the timing diagram associated with circuit **2600** in FIG. **25**. The VDD\_IN waveform **2702** is shown having an overshoot. The output of the first delay cell **2706** is shown slightly delayed and having no overshoot. The output of the slew filter **2704** is shown still further delayed and having a slew-controlled output up to a final stable voltage output. This output is still further delayed and regulated by the voltage regulator as shown in waveform **2708**. The total delay **2710** is shown between the onset of the VDD\_IN waveform and the start of the VDD\_OUT regulated output voltage.

The purpose of the various single and cascaded power supply delay circuits is to provide a control mechanism for turning on circuit blocks and functions inside of an RFID tag only when it can be assured that a stable power supply voltage can be provided. It will be apparent to those skilled in the art that the cascaded delay circuit **2600** can be designed with other arrangements of delay cells while still providing the desirable stable voltage function.

Referring to FIG. **27**, a circuit for detecting the safe voltage operation for a chip such as found in an RFID tag, it is necessary to first detect when the system reference level, derived from a bandgap voltage generator, is sufficiently stable so that signals generated from this reference will be in a range near steady state operation. A regulator that has a bandgap reference generates a voltage proportional to the reference. If the reference is not fully settled, the regulator output is not in its design range. The bandgap circuit operates by feedback control to maintain operation at a crossing point of two node voltages, nodes **1** and **2**. According to the present invention, a third branch that crosses one of the nodes during the turn-on transient and is at a higher steady state voltage, at a lower than final operational voltage is used to generate a voltage that is compared with one of the bandgap reference voltages, node **1**, to create part of a bandgap ready logic signal. However, when addressing input transients, slow and erratic power supplies, an additional problem was identified. The branch transients are not well controlled and an erroneous valid operation was predicted. To fix this secondary problem, an additional monitoring circuit was added to detect saturation operation of the core branch of currents in the bandgap voltage generator that would be combined with the crossing information logic signal to more reliably predict when the bandgap reference cell was close to steady state operation. Once the band gap reference cell is at steady state

operation valid comparisons of regulator outputs for signaling to control circuits that the proper state of the power supply has been reached.

In the bandgap ready circuit **2800** of FIG. **27**, levels that are monitored for control of operations only at a defined range rely on having a reference that is at or close to the end of its turn-on transient. Once a reference valid monitor for the bandgap reference cell is generated, false release of operation of the RFID chip at voltage levels that are too low for reliable operation is substantially obviated.

Bandgap circuits are well known in the art. It is also well known that voltage regulation such as is required in a chip in an RFID tag requires a stable bandgap reference voltage. During power up, monitor circuits used in the power-up sequence will undesirably glitch if the reference is not yet stable and may improperly release circuit functions when supplies are out of operational range. Prior art uses timing delays to allow the bandgap reference circuit to settle before indicating that a stable operating voltage has been reached. While the approach according to the present invention is effective for assuring that a proper operating voltage has been reached, and then other circuit function can begin, it is process sensitive and should be tuned to ensure optimum performance.

Referring to FIG. **27**, a 'bandgap ready' circuit **2800** includes a bandgap circuit for providing a bandgap voltage including diodes **D2820**, **D2822**, resistor **R1** designated **2832**, N-channel transistors **Q2810** and **Q2812**, and P-channel transistors **Q2804** and **Q2806**. Transistors **Q2810** and **Q2812** form an N-channel current mirror. Transistors **Q2804** and **Q2806** form a P-channel current mirror. Other bandgap designs would have equivalent monitoring nodes from this example design. P-channel transistor **Q2808** is mirrored from the P-channel current mirror. The drain current from transistor **Q2808** is used to generate the  $V_{BGAP}$  voltage across diode resistor **R2** designated **2834** and diode **D2824**. A capacitor **C2826** is coupled to the bandgap output voltage node. A first comparator **2828** is used for monitoring first and second voltages in the bandgap circuit and for providing a first logic signal at node **2814**. A first input is coupled to the source of transistor **Q2810** and a second input is coupled to the drain of P-channel transistor **Q2802** in a replica branch. The current through transistor **Q2802** generates a slightly larger and tracking voltage to node **2** in the bandgap core, across resistor **R3** designated **2830** and diode **D2818**. A second comparator **2826** is used for monitoring third and fourth voltages in the bandgap circuit and for providing a second logic signal at node **2816**. A first input is coupled to the drain of transistor **Q2806** and a second input is coupled to the drain of transistor **Q2808**, which is also coupled to resistor **R2830**, as shown.

In circuit **2800** shown in FIG. **27**, the relative sizes of the diodes for proper generation of the bandgap voltage are given as follows: **D2818**, m=M; **D2820**, m=1; **D2822**, m=N; and **D2824**, m=1.

Referring now to FIG. **28**, an AND logic circuit **2900** for combining the first and second logic signals at nodes **2814** and **2816** is used to provide a bandgap ready logic signal BGOK.

Referring now to FIG. **29(a)** a graph of the voltages at the source of transistor **Q2810** and drain of transistor **Q2802** are shown, designated nodes **(1)** and **(3006)** in FIG. **27**. The crossover point of these two voltages is used to generate the first logic signal at node **2814**. The comparison is not done directly on core nodes, but rather through the replica branch provided by transistor **Q2802**, resistor **R3** designated **2830**, and diode **D2818** as discussed above. In FIG. **29(b)** the VDD supply voltage is shown crossing a minimum allowable

operational threshold with respect to time. Waveform **3002** represents the voltage at node (3), waveform **3004** represents the voltage at node (1), waveform **3006** represents the voltage at the top of resistor **R3** at node (2), and voltage difference **3008** represents a guaranteed crossing voltage difference due to steady state core current  $I$  multiplied by  $R3$ .

Referring now to FIG. 30, a prior art demodulation circuit **3100** is shown including an RF input at node **3114**, an input diode **3102** coupled between input node **3114** and node **3116**. A resistor **3104** in parallel with capacitor **3106** is coupled to node **3116**. Diode **3102**, resistor **3104**, and capacitor **3106** form an envelope detector as is known in the art. The signal at node **3116** is filtered by a low pass filter including resistor **3108** and capacitor **3110**. The output of the low pass filter at node **3118**, and the envelope signal at node **3116** are received by a comparator **3112** to provide a data output digital signal at output node **3120**.

Referring now to FIG. 31, a timing diagram is shown including the RF waveform **3114** and the envelope waveform **3116**. The timing diagram of FIG. 32 shows the envelope waveform **3116**, as well as the output waveform showing the desirable average value and the undesirable ripple that is produced due to the averaging circuit **3100**.

Prior art RFID demodulation circuits such as those described above may not provide proper operation over all input power levels due to large input signals at high power. Averaging schemes to correct this problem are problematic because they are data rate dependent, leading to a variation in pulse widths during the averaging transient. To correct this problem, a fixed reference was added where the power level reduction in operating margin was detected. An additional signal dependent current was added to the reference voltage so that higher power levels generated their own higher level reference as is explained in further detail below.

Transient pulse width changes with averaging circuits corrupt data detection. With existing averaging circuits a single filter time constant is not sufficient for both low and high data rates. At high data rates the ripple signal on the average is low, but there is a long transient during which the duty cycle changes. At low data rates the ripple signal is large and can cross the detection threshold depending on input power level. Both of these extremes can see errors in data detection during startup conditions.

Referring now to FIG. 33, a dynamic adjusting RFID demodulation circuit **3400** is shown according to the present invention. Dynamic adjusting RFID demodulator circuit **3400** includes an envelope detector **3402**, **3404**, **3406** having an input for receiving a modulated RF signal at node **3422**, a fixed reference **3412**, **Q3414** coupled to the input of an RC filter **3416**, **3418** and a comparator **3420** having a first input coupled to the output of the envelope detector, a second input coupled to an output of the RC filter, and an output for providing a data output signal at node **3430**. The envelope detector includes an input diode **3402**, parallel resistor **3404** and capacitor **3406**, as well as an output diode **3408** and an output resistor **3410**. The fixed reference includes a current source **3412**, which can be a thermally compensated current source derived from a bandgap circuit, and a diode-connected N-channel transistor **Q3414**. Other fixed references can be used. The RC filter includes a resistor **3416** and a capacitor **3418**. The first input of the comparator **3424** is a positive input and the second input is a negative input in a preferred embodiment.

Demodulator circuit **3400** of the present invention thus includes a fixed reference generated by a current source (from a bandgap circuit if desired) and a diode-connected MOS transistor and an RC filter plus another energy path activated

at higher power levels that inject current into the output of the RC filter at the input to the comparator. The threshold of the comparator is thus augmented proportionally to the input power so that high power and low power RF input signals are equally discriminated.

Referring now to FIGS. 34-36, various circuit waveforms are shown that illustrate the dynamic threshold of circuit **3400** responding to different input levels. In FIG. 34, two RF envelopes are shown. A first RF envelope **3424A** is shown at low power levels. A second RF envelope **3424B** is shown at relatively higher power levels. The threshold voltage for comparator **3420** at low power levels is the same at both nodes **3426** and **3428**. However, as is shown in FIG. 35, the voltage levels at nodes **3426** and **3428** are different at higher power levels. That is, the voltage at node **3428** is greater than that at node **3426** at higher power levels. Finally, in FIG. 36, the voltage at node **3428** is shown with respect to increasing RF input power levels. The voltage at node **3428** begins at a first level and increases as the input power is increased.

Referring now to FIG. 37A, a schematic diagram of a prior art shunt voltage regulator **3800** is shown in the context of an RFID tag application. A rectifier **3802** receives an RF input signal, which is rectified to provide a supply voltage, which is the same voltage node that is regulated,  $V_{REG}$ , as is known for a shunt regulator. A resistor divider circuit and comparator **3804** are coupled between  $V_{REG}$  and ground. The resistor divider circuit and comparator receive an input reference voltage and provide a control voltage at node **3812** for a discharge device. A P-channel discharge device shown here for example, transistor **Q3806** has a source coupled to the  $V_{REG}$  node, a gate for receiving the control voltage at node **3812**, and a drain coupled to ground. The  $V_{REG}$  is coupled to a large holding capacitor **3808**, which provides a stable voltage and energy for powering on-chip circuits such as a FRAM memory circuit, various digital and analog circuits, and I/O circuits.

The resistor divider circuit and comparator **3804** are shown in further detail in FIG. 37B, wherein a resistor divider including resistors **3814** and **3816** is coupled between the  $V_{REG}$  and ground. An amplifier **3818** receives the input reference voltage at a first input (negative) and a tap voltage of the resistor divider at a second input (positive). The output voltage of the amplifier **3818** provides the control voltage for the P-channel transistor **Q3806** at node **3812** as shown.

The holding capacitor **3808** is effectively the on-chip power supply voltage for the rest of the integrated circuit, or circuits in an RFID tag. The voltage on the capacitor **3808** is from charge harvested from an RF reader. It is important that this charge be conserved and not wasted during any regulation operations.

Referring now to FIG. 38, a shunt regulator **3900** for an RFID tag chip according to the present invention is shown having a split source output from the RF rectifier including a first output **3914** for providing a power delivery path to on-chip circuits **3916** and a second output **3924** for providing a discharge-regulation path. As previously discussed, the on-chip circuits can include a FRAM memory circuit, I/O circuits, and other digital and analog circuitry as required for a specific application. A large holding capacitor **3912** is coupled between the first output **3914** and ground. The shunt regulator **3900** includes an input node **3902** for receiving a power supply voltage from a rectifier output, a first diode **3904** having an anode coupled to the input node, a second diode **3906** having an anode coupled to the input node, a resistor divider circuit and comparator **3908** coupled between a cathode of the first diode and ground, a P-channel transistor **3910** having a control terminal coupled to an output of the

resistor divider circuit and comparator at node **3918**, and a current path coupled between a cathode of the second diode and ground, wherein the cathode of the first diode forms the first output **3914** and the cathode of the second diode forms the second output **3924**.

The resistor divider and comparator circuit **3908** are substantially the same as is shown in FIG. **37B**.

Referring now to FIG. **39** a plot **4000** is shown of the unregulated voltage waveform **4002** and the regulated voltage waveform **4004** with respect to ground. The input unregulated voltage **4002**, which exceeds a desirable upper value, is shown to be regulated to a constant acceptable upper value in the regulated voltage **4004**. Note that current **ICONTROL**, shown in FIG. **38** pulls down node **3902**, isolating node **3914** in the presence of excess RF energy.

Referring to FIG. **40**, the input voltage from the rectifier at node **3902** is plotted in juxtaposition with the output voltage at the first output node **3914** with the shunt regulator crossing into regulation. An overvoltage condition results in activation of **Q3910** in FIG. **39** dumping excess harvested energy and pulling down node **3902** and isolating **3914** and not discharging capacitor **3912**. Note that in the case of a voltage drop-out due to loss of contact with the RF reader, the input voltage also drops; however, the on-chip power supply voltage at node **3914** remains high momentarily, and the extra charge is conserved and can be continued to be used for powering on-chip circuits. With the separation of the discharge-regulation path from the power delivery path regulation can be maintained while not removing the charge from the hold capacitor **3912** that powers the rest of the circuitry. Separating the outputs according to the present invention as described makes the RFID tag more efficient.

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the invention. As would be apparent to those skilled in the art, equivalent embodiments of the present invention can be realized in firmware, software, or hardware, or any possible combination thereof. In addition, although representative block diagrams are shown for an aid in understanding the invention, the exact boundaries of the blocks may be changed and combined or separated out as desired for a particular application or implementation. Finally, although FRAM memory is described and claimed, the present invention is also applicable to any other high speed non-volatile memory technology. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is claimed is:

1. A low power voltage regulator comprising:

a first diode-connected transistor of a first polarity type in series with a second diode-connected transistor of a second polarity type coupled between an output node and ground;

a first bias current having a value for biasing the first and second diode-connected transistors in a sub-threshold mode of operation; and

a buffer amplifier comprising an input transistor having a gate forming an input of the buffer amplifier coupled to the output node, a drain, and a source forming an output of the buffer amplifier for providing the regulated output voltage, a feedback transistor having a gate coupled to the drain of the input transistor, a source for coupling to a power supply voltage, and a drain coupled to the source of the input transistor, a second bias current coupled to

the drain of the input transistor, and a third bias current coupled to the source of the input transistor.

2. The low power voltage regulator of claim **1** wherein the first diode-connected transistor comprises a P-channel transistor.

3. The low power voltage regulator of claim **1** wherein the second diode-connected transistor comprises an N-channel transistor.

4. The low power voltage regulator of claim **1** wherein the first bias current is generated by a bandgap circuit.

5. A method of providing a regulated output voltage comprising:

providing a first diode-connected transistor of a first polarity type in series with a second diode-connected transistor of a second polarity type coupled between an output node and ground; and

biasing with a first bias current the first and second diode-connected transistors in a sub-threshold mode of operation for low power operation; and

buffering the regulated output voltage with a buffer amplifier comprising an input transistor having a gate forming an input of the buffer amplifier coupled to the output node, a drain, and a source forming an output of the buffer amplifier for providing the regulated output voltage, a feedback transistor having a gate coupled to the drain of the input transistor, a source for coupling to a power supply voltage, and a drain coupled to the source of the input transistor, a second bias current coupled to the drain of the input transistor, and a third bias current coupled to the source of the input transistor.

6. The method of claim **5** wherein the first diode-connected transistor comprises a P-channel transistor.

7. The method of claim **5** wherein the second diode-connected transistor comprises an N-channel transistor.

8. A low power voltage regulator comprising:

a first diode-connected transistor of a first polarity type in series with a second diode-connected transistor of a second polarity type coupled between an output node and ground;

a first bias current having a value for biasing the first and second diode-connected transistors in a sub-threshold mode of operation;

a third transistor coupled between the first bias current and the first and second diode-connected transistors; and

a buffer amplifier coupled to the third transistor, the buffer amplifier comprising:

an input transistor having a gate forming an input of the buffer amplifier, a drain, and a source forming an output of the buffer amplifier for providing the regulated output voltage;

a feedback transistor having a gate coupled to the drain of the input transistor, a source for coupling to a power supply voltage, and a drain coupled to the source of the input transistor;

a second bias current coupled to the drain of the input transistor; and

a third bias current coupled to the source of the input transistor.

9. The low power voltage regulator of claim **8** wherein the third bias current is greater than the second bias current.

10. The low power voltage regulator of claim **8** wherein the input transistor comprises an N-channel transistor.

11. The low power voltage regulator of claim **8** wherein the feedback transistor comprises a P-channel transistor.

12. The low power voltage regulator of claim **8** wherein the first diode-connected transistor comprises a P-channel transistor.

**15**

**13.** The low power voltage regulator of claim **8** wherein the second diode-connected transistor comprises an N-channel transistor.

**14.** The low power voltage regulator of claim **8** wherein the first bias current is generated by a bandgap circuit. 5

\* \* \* \* \*

**16**