



(51) International Patent Classification:

G06Q 10/06 (2012.01)

(21) International Application Number:

PCT/US2020/050850

(22) International Filing Date:

15 September 2020 (15.09.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16/576,434 19 September 2019 (19.09.2019) US

(71) Applicant: **AFINITI, LTD.** [—/US]; 50 Cedar Avenue,
Crawford House, Hamilton, HM 11 (BM).

(72) Inventors: **O'BRIEN, Caroline**; 25a Sandridge St., Bon-
di Nsw, 2026 (AU). **LOPEZ-PORTILLO, Julian**; Carlos
Dickens 68, Int 201, Polanco, Mexico City, 11540 (MX).
GARBACIK, Karl; 1701 Pennsylvania Ave. Nw, Ste. 600,
Washington, DC 20006 (US). **KAN, Ittai**; 7303 Hooking
Road, Mclean, VA 22101 (US).

(74) Agent: **ANDERSON, Thomas, E.** et al.; Wilmer Cutler
Pickering Hale And Dorr LLP, 1875 Pennsylvania Avenue,
Nw, Washington, DC 20006 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN,
HR, HU, ID, IL, IN, IR, IS, IT, JO, JP, KE, KG, KH, KN,
KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO,
NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW,
SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: TECHNIQUES FOR DECISIONING BEHAVIORAL PAIRING IN A TASK ASSIGNMENT SYSTEM

(57) Abstract: Techniques for decisioning behavioral pairing in a task assign-
ment system are disclosed. In one particular embodiment, the techniques may
be realized as a method for decisioning behavioral pairing in a task assignment
system comprising: determining, by at least one computer processor commu-
nicatively coupled to and configured to operate in the task assignment system,
a plurality of possible task-agent pairings among at least one task waiting for
assignment and at least one agent available for assignment; and selecting, by the
least one computer processor for assignment in the task assignment system, a
first task-agent pairing of the plurality of possible task-agent pairings based at
least in part on a first offer set to be offered by the agent or a first compensation
to be received by the agent.




FIG. 1

TECHNIQUES FOR DECISIONING BEHAVIORAL PAIRING
IN A TASK ASSIGNMENT SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This international patent application is claiming priority to U.S. Patent Application No. 16/576,434, filed September 19, 2019, which is hereby incorporated by reference herein in its entirety.

FIELD OF THE DISCLOSURE

 The present disclosure generally relates to behavioral pairing and, more particularly, to
10 techniques for decisioning behavioral pairing in a task assignment system.

BACKGROUND OF THE DISCLOSURE

 A typical task assignment system algorithmically assigns tasks arriving at a task assignment center to agents available to handle those tasks. At times, the task assignment center
15 may be in an “L1 state” and have agents available and waiting for assignment to tasks. At other times, the task assignment center may be in an “L2 state” and have tasks waiting in one or more queues for an agent to become available for assignment.

 In some typical task assignment centers, tasks are assigned to agents ordered based on time of arrival, and agents receive tasks ordered based on the time when those agents became
20 available. This strategy may be referred to as a “first-in, first-out,” “FIFO,” or “round-robin” strategy. For example, in an L2 environment, when an agent becomes available, the task at the head of the queue would be selected for assignment to the agent.

 In other typical task assignment centers, a performance-based routing (PBR) strategy for prioritizing higher-performing agents for task assignment may be implemented. Under
25 PBR, for example, the highest-performing agent among available agents receives the next

available task. Other PBR and PBR-like strategies may make assignments using specific information about the agents.

“Behavioral Pairing” or “BP” strategies, for assigning tasks to agents, improve upon traditional assignment methods. BP targets balanced utilization of agents while simultaneously improving overall task assignment center performance potentially beyond what FIFO or PBR methods will achieve in practice.

In some task assignment systems, it may be advantageous to consider the next-best action for a task given its assignment to a particular agent. Thus, it may be understood that there may be a need for a decisioning BP strategy that takes into consideration the next-best action for a task-agent pairing in order to optimize the overall performance of the task assignment system.

SUMMARY OF THE DISCLOSURE

Techniques for decisioning behavioral pairing in a task assignment system are disclosed. In one particular embodiment, the techniques may be realized as a method for decisioning behavioral pairing in a task assignment system comprising: determining, by at least one computer processor communicatively coupled to and configured to operate in the task assignment system, a plurality of possible task–agent pairings among at least one task waiting for assignment and at least one agent available for assignment; and selecting, by the least one computer processor for assignment in the task assignment system, a first task–agent pairing of the plurality of possible task–agent pairings based at least in part on a first offer set to be offered by the agent or a first compensation to be received by the agent.

In accordance with other aspects of this particular embodiment, the task assignment system may be a contact center system.

In accordance with other aspects of this particular embodiment, selecting the first task–agent pairing may be based at least in part on both the first offer set and the first compensation.

In accordance with other aspects of this particular embodiment, the method may further comprise selecting, by the at least one computer processor, the first offer set from a plurality
5 of potential offer sets.

In accordance with other aspects of this particular embodiment, the method may further comprise selecting, by the at least one computer processor, the first compensation from a plurality of potential compensations.

In accordance with other aspects of this particular embodiment, selecting the first task–
10 agent pairing may be based on at least one of a first ordering of a plurality of tasks and a second ordering of a plurality of agents, and wherein the at least one of the first and second orderings is expressed as percentiles or percentile ranges.

In accordance with other aspects of this particular embodiment, the method may further comprise adjusting, by the at least one computer processor, the first offer set or the first
15 compensation to adjust the first or second orderings.

In another particular embodiment, the techniques may be realized as a system for decisioning behavioral pairing in a task assignment system comprising at least one computer processor communicatively coupled to and configured to operate in the task assignment system, wherein the at least one computer processor is further configured to perform the steps in the
20 above-described method.

In another particular embodiment, the techniques may be realized as an article of manufacture for decisioning behavioral pairing in a task assignment system comprising a non-transitory processor readable medium and instructions stored on the medium, wherein the instructions are configured to be readable from the medium by at least one computer processor
25 communicatively coupled to and configured to operate in the task assignment system and

thereby cause the at least one computer processor to operate so as to perform the steps in the above-described method.

The present disclosure will now be described in more detail with reference to particular embodiments thereof as shown in the accompanying drawings. While the present disclosure is described below with reference to particular embodiments, it should be understood that the present disclosure is not limited thereto. Those of ordinary skill in the art having access to the teachings herein will recognize additional implementations, modifications, and embodiments, as well as other fields of use, which are within the scope of the present disclosure as described herein, and with respect to which the present disclosure may be of significant utility.

BRIEF DESCRIPTION OF THE DRAWINGS

To facilitate a fuller understanding of the present disclosure, reference is now made to the accompanying drawings, in which like elements are referenced with like numerals. These drawings should not be construed as limiting the present disclosure, but are intended to be illustrative only.

FIG. 1 shows a block diagram of a task assignment center according to embodiments of the present disclosure.

FIG. 2 shows a block diagram of a task assignment system according to embodiments of the present disclosure.

FIG. 3 shows a flow diagram of a task assignment method according to embodiments of the present disclosure.

DETAILED DESCRIPTION

A typical task assignment system algorithmically assigns tasks arriving at a task assignment center to agents available to handle those tasks. At times, the task assignment center

may be in an “L1 state” and have agents available and waiting for assignment to tasks. At other times, the task assignment center may be in an “L2 state” and have tasks waiting in one or more queues for an agent to become available for assignment. At yet other times, the task assignment system may be in an “L3” state and have multiple agents available and multiple tasks waiting for assignment. An example of a task assignment system is a contact center system that receives contacts (*e.g.*, telephone calls, internet chat sessions, emails, etc.) to be assigned to agents.

In some traditional task assignment centers, tasks (*e.g.*, callers) are assigned to agents ordered based on time of arrival, and agents receive tasks ordered based on the time when those agents became available. This strategy may be referred to as a “first-in, first-out,” “FIFO,” or “round-robin” strategy. For example, in an L2 environment, when an agent becomes available, the task at the head of the queue would be selected for assignment to the agent. In other traditional task assignment centers, a performance-based routing (PBR) strategy for prioritizing higher-performing agents for task assignment may be implemented. Under PBR, for example, the highest-performing agent among available agents receives the next available task.

The present disclosure refers to optimized strategies, such as “Behavioral Pairing” or “BP” strategies, for assigning tasks to agents that improve upon traditional assignment methods. BP targets balanced utilization of agents while simultaneously improving overall task assignment center performance potentially beyond what FIFO or PBR methods will achieve in practice. This is a remarkable achievement inasmuch as BP acts on the same tasks and same agents as FIFO or PBR methods, approximately balancing the utilization of agents as FIFO provides, while improving overall task assignment center performance beyond what either FIFO or PBR provide in practice. BP improves performance by assigning agent and task pairs in a fashion that takes into consideration the assignment of potential subsequent agent and task pairs such that, when the benefits of all assignments are aggregated, they may exceed those of FIFO and PBR strategies.

Various BP strategies may be used, such as a diagonal model BP strategy or a network flow (or “off-diagonal”) BP strategy. These task assignment strategies and others are described in detail for a contact center context in, *e.g.*, U.S. Patent Nos. 9,300,802; 9,781,269; 9,787,841; and 9,930,180; all of which are hereby incorporated by reference herein. BP strategies may be applied in an L1 environment (agent surplus, one task; select among multiple available/idle agents), an L2 environment (task surplus, one available/idle agent; select among multiple tasks in queue), and an L3 environment (multiple agents and multiple tasks; select among pairing permutations).

The various BP strategies discussed above may be considered two-dimensional (2-D), where one dimension relates to the agents, and the second dimension relates to the tasks (*e.g.*, callers), and the various BP strategies take into account information about agents and tasks to pair them. As explained in detail below, embodiments of the present disclosure relate to decisioning BP strategies that account for higher-dimensional assignments. For a three-dimensional (3-D) example, the BP strategy may assign an agent to both a task and a set of offers the agent can make or a set of actions the agent can take during the task assignment. For another 3-D example, the BP strategy may assign an agent to both a task and a (monetary or non-monetary) reward to be given to an agent for a given task assignment. For a four-dimensional (4-D) example, the BP strategy may assign an agent to a task, an offer set, and a reward.

These decisioning BP strategies may also consider historical outcome data for, *e.g.*, agent–task–offers, agent–task–reward, or agent–task–offer–reward pairings to build a BP model and apply a BP strategy to “pair” a task with an agent and a specific offer set and/or agent compensation (throughout the specification, the noun and verb “pair” and other forms such as “Behavioral Pairing” may be used to describe triads and higher-dimensional groupings).

FIG. 1 shows a block diagram of a task assignment center 100 according to embodiments of the present disclosure. The description herein describes network elements, computers, and/or components of a system and method for pairing strategies in a task assignment system that may include one or more modules. As used herein, the term “module”
5 may be understood to refer to computing software, firmware, hardware, and/or various combinations thereof. Modules, however, are not to be interpreted as software which is not implemented on hardware, firmware, or recorded on a non-transitory processor readable recordable storage medium (*i.e.*, modules are not software *per se*). It is noted that the modules are exemplary. The modules may be combined, integrated, separated, and/or duplicated to
10 support various applications. Also, a function described herein as being performed at a particular module may be performed at one or more other modules and/or by one or more other devices instead of or in addition to the function performed at the particular module. Further, the modules may be implemented across multiple devices and/or other components local or remote to one another. Additionally, the modules may be moved from one device and added to
15 another device, and/or may be included in both devices.

As shown in FIG. 1, the task assignment center 100 may include a central switch 210. The central switch 110 may receive incoming tasks (*e.g.*, telephone calls, internet chat sessions, emails, etc.) or support outbound connections to contacts via a dialer, a telecommunications network, or other modules (not shown). The central switch 110 may include routing hardware
20 and software for helping to route tasks among one or more subcenters, or to one or more Private Branch Exchange (“PBX”) or Automatic Call Distribution (ACD) routing components or other queuing or switching components within the task assignment center 100. The central switch 110 may not be necessary if there is only one subcenter, or if there is only one PBX or ACD routing component in the task assignment center 100.

If more than one subcenter is part of the task assignment center 100, each subcenter may include at least one switch (e.g., switches 120A and 120B). The switches 120A and 120B may be communicatively coupled to the central switch 110. Each switch for each subcenter may be communicatively coupled to a plurality (or “pool”) of agents. Each switch may support
5 a certain number of agents (or “seats”) to be logged in at one time. At any given time, a logged-in agent may be available and waiting to be connected to a task, or the logged-in agent may be unavailable for any of a number of reasons, such as being connected to another contact, performing certain post-call functions such as logging information about the call, or taking a break. In the example of FIG. 1, the central switch 110 routes tasks to one of two subcenters
10 via switch 120A and switch 120B, respectively. Each of the switches 120A and 120B are shown with two agents each. Agents 130A and 130B may be logged into switch 120A, and agents 130C and 130D may be logged into switch 120B.

The task assignment center 100 may also be communicatively coupled to an integrated service from, for example, a third-party vendor. In the example of FIG. 1, behavioral pairing
15 module 140 may be communicatively coupled to one or more switches in the switch system of the task assignment center 100, such as central switch 110, switch 120A, and switch 120B. In some embodiments, switches of the task assignment center 100 may be communicatively coupled to multiple behavioral pairing modules. In some embodiments, behavioral pairing module 140 may be embedded within a component of the task assignment center 100 (e.g.,
20 embedded in or otherwise integrated with a switch).

Behavioral pairing module 140 may receive information from a switch (e.g., switch 120A) about agents logged into the switch (e.g., agents 130A and 130B) and about incoming tasks via another switch (e.g., central switch 110) or, in some embodiments, from a network (e.g., the Internet or a telecommunications network) (not shown). The behavioral pairing
25 module 140 may process this information to determine which agents should be paired (e.g.,

matched, assigned, distributed, routed) with which tasks along with other dimensions (*e.g.*, offers, actions, channels, non-monetary rewards, monetary rewards or compensation, etc.).

For example, in an L1 state, multiple agents may be available and waiting for connection to a contact, and a task arrives at the task assignment center 100 via a network or the central switch 110. As explained above, without the behavioral pairing module 140, a switch will typically automatically distribute the new task to whichever available agent has been waiting the longest amount of time for an agent under a FIFO strategy, or whichever available agent has been determined to be the highest-performing agent under a PBR strategy. With a behavioral pairing module 140, contacts and agents may be given scores (*e.g.*, percentiles or percentile ranges/bandwidths) according to a pairing model or other artificial intelligence data model, so that a task may be matched, paired, or otherwise connected to a preferred agent. The higher-dimensional analysis of BP decisioning will be explained in more detail below.

In an L2 state, multiple tasks are available and waiting for connection to an agent, and an agent becomes available. These tasks may be queued in a switch such as a PBX or ACD device. Without the behavioral pairing module 140, a switch will typically connect the newly available agent to whichever task has been waiting on hold in the queue for the longest amount of time as in a FIFO strategy or a PBR strategy when agent choice is not available. In some task assignment centers, priority queuing may also be incorporated, as previously explained. With a behavioral pairing module 140 in this L2 scenario, as in the L1 state described above, tasks and agents may be given percentiles (or percentile ranges/bandwidths, etc.) according to, for example, a model, such as an artificial intelligence model, so that an agent becoming available may be matched, paired, or otherwise connected to a preferred task. The higher-dimensional analysis of BP decisioning will be explained in more detail below.

FIG. 2 shows a block diagram of a task assignment system 200 according to embodiments of the present disclosure. The task assignment system 200 may be included in a task assignment center (e.g., task assignment center 100) or incorporated in a component or module (e.g., behavioral pairing module 140) of a task assignment center for helping to assign agents among various tasks and other dimensions for grouping.

The task assignment system 200 may include a task assignment module 210 that is configured to pair (e.g., match, assign) incoming tasks to available agents. (The higher-dimensional analysis of BP decisioning will be explained in more detail below.) In the example of FIG. 2, m tasks 220A–220 m are received over a given period, and n agents 230A–230 n are available during the given period. Each of the m tasks may be assigned to one of the n agents for servicing or other types of task processing. In the example of FIG. 1, m and n may be arbitrarily large finite integers greater than or equal to one. In a real-world task assignment center, such as a contact center, there may be dozens, hundreds, etc. of agents logged into the contact center to interact with contacts during a shift, and the contact center may receive dozens, hundreds, thousands, etc. of contacts (e.g., telephone calls, internet chat sessions, emails, etc.) during the shift.

In some embodiments, a task assignment strategy module 240 may be communicatively coupled to and/or configured to operate in the task assignment system 200. The task assignment strategy module 240 may implement one or more task assignment strategies (or “pairing strategies”) for assigning individual tasks to individual agents (e.g., pairing contacts with contact center agents). A variety of different task assignment strategies may be devised and implemented by the task assignment strategy module 240. In some embodiments, a FIFO strategy may be implemented in which, for example, the longest-waiting agent receives the next available task (in L1 environments) or the longest-waiting task is assigned to the next available agent (in L2 environments). In other embodiments, a PBR strategy for prioritizing

higher-performing agents for task assignment may be implemented. Under PBR, for example, the highest-performing agent among available agents receives the next available task. In yet other embodiments, a BP strategy may be used for optimally assigning tasks to agents using information about either tasks or agents, or both. Various BP strategies may be used, such as a diagonal model BP strategy or a network flow (“off-diagonal”) BP strategy. *See* U.S. Patent Nos. 9,300,802; 9,781,269; 9,787,841; and 9,930,180.

In some embodiments, the task assignment strategy module 240 may implement a decisioning BP strategy that takes into account the next-best action for a task, when the task is assigned to a particular agent. For a task-agent pair, the decisioning BP strategy may also assign an action or set of actions available to the agent to complete the task. In the context of a contact center system, the action or set of actions may include an offer or a set of offers that the agent may present to a customer. For example, in a contact center system, a decisioning BP strategy may pair a contact with an agent along with an offer or set of offers available to the agent to make to a customer, based on the expected outcome of the contact-agent interaction using that particular offer or set of offers. By influencing the choices or options among offers available to an agent, a decisioning BP strategy goes beyond pairing a contact to an agent by optimizing the outcome of the individual interaction between the agent and the contact.

For example, if agent 230A loves sports, agent 230A may be more adept at selling sports packages. Therefore, sports packages may be included in agent 230A’s set of offers for some or all contact types. On the other hand, agent 230B may love movies and may be more adept at selling premium movie packages; so premium movie packages may be included in agent 230B’s set of offers for some or all contact types. Further, based on an artificial intelligence process such as machine learning, a decisioning BP model may automatically segment customers over a variety of variables and data types. For example, the decisioning BP model may recommend offering a package that includes sports to a first type of customer

(“Customer Type 1”) that may fit a particular age range, income range, and other demographic and psychographic factors. The decisioning BP model may recommend offering a premium movie package to a second type of customer (“Customer Type 2”) that may fit a different age range, income range, or other demographic or psychographic factors. A decisioning BP strategy
5 may preferably pair a Customer Type 1 with agent 230A and an offer set with a sports package, and a Customer Type 2 with agent 230B and an offer set with a premium movie package.

As with previously-disclosed BP strategies, a decisioning BP strategy optimizes the overall performance of the task assignment system rather than every individual instant task-agent pairing. For instance, in some embodiments, a decisioning BP system will not always
10 offer sports to a Customer Type 1, nor will agent 230A always be given the option of offering deals based on a sports package. Such a scenario may arise when a marketing division of a company running a contact center system may have a budget for a finite, limited number deals (*e.g.*, a limited number of discounted sports packages), other constraints on the frequency of certain offers, limits on the total amount of discounts (*e.g.*, for any discount or discounted
15 package) that can be made over a given time period, etc. Similarly, deals based on sports may sometimes be offered to a Customer Type 2, and agent 230B may sometimes be given the option of offering deals based on a sports package.

To optimize the overall performance of the task assignment system, a decisioning BP strategy may account for all types of customers waiting in a queue, agents available for
20 customers, and any other dimensions for pairing such as the number and types of offers remaining, agent compensation or other non-monetary rewards, next-best actions, etc. In some embodiments, a probability distribution may be assigned based on the likelihood that an incoming task or customer type will accept a given offer level based on the agent being paired with the task or customer.

For example, for a Customer Type 1, if the discount offered is 0%, the likelihood of the customer accepting the offer from an average agent is 0%, and the likelihood of accepting the offer specifically from agent 230A is also 0% and from agent 230B is also 0%. For a 20% discount offer, the likelihood of the customer accepting the offer from an average agent may be 30%, whereas the likelihood of accepting the offer from agent 230A may be 60% and from agent 230B may be 25%. In a scenario where an average agent, agent 230A, and agent 230B are all assigned to the queue and available, it is possible for agent 230A to perform much higher than the average agent or agent 230B.

In some embodiments, an output measurement may be attached to each task before and after interaction with an agent. For example, a revenue number may be attached to each caller pre- and post-call. A decisioning BP system may measure the change in revenue and the influenceability of a caller based on an offer or a set of offers presented by an agent. For example, a Customer Type 1 may be more likely to renew her existing plan regardless of the discount offered, or regardless of the ability of the individual agent. A Customer Type 2 may be preferably assigned to a lower-performing agent with a higher cap on discounts in the offer set. In contrast, a Customer Type 2 may be more likely to upgrade her plans if she were paired with a higher-performing agent or an agent authorized to offer steeper discounts.

In some embodiments, a decisioning BP strategy may make sequential pairings of one or more dimensions in an arbitrary order. For example, the decisioning BP strategy may first pair an agent to a task and then pair an offer set to the agent–task pairing, then pair a reward to the agent–task–offer set pairing, and so on.

In other embodiments, a decisioning BP strategy may make “fully-coupled,” simultaneous multidimensional pairings. For example, the decisioning BP strategy may consider all dimensions at once to select an optimal 4-D agent–task–offers–reward pairing.

The same task may arrive at the task assignment system multiple times (*e.g.*, the same caller calls a call center multiple times). In these “multi-touch” scenarios, in some embodiments, the task assignment system may always assign the same item for one or more dimensions to promote consistency. For example, if a task is paired with a particular offer set the first time the task arrives, the task will be paired with the same offer set each subsequent time the task arrives (*e.g.*, for a given issue, within a given time period, etc.).

In some embodiments, a historical assignment module 250 may be communicatively coupled to and/or configured to operate in the task assignment system 200 via other modules such as the task assignment module 210 and/or the task assignment strategy module 240. The historical assignment module 250 may be responsible for various functions such as monitoring, storing, retrieving, and/or outputting information about task–agent assignments and higher-dimensional assignments that have already been made. For example, the historical assignment module 250 may monitor the task assignment module 210 to collect information about task assignments in a given period. Each record of a historical task assignment may include information such as an agent identifier, a task or task type identifier, offer or offer set identifier, outcome information, or a pairing strategy identifier (*i.e.*, an identifier indicating whether a task assignment was made using a BP strategy, a decisioning BP strategy, or some other pairing strategy such as a FIFO or PBR pairing strategy).

In some embodiments and for some contexts, additional information may be stored. For example, in a call center context, the historical assignment module 250 may also store information about the time a call started, the time a call ended, the phone number dialed, and the caller’s phone number. For another example, in a dispatch center (*e.g.*, “truck roll”) context, the historical assignment module 250 may also store information about the time a driver (*i.e.*, field agent) departs from the dispatch center, the route recommended, the route taken, the

estimated travel time, the actual travel time, the amount of time spent at the customer site handling the customer's task, etc.

In some embodiments, the historical assignment module 250 may generate a pairing model, a decisioning BP model, or similar computer processor-generated model based on a set of historical assignments for a period of time (*e.g.*, the past week, the past month, the past year, etc.), which may be used by the task assignment strategy module 240 to make task assignment recommendations or instructions to the task assignment module 210.

In some embodiments, instead of relying on predetermined offer sets in generating a decisioning BP model, the historical assignment module 250 may analyze historical outcome data to create or determine new or different offer sets, which are then incorporated into the decisioning BP model. This approach may be preferred when there is a budget or other limitation on the number of a particular offer set that may be made. For example, the marketing division may have limited the contact center system to five hundred discounted sports packages and five hundred discounted movie packages per month, and the company may want to optimize total revenue irrespective of how many sports and movie packages are sold, with or without a discount. Under such a scenario, the decisioning BP model may be similar to previously-disclosed BP diagonal models, except that, in addition to the "task or contact percentile" (CP) dimension and the "agent percentile" (AP) dimension, there may be a third "revenue or offer set percentile" dimension. Moreover, all three dimensions may be normalized or processed with mean regression (*e.g.*, Bayesian mean regression (BMR) or hierarchical BMR).

In some embodiments, the historical assignment module 250 may generate a decisioning BP model that optimizes task-agent-offer set pairing based on individual channels or multi-channel interactions. The historical assignment module 250 may treat different channels differently. For example, a decisioning BP model may preferably pair a contact with

different agents or offer sets depending on whether the contact calls a call center, initiates a chat session, sends an email or text message, enters a retail store, etc.

In some embodiments, the task assignment strategy module 240 may proactively create tasks or other actions (*e.g.*, recommend outbound contact interactions, next-best actions, etc.)

5 based on information about a contact or a customer, available agents, and available offer sets.

For example, the task assignment system 200 may determine that a customer's contract is set to expire, the customer's usage is declining, or the customer's credit rating is declining. The task assignment system 200 may further determine that the customer is unlikely to renew the

10 assignment module 250). The task assignment system 200 may determine that the next-best

action is to call the customer (contact selection, channel selection, and timing selection), connect with a particular agent (agent selection), and give the agent the option to offer a downgrade at a particular discount or range of discounts (offer set selection). If the customer

does not come to an agreement during the call, the task assignment system 200 may further
15 determine that this customer is more likely to accept a downgrade discount offer if the agent follows up with a text message with information about the discount and how to confirm (multi-channel selection and optimization).

In some embodiment, similar to how a Kappa (κ) parameter is used to adjust/skew the agent percentile or percentile range (*see* U.S. Patent No. 9,781,269) and how a Rho (ρ)

20 parameter is used to adjust/skew the task or contact percentile or percentile range (*see* U.S.

Patent No. 9,787,841), the task assignment strategy module 240 may apply an Iota (ι) parameter to a third (or higher) dimension such as the offer set percentile or percentile range in a decisioning BP strategy. With the Iota parameter, the task assignment strategy module 240

may, for example, adjust the offer set percentile or percentile range (or other dimensions) to

25 skew task-agent-offer set pairing toward higher-performing offers and imbalance offer set

availability. The Iota parameter may be applied in either L1 or L2 environment and may be used in conjunction with Kappa or Rho parameter, or it may be applied with both Kappa and Rho parameters in an L3 environment. For example, if the task assignment strategy module 240 determines that the expected wait time for a contact has exceeded 100 seconds (high congestion), it may apply the Iota parameter so that an agent is more likely to have steeper discounts available to offer, which can be sold more quickly to reduce congestion and the expected wait time. More generous offers can speed up task-agent interaction, thereby reducing average handle time (AHT). When congestion is low, expected wait time may be low, and the Iota parameter may be adjusted to make only less generous offers available. These calls may take longer, and AHT may increase, but sales and revenue may be expected to increase as well.

In some embodiments, the task assignment strategy module 240 may optimize performance by optimizing for multiple business objectives or other goals simultaneously. Where the objectives are competing (*e.g.*, discount amount and retention rates), module 240 may balance the tradeoff between the two objectives. For example, the task assignment strategy module 240 may balance increasing (or maintaining) revenue with maintaining or minimally decreasing retention rates, or it may balance decreasing (or maintaining) AHT with increasing (or maintaining) customer satisfaction, etc.

In some embodiments, the task assignment strategy module 240 may implement a decisioning BP strategy that takes into account agent compensation in lieu of an offer or offer set. The framework is similar to the description above, except that, instead of influencing a customer with an offer or offer set, the decisioning BP strategy influences the performance of an agent with a compensation that the agent may receive. In other words, instead of the task-agent-offer set three-dimensional pairing, the decisioning BP strategy makes a three-dimensional pairing of task-agent-reward. In some embodiments, a decisioning BP strategy may make a four-way pairing of task-agent-offer-reward.

A decisioning BP strategy being capable of providing variable agent compensation based on task-agent pairing may lead to better transparency and fairness. For example, some task assignment (*e.g.*, contact center) systems may see a mix of more challenging and less challenging contacts and employ a mix of higher-performing and lower-performing agents.

5 Under a FIFO strategy or a PBR strategy, agents of any ability are equally likely to be paired with more or less challenging contacts. Under a FIFO strategy, the overall performance of the contact center system may be low, but the average agent compensation may be transparent and fair. Under a PBR strategy, agent utilization may be skewed, and compensation may also be skewed toward higher-performing agents. Under previously-disclosed BP strategies, a more
10 challenging contact type may be preferably paired with a higher-performing agent, whereas a less challenging contact type may be preferably paired with a lower-performing agent. For example, if a high-performing agent gets more difficult calls on average, this “call type skew” may result in the high-performing agent’s conversion rate going down and compensation going down.

15 Therefore, adjusting an agent’s compensation up or down for a given task (or contact) types may improve the fairness of compensation under the previously-disclosed BP strategies. When an agent is paired with a task or contact, a decisioning BP strategy may inform the agent of the expected value of the contact to the contact center and/or how much the agent will receive as a commission or other non-monetary reward for handling the contact or achieving a
20 particular outcome. The decisioning BP strategy may influence the agent’s behavior through offering variable compensation. For example, if the decisioning BP strategy determines that the agent should process the task or contact quickly (lower AHT, lower revenue), the decisioning BP strategy may select a lower compensation. Consequently, the agent may have less incentive to spend a lot of time earning a relatively lower commission. In contrast, if the
25 decisioning BP strategy determines that the agent should put high effort into a higher value call

(higher AHT, higher revenue), it may select a higher compensation. Such a decisioning BP strategy may maximize an agent's reward while improving the overall performance of the task assignment system 200.

The historical assignment module 250 may model a decisioning BP model based on historical information about task types, agents, and compensation amounts so that a simultaneous selection of task-agent-reward may be made. The amount of variation in compensation up or down may vary and depend on each combination of an individual agent and contact type, with the goal of improving the overall performance of the task assignment system 200.

Similar to applying the Iota parameter to the offer set or next-best action percentile or percentile range dimension, and as noted above, the task assignment strategy module 240 may apply an Iota parameter to other dimensions, such as skewing agent compensation to a greater or lesser degree, or to generally higher or generally lower values. In some embodiments, the amount and type of Iota parameter applied to agent compensation or other non-monetary rewards may be based at least in part on factors in the task assignment system 200 (*e.g.*, the expected wait time of callers on hold in a call center).

In some embodiments that employ strategies that are similar to the diagonal model BP strategy, a variable compensation may be viewed as temporarily influencing the effective agent percentile (AP) of an available agent to be higher or lower, in order to move an available contact-agent pairing closer to the optimal diagonal. Similarly, adjusting the value of offers to be higher or lower may be viewed as influencing the effective contact percentile (CP) of a waiting contact to be higher or lower, in order to move an available contact-agent pairing closer to the optimal diagonal.

In some embodiments, a benchmarking module 260 may be communicatively coupled to and/or configured to operate in the task assignment system 200 via other modules such as

the task assignment module 210 and/or the historical assignment module 250. The benchmarking module 260 may benchmark the relative performance of two or more pairing strategies (*e.g.*, FIFO, PBR, BP, decisioning BP, etc.) using historical assignment information, which may be received from, for example, the historical assignment module 250. In some
5 embodiments, the benchmarking module 260 may perform other functions, such as establishing a benchmarking schedule for cycling among various pairing strategies, tracking cohorts (*e.g.*, base and measurement groups of historical assignments), etc. Benchmarking is described in detail for the contact center context in, *e.g.*, U.S. Patent No. 9,712,676, which is hereby incorporated by reference herein.

10 In some embodiments, the benchmarking module 260 may output or otherwise report or use the relative performance measurements. The relative performance measurements may be used to assess the quality of the task assignment strategy to determine, for example, whether a different task assignment strategy (or a different pairing model) should be used, or to measure the overall performance (or performance gain) that was achieved within the task assignment
15 system 200 while it was optimized or otherwise configured to use one task assignment strategy instead of another.

 In some embodiments, the benchmarking module 260 may benchmark a decisioning BP strategy against one or more alternative pairing strategies such as FIFO in conjunction with offer set availability. For example, in a contact center system, agents may have a matrix of nine
20 offers—three tiers of service levels, each with three discount levels. During “off” calls, the longest-waiting agent may be connected to the longest-waiting caller, and the agent may offer any of the nine offers. A high-performing agent may be more likely to sell a higher tier of service at a higher price, whereas a lower-performing agent may not try as hard and go immediately to offering the biggest discounts. During “on” calls, the decisioning BP strategy
25 may pair contacts with agents but limit agents to a subset of the nine available offers. For

example, for some contact types, a higher-performing agent may be empowered to make any of the nine offers, whereas a lower-performing agent may be limited to offer only the smaller discount for certain tiers, if the task assignment strategy module 240 determines, based on the decisioning BP model, that the overall performance of the contact center system may be optimized by selectively limiting the offer sets in a given way for a given contact–agent pairing. Additionally, if a provider (*e.g.*, vendor) that provides a task assignment system with decisioning BP strategy uses a benchmarking and revenue sharing business model, the provider may contribute a share of benchmarked revenue gain to the agent compensation pool.

In some embodiments, the task assignment system 200 may offer dashboards, visualizations, or other analytics and interfaces to improve overall performance of the system. For each agent, the analytics provided may vary depending on the relative ability or behavioral characteristics of an agent. For example, competitive or higher-performing agents may benefit from a rankings widget or other “gamification” elements (*e.g.*, badges or achievements to unlock points and score boards, notifications when agents overtake one another in the rankings, etc.). On the other hand, less competitive or lower-performing agents may benefit from periodic messages of encouragement, recommendations on training/education sessions, etc.

FIG. 3 shows a task assignment method 300 according to embodiments of the present disclosure.

Task assignment method 300 may begin at block 310. At block 310, the task assignment method 300 may order a plurality of tasks, which may be in queue in a task assignment system (*e.g.*, task assignment system 200). The task assignment method 300 may order the plurality of tasks by giving them percentiles or percentile ranges according to, for example, a model, such as an artificial intelligence model. In a contact center system, contacts may be ordered according to how long each contact has been waiting for an assignment to an agent relative to the other contacts, or how well each contact contributes to performance of the contact center

system for some metric relative to the other contacts. In other embodiments, the plurality of tasks may be analyzed according to an “off-diagonal” model (*e.g.*, a network flow model).

Task assignment method 300 may then proceed to block 320. At block 320, the task assignment method 300 may order a plurality of agents, who may be available in the task assignment system. The task assignment method 300 may order the plurality of agents by giving them percentiles or percentile ranges according to, for example, a model, such as an artificial intelligence model. In a contact center system, agents may be ordered according to how long each agent has been waiting for an assignment to a contact relative to the other agents, or how well each agent contributes to performance of the contact center system for some metric relative to the other agent. In other embodiments, the plurality of tasks may be analyzed according to a network flow model.

Task assignment method 300 may then proceed to block 330. At block 330, the task assignment method 300 may pair a task of the plurality of tasks to an agent of the plurality of agents. In some embodiments, the task-agent pairing may be based at least in part on the order of the plurality of tasks, the order of the plurality of agents, and at least one of a plurality of offers to be offered to the plurality of tasks or a compensation to be received by at least one of the plurality of agents. In some embodiments, the task-agent pairing may be based on an alternative behavioral pairing technique such as a network flow model.

In some embodiments, the task assignment method 300 may subsequently select an offer or offer set and/or an agent reward to be used in conjunction the task-agent pairing. In other embodiments, the task assignment method 300 may perform a three-way pairing (*e.g.*, task-agent-offers, task-agent-reward, etc.) or a four-way pairing (*e.g.*, task-agent-offer-reward). A given offer may skew or adjust the percentile or percentile range of task, while a given compensation may skew or adjust the percentile or percentile range of agent. Therefore, by considering at least one offer or a compensation, the task assignment method 300 is able to

select a task-agent (or task-agent-offer, task-agent-compensation, task-agent-offer-compensation, etc.) pairing that improves the overall performance of the task assignment system.

At this point it should be noted that task assignment in accordance with the present disclosure as described above may involve the processing of input data and the generation of output data to some extent. This input data processing and output data generation may be implemented in hardware or software. For example, specific electronic components may be employed in a behavioral pairing module or similar or related circuitry for implementing the functions associated with task assignment in accordance with the present disclosure as described above. Alternatively, one or more processors operating in accordance with instructions may implement the functions associated with task assignment in accordance with the present disclosure as described above. If such is the case, it is within the scope of the present disclosure that such instructions may be stored on one or more non-transitory processor readable storage media (*e.g.*, a magnetic disk or other storage medium), or transmitted to one or more processors via one or more signals embodied in one or more carrier waves.

The present disclosure is not to be limited in scope by the specific embodiments described herein. Indeed, other various embodiments of and modifications to the present disclosure, in addition to those described herein, will be apparent to those of ordinary skill in the art from the foregoing description and accompanying drawings. Thus, such other embodiments and modifications are intended to fall within the scope of the present disclosure. Further, although the present disclosure has been described herein in the context of at least one particular implementation in at least one particular environment for at least one particular purpose, those of ordinary skill in the art will recognize that its usefulness is not limited thereto and that the present disclosure may be beneficially implemented in any number of

environments for any number of purposes. Accordingly, the claims set forth below should be construed in view of the full breadth and spirit of the present disclosure as described herein.

CLAIMS

1. A method for decisioning behavioral pairing in a task assignment system comprising:

determining, by at least one computer processor communicatively coupled to and configured to operate in the task assignment system, a plurality of possible task–agent pairings among at least one task waiting for assignment and at least one agent available for assignment; and

selecting, by the least one computer processor for assignment in the task assignment system, a first task–agent pairing of the plurality of possible task–agent pairings based at least in part on a first offer set to be offered by the agent or a first compensation to be received by the agent.

2. The method of claim 1, wherein the task assignment system is a contact center system.

3. The method of claim 1, wherein the selecting is based at least in part on both the first offer set and the first compensation.

4. The method of claim 1, further comprising:

selecting, by the at least one computer processor, the first offer set from a plurality of potential offer sets.

5. The method of claim 1, further comprising:

selecting, by the at least one computer processor, the first compensation from a plurality of potential compensations.

6. The method of claim 1, wherein the selecting is based on at least one of a first ordering of a plurality of tasks and a second ordering of a plurality of agents, and wherein the at least one of the first and second orderings is expressed as percentiles or percentile ranges.
7. The method of claim 6, further comprising adjusting, by the at least one computer processor, the first offer set or the first compensation to adjust the first or second orderings.
8. A system for decisioning behavioral pairing in a task assignment system comprising:
- at least one computer processor communicatively coupled to and configured to operate in the task assignment system, wherein the at least one computer processor is further configured to:
 - determine a plurality of possible task–agent pairings among at least one task waiting for assignment and at least one agent available for assignment; and
 - selecting, for assignment in the task assignment system, a first task–agent pairing of the plurality of possible task–agent pairings based at least in part on a first offer set to be offered by the agent or a first compensation to be received by the agent.
9. The system of claim 8, wherein the task assignment system is a contact center system.
10. The system of claim 8, wherein the at least one computer processor is configured to select the first task–agent pairing based at least in part on both the first offer set and the first compensation.
11. The system of claim 8, wherein the at least one computer processor is further configured to select the first offer set from a plurality of potential offer sets.

12. The system of claim 8, wherein the at least one computer processor is further configured to select the first compensation from a plurality of potential compensations.

13. The system of claim 8, wherein the at least one computer processor is configured to select the first task–agent pairing based on at least one of a first ordering of a plurality of tasks and a second ordering of a plurality of agents, and wherein the at least one of the first and second orderings is expressed as percentiles or percentile ranges.

14. The system of claim 13, wherein the at least one computer processor is further configured to adjust the first offer set or the first compensation to adjust the first or second orderings.

15. An article of manufacture for decisioning behavioral pairing in a task assignment system comprising:

a non-transitory processor readable medium; and

instructions stored on the medium;

wherein the instructions are configured to be readable from the medium by at least one computer processor communicatively coupled to and configured to operate in the task assignment system and thereby cause the at least one computer processor to operate so as to:

determine a plurality of possible task–agent pairings among at least one task waiting for assignment and at least one agent available for assignment; and

select, for assignment in the task assignment system, a first task–agent pairing of the plurality of possible task–agent pairings based at least in part on a first offer set to be offered by the agent or a first compensation to be received by the agent.

16. The article of manufacture of claim 15, wherein the task assignment system is a contact center system.

17. The article of manufacture of claim 15, wherein the instructions are configured to cause the at least one computer processor to operate so as to select the first task–agent pairing based at least in part on both the first offer set and the first compensation.

18. The article of manufacture of claim 15, wherein the instructions are further configured to cause the at least one computer processor to operate so as to select the first offer set from a plurality of potential offer sets.

19. The article of manufacture of claim 15, wherein the instructions are further configured to cause the at least one computer processor to operate so as to select the first compensation from a plurality of potential compensations.

20. The article of manufacture of claim 15, wherein the instructions are configured to cause the at least one computer processor to operate so as to select the first task–agent pairing based on at least one of a first ordering of a plurality of tasks and a second ordering of a plurality of agents, and wherein the at least one of the first and second orderings is expressed as percentiles or percentile ranges.

21. The article of manufacture of claim 20, wherein the instructions are further configured to cause the at least one computer processor to operate so as to adjust the first offer set or the first compensation to adjust the first or second orderings.

Task Assignment Center
100




FIG. 1

Task Assignment System 200




FIG. 2

Task Assignment Method
300




FIG. 3

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/050850

A. CLASSIFICATION OF SUBJECT MATTER
INV. G06Q10/06
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G06Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 10 116 795 B1 (CHISHTI ZIA [US] ET AL) 30 October 2018 (2018-10-30) abstract; claims 1-8; figures 1,2,4B,4C page 4, line 65 - page 7, line 11 page 12, lines 8-49	1-21
X	WO 2017/055900 A1 (AFINITI INT HOLDINGS LTD [GB]) 6 April 2017 (2017-04-06) abstract; claims 1-11; figures 1-7 page 3, line 1 - page 4, line 8 page 7, line 2 - page 9, line 7 page 10, column 1 - page 11, column 3 ----- -/-	1-21



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

12 October 2020

Date of mailing of the international search report

23/10/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Bauer, Rodolphe

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/050850

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 3 495 953 A1 (AFINITI EUROPE TECH LTD [GB]) 12 June 2019 (2019-06-12) abstract; claims 1-4,11; figures 1,2 paragraphs [0006], [0016] - [0018], [0022] - [0026] paragraphs [0028] - [0036], [0046] - [0050] -----	1-21
X	US 2013/251137 A1 (CHISHTI ZIA [US] ET AL) 26 September 2013 (2013-09-26) abstract; figures 1,3-5B claims 1-5 paragraphs [0010] - [0022], [0028] - [0030] paragraphs [0140] - [0142] -----	1-21

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2020/050850

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
US 10116795	B1	30-10-2018	AU	2018206689	A1	24-01-2019
			CA	3048855	A1	10-01-2019
			CN	109496321	A	19-03-2019
			CN	111639834	A	08-09-2020
			EP	3479311	A1	08-05-2019
			EP	3506179	A1	03-07-2019
			JP	6674559	B2	01-04-2020
			JP	2019530029	A	17-10-2019
			JP	2020095746	A	18-06-2020
			KR	20190011248	A	01-02-2019
			KR	20190122897	A	30-10-2019
			US	10116795	B1	30-10-2018
			US	10122860	B1	06-11-2018
			US	2019068787	A1	28-02-2019
			US	2019356781	A1	21-11-2019
			WO	2019012326	A1	17-01-2019

WO 2017055900	A1	06-04-2017	AU	2016321485	A1	20-04-2017
			AU	2020227104	A1	24-09-2020
			BR	112017007054	A2	19-06-2018
			CA	2961080	A1	30-03-2017
			CN	107005617	A	01-08-2017
			CN	110035189	A	19-07-2019
			EP	3186948	A1	05-07-2017
			EP	3474524	A1	24-04-2019
			EP	3474525	A1	24-04-2019
			EP	3477929	A1	01-05-2019
			ES	2710290	T3	24-04-2019
			HU	E043404	T2	28-08-2019
			IL	250776	A	28-11-2019
			IL	264332	A	29-08-2019
			JP	6526180	B2	05-06-2019
			JP	2018519681	A	19-07-2018
			JP	2019154060	A	12-09-2019
			JP	2020145677	A	10-09-2020
			PH	12017500585	A1	30-08-2017
			PT	3186948	T	20-03-2019
			TR	201820929	T4	21-01-2019
			WO	2017055900	A1	06-04-2017

EP 3495953	A1	12-06-2019	AU	2018383093	A1	25-07-2019
			CA	3071319	A1	20-06-2019
			CN	110574010	A	13-12-2019
			EP	3495953	A1	12-06-2019
			JP	2020516987	A	11-06-2020
			KR	20200075883	A	26-06-2020
			US	2019179667	A1	13-06-2019
			US	2020125407	A1	23-04-2020
			WO	2019116086	A1	20-06-2019

US 2013251137	A1	26-09-2013	AU	2013240131	A1	09-10-2014
			AU	2013240133	A1	02-10-2014
			AU	2016269461	A1	02-02-2017
			AU	2019201218	A1	14-03-2019
			AU	2020203838	A1	02-07-2020
			CA	2868022	A1	03-10-2013
			CA	2868802	A1	03-10-2013
			CA	2993375	A1	03-10-2013

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2020/050850

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		CA 2993380 A1	03-10-2013
		CN 104509081 A	08-04-2015
		CN 104521225 A	15-04-2015
		CN 106878572 A	20-06-2017
		CN 107749932 A	02-03-2018
		EP 2832079 A1	04-02-2015
		EP 2832083 A1	04-02-2015
		EP 3506614 A1	03-07-2019
		ES 2732750 T3	25-11-2019
		HK 1206893 A1	15-01-2016
		HK 1208975 A1	18-03-2016
		HK 1251835 A1	12-04-2019
		HU E044697 T2	28-11-2019
		JP 5990634 B2	14-09-2016
		JP 6109922 B2	05-04-2017
		JP 6751126 B2	02-09-2020
		JP 2015514268 A	18-05-2015
		JP 2015514371 A	18-05-2015
		JP 2016208546 A	08-12-2016
		JP 2017055408 A	16-03-2017
		JP 2019033528 A	28-02-2019
		JP 2019193301 A	31-10-2019
		MX 340854 B	28-07-2016
		MX 346287 B	14-03-2017
		PH 12014502129 A1	10-12-2014
		PH 12014502130 A1	10-12-2014
		PT 2832083 T	07-08-2019
		US 2013251137 A1	26-09-2013
		US 2013251138 A1	26-09-2013
		US 2014044255 A1	13-02-2014
		US 2015271332 A1	24-09-2015
		US 2019281160 A1	12-09-2019
		WO 2013148452 A1	03-10-2013
		WO 2013148454 A1	03-10-2013
