



(22) Date de dépôt/Filing Date: 2011/10/26

(41) Mise à la disp. pub./Open to Public Insp.: 2013/01/01

(45) Date de délivrance/Issue Date: 2017/04/18

(30) Priorités/Priorities: 2011/07/01 (US13/174,853);
2011/10/18 (US13/275,553)

(51) Cl.Int./Int.Cl. *B42F 13/20* (2006.01),
B42F 13/16 (2006.01)


(72) Inventeurs/Inventors:
BUSAM, EDWARD P., US;
HARRIS, RICHARD H., US;
CICENAS, CHRIS W., US

(73) Propriétaire/Owner:
ACCO BRANDS CORPORATION, US

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : CARNET RECHARGEABLE AVEC MECANISME DE DEGAGEMENT

(54) Title: REFILLABLE NOTEBOOK WITH RELEASE MECHANISM



(57) Abrégé/Abstract:

A binding mechanism assembly for binding a sheet item, the binding mechanism assembly including a backing member having an upper surface, and a binding member directly or indirectly coupled to the backing member. The binding member includes a protrusion shaped and located to protrude through a hole of a sheet item to be bound thereto. The binding member further includes a generally flexible flange that is manually movable into engagement with the protrusion to form a generally closed loop and thereby bind the sheet item thereto. The loop is rotatable relative to the backing member from a first position in which the loop is generally located above the upper surface to a second position wherein at least part of the loop is located below the upper surface. A release mechanism is provided for opening the loop.

ABSTRACT

A binding mechanism assembly for binding a sheet item, the binding mechanism assembly including a backing member having an upper surface, and a binding member directly or indirectly coupled to the backing member. The binding member includes a protrusion shaped and located to protrude through a hole of a sheet item to be bound thereto. The binding member further includes a generally flexible flange that is manually movable into engagement with the protrusion to form a generally closed loop and thereby bind the sheet item thereto. The loop is rotatable relative to the backing member from a first position in which the loop is generally located above the upper surface to a second position wherein at least part of the loop is located below the upper surface. A release mechanism is provided for opening the loop.

REFILLABLE NOTEBOOK WITH RELEASE MECHANISM

[0001]

DESCRIPTION

[0002] The present invention is directed to a notebook, and more particularly, to a notebook in which sheet items and other contents can be added to or removed from the notebook, and the binding mechanism of the notebook may be rapidly and / or simultaneously opened.

BACKGROUND

[0003] Many notebooks, such as spiral bound or coil bound notebooks, include a set of papers, and optionally covers, which are bound together by the spiral or coil binding mechanism. The spiral or coil binding mechanism may allow the various sheets of the notebook to be folded three hundred and sixty degrees or nearly three hundred and sixty degrees around the binding mechanism such that the folded sheets can underlie the unfolded sheets lying thereabove.

[0004] However, in most spiral bound or coil bound notebooks, papers cannot be removed from the notebook without tearing the papers. In addition, such spiral bound and coil bound notebooks do not easily allow a user to add papers thereto. Accordingly, there is a need for a notebook having a binding mechanism which allows sheets and other contents to be pivoted underneath overlying sheets, and which allows the sheets and other contents to be easily removed from, and added to, the notebook.

SUMMARY

[0005] In one embodiment, the invention is a binding mechanism assembly for binding a sheet item. The binding mechanism assembly includes a backing member having an upper surface, and a binding member directly or indirectly coupled to the backing member. The binding member includes a protrusion shaped and located to protrude through a hole of a sheet item to be bound thereto. The binding member further includes a generally flexible flange that is manually movable into engagement with the protrusion to form a generally closed loop and thereby bind the sheet item thereto. The loop is rotatable relative to the backing member from a first position in which the loop is generally located above the upper surface to a second position wherein at least part of the loop is located below the upper surface. The loop is fixedly and not slidably coupled to the backing member. The binding mechanism may include one or more binding members. One or more of the loops may be released or opened by one or more release mechanisms.

[0006] In another embodiment the invention is a binding mechanism assembly for binding a plurality of sheet items. The binding mechanism assembly includes a generally flat, planar backing member configured to generally fully support 8-1/2 inch by 11 inch paper or A4 size paper thereon. The binding mechanism assembly further includes at least two binding members directly or indirectly coupled to the backing member. Each binding member includes a protrusion shaped and located to protrude through a hole of a plurality of sheet items to be bound thereto. Each binding member further includes a flange configured to engage the associated protrusion to form a generally closed loop and thereby bind the plurality of sheet items thereto. Each binding member is independently pivotable relative to the backing member. Selected ones of the plurality of sheet items bound to the binding member are pivotable about the closed loops to a position wherein the pivoted sheet items are located below the backing member and the remainder of the plurality of sheet items are in a generally flat configuration and located above the backing member. The plurality of sheet items located below the backing member are in a generally flat configuration and are oriented generally parallel with the plurality of sheet items located above the backing member. The binding mechanism may include at least one binding member including a loop, and the loop or loops may be opened by disengaging from the associated protrusions through at least one release mechanism. In some embodiments with more

than one loop, loops may be opened simultaneously or sequentially. In some embodiments the loop or loops, or the release mechanism, may include a spring, ramp, or wedge to assist in opening a loop.

[0007] In another embodiment the invention is a method for manipulating a binding mechanism assembly. The method includes the step of providing a binding mechanism assembly including a generally flat, planar backing member having an inner edge and a binding member coupled to the backing member. The binding member includes a protrusion and a flange, and the binding member is generally located above the backing member. The method further includes coupling a plurality of sheet items, each sheet item having a hole, to the binding mechanism assembly such that the protrusion extends through the hole of each sheet item. The method further includes manually causing the flange to engage the protrusion to form a generally closed loop and thereby bind the sheet items therein. The method includes the step of causing the generally closed loop to pivot about a pivot axis in a first direction relative to the backing member such that at least part of the generally closed loop is located below the backing member while the backing member remains in a generally flat, planar condition. The pivot axis is spaced away from the inner edge. The method further includes using at least one release mechanism to open at least one loop, or a plurality of loops. In some embodiments a plurality of loops may be opened using one or more release mechanisms. In some embodiments the loop or loops, or the release mechanism, may include a spring, ramp, or wedge to assist in opening a loop. In some embodiments more than one loop may be opened simultaneously or sequentially.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] FIG. 1 is a front perspective view of one embodiment of the notebook of the present invention, with the front cover closed and the binding mechanisms shown in their closed position;

[0009] FIG. 2 is a front perspective view of the notebook of FIG. 1, with the front cover pivoted away from the closed position;

[00010] FIG. 3 is a front perspective view of the notebook of FIG. 2, with the binding mechanisms in their open positions;

[00011] FIG. 4 is a front perspective view of the notebook of FIG. 3, with a plurality of papers added therein;

[00012] FIG. 5 is a front perspective view of the notebook of FIG. 4, with the binding mechanisms in their closed positions;

[00013] FIG. 6 is a front perspective view of the notebook of FIG. 5, with a pocket component bound therein;

[00014] FIG. 7 is a front perspective view of the notebook of FIG. 6, with the front cover closed;

[00015] FIG. 8 is an exploded perspective view of the notebook of FIG. 1, with the binding mechanisms in their open positions;

[00016] FIG. 9 is a perspective view of the notebook of FIG. 8 in a partially assembled state;

[00017] FIG. 10 is a side cross section of one of the binding mechanisms of the notebook of FIG. 1;

[00018] FIG. 11 is a side cross section of the binding mechanism of FIG. 10, shown in its open position;

[00019] FIG. 12 is an end view of the binding mechanism of FIG. 10, with a plurality of papers bound thereto;

[00020] FIG. 13 is an end view of the binding mechanism of FIG. 12, with part of the plurality of papers pivoted about the binding mechanism;

[00021] FIG. 14 is a detail perspective view of the binding mechanism of FIG. 10;

[00022] FIG. 15 is a detail perspective view of the binding mechanism of FIG. 14, shown in its open position;

[00023] FIGS. 16A-C are various cross sections taken along the lines indicated in FIG. 15;

[00024] FIG. 17 is a side view of the notebook of FIG. 7;

[00025] FIG. 18 is a side view of the notebook of FIG. 17, with the front cover and part of the papers pivoted about the binding mechanisms;

[00026] FIG. 19 is a front perspective view of the notebook of FIG. 18;

[00027] FIG. 20 is an exploded perspective view of another embodiment of the notebook of the present invention;

[00028] FIG. 21 is a perspective view of the notebook of FIG. 20, shown in an assembled condition;

[00029] FIG. 22 is a perspective view of the parts of an alternative notebook shown in an exploded view;

[00030] FIG. 23 is a detail view of certain parts of the notebook of FIG. 22;

[00031] FIG. 24 is a perspective view of the parts of the notebook of FIG. 22, in an assembled condition;

[00032] FIG. 25A and 25B are plan views of the assembled notebook of FIG. 22 seen from the front and back;

[00033] FIG. 26A is a cross section view of the opening binding mechanism seen from the end;

[00034] FIG. 26B is a plan view of the closed binding mechanism seen from the top;

[00035] FIGs. 26C – 26D are cross section views of a binding loop in a closed or nearly closed configuration;

[00036] FIGs. 27A – 27F are plan views of the release mechanism in engaged and disengaged configurations;

[00037] FIGs. 28A – 28G are plan views of alternative release mechanisms in engaged and disengaged configurations for both simultaneous and sequential release actions;

[00038] FIG. 29 is a cross section exploded view of certain parts of another release mechanism having a ramp element; and

[00039] FIGs. 30A and 30B are cross section views of the mechanism of FIG. 29 in a closed configuration and in an opening configuration.

DETAILED DESCRIPTION

[00040] As best shown in FIGS. 1-3, in one embodiment the present invention is a notebook 10 having a front cover 12, a rear cover or backing panel 14, and a spine guard 16 coupled to the front cover 12 and rear cover 14. Each of the front 12 and rear 14 covers may be a generally flat, stiff planar sheet-like member having a flat upper surface, and can be made of a variety of materials, including plastic, cardboard, paperboard, combinations of these materials and the like. The front 12 and rear covers 14 may have a variety of thicknesses, such as between about 0.01 inches and about 0.5 inches, and in one case are each about 0.08 inches thick.

[00041] The front 12 and rear 14 covers may have a variety of shapes and dimensions. For example, each of the front 12 and rear 14 covers may have a width (i.e., extending perpendicular to the spine guard 16) of between about eight and about twelve inches, and a height (extending generally parallel to the spine guard 16) of between about eleven and one-half and about fourteen inches. Thus, front and rear covers 12, 14 may be sufficiently sized to generally fully support and closely receive eight and one-half inch by eleven inch sheets of paper thereon. However, the front 12 and rear 14 covers can have various other sizes and may be sized to generally correspond to and support various other papers and components (i.e., index cards, legal size paper, A4 size paper, etc.) thereon.

[00042] In the illustrated embodiment the notebook 10 includes the spine guard 16 which may be a generally rectangular piece of material that is made of a relatively thin, flexible material, such as plastic, woven plastic, woven fabric or the like. The spine guard 16 may be more flexible and/or thinner than the front 12 or rear 14 covers. The notebook 10 may lack a generally rigid spine (i.e., in one case a spine having at least about the same stiffness and/or thickness as the front 12 and/or rear 14 covers). The spine guard 16 can be coupled to the front cover 12 and rear cover 14 by a variety of means, including stitching (i.e., see stitching 21 shown in FIGS. 2-6), adhesives, molding, heat welding, sonic welding or the like. In the illustrated embodiment, the spine guard 16 is generally rectangular (when laid flat) and has a pair of

longitudinal edges, wherein each longitudinal edge is coupled to the one of the front cover 12 or rear cover 14 by stitching.

[00043] The notebook 10 includes a binding mechanism assembly 18, with the binding mechanism assembly 18 including a plurality of individual binding mechanisms or binding members 20. Each binding mechanism 20 may include a protrusion 22 that is shaped and located to fit through the hole 24 of a sheet item 26, as shown in FIG. 4. Each protrusion 22 may extend generally perpendicular to the rear cover 14 when no papers, sheet items 26 or components are located on the rear cover 14. Alternately each protrusion 22 may extend at a slight angle, such as a rearward angle wherein each protrusion 22 angles back towards the spine of the notebook 10, as best shown in FIG. 1.

[00044] Once a flange 28 is coupled to the protrusion 22, the flange 28 and protrusion 22 formed a closed loop 30. The length of the protrusion 22 and/or flange 28 can be adjusted to provide loops 30 with varying storage capacities. For example, relatively long protrusions 22 and flanges 28 may be utilized to provide relatively large loops 30 for a relatively high capacity notebook, and relatively short protrusions 22 and flanges 28 may be utilized to provide relatively small loops 30 for a relatively low profile, low capacity notebook.

[00045] Each binding mechanism 20 may further include a flange 28 which is movable or flexible to move between a closed position as shown in, for example, FIGS. 1 and 2 (wherein each flange 28 engages and/or is coupled to the associated protrusion 22) and an open position as shown in, for example, FIG. 3 (wherein each flange 28 is spaced away from the associated protrusion 22). When a flange 28 is coupled to an associated protrusion 22, each flange/protrusion combination forms a generally closed loop 30 to thereby bind any sheet item 26 on the protrusions 22 to the notebook 10. Each binding mechanism 20 may be individually or independently operable (i.e., each binding mechanism 20 is independently or individually movable between the closed and open positions).

[00046] As best shown in FIG. 10, each protrusion 22 may be a hollow generally cylindrical member having a generally cylindrical cavity 32 formed therein. Each flange 28 may terminate in a generally cylindrical projection 34 sized and shaped to be closely received in the cavity 32 of the protrusion 22 to form the closed loop 30. Each projection 34 may include a

tapered end surface 38, although the end surface 38 need not necessarily be tapered. The base of the projection 34 may have a generally rounded outer corner 48 (see FIG. 10) to prevent sheet items 26 from being caught on the outer corner 48 as the sheet items 26 are pivoted around the closed loops 30.

[00047] Each binding mechanism 20 may include a coupling assembly or locking arrangement, generally designated 36, for attaching or coupling each flange 28 to an associated protrusion 22 (and more particularly, for securing each projection 34 within an associated cavity 32). In the illustrated embodiment, the lower end of each cavity 32 includes an annular or ring-like lip, bump or locking member 44 located therein. Each projection 34 includes an annular or circumferential recess or groove 46 shaped to receive the locking member 44 therein.

[00048] In order to couple a flange 28 to an associated protrusion 22, the projection 34 of the flange 28 is inserted into the cavity 32 of the protrusion 22 until the tapered end surface 38 of the projection 34 engages the locking member 44. As the flange 28 is urged deeper into the protrusion 22, the distal end of the projection 34 may be deflected or compressed radially inwardly. If desired, the flange 28/projection 34, or parts of the flange 28/projection 34, may be hollow (not shown) to allow the flange 28/projection 34 to be compressed radially inwardly. At the same time, the portions of protrusion 22 located adjacent to the locking member 44 may move radially outwardly or "bulge" outwardly to allow the projection 34 and tip 38 to fit therethrough. Once the projection 34 is inserted to a sufficient depth, the locking member 44 seats in the annular groove 46 to releasably couple the flange 28/projection 34 to the protrusion 22 (FIG. 10).

[00049] In order to uncouple the flange 28/projection 34 from the protrusion 22, the flange 28/projection 34 can be manually pulled upwardly until the locking member 44 is pulled out of the annular groove 46 to allow the flange 28/projection 34 to be lifted out of the protrusion 22/cavity 32. The size and shape of the annular groove 46 and locking member 44, as well as the thickness of the protrusion wall around the locking member 44 may be adjusted as desired so that the force required to lock and unlock the protrusion 22 and flange 28 is set to the desired level.

[00050] The coupling assembly 36 (which may include the locking member 44 and annular groove 46) may be shaped and/or configured such that a user can relatively easily

manually couple and uncouple the protrusion 22 and flange 28, while providing a sufficiently strong connection that the protrusion 22 and flange 28 resist being uncoupled during normal usage. The tapered shape of the end surface 38 allows the projection 34 to be fully inserted into the cavity 32 relatively easily, yet resist withdrawal to prevent accidental opening of the closed loops 30. Although the protrusion 22, cavity 32 and projection 34 can have a variety of lengths, in one embodiment the protrusions 22, and/or cavity 32 and/or projection 34 each have a length of at least about 0.25 inches, or at least about 0.5 inches, or at least about 1 inch to ensure that the flange 28 can be securely coupled to the protrusion 22.

[00051] The coupling assembly 36 can take any of a wide variety of shapes and forms beyond the annular groove 46/locking member 44 arrangement shown in FIGS. 10 and 11. For example, the positions of the locking member 44 and the annular groove 46 may be reversed such that the locking member 44 is located on the projection 34, and the annular groove 46 is located in the protrusion cavity 32. Furthermore, broadly speaking the position of the projection 34 and protrusion cavity 32 may be reversed. Thus, the protrusion 22 may be a cylinder to form the male projection 34 and the flange 28 may include a hollow member defining the female cavity 32 at its distal end. In addition, any of a wide variety of snaps, interengaging and interlocking geometries, interference fits and the like may be utilized as the coupling assembly 36.

[00052] In the illustrated embodiment, each projection 34 is generally cylindrical and the cavity 32 of each protrusion 22 is also generally cylindrical to closely receive the projection 34 therein. However, if desired the projections 34/cavity 32 can have any of variety of other shapes in cross section, such as square, hexagon, oval, triangular, etc. The use of eccentric or noncircular cross sectional shapes may be used to rotationally couple the projections 34 and associated cavity 32. If desired, each projection 34 may include longitudinally or axially extending grooves 50 (see FIG. 15) formed therein to provide materials savings, improve molding conditions, or improve structural characteristics of the projection 34.

[00053] As best shown in FIG. 8, each binding mechanism 20 may be located on or coupled to a generally flat support surface 52 having a flat upper surface, with one or more binding mechanisms 20 coupled to and/or extending from the support surface 52 to form a binding portion or backing member 54. Each binding mechanism 20 may be directly coupled to

the support surface 52; i.e. in a non-binding manner wherein the support surface 52 does not receive the loops 30 therethrough. The support surface 52/binding portion 54 may have a width of between about 3/4 inches and about 2 inches. In the illustrated embodiment the binding portion 54 is coupled to the underside of the rear cover 14 by a set of rivets 60. However, a wide variety of methods for coupling the binding portion 54 to the rear cover 14 may be utilized, including but not limited to, adhesives, welding, use of plastic or metal rivets, various interference fits, heat welding, sonic welding and the like. In one embodiment, the binding portion 54 is directly coupled to the rear cover 14 by a line of stitching 63 (see FIG. 9) that extends generally the entire length of the binding portion 54, and through the rear cover 14 and binding portion 54. The stitching 63 helps to further secure the binding portion 54 to the rear cover 14 and ensures that an end of the binding portion 54 cannot be pried upwardly and away from the rear cover 14 (which could lead to de-coupling of the binding portion 54 and rear cover 14 should a component get wedged between the binding portion 54 and rear cover 14). The rear cover 14 may include a set of notches 58 formed along its inner edge to receive the protrusions 22 therein, with each notch 58 having an inner surface 59.

[00054] If desired, the binding portion 54 (i.e. the support surface 52, protrusions 22 and flanges 28) may be of a one-piece or monolithic piece of material. Thus, the binding portion 54 may be formed from a single, unitary piece of material, such as plastic or polymer that is molded in the desired shape. Making the binding portion 54 out of a plastic or polymer may also provide flanges 28 with the desired flexibility. In another embodiment, the protrusions 22, flanges 28 and rear cover 14 may be formed as a one-piece or monolithic piece of material, as shown in FIG. 20. In this case there is no separate binding portion 54 and accordingly there is no need for the rivets 60, or stitching 63 or other coupling mechanisms.

[00055] The embodiment of FIG. 8 (with a separate binding portion 54) may allow more efficient manufacturing because the rear panel 14 of that embodiment can be easily formed from flat, plastic sheets, or various other materials which can be cheaply made and easily cut to size. In contrast, in certain cases the embodiment of FIG. 20 may provide more efficient manufacturing since a manufacturing step (i.e., attaching the binding portion 54 to the rear cover 14) is eliminated.

[00056] As best shown in FIGS. 14 and 15, each protrusion 22 may be located on and extend generally upwardly from a generally flat support portion 62. If desired, each support portion 62 can be considered to be part of the associated flange 28 and/or protrusion 22, and each flange 28 may thus be directly coupled to the associated protrusion 22. Each associated flange 28 is also coupled to, and extends laterally from, the associated support portion 62 at its base/base portion/base end 64.

[00057] Each support portion 62 (and the associated protrusion 22/flange 28/binding mechanism 20/closed loop 30) may be movably (i.e. pivotally or rotationally) coupled to the support surface 52/rear cover 14 by a crease, indentation, transition portion, area of thinning or the like 66 (see also FIGS. 10 and 11). As best shown in FIGS. 14 and 15 the crease 66 may have some raised stiffening ribs located thereon to limit the flexibility/increase strength of the crease 66. However, the notebook 10 need not necessarily include any crease 66 or the like. In particular, in one embodiment each support portion 62 transitions smoothly to the support surface 52/rear cover 14 such that both the support portion 62 and the support surface 52/rear cover 14 have the same thickness, and there are no notches or areas of weakness located therebetween. In this case, however, the cantilevered and/or flexible nature of each support portion 62 may allow each support portion 62 move, pivot or rotate relative to the support surface 52/rear cover 14.

[00058] Because each protrusion 22 and flange 28 is fixedly and non-removably coupled to the support surface 52/rear cover 14, each loop 30 may be fixedly and non-removably coupled to the support surface 52/rear cover 14. In addition, each loop 30 may not be slidably coupled to the support surface 52/rear cover 14 such that each loop 30 cannot spin (i.e. spin about an axis extending along the length of the support surface 52) or slide relative to the support surface 52/rear cover 14. This ensures that each loop 30 is consistently located in a known and desired position.

[00059] As best shown in FIGS. 14 and 15, the base 64 of each flange 28 may be generally flat (i.e., generally rectangular in cross section) so that the flange 28 can be securely coupled to the associated support portion 62. However, the distal end of each flange 28 (i.e., the end adjacent to the associated projection 34) may be generally cylindrical in cross section such that the projection 34 can be securely coupled thereto. Accordingly, each flange 28 may

gradually transition from a generally rectangular cross section (at its base 64) to a generally circular cross section (at its distal end). The flat shape at the base 64 of each flange 28 also provides increased pivotable flexibility to allow the flange 28 and projection 34 to be manually moved by an adult or juvenile of ordinary strength into and out of contact with the associated protrusion 22.

[00060] FIGS. 16A, 16B and 16C show various cross sections along the length of a flange 28 to illustrate one embodiment of the transition of shape along the flange 28. Although the flange 28 may vary in its cross sectional shape along its length, the flange 28 may have a generally uniform volume along its entire length (i.e., each cross section may have the same surface area). The flange 28 may include a cored out area 70 to improve ease of manufacture, provide material savings, or improve structural characteristics.

[00061] In order to assemble the notebook 10 of FIGS. 1-3, the binding portion 54, rear cover 14, spine guard 16 and front cover 12 may be provided, as shown in FIG. 8. The binding portion 54 may then be coupled to the rear cover 14 by the rivets 60 and/or stitching 63. The inner edge of the spine guard 16 is then doubled over and coupled to the front cover 12, such as by stitching or the like (although, if desired, the spine guard 16 could instead be coupled to the rear cover 14 prior to attachment to the front cover 12). Carrying out these steps provides the assembly shown in FIG. 9.

[00062] The spine guard 16 may have a set of three elongated holes 72 formed therethrough with each hole 72 being located and configured to receive one of the protrusions 22 therethrough. The front cover 12 may also include a set of three notches 74 formed therethrough, with each notch 74 being aligned with an associated hole 72, and being located and configured to receive one of the protrusions 22 therethrough. The free longitudinal edge of the spine guard 16 is then coupled to the rear cover 14, such as by stitching, to thereby provide the notebook 10 shown in FIGS. 1-3. In this manner the front cover 12 and spine guard 16 are both mounted to the binding mechanisms 20 such that the front cover 12 and spine guard 16 can freely pivot about the loops 30/binding mechanisms 20, and the front cover 12 and spine guard 16 are not fixedly coupled to the rear cover 14.

[00063] In order to utilize the notebook 10, the notebook 10 of FIG. 1 is first provided. The front cover 12 is then pivoted about the loops 30/binding mechanisms 20 to its open position, as shown in FIG. 2. Each of the binding mechanisms 20 are then moved to their open positions, as shown in FIG. 3, wherein the flanges 28 are spaced apart from the associated protrusions 22. Sheet items 26, such as paper sheets, can then be located on or supported by the rear cover 14 such that a protrusion 22 passes through each of the holes 24 of the sheet items 26 (FIG. 4). For example, each of the binding mechanisms 20 may be spaced apart by about 4 1/4 inches on center to receive sheet items 26 or other components having corresponding holes thereon. Of course, the spacing, number and arrangement of binding mechanisms 20 can be adjusted to accommodate sheet items having differing hole configurations from that shown in FIG. 4. As noted above and shown in FIG. 4, the rear cover 14 may be sized to generally correspond to the size of the sheet items 26.

[00064] In addition, besides sheets of paper, various other components such as folders, pockets, dividers, hole punches, sticker sheets, rulers or nearly any component having the appropriate hole configuration can be used as sheet items and mounted onto the protrusions 22/rear cover 14. For example, as shown in FIG. 6, a pocket component 78 having holes in a pattern matching the pattern of the binding mechanisms 20 can be bound thereto. If desired, an uppermost and/or lowermost one of the bound sheet items 26 may be a relatively stiff, rigid material, such as cardboard, plastic or the like, to provide top and bottom protective components (not shown) in place of or in addition to the covers 12, 14.

[00065] After the sheet items 26 have been mounted onto the protrusions 22/rear cover 14, the flanges 28 are moved to a closed position such that their projections 34 are received in the associated protrusions 22 and securely coupled thereto (in the manner described above) by the associated coupling assembly 36 to form the closed loops 30 (FIG. 5). In this manner, the notebook 10 of FIG. 5 has a plurality of sheet components 26 bound therein which are securely held in place by the binding mechanisms 20. The front cover 12 may be closed to thereby cover and protect the sheet components 26 bound thereto (see FIG. 7). When the notebook 10 is in the closed position the spine guard 16 helps to protect the spine (i.e., inner edges) of the sheet components 26 and the top cover 12 protects the top surface of the sheet components 26 to provide a finished and pleasing look to the notebook 10.

[00066] As shown in FIG. 10, each support portion 62 may form an angle A with the support surface 52/rear cover 14 when no sheet items are received in the notebook 10. The angle A may range between zero degrees and thirty degrees, and in one embodiment is about fifteen degrees. As described above, if desired the protrusions 22 may extend generally vertically relative to the support surface 52/rear cover 14 when no sheet items are bound therein (as shown in FIG. 10). In this case the protrusion 22 may form an acute angle of, for example, between about sixty degrees and about ninety degrees with the support portions 62. Further alternately, the angle A may be about zero degrees. In this case, the protrusion 22 may lean to the left of its position shown in FIG. 10, and may form an angle of between about zero degrees and about thirty degrees with a vertical axis. In yet another embodiment, the protrusions 22 extends generally perpendicularly from the support surface 52/rear cover 14.

[00067] As shown in FIG. 12, when a plurality of sheet items 26 are received in the notebook 10, the weight of the sheet items 26 may press down on the support portions 62, thereby reducing the angle A (with respect to the angle A shown in FIG. 10) and causing the protrusions 22 to lean back and form a slight angle B with a vertical axis that is perpendicular to the support surface 52/rear cover 14. In addition, in the configuration of FIG. 12, the notebook 10 lies flat. In other words, the binding mechanisms 20 are located above, flush with or slightly below the support surface 52/rear cover 14 such that the notebook 10 can lie substantially flat on a planar surface such as a table, desktop, another notebook or binder, or the like.

[00068] During use of the notebook 10, the user will typically desire to access sheet items 26 located in the middle of the stack of sheet items 26 for writing upon, for removal, for the addition of sheet items, etc. Accordingly, in order to access the intermediate sheet items, selected upper sheet items of the stack of sheet items 26 are lifted up and folded around the closed loops 30 of the binding mechanisms 20 until they are located below the support surface 52/rear cover 14, as shown in FIGS. 13, 18 and 19. As the pages 26 are folded in this manner, due to the positioning of the pages 26 each support portion 62 may pivot relative to the support surface 52/rear cover 14 such that at least part of the support portions 62/protrusions 22/closed loops 30 are located below the support surface 52/rear cover 14 (see FIG. 13). In this position, each protrusion 22 forms a greater angle B with the vertical axis compared to when sheet items 26 do not underlie the support surface 52/rear cover 14. In addition, the angle A formed between the

support portions 26 and the support surface 54/ rear cover 14 is a negative angle. As can be seen in comparing FIGS. 12 and 13, the loop 30 is pivotable about a pivot axis C that is spaced inwardly from an inner edge of the support surface 52/rear cover 14.

[00069] This pivoting nature of the binding mechanisms 20, in combination with the shape/curvature of the base portion 64 of the flanges 28, allows the folded/pivoted sheet items 26 to substantially entirely underlie the rear cover 14 to provide a compact notebook 10 in the folded position. Each sheet item 26 may be pivotable at least about 330 degrees. Each loop 30 may be pivotable about a point located on or adjacent to the loop 30 that is spaced away from an inner edge of the support surface 52/rear cover 14. The loops 30 may not be rotatable or pivotable about a center axis that extends through a center of the closed loops 30.

[00070] The pivotal nature of the binding mechanisms 20 allows the base portion 64 of the flange 28 to assume a more "vertical" position compared to when the binding mechanisms 20 are not pivoted. In addition, portions of the flange 28 are located below an upper flat surface of the support surface 52/rear cover 14. These features allow the sheet items 26 to move more to the right (with reference to FIG. 13) than would otherwise be possible so that the folded sheet items 26 more closely underlie the rear cover 14 and overlying sheet items 26. In addition, the pivoted sheet items (located below the support surface 52/rear cover 14) may be generally aligned with, and generally parallel to, the unpivoted sheet items (located above the support surface 52/rear cover 14). This allows for a more compact notebook 10 in its folded position.

[00071] Each binding mechanism 20 automatically pivots to the optimal position given the number of sheet items 26 located under the rear cover 14 to provide a flat, compact notebook 10. The manner in which the binding mechanisms 20 pivot such that they are located below the rear cover 14/support surface 52 which allows the sheet items 26 to remain generally flat and planar with minimal creasing or folding thereof. Although some of the folded sheet items 26 may have somewhat of a crease formed therein (see FIG. 13), the crease is not very sharp and forms an obtuse angle. In addition, as shown in FIGS. 18 and 19, the notebook 10 can lie substantially flat, even when sheet items 26 are folded around the binding mechanisms 20 to underlie each other or the rear cover 14.

[00072] Each protrusion 22 and/or binding mechanism 20 may be located adjacent to the outer edge of the rear cover 14 in the illustrated embodiment. For example, with reference to FIGS. 14 and 15, the support surface 52 includes the plurality of notches 61, and each support portion 62 is located in one of the notches 61. In this manner, as described above, each protrusion 22/closed loop 30 can be pivoted or moved to a position such that at least part of the protrusion 22/support portion 62/closed loop 30 is located below the rear cover 14/support surface 52 (i.e., on the opposite side of the rear cover 14/support surface 52 from which the protrusion 22 extends upwardly).

[00073] With reference to FIGS. 8 and 9, the inner surface 59 of each notch 58 of the rear cover 14 defines a stop surface which limits the pivoting motion of each binding mechanism 20 in a forward direction. In particular, if a binding mechanism 20 were attempted to be pivoted in the opposite direction to that described above (i.e., if a binding mechanism 20 of FIG. 12 were attempted to be pivoted clockwise), the lower end of the protrusion 22 would engage the stop surface 59 and limit significant pivoting motion (i.e., about 15 degrees in one case) in this direction. In the embodiment shown in FIGS. 8 and 9 each notch 58 has a generally tapered shape, with the narrowest portion of the notch 58 being configured to relatively closely receive a protrusion 22 therein. The tapered shaped of the notch 58 may help to smoothly guide the associated protrusion 22 therein (i.e. when a protrusion 22 is pivoted), and the narrowest portion of each notch 58 may help to limit lateral deflection of the associated protrusion 22. However the notches 58 can take a variety of shapes, and may, for example, be generally "U" shaped.

[00074] In an alternate embodiment shown in FIGS. 20 and 21 the binding mechanisms 20 are located generally inside the spine guard 16. In this case a set of auxiliary notches 82 may be provided in the spine guard 16 to allow the upper portions of the binding mechanisms 20 to protrude therethrough. If desired, the length of the auxiliary notches 82 may be increased to allow more of the closed binding mechanisms 20 to be received therethrough. The longer auxiliary notches 82 may allow easier operation and/or access to the binding mechanism 20 and may allow the spine guard 16 to more closely conform to the contents of the notebook 10.

[00075] In the illustrated embodiments above, each binding mechanism 20 is independently pivotable about an axis that is generally perpendicular to a plane of that binding mechanism 20 which allows each binding mechanism 20 to independently pivot to the optimal

position for that binding mechanism. However, if desired each binding mechanism 20 could be coupled together by a piece of material or the like such that each of the binding mechanisms 20 are commonly pivotable about a pivot line. Each binding mechanism 20 may be rotatable at least about 15 degrees, or at least about 30 degrees, or at least about 90 degrees, or at least about 180 degrees. Thus, for example, each binding mechanism 20 may be able to be pivoted about 180 degrees such that each binding mechanism 20 is located generally entirely below the rear cover 14/support surface 52.

[00076] The front cover 12 and spine guard 16 may not necessarily be used or included as part of the notebook 10. For example, the lower component of the embodiment of FIG. 20, wherein the front cover 12 and spine guard 16 are not utilized, can be used alone (with or without the separate binding portion 54). In addition, if desired the binding portion 54 can be used by itself, and without an attached rear cover 14. In addition, if desired an additional locking mechanism (in addition to the coupling assembly 36), can be used to mechanically lock the protrusions 22 into the cavities 32, can be used.

[00077] FIGs. 22 – 28 illustrate embodiments in some aspects similar to what is shown in FIGs. 1 – 21, but having one or more release mechanisms/ actuators by which one or more loops may be opened simultaneously or sequentially. Many of the features are similar to those already shown, and in most cases are denoted by the identifying numerals already used, except that in FIGs. 22 – 28, the identifying numerals have 100 added to their value.

[00078] FIG. 22 shows a set of three binding mechanism assemblies 118 each including a protrusion 122 and flange 128 which together are capable of forming a loop to hold sheets of material, as illustrated previously. The binding mechanism assemblies 118 are joined to a main fixture body 180 which may have on its lower or back surface a lower fixture cover 186.

[00079] Main fixture body 180 may be attached via one or more pivots 166 such as creases or living hinges to a support surface 152 which in turn may be attached to rear cover 114 for example by way of rivets (not shown) through rivet holes 160 in at least one of the main fixture body 180 and rear cover 114.

[00080] A release mechanism / actuator 190 may be moveably positioned relative to main fixture body 180, for example between the main fixture body 180 and the lower fixture cover

186. The release mechanism / actuator 190 may include locking features 195 (see Figures 26D and 27-30) for selectively engaging flange 128, for example at its end 134, 136, 138 as described below. The release mechanism 190 may also include one or more biasing features or springs 192 such as serpentine springs to urge the release mechanism 190 to a first position, for example with the locking features 195 in position for engaging flange 128. The release springs 192 may be molded as a part of the release mechanism 190 or may be otherwise provided such as rubber bands, coil springs, or other elastic structures. The release mechanism 190 may include an actuator 199 (such as a pull tab or push tab, or both) to move the release mechanism to a second position with locking features 195 out of engagement from flange 128. The actuator 199 may be at either (or both) ends of the release mechanism (or possibly even somewhere also the length of the release mechanism other than at the ends). The actuator 199 may respond to either a pulling or a pushing force, or both, to move the locking features 195 out of engagement with the flange 128.

[00081] Fig. 23 shows a detail of certain parts of the mechanism including main fixture body 180 which may include a main housing 181 and a support surface 152, rivet holes 160, protrusion 122, flange 128, and spring anchor point, for example a spring anchor post 182 located underneath main fixture body 180 and positioned to engage a spring end 193 such as a loop formed in release spring 192. The spring anchor point 182 may be a downward post that passes through spring end 193 and engages fingers 187 on lower fixture cover 186, as shown by path 183. The spring anchor post 182 may include barbs (not shown) to engage fingers 187. The spring anchor post 182 may be at least partially split (not shown) along its lower end to provide resilience to be received into engagement with fingers 187. Alternately or additionally, such resilience may be provided by fingers 187. The release mechanism 190 may include a spring aperture 191 suitably sized to allow release spring 192 room to stretch and contract.

[00082] Additional anchor points or posts similar to spring anchor posts 182 may be provided. These may be anchor posts 184 that may engage fingers 187 in the lower fixture cover. The additional anchor posts may also pass through openings in release mechanism 190, such as through unlocking features 196 described below, for example as denoted by dotted line 185. The anchor posts 184, in combination with size and position of the openings through which they pass, may limit the sliding travel of release mechanism 190, for example by allowing minimal side to

side movement, and providing sufficient length-wise movement to allow disengaging the locking features without permitting excessive length-wise movement of release mechanism 190. Instead of, or in addition to, anchor posts 182, 184, the lower fixture cover may be held to the main housing 181 by other methods such as adhesive, welding, snap-together features, mechanical fasteners, and combinations of the above. Lower fixture cover 186 may include walls 189 that may serve to contain or guide release mechanism 190. Lower fixture cover 186 may also include clearance wells 188 whose purpose will be described later.

[00083] Fig. 24 shows a perspective view of the back cover 114 with the main fixture body attached behind it (for example using rivet holes 160 or other suitable attachment). The protrusions 122 are seen extending forward or upward from back cover 114, and the flanges 128 in an 'open-loop' configuration extending outward from the cover to the flange ends 134. An actuator 199 is shown at one end of the main fixture body.

[00084] Fig. 25A shows a plan view (otherwise similar to Fig. 24) of the back cover 114 with the protrusions 122 seen extending or upward and the flanges 128 in an 'open-loop' configuration extending outward from the cover to the flange ends 134. An actuator 199 is shown at one end of the main fixture body.

[00085] Fig. 25B shows a plan view (flipped relative to Fig. 25A so that the actuator 199 is not at the opposite end of the view) of the back cover 114 main fixture body 180 seen attached to the back cover, the flanges 128 in an 'open-loop' configuration extending outward from the cover to the flange ends 134. A cross-sectional line 26A is indicated which relates to Fig. 26A described next.

[00086] Fig. 26A is a cross section end view of the open binding mechanism. The view includes, from right to left, back cover 114, the support surface 152, protrusion 122, flange 128, flange spring 129, and flange end 134. The flange spring 129 is optional and may be any material with suitable resilient properties, for example a strip, ribbon, coil or wire of spring steel or other metal. The flange spring 129 may be attached to the flange by adhesive, by inserting into suitable recesses in the flange, by inserting through a hollow flange, by molding in the flange, or by other methods according to manufacturing preference. The shape and resilience of the flange spring 129 may be chosen according to manufacturing preference. The use of a flange spring

129 may serve to straighten the flange 128 when the release mechanism 190 is opened, to facilitate the loops opening without requiring the user to pull the loops open.

[00087] Fig. 26B shows a plan view of the main fixture body 180 with the flanges 128 in closed configuration, forming loops. A cross-sectional line 26C indicates the position of the views shown in Figs. 26C and 26D.

[00088] Fig. 26C shows a cross section side view of a closed loop made up of protrusion 122 and flange 128, while Fig. 26D shows a similar cross section side view with the loop slightly opened. Flange end 134 fits inside protrusion 122. The flange tip 138 may be pointed, cone-shaped, tapered, or otherwise shaped to allow it to easily enter the protrusion 122 and the locking feature 195. A shaped area 136 such as one or more grooves, cuts, or slots may be provided at or near the flange tip 138, to serve as a receptor area to fit in or upon the locking feature 195. Various shapes may be used on or near the flange tip 138 and in the locking feature 195 to accomplish the locking and unlocking action. When the flange tip 138 is pressed into the locking feature 195, the locking feature may flex downward slightly to allow the flange tip 138 to pass through the locking feature. A clearance well 188 (seen in Fig. 23) may be provided in lower fixture cover 186 to provide clearance for the flange tip 138 and / or downward flexing locking feature 195. However, the lower side of main housing 181 just below protrusion 122 may be in close contact with locking feature 195 so as to limit any upward flexing and thereby more securely hold flange tip 138 once it is captured by locking feature 195.

[00089] Figs. 27A – 27F show plan views of release mechanism 190 in locked and unlocked configurations. In these figures, lines 138A represent the position of flange tip 138 (not shown) and lines 182A represent the position of spring anchor point 182 (not shown).

[00090] In Fig. 27A and 27B, the release feature 196 is double-ended, that is, from the position shown in Fig. 27A, the release mechanism 190 may be moved in either direction (subject to constraints on the release spring) to release the flange tip 138. The locking feature 195 may be a narrowed portion 195 of a slot located between two wider portions 196 of the slot with the wider portions being unlocking features 196. To release the flange ends 138 and open the loops, actuator 199 may be pulled outward as shown in Fig. 26B. This stretches release spring 192 to an extended configuration 192S, while moving the locking feature 195 away from

the flange tip 138. The flange tip 138 is then free to move through the unlocking feature 196 and to open, for example through the action of flange spring 129, by manual pulling or manipulation of the loop, or other application of force.

[00091] When the user releases actuator 199, release spring 192 contracts and brings the release mechanism 190 back to its normal position with the locking features 195 in line with protrusions 122 so that when the loops are closed again (by placing the flange ends 138 into the protrusions 122) the flange ends 138 will be captured by the locking features 195.

[00092] Figs. 27A and 27B show the release mechanism 190 being operated by pulling on actuator 199 which extends release spring 192. If release spring 192 is provided with some spacing between its 'coils,' then the release spring might be utilized either as an tension spring (as shown) or as a compression spring, in which case the actuator 199 might be designed to operate by pushing inward, compressing release spring 192, and thereby moving locking features 195 out of alignment from the flange ends 138.

[00093] Figs. 27C and 27D show single-ended release features which may have only a single unlocking region 196 inboard from locking region 195A. In other aspects this design is similar to that shown in Figs. 27A and 27B. While double-ended release features as shown in Figs. 27A and 27B may have the locking feature 195 engage the flange tip 138 on one or two sides, a single ended release mechanism as shown in Figs. 27C and 27D might be designed with a locking feature 195A to engage flange tip 138 around part of its periphery, or even around as much as 270 degrees of its periphery. However, using a single ended release feature 196 as shown in Fig. 27C may reduce the number of points at which an anchor post 184 may conveniently be located.

[00094] Figs. 27E and 27F show another single-acting release mechanism which has only a single unlocking region 196 outboard from locking region 195B. In some aspects this design is similar to those already shown in Figs. 27A – 27D. However, the placement of release spring 192 is reversed so that the spring is extended and stretched when the release actuator 199 is pushed inward. The locking feature 195B may be configured to engage flange tip 138 around part of its periphery, or even around as much as 270 degrees of its periphery.

[00095] While the release spring 192 is shown as a tension spring, for example having its 'coils' in contact with each other in a relaxed position, and separated from each other in a stretched position, the release spring 192 could be designed otherwise according to manufacturing preference. For example if the 'coils' of the release spring were separated from each other in the relaxed position then the spring could be compressed and act as a compression spring. If sufficient space was provided in the spring aperture 191, such a 'compression' spring might also be stretched, thus facilitating a double acting release mechanism that could open by either pulling or pushing on release actuator 199. The 'rest' or relaxed position of this or the other springs could be designed to position the locking feature 195 in the 'locking' position in line with protrusion 122.

[00096] Figs. 28A – 28G show plan views of other release mechanisms 190 in locked and unlocked configurations. In these figures, lines 138A represent the position of flange tip 138 (not shown) and lines 182A represent the position of spring anchor point 182 (not shown).

[00097] In Fig. 28A – 28D, the locking features 195 and release features 196 are designed to disengage sequentially. Fig. 28A shows a rest configuration before the actuator 199 is moved. All of the locking features 195 are aligned with the flange ends (e.g. aligned with lines 138A, as denoted by point "D1" for example) so that the three loops of this embodiment would all be locked closed.

[00098] Fig. 28B shows the situation after actuator 199 is pulled slightly outward causing a first one of the loops to be opened, as locking feature 195 disengages (moves away from line 138A) as shown at point "D2." However, the second and third loops remain locked.

[00099] Fig. 28C shows the situation after actuator 199 is pulled further outward causing a second one of the loops to be opened, as locking feature 195 disengages as shown at point "D3." However, the third loop remains locked.

[000100] Fig. 28D shows the situation after actuator 199 is pulled still further outward causing the third one of the loops to be opened, as locking feature 195 disengages as shown at point "D4." By appropriate design of the individual locking/ unlocking features 195, 196 the various loops may be caused to open in any particular sequence, for example 1-2-3 as just described, 3-2-1, 1-3-2, 1 and 3 together followed by 2, and so on.

[000101] Fig. 28E shows an embodiment where two release mechanisms 190A, 190B are used. For example, this could be achieved by making the release mechanism in two parts as shown. As shown in Fig. 28F, the first release mechanism 190A, when moved by pulling on its actuator 199, unlocks the first loop. As shown in Fig. 28G, the second release mechanism 190B when moved by pulling on its actuator 199B, unlocks the second and third loops. Instead of or in addition to the springs 192 within release mechanisms 190A, 190B, the release mechanisms might be designed with an integral or separate metal or plastic spring or springs between the release mechanisms 190A, 190B.

[000102] As shown in FIG.26A, a flange spring 129 may be included in the flange 128 to help withdraw the flange end 134 from protrusion 122 after the release mechanism has unlocked the loops. Another device for assisting the flange end 134 out of protrusion 122 is shown in FIGS. 29 and 30. FIG. 29 shows an exploded cross section view of certain locking and release elements associated with one loop. At the top of the Figure, flange 128 is shown with flange end 134. Flange end 134 may have a shaped flange tip 138 with optional sloped or angled edge as indicated by angle C. A shaped area 136 such as a slot may be provided near flange tip 138, for fitting onto or into locking feature 195.

[000103] Main housing 181, which is a portion of main fixture body 180, is shown in cross section including protrusion 122 into which flange end 134 fits to close the loop. Anchor posts 184 may be provided that may fit into fingers or openings 187 in lower fixture cover 186.

[000104] Release mechanism 190 may be situated between main housing 181 and lower fixture cover 186. The release mechanism may include an actuator 199, one or more release springs 192, a locking feature 195 such as a narrowed feature to receive flange end 134 and/or flange tip 138 and particularly shaped area 136, and also an unlocking feature 196 such as a widened area to release flange end 134 and /or flange tip 138 and particularly shaped area 136. The release mechanism 190 in this example may also have a sloped element such as a ramp 194 or wedge or cam whose action will be described below. The ramp 194 may have a sloped upper surface as indicated by ramp angle D.

[000105] FIG. 30A shows the parts of FIG. 29 in an assembled configuration with the loop closed and locked. Flange end 134 is contained within protrusion 122 and is locked by locking

feature 195, for example a narrowed portion of release mechanism 190 which engages shaped area 136 on one or more sides. Meanwhile the unlocking feature 196 is spaced apart from flange tip 138. The ramp 194 is also spaced apart from flange tip 138.

[000106] FIG. 30B shows the same parts in an assembled configuration during an unlocking process. Actuator 199 may be pulled as shown by arrow E1, against the force of release spring 192. This moves locking feature 195 away from the flange tip 138, and moves unlocking feature 196 into alignment with flange tip 138, which frees the flange tip 138. Ramp 194 also moves as indicated by arrow E2 toward and contacts flange tip 138, pushing it upward as indicated by arrow E3 through the action of either or both of angled surfaces of the ramp 194 and flange tip 138 with indicated angles D and C respectively.

[000107] The flange spring 129 shown in FIG. 26A and the ramp 194 shown in FIGs. 29-30 may be used separately or in combination with one another, or with other features for encouraging the flange end 134 to start moving out of the protrusion 122.

[000108] Having described the invention in detail and by reference to the preferred embodiments, it will be apparent that modifications and variations thereof are possible without departing from the scope of the invention.

CLAIMS:

1. A binding mechanism assembly for binding a plurality of sheet items comprising:
a generally flat, planar backing member; and
at least one binding member directly or indirectly coupled to said backing member,
said binding member including a protrusion shaped and located to protrude through
a hole of a plurality of sheet items to be bound thereto,
said binding member further including a generally flexible flange configured to
engage the associated protrusion to form a generally closed loop and thereby bind
said plurality of sheet items thereto, wherein said binding member is non-slidably
coupled to said backing member,
a generally flexible transition portion coupled to and positioned between said backing
member and said binding member, wherein said flexible transition portion is
deflected when said closed loop is moved, and
at least one release mechanism moveable relative to said binding member between a
locked position, in which said release mechanism locks said binding member in
said closed loop configuration, and an unlocked position, in which said release
mechanism does not lock said binding member in said closed loop configuration,
wherein when said release mechanism is in said locked position said release mechanism
mechanically cooperates with said binding member to prevent said flange from being
disengaged from the associated protrusion, and wherein when said release mechanism is
in said unlocked position said release mechanism does not mechanically cooperate with
said binding member to prevent said flange from being disengaged from the associated
protrusion.
2. The binding mechanism assembly of claim 1, comprising a plurality of binding members.
3. The binding mechanism assembly of claim 2, where said release mechanism when moved
to the unlocked position releases all of the plurality of binding members simultaneously
4. The binding mechanism assembly of claim 2, where said release mechanism when moved
to the unlocked position releases the plurality of binding members sequentially.

5. The binding mechanism assembly of claim 1, wherein the release mechanism is moved outward from the binding mechanism to reach the unlocked position.
6. The binding mechanism assembly of claim 1, wherein the release mechanism is moved inward toward the binding mechanism to reach the unlocked position.
7. The binding mechanism assembly of claim 2, further comprising an additional release mechanism.
8. The binding mechanism assembly of claim 7, wherein the release mechanism and the additional release mechanism are located at opposed ends of the binding mechanism.
9. The binding mechanism of claim 7, wherein the release mechanism when moved to an unlocked position releases at least one loop, and the additional release mechanism when moved to an unlocked position releases at least one other loop.
10. The binding mechanism assembly of claim 1 wherein said flange of said binding member is manually deformable to engage the associated protrusion to form said generally closed loop.
11. The binding mechanism assembly of claim 1 wherein said loop is movable to a position wherein at least part of said closed loop is located below said backing member.
12. The binding mechanism assembly of claim 1 wherein said closed loop defines a plane, and wherein said binding member is rotatable about an axis oriented generally perpendicular to said plane of said closed loop when said closed loop moves from a first position to a second position.
13. The binding mechanism assembly of claim 12 wherein said binding member is rotatable at least about 15 degrees.
14. The binding mechanism assembly of claim 1 wherein said binding member and said backing member are made of a single monolithic piece of material.

15. The binding mechanism assembly of claim 1 wherein said protrusion has an opening shaped to receive a distal end of said flange therein.
16. The binding mechanism assembly of claim 1 wherein said binding member has a support portion supporting said protrusion and said flange, and wherein said transition portion is positioned between and coupled to said support portion and said backing member, wherein said support portion and said backing member each have a thickness adjacent to said transition portion, and wherein said transition portion has a thickness less than the adjacent thickness of both said support portion and said backing member.
17. The binding mechanism assembly of claim 1 wherein said backing member has a cut-out formed therein, and wherein said protrusion is located in said cut-out.
18. The binding mechanism assembly of claim 1 wherein when said closed loop is moved from a first position to a second position said closed loop is moved in a first direction, wherein the binding mechanism assembly further includes a stop surface configured to limit significant pivoting of said binding member in a second direction that is generally opposite to said first direction.
19. The binding mechanism assembly of claim 1 wherein said flange is sufficiently flexible to be manually deflected when said flange is moved into and out of contact with said protrusion.
20. The binding mechanism assembly of claim 1 wherein said flange comprises a flange spring.
21. The binding mechanism assembly of claim 1 wherein said backing member has an upper surface, and wherein said binding member is movable to a position wherein said flange and said protrusion are both generally entirely located below said upper surface.
22. The binding mechanism assembly of claim 1 wherein said backing member has an upper surface, and wherein said closed loop is configured to be generally entirely located in a first position above said upper surface when no sheet items are bound thereto.

23. The binding mechanism assembly of claim 22 wherein said binding member is configured to bind a plurality of sheet items thereto, and wherein at least part of said bound plurality of sheet items are pivotable about said closed loop to a position wherein said pivoted sheet items are located below said backing member, and wherein said loop is configured to be automatically moved to a second position when said pivoted sheet items are located below said backing member.
24. The binding mechanism assembly of claim 22 wherein said flange includes a generally horizontally extending base portion when all of said plurality of sheet items are located on a front side of said backing member, and wherein said generally horizontally extending base portion extends at least partially in a downward direction relative to said backing member when said pivoted sheet items are located below said backing member to thereby allow said pivoted sheet items to more fully underlie said backing member.
25. The binding mechanism assembly of claim 1 wherein said binding member is configured to bind a plurality of sheet items thereto, and wherein at least part of said bound plurality of sheet items are pivotable about said closed loop to a position wherein said pivoted sheet items are located below said backing member and the remainder of said plurality of sheet items are located above said backing member, and wherein said plurality of sheet items located below said backing member are generally parallel with said plurality of sheet items located above said backing member.
26. The binding mechanism assembly of claim 1 wherein said flange is directly coupled to said protrusion.
27. The binding mechanism assembly of claim 1 wherein said backing member has an inner edge extending generally parallel to a spine of said binding mechanism assembly, and wherein said closed loop is rotatable about a pivot axis relative to said backing member and wherein said pivot axis is laterally spaced away from said inner edge.
28. The binding mechanism assembly of claim 1 wherein said release mechanism further comprises a sloped element or a ramp to urge said flange at least partly out of said protrusion.

29. The binding mechanism of claim 1 wherein said binding member is non-rotatably coupled to said backing member.
30. The binding mechanism assembly of claim 1 wherein said binding member is non-slidably coupled to said backing member.
31. A binding mechanism assembly for binding a plurality of sheet items comprising:
a generally flat, planar backing member; and
at least one binding member directly or indirectly coupled to said backing member,
said binding member including a protrusion shaped and located to protrude through a hole of a plurality of sheet items to be bound thereto,
said binding member further including a generally flexible polymer or plastic flange configured to engage the associated protrusion to form a generally closed loop and thereby bind said plurality of sheet items thereto, and
at least one release mechanism moveable between a locked position and an unlocked position,
the release mechanism comprising a locking feature to hold said loop closed in the locked position and to release said loop in the unlocked position,
the release mechanism further comprising a sloped element in the form of a ramp to urge said flange at least partly out of said protrusion,
wherein when said release mechanism is in said locked position said release mechanism mechanically cooperates with said binding member to prevent said flange from being disengaged from the associated protrusion, and wherein when said release mechanism is in said unlocked position said release mechanism does not mechanically cooperate with said binding member to prevent said flange from being disengaged from the associated protrusion.
32. The binding mechanism assembly of claim 31, comprising a plurality of binding members.

33. The binding mechanism assembly of claim 32, where said release mechanism when moved to the unlocked position releases all of the plurality of binding members simultaneously.
34. The binding mechanism assembly of claim 32, where said release mechanism when moved to the unlocked position releases the plurality of binding members sequentially.
35. The binding mechanism assembly of claim 31, wherein the release mechanism is moved outward from the binding mechanism to reach the unlocked position.
36. The binding mechanism assembly of claim 31, wherein the release mechanism is moved inward toward the binding mechanism to reach the unlocked position.
37. The binding mechanism assembly of claim 32, further comprising an additional release mechanism.
38. The binding mechanism assembly of claim 37, wherein the release mechanism and the additional release mechanism are located at opposed ends of the binding mechanism.
39. The binding mechanism of claim 37 wherein the release mechanism when moved to an unlocked position releases at least one loop, and the additional release mechanism when moved to an unlocked position releases at least one other loop.
40. The binding mechanism assembly of claim 31 wherein said closed loop defines a plane, and wherein said binding member is rotatable about an axis oriented generally perpendicular to said plane of said closed loop when said closed loop moves from a first position to a second position.
41. The binding mechanism assembly of claim 40 wherein said binding member is rotatable at least about 15 degrees.
42. The binding mechanism assembly of claim 31 further comprising a generally flexible transition portion coupled to and positioned between said backing member and said binding member, wherein said flexible transition portion is deflected when said closed loop is moved to said second position.

43. The binding mechanism assembly of claim 42 wherein said binding member has a support portion supporting said protrusion and said flange, and wherein said transition portion is positioned between and coupled to said support portion and said backing member, wherein said support portion and said backing member each have a thickness adjacent to said transition portion, and wherein said transition portion has a thickness less than the adjacent thickness of both said support portion and said backing member.
44. The binding mechanism assembly of claim 31 wherein said backing member has a cut-out formed therein, and wherein said protrusion is located in said cut-out.
45. The binding mechanism assembly of claim 31 wherein when said closed loop is moved from a first position to a second position said closed loop is moved in a first direction, wherein the binding mechanism assembly further includes a stop surface configured to limit significant pivoting of said binding member in a second direction that is generally opposite to said first direction.
46. The binding mechanism assembly of claim 31 wherein said flange is sufficiently flexible to be manually deflected when said flange is moved into and out of contact with said protrusion.
47. The binding mechanism assembly of claim 31 wherein said flange comprises a flange spring.
48. The binding mechanism assembly of claim 31 wherein said flange is directly coupled to said protrusion.
49. The binding mechanism assembly of claim 31 wherein said backing member has an inner edge extending generally parallel to a spine of said binding mechanism assembly, and wherein said closed loop is rotatable about a pivot axis relative to said backing member and wherein said pivot axis is laterally spaced away from said inner edge.
50. A binding mechanism assembly for binding a plurality of sheet items comprising:

a backing member;

a binding member directly or indirectly coupled to said backing member, said binding member including a protrusion shaped and located to protrude through a hole of a sheet item to be bound thereto, said binding member further including a generally flexible flange configured to engage the protrusion to form a generally closed loop and thereby bind said sheet item thereto;

a generally flexible transition portion coupled to and positioned between said backing member and said binding member, wherein said flexible transition portion is deflected when said closed loop is moved; and

a locking mechanism moveable between a locked position and an unlocked position, wherein when said locking mechanism is in said locked position and said flange and protrusion form said generally closed loop, said locking mechanism holds said flange in said generally closed loop configuration,

wherein when said locking mechanism is in said locked position said locking mechanism mechanically cooperates with said binding member to prevent said flange from being disengaged from the protrusion, and wherein when said locking mechanism is in said unlocked position said locking mechanism does not mechanically cooperate with said binding member to prevent said flange from being disengaged from the protrusion.

51. A binding mechanism assembly comprising:

a backing member;

a binding member including a protrusion shaped and located to protrude through a hole of a sheet item to be bound thereto, said binding member further including a manually flexible flange configured to engage in the protrusion to form a generally closed loop therewith;

a generally flexible transition portion coupled to and positioned between said backing member and said binding member, wherein said flexible transition portion is deflected when said closed loop is moved, and

a locking mechanism moveable between a locked position wherein said locking mechanism retains said flange in place engaging said protrusion and an unlocked position in

which said locking mechanism does not retain said flange in place with respect to said protrusion,

wherein when said locking mechanism is in said locked position said locking mechanism mechanically cooperates with said binding member to prevent said flange from being disengaged from the protrusion, and wherein when said locking mechanism is in said unlocked position said locking mechanism does not mechanically cooperate with said binding member to prevent said flange from being disengaged from the protrusion.





FIG. 1



3 / 28




FIG. 3

4 / 28




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8






FIG. 9



11/ 28






FIG. 12




FIG. 13

14 / 28




FIG. 14




FIG. 15

15 / 28



FIG. 16A




FIG. 16B



FIG. 16C

16 / 28




FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21






FIG. 23




FIG. 24




FIG. 25A

FIG. 25B




FIG. 26A




FIG. 26B




FIG. 26C




FIG. 26D

