



(86) **Date de dépôt PCT/PCT Filing Date:** 2021/11/08
(87) **Date publication PCT/PCT Publication Date:** 2022/05/12
(45) **Date de délivrance/Issue Date:** 2023/04/18
(85) **Entrée phase nationale/National Entry:** 2022/05/06
(86) **N° demande PCT/PCT Application No.:** CA 2021/051587
(87) **N° publication PCT/PCT Publication No.:** 2022/094725
(30) **Priorité/Priority:** 2020/11/09 (US63/111,262)

(51) **Cl.Int./Int.Cl. F16L 55/12** (2006.01)
(72) **Inventeurs/Inventors:**
NABER, DAVID, CA;
DHALIWAL, AMANJEET, CA;
SKIBA, ALEXANDER, CA
(73) **Propriétaire/Owner:**
ENREACH HOT TAP SERVICES INC., CA
(74) **Agent:** GOWLING WLG (CANADA) LLP

(54) **Titre : OUTIL D'ISOLATION ET METHODES D'ISOLATION D'UNE SECTION DE TUYAU OU DE RECIPIENT**
(54) **Title: ISOLATION TOOL AND METHODS OF ISOLATING A SECTION OF PIPE OR A VESSEL**

(57) **Abrégé/Abstract:**

The present disclosure provides an isolation tool for isolating a section of pipe or a vessel and methods for isolating a section of a pipe or a vessel. In particular, the present disclosure provides a double isolation and bleed (DI B) isolation tool, for use in line-stopping operations and methods of line isolation employing the isolation tool.



Date Submitted: 2022/05/06

CA App. No.: 3157635

Abstract:

The present disclosure provides an isolation tool for isolating a section of pipe or a vessel and methods for isolating a section of a pipe or a vessel. In particular, the present disclosure provides a double isolation and bleed (DIB) isolation tool, for use in line-stopping operations and methods of line isolation employing the isolation tool.

ISOLATION TOOL AND METHODS OF ISOLATING A SECTION OF PIPE OR A VESSEL

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and benefit of United States Provisional Patent Application Serial Number 63/111,262 filed on November 9, 2020.

TECHNICAL FIELD

[0002] The present disclosure generally relates to an isolation tool for use in isolating a section of pipe or a vessel, and for example to a line-stopping tool. In particular aspects, the isolation tool may be a double isolation and bleed (DIB) tool.

BACKGROUND

[0003] The isolation of pipes or other types of cylindrical vessels (e.g. tanks) is required in many different industries. Effective isolation tools, particularly those that function under a wide range of pressure conditions in the pipe or vessel (e.g. no pressure, low pressure and high pressure), are required. This is particularly the case for the isolation of operational pipelines.

[0004] Pipes and other flow lines, such as those used in the oil and gas industry, commonly require hot-tapping and line-stopping operations to isolate a section of pipe while the pipeline itself remains pressurized.

[0005] Hot-tapping, or pressure-tapping, refers to the process of making a connection into a pressurized pipe or vessel using equipment and procedures to ensure that the pressure and fluids are safely contained when access is made. A common example is tapping into a pressurized oil and gas pipeline. Hot-tapping is often performed by fitting a branch connection (e.g. flanged saddle) to the live pipe, whereby the branch connection is fitted with a temporary valve that prevents leakage from the live fluid pipe after tapping (e.g. drilling) into the pipe. The tapping tool itself is configured to prevent leakage during pipe cutting and, upon removal, the temporary valve is closed to complete the branch connection. Line-stopping tools may then be inserted into the live pipe through the hot-tap connection to isolate a downstream region of the pipe from pressures and fluids.

[0006] The industry currently utilizes hot-tapping and line isolation techniques to perform a variety of tasks, including pipeline maintenance and repairs. The requirements of a line isolation are defined by various safety and regulatory bodies in which operator guidelines are established. For example, according to the Occupational Health and Safety (OHS) Code in Alberta, Canada, in order to isolate piping or a pipeline containing harmful substances under pressure, an operator is required to use either (a) a system of blanking or blinding or (b) a double-block and bleed isolation system (Section 215.4 – Isolating piping). Blanking and blinding are methods of providing a physical barrier to the end of a pipe section or into a cross-section of piping. These methods can only be employed when the section of piping is not in-service.

[0007] A double-block and bleed (DBB) system is required, on each upstream side of a pipeline, when the pipeline is in-service and there is potential for the flow of the substance to come from more than one direction. This system involves the use of a three-valve setup where a pipe has two unidirectional block valves (double-block) and an open drain (bleed) valve positioned in between. The closed valves provide a stop in fluid flow, while the bleed valve is used to redirect flow in the event of a valve leak. In situations in which there was no system in place to provide any isolation (e.g. typically DBB valve systems are not in place unless installed during new construction), a DBB line-stopping tool can be used in conjunction with in-service hot-tapping systems to provide temporary isolation of downstream pipe.

[0008] In addition to DBB systems, a double isolation and bleed (DIB) system typically seals from pressure from a given direction using two separate bi-directional seals and a bleed positioned in between. In a DIB system, if one seal leaks, the second seal will maintain the seal. Also, since DIB systems having bi-directional seals, they allow for pipeline pressures and fluids to be isolated from both directions.

[0009] Several issues exist with conventional line-stopping systems and methods. For one, a basic system with two plugs and a bleed valve does not meet the full criteria of a DBB isolation system. In such systems, the seals require pipeline pressure to actively engage the wall of the pipe, i.e. to become energized. However, when pipeline pressure is against the first plug creating a seal, there is no pressure in the void between the energized seal and the second downstream seal. Therefore, the second downstream seal is not energized (i.e. not engaged against the wall of the pipe) when the first seal is energized. As such, there is no double-

block. In such situations, if the energized seal on the first plug fails, there is a high likelihood of the first plug shifting on angle, thereby affecting the alignment of the second plug and causing improper seal engagement with the pipeline and, ultimately, a line stop failure.

[0010] For another, in typical systems with two plugs such as the STOPPLE® system, additional fittings are required to provide the bleed valve, which need to be hot-tapped to the pipeline in between the two seals and remain thereafter. Further, large fittings with two strand plug heads result in a very large installation foot print and limit installation options. Moreover, the large fittings and plug seal cup design complicates removal of the line stop from the pipeline.

[0011] As with conventional two plug line-isolation tools, single plug systems involving actuator engagement of multiple seals do not meet DBB (or DIB) isolation system requirements. In such systems, the seals are not engaged independently. Rather, a single actuator operates both seals. If the actuator fails, both seals will fail.

[0012] Therefore, a need exists for a line-stopping tool that provides greater safety, functionality and compliance with DBB and DIB criteria, while at the same time being smaller and more flexible in its operation. More broadly, there exists a need for an isolation tool that provides improved operation in sealing a pipe wall or a vessel, with greater safety and greater functionality.

SUMMARY

[0013] The present disclosure provides isolation tools and methods for isolating a section of a pipe or a vessel. The present disclosure recognizes that there are problems in the current existing isolation and line-stopping technologies in respect of tools, processes and systems, including in DBB and DIB technologies and tools.

[0014] An advantage of the present disclosure is the provision of isolation tools and methods having improved characteristics over existing technologies.

[0015] In an embodiment, the present disclosure relates to a head unit for an isolation tool, the head unit comprising: at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the

exterior of the head unit, and a curvature therebetween; and a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove.

[0016] In an embodiment, the present disclosure relates to an isolation tool for isolating a section of a pipe or a vessel, the isolation tool comprising: a head unit configured for location in a section of a pipe or a vessel, the head unit comprising: at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove.

[0017] In an embodiment, the present disclosure relates to methods of isolating a section of a pipe or a vessel using the isolation tools as disclosed herein.

[0018] In an embodiment, the present disclosure relates to a method of isolating a section of a pipe or a vessel, the method comprising the steps of: inserting a head unit of an isolation tool into a pipe or a vessel, the head unit comprising: (i) at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and (ii) a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; and providing a force at the first end of the at least one groove to impart radial expansion of the circumferential seal element at the second end to engage the circumferential seal element against the pipe or vessel and thereby isolate the section of the pipe or vessel.

[0019] In an embodiment, the present disclosure relates to a method of engaging a seal against a wall of a pipe or a vessel, the method comprising imparting a linear force within a fixed space and in an axial or tangential direction to a circumferential seal element, to impart radial expansion of the circumferential seal element via a curvature within the fixed space.

[0020] In an embodiment, the present disclosure relates to a locking mechanism for a line-stopping tool, the locking mechanism comprising: a circumferential cartridge for engaging a piston or a circumferential seal element of a line-stopping tool, the circumferential cartridge comprising one or more dogs positioned around a circumference of the circumferential seal element and a biasing component for maintaining the one or more dogs in an outwardly biased position; a release ring for engaging the one or more dogs of the circumferential cartridge; and an alignment component for biasing the release ring away from the circumferential cartridge.

[0021] Other aspects and embodiments of the disclosure are evident in view of the detailed description provided herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] Further advantages, permutations and combinations of the invention will now appear from the above and from the following detailed description of the various particular embodiments of the invention taken together with the accompanying drawings, each of which are intended to be non-limiting, in which:

[0023] **FIG. 1** is a view of an exemplary head unit of the present disclosure.

[0024] **FIG. 2** is a cross-sectional view of a head unit of the present disclosure along the A-A line shown in **FIG. 1**.

[0025] **FIGs. 3A-C** illustrate an exemplary circumferential seal element of the present disclosure, wherein **FIG. 3A** is a perspective view of the seal; **FIG. 3B** is a top-plan view of the circumferential seal element; and **FIG. 3C** is a cross-sectional view of the circumferential seal element along the B-B line shown in **FIG. 3B**.

[0026] **FIG. 4** illustrates an exemplary embodiment of components of an isolation tool of the present disclosure having groove channels into which a portion of the circumferential seal element may extend.

[0027] **FIG. 5** is a cross-sectional view of an exemplary head unit of the present disclosure having a circumferential seal element disposed therein, whereby the circumferential seal element is a single unit.

[0028] FIG. 6 is a cross-sectional view of an exemplary head unit of the present disclosure having a circumferential seal element disposed therein, whereby the circumferential seal element is comprised of two separate units placed adjacent each other.

[0029] FIG. 7 is a cross-sectional view of an exemplary head unit of the present disclosure having a circumferential seal element disposed therein, whereby the circumferential seal element is comprised of two separate units with a medium therebetween.

[0030] FIGs. 8A-B illustrate an exemplary core of the present disclosure, wherein FIG. 8A is a perspective view the core and FIG. 8B is a cross-sectional internal view of the core along the C-C line shown in FIG. 8A.

[0031] FIGs. 9A-C illustrate an exemplary internal member of the present disclosure, wherein FIG. 9A is a perspective view of the internal member; FIG. 9B is a top plan view of the internal member; and FIG. 9C is a cross-section view of the internal member along the D-D line shown in FIG. 9B.

[0032] FIGs. 10A-B are views of the first end (FIG. 10A) and second end (FIG. 10B) of an exemplary casing of the present disclosure.

[0033] FIG. 11 is a view of a line-stopping tool of the present disclosure approaching an opening in the wall of a pipe.

[0034] FIG. 12 is a view of the line-stopping tool of the present disclosure as it is being lowered through the opening in the wall of the pipe.

[0035] FIG. 13 is a view of the line-stopping tool of the present disclosure as it transitions into the pipe.

[0036] FIG. 14 is a view of the line-stopping tool of the present disclosure in its sealing position in the pipe, prior to a force being applied.

[0037] FIG. 15 is a view of the line-stopping tool of the present disclosure in its sealing position in the pipe, after the force is applied (i.e. activated).

[0038] FIG. 16 illustrates an exemplary line-stopping tool of the present disclosure comprising a wheel assembly.

[0039] FIGs. 17A-B are cross-sectional views illustrating exemplary embodiments of a groove with a 90 degree curvature and a circumferential seal element disposed therein in the deactivated state, wherein each of FIG. 17A and FIG. 17B show different types of a circumferential seal element.

[0040] FIG. 18 is a cross-sectional view illustrating the circumferential seal element of either FIG. 17A or FIG. 17B in the activated state.

[0041] FIGs. 19A and 19B are graphic depictions of the cross-sectional illustrations of FIGs. 17A and 17B, respectively.

[0042] FIG. 20 is a graphic depiction of the cross-sectional illustration of FIG. 18.

[0043] FIG. 21 is a deconstructed view of an exemplary locking mechanism of the present disclosure.

[0044] FIGs. 22A-B are graphic representations of head unit components for purposes of describing an exemplary locking mechanism of the present disclosure, whereby FIG. 22A is a perspective view and FIG. 22B is a side view with cross-sectional lines shown.

[0045] FIG. 23 is cross-sectional view of the representative head unit of FIG. 22B along each of lines E-E, F-F and G-G when the circumferential seal element is in an activated state.

[0046] FIG. 24 is cross-sectional view of the representative head unit of FIG. 22B along each of lines E-E, F-F and G-G when the circumferential seal element is in a de-activated state.

[0047] FIG. 25 is a detailed expanded view of the locking mechanism as depicted in E-E in FIG. 23.

[0048] FIG. 26 is a detailed expanded view of the locking mechanism as depicted in F-F in FIG. 23.

[0049] FIG. 27 is a detailed expanded view of the locking mechanism as depicted in G-G in FIG. 23.

[0050] FIG. 28 is a detailed expanded view of the locking mechanism as depicted in E-E in FIG. 24.

[0051] FIG. 29 is a detailed expanded view of the locking mechanism as depicted in F-F in FIG. 24.

[0052] FIG. 30 is a detailed expanded view of the locking mechanism as depicted in G-G in FIG. 24.

DETAILED DESCRIPTION

[0053] Unless otherwise defined, all technical and scientific terms used herein generally have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure pertains. Exemplary terms are defined below for ease in understanding the subject matter of the present disclosure.

Definitions

[0054] The term “a” or “an” refers to one or more of that entity; for example, “a circumferential seal element” refers to one or more circumferential seal elements or at least one circumferential seal element. As such, the terms “a” (or “an”), “one or more” and “at least one” are used interchangeably herein. In addition, reference to an element or feature by the indefinite article “a” or “an” does not exclude the possibility that more than one of the elements or features are present, unless the context clearly requires that there is one and only one of the elements. Furthermore, reference to a feature in the plurality (e.g. circumferential seal elements), unless clearly intended, does not mean that the line-stopping tool or methods disclosed herein must comprise a plurality.

[0055] “About”, when referring to a measurable value such as an angle, a dimension, and the like, is meant to encompass variations of $\pm 10\%$, $\pm 5\%$, $\pm 1\%$, $\pm 0.5\%$ or $\pm 0.1\%$ of the specified amount. When the value is a whole number, the term about is meant to encompass decimal values, as well the degree of variation just described. It is to be understood that such a variation is always included in any given value provided herein, whether or not it is specifically referred to.

[0056] “And/or” refers to and encompasses any and all possible combinations of one or more of the associated listed items (e.g. one or the other, or both), as well as the lack of combinations when interrupted in the alternative (or).

[0057] “Comprise” as is used in this description and in the claims, and its conjugations, is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded.

Isolation Tools and Methods

[0058] The technology of the present disclosure may be suitable for several applications of isolating a pipe or a vessel. The present disclosure provides advantageous isolation tools comprising an improved design, and methods of employing the isolation tool. The disclosure herein largely discusses the technology in the context of line-stopping applications, but it will be appreciated that other applications and uses are equally applicable. In this context, reference to a “line-stopping tool” of the present disclosure is intended as an embodiment of the disclosed “isolation tool”. The term “line-stopping tool” applies to embodiments for isolating a pipeline.

[0059] The present disclosure provides advantageous isolation tools comprising an improved design, and methods of employing the isolation tool. More particularly, the present disclosure provides improved line-stopping tools that, for example, meet double-block and bleed (DBB) requirements, including providing a true DIB line-stopping tool.

[0060] As discussed elsewhere herein, several issues and/or inefficiencies exist with conventional isolation tools, systems and methods, for example those used in line-stopping applications. One advantage of the present disclosure is the provision of isolation tools and methods having improved characteristics over existing technologies.

[0061] Another advantage of the present disclosure is the provision of isolation tools that optionally provide two independently activated and monitored circumferential seal elements on a single head unit. The circumferential seal elements may be activated individually and completely independently from each other. Moreover, the pressure and sealing engagement of each of the circumferential seal elements may each be monitored and tested throughout operation. This ensures the safety of any personnel, for example that may need to work downstream of a line-stop location.

[0062] Another advantage of the present disclosure is the ability to pressure test the circumferential seal elements after activation to ensure that the equipment is in place and the

intended isolation is achieved. If for some reason a sealing engagement was not obtained, the present isolation tool allows for detection of this fault, deactivation of one or multiple circumferential seal elements and subsequent re-activation of the circumferential seal elements without exiting and re-entering the tool from the pipe or vessel, which would cause significant delay. In select embodiments, pressure at a bleed port between the circumferential seal elements may be continually monitored and bled, providing a true DIB line-stopping tool in line-stopping applications.

[0063] A further advantage of the isolation tool of the present disclosure is that sealing engagement of the circumferential seal elements is not activated by pipeline pressure and therefore the pressure in the pipeline or vessel does not impact the functionality of the present technology. The isolation tool (e.g. line-stopping tool) of the present disclosure can be used, and the circumferential seal elements engaged against the wall of the pipeline, irrespective of whether pipeline pressure is present or not. This is quite advantageous since conventional line-stopping tools, which are incapable of creating a sealing engagement on low-pressure systems, may require the pipeline pressure to be increased solely for the purpose of engaging the seals. In contrast, the isolation tools of the present disclosure work irrespective of pipeline pressure (e.g. no pressure, low pressure or high pressure).

[0064] A further advantage of isolation tool of the present disclosure is the effectiveness in the design of the circumferential seal element within a curved groove. A non-radial force (e.g. a hydraulic fluid or a mechanical force) causes the circumferential seal element to move within the groove in a manner that, via the curvature, causes a seal portion of the circumferential seal element to expand or grow radially to form a strong and effective sealing engagement with the pipe. Moreover, upon deactivation, the curvature in the groove may further function or aid in pulling the seal portion back into the tool to its original (de-activated) conformation.

[0065] A further advantage is that the isolation tools of the present disclosure are capable of being easily and properly aligned in the pipeline. Embodiments of the line-stopping tool disclosed herein minimize loading, and the placement of the pivot point between the carrier unit and arm assembly results in a zero balance load, whereby the head unit cannot rotate in the pipe. A zero moment is formed whereby longitudinal force within the pipe is directed directly up the carrier unit (i.e. the force is turned 90°), preventing rotational movement of the

head unit. The zero moment locks the carrier unit into position when line pressure is applied through the seals being activated and allows for higher sealing pressures.

[0066] The above advantages allow for the provision of isolation tools that enhance safety and increase efficiency and/or functionality of the tools. In certain embodiments, the result is a pretested and verified DIB line-stopping tool.

[0067] Still other advantages and benefits of the isolation tools and methods disclosed herein will become apparent to those skilled in the art upon a reading and understanding of the following detailed description.

[0068] As used herein, the term “line-stopping” is intended to refer to isolating a section of pipe within a process pipeline and may be used interchangeably with expressions such as “isolating a pipe” or “pipeline isolation”.

[0069] It will be understood that reference herein to a “line-stopping tool” is to an apparatus or a system that may be used to isolate a section of pipe within a process pipeline, or a component of the entire system such as the head unit alone which itself functions as a line-stopping tool. As used herein, the “line-stopping tool” may comprise one or any number of components, including the head unit alone or together with one or more of a carrier unit, arm assembly, or other components.

[0070] As used herein, the term “isolate” or “isolation” means to plug or stop the flow within a pipe or vessel. In effect, the “isolation” acts to seal off one portion of the pipe or vessel from another portion. In an embodiment, the “pipe” is a process pipeline. By “process pipeline” it is meant to include any pipe that may be used to carry substances, including in particular any fluid-carrying or gas-carrying pipeline. The process pipeline may be a pipeline carrying any type of fluid, gas or chemical, including without limitation oil, gas, natural gas, ammonia, gasoline, alcohol fuels, water, hazardous materials, hazardous waste, waste water, sewage, chemicals or drainage from households, municipalities, manufacturing plants, or food-processing plants. The reference to “pipe” or “pipeline” includes any tubular structure or construction. The pipe may be above ground, below ground, or undersea, or may be any type of downhole tubing. In an embodiment, the “pipe” is a well bore, including for example an uncased well bore. The isolation tool may be installed within a section of pipe at any time,

including before the pipeline becomes operational, during operation, or during a period when the pipeline is shutdown.

[0071] As used herein, the reference to “vessel” includes any container, such as for example a tank (e.g. a storage tank), of cylindrical or substantially cylindrical shape. The isolation tool of the present disclosure may be installed within a section of a vessel at any suitable time and location.

[0072] In an embodiment, the isolation tool disclosed herein is a line-stopping tool, and in particular embodiments a double isolation and bleed (DIB) line-isolation tool. By a “DIB line-isolation tool”, it is meant to refer to a line-stopping tool that typically comprises at least two separate and independent bi-directional circumferential seal elements for isolation of a section of pipe, and between the circumferential seal elements is located a bleed valve or conduit to purge pressure, fluid and/or gas if it passes one of the circumferential seal elements. Alternate embodiments of a DIB line-isolation tool are possible.

[0073] Reference will now be made in detail to exemplary embodiments of the disclosure, wherein numerals refer to like components, examples of which are illustrated in the accompanying drawings that further show exemplary embodiments, without limitation.

Isolation Tool

[0074] The present disclosure provides isolation tools, including a head unit and/or a multi-component apparatus that includes the head unit in association with other components, such as for example a carrier unit and arm assembly.

[0075] In an embodiment, the present disclosure relates to an isolation tool for isolating a section of a pipe or a vessel, the isolation tool comprising: a head unit configured for location in a section of a pipe or a vessel, the head unit comprising: at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove

imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove.

[0076] In an embodiment, the present disclosure relates to a head unit for an isolation tool, the head unit comprising: at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove.

[0077] The technology of the present disclosure may be suitable for several applications of isolating a pipe or a vessel. In an embodiment the isolation tool of the present disclosure is a line-stopping tool. With reference below to the drawings herein, the present disclosure largely discusses the technology in the context of line-stopping applications, but it will be appreciated that other applications and uses are equally applicable.

[0078] FIG. 1 is an image of an exemplary head unit **20** of the present disclosure and FIG. 2 is a cross-sectional view along the A-A line shown in FIG. 1. As used herein, the term “head unit” is intended to refer to the component of an isolation tool that acts as a plug during isolation of a section of a pipe or vessel such as for example a pipe **200**. The head unit is itself a tool for isolation, and is alone encompassed herein by the term “isolation tool”, although a complete isolation tool such as for example a line-stopping tool typically includes additional components such as for example a carrier unit and an arm assembly. For ease in positioning the head unit **20** within the pipe **200** or a vessel, a preferred shape for the head unit **20** may be a spherical shape or a cylindrical shape. However, as the skilled person will appreciate other shapes may be employed.

[0079] The head unit **20** of the present disclosure may be used in the line-stopping tool **10** as described herein or may be used in other available line-stopping tools, as well as in any other suitable isolation tool such as for example pressure test plugs. In embodiments where the head unit **20** of the present disclosure is used in other tools, it is contemplated that the tools may need to be modified to accommodate the head unit of the present disclosure. This could readily be accomplished by the skilled person having regard to the present disclosure.

[0080] The head unit **20** comprises at least one groove **22** around a circumference of the head unit **20** for containing within the groove a circumferential seal element **24**. In an embodiment, each groove **22** comprises a first end **22a** within the head unit, a second end **22b** open to the exterior of the head unit **20**, and a curvature **22c** therebetween. As used herein, the term “groove” refers to a channel, a cut, or an indentation in an object that is configured to permit another component to move within the defined space and/or be guided by the defined space. In an embodiment, the groove is a fixed structure that does not change in shape or size during operation of the isolation tool (e.g. during activation or deactivation of the circumferential seal element). As used herein, the term “curvature” refers to a portion of the groove **22** that deviates from being linear, including a bend and/or a 90 degree corner. The curvature **22c** is positioned between the first end **22a** and the second end **22b** of the groove **22** and functions as a curve or corner through which at least a portion of the circumferential seal element **24** travels upon activation and/or deactivation.

[0081] As used herein, the term “circumference” is a linear distance around an object such as for example the head unit **20**. An object may have a circumference at more than one position, depending on its shape. In an embodiment, the one or more circumferences defining the position of each of the grooves **22** on the head unit **20** are at positions that closely share a common axis with the pipe **200** or vessel when the head unit **20** is located within the pipe **200** or vessel. By “closely share”, it is meant that the circumference is not perfectly coaxial with the pipe **200** or vessel as the axis of the circumference may be angled slightly in relation to the axis of the pipe **200** or vessel. This may be due to the head unit **20** being slightly angled in the pipe **200** or vessel and/or the circumference being slightly angled on the head unit **20**.

[0082] In other embodiments, the one or more circumferences defining the position of each of the grooves **22** on the head unit **20** are at positions that are in coaxial alignment with the pipe when the head unit **20** is located within the pipe **200** or a vessel, e.g. in an activated state. As will be appreciated, by “coaxial alignment” it is meant that the referenced circumference and the pipe are aligned such that they share a common axis of rotation. In this configuration, the pipe circumference encircles the referenced circumference of the head unit **20** and thereby the second end **22b** of the groove **22**, when the head unit **20** is located within the pipe. By “located within the pipe” it is intended to mean when the head unit **20** is in an operational position in the pipe **200** (e.g. in a position for sealing engagement with the pipe), such as for

example as shown in **FIG. 14**. By “activated state” it is meant that the head unit **20** is in sealing engagement with the pipe **200** or vessel.

[0083] In an embodiment, the head unit **20** has at least two grooves, such as for example two, three or four grooves, and in particular, two grooves. In embodiments where the head unit **20** includes more than one groove **22**, the circumference defining the position of each groove **22** on the head unit **20** may be spaced apart along the head unit **20** such that each circumferential seal element **24** would engage the pipe at a different position along a length of the pipe. This is for example shown in **FIGs. 1** and **14** where the head unit **20** comprises two grooves **22**. As discussed elsewhere herein, the inclusion of two grooves **22**, each with an independently activated circumferential seal element **24**, is of particular relevance to DBB and DIB line-stopping tools. In an embodiment, the two grooves **22** may be configured in a stacked manner such that the curvature of each groove is oriented in the same direction (not shown).

[0084] The groove **22** may be of any suitable size to accommodate a circumferential seal element **24** (**FIG. 3** and **14**). In an embodiment, the groove **22** has a substantially uniform width (**w**) from the first end **22a** to the second end **22b**. In an embodiment, the width is between about 0.5 inches and about 2.5 inches. In an embodiment, the width is between about 0.5 inches and about 1.0 inches. In a particular embodiment, the groove **22** has a width of about 0.5 inches, about 0.6 inches, about 0.7 inches, about 0.8 inches, about 0.9 inches, or about 1.0 inches. In another particular embodiment, the groove **22** has a width of about 0.75 inches.

[0085] In an embodiment, the groove **22** narrows at or near the second end **22b**. Without being bound by any particular theory, the narrowing of the groove **22** at the second end **22b** may cause the second end **22b** to act as an extrusion point. In an embodiment, the width of the groove narrows at the second end **22b** by between about 0.1 inches and about 0.5 inches as compared to the first end **22a**. In an embodiment, the width of the groove **22** narrows at the second end **22b** by about 0.1 inches, about 0.15 inches, about 0.2 inches, about 0.25 inches, about 0.3 inches, about 0.35 inches, about 0.4 inches about 0.45 inches, or about 0.5 inches. In an embodiment, the groove narrows at the second end **22b** by between about 5 degrees and about 10 degrees over a suitable distance to achieve the desired narrowing. In a

particular embodiment, the groove narrows at the second end **22b** by about 7 degrees over a suitable distance to achieve the desired narrowing.

[0086] The curvature **22c** of the groove **22** may be of any suitable angle to provide a non-linear shape or path to the groove **22**. The curvature **22c** of the groove may be any angle greater than 0 degrees and less than 180 degrees. In an embodiment, the curvature **22c** of the groove **22** is between about 60 degrees and about 120 degrees. In an embodiment, the curvature is between about 80 degrees and about 100 degrees. In an embodiment, the curvature is about 80 degrees, about 81 degrees, about 82 degrees, about 83 degrees, about 84 degrees, about 85 degrees, about 86 degrees, about 87 degrees, about 88 degrees, about 89 degrees, about 90 degrees, about 91 degrees, about 92 degrees, about 93 degrees, about 94 degrees, about 95 degrees, about 96 degrees, about 97 degrees, about 98 degrees, about 99 degrees, or about 100 degrees. In a particular embodiment, the curvature is a 90 degree corner.

[0087] In an embodiment, the groove **22** has a depth defined by the distance from the second end **22b** to the midpoint of the curvature **22c**. In an embodiment, the depth is between about 0.5 inches and about 10.0 inches, more particularly 0.5 inches and about 2.5 inches. In an embodiment, the depth is between about 1.0 inch and about 2.0 inches. In a particular embodiment, the depth is about 1.0 inch, about 1.1 inches, about 1.2 inches, about 1.3 inches, about 1.4 inches, about 1.5 inches, about 1.6 inches, about 1.7 inches, about 1.8 inches, about 1.9 inches, or about 2.0 inches. In another particular embodiment, the depth is about 1.6 inches. As will be appreciated, the depth may be any suitable distance within the confines of the configuration of the head unit.

[0088] In an embodiment, the groove **22** comprises a length defined by the distance from first end **22a** to the midpoint of the curvature **22c**. In an embodiment, the length is about 1.0 inch and about 10.0 inches. In an embodiment, the length is between about 2.0 inches and about 3.0 inches. In a particular embodiment, the length is about 2.0 inches, about 2.1 inches, about 2.2 inches, about 2.3 inches, about 2.4 inches, about 2.5 inches, about 2.6 inches, about 2.7 inches, about 2.8 inches, about 2.9 inches, or about 3.0 inches. In another particular embodiment, the length is about 2.25 inches. In an embodiment, the depth and the length of the groove **22** are approximately equal. As will be appreciated, the length may be any suitable distance within the confines of the configuration of the head unit **20**.

[0089] In an embodiment, the curvature **22c** interconnecting the depth and the length of the groove **22** may be defined by a radius of curvature. The term “radius of curvature” refers to the radius of the circular arc that best approximates each of the inner and outer curves of the curvature **22c**. In an embodiment, the inner radius of curvature is between about 0.2 inches and about 0.5 inches. In an embodiment, the inner radius of curvature is about 0.2 inches, about 0.3, inches, about 0.4 inches, or about 0.5 inches. In a particular embodiment, the inner radius of curvature is about 0.38 inches. In an embodiment, the outer radius of curvature is between about 1.0 inches and about 1.5 inches. In an embodiment, the outer radius of curvature is about 1.0 inches, about 1.1 inches, about 1.2 inches, about 1.3 inches, about 1.4 inches, or about 1.5 inches. In a particular embodiment, the outer radius of curvature is about 2.35 inches. As will be appreciated, the radius of curvature may be of any suitable dimensions within the confines of the configuration of the head unit **20**.

[0090] In an embodiment, the at least one groove **22** may have more than one first end **22a** (e.g. a split groove). For example, the groove may be of a “Y” configuration whereby there are two first ends **22a** and a single second end **22b**. In such embodiments, the circumferential seal element **24** (described below) may comprise first and second seal engagement portions **24b** disposed respectively within each of the first ends **22a**, and the force may be applied at each of the first ends **22a**.

[0091] In an embodiment, the head unit **20** comprises a single groove **22**. In other embodiments, the head unit **20** comprises two grooves **22**. In embodiments in which the head unit comprises more than one groove **22**, each groove **22** may be of similar shape, size and orientation or may be a different shape, size, and/or orientation. In a particular embodiment, a head unit **20** of the present disclosure comprises two grooves **22** of similar size and shape, but in an opposing orientation within the head unit **20**, for example as shown in **FIG. 2**.

[0092] In an embodiment, the groove **22** may further comprises two or more groove channels **23** extending at least a portion of the first end **22a** further within the head unit **20**, the groove channels spaced apart from each other around the circumference of the groove (see e.g. **FIG. 4**). The groove channels may function, for example, to provide a channel in which the force may be localized and applied to the circumferential seal element **24** at the first end **22a**. The two or more groove channels may be of any suitable shape or size and may extend to any suitable length into the head unit **20**. In an embodiment, each of the two or more groove

channels may be the same shape, size and/or length, or not. In an embodiment, each of the two or more groove channels are spaced equidistant around the circumference.

[0093] In an embodiment, the force at or near the first end **22a** of the groove **22** is from within the two or more groove channels. The force may be from within each of the groove channels or may be from within a selected number of the groove channels.

[0094] In an embodiment, the curvature **22c** of the groove **22** may be formed within the two or more groove channels. In an embodiment, a portion **24c** of the circumferential seal element **24** extends within the two or more groove channels. In an embodiment as described in more detail elsewhere herein, the circumferential seal element **24** comprises a seal portion **24a** for engaging the pipe and a seal engagement portion **24b** for receiving the force. In such embodiments, the seal engagement portion **24b** may be disposed within the two or more groove channels.

[0095] Disposed within each groove **22** of the head unit **20** is a circumferential seal element **24**. As used herein, the term “circumferential seal element” is intended to refer to a sealing component having at least one circumference and may also be referred to as a seal or a ring seal. As will be appreciated, the term “disposed within” indicates that the circumferential seal element **24** is positioned within the groove **22**. In an embodiment, a portion of the circumferential seal element **24** may protrude from the second end **22b** of the groove **22**, even in the deactivated state. In the activated state, radial expansion of the circumferential seal element **24** causes an even greater proportion of the circumferential seal element **24** to protrude from the second end **22b** of the groove **22**. As used herein, the term “radial expansion” is intended to refer to an outward expansion of the circumferential seal element **24** from the second end **22b** of the groove **22** to thereby provide an enlarged outer seal edge for engaging the pipe.

[0096] Within the groove **22**, the circumferential seal element **24** spans at least a portion of the curvature **22c**. As used herein, the term “spanning at least a portion of the curvature” is intended to refer to the circumferential seal element **24** being present over either a portion of the full length of the curvature **22c** or the full length of the curvature **22c** at least when the circumferential seal element **24** is in the deactivated state. In an embodiment, the circumferential seal element **24** spans at least about 1/8, 1/4, 3/8, 1/2, 5/8, 3/4 or 7/8 of the full length of the curvature **22c** at the end or portion of the curvature **22c** proximal to the second

end **22b** of the groove **22**. In a particular embodiment, the circumferential seal element **24** spans the full length of the curvature **22c** and extends to the opening at the second end **22b** of the groove. In a particular embodiment, the circumferential seal element **24** spans the full length of the curvature **22c**, extends to the opening at the second end **22b** of the groove **22**, and extends beyond the curvature **22c** towards the first end **22a** of the groove **22**. In instances where the curvature is a 90 degree corner, spanning at least a portion of the curvature means that at least a portion of the circumferential seal element **24** extends into the first end **22a** at least when the circumferential seal element **24** is in the deactivated state. Exemplary embodiment are shown in **FIG. 17A** and **17B** where at least a portion of the circumferential seal element crosses plane (**p**; dashed line) into the first end **22a**. **FIG. 17A** and **17B** show the conformation of a circumferential seal element **24** in a deactivated state. **FIG. 18** shows an exemplary change in conformation of the circumferential seal element of **FIG. 17A** and **17B** when either one is actuated into the activated state by a force at the first end **22a** (e.g. a force upon piston **30**).

[0097] **FIG. 3** shows an exemplary embodiment of a circumferential seal element **24** of the present disclosure. In an embodiment, the circumferential seal element **24** comprises a seal portion **24a** and a seal engagement portion **24b**. As used herein, the “seal portion” refers to the part of the circumferential seal element **24** that sealingly engages the wall of the pipe **200** upon activation of circumferential seal element **24**. In an embodiment, the seal portion **24a** sealingly engages the wall of the pipe **200** when the seal portion **24a** is radially expanded by a force at or near the first end **22a** of the groove **22**. As used herein, the term “seal engagement portion” is intended to refer to the part of the circumferential seal element **24** that is located proximal to the first end **22a** of the groove **22** relative to the seal portion **24a** and that is configured for receiving the force. For example, in an embodiment, application of a force against the circumferential seal element **24** at or near the first end **22a** of the groove **22** causes the seal engagement portion **24b** to move transversely within the groove **22** and, via the curvature **22c**, impart radial expansion of the seal portion **24a** of the circumferential seal element **24**.

[0098] In an embodiment, the circumferential seal element **24** is a single unit comprising the seal portion **24a** and the seal engagement portion **24b** (see e.g. **FIG. 5**). In an embodiment, the single unit is a monolithic structure. By “monolithic structure”, it is meant that the circumferential seal element **24**, including the seal engagement portion **24b** and the seal

portion **24a**, is made or formed from a single piece of material. In other embodiments, the seal engagement portion **24b** and the seal portion **24a** may be made from different pieces of material and then fused or adhered together to form the single unit.

[0099] In another embodiment, the circumferential seal element **24** is made or comprised of two or more separate and distinct units. In an embodiment, the units may be positioned adjacent to each other within the groove **22** to form the circumferential seal element **24**. For example, in an embodiment, the seal portion **24a** and the seal engagement portion **24b** are formed from more than one piece of material (see e.g. **FIG. 6**). In such embodiments, the seal portion **24a** and the seal engagement portion **24b** may be made from the same or a different type of material. In alternate embodiments, the separate and distinct units of the circumferential seal element **24** may be dimensioned to contain a medium **25** therebetween (see e.g. **FIG. 7**). For example, seal engagement portion **24b** and the seal portion **24a** may be separated by a medium **25** within the groove, whereby the force acting upon the seal engagement portion **24b** is transferred to the seal portion **24a** via the medium to impart radial expansion of the seal portion **24a**. The medium may be any suitable shape-conforming medium such as, but not limited to, a fluid or grains/beads of material.

[00100] The circumferential seal element **24**, including the seal portion **24a** and the seal engagement portion **24b**, may be made of any suitable material that permits sealing engagement against the wall of the pipe. In an embodiment, the circumferential seal element **24** may be comprised of an elastomer or a thermoplastic. More particularly, the circumferential seal element **24** may be comprised of a natural rubber, synthetic rubber, urethane, polyurethane, or an equivalent material thereto. By an "equivalent material thereto", it is meant any material having similar functional properties to natural rubber, synthetic rubber, urethane, or polyurethane in respect of elasticity, hardness and permeability. In an embodiment, the circumferential seal element **24** may be comprised of a soft metal. In an embodiment, the circumferential seal element **24** may be comprised of silicone.

[00101] The circumferential seal element **24** may be comprised of a material of any suitable hardness and/or elasticity. In an embodiment, the circumferential seal element **24** is comprised of a material having a Scale D Shore Durometer hardness of at least 80°Sh. In an embodiment, the material has a Scale A Shore Durometer of between about 80°Sh and about 100°Sh. If such a material is to be used, it must be highly resistant to being permanently

deformed elastically. Minimally, in embodiments disclosed herein, the modulus of elasticity (Young's modulus) value may be at least 10 GPa. More preferably, the modulus of elasticity may be at least 50 GPa. In an embodiment, the modulus of elasticity may be between about 100 GPa and about 500 GPa.

[00102] In an embodiment, the circumferential seal element **24** is comprised of urethane or polyurethane. In a particular embodiment, the circumferential seal element **24** is comprised of polyurethane 90A.

[00103] In certain embodiments, the seal engagement portion **24b** may be comprised of a material of different hardness than the seal portion **24a**. In a preferred embodiment, the seal engagement portion **24b** may be comprised of a material of greater hardness than the seal portion **24a**. In certain embodiments, the seal engagement portion **24b** may be comprised of a material having a higher modulus of elasticity value than that of the seal portion **24a**. In an embodiment, the seal engagement portion **24b** may comprise a metal or a metallic alloy material at a region or surface that is contacted by the force that is applied when the head unit is activated to sealingly engage the pipe.

[00104] In an embodiment, the seal engagement **24b** portion and seal portion **24a** of the circumferential seal element **24** are dimensioned to contact each other within the curvature **22c** of the groove **22** to impart radial expansion of the seal portion **24a**. For example, if the circumferential seal element **24** is a single unit comprised of a seal portion **24a** and a seal engagement portion **24b** of different materials, these materials may interconnect within a region spanning the curvature **22c**. If the seal portion **24a** and the seal engagement portion **24b** are separate units, they may be positioned adjacent to each other within the groove **22** to form the circumferential seal element **24**. Irrespective of the configuration, in such embodiments, the force acts on the seal engagement portion **24b**, directly or indirectly, such that the seal engagement portion **24b** transfers the force to the seal portion **24a** to effect radial expansion of the seal portion **24a** directly or indirectly.

[00105] As will be understood, when the circumferential seal element **24** is a single unit and the seal portion **24a** and seal engagement portion **24b** are comprised of the same materials, reference to these as different portions (seal versus engagement) is largely a functional distinction, as opposed to a structural distinction.

[00106] In an embodiment, the circumferential seal element **24** may comprise an anti-extrusion device or component. In an embodiment, the circumferential seal element **24** may comprise a spring (not shown) at or near the end which, upon activation, sealingly engages the wall of the pipe. The spring may be of any suitable diameter, shape, wire thickness and material. In an embodiment, the shape of the spring is round, square or oval. In an embodiment, the spring is made of metal or a metallic alloy. The spring may itself form a ring within the circumferential seal element **24**, going around the circumferential seal element **24** at or near the end which, upon activation, sealingly engages the wall of the pipe. Alternatively, smaller pieces of spring may be appropriately positioned within the seal portion **24a** of the circumferential seal element **24**. The circumferential seal element **24** may include any number of springs in any number of different positions.

[00107] In an embodiment, the spring is a circular spring positioned within the circumferential seal element **24** in co-axial arrangement with the pipe when the head unit **20** is located within the pipe. In an embodiment, the diameter of the spring is larger than the gap formed between the head unit **20** and the wall of a pipe when the head unit **20** is located within the pipe. In this manner, the spring cannot easily be pushed into the gap and the spring will provide additional resistance to the pressures within the pipeline to aid in maintaining a strong sealing engagement by the circumferential seal element **24** against the pipe. Thus, one function of the spring is to prevent the outer region of the circumferential seal element **24** from deforming in a direction parallel to the pipe wall. Additionally, the spring may aid in retracting the seal portion **24a** of the circumferential seal element **24** back into the head unit **20** upon deactivation.

[00108] In an embodiment, the spring is positioned within the circumferential seal element **24** such that when the head unit **20** is located in position within a pipe, the spring is at a downstream side of the circumferential seal element **24**. By “downstream side”, it is meant the side of the circumferential seal element **24** that is on the same side as the isolated section of pipe. In contrast, the “upstream side” refers to the side of the circumferential seal element **24** that is on the operational side of the pipeline where fluids and/or gas are to be sealed-off from the downstream isolation section. While orientation of the spring towards the downstream side may be preferred, the spring can be positioned in the upstream side, center or downstream side of the circumferential seal element **24**, or any combination thereof in embodiments with multiple springs.

[00109] The circumferential seal element **24** may be of any size or shape depending on, for example, the design of each respective groove, the design of the head unit, the inclusion and position of springs, the type of material, the size of the pipe to be sealed, and the conditions within the pipeline (e.g. operating pressures). The circumferential seal element **24** is of sufficient hardness and rigidity to withstand the operating pressures of the pipeline and maintain a sealing engagement with the wall of the pipe. Further, the circumferential seal element **24** is of sufficient resiliency such that it does not permanently deform.

[00110] In an embodiment, the circumferential seal element **24** conforms to the shape of the groove **22** at the second end **22b** of the groove **22**. By “conforms to the shape of the groove”, it is meant that the circumferential seal element **24** is shaped to conform with and/or be in contact with the walls of the groove **22** in the defined region (e.g. at the second end **22b**). In an embodiment, the circumferential seal element only conforms to the shape of the groove at the second end (see e.g. **FIG. 17A** and **17B**). In other embodiments, the circumferential seal element **24** conforms to the shape of the groove **22** over its entire distance within the groove **22** (see e.g. **FIG. 14**).

[00111] The circumferential seal element **24** is configured within the groove **22** such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove. In an embodiment, the force is a fluid force, a mechanical force, or a combination thereof. The fluid force may be provided by any fluid medium, including a liquid or a gas.

[00112] As used herein, the term “force” is intended to refer to an interaction that, when unopposed, will change the motion of an object, the position of an object, or both (the object being, for example, the circumferential seal element **24** and/or a piston **30** as described herein).

[00113] As above, the force may comprise or be a fluid force. In such embodiments, to supply force to the circumferential seal element **24**, the head unit **20** may comprise a fluid conduit **26** in fluid communication with the first end **22a** of the at least one groove **22**. By “fluid communication” it is meant that a fluid (e.g. a liquid and/or a gas) is able to pass through the fluid conduit **26** and be delivered at or near the first end **22a** of the groove **22**, for example from the surface. The fluid conduit may be any passageway capable of transferring a fluid or gas, such as for example a tubing or a channel (e.g. a drilled-out channel in a component of

the head unit **20**). In an embodiment, the fluid conduit **26** of the head unit forms only a portion of the entire passageway from the source of the fluid medium to the first end **22a** of the groove **22**. For example, the carrier unit and/or arm assembly (as described elsewhere herein) may also comprise a fluid conduit in fluid communication with the fluid conduit **26** of the head unit **20**. Furthermore, depending on the configuration of the head unit **20**, the fluid conduit **26** within the head unit may comprise any number of different conduits, such as shown in **FIG. 2** as **26a**, **26b** and **26c**.

[00114] The fluid conduit **26** is configured for delivering a fluid medium to provide a fluid force at or near the first end **22a** of the groove **22** to impart radial expansion of the circumferential seal element at the second end **22b**.

[00115] In embodiments in which the head unit **20** comprises a single groove **22**, one configuration is for the head unit **20** to comprise a single fluid conduit **26** in fluid communication with the first end **22a** of the groove **22**. However, alternate embodiments may involve configurations in which more than one fluid conduit **26** is in fluid communication with the first end **22a** of the groove **22**.

[00116] In embodiments in which the head unit **20** comprises more than one groove (e.g. two grooves), one configuration is for the head unit **20** to comprise a separate fluid conduit **26** for each groove, such as shown in **FIGs. 2** and **12-14**. In this configuration, each of the circumferential seal elements **24** can be activated/deactivated independently of each other. However, alternate embodiments may involve configurations in which more than one fluid conduit **26** is in fluid communication with each of the grooves **22**, or configurations in which a single fluid conduit **26a** (e.g. within the core **40**) is in fluid communication with both fluid conduits **26c** (e.g. within the internal member **50**) that are in fluid communication with the first end **22a** of each respective groove **22**.

[00117] Irrespective of the configuration, the force provided via the fluid conduit **26** acts on the circumferential seal element **24** (e.g. at the seal engagement portion **24b**), either directly or indirectly, to effect a radial expansion of the seal portion **24a** for sealing engagement against the wall of the pipe. In an embodiment, the force may be applied directly to the seal engagement portion **24b** at or near the first end **22a** of the groove **22** without any intervening component being present. Alternatively, in other embodiments, the force may be applied indirectly to the seal engagement portion **24b** via an intervening component, for example and

without limitation a piston **30** disposed within the groove **22** between a port of opening of the fluid conduit **26** and the circumferential seal element **24**. In such embodiments, the force causes the intervening component (e.g. piston **30**) to contact the seal engagement portion **24b** and thereby radially expand the seal portion **24a**.

[00118] In an embodiment, the piston **30** is a circumferential ring comprised of a metal or a metallic alloy. The metal may be, for example and without limitation, iron, copper, aluminum, nickel, titanium or magnesium, and the metallic alloy may be an alloy of these metals, such as steel. In an embodiment, the piston **30** is made of steel. The steel may be conventional steel or high tensile steel. In an embodiment, the piston comprises an O-ring around its outer surface to aid in blocking the fluid medium from passing to the other side.

[00119] Since the seal portion **24a** is entirely or largely disposed within groove **22** in the deactivated state, radial expansion upon activation is in the outward direction causing the seal portion **24a** to engage the wall of the pipe **200**. In embodiments where the groove **22** narrows at the second end **22b**, radial expansion of the seal portion **24a** may further include an extrusion-type event at the second end **22b** of the groove **22**. In an embodiment, the amount of radial expansion is between about 0.1 inches and about 1 inch. In an embodiment, the amount of radial expansion is about 0.1 inches, about 0.2 inches, about 0.3 inches, about 0.4 inches, about 0.5 inches, about 0.6 inches, about 0.7 inches, about 0.8 inches, about 0.9 inches, or about 1 inch. By “amount of radial expansion”, it is meant to refer to how much the seal portion **24a** extends or expands radially in each direction to engage with the pipe **200**.

[00120] As will be understood, even in the deactivated state a portion of the seal portion **24a** of the circumferential seal element **24** may extend out of the second end **22b** of the groove **22**. However, upon activation, the seal portion **24a** is caused to extend or expand outwardly even further.

[00121] In an embodiment, the circumferential seal member **24** may be maintained in the activated state by continuous application of force via the fluid conduit **26**. In another embodiment, the head unit **20** may further comprise a locking mechanism (not shown) for releasably locking the piston **30** in an activated position or at various different positions during seal activation or deactivation. When locked in an activated position, the locking mechanism can maintain the circumferential seal member **24** in the activated state. When the locking mechanism is engaged in the activated position, the force from the fluid conduit **26** may be

removed without disrupting the sealing engagement of the circumferential seal member **24** with the wall of the pipe **200**. The locking mechanism may be deactivated at a desired time, for example and without limitation by re-applying force to the piston to release the locking mechanism and restore the piston **30** to a deactivated position. The locking mechanism may be any suitable mechanism for releasable locking the piston **30** in place including, but not limited to, a pin, serrated teeth, split rings, or an outward contact force. In an embodiment, the radial expansion of the circumferential seal element **24** at the seal portion **24a** is reversible upon release of the locking mechanism. An exemplary locking mechanism of the present disclosure is described elsewhere herein.

[00122] In an embodiment, the force is provided by a hydraulic fluid. Non-limiting examples of hydraulic fluids include petroleum-based or mineral-based fluids, water-based fluids, and synthetic fluids. In an embodiment, the hydraulic fluid is aqueous. In an embodiment, the hydraulic fluid is an oil. The fluid conduit **26** may also be used to deliver other fluids and gases to the head unit **20**, such as a cleaning solution to clean the circumferential seal element **24** after its activation and prepare the circumferential seal element for re-use. In an embodiment, the force is provided by a suitable gas, such as, but not limited to nitrogen or oxygen (e.g. air). In an embodiment, the radial expansion of the circumferential seal element **24** is reversible upon release of the fluid force. In an embodiment, radial expansion at the seal portion **24a** of the circumferential seal element **24** of each of two grooves is independently activated by separate fluid conduits **26**.

[00123] In an embodiment, the head unit **20** comprises a core **40** having a fluid channel **42** (also **26a** in **FIG. 2**), the fluid channel **42** forming at least a portion of the fluid conduit **26** (**FIG. 8**). As used herein, the term “fluid channel” is intended to refer to a passageway within the solid material of the core or other component, and configured to allow a fluid (e.g. a liquid, a gas, or both) to pass through. In an embodiment, the fluid channel **42** is operatively connected to a tubing or other supply line that runs from the source of the fluid medium to the head unit **20** where there is fluid communication with the fluid conduit **26**. Typically, the source of the fluid medium will be external to the line stopping tool **10**. Thus, in some embodiments, an external supply line is part of the fluid conduit **26** described herein. In an embodiment, the fluid channel **42** may be a continuous channel in the material of the core **40** formed by any means available in the art, including cutting, grinding, drilling, casting from molten metal (e.g. melting and pouring into a mold), etching, machining, or any combination thereof. In an

embodiment, rather than a fluid channel **42**, the core comprises a tubing as a fluid conduit, for example that runs through a cavity in the core **40**. In an embodiment, the tubing is a braided or non-braided tubing, or any combination thereof. The fluid conduit **26a** whether it be a fluid channel **42** or a tubing, may be of any suitable shape and may include any number of fittings, connectors and tubing/channels.

[00124] In an embodiment, the core **40** comprises a rod-shape oriented parallel to the pipe when the head unit **20** is located within the pipe, such as shown in **FIG. 14**. In an embodiment, a portion of the groove **22**, spanning from the first end **22a** to the curvature **22c**, is perpendicular to the core (as shown in **FIGs. 2** and **14**). In an embodiment, a portion of the groove **22**, spanning from the first end **22a** to the curvature **22c**, is oriented at an angle with respect to the core.

[00125] An advantageous aspect of the isolation tool of the present disclosure is that each circumferential seal element **24** in the head unit **20** can be activated and deactivated separately. In such embodiments, the core **40** may include separate fluid channels **42** (**42a** and **42b** in **FIG. 14**) to provide a force at the first end **22a** of each of the grooves **22**. As shown in **FIG. 14**, each of the fluid channel **42a** and the fluid channel **42b** can use separate and independent passageways in core **40**. Moreover, in embodiments where the fluid medium is provided by a hydraulic system, each of fluid channel **42a** and fluid channel **42b** may use separate hydraulic systems.

[00126] In an embodiment, the head unit **20** comprises an internal member **50** defining a bore **52** to receive the core **40**. In an embodiment, the exterior wall of the internal member may define the lower wall **22d** of the groove (**FIGs. 2** and **9**). In an embodiment, the internal member **50** is comprised of metal or a metallic alloy as described elsewhere herein. In an embodiment, the internal member **50** is comprised of high tensile steel such as for example American Iron and Steel Institute (AISI) 4140 steel. In an embodiment, the internal member **50** is of any suitable shape to receive the core **40**, and may additionally be of suitable shape to define the lower wall **22d** of the groove. In an embodiment, the bore defined by the internal member is cylindrical.

[00127] As shown in **FIG. 9C**, the internal member may comprise a bleed conduit **72**. The bleed conduit **72** may open to the exterior of the head unit at a bleed port **70**. As described elsewhere herein, the bleed conduit **72** can continuously bleed substances (e.g. fluid, gas, or

both) from the exterior space between two circumferential seal elements **24** to the surface, and as well may be used for monitoring the functional of the line-stopping tool. In embodiments where the head unit comprises core **40**, the core **40** may comprise a bleed channel **74** as a portion or component of a continuous bleed conduit **72**.

[00128] In an embodiment, as shown in **FIG. 2** and **9C**, the internal member may also comprise a fluid channel **44** that forms at least a portion of the fluid conduit **26** (**FIG. 8**). In an embodiment, fluid channel **44** may provide a fluid communication between fluid channel **42** (e.g. **42a** or **42b**) in the core **40** and the first end **22a** of the groove **22**.

[00129] In an embodiment, the head unit **20** comprises a casing **60** having a hole **61** to receive the core. In an embodiment, the casing **60** may comprise two separate parts, namely a first end **60a** to be positioned at an upstream end of the head unit **20** and second end **60b** to be positioned at a downstream end of the head unit (**FIGs. 2** and **10**). In an embodiment, the interior walls of the casing may define an upper wall **22e** and an end wall **22f** at the first end **22a** of the groove **22**. In an embodiment, the casing **60** is comprised of a metal or metallic alloy as described elsewhere herein. In an embodiment, the casing is comprised of mild steel (i.e. a ferrous metal comprising iron and carbon) or alloy steel. For ease in positioning the head unit **20** within a pipe **200**, a preferred shape for the casing **60** may be a spherical shape or a cylindrical shape. Therefore, in an embodiment, the first end **60a** and the second end **60b** come together to form the desired shape of the head unit **20**.

[00130] In an embodiment, as shown in **FIG. 2** and **10B**, the internal wall of the casing may include a recess **46** that forms a portion of the fluid conduit **26**. In an embodiment, recess **46** may provide a fluid communication between fluid channel **44** in the internal member **50** and the first end **22a** of the groove **22**.

[00131] As the skilled person will appreciate from the above, in operation the fluid conduit **26** forms a continuous passageway from the source of the fluid medium to the first end **22a** of the groove **22**. Because of this arrangement, a fluid medium may pass from the source of the fluid medium to the first end **22a** of the groove **22**. Here, the fluid medium can accumulate, creating a force (e.g. a pressure) at the first end **22a** that acts on the seal engagement portion **24b** of the circumferential seal element **24**, directly or indirectly, and imparts movement thereto that, through curvature **22c**, translates to a radial expansion of the seal portion **24a**. In the radially expanded position, the seal portion **24a** can engage the wall of the pipe **200**.

[00132] In some embodiments, in addition to or instead of a fluid force, a mechanical force may be employed to actuate the circumferential seal element **24**. The mechanical force may be of any suitable construction, such as for example a mechanically actuated piston. In embodiments employing a mechanical force, the head unit **20** may comprise any of the components described herein in respect of a head unit **20** that employs a fluid force (e.g. a core, internal member, casing, etc.). Modifications to each component to supply the force by mechanical force instead of or in addition to fluid force, would be well understood by the skilled person having regard to the disclosure herein as a whole.

[00133] As such, the head unit **20** may be configured in any suitable arrangement to supply the mechanical force. In an embodiment, the head unit **20** comprises a piston disposed within the groove **22** and actuated by a rod to provide the mechanical force. In another embodiment, the head unit **20** may comprise a threaded ring **27** disposed within the at least one groove **22**, wherein the threaded ring **27** travels on the threads **29** within the groove **22** to shift the circumferential seal element **24** between an activated and deactivated state (see e.g. **FIGs. 5-7**). The piston or threaded ring may be comprised of any suitable material, including those described elsewhere herein. In an embodiment, the piston and/or threaded ring are comprised of metal or a metallic alloy. The skilled person will appreciate that other means of supplying the mechanical force may also be used. Similar to as described for a fluid force, the head unit **20** may comprise a locking mechanism for releasably locking the mechanical means of force (e.g. piston or threaded ring) in an activated position or in any other position during seal activation or deactivation.

[00134] The line-stopping tool **10** of the present disclosure does not require pipeline pressure to activate the seal. Moreover, as described elsewhere herein, control systems for the line-stopping tool **10** of the present disclosure allow for continued monitoring of the seal engagement, hydraulic pressure, upstream pipeline pressure, and downstream isolation pressure, and also allow for continuous bleed and bleed monitoring, as well as performing a downstream purge. Moreover, because of the design of the seals and the accumulation and maintenance of fluid medium within the first end **22a** of the groove **22**, advantageous properties are achieved, such as the avoidance of floating because the seal is always centered in the pipe due to even distribution of the radial expansion around the circumference of the head unit.

[00135] Other advantages still include the ability to provide a DIB line-stopping tool by including two grooves **22** with independently activated circumferential seal elements **24** disposed therein. In embodiments of a DIB line-stopping tool, the head unit **20** further comprises a bleed port **70** (for example as shown in **FIG. 2**) open to the exterior of the head unit **20** between the two grooves. The bleed port **70** is configured in fluid communication with a bleed conduit **72** within the head unit **20**. In an embodiment, the bleed port **70** can continuously bleed substances (e.g. fluid, gas, or both) from the interior space within the pipe between the circumferential seal elements **24**. In operation, the bleed port **70** may be left open and monitored for flow. In alternative embodiments, the pressure within the interior space of the pipe between the circumferential seal elements **24** may be monitored. A sudden spike in pressure may be indicative of a seal leak and the bleed port **70** and bleed conduit **72** may be used to bleed pressure and/or fluid. In an embodiment, this process could be automated such that if the system detects a spike in pressure, a release valve is opened to bleed the pressure and/or fluids. Alternatively, the process could be manual requiring the physical interaction of an operator. Depending on the product within the pipeline, the bleed could be vented or drained to a reservoir or to ambient.

[00136] In an embodiment, the head unit **20** may further comprise a wheel assembly **80**. **FIG. 16** shows an exemplary embodiment of an isolation tool (e.g. line-stopping tool **10**) of the present disclosure comprising a wheel assembly **80**. In an embodiment, the wheel assembly **80** may be used to guide the head unit **20** in the pipe **200**. In an embodiment, the wheel assembly **80** comprises a chassis **82** and one or more wheels **84**, each wheel attached to the chassis **82** by an axle **86**. The chassis **82** is of a suitable shape to allow the head unit **20** to rotate into position inside the pipe **200**, including under no flow service conditions. The wheels **84** can prevent the line-stopping tool **10** from rubbing on the wall of the pipe **200** during positioning, and help the head unit **20** rotate into position inside the pipe, particularly under no flow service conditions. Other wheel assembly structures may also be employed and would be known to the skilled person.

[00137] In an embodiment, the line-stopping tool **10** further comprises a carrier unit **100** having a pivotal connection **102** to the head unit **20** (**FIG. 12**). A purpose of the carrier unit **100** is to connect the line-stopping tool **10** to an apparatus for moving the tool into and out of the pipe. In an embodiment, the apparatus for moving the tool is a ram. In a more particular embodiment, the apparatus is a hydraulic cylinder ram. The body of the carrier unit **100** is of a

design to resist and transfer service loads and protect fluid conduit components. In an embodiment, at least part of the fluid conduit components are housed within and pass through an internal bore of the carrier unit **100**.

[00138] In an embodiment, the pivotal connection **102** is positioned to provide a zero moment on the base **104**. By “zero moment” it is meant that there is no rotation about a point of an axis. At least one advantage of having a zero moment on the base **104** is that the base **104** will not rotate, translate, or shift under high pressure. In an embodiment, the carrier unit **100** is pivotally connected to an arm assembly **110** that is connected to the head unit **20**. A purpose and function of the arm assembly **110** is to connect the head unit **20** to the carrier unit **100** in a configuration to resist and transfer service loads. The arm assembly **110** may be of any suitable design to allow for pivotal positioning of the head unit **20** into the pipe **200** in relation to the carrier unit **100**. In an embodiment, the arm assembly **110** has a smaller girth than the head unit **20** to more readily permit pivotal movement of the head unit **20** into the pipe **200**. By “smaller girth”, it is meant that the perimeter of the arm assembly **110** around its longitudinal axis is smaller than the perimeter of the head unit **20** around its longitudinal axis. In an embodiment, the girth of the arm assembly **110** is smaller at the end that connects to the carrier unit **100** than at the end that connects to the head unit **20**. This design aids in making a 90° corner to position the head unit **20** within the pipe **200**.

[00139] In an embodiment, the arm assembly **110** is a single piece and may be threaded onto the head unit **20**. In another embodiment, the arm assembly **110** is comprised of two separate longitudinal halves. This design may be advantageous for several reasons. For one, being comprised of two halves makes for easy attachment of the arm assembly **110** onto the core **40** of head unit **20** and onto the carrier unit **100** via a pivot pin that passes through respective holes on each half of the arm assembly **110**. The skilled person will appreciate that other pivot means are available and could be used in place of a pivot pin. The purpose of the pivot means is to secure the carrier unit **100** to the head unit **20**, resist and transfer service loads, and allow the head unit **20** to rotate relative to the carrier unit **100**. Other pivot or rotational means that provide these purposes may alternatively be used. For another, being comprised of two halves allows for easy installation within the arm assembly **110** of fluid conduit components, if desired. In this regard, in an embodiment, the arm assembly **110** may comprise an access panel on its external surface with connectors in fluid communication with the fluid conduit components within the arm assembly **110** and head unit **20**. The connectors

may, for example be female connectors to receive male connectors from the fluid conduit components of the carrier unit **100**, or vice versa.

[00140] In a further embodiment, the line-stopping tool **10** of the present disclosure may include one or more magnets on or within the head unit **20**. The function of the magnets is to capture metal filings and/or debris from the hot-tap procedure. In an embodiment, the magnets may be positioned on opposing ends. Other means of capturing debris from in front of the head unit **20** or sweeping debris out of the sealing zone via bristles may also be used. The head unit **20** of the line-stopping tool is typically narrow to allow for easier bypass capability upon insertion into a pipe, so debris should also be reduced.

[00141] The line-stopping tool **10** of the present disclosure may comprise only one circumferential seal element **24** or may comprise one or more circumferential seal elements **24** alone or in combination with another type of seal, on one or more head assemblies.

[00142] Referring to **FIGs. 11-16**, there is shown a line-stopping tool **10** according to an embodiment of the present disclosure. The embodiment in **FIGs. 11-16** comprises two grooves **22** on the head unit **20**, with a circumferential seal element **24** disposed within each groove, as disclosed herein.

[00143] In each of **FIGs. 11-14**, the line-stopping tool **10** is shown prior to activation, whereas in **FIG. 15** the circumferential seal elements **24** have been activated. By "activated", it is meant that the seal portions **24a** are in a radially expanded state to engage the walls of the pipe. Prior to activation, the seal portions **24a** are in a retracted state. As shown in **FIGs. 11-15**, the line-stopping tool **10** has a head unit **20**, a carrier unit **100**, and an arm assembly **110**. **FIG. 12** provides an internal view of an embodiment of a line-stopping tool **10** showing the various fluid conduits (or fluid channels) as described elsewhere herein.

[00144] In another embodiment, the present disclosure provides a locking mechanism. The locking mechanism may be used with the line-stopping tool **10** of the present disclosure, other line-stopping tools, or other tools generally.

[00145] Referring to **FIG. 21**, a dissected view of an exemplary locking mechanism **90** is shown. Locking mechanism **90** includes a piston **30** having teeth or ridges around the inner circumference. As described elsewhere herein, a piston **30** may be used to engage the

circumferential seal element **24** into the activated state. In other embodiments, the circumferential seal element **24** may itself comprise the teeth or ridges, and a piston **30** may or may not be present. The teeth or ridges on piston **30** provide a surface onto which other components of the locking mechanism **90** may engage to lock the circumferential seal element **24** in the activated state.

[00146] Locking mechanism **90** further comprises a circumferential cartridge **91** around which are provided a number of dogs **92**. In an embodiment, there may be 2, 3, 4, 5, or more dogs **92**. In a particular embodiment, there are four dogs **92** equally spaced around the circumferential cartridge **91** (see **FIG. 21**). In the embodiment of **FIG. 21**, the dogs **92** do not go around the entire circumference of the circumferential cartridge **91**, but rather there are gaps between each dog **92**. These gaps allow a space for an alignment component to pass between, such as for example a guide pin **93** and coil spring **94** extending from wall **91a** on the circumferential cartridge **91** to a release ring **95**. One end of the guide pin **93** may be received by a guide hole **91b** in wall **91a** of the circumferential cartridge **91**. A constant outwardly directed force may be applied to the dogs **92** by a biasing component, such as for example a leaf spring **96** positioned between each dog **92** and the circumferential cartridge **91**. The dogs **92** include outwardly oriented teeth or ridges **92a** capable of interacting with the corresponding teeth or ridges on the piston **30**, and thereby locking the piston **30** in position. The dogs **92** may also comprise a ramped contact surface **92b**.

[00147] To bias the dogs **92** to a retracted position, a force may be applied to an external surface **95a** of the release ring **95** to cause the release ring **95** to slide. On sliding movement, a ramped protrusion **95b** of the release ring **95** contacts the corresponding ramped contact surface **92b** on the dog **92** to retract the dog **92** against the force of the leaf spring **96** and thereby disengage the teeth or ridges **92a** from the piston **30**. Operation of locking mechanism **90** is further described below with reference to **FIGs. 22-24**.

[00148] Referring to **FIGs. 22A** and **22B**, as described elsewhere, in some embodiments the head unit **20** of the line-stopping tool **10** may comprise a casing **60** and an internal member **50**. For purposes of further describing locking mechanism **90**, **FIGs. 22A** and **22B** show a representation of these structures, together with the circumferential seal element **24** received therein. **FIGs. 22A** and **22B** are not intended to show a functional head unit **20**, but rather give context to the location and orientation of locking mechanism **90** shown in **FIG. 21**.

[00149] Turning now to **FIGs. 23 and 25-27**, a cross-sectional view along each of cross-sections E-E, F-F and G-G of **FIG. 22B** is shown when the circumferential seal element **24** is in an activated (i.e. radially expanded) state. Fluid conduit **26c** within the head unit **20** is hydraulically pressurized, which has caused piston **30** to translate right and thereby caused circumferential seal element **24** to extrude along the curvature **22c**. Coil spring **94** applies constant spring force to release ring **95** and keeps release ring **95** pushed to the right. Release conduit **98** is not pressurized. For locking the piston **30** in place, leaf spring **96** applies constant outward spring force on the dog **92**. The teeth on the piston **30** and the teeth **92a** on the dogs **92** are angled so that engagement only happens as the piston **30** slides left. As the piston **30** slides right, it causes the dog **92** to move down and up slightly because the teeth are sliding past each other. This results in piston **30** experiencing a “ratchet” effect. If unexpected pressure loss occurs in fluid conduit **26c**, then piston **30** would be locked by engagement of the teeth on the piston **30** with the teeth **92a** on the dogs **92**, with the dogs **92** ultimately keeping the circumferential seal element **24** activated (i.e. radially expanded).

[00150] Based on the material of which circumferential seal element **24** is made it does not want to remain extruded so it will apply constant force against piston **30** during extrusion. Piston **30** is locked in position when there is engagement of the teeth on the piston **30** with the teeth **92a** on the dogs **92**. This engagement can occur at a number of positions since piston **30** has more teeth than the teeth **92a** on the dogs **92** (e.g. to allow for the “ratcheting” effect).

[00151] Turning now to **FIGs. 24 and 28-30**, a cross-sectional view along each of cross-sections E-E, F-F and G-G of **FIG. 22B** is shown when the circumferential seal element **24** is in a de-activated (i.e. retracted or not radially expanded) state. To allow for de-activation of circumferential seal element **24**, release conduit **98** is pressurized which causes release ring **95** to overcome the spring force of coil spring **94** and slide toward the circumferential cartridge **91**. As the pressure acts on external surface **95a** of the release ring **95** to cause the release ring **95** to slide towards the circumferential cartridge **91**, the ramped protrusions **95b** push the dogs **92** down via the ramped contact surface **92b**. This allows the teeth **92a** of the dogs **92** to disengage from the teeth of the piston **30**. The pressure in fluid conduit **26c** is gradually released, thereby allowing piston **30** to slide back further into groove **22** and the circumferential seal element **24** to retract.

[00152] As will be described further below, methods of employing the line-stopping tool **10** of the present disclosure are also improved in comparison to other available tools, which are more complex and may not meet the full criteria of a DBB or DIB isolation system.

Methods

[00153] In another aspect, the present disclosure provides methods for isolating a section of a pipe or a vessel. By “isolating a section of pipe”, it is meant plugging or sealing off a section of pipe such that pipeline products (fluids, gases or other substances) are prevented from entering the isolated section. Similarly, by “isolating a section of a vessel” it is meant plugging or sealing off a section or portion of the vessel such that products are prevented from entering the isolated section. While the methods discussed herein are in the context of line-stopping applications, it will be appreciated that other applications are equally applicable.

[00154] In an embodiment, a section of pipe may be isolated from both sides by employing a line-stopping tool of the present disclosure at each end of the isolated section. This would involve two line-stops and, as discussed above, the pipeline payload could be transferred to an alternate (e.g. temporary) pipeline to bypass the isolated section. In another embodiment, the section of pipe may be isolated at only one end of the section of pipe, typically the side from which the pipeline products flow.

[00155] As used herein, “isolating” may be used interchangeably with “stopping”. Thus, reference herein to a “line-stopping tool” is equivalent to a “line-isolation tool”. Both terms mean a tool for plugging or sealing off a section of pipe.

[00156] Although the line-stopping tool **10** may be used for lengthy periods of time to isolate a section of pipe, the methods disclosed herein are typically for temporary isolation of a section of pipe, e.g. while maintenance or other activities are performed downstream of the line-stopping tool **10**. However, in some embodiments, the head unit **20** of the isolation tool disclosed herein could be disconnect from the launch equipment (e.g. carrier unit) and left in place for long periods of time or permanently.

[00157] In some embodiments herein, the methods of isolating a section of pipe involve inserting a head unit **20** of the line-stopping tool **10** as described herein into a pipe **200**, such as for example through an opening in a wall of the pipe. In an embodiment, the head unit **20**

comprises two of the circumferential seal elements **24**. In another embodiment, a different line-stopping tool may be used or adapted to use the head unit **20** as described herein. In an alternative embodiment, a different line-stopping tool may be used or adapted to use one or more circumferential seal elements **24** of the present disclosure.

[00158] In an embodiment, the method of isolating a section of a pipe or a vessel comprises the steps of: inserting a head unit of an isolation tool into a pipe or a vessel, the head unit comprising: (i) at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and (ii) a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; and providing a force at the first end of the at least one groove to impart radial expansion of the circumferential seal element at the second end to engage the circumferential seal element against the pipe or vessel and thereby isolate the section of the pipe or vessel.

[00159] In an embodiment, the line-stopping tool **10** is further defined as disclosed herein. In an embodiment, the at least one groove **22** is two grooves **22**, and the head unit **20** comprises a separate fluid conduit **26** in fluid communication with each of the two grooves. In an embodiment, the step of providing the force to impart radial expansion of each circumferential seal element of the two grooves is independent of the other. In other embodiments, the step of providing the force to impart radial expansion of each circumferential seal element of the two grooves is dependent on the other.

[00160] In an embodiment, the force is a mechanical force. In such embodiments, providing the mechanical force may comprise rotating a threaded ring disposed within the at least one groove to shift the circumferential seal element and impart the radial expansion. The skilled person will appreciate that other methods of providing the mechanical force may be used. In an embodiment, the at least one groove is two grooves. The mechanical force to impart radial expansion of each circumferential seal element of the two grooves may be independently imparted.

[00161] Line-stopping will now be described further with reference to **FIGs. 11-16**. In use, a line-stop is performed by any appropriate method by employing a line-stopping tool with a head unit **20** of the present disclosure, such as by a hot-tap or by connection through an existing branch.

[00162] A hot-tap may be performed as is well-known in the art. In an exemplary hot-tap procedure, an access connection **98** (e.g. flanged saddle) is fitted to a live pipe **200** (**FIG. 11**). A temporary valve and access pipe (not shown) may be bolted to the access connection **98**. The temporary valve prevents leakage from the live pipe after tapping (e.g. drilling) into the pipe. The tapping tool itself is likewise configured to prevent leakage during pipe cutting and upon removal the temporary valve is closed to complete the branch connection.

[00163] After the hot-tap, and referring to the embodiments shown in **Figs. 11-15**, line-stopping tool **10** approaches the access connection **98** (**FIG. 11**) travels downwardly through access connection **98** (**FIG. 12**) until the head unit **20** (or wheel assembly **90** connected thereto; not shown) contacts a bottom portion of the pipe **200** (**FIG. 13**). When traveling down the access pipe (not shown), the carrier unit **100** and head unit **20** are aligned substantially longitudinally with each other. The circumferential seal elements **24** are in a de-activated (i.e. retracted or not radially expanded) state. As the line-stopping tool **10** is advanced down the access pipe and through the access connection **98**, contact between the head unit **20** (or wheel assembly **90** connected thereto; not shown) and the wall of the pipe causes the head unit **20** to pivot about the carrier unit **100** (**Fig. 13**).

[00164] Downward transfer service (e.g. by a hydraulic cylinder ram) continues from above and soon the head unit is positioned within the pipe **200** (**FIG. 14**). Notably, the branch connection need not be at 90 degrees. It could be at an angle as well. The head unit **20** can be centered inside the pipe **200** using additional components and/or geometry, or the head unit **20** may simply be left resting on the inside wall of the pipe **200** at a slight angle.

[00165] With the head unit **20** positioned within the pipe **200**, the circumferential seal elements **24** may be activated by providing a force at or near the first end **22a** of each respective groove **22** via a fluid conduit **26**. In an embodiment, the force is provide by a fluid medium. In an embodiment, the fluid medium is a hydraulic fluid as described elsewhere herein. In a preferred embodiment, separate fluid conduits **26** communicate with each first end **22a** of a respective groove **22** such that each circumferential seal element **24** can be independently activated (**FIG. 14**). The delivery of the force causes movement of the circumferential seal element **24** within the groove and, through the curvature **22c**, the seal portion **24a** expands radially outwards to engage the wall of the pipe **200** (**Fig. 15**). In an embodiment, the carrier unit **100** transfers the pipeline pressure loads to the pipe and anchors itself without creating

any substantial additional loading. In an embodiment, the launch equipment can be disconnected and the carrier unit **100** would continue to hold the head unit **20** in position.

[00166] When the head unit comprises two or more circumferential seal elements **24**, the seals may be activated at the same time, sequentially or in an alternating pattern of partially activating one and then the other until each is fully activated. The skilled person will appreciate that any order and combination of steps may be used to activate the circumferential seal elements **24**. In an embodiment, the most upstream circumferential seal element **24** is activated first and after it has engaged the wall of the pipe **200**, a second downstream circumferential seal element **24** on the head unit **20** is activated. This order of activation may be preferred when the line-stopping tool **10** is positioned in an operational pipeline. In an alternate embodiment, both of the circumferential seal elements **24** are activated simultaneously to engage the seal portions **24a** thereof against the pipe **200**. This simultaneous mode of activation may be preferred in pipelines that are not operational when the line-stopping tool **10** is installed. In an alternate embodiment, the circumferential seal elements **24** are activated in a “walked-up” or “step-wise” fashion, meaning that each seal portion **24a** of a circumferential seal element **24** is radially expanded gradually, alternating between the seals with incremental increases in the delivery of force to each first end **22a** of the groove **22** at each step.

[00167] In the methods disclosed herein, the step of providing a force, such as for example a force provided by a fluid medium, may be repeated at any time for any one or more of the circumferential seal elements **24** in any order. This step may be performed to maintain the sealing engagement of the seal portion **24a** against the wall of the pipe **200** if an insufficient sealing engagement is observed at any time during operation of the line-stopping tool **10**. This step may also be performed if it is desired to de-activate and re-activate a circumferential seal element **24** at any time during operation. For instance, it may be desirable to move the line-stopping tool within the pipe **200** or to allow pipeline products to flow past the seal to test repairs on the downstream isolated section.

[00168] In an embodiment, the methods disclosed herein may further comprise a step of activating a locking mechanism within the head unit **20** to lock the circumferential seal element **24** in an activated state in which the seal portion **24a** of the circumferential seal element **24** is

sealingly engaged against the pipe. The locking mechanism may be the locking mechanism as described elsewhere herein.

[00169] As described elsewhere herein, the head unit **20** may comprise a bleed port **70** and a bleed conduit **72**. Thus, in further embodiments of the methods disclosed herein, the bleed port **70** and bleed conduit **72** may be used to bleed pressure and/or fluid from the interior space of the pipe between the circumferential seal elements **24**. This may be done for several reasons. Firstly, in the event of a seal failure and leak of pipeline products into the interior space between the seals, the bleed port **70** and bleed conduit **72** may be used to bleed the pipeline products and pressure therefrom. In such embodiments, the line-stopping tool **10** disclosed herein functions as a DBB or DIB line-stopping tool. Secondly, in some embodiments, it may be desirable to create a vacuum within the interior space by bleeding pressure therefrom.

[00170] It will be apparent to those skilled in the art that an embodiment of the line-stopping tool **10** of the present disclosure provides two bi-directional circumferential seal elements **24** within a single head unit **20** (e.g. DIB embodiments). By “bi-directional”, it is meant that pipeline pressures and fluids may be isolated from both directions within the pipe **200** without removing and re-inserting the isolation tool in the opposition orientation in the pipe **200**. This may serve to reduce operation time and cost involved with isolating a section of pipe.

[00171] While the term “upstream” has been used generally throughout to refer to the operational side of the site of isolation (i.e. the side where pipeline products would be present), it is possible that the line-stopping tool **10** of the present disclosure could be used in the alternate orientation. Likewise, the term “downstream” has been used to refer to the isolated side of the site of isolation, this side could likewise have pipeline products therein at any given time during operation.

[00172] It will also be apparent to those skilled in the art that while exemplary methods and steps have been described, the line-stopping tool **10** and circumferential seal elements **24** of the present application are of broad application in providing hot-tapping and subsequent line-stopping services, and the skilled person would appreciate other uses and methods for employing the line-stopping tools **10** and head unit **20** disclosed herein.

[00173] In an embodiment, the present disclosure provides a method of engaging a seal against a wall of a pipe wall or a vessel, the method comprising imparting a linear force within a fixed space and in an axial or tangential direction to a circumferential seal element, to impart radial expansion of the circumferential seal element via a curvature within the fixed space. In an embodiment, the fixed space is a groove. By "linear force" it is meant a force in a single direction or substantially in a single direction. By "axial or tangential direction" it is meant that the force is in a direction that is different from the plane of the radial expansion. In an embodiment, linear force is imparted perpendicular or substantially perpendicular to the plane of radial expansion. The groove may be a groove as described herein or any other suitable groove.

[00174] In the present disclosure, all terms referred to in singular form are meant to encompass plural forms of the same. Likewise, all terms referred to in plural form are meant to encompass singular forms of the same. Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosure pertains.

[00175] For the sake of brevity, only certain ranges are explicitly disclosed herein. However, ranges from any lower limit may be combined with any upper limit to recite a range not explicitly recited, as well as, ranges from any lower limit may be combined with any other lower limit to recite a range not explicitly recited, in the same way, ranges from any upper limit may be combined with any other upper limit to recite a range not explicitly recited. Additionally, whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range are specifically disclosed. In particular, every range of values (of the form, "from about a to about b," or, equivalently, "from approximately a to b," or, equivalently, "from approximately a-b") disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values even if not explicitly recited. Thus, every point or individual value may serve as its own lower or upper limit combined with any other point or individual value or any other lower or upper limit, to recite a range not explicitly recited.

[00176] Many obvious variations of the embodiments set out herein will suggest themselves to those skilled in the art in light of the present disclosure. Such obvious variations are within the scope of the appended claim.

Claims:

1. An isolation tool for isolating a section of a pipe or a vessel, the isolation tool comprising:

a head unit configured for location in a section of a pipe or a vessel, the head unit comprising:

- at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and

- a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature;

wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove, and

wherein each of the at least one groove is a fixed structure that remains the same shape and size during application of the force that imparts the radial expansion of the circumferential seal element.

2. The isolation tool of claim 1, wherein the circumference of the head unit is in coaxial alignment with the pipe or the vessel when the head unit is located within the pipe or the vessel in an activated state.

3. The isolation tool of claim 1 or 2, wherein the curvature of the at least one groove is a bend forming an angle between about 60 degrees and about 120 degrees.

4. The isolation tool of claim 1 or 2, wherein the curvature of the at least one groove is a bend forming an angle between about 80 degrees and about 100 degrees.

5. The isolation tool of claim 1 or 2, wherein the curvature of the at least one groove is a bend forming a 90 degree corner.

6. The isolation tool of claim 1 or 2, wherein the curvature of the at least one groove is a bend having an inner radius of curvature of between about 0.2 inches and about 0.5 inches; and an outer radius of curvature of between about 1.0 inches and 1.5 inches.
7. The isolation tool of any one of claims 1 to 6, wherein the at least one groove narrows at the second end.
8. The isolation tool of any one of claims 1 to 6, wherein the at least one groove has a uniform width from the first end to the second end.
9. The isolation tool of claim 8, wherein the uniform width is between 0.5 inches and 2.0 inches.
10. The isolation tool of claim 8, wherein the uniform width is between 0.5 inches and 1.0 inches.
11. The isolation tool of any one of claims 1 to 10, wherein each of the at least one groove further comprises two or more groove channels, each of the two or more groove channels extending a portion of the first end of the groove further within the head unit, and each of the two or groove channels spaced apart from each other.
12. The isolation tool of claim 11, wherein each of the two or more groove channels are spaced equidistant from each other.
13. The isolation tool of claim 11 or 12, wherein the force at or near the first end of the groove is from within the two or more groove channels.
14. The isolation tool of any one of claims 11 to 13, wherein a portion of the circumferential seal element extends within the two or more groove channels.
15. The isolation tool of any one of claims 1 to 14, wherein the circumferential seal element comprises a seal portion for engaging the pipe or the vessel upon activation.
16. The isolation tool of claim 15, wherein the seal portion is comprised of natural rubber, synthetic rubber, urethane, polyurethane, or an equivalent material thereto.

17. The isolation tool of claim 15 or 16, wherein the circumferential seal element further comprises a seal engagement portion for receiving the force, the seal engagement portion located proximal to the first end of the at least one groove relative to the seal portion.

18. The isolation tool of claim 17, wherein the seal engagement portion is comprised of a material of different hardness than the seal portion.

19. The isolation tool of claim 17 or 18, wherein the seal engagement portion and seal portion of the circumferential seal element are dimensioned to contact each other within the first end or the curvature of the at least one groove to impart radial expansion of the seal portion.

20. The isolation tool of claim 14, wherein the circumferential seal element comprises a seal portion for engaging the pipe or the vessel and a seal engagement portion for receiving the force, and wherein the seal engagement portion is disposed within the two or more groove channels.

21. The isolation tool of any one of claims 17 to 20, wherein the circumferential seal element is a single unit comprising the seal engagement portion and the seal portion.

22. The isolation tool of any one of claims 17 to 20, wherein the seal engagement portion and the seal portion are separate units positioned adjacent to each other to form the circumferential seal element.

23. The isolation tool of claims 17 to 20, wherein the seal engagement portion and seal portion of the circumferential seal element are dimensioned to contain a medium therebetween, wherein the force acting upon the seal engagement portion is transferred to the seal portion via the medium to impart radial expansion of the seal portion.

24. The isolation tool of claim 23, wherein the medium is a fluid.

25. The isolation tool of any one of claims 1 to 24, wherein the circumferential seal element conforms to the shape of the groove at the second end.

26. The isolation tool of claim 25, wherein the circumferential seal element conforms to the shape of the groove over the entire circumferential seal element disposed within the groove.

27. The isolation tool of any one of claims 1 to 26, wherein the at least one groove is two grooves.
28. The isolation tool of claim 27, which comprises a bleed port open to the exterior of the head unit between the two grooves, the bleed port in fluid communication with a bleed conduit within the head unit.
29. The isolation tool of claim 27 or 28, wherein radial expansion of the circumferential seal element of each of the two grooves is independently activated.
30. The isolation tool of any one of claims 1 to 29, wherein radial expansion of the circumferential seal element is reversible upon release of the force.
31. The isolation tool of any one of claims 1 to 30, wherein the head unit comprises a wheel assembly.
32. The isolation tool of any one of claims 1 to 31, further comprising a carrier unit having a pivotal connection to the head unit.
33. The isolation tool of claim 32, wherein the carrier unit is pivotally connected to an arm assembly that is connected to the head unit.
34. The isolation tool of claim 32 or 33, wherein the pivotal connection is positioned to provide a zero moment on the carrier unit.
35. The isolation tool of any one of claims 1 to 34, wherein the force is a fluid force.
36. The isolation tool of claim 35, wherein the head unit comprises a fluid conduit in fluid communication with the first end of the at least one groove and configured for providing the fluid force to impart radial expansion of the circumferential seal element at the second end.
37. The isolation tool of claim 36, wherein the head unit comprises a core having a fluid channel, the fluid channel forming at least a portion of the fluid conduit.
38. The isolation tool of claim 37, wherein a portion of the at least one groove, spanning from the first end to the curvature, is perpendicular to the core.

39. The isolation tool of any one of claims 36 to 38, wherein the head unit comprises a casing comprising a hole to receive the core, the casing defining an upper wall and an end wall at the first end of the groove.
40. The isolation tool of claim 39, wherein the core comprises a rod-shape oriented parallel to the pipe or the vessel when the head unit is located within the pipe or the vessel in an activated state.
41. The isolation tool of any one of claims 36 to 40, wherein the head unit comprises an internal member defining a bore to receive the core, the internal member defining a lower wall of the groove.
42. The isolation tool of any one of claims 1 to 34, wherein the force is a mechanical force.
43. The isolation tool of claim 42, wherein the head unit comprises a threaded ring disposed within the at least one groove, wherein the threaded ring travels on threads in the groove to shift the circumferential seal element between an activated and deactivated state.
44. The isolation tool of claim 42, wherein the head unit comprises a piston disposed within the groove and actuated by a rod to provide the mechanical force.
45. The isolation tool of any one of claims 36 to 41, wherein the head unit comprises a piston disposed within the at least one groove between the fluid conduit and the circumferential seal element.
46. The isolation tool of claim 44 or 45, wherein the piston is a circumferential ring comprised of a metal or a metallic alloy.
47. The isolation tool of any one of claims 44 to 46, wherein the head unit comprises a locking mechanism for releasably locking the piston in an activated position.
48. The isolation tool of claim 47, wherein radial expansion of the circumferential seal element is reversible upon release of the locking mechanism.

49. A method of isolating a section of a pipe or a vessel, the method comprising the steps of:

- inserting a head unit of an isolation tool into a pipe or a vessel, the head unit comprising:

(i) at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and

(ii) a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature; and

- providing a force at the first end of the at least one groove to impart radial expansion of the circumferential seal element at the second end to engage the circumferential seal element against the pipe or vessel and thereby isolate the section of the pipe or vessel,

wherein each of the at least one groove is a fixed structure that remains the same shape and size during application of the force that imparts the radial expansion of the circumferential seal element.

50. The method according to claim 49, wherein the isolation tool is as defined in any one of claims 2 to 48.

51. The method according to claim 50, wherein the head unit comprises a fluid conduit in fluid communication with the first end of the at least one groove and configured for providing a fluid force to impart radial expansion of the circumferential seal element at the second end.

52. The method according to claim 51, wherein the at least one groove is two grooves, and the head unit comprises a separate fluid conduit in fluid communication with each of the two grooves.

53. The method according to claim 52, wherein providing the fluid force to impart radial expansion of each circumferential seal element of the two grooves is independent of the other.

54. The method according to claim 49, wherein the force is a mechanical force.

55. The method according to claim 54, wherein providing the mechanical force comprises rotating a threaded ring disposed within the at least one groove to shift the circumferential seal element and impart the radial expansion.

56. The method according to claim 54 or 55, wherein the at least one groove is two grooves.

57. The method according to claim 56, wherein providing the mechanical force to impart radial expansion of each circumferential seal element of the two grooves is independent of the other.

58. The method according to any one of claims 50 to 57, further comprising activating a locking mechanism within the head unit to lock the circumferential seal element in an activated state in which the circumferential seal element is sealing engaged against the pipe.

59. A head unit for an isolation tool, the head unit comprising:

- at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween; and

- a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature;

wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove, and

wherein each of the at least one groove is a fixed structure that remains the same shape and size during application of the force that imparts the radial expansion of the circumferential seal element.

60. The head unit of claim 59, wherein the circumference is in coaxial alignment with a pipe when the head unit is located within the pipe.

61. The head unit of claim 59 or 60, comprising a fluid conduit in fluid communication with the first end of the at least one groove and configured for providing a fluid force to impart radial expansion of the circumferential seal element at the second end.

62. The head unit of claim 59 or 60, wherein the force is a mechanical force.

63. An isolation tool for isolating a section of a pipe or a vessel, the isolation tool comprising:

a head unit configured for location in a section of a pipe or a vessel, the head unit comprising:

- at least one groove around a circumference of the head unit, each of the at least one groove comprising a first end within the head unit, a second end open to the exterior of the head unit, and a curvature therebetween, the curvature being a bend formed by opposing and complementarily oriented walls of the groove, with one of the walls having a larger radius of curvature than the other to form the bend; and

- a circumferential seal element disposed within each of the at least one groove and spanning at least a portion of the curvature;

wherein the circumferential seal element is configured within the groove such that a force at or near the first end of the groove imparts radial expansion of the circumferential seal element at the second end of the groove via the curvature in the groove, and

wherein the circumferential seal element is slidably moved along or pushed through the curvature by the force to impart the radial expansion.

64. The isolation tool of claim 63, wherein the bend in the curvature of the at least one groove forms an angle between about 60 degrees and about 120 degrees.

65. The isolation tool of claim 63, wherein the bend in the curvature of the at least one groove forms an angle between about 80 degrees and about 100 degrees.

66. The isolation tool of claim 63, wherein the bend in the curvature of the at least one groove forms a 90 degree corner.

67. The isolation tool of claim 63, wherein the bend in the curvature of the at least one groove has an inner radius of curvature of between about 0.2 inches and about 0.5 inches; and an outer radius of curvature of between about 1.0 inches and 1.5 inches.
68. The isolation tool of any one of claims 63 to 67, wherein the at least one groove narrows at the second end.
69. The isolation tool of any one of claims 63 to 67, wherein the at least one groove has a uniform width from the first end to the second end.
70. The isolation tool of claim 69, wherein the uniform width is between 0.5 inches and 2.0 inches.
71. The isolation tool of claim 69, wherein the uniform width is between 0.5 inches and 1.0 inches.
72. The isolation tool of any one of claims 63 to 71, wherein the circumferential seal element comprises a seal portion for engaging the pipe or the vessel upon activation.
73. The isolation tool of claim 72, wherein the circumferential seal element further comprises a seal engagement portion for receiving the force, the seal engagement portion located proximal to the first end of the at least one groove relative to the seal portion.
74. The isolation tool of claim 73, wherein the seal engagement portion and seal portion of the circumferential seal element are dimensioned to contact each other within the first end or the curvature of the at least one groove to impart radial expansion of the seal portion.
75. The isolation tool of claim 73 or 74, wherein the circumferential seal element is a single unit comprising the seal engagement portion and the seal portion.
76. The isolation tool of claim 73 or 74, wherein the seal engagement portion and the seal portion are separate units positioned adjacent to each other to form the circumferential seal element.
77. The isolation tool of claim 73 or 74, wherein the seal engagement portion and seal portion of the circumferential seal element are dimensioned to contain a medium

therebetween, wherein the force acting upon the seal engagement portion is transferred to the seal portion via the medium to impart radial expansion of the seal portion.

78. The isolation tool of claim 77, wherein the medium is a fluid.

79. The isolation tool of any one of claims 63 to 78, wherein the circumferential seal element conforms to the shape of the groove at the second end.

80. The isolation tool of claim 79, wherein the circumferential seal element conforms to the shape of the groove over the entire circumferential seal element disposed within the groove.

81. The isolation tool of any one of claims 63 to 80, wherein the at least one groove is two grooves.

82. The isolation tool of claim 81, which comprises a bleed port open to the exterior of the head unit between the two grooves, the bleed port in fluid communication with a bleed conduit within the head unit.

83. The isolation tool of claim 81 or 82, wherein radial expansion of the circumferential seal element of each of the two grooves is independently activated.

84. The isolation tool of any one of claims 63 to 83, wherein radial expansion of the circumferential seal element is reversible upon release of the force.

85. The isolation tool of any one of claims 63 to 84, wherein the force is a fluid force.

86. The isolation tool of claim 85, wherein the head unit comprises a fluid conduit in fluid communication with the first end of the at least one groove and configured for providing the fluid force to impart radial expansion of the circumferential seal element at the second end.

87. The isolation tool of claim 86, wherein the head unit comprises a core having a fluid channel, the fluid channel forming at least a portion of the fluid conduit.

88. The isolation tool of claim 87, wherein a portion of the at least one groove, spanning from the first end to the curvature, is perpendicular to the core.

89. The isolation tool of any one of claims 86 to 88, wherein the head unit comprises a casing comprising a hole to receive the core, the casing defining an upper wall and an end wall at the first end of the groove.
90. The isolation tool of claim 89, wherein the core comprises a rod-shape oriented parallel to the pipe or the vessel when the head unit is located within the pipe or the vessel in an activated state.
91. The isolation tool of any one of claims 86 to 90, wherein the head unit comprises an internal member defining a bore to receive the core, the internal member defining a lower wall of the groove.
92. The isolation tool of any one of claims 63 to 84, wherein the force is a mechanical force.
93. The isolation tool of claim 92, wherein the head unit comprises a threaded ring disposed within the at least one groove, wherein the threaded ring travels on threads in the groove to shift the circumferential seal element between an activated and deactivated state.
94. The isolation tool of claim 92, wherein the head unit comprises a piston disposed within the groove and actuated by a rod to provide the mechanical force.
95. The isolation tool of any one of claims 86 to 91, wherein the head unit comprises a piston disposed within the at least one groove between the fluid conduit and the circumferential seal element.
96. The isolation tool of claim 94 or 95, wherein the piston is a circumferential ring comprised of a metal or a metallic alloy.
97. The isolation tool of any one of claims 94 to 96, wherein the head unit comprises a locking mechanism for releasably locking the piston in an activated position.
98. The isolation tool of claim 97, wherein radial expansion of the circumferential seal element is reversible upon release of the locking mechanism.

20




FIG. 1




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 18




FIG. 19A




FIG. 19B




FIG. 20




FIG. 21




FIG. 22A




FIG. 22B




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27





FIG. 28



F-F

FIG. 29




FIG. 30