



US 20040215177A1

(19) **United States**

(12) **Patent Application Publication**
Swanson

(10) **Pub. No.: US 2004/0215177 A1**

(43) **Pub. Date: Oct. 28, 2004**

(54) **THERAPEUTIC APPARATUS HAVING INSULATED REGION AT THE INSERTION AREA**

(21) Appl. No.: 10/423,627

(22) Filed: Apr. 24, 2003

(75) Inventor: **David K. Swanson**, Campbell, CA (US)

Publication Classification


Correspondence Address:
HENRICKS SLAVIN AND HOLMES LLP
SUITE 200
840 APOLLO STREET
EL SEGUNDO, CA 90245

(51) **Int. Cl.⁷** **A61B 18/18**
(52) **U.S. Cl.** **606/21**

(57) **ABSTRACT**

Apparatus and methods for insulating tissue during therapeutic procedures.

(73) Assignee: **Scimed Life Systems, Inc.**






FIG. 1




FIG. 3




FIG. 2

FIG. 4




FIG. 6




FIG. 7




FIG. 5




FIG. 8




FIG. 9







FIG. 10






FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21

THERAPEUTIC APPARATUS HAVING INSULATED REGION AT THE INSERTION AREA

BACKGROUND OF THE INVENTIONS

[0001] 1. Field of Inventions

[0002] The present inventions relate generally to devices for performing therapeutic operations on body tissue.

[0003] 2. Description of the Related Art

[0004] There are many instances where therapeutic elements must be positioned adjacent to body tissue. One instance involves the formation of therapeutic lesions to the treat cardiac conditions such as atrial fibrillation, atrial flutter and arrhythmia. Therapeutic lesions, which may also be used to treat conditions in other regions of the body such as the prostate, liver, brain, gall bladder, uterus and other solid organs, are typically formed by ablating tissue.

[0005] Cryogenic cooling devices are one example of the devices that have been used to form lesions in tissue. During the cryo-ablation of soft tissue (i.e. tissue other than blood, bone and connective tissue), ice crystals disrupt cell and organelle membranes and it is the disruption that kills the tissue. A cryogenic element, such as a balloon or hollow metal tip, is carried on the distal end of a catheter or surgical probe (referred to herein collectively as "probes"), placed in contact with tissue and cooled to a temperature that will cause tissue death. The cryogenic element may be cooled by a variety of techniques. One technique employs the Joule-Thompson ("JT") effect. Here, cryogenic cooling occurs as a result of a rapid decrease of gas pressure that occurs within the therapeutic element. Pressurized cryogenic fluid, such as liquid nitrous oxide, is directed into the therapeutic element where it undergoes rapid phase change and a rapid expansion of the gas from a high-pressure to a lower pressure state. The reaction is endothermic and produces temperatures as low as minus 70° C. at the therapeutic element. In some instances, the cryogenic fluid is pre-cooled in order to increase the cooling power delivered to the targeted tissue. The cryogenic element may also be cooled by directing super-cooled fluid through the catheter or surgical probe to the cryogenic element. Here, the temperature at the therapeutic element can be as low as minus 100° C. when it enters the patient.

[0006] The present inventor has determined that conventional cryogenic cooling devices are susceptible to improvement. For example, the present inventor has determined that conventional cryogenic cooling devices can damage tissue at the insertion area, i.e. the area at which the probe is inserted into the patient. In the context of cryogenic probes, which utilize the JT effect, the tissue in the insertion area may be damaged by the nitrous oxide as it returns to the proximal end of probe in its extremely cold gaseous state. Super-cooled fluid, on the other hand, is more likely to damage tissue in the insertion area as it enters the patient. The insertion area, and the tissue contained therein, will vary from procedure to procedure. In the context of cardiovascular therapies which require a catheter to be passed through the femoral vein to a chamber within the heart, for example, the insertion area would include the tissue between the outer surface of the patient's thigh and the femoral vein. With respect to surgical probes, conventional cryogenic cooling devices can damage tissue at the insertion area, i.e. the area

at which the probe is inserted into the patient, especially in minimally invasive procedures, in a manner similar to that observed with percutaneous catheter procedures. The proximal or mid-portion of the surgical cryogenic probes can also freeze soft tissues not intended to be ablated. For example, lung tissue can be unintentionally damaged when heart tissue is targeted. When liver tumors are targeted for cryo-ablation, the abdominal wall, spleen, pancreas or stomach could be injured.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Detailed description of preferred embodiments of the inventions will be made with reference to the accompanying drawings.

[0008] FIG. 1 is a plan view of a probe in accordance with a preferred embodiment of a present invention.

[0009] FIG. 2 is a section view taken along line A-A in FIG. 1 with the inflatable insulation device in a deflated state.

[0010] FIG. 3 is an enlarged, partial section view of a portion of the probe illustrated in FIG. 1.

[0011] FIG. 4 is a section view taken along line A-A in FIG. 1 with the inflatable insulation device in an inflated state.

[0012] FIG. 5 is a cutaway view showing the probe illustrated in FIG. 1 being inserted into the femoral vein in the thigh of a patient.

[0013] FIG. 6 is side view showing the distal portion of the probe illustrated in FIG. 1 adjacent to a pulmonary vein.

[0014] FIG. 7 is a section view take along line 7-7 in FIG. 5.

[0015] FIG. 8 a plan view of an introducer sheath in accordance with a preferred embodiment of a present invention in an inflated state.

[0016] FIG. 9 is a section view take along line 9-9 in FIG. 8.

[0017] FIG. 10 is an enlarged, partial section view of a portion of the introducer sheath illustrated in FIG. 8.

[0018] FIG. 11 is a plan view of a probe in accordance with a preferred embodiment of a present invention.

[0019] FIG. 12 is a section view taken along line 12-12 in FIG. 11.

[0020] FIG. 13 is an enlarged, partial section view of a portion of the probe illustrated in FIG. 11.

[0021] FIG. 14 is a front view of an introducer port in accordance with a preferred embodiment of a present invention.

[0022] FIG. 15 is a section view take along line 15-15 in FIG. 14.

[0023] FIG. 16 is a front view of an introducer port in accordance with a preferred embodiment of a present invention.

[0024] FIG. 17 is a section view take along line 17-17 in FIG. 16.

[0025] FIG. 18 is a front view of an introducer port in accordance with a preferred embodiment of a present invention.

[0026] FIG. 19 is a section view take along line 19-19 in FIG. 18.

[0027] FIG. 20 is a front view of a portion of a portion of trocar sleeve in accordance with a preferred embodiment of a present invention.

[0028] FIG. 21 is a section view of the portion of a trocar sleeve illustrated in FIG. 20.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0029] The following is a detailed description of the best presently known modes of carrying out the inventions. This description is not to be taken in a limiting sense, but is made merely for the purpose of illustrating the general principles of the inventions.

[0030] The detailed description of the preferred embodiments is organized as follows:

- [0031] I. Introduction
- [0032] II. Exemplary Insulated Catheter
- [0033] III. Exemplary Insulated Introducer Sheath
- [0034] IV. Exemplary Insulated Surgical Probe
- [0035] V. Exemplary Insulated Introducer Ports
- [0036] VI. Exemplary Trocars

[0037] The section titles and overall organization of the present detailed description are for the purpose of convenience only and are not intended to limit the present inventions.

[0038] I. Introduction

[0039] This specification discloses a number of structures, mainly in the context of cardiac treatment, because the structures are well suited for use with myocardial tissue. Nevertheless, it should be appreciated that the structures are applicable for use in therapies involving other types of soft tissue. For example, various aspects of the present inventions have applications in procedures concerning other regions of the body such as the prostate, liver, brain, gall bladder, uterus and other solid organs. The inventions herein are also applicable to catheter-based probes, surgical probes, introducer sheaths, introducer ports, trocars and other devices that may be inserted into the body. Additionally, although the preferred embodiments of the inventions are described in the context of cryogenic therapies, the inventions are not limited to cryogenic applications. Other applications where thermal insulation is required, such as devices that provide hyperthermic treatments for tumors, or devices that ablate tissue by thermal conduction from hot balloons, are also contemplated. Protection from hot circulating fluids is also required in devices that must be cooled to be safely operated within the body. One example of such a device is a laser ablation device.

[0040] Catheter-based probes used to create lesions typically include a relatively long and flexible catheter body that supports a cryogenic element at or near its distal end. The portion of the catheter body that is inserted into the patient

is typically from 60 to 140 cm in length and there may be another 20 to 40 cm, including a handle, outside the patient. The length and flexibility of the catheter body allow the catheter to be inserted into a main vein or artery (typically the femoral vein) and directed into the interior of the heart such that the cryogenic element contacts the tissue that is to be ablated. Fluoroscopic imaging is used to provide the physician with a visual indication of the location of the catheter.

[0041] Surgical probes, on the other hand, are configured such that the distal end of a surgical probe may be placed directly in contact with the targeted tissue area by a physician during a surgical procedure, such as open-heart surgery. Here, access may be obtained by way of a thoracotomy, median sternotomy, or thoracostomy. Exemplary surgical probes are disclosed in U.S. Pat. No. 6,142,994, which is incorporated herein by reference. Surgical probes preferably include a handle and a relatively short shaft that supports a cryogenic element at or near the distal end.

[0042] Introducer sheaths and introducer ports are used to introduce catheters and surgical probes into the body. Introducer sheaths have a relatively long body that may extend through the insertion area to the target tissue region, while introducer ports tend to be relatively short and extend only a short distance beyond the insertion area. Trocars are sharp instruments used to puncture a body cavity and are typically adapted to be used together with a obturator. Once the body cavity has been punctured by the obturator and trocar sleeve (sometimes referred to as a "cannula"), the obturator is removed from the trocar sleeve, thereby leaving the trocar sleeve extending into the body cavity. Surgical procedures are then performed through the trocar sleeve.

[0043] Catheters, surgical probes, introducer sheaths, introducer ports and trocars each have a "working length," which is the portion of the device that is inserted into the patient during a procedure, and a "non-working length," which is the portion of the device that remains outside the patient during the procedure. In other words, the non-working length is the portion of the device that will not enter the insertion area. The non-working lengths for catheter and sheath bodies are typically about 10 cm to about 50 cm, while the non-working length for a surgical probe shaft is typically about 10 cm to about 40 cm, and the non-working length for an introducer port is typically about 2 cm to about 10 cm and the non-working length for a trocar is typically about 1 cm to about 2 cm. The length of the insertion area will, of course, vary from procedure to procedure. In those instances where a catheter is inserted through the patient's thigh and into the femoral vein, the insertion area will typically be about 4 cm to about 15 cm in length, because the catheter is deployed at an acute angle. Alternatively, in those instances where a surgical probe is deployed in the directly into the chest by way of a mini-thoracotomy, the insertion area will typically be about 3 cm to about 10 cm in length.

[0044] The present apparatus and methods may be used to provide insulation between catheters and surgical probes and, at a minimum, the tissue in the insertion area. In some embodiments, the insulation is provided by an inflatable insulation device. There are a number of advantages associated with such apparatus and methods. For example, in those instances where a probe is used to transport extremely low temperature fluids to and/or from a cryogenic element,

the insulation will protect the tissue in the insertion area. The insulation may also be extended distally if desired in order to protect other tissue and/or improve the thermal efficiency of the overall cryogenic system.

[0045] II. Exemplary Insulated Catheter

[0046] A catheter 100 in accordance with a preferred embodiment of a present invention is illustrated in FIGS. 1-7. The illustrated embodiment includes an elongate catheter body 102 and an inflatable cryogenic element 104 carried on the distal portion 106 of the catheter body. The proximal portion 108 of the catheter body 102 is secured to a handle 110. The exemplary catheter 100 is a non-steerable catheter and is configured to be advanced over a guidewire 112 to the target location. More specifically, the catheter body 102 is provided with a guidewire lumen 114 and the handle 110 is provided with a guidewire port 116 and an internal guidewire lumen (not shown). Thus, once the distal end of the guidewire 112 has been positioned at the target tissue location, the catheter 100 may be advanced over the guidewire to the target tissue location.

[0047] In addition to the guidewire lumen 112, the exemplary catheter body 102 includes an infusion lumen 118 and a ventilation lumen 120. The distal ends of the infusion and ventilation lumens 118 and 120 terminate at respective openings (not shown) on the exterior surface of the catheter body that are located within the cryogenic element 104. The proximal ends of the infusion and ventilation lumens 118 and 120 are connected to infusion and ventilation lumen ports 122 and 124 on the handle 110. Suitable infusion and ventilation lumen ports usually includes high-pressure connectors that withstand pressures of at least 100 PSI. Depending on the type of cryogenic cooling that is desired, the infusion and ventilation lumens 118 and 120 may be used to supply and ventilate super-cooled fluid, such as liquid perfluorocarbon that has been cooled to a suitably low temperature such as minus 90° C., or to supply liquid nitrous oxide and ventilate the gas that results from the expansion within the cryogenic element 104. The gas is typically about minus 50° C. when it reaches the proximal end of the catheter body 102.

[0048] In order to protect non-target tissue generally, and the tissue associated with the insertion area in particular, the exemplary catheter 100 also includes an inflatable insulation device 126 that is carried on the exterior surface of the catheter body 102. The inflatable insulation device 126 preferably extends distally from a location in close proximity to the distal end of the handle 110, over the non-working length 128 of the catheter body and along at least the proximal area of the working length 130. This will insure that a portion of the inflatable insulation device 126 will be coextensive with the insertion area during use, as is described below with reference to FIG. 5. In the exemplary embodiment illustrated in FIGS. 1-7, the inflatable insulation device 126 extends from a location in close proximity to the handle 110 to a location in spaced relation to the inflatable cryogenic element 104.

[0049] As illustrated in FIG. 3, the exemplary inflatable insulation device 126 may be formed by securing a tubular length of material to the exterior of the catheter body 102. In those instances where the insulation device material is from the same class of materials as the catheter body material, thermal bonding may be employed. Adhesive

bonding is another suitable technique. In either case, anchors 132 may be positioned on the longitudinal ends of the inflatable insulation device 126 in order to prevent leakage. Gas may be infused into inflatable insulation device 126 by way of a small tube 134, which is carried on the exterior of the catheter body 102 and connected to a gas port 136 on the handle 110. Suitable gas ports include luer lock stopcocks. The gas may also be ventilated from the inflatable insulation device 126 by way of the tube 134 and gas port 136. The outer diameter of the inflatable insulation device 126 will be slightly larger when inflated, as is illustrated in FIG. 4, and a gas filled insulation zone 138 will be formed between the outer surface of the catheter body 102 and the inner surface of the insulation device.

[0050] One exemplary method of deploying the catheter 100 and using super-cooled fluid to create a lesion is illustrated in FIGS. 5-7. The same deployment method would be used in a JT cooling based system. After the guidewire 112 has been advanced through the femoral vein and into the target pulmonary vein, a long, transseptal introducer sheath 140 may be advanced over the guidewire to a position adjacent to the pulmonary vein. The catheter 100 may then be advanced through the sheath 140 and over the guidewire 112 with the cryogenic element 104 and inflatable insulation device 126 deflated. After the deflated cryogenic element 104 has been positioned adjacent to the pulmonary vein, it will be inflated with room temperature perfluorocarbon and advanced into contact with the pulmonary vein ostium. Alternatively, the cryogenic element 104 may be advanced into contact with the ostium prior to inflation with room temperature perfluorocarbon. The inflatable insulation device 126 will then be inflated, preferably with a gas such as CO₂ that can be readily absorbed by the body in the event of a leak, to a pressure of about 1-3 atmospheres. This may be accomplished by hand with a syringe or through the use of an automated device that would supply a suitable amount of gas. In either case, the pressure within the inflatable insulation device 126 may be monitored to detect leaks. The gas within the insulation device 126 will insulate tissue from super-cooled fluid within the catheter body 102 during the lesion formation procedure. Super-cooled fluid may then be circulated through the cryogenic element 104 by way of the infusion and ventilation lumens 118 and 120 for prescribed freezing periods (e.g. 60 to 180 seconds) to form the lesion. In addition to insulating tissue from the super-cooled fluid and increasing the thermal efficiency of the overall system, the inflatable insulation device 126 will engage the inner surface of the introducer sheath 140 (FIG. 7) and prevent the catheter body 102 from moving during the procedure. Once the cryogenic procedure has been completed, the cryogenic element 104 and inflatable insulation device 126 will be deflated and the catheter 100 removed from the patient.

[0051] The present inventions are not limited to any particular dimensions and materials. Nevertheless, the materials and dimensions of an exemplary implementation of the catheter 100 that is well suited for the isolation of pulmonary veins will be described for illustrative purposes. The exemplary catheter body 102 is preferably a multi-lumen extrusion formed from a flexible biocompatible thermoplastic material, such as a Pebax® material (polyether block emide). Suitable catheter lengths for cardiovascular applications range from about 80 cm to about 100 cm, although the length may be varied to suit the intended application. The

outer diameter of the catheter body **102** will be about 3 mm to about 4 mm, while the diameter of the guidewire lumen **114** will be about 1 mm. The cross-sectional area of the infusion and ventilation lumens **118** and **120** should be equal so that the flow resistance to and from the cryogenic element **104** is equal. Here, the inflation pressure of the cryogenic element **104** will be one-half the pressure at the inlet of the infusion lumen **118**. The exemplary cryogenic element **104**, which is an inflatable structure that is intended occlude a pulmonary vein and form a therapeutic lesion around the pulmonary vein ostium, will be about 15 mm to about 30 mm in diameter when inflated.

[0052] Turning to the inflatable insulation device **126** in the exemplary implementation, suitable materials include Nylon 12 or Pebax® with a wall thickness of about 0.025 to about 0.075 mm. The proximal end of the inflatable insulation device **126** will be about 1 cm to about 20 cm from the distal end of handle **110** (or the distal end of the strain relief element in those instances where a strain relief element is employed), which corresponds to a non-working length of about 2 cm to about 25 cm. It should be noted here that an insertion area for the catheter **100** will typically be about 1 cm to about 5 cm, measured from the skin to the vein, because physicians will insert the catheter at an acute angle. The distal end of the exemplary insulation device **126** will be about 2 cm to about 40 cm from the cryogenic element **104**. The outer diameter of the inflatable insulation device **126** will be about 0.3 mm to about 1.0 mm larger than the outer diameter of the catheter body **102** (i.e. about 3.3 mm to 5 mm depending on the diameter of the catheter body) when inflated. Typically, about 3-5 ml of gas will be used to inflate the insulation device **126**. When deflated, the outer diameter of the inflatable insulation device **126** will be only slightly greater than that of the catheter body **102**. An inflatable insulation device **126** with a 0.05 mm wall thickness, for example, will have an outer diameter that is only about that is only about 0.15 mm greater than the diameter of the catheter body **102**.

[0053] The exemplary catheter **100** may be reconfigured in a variety of ways. For example, the catheter body **102** could be a steerable catheter body with steering wires connected to a steering control on the handle **110**. Another alternative would be to replace the exemplary inflatable cryogenic element **104** with a hollow metal tip. With respect to insulation, the length inflatable insulation device **126** could be reduced such that it only extends over the small portion of the working length **130** that will be aligned with tissue in the insertion area. Such an inflatable insulation device **126** could, for example, extend from about an area just proximal of the distal end of the non-working length to an area just distal of the insertion area. In the context of a catheter **100** that has a 10 cm long non-working length and is intended to be inserted into the femoral vein, the proximal end of the inflatable insulation device **126** would be about 2 cm to about 8 cm from the distal end of the handle **110**, while the distal end of the inflatable insulation device would be about 20 cm to about 30 cm from the distal end of the handle.

[0054] III. Exemplary Insulated Introducer Sheath

[0055] An introducer sheath **200** in accordance with a preferred embodiment of a present invention is illustrated in FIGS. 8-10. The illustrated embodiment includes an elongate sheath body **202** with a proximal portion **208** that is secured

to a handle **210**. An inflatable insulation device **226** is carried on the exterior surface of the sheath body **202**. The inflatable insulation device **226** preferably extends distally from a location in close proximity to the distal end of the handle **210**, over the non-working length **228** of the sheath body **202** and along at least the proximal area of the working length **230**. This will insure that a portion of the inflatable insulation device **226** will be coextensive with the insertion area during use. In the exemplary embodiment, the inflatable insulation device **226** extends from a location in close proximity to the handle **210** to the distal portion **206** of the sheath body **202**. This would typically be about 2 mm to about 3 mm from the distal end of the handle **210**. The distal end of the inflatable insulation device **226** will preferably be about 2 mm to about 3 mm from the distal end of the sheath body **202** so there will be "end to end" insulation.

[0056] The sheath body **202**, which should be lubricious to reduce friction during movement of a catheter through the sheath, may be advanced into position over a guidewire or steerable catheter in conventional fashion. Alternatively, the sheath may be provided with its own steering mechanisms. The materials and dimensions will depend on the intended application. In cardiovascular applications, for example, the proximal portion **208** of the sheath body **202** is preferably formed from a Pebax® and stainless steel braid composite and the distal portion **206** is preferably formed from a more flexible material, such as unbraided Pebax®. The length of the sheath body **202** will typically range from about 60 cm to about 110 cm, the outer diameter will typically be about 3 mm to about 5 mm and the inner diameter will typically be about 2.3 mm to about 4 mm.

[0057] The inflatable insulation device **226** illustrated in FIGS. 8-10 is substantially similar to the inflatable insulation device **126** described above with reference to FIGS. 1-7 and the discussion in Section II above is applicable to the insulation device **226**. For example, the inflatable insulation device **226** may be formed by securing a tubular length of material to the exterior of the sheath body **202** with thermal bonding or adhesive bonding (depending on materials) and anchors **232** may be provided to prevent leakage. Gas may be infused and ventilated by way of a small tube **234**, which is carried on the exterior of the sheath body **202** and connected to a gas port **236** on the handle **210**. When inflated, a gas filled insulation zone **238** will be formed between the outer surface of the sheath body **202** and the inner surface of the insulation device **226**.

[0058] The exemplary sheath **200** has a wide variety of applications. In the context of lesion formation procedures which involve the use of a catheter with a cryogenic element at or near the distal tip, the sheath **200** may be used to guide the catheter to the target tissue area and to protect non-target tissue, including the tissue in the insertion area, from the damage. When creating a pulmonary vein lesion with super-cooled fluid, for example, the sheath **200** may be advanced over a guidewire through the femoral vein and into position adjacent to the target pulmonary vein with the inflatable insulation device **226** deflated. The catheter may then be advanced through the sheath **200** with the cryogenic element deflated. After the deflated cryogenic element has been positioned adjacent to the pulmonary vein, it will be inflated with room temperature perfluorocarbon and advanced into contact with the pulmonary vein ostium. Alternatively, the cryogenic element may be advanced into contact with the

ostium prior to inflation with room temperature perfluorocarbon. After the inflatable insulation device 226 has been inflated, preferably with a gas such as CO₂ in the manner described in Section II above, the lesion formation procedure may begin. The gas within the insulation device 226 will insulate tissue from the extremely low temperatures associated with the catheter body as super-cooled fluid is circulated through the cryogenic element during the lesion formation procedure. The cryogenic element and inflatable insulation device 226 may be deflated after the lesion formation procedure is complete so that the catheter and sheath may be removed from the patient.

[0059] IV. Exemplary Insulated Surgical Probe

[0060] A surgical probe 300 in accordance with one embodiment of a present invention is illustrated in FIGS. 11-13. The exemplary surgical probe 300 includes a relatively short shaft 302 and an inflatable cryogenic element 304 carried on the distal portion 306 of the shaft. The proximal portion 308 of the shaft 302 is secured to a handle 310. A strain relief element 312 is also provided. The shaft 302 will typically be about 10 cm to about 45 cm in length and will also typically be relatively stiff. In other words, the shaft is either rigid, malleable, or somewhat flexible. A rigid shaft cannot be bent. A malleable shaft is a shaft that can be readily bent by the physician to a desired shape, without springing back when released, so that it will remain in that shape during the surgical procedure. Thus, the stiffness of a malleable shaft must be low enough to allow the shaft to be bent, but high enough to resist bending when the forces associated with a surgical procedure are applied to the shaft. A somewhat flexible shaft will bend and spring back when released. However, the force required to bend the shaft must be substantial. The exemplary shaft 302 consists of a malleably hypotube 314 with an outer polymer jacket 316. The proximal portion 308 is, however, stiffer than the distal portion 306. The proximal portion 308 is also longer than the distal portion 306 in the exemplary embodiment.

[0061] Infusion and ventilation lumens 318 and 320 for the cooling fluid extend through the shaft 302. The distal ends of the infusion and ventilation lumens 318 and 320 terminate at respective openings (not shown) on the exterior surface of the shaft 302 that are located within the cryogenic element 304. The proximal ends of the infusion and ventilation lumens 318 and 320 are connected to infusion and ventilation ports 322 and 324 on the handle 310.

[0062] An inflatable insulation device 326 is carried on the exterior surface of the shaft 302 in the exemplary embodiment illustrated in FIGS. 11-13. The inflatable insulation device 326 preferably extends distally from a location in close proximity to the distal end of the strain relief element 312 (or the handle 310 if there is no strain relief element), over the non-working length 328 of the shaft 302 and along at least the proximal area of the working length 330. This will insure that a portion of the inflatable insulation device 326 will be coextensive with the insertion area during use. In the exemplary embodiment, the inflatable insulation device 326 extends from a location in close proximity to the strain relief element 312 and over the proximal portion 308 of the shaft 302. This would typically be about 1 cm to about 10 cm from the distal end of the strain relief element 312, which corresponds to a non-working length of about 2 cm to about 15 cm.

[0063] The inflatable insulation device 326 illustrated in FIGS. 11-13 is substantially similar to the inflatable insulation device 126 described above with reference to FIGS. 1-7 and the discussion in Section II above is applicable to the insulation device 326. For example, the inflatable insulation device 326 may be formed by securing a tubular length of material to the exterior of the shaft 302 with thermal bonding or adhesive bonding (depending on materials) and anchors 332 may be provided to prevent leakage. Gas may be infused and ventilated by way of a small tube 334, which is carried on the exterior of the shaft 302 and connected to a gas port 336 on the handle 310. When inflated, a gas filled insulation zone 338 will be formed between the outer surface of the shaft 302 and the inner surface of the insulation device 326.

[0064] The exemplary surgical probe 300 may be used in wide variety of procedures that employ super-cooled fluid, or the JT effect, for therapeutic purposes. For example, surgical probe 300 may be introduced into a target location, such as within a cancerous tumor, using laparoscopic techniques. Here, the surgical probe 300 may be introduced with a trocar, radially expandable port, or step trocar expandable port. The exemplary surgical probe 300 may also be used to create endocardial and epicardial lesions where access to the heart is obtained by way of a thoracostomy. In either case, and in the context of a super-cooled fluid system, the cryogenic element 304 and insulation device 326 will be deflated when the working portion of the probe 300 is inserted into the patient. After the deflated cryogenic element 304 has been positioned at or within the target tissue region, it will be inflated with room temperature perfluorocarbon. The inflatable insulation device 326 will then be inflated to insulate tissue from super-cooled fluid that will subsequently flow through the shaft 302 during the therapeutic procedure. Once the procedure has been completed, the cryogenic element 304 and inflatable insulation device 326 will be deflated and the probe 300 removed from the patient.

[0065] The exemplary surgical probe 300 may be reconfigured in a variety of ways. For example, the shaft distal portion 306 could be steerable and controlled by steering wires that extend from the distal tip to a steering control on the handle 310. Another alternative would be to replace the exemplary inflatable cryogenic element 304 with a hollow metal tip. With respect to insulation, the length inflatable insulation device 326 could be reduced such that it only extends over the small portion of the working length 330 that will be aligned with tissue in the insertion area. Such an inflatable insulation device 326 could, for example, extend from about an area just proximal of the distal end of the non-working length to an area just distal of the insertion area. In the context of a surgical probe 300 that has a 5 cm long non-working length and is intended to be inserted into the chest through the use of a thoracostomy, the proximal end of the inflatable insulation device 326 would be about 1 cm to about 3 cm from the distal end of the strain relief element 312 (or the handle 310 if there is no strain relief element), while the distal end of the inflatable insulation device would be about 20 cm to about 30 cm from the distal end of the handle.

[0066] V. Exemplary Insulated Introducer Ports

[0067] An introducer port 400 in accordance with one embodiment of a present invention is illustrated in FIGS. 14

and 15. The illustrated embodiment includes an introducer tube **402** with a proximal portion **408** that is secured to a handle **410**. An inflatable insulation device **426** is carried on the exterior surface of the introducer tube **402**. The inflatable insulation device **426** preferably extends distally from a location in close proximity to the distal end of the handle **410**, over the non-working length **428** of the introducer tube **402** and along at least the proximal area of the working length **430**. This will insure that a portion of the inflatable insulation device **426** will be coextensive with the insertion area during use. In the exemplary embodiment, the inflatable insulation device **426** extends from a location in close proximity to the handle **410** to the distal portion **406** of the introducer tube **402**. This would typically be about 2 mm to about 3 mm from the distal end of the handle **410** to about 2 mm to about 3 mm from the distal end of the introducer tube **402** so that “end to end” insulation is provided.

[0068] The introducer port **400** may be used, for example, to introduce catheters and surgical probes into the body. The materials and dimensions of the introducer tube **402** will depend on the intended application. In cardiovascular applications, for example, the introducer tube **402** is preferably formed from polyethylene and its length will typically range from about 5 cm to about 20 cm, the outer diameter will typically be about 3 mm to about 6 mm and the inner diameter will typically be about 2.3 mm to about 5 mm.

[0069] The inflatable insulation device **426** illustrated in **FIGS. 14 and 15** is substantially similar to the inflatable insulation device **126** and the discussion in Section II above is applicable to the insulation device **426**. For example, the inflatable insulation device **426** may be formed by securing a tubular length of material to the exterior of the introducer tube **402** with thermal bonding or adhesive bonding (depending on materials) and anchors **432** may be provided to prevent leakage. Gas may be infused and ventilated by way of a small tube **434**, which is carried on the exterior of the introducer tube **402** and connected to a gas port **436** on the handle **410**. When inflated, a gas filled insulation zone **438** will be formed between the outer surface of the introducer tube **402** and the inner surface of the insulation device **426**.

[0070] Another exemplary introducer port, which is generally represented by reference numeral **400'** in **FIGS. 16 and 17**, is substantially similar to introducer port **400**. Here, however, introducer tube **402'** has a slightly larger inner and outer diameter and the inflatable insulation device **426'** is located within the introducer tube. The handle **410'** includes a gas port **436'** that may be connected to the interior of the inflatable insulation device **426'** by a tube (not shown). When inflated, a gas filled insulation zone **438'** will be formed between the inner surface of the introducer tube **402'** and the surface of the insulation device **426'** that faces the tube.

[0071] The introducer ports **400** and **400'** have a wide variety of applications. In the context of lesion formation procedures which involve the use of a catheter or surgical probe with a distal cryogenic element, the introducer ports **400** and **400'** may be used to provide access to interior regions of the patient's body as well as to protect non-target tissue, including the tissue in the insertion area, from damage. More specifically, a cryogenic catheter or surgical probe may be inserted through the introducer port **400** (or **400'**)

with the insulation device **426** (or **426'**) and cryogenic element deflated. Once the catheter or surgical probe has been positioned at the target tissue region, the cryogenic element may be inflated with room temperature perfluorocarbon. Next, the inflatable insulation device **426** (or **426'**) will be inflated to insulate tissue from the super cool temperatures associated with the catheter body or surgical probe shaft during the lesion formation procedure. Next, super-cooled fluid will be circulated through the cryogenic element for prescribed freezing periods. Once the procedure has been completed, the cryogenic element and inflatable insulation device **426** (or **426'**) will be deflated so that the catheter or surgical probe may be removed from the patient.

[0072] VI. Exemplary Trocars

[0073] A trocar **500** in accordance with one embodiment of a present invention is illustrated in **FIGS. 18 and 19**. The illustrated embodiment includes a trocar sleeve **502** with a proximal portion that is secured to a handle **510**. An inflatable insulation device **526** is carried on the interior surface of the trocar sleeve **502**. The inflatable insulation device **526** preferably extends distally from a location in close proximity to the distal end of the handle **510** to the proximal end of the sharpened sleeve area **503**. This will insure that a portion of the inflatable insulation device **526** will be coextensive with the insertion area during use. This would typically be about 2 mm to about 3 mm from the distal end of the handle **510** to about 2 mm to about 3 mm from the distal end of the trocar sleeve **402** so that “end to end” insulation is provided.

[0074] The trocar **500** may be used, for example, to introduce surgical devices into the body. The materials and dimensions of the trocar sleeve **502** will depend on the intended application. The trocar sleeve **502** is preferably formed from stainless steel and its length will typically range from about 3 cm to about 8 cm, the outer diameter will typically be about 16 mm to about 32 mm and the inner diameter will typically be about 15 mm to about 30 mm. The inflatable insulation device **526** illustrated in **FIGS. 18 and 19** is substantially similar to the inflatable insulation device **126** and the discussion in Section II above is applicable to the insulation device **526**. For example, the inflatable insulation device **526** may be formed by securing a tubular length of material to the interior of the trocar sleeve **502** with adhesive bonding. Gas may be infused and ventilated by way of a small tube (not shown), which is carried on the interior of the trocar sleeve **502** and connected to a gas port **536** on the handle **510**. When inflated, a gas filled insulation zone **538** will be formed between the inner surface of the trocar sleeve **502** and the surface of the insulation device **526** that faces the tube. The cross-sectional size of the gas filled insulation zone **538** when inflated, i.e. percentage of the sleeve lumen that is occluded, will depend on the intended application and can vary from a small percentage to near complete occlusion.

[0075] The trocar **500** has a wide variety of applications. In the context of lesion formation procedures which involve the use of a surgical probe with a distal cryogenic element, the trocar **500** may be used to provide access to interior regions of the patient's body as well as to protect non-target tissue, including the tissue in the insertion area, from damage. More specifically, a cryogenic surgical probe may be inserted through the trocar **500** with the insulation device **526** and cryogenic element deflated. Once the surgical probe

has been positioned at the target tissue region, the cryogenic element may be inflated with room temperature perfluorocarbon. Next, the inflatable insulation device 526 will be inflated to insulate tissue from the super cool temperatures associated with the surgical probe shaft during the lesion formation procedure. Next, super-cooled fluid will be circulated through the cryogenic element for prescribed freezing periods. Once the procedure has been completed, the cryogenic element and inflatable insulation device 526 will be deflated so that the surgical probe may be removed from the patient.

[0076] It should be noted that trocars in accordance with the present inventions are not limited to those which employ the angled sharpened sleeve area 503 illustrated in FIG. 18. For example, and turning to FIGS. 20 and 21, a trocar sleeve 502' is shown with a sharpened sleeve area 503' that is generally perpendicular to the longitudinal axis of the sleeve. The sleeve 502' may be substituted for the sleeve 502 in the trocar 500.

[0077] Although the present inventions have been described in terms of the preferred embodiments above, numerous modifications and/or additions to the above-described preferred embodiments would be readily apparent to one skilled in the art. Additionally, the scope of the inventions includes any combination of the elements from the various species and embodiments disclosed in the specification that are not already described. It is intended that the scope of the present inventions extend to all such modifications and/or additions and that the scope of the present inventions is limited solely by the claims set forth below.

I claim:

1. A device for forming lesions in target body tissue after passing through an insertion area, the device comprising:
 - a shaft defining a proximal region, a distal region and at least one lumen;
 - a lesion formation device associated with the distal region of the shaft and operably connected to the lumen; and
 - an inflatable insulation device carried by the shaft such that at least a portion of the inflatable insulation device will be aligned with the insertion area when the lesion formation device is adjacent to the target body tissue.
2. A device as claimed in claim 1, further comprising:
 - a handle associated with the proximal region of the shaft.
3. A device as claimed in claim 1, wherein the shaft comprises a catheter body.
4. A device as claimed in claim 1, wherein the shaft comprises a relatively short surgical probe shaft.
5. A device as claimed in claim 1, wherein the shaft defines an exterior and the inflatable insulation device is carried on the exterior of the shaft.
6. A device as claimed in claim 1, wherein the inflatable insulation device defines an inflated diameter and a deflated diameter and the inflated diameter is greater than the deflated diameter.
7. A device as claimed in claim 1, wherein the inflatable insulation device extends from the proximal region of the shaft to the distal region.
8. A device for forming lesions in target body tissue after passing through an insertion area, the device comprising:

- a shaft defining a proximal region, a distal region and at least one lumen;
 - a lesion formation device associated with the distal region of the shaft and operably connected to the lumen; and
 - inflatable insulation means, associated with the shaft, for thermally insulating the insertion area from the shaft.
9. A device as claimed in claim 8, further comprising:
 - a handle associated with the proximal region of the shaft.
 10. A device as claimed in claim 8, wherein the shaft comprises a catheter body.
 11. A device as claimed in claim 8, wherein the shaft comprises a relatively short surgical probe shaft.
 12. A device as claimed in claim 8, wherein the shaft defines an exterior and the inflatable insulation device is carried on the exterior of the shaft.
 13. An apparatus facilitating passage of a therapeutic device into a body through an insertion area, the apparatus comprising:
 - a tubular member defining a proximal end, a distal end, and at least one lumen; and
 - an inflatable insulation device carried by tubular member such that at least a portion of the inflatable insulation device will be aligned with the insertion area when the apparatus is deployed.
 14. An apparatus as claimed in claim 13, wherein the tubular member defines an exterior and the inflatable insulation device is carried on the exterior of the tubular member.
 15. An apparatus as claimed in claim 13, wherein the tubular member defines an interior and the inflatable insulation device is carried on the interior of the tubular member.
 16. An apparatus as claimed in claim 13, wherein the inflatable insulation device defines an inflated diameter and a deflated diameter and the inflated diameter is greater than the deflated diameter.
 17. An apparatus as claimed in claim 13, wherein the inflatable insulation device extends from about the proximal end of the tubular member to about the distal end of the tubular member.
 18. An apparatus as claimed in claim 13, wherein the tubular member comprises a sheath body.
 19. An apparatus as claimed in claim 13, wherein the tubular member comprises an introducer tube.
 20. An apparatus as claimed in claim 13, wherein the tubular member comprises a trocar sleeve.
 21. An apparatus facilitating passage of a therapeutic device into a body through an insertion area, the apparatus comprising:
 - a tubular member defining a proximal end, a distal end, and at least one lumen; and
 - inflatable insulation means, associated with the tubular member, for thermally insulating the insertion area from the therapeutic device.
 22. An apparatus as claimed in claim 21, wherein the tubular member comprises a sheath body.
 23. An apparatus as claimed in claim 21, wherein the tubular member comprises an introducer tube.
 24. An apparatus as claimed in claim 21, wherein the tubular member comprises a trocar sleeve.
 25. A therapeutic method, comprising the steps of:

positioning at least a portion of an inflatable insulation device in an insertion area;

inflating the insulation device; and

performing a therapeutic procedure at a location in spaced relation to the insertion area.

26. A method as claimed in claim 25, wherein the step of performing a therapeutic procedure comprises the steps of:

passing a therapeutic device, including a shaft and a therapeutic element, through the inflatable insulation device prior to inflating the inflatable insulation device; and

passing a fluid at a temperature other than body temperature through the shaft to the therapeutic element after inflating the inflatable insulation device.

27. A method as claimed in claim 26, wherein the step of passing a fluid at a temperature other than body temperature through the shaft to the therapeutic element comprises passing cryogenic fluid through the shaft to the therapeutic element.

28. A method as claimed in claim 25, wherein the step of positioning at least a portion of an inflatable insulation device in an insertion area comprises the steps of:

providing a therapeutic device that includes the inflatable insulation device and a therapeutic element; and

passing the therapeutic device through the insertion area until at least a portion of the inflatable insulation device

is within the insertion area and the therapeutic element is located at the location in spaced relation to the insertion area.

29. A method as claimed in claim 28, wherein the step of performing a therapeutic procedure comprises the steps of:

passing a fluid at a temperature other than body temperature through the therapeutic device after inflating the inflatable insulation device.

30. A method as claimed in claim 29, wherein the step of passing a fluid at a temperature other than body temperature through the therapeutic device comprises passing cryogenic fluid through the therapeutic device.

31. A method as claimed in claim 25, wherein the step of positioning at least a portion of an inflatable insulation device in an insertion area comprises positioning at least a portion of an inflatable insulation device in an insertion area that extends from an exterior skin surface to a body lumen.

32. A method as claimed in claim 25, wherein the step of positioning at least a portion of an inflatable insulation device in an insertion area comprises positioning at least a portion of an inflatable insulation device in an insertion area that extends from an exterior skin surface to a vein.

33. A method as claimed in claim 25, wherein the step of positioning at least a portion of an inflatable insulation device in an insertion area comprises positioning at least a portion of an inflatable insulation device in an insertion area that extends from an exterior skin surface to a chest cavity.

* * * * *