

(No Model.)

W. E. NASH.
BROOM ATTACHMENT.

No. 345,069.

Patented July 6, 1886.

Fig. 1




Fig. 2





Fig. 3



WITNESSES:

C. Swanwick
to Sedgwick

INVENTOR:

W. E. Nash

BY

Munn & Co

ATTORNEYS.

UNITED STATES PATENT OFFICE.

WALTER ELLIOTT NASH, OF DARLINGTON, WISCONSIN.

BROOM ATTACHMENT.

SPECIFICATION forming part of Letters Patent No. 345,069, dated July 6, 1886.

Application filed June 2, 1885. Serial No. 167,404. (No model.)

To all whom it may concern:

Be it known that I, WALTER ELLIOTT NASH, of Darlington, in the county of Lafayette and State of Wisconsin, have invented a certain
5 new and useful Broom Attachment, of which the following is a full, clear, and exact description.

This invention more particularly relates to brooms used for sweeping floors, and other household purposes; and it consists in a detachable broom-like-shaped guard, the same being made flaring toward its front end, to conform to or approximate the spread or fan-like shape of the opposite sides or faces of the broom or broom-head, and with its side
15 edges, from its back to its front end, turned up to fit and clasp both side edges of the broom, also provided at its back end with a central tubular handle, open throughout its
20 length, to admit of the guard being slipped over the handle of the broom, and serving to cause the guard to bear against and support the side of the broom below or beyond the bound portion of its splints. When fitted to
25 the broom-head and its handle, as described, this broom-shaped-like guard operates to give to the broom a comparatively rigid action on its one side or face, without restricting the elasticity of it on its opposite side or face,
30 thus by simply turning the broom about varying its sweeping capacity or action, which will be found very convenient. Furthermore, said guard, when removed from the broom and its handle, constitutes a very serviceable
35 dust-pan for gathering the sweepings brushed up by the broom, and which, by being carried by or combined with the broom, as described, will always be ready for use as a dust-pan by the person using the broom, and the
40 two articles—viz., broom and dust-pan—convenient for use, as required, also, when combined, serving to protect from injury each the other.

Reference is to be had to the accompanying
45 drawings, forming part of this specification, in which similar letters of reference indicate corresponding parts in all the figures.

Figure 1 represents a longitudinal view, looking toward its edge side, of a broom with

attached handle in part, and having the com- 50
bined guard and dust-pan applied. Fig. 2 is a similar view of the same, upon a smaller scale, looking toward a face or flat side of the broom; and Fig. 3 is a front face view of the combined broom-guard and dust-pan de- 55
tached.

A indicates an ordinary house broom or broom-head with attached handle B.

C is the combined broom-guard and dust-pan, of broom-like shape in its general con- 60
figuration, being made flaring toward its front end and rounded at its back or upper end—that is, as viewed from its face or back. It is made of metal, and has its side edges, from its back to its front end, turned up, as at *b*, to
65 fit and clamp both side edges of the broom. Its tubular handle *c*, which is open at both ends, is of a size to admit of its being readily slipped over the handle of the broom when fitting the guard to its place on the broom, and is at such an angle in relation with the bottom
70 of the article as will cause its bottom or back to bear against and support the one face or side of the broom, and to extend below or beyond the lowest tied or bound part, *s*, of its splints. Thus applied, the guard C will serve to stiffen the broom on its one side or face, so that when sweeping with the opposite side or face in front the broom will have a comparatively rigid sweeping action, which will
80 be useful when rough or hard sweeping is required; but by turning the broom about, so as to sweep from its other side or face, then it will have its usual free or elastic action for lighter sweeping. This will be found very
85 convenient, and after sweeping with the broom, or at any time, the guard C may be slipped from off the broom, and its handle and be used as a dust-pan to gather up the sweepings, &c. It, in fact, as combined with the
90 broom, will be a dust-pan always ready for use in connection with the broom.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. The within-described combined broom-guard and dust-pan C, of tapering or flaring
95 broom-like-shaped construction, with its edges *b* turned up on its one side or face, and pro-

vided with a tubular handle, *c*, open at its opposite ends and throughout its length, substantially as shown and described.

2. The combination, with the broom or
5 broom-head A and its handle B, of the removable combined guard and dust-pan C, constructed as described, and arranged, when in place on the broom, to project below the

10 tied or bound portions of its fiber, and to support the broom on its one side or face and opposite edges, essentially as and for the purposes herein set forth.

WALTER ELLIOTT NASH.

Witnesses:

P. A. ORTON,

GEO. S. ANTHONY.