



(51) International Patent Classification:

C11D 1/75 (2006.01) *C11D* 3/20 (2006.01)
C11D 1/83 (2006.01) *C11D* 3/43 (2006.01)
C11D 1/94 (2006.01) *C11D* 17/04 (2006.01)

(21) International Application Number:

PCT/US2016/040269

(22) International Filing Date:

30 June 2016 (30.06.2016)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

15176536.9 13 July 2015 (13.07.2015) EP

(71) Applicant: **THE PROCTER & GAMBLE COMPANY**
[US/US]; One Procter & Gamble Plaza, Cincinnati, Ohio
45202 (US).

(72) Inventors: **BOERS, Wesley, Yvonne Pieter**; NV Procter
& Gamble, Services Company SA, Temselaan 100, B-1853
Strombeek-Bever (BE). **VANCAMPENHOUT, Peter**;
NV Procter & Gamble, Services Company SA, Temselaan
100, B-1853 Strombeek-Bever (BE). **GONZALES, Denis,**
Alfred; NV Procter & Gamble, Services Company SA,
Temselaan 100, B-1853 Strombeek-Bever (BE). **DKIDAK,**
Aicha; NV Procter & Gamble, Services Com-
pany SA, Temselaan 100, B-1853 Strombeek-Bever (BE).
BETTIOL, Jean-Luc, Philippe; NV Procter & Gamble,
Services Company SA, Temselaan 100, B-1853 Strom-
beek-Bever (BE).

(74) Agent: **KREBS, Jay A.**; c/o THE PROCTER & GAMBLE
COMPANY, Global Patent Services, One Procter &
Gamble Plaza, C8-229, Cincinnati, Ohio 45202 (US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR,
KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG,
MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM,
PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC,
SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ,
TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU,
TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE,
DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,
SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: CLEANING PRODUCT

(57) Abstract: A cleaning product comprising a spray dispenser and a cleaning composition suitable for spraying and foaming, the composition housed in the spray dispenser wherein the composition comprises: i) a surfactant system comprising a branched short chain alkyl sulfate and a co-surfactant selected from the group consisting of amphoteric surfactant, zwitterionic surfactant and mixtures thereof; and ii) a glycol ether solvent selected from the group consisting of glycol ethers of Formula I: $R1O(R2O)_nR3$, Formula II: $R4O(R5O)_nR6$ and mixtures thereof wherein R1 is a linear or branched C4, C5 or C6 alkyl, a substituted or unsubstituted phenyl, R2 is ethyl or isopropyl, R3 is hydrogen or methyl and n is 1, 2 or 3 R4 is n-propyl or isopropyl, R5 is isopropyl, R6 is hydrogen or methyl and n is 1, 2 or 3.



CLEANING PRODUCT

FIELD OF INVENTION

The present invention relates to a cleaning product. In particular, it relates to a cleaning product comprising a spray dispenser and a cleaning composition. The product makes the cleaning of
5 dishware easier and faster.

BACKGROUND OF THE INVENTION

Traditionally manual dishwashing has been performed by filling a sink with water, adding a dishwashing detergent to create a soapy solution, immersing the soiled articles in the solution, scrubbing the articles and rinsing to remove the remaining soils and remove the suds generated
10 from the soapy solution from the washed articles. Traditionally an entire load of soiled dishware has usually been washed in one go. Nowadays some users prefer to clean articles as soon as they have finished with them rather than wait until they have a full load. This involves washing one article or a small number of articles at the time. The washing is usually performed under running water rather than in a full sink. The cleaning should be fast and involve minimum effort from
15 the user.

Nowadays, a high number of users prefer to do the washing under the tap. This usually involves the use of a cleaning implement, such as a sponge. The user delivers detergent to the sponge. When the number of items to be cleaned is small, there is the risk of dosing more detergent than
20 required, this will require the need for more rinsing for the dishware and the cleaning implement. Another disadvantage associated to this method, is that some time is required to mix the detergent with water in the sponge, this can slow down the cleaning process.

The level and type of soil found on dishware varies considerably depending on the use of the
25 dishware. Dishware can be lightly soiled or can have hard to remove soils such as baked-, cooked- and/or burnt-on soils. It might be easier to design different products for different types/degrees of soils however this might not be very practical because the user would have to have a large number of dishwashing products.

When the cleaning of a lightly soiled article is done under running water, it is desirable that the cleaning is performed quickly and with minimum effort. Ideally, the product should be applied and then immediately rinsed obviating or reducing the need for scrubbing.

When articles are soiled with difficult to remove soils, it is desirable that the product facilitates the cleaning task by softening the well-attached soils. It is desirable that the softening takes place in a short time. In cases in which the soils are really tough it is common practice to soak the items before cleaning. The soaking time should be short.

Spray products are well liked by users. A sprayable composition for use in hand dishwashing should be easy to spray, deliver fast and long lasting suds, easy to rinse and at the same time should provide fast and good cleaning of a variety of soils. The composition should be such that when sprayed onto the dishware spreading to the surrounding atmosphere should be minimised or avoided. Spreading to the surrounding atmosphere can not only give rise to waste of the product but it can also have inhalation risks associated to it.

The object of the present invention is to facilitate cleaning, especially the manual dishwashing task, in particular by reducing the time and effort needed to achieve the cleaning.

SUMMARY OF THE INVENTION

According to a first aspect of the invention, there is provided a cleaning product. The product is suitable for the cleaning of any kind of surfaces but preferably the product is a hand dishwashing cleaning product. The product comprises a spray dispenser and a cleaning composition. The composition is a foaming composition and it is suitable for spraying. The composition is housed in the spray dispenser. The “composition” of the cleaning product of the invention is herein sometimes referred to as “the composition of the invention”.

By “spray dispenser” is herein meant a container comprising a housing to accommodate the composition and means to spray that composition. The preferred spraying means being a trigger spray. The composition foams when it is sprayed. Foaming is a property that users associate with cleaning therefore it is important that the composition of the invention foams to send the user the signal that the composition is cleaning.

The composition of the invention comprises:

i) a surfactant system comprising a branched short chain alkyl sulfate and a co-surfactant selected from the group consisting of amphoteric surfactant, zwitteronic surfactant and mixtures thereof; and

ii) a glycol ether solvent selected from the group consisting of glycol ethers of Formula I: $R1O(R2O)_nR3$, Formula II: $R4O(R5O)_nR6$ and mixtures thereof wherein

R1 is a linear or branched C4, C5 or C6 alkyl or a substituted or unsubstituted phenyl, R2 is ethyl or isopropyl, R3 is hydrogen or methyl and n is 1, 2 or 3

R4 is n-propyl or isopropyl, R5 is isopropyl, R6 is hydrogen or methyl and n is 1, 2 or 3

The surfactant system and the glycol ether solvent preferably are in a weight ratio of from about 5:1 to about 1:1, preferably from about 3:1 to about 1:1. The surfactant system seems to help with the cleaning and foam generation. Preferably, the composition comprises at least 5% by weight of the composition of the surfactant system, with this level of surfactant, the specific solvent and the surfactant:solvent weight ratio flash suds and long lasting suds are generated. The suds generated when spraying the composition of the invention are strong enough to withstand the impact force when the foam contact the article to be washed but at the same time the composition is easy to rinse.

Furthermore, the composition of the invention provides good cleaning, including cleaning of tough food soils such as cooked-, baked- and burnt-on soils and good cleaning of light oily soils. The composition of the invention not only provides outstanding cleaning but also very fast cleaning, requiring reduced scrubbing effort by the consumer. Thus the product of the invention is especially suitable for cleaning dishware under the tap. When the dishware is only lightly soiled the composition of the invention provides very good cleaning with reduced scrubbing or in the absence of scrubbing. The dishware can be cleaned by simply spraying the composition followed by a rinse with water, optionally aided by a low force wiping action.

In the case of heavily soiled dishware the product of the invention is very good to facilitate the removal of the soil when the product is used to pre-treat the dishware. Pre-treatment usually involves leaving the soiled dishware with the neat product.

- 5 Compositions having the claimed level of surfactant system and the claimed weight ratio of surfactant system to glycol ether solvent when sprayed provide good coverage on the dishware with minimum over spray, thereby avoiding wasting product or the risk of inhalation.

Compositions having a surfactant:solvent weight ratio lower than 1:1 do not seem to be able to foam and/or tend to phase separate creating physical instability in the product. Compositions
10 having a surfactant:solvent weight ratio higher than 5:1 are difficult to spray and are prone to gelling when in contact with greasy soils in the presence of the low levels of water typically present when the product of the invention is used. Gel formation would inhibit the spreading of the composition negatively impairing on the cleaning.

- 15 Preferably, the composition of the invention has a pH greater than 8, more preferably from 10 to 12, most preferably from 10.5 to 11.5 as measured at 10% solution in distilled water at 20°C and a reserve alkalinity of from about 0.1 to about 1, more preferably from about 0.1 to about 0.5. Reserve alkalinity is herein expressed as grams of NaOH/100 ml of composition required to titrate product from a pH 10 to the pH of the finished composition. This pH and reserve
20 alkalinity further contribute to the cleaning of tough food soils.

Compositions having a surfactant system comprising a branched short chain alkyl sulfate and a co-surfactant have been found to be very good from a cleaning and sudsing viewpoint. They have also been found very good from a spray pattern view point. The presence of small droplets (and therefore the risk of inhalation) is minimized when the surfactant system of the composition
25 of the invention contains anionic surfactant. By co-surfactant is herein meant a surfactant that is present in the composition in an amount lower than the main surfactant. By main surfactant is herein meant the surfactant that is present in the composition in the highest amount.

By a “branched short chain alkyl sulfate” is herein meant a surfactant having a linear alkyl sulfate backbone, the backbone comprising from 4 to 8, preferably from 5 to 7 carbon atoms,
30 substituted with one or more C1-C5 preferably C1-C3 alkyl branching groups in the C1, C2 or C3, preferably C2 position on the linear alkyl sulfate backbone. This type of anionic surfactant

has been found to deliver strong grease cleaning as well as good foaming performance, especially immediate foaming performance upon spraying when the composition comprises amine oxide or betaine, preferably amine oxide as co-surfactant. Preferred branched short chain alkyl sulfate for use herein is a branched hexyl sulfate, more preferably 2-ethyl hexyl sulfate.

5

The co-surfactant is selected from the group consisting of amphoteric surfactant, zwitterionic surfactant and mixtures thereof. Preferably, the co-surfactant is selected from the group consisting of betaine, amine oxide and mixtures thereof. Amine oxide is the preferred co-surfactant for use herein. The co-surfactant seems to help with the sudsing of the product.

10 Particularly good performing products are those in which the sulfate surfactant and the co-surfactant are present in a weight ratio of about 4:1 to about 1:1, preferably in a weight ratio of from about 3:1 to about 1:1, most preferably in a weight ratio from about 2:1 to about 1:1. Especially preferred are compositions in which the co-surfactant comprises amine oxide.

15 The composition of the invention comprises glycol ethers selected from the group consisting glycol ethers of Formula I, Formula II and mixtures thereof. It has been found that these glycol ethers help not only with the speed of cleaning of the product but also with the cleaning, especially greasy soils cleaning. This does not seem to happen with glycol ethers having a different formula to Formula I and Formula II.

20 Preferably, the composition of the invention further comprises a chelant, preferably an aminocarboxylate chelant, more preferably GLDA. The aminocarboxylate not only act as a chelant but also contributes to the reserve alkalinity, this seems to help with the cleaning of cooked-, baked- and burnt-on soils. Preferably, the composition of the invention comprises bicarbonate and/or monoethanol and/or carboxylate builder preferably citrate builder, that as in
25 the case of the of the aminocarboxylate chelant also contribute to the reserve alkalinity.

The composition of the invention can be Newtonian or non-Newtonian. Preferably the composition is a shear thinning fluid. This is important to allow the composition to be easily sprayed. The viscosity of the composition of the invention should also make the fluid to stay in
30 vertical surfaces to provide cleaning and at the same time be easy to rinse. Especially suitable have been found compositions having a starting viscosity at high shear (10,000 s⁻¹) of from

about 1 to about 10 mPa s. Preferably, the composition is a shear thinning composition having a low shear (100 s⁻¹) to high shear (10,000 s⁻¹) viscosity ratio of from about 10:1 to about 1.5:1 at 20°C as measured using the method defined herein below. Preferably the compositions of the invention comprises xanthan gum.

- 5 A preferred composition has a pH of from 10 to 11.5 as measured in a 10% solution in distilled water at 20°C, a reserve alkalinity of from 0.1 to 0.3, expressed as g NaOH/ 100ml of composition at a pH of 10, the composition comprising:
- 10 i) from about 4 to about 10%, from about 5 to about 8% by weight of the composition of a branched short chain sulfate, preferably 2-ethyl hexyl sulfate,
 - ii) from about 1 to 5% by weight of the composition of amine oxide surfactant; and
 - iii) from about 3% to 8%, preferably from about 4 to about 7% by weight of the composition of glycol ether solvent, preferably dipropylene glycol n-butyl ether.

- According to the second aspect of the invention, there is provided a method of cleaning soiled
- 15 dishware using the product according to any of the preceding claims comprising the steps of:
- a) optionally pre-wetting the soiled dishware
 - b) spraying the cleaning composition onto the soiled dishware;
 - c) optionally adding water to the soiled dishware during a period of time;
 - d) optionally scrubbing the dishware; and
 - 20 e) rinsing the dishware.

The method of the invention allows for faster and easier cleaning of dishware under running tap, especially when the dishware is lightly soiled. When the dishware is soiled with tough food soils such as cooked-, baked- or burnt-on soils the method of the invention facilitates the cleaning when the soiled dishware is soaked with the product of the invention in neat form or diluted in

25 water.

DETAILED DESCRIPTION OF THE INVENTION

The present invention envisages a cleaning product, preferably a hand dishwashing cleaning product, the product comprises a spray dispenser and a cleaning composition. The cleaning composition comprises a surfactant system and a specific glycol ether solvent. The product of

30 the invention simplifies the cleaning task, in particular the manual cleaning task, by making the

task easier and faster. The product of the invention is particularly suitable for the manual cleaning of dishware.

For the purpose of the present invention “dishware” encompasses all the items used to either cook or used to serve and eat food.

5 Cleaning composition

The cleaning composition is preferably a hand dishwashing cleaning composition, preferably in liquid form.

10 Preferably the pH of the composition is greater than 8, more preferably from about 10 to about 12 and most preferably from about 10.5 to about 11.5, as measured at 20°C and 10% concentration in distilled water. Preferably, the composition has a reserve alkalinity of from about 0.1 to about 1, more preferably from about 0.1 to about 0.5 measured as detailed herein below.

15 Reserve alkalinity is defined as the grams of NaOH per 100 g of composition required to titrate the test composition at pH 10 to come to the test composition pH. The reserve alkalinity for a solution is determined in the following manner.

20 A pH meter (for example An Orion Model 720A) with a Ag/AgCl electrode (for example an Orion sure flow Electrode model 9172BN) is calibrated using standardized pH 7 and pH 10 buffers. A 100g of a 10% solution in distilled water at 20°C of the composition to be tested is prepared. The pH of the 10% solution is measured and the 100g solution is titrated down to pH 10 using a standardized solution of 0.1 N of HCl. The volume of 0.1N HCl required is recorded in ml. The reserve alkalinity is calculated as follows:

Reserve Alkalinity = ml 0.1N HCl x 0.1 (equivalent / liter) x Equivalent weight NaOH (g/equivalent) x 10

25

Surfactant system

The cleaning composition preferably comprises from about 5% to about 15%, preferably from about 6% to about 14%, more preferably from about 7% to about 12% by weight thereof of a surfactant system. The surfactant system comprises a branched short chain alkyl sulfate. The

system preferably comprises a co-surfactant selected from the group consisting of amphoteric surfactants, zwitterionic surfactants and mixtures thereof. The system can optionally comprise a non-ionic surfactant.

5 Preferably, the branched short chain alkyl sulfate surfactant and the co-surfactant are present in the composition of the invention in a weight ratio of about 4:1 to about 1:1, preferably from 3:1 to 1:1 and more preferably from 2.8:1 to 1.3:1.

10 The most preferred surfactant system for the detergent composition of the present invention comprise: (1) 4% to 10%, preferably 5% to 8% by weight of the composition of a branched short chain alkyl sulfate, preferably 2-ethyl hexyl sulfate; (2) 1% to 5%, preferably from 1% to 4% by weight of the composition of a surfactant selected from the group consisting of amphoteric surfactant, zwitterionic surfactant and mixtures thereof, preferably an amine oxide surfactant. It has been found that such surfactant system in combination with the glycol ether of the invention provides excellent cleaning and good foaming profile.

15

Branched short chain alkyl sulfate surfactant

This type of anionic surfactants has been found to deliver strong grease cleaning. They also present good foaming performance, when used in combination with amine oxide or betaine especially amine oxide surfactants, especially immediate foaming performance upon spraying.

20 The branched short chain alkyl sulphate surfactants according to the current invention have a linear alkyl sulphate backbone comprising from 4 to 8 carbon atoms, substituted with one or more C1-C5 alkyl branching groups in the C1, C2 or C3 position on the linear alkyl sulphate backbone. The sulphate group within the branched short chain alkyl sulphate surfactant is bonded directly to said C4-C8 linear backbone in terminal position.

25 Preferably the linear alkyl sulphate backbone comprises from 5 to 7 carbon atoms. Preferably the one or more alkyl branching groups are selected from methyl, ethyl, propyl or isopropyl. Preferably the branched short chain alkyl sulphate surfactant has only one branching group substituted on its linear backbone chain. Preferably the alkyl branching group is on the C2 position in the linear alkyl sulphate backbone.

More preferably the branched short chain alkyl sulphate according to the current invention has a linear alkyl backbone comprising from 5 to 7 carbons, substituted on the C2 position in the linear alkyl sulphate backbone with one alkyl branching group selected from methyl, ethyl, propyl. Most preferably the branched short chain alkyl sulphate surfactant is 2-ethylhexylsulphate.

- 5 The composition of the present invention might further comprise a fraction of the corresponding non-sulphated branched short chain alcohol feedstock material of the formulated branched short chain alkyl sulphate surfactant.

Suitable branched short chain alkyl sulphate surfactants include 1-methylbutylsulphate, 1-ethylbutylsulphate, 1-propylbutylsulphate, 1-isopropylbutylsulphate 1-methylpentylsulphate, 1-ethylpentylsulphate, 1-propylpentylsulphate, 1-isopropylpentylsulphate 1-butylpentylsulphate, 1-methylhexylsulphate, 1-ethylhexylsulphate, 1-propylhexylsulphate, 1-isopropylhexylsulphate 1-butylhexylsulphate, 1-pentylhexylsulphate, 1-methylheptylsulphate, 1-ethylheptylsulphate, 1-propylheptylsulphate, 1-isopropylheptylsulphate, 1-butylheptylsulphate, 1-pentylheptylsulphate, 1-hexylheptylsulphate, 1-methyloctylsulphate, 1-ethyloctylsulphate, 1-propyloctylsulphate, 1-isopropyloctylsulphate, 1-butyloctylsulphate, 1-pentyloctylsulphate, 1-hexyloctylsulphate, 1-heptyloctylsulphate, 2-methylbutylsulphate, 2-ethylbutylsulphate, 2-propylbutylsulphate, 2-isopropylbutylsulphate 2-methylpentylsulphate, 2-ethylpentylsulphate, 2-propylpentylsulphate, 2-isopropylpentylsulphate, 2-butylpentylsulphate, 2-methylhexylsulphate, 2-ethylhexylsulphate, 2-propylhexylsulphate, 2-isopropylhexylsulphate, 2-butylhexylsulphate, 2-pentylhexylsulphate, 2-methylheptylsulphate, 2-ethylheptylsulphate, 2-propylheptylsulphate, 2-isopropylheptylsulphate, 2-butylheptylsulphate, 2-pentylheptylsulphate, 2-hexylheptylsulphate, 2-methyloctylsulphate, 2-ethyloctylsulphate, 2-propyloctylsulphate, 2-isopropyloctylsulphate, 2-butyloctylsulphate, 2-pentyloctylsulphate, 2-hexyloctylsulphate, 2-heptyloctylsulphate, 3-methylbutylsulphate, 3-ethylbutylsulphate, 3-propylbutylsulphate, 3-isopropylbutylsulphate, 3-methylpentylsulphate, 3-ethylpentylsulphate, 3-propylpentylsulphate, 3-isopropylpentylsulphate, 3-butylpentylsulphate, 3-methylhexylsulphate, 3-ethylhexylsulphate, 3-propylhexylsulphate, 3-isopropylhexylsulphate, 3-butylhexylsulphate, 3-pentylhexylsulphate, 3-methylheptylsulphate, 3-ethylheptylsulphate, 3-propylheptylsulphate, 3-isopropylheptylsulphate, 3-butylheptylsulphate, 3-pentylheptylsulphate, 3-hexylheptylsulphate, 3-methyloctylsulphate, 3-ethyloctylsulphate, 3-propyloctylsulphate, 3-isopropyloctylsulphate, 3-butyloctylsulphate, 3-pentyloctylsulphate, 3-hexyloctylsulphate, 3-heptyloctylsulphate, and mixtures thereof.

More preferably the branched short chain alkyl sulphate surfactant is selected from the list of 1-methylpentylsulphate, 1-ethylpentylsulphate, 1-propylpentylsulphate, 1-butylpentylsulphate, 1-methylhexylsulphate, 1-ethylhexylsulphate, 1-propylhexylsulphate, 1-butylhexylsulphate, 1-pentylhexylsulphate, 1-methylheptylsulphate, 1-ethylheptylsulphate, 1-propylheptylsulphate, 1-butylheptylsulphate, 1-pentylheptylsulphate, 1-hexylheptylsulphate, 2-methylpentylsulphate, 2-ethylpentylsulphate, 2-propylpentylsulphate, 2-butylpentylsulphate, 2-methylhexylsulphate, 2-ethylhexylsulphate, 2-propylhexylsulphate, 2-butylhexylsulphate, 2-pentylhexylsulphate, 2-methylheptylsulphate, 2-ethylheptylsulphate, 2-propylheptylsulphate, 2-butylheptylsulphate, 2-pentylheptylsulphate, 2-hexylheptylsulphate, 3-methylpentylsulphate, 3-ethylpentylsulphate, 3-propylpentylsulphate, 3-butylpentylsulphate, 3-methylhexylsulphate, 3-ethylhexylsulphate, 3-propylhexylsulphate, 3-butylhexylsulphate, 3-pentylhexylsulphate, 3-methylheptylsulphate, 3-ethylheptylsulphate, 3-propylheptylsulphate, 3-butylheptylsulphate, 3-pentylheptylsulphate, 3-hexylheptylsulphate, and mixtures thereof.

Even more preferably the branched short chain alkyl sulphate surfactant is selected from the list of 2-methylpentylsulphate, 2-ethylpentylsulphate, 2-propylpentylsulphate, 2-butylpentylsulphate, 2-methylhexylsulphate, 2-ethylhexylsulphate, 2-propylhexylsulphate, 2-butylhexylsulphate, 2-pentylhexylsulphate, 2-methylheptylsulphate, 2-ethylheptylsulphate, 2-propylheptylsulphate, 2-butylheptylsulphate, 2-pentylheptylsulphate, 2-hexylheptylsulphate, and mixtures thereof.

Even more preferably the branched short chain alkyl sulphate surfactant is selected from the list of 2-methylpentylsulphate, 2-ethylpentylsulphate, 2-propylpentylsulphate, 2-methylhexylsulphate, 2-ethylhexylsulphate, 2-propylhexylsulphate, 2-methylheptylsulphate, 2-ethylheptylsulphate, 2-propylheptylsulphate, and mixtures thereof.

Most preferred branched short chain alkyl sulphate surfactant is 2-ethylhexylsulphate. This compound is commercially available under the Syntapon EH tradename from Enaspol and Empicol 0585U from Huntsman.

The branched short chain alkyl sulphate surfactant will be formulated from about 3% to about 10%, preferably from about 4% to about 8% by weight of the composition.

The branched short chain alkyl sulphate surfactant will be formulated from about 50% to about 100%, preferably from about 55% to about 75% by weight of the total surfactant composition.

Amphoteric surfactant


5 Preferably the amphoteric surfactant is an amine oxide. Preferred amine oxides are alkyl dimethyl amine oxide or alkyl amido propyl dimethyl amine oxide, more preferably alkyl dimethyl amine oxide and especially coco dimethyl amino oxide. Amine oxide may have a linear or mid-branched alkyl moiety. Typical linear amine oxides include water-soluble amine oxides containing one R1 C8-18 alkyl moiety and 2 R2 and R3 moieties selected from the group
10 consisting of C1-3 alkyl groups and C1-3 hydroxyalkyl groups. Preferably amine oxide is characterized by the formula $R1 - N(R2)(R3) O$ wherein R1 is a C8-18 alkyl and R2 and R3 are selected from the group consisting of methyl, ethyl, propyl, isopropyl, 2-hydroxyethyl, 2-hydroxypropyl and 3-hydroxypropyl. The linear amine oxide surfactants in particular may include linear C10-C18 alkyl dimethyl amine oxides and linear C8-C12 alkoxy ethyl dihydroxy
15 ethyl amine oxides. Preferred amine oxides include linear C10, linear C10-C12, and linear C12-C14 alkyl dimethyl amine oxides. As used herein "mid-branched" means that the amine oxide has one alkyl moiety having n1 carbon atoms with one alkyl branch on the alkyl moiety having n2 carbon atoms. The alkyl branch is located on the α carbon from the nitrogen on the alkyl moiety. This type of branching for the amine oxide is also known in the art as an internal amine
20 oxide. The total sum of n1 and n2 is from 10 to 24 carbon atoms, preferably from 12 to 20, and more preferably from 10 to 16. The number of carbon atoms for the one alkyl moiety (n1) should be approximately the same number of carbon atoms as the one alkyl branch (n2) such that the one alkyl moiety and the one alkyl branch are symmetric. As used herein "symmetric" means that $|n1 - n2|$ is less than or equal to 5, preferably 4, most preferably from 0 to 4 carbon
25 atoms in at least 50 wt%, more preferably at least 75 wt% to 100 wt% of the mid-branched amine oxides for use herein.

The amine oxide further comprises two moieties, independently selected from a C1-3 alkyl, a C1-3 hydroxyalkyl group, or a polyethylene oxide group containing an average of from about 1
30 to about 3 ethylene oxide groups. Preferably the two moieties are selected from a C1-3 alkyl, more preferably both are selected as a C1 alkyl.

Zwitterionic surfactant

Other suitable surfactants include zwitterionic surfactants, preferably betaines, such as alkyl betaines, alkylamidobetaine, amidazoliniumbetaine, sulfobetaine (INCI Sultaines) as well as the

5 Phosphobetaine and preferably meets formula (I):



(I)

wherein

10 R1 is a saturated or unsaturated C6-22 alkyl residue, preferably C8-18 alkyl residue, in particular a saturated C10-16 alkyl residue, for example a saturated C12-14 alkyl residue;

X is NH, NR₄ with C1-4 Alkyl residue R₄, O or S,

n a number from 1 to 10, preferably 2 to 5, in particular 3,

x 0 or 1, preferably 1,

15 R₂, R₃ are independently a C1-4 alkyl residue, potentially hydroxy substituted such as a hydroxyethyl, preferably a methyl.

m a number from 1 to 4, in particular 1, 2 or 3,

y 0 or 1 and

Y is COO, SO₃, OPO(OR₅)O or P(O)(OR₅)O, whereby R₅ is a hydrogen atom H or a C1-4 alkyl residue.

20

Preferred betaines are the alkyl betaines of the formula (Ia), the alkyl amido propyl betaine of the formula (Ib), the Sulfo betaines of the formula (Ic) and the Amido sulfobetaine of the formula (Id);





R1-CO-NH-(CH₂)₃-N+(CH₃)₂-CH₂CH(OH)CH₂SO₃⁻ (Id) in which R11 as the same meaning as in formula I. Particularly preferred betaines are the Carbobetaine [wherein Y=COO⁻], in particular the Carbobetaine of the formula (Ia) and (Ib), more preferred are the Alkylamidobetaine of the formula (Ib).

Examples of suitable betaines and sulfobetaine are the following [designated in accordance with INCI]: Almondamidopropyl of betaines, Apricotamidopropyl betaines, Avocamidopropyl of betaines, Babassuamidopropyl of betaines, Behenamidopropyl betaines, Behenyl of betaines, betaines, Canolamidopropyl betaines, Capryl/Capram idopropyl betaines, Carnitine, Cetyl of betaines, Cocamidopropyl of betaines, Cocamidopropyl betaines, Cocamidopropyl Hydroxysultaine, Coco betaines, Coco Hydroxysultaine, Coco/Oleamidopropyl betaines, Coco Sultaine, Decyl of betaines, Dihydroxyethyl Oleyl Glycinate, Dihydroxyethyl Soy Glycinate, Dihydroxyethyl Stearyl Glycinate, Dihydroxyethyl Tallow Glycinate, Dimethicone Propyl of PG-betaines, Erucamidopropyl Hydroxysultaine, Hydrogenated Tallow of betaines, Isostearam idopropyl betaines, Lauramidopropyl betaines, Lauryl of betaines, Lauryl Hydroxysultaine, Lauryl Sultaine, Milkamidopropyl betaines, Minkamidopropyl of betaines, Myristamidopropyl betaines, Myristyl of betaines, Oleamidopropyl betaines, Oleamidopropyl Hydroxysultaine, Oleyl of betaines, Olivamidopropyl of betaines, Palmamidopropyl betaines, Palm itamidopropyl betaines, Palmitoyl Carnitine, Palm Kernelamidopropyl betaines, Polytetrafluoroethylene Acetoxypropyl of betaines, Ricinoleamidopropyl betaines, Sesamidopropyl betaines, Soyamidopropyl betaines, Stearamidopropyl betaines, Stearyl of betaines, Tallowamidopropyl betaines, Tallowamidopropyl Hydroxysultaine, Tallow of betaines, Tallow Dihydroxyethyl of betaines, Undecylenamidopropyl betaines and Wheat Germamidopropyl betaines.

A preferred betaine is, for example, Cocoamidopropylbetaine.

Non ionic surfactant

Nonionic surfactant, when present, is comprised in a typical amount of from 0.1% to 10%, preferably 0.2% to 8%, most preferably 0.5% to 6% by weight of the composition. Suitable nonionic surfactants include the condensation products of aliphatic alcohols with from 1 to 25

moles of ethylene oxide. The alkyl chain of the aliphatic alcohol can either be straight or branched, primary or secondary, and generally contains from 8 to 22 carbon atoms. Particularly preferred are the condensation products of alcohols having an alkyl group containing from 10 to 18 carbon atoms, preferably from 10 to 15 carbon atoms with from 2 to 18 moles, preferably 2 to 15, more preferably 5-12 of ethylene oxide per mole of alcohol. Highly preferred nonionic surfactants are the condensation products of guerbet alcohols with from 2 to 18 moles, preferably 2 to 15, more preferably 5-12 of ethylene oxide per mole of alcohol.

Other suitable non-ionic surfactants for use herein include fatty alcohol polyglycol ethers, alkylpolyglucosides and fatty acid glucamides.

Glycol ether solvent

The composition of the invention comprises a glycol ether solvent selected from glycol ethers of Formula I or Formula II.

Formula I = $R_1O(R_2O)_nR_3$

wherein

R_1 is a linear or branched C_4 , C_5 or C_6 alkyl, a substituted or unsubstituted phenyl, preferably n-butyl. Benzyl is one of the substituted phenyls for use herein.

R_2 is ethyl or isopropyl, preferably isopropyl

R_3 is hydrogen or methyl, preferably hydrogen

n is 1, 2 or 3, preferably 1 or 2

Formula II = $R_4O(R_5O)_nR_6$

wherein

R_4 is n-propyl or isopropyl, preferably n-propyl

R_5 is isopropyl

R6 is hydrogen or methyl, preferably hydrogen

n is 1, 2 or 3 preferably 1 or 2

Suitable glycol ether solvents according to Formula I include ethyleneglycol n-butyl ether,
5 diethyleneglycol n-butyl ether, triethyleneglycol n-butyl ether, propyleneglycol n-butyl ether,
dipropyleneglycol n-butyl ether, tripropyleneglycol n-butyl ether, ethyleneglycol n-pentyl ether,
diethyleneglycol n-pentyl ether, triethyleneglycol n-pentyl ether, propyleneglycol n-pentyl ether,
dipropyleneglycol n-pentyl ether, tripropyleneglycol n-pentyl ether, ethyleneglycol n-hexyl
10 ether, diethyleneglycol n-hexyl ether, triethyleneglycol n-hexyl ether, propyleneglycol n-hexyl
ether, dipropyleneglycol n-hexyl ether, tripropyleneglycol n-hexyl ether, ethyleneglycol phenyl
ether, diethyleneglycol phenyl ether, triethyleneglycol phenyl ether, propyleneglycol phenyl
ether, dipropyleneglycol phenyl ether, tripropyleneglycol phenyl ether, ethyleneglycol benzyl
ether, diethyleneglycol benzyl ether, triethyleneglycol benzyl ether, propyleneglycol benzyl
15 ether, dipropyleneglycol benzyl ether, tripropyleneglycol benzyl ether, ethyleneglycol isobutyl
ether, diethyleneglycol isobutyl ether, triethyleneglycol isobutyl ether, propyleneglycol isobutyl
ether, dipropyleneglycol isobutyl ether, tripropyleneglycol isobutyl ether, ethyleneglycol
isopentyl ether, diethyleneglycol isopentyl ether, triethyleneglycol isopentyl ether,
propyleneglycol isopentyl ether, dipropyleneglycol isopentyl ether, tripropyleneglycol isopentyl
20 ether, ethyleneglycol isohexyl ether, diethyleneglycol isohexyl ether, triethyleneglycol isohexyl
ether, propyleneglycol isohexyl ether, dipropyleneglycol isohexyl ether, tripropyleneglycol
isohexyl ether, ethyleneglycol n-butyl methyl ether, diethyleneglycol n-butyl methyl ether
triethyleneglycol n-butyl methyl ether, propyleneglycol n-butyl methyl ether, dipropyleneglycol
n-butyl methyl ether, tripropyleneglycol n-butyl methyl ether, ethyleneglycol n-pentyl methyl
25 ether, diethyleneglycol n-pentyl methyl ether, triethyleneglycol n-pentyl methyl ether,
propyleneglycol n-pentyl methyl ether, dipropyleneglycol n-pentyl methyl ether,
tripropyleneglycol n-pentyl methyl ether, ethyleneglycol n-hexyl methyl ether, diethyleneglycol
n-hexyl methyl ether, triethyleneglycol n-hexyl methyl ether, propyleneglycol n-hexyl methyl
ether, dipropyleneglycol n-hexyl methyl ether, tripropyleneglycol n-hexyl methyl ether,
ethyleneglycol phenyl methyl ether, diethyleneglycol phenyl methyl ether, triethyleneglycol
30 phenyl methyl ether, propyleneglycol phenyl methyl ether, dipropyleneglycol phenyl methyl
ether, tripropyleneglycol phenyl methyl ether, ethyleneglycol benzyl methyl ether,
diethyleneglycol benzyl methyl ether, triethyleneglycol benzyl methyl ether, propyleneglycol
benzyl methyl ether, dipropyleneglycol benzyl methyl ether, tripropyleneglycol benzyl methyl

ether, ethyleneglycol isobutyl methyl ether, diethyleneglycol isobutyl methyl ether, triethyleneglycol isobutyl methyl ether, propyleneglycol isobutyl methyl ether, dipropyleneglycol isobutyl methyl ether, tripropyleneglycol isobutyl methyl ether, ethyleneglycol isopentyl methyl ether, diethyleneglycol isopentyl methyl ether, triethyleneglycol isopentyl methyl ether, propyleneglycol isopentyl methyl ether, dipropyleneglycol isopentyl methyl ether, tripropyleneglycol isopentyl methyl ether, ethyleneglycol isohexyl methyl ether, diethyleneglycol isohexyl methyl ether, triethyleneglycol isohexyl methyl ether, propyleneglycol isohexyl methyl ether, dipropyleneglycol isohexyl methyl ether, tripropyleneglycol isohexyl methyl ether, and mixtures thereof.

- 10 Preferred glycol ether solvents according to Formula I are ethyleneglycol n-butyl ether, diethyleneglycol n-butyl ether, triethyleneglycol n-butyl ether, propyleneglycol n-butyl ether, dipropyleneglycol n-butyl ether, tripropyleneglycol n-butyl ether, and mixtures thereof.

Most preferred glycol ethers according to Formula I are propyleneglycol n-butyl ether, dipropyleneglycol n-butyl ether, and mixtures thereof.

15

Suitable glycol ether solvents according to Formula II include propyleneglycol n-propyl ether, dipropyleneglycol n-propyl ether, tripropyleneglycol n-propyl ether, propyleneglycol isopropyl ether, dipropyleneglycol isopropyl ether, tripropyleneglycol isopropyl ether, propyleneglycol n-propyl methyl ether, dipropyleneglycol n-propyl methyl ether, tripropyleneglycol n-propyl methyl ether, propyleneglycol isopropyl methyl ether, dipropyleneglycol isopropyl methyl ether, tripropyleneglycol isopropyl methyl ether, and mixtures thereof.

Preferred glycol ether solvents according to Formula II are propyleneglycol n-propyl ether, dipropyleneglycol n-propyl ether, and mixtures thereof.

- 25 Most preferred glycol ether solvents are propyleneglycol n-butyl ether, dipropyleneglycol n-butyl ether, and mixtures thereof, especially dipropyleneglycol n-butyl ether.

Suitable glycol ether solvents can be purchased from The Dow Chemical Company, more particularly from the E-series (ethylene glycol based) Glycol Ethers and the P-series (propylene glycol based) Glycol Ethers line-ups. Suitable glycol ether solvents include Butyl Carbitol,

30

Hexyl Carbitol, Butyl Cellosolve, Hexyl Cellosolve, Butoxytriglycol, Dowanol Eph, Dowanol PnP, Dowanol DPnP, Dowanol PnB, Dowanol DPnB, Dowanol TPnB, Dowanol PPh, and mixtures thereof.

The glycol ether of the product of the invention can boost foaming.

- 5 The glycol ether solvent typically is present from about 1% to about 10%, preferably from about 2 to about 8%, most preferably from about 3% to about 7% by weight of the composition.

Chelant

- The composition herein may optionally further comprise a chelant at a level of from 0.1% to 10%, preferably from 0.2% to 5%, more preferably from 0.2% to 3%, most preferably from 0.5%
10 to 1.5% by weight of the composition.

Suitable chelating agents can be selected from the group consisting of amino carboxylates, amino phosphonates, polyfunctionally-substituted aromatic chelating agents and mixtures thereof.

- 15 Amino carboxylates include ethylenediaminetetra-acetates, N-hydroxyethylethylenediaminetriacetates, nitrilo-triacetates, ethylenediamine tetrapropionates, triethylenetetraaminehexacetates, diethylenetriaminepentaacetates, and ethanoldiglycines, alkali metal, ammonium, and substituted ammonium salts therein and mixtures therein, as well as MGDA (methyl-glycine-diacetic acid), and salts and derivatives thereof and GLDA (glutamic-
20 N,N- diacetic acid) and salts and derivatives thereof. GLDA (salts and derivatives thereof) is especially preferred according to the invention, with the tetrasodium salt thereof being especially preferred.

Builder

- The composition herein may comprise a builder, preferably a carboxylate builder. Salts of
25 carboxylic acids useful herein include salts of C1-6 linear or at least 3 carbon containing cyclic acids. The linear or cyclic carbon-containing chain of the carboxylic acid or salt thereof may be substituted with a substituent group selected from the group consisting of hydroxyl, ester, ether, aliphatic groups having from 1 to 6, more preferably 1 to 4 carbon atoms, and mixtures thereof.

Preferred salts of carboxylic acids are those selected from the salts from the group consisting of salicylic acid, maleic acid, acetyl salicylic acid, 3 methyl salicylic acid, 4 hydroxy isophthalic acid, dihydroxyfumaric acid, 1,2, 4 benzene tricarboxylic acid, pentanoic acid, citric acid, and mixtures thereof, preferably citric acid.

- 5 Alternative carboxylate builders suitable for use in the composition of the invention includes salts of fatty acids like palm kernel derived fatty acids or coconut derived fatty acid, or salts of polycarboxylic acids.

The cation of the salt is preferably selected from alkali metal, alkaline earth metal, monoethanolamine, diethanolamine or triethanolamine and mixtures thereof, preferably sodium.

- 10 The carboxylic acid or salt thereof, when present, is preferably present at the level of from 0.1% to 5%, more preferably from 0.2% to 1% by weight of the total composition.

Shear thinning rheology modifier

- 15 The composition according to the invention might further comprise a rheology modifying agent, providing a shear thinning rheology profile to the product. Preferably the rheology modifying agent is a non crystalline polymeric rheology modifier. This polymeric rheology modifier can be a synthetic or a naturally derived polymer.

- 20 Examples of naturally derived polymeric structurants of use in the present invention include: hydroxyethyl cellulose, hydrophobically modified hydroxyethyl cellulose, carboxymethyl cellulose, polysaccharide derivatives and mixtures thereof. Polysaccharide derivatives include but are not limited to pectine, alginate, arabinogalactan (gum Arabic), carrageenan, gum karaya, gum tragacanth, gellan gum, xanthan gum and guar gum. Examples of synthetic polymeric structurants of use in the present invention include polymers and copolymers comprising polycarboxylates, polyacrylates, polyurethanes, polyvinylpyrrolidone, polyols and derivatives
25 and mixtures thereof.

Preferably the composition according to the invention comprises a naturally derived rheology modifying polymer, most preferably Xanthan Gum.

- 30 Generally, the rheology modifying polymer will be comprised at a level of from 0.001% to 1% by weight, alternatively from 0.01% to 0.5% by weight, more alternatively from 0.05% to 0.25% by weight of the composition.

Further optional ingredients

The composition herein may comprise a number of optional ingredients such as rheology trimming agents selected from inorganic salts preferably sodium chloride, C2-C4 alcohols, C2-
5 C4 polyols, poly alkylene glycols, hydrotropes, and mixtures thereof. The composition might also comprise pH trimming and/or buffering agents such as sodium hydroxyde, alkanolamines including monoethanolamine, and bicarbonate inorganic salts. The composition might comprise further minor ingredients selected from preservatives, UV stabilizers, antioxidants, perfumes, coloring agents and mixtures thereof.

10

Viscosity

The flow curve of products is measured with the use of a Rheometer (TA instruments – model DHR1), a Peltier concentric cylinder temperature system (TA instruments) and a double gap cup and rotor (TA instruments). The flow curve procedure comprises a conditioning step and a flow
15 ramp step at 20°C, the conditioning step comprising a 30s pre-shear step at a shear rate of 10s-1 followed by a 120s zero shear equilibration time. The flow ramp step comprises a Logarithmical shear rate increase from 0.001 s-1 to 10000 s-1 in a time span of 300s. A data filter is set at the instrument recommended minimum torque value of 20µNm.

“Low shear viscosity” is defined as the viscosity measured at a shear rate of 100 s-1. “High shear
20 viscosity” is measured at a shear rate of 10000 s-1.

Spray dispenser

The spray dispenser comprises a housing to accommodate the composition of the invention and spraying means. Suitable spray dispensers include hand pump (sometimes referred to as
25 "trigger") devices, pressurized can devices, electrostatic spray devices, etc. Preferably the spray dispenser is non-pressurized and the spray means are of the trigger dispensing type. Preferably the spray dispenser is non-pressurized and the spray means are of the trigger dispensing type.

Examples

Cleaning provided by compositions inside and outside the scope of the invention is assessed by means of a whiteness index defined following the procedure described below.

Cooked oil soil preparation

- 5 Soil preparation prior to baking is carried out at ambient temperature of 21°C+2°C. All used products should be acclimatized within this temperature range.

Corn oil (Supplier: Vandemoortele - Item: #1001928), peanut oil (Supplier: Vandemoortele - Item: #1002974) and sunflower oil (Supplier: Vandemoortele - Item: #1001926) are mixed in equal weight amounts. Whilst mixing, 1wt.% black dye (Supplier: AMRESCO - Item: Sudan Black B #0593) is added on top. Mixing is continued afterwards for 1 hour.

- 10 20g of the above mixture is then put in a Borosilicate Glass baking dish (Supplier: Pyrex – Item: sku232B000) and baked in an oven at 135°C for 16hours. After baking, the Pyrex plate is put overnight in a humidity cabinet at 25 °C and 70% humidity level. The polymerized oil is then collected in a glass vial.

Tile preparation and camera setup

- 15 With the help of a paint roller, cooked oil is applied to a ceramic white tile (Supplier: Sphinx – Item: White tile 20cmX25cm #H083001) until a uniform layer is obtained (1.25g +/- 0.1g of oil required). The tile is placed on a flat surface. With the help of a stand, a photo-camera is placed at approximately 63cm above the tile.

Test execution

- 20 The test is carried out at ambient temperature of 21°C+2°C. All used products should be acclimatized within this temperature range.

- The test is conducted pairwise on one tile, with a standard benchmark during every run. With the help of a Pasteur pipette (Supplier: VWR – Item: 5ml #612-1684) one drop of product is pipetted to the tile from a height of approx. 10cm. This is done, in parallel/synchronized, with the benchmark product, each in the middle of one half of the tile. A timer is started, right after products are pipetted to the tile. A picture is taken after 30 seconds product exposure.
- 25

Product Assessment

Afterwards, with the help of the picture, the test product is compared to the reference and a grading number on the cleanness of the diffusion area (whiteness index):

-4: Negative WOW / -3: Definitely worse / -2: I see it's worse / -1: I Think it's worse

0: reference

+1: I Think it's better / +2: I see it's better / +3: Definitely better / +4: Positive WOW

5 Composition

% active by weight of the composition	Example 1	Comparative Example 1	Comparative Example 2	Comparative Example 3	Comparative Example 4	Comparative Example 5 Dreft Power Spray Belgium	Comparative Example 6 Method HDW Spray Market Product Bottle code: 14205A
Water and minors (preservative, perfume, dye)	To 100 parts	To 100 parts	To 100 parts	n.a.	To 100 parts	To 100 parts	
Sodium Chloride	-	-	-	-	0.11	-	
Sodium bicarbonate	0.1	0.5	0.1	-	-	-	
Ethanol	0.34	0.34	0.34	-	0.215	-	
Polypropylene glycol	0.05	0.05	0.05	-	0.12	-	
Sodium Cumene Sulphonate	-	-	-	-	-	4.56	

EPh Glycol ether	-	-	-	-	-	5
DPnB Glycol Ether	5	5	-	100	-	5
Mono-ethanolamine	0.5	-	0.5	-	-	5
L-glutamic acid N,N-diacetic acid, tetra sodium salt	1	0.25	1	-	-	-
Citric Acid	-	0.25	-	-	-	-
TPK Fatty Acid	-	0.84	-	-	-	-
Acusol 823	-	-	-	-	-	1.5
Laponite RDS	-	-	-	-	-	0.31
Laponite RD	-	-	-	-	-	0.31
Sodium Silicate	-	-	-	-	-	0.30
Potassium carbonate	-	-	-	-	-	1
Sodium Hydroxide	-	0.62	-	-	0.02	0.64
Alkyl Ethoxy Sulphate (C24EO0.6)	-	-	-	-	0.2253	-
2-Ethyl Hexyl Sulphate	5.4	-	5.4	-	-	-
Lin. Alkyl Benzene Sulfonate	-	1.5	-	-	-	-
Alkyl Dimethyl	3.6	1.3	-	-	0.644	1

Amine Oxide (C12-14)						
C10 (Guerbet) alcohol 8 Ethoxylated	-	-	-	-	0.044	-
Non-ionic Alkyl Ethoxylate (C9-11EO8)	-	5.2	-	-	-	-
Xanthan Gum	0.15	-	0.15	-	-	-
pH (10% dilution in distilled water)	10.5	10.1	10.5	n.a.	9.1	11.4

Results

Example 1 represents a composition according to the invention. Comparative examples 2 to 6 represent compositions outside the scope of the invention. Comparative example 1 has a surfactant system outside the scope of the invention. Comparative examples 3 and 4 are single variable deviations of example formula 1 from which respectively the solvent according to the invention has been removed (comparative example 2) or tested in isolation (comparative example 3). Comparative example 4 represents a low active version of a traditional surfactant based hand dish formulation liquid, while comparative example 5 represents a detergent spray composition used as a pre-treater for automatic dishwashing applications. Comparative example 6 is an in market hand dishwashing spray product (2015) from the “Method” company. From the data in the table below it is clear that a composition according to the invention has the highest cleanness of the diffusion area after 30 seconds product exposure time, compared to the comparative examples outside of the scope of the invention.

Reference product	Test product	Whiteness Index (the higher the better)
Comparative example 1	Example 1	+2
Comparative example 1	Comparative example 2	+1
Comparative example 1	Comparative example 3	No cleaning observed*
Comparative example 1	Comparative example 4	+1
Comparative example 1	Comparative example 5	-2
Comparative example 1	Comparative example 6	0

*Solvent shifts soil outside product application area with no soil emulsification or solubilization happening. No grading applied as different and inferior (i.e. no cleaning) effect observed.

The dimensions and values disclosed herein are not to be understood as being strictly limited to the exact numerical values recited. Instead, unless otherwise specified, each such dimension is intended to mean both the recited value and a functionally equivalent range surrounding that value. For example, a dimension disclosed as “40 mm” is intended to mean “about 40 mm”

CLAIMS

What is claimed is:

1. A cleaning product comprising a spray dispenser and a cleaning composition suitable for spraying and foaming, the composition housed in the spray dispenser wherein the composition comprises:
 - i) a surfactant system comprising a branched short chain alkyl sulfate and a co-surfactant selected from the group consisting of amphoteric surfactant, zwitteronic surfactant and mixtures thereof; and
 - ii) a glycol ether solvent selected from the group consisting of glycol ethers of Formula I: $R1O(R2O)_nR3$, Formula II: $R4O(R5O)_nR6$ and mixtures thereofwherein
R1 is a linear or branched C4, C5 or C6 alkyl, a substituted or unsubstituted phenyl, R2 is ethyl or isopropyl, R3 is hydrogen or methyl and n is 1, 2 or 3
R4 is n-propyl or isopropyl, R5 is isopropyl, R6 is hydrogen or methyl and n is 1, 2 or 3.
2. A product according the claim 1 wherein the surfactant system and the solvent are in a weight ratio of from about 4:1 to about 1:1.
3. A product according to any of the preceding claims wherein the composition comprises at least 5% by weight of the composition of the surfactant system.
4. A product according to any of the preceding claim wherein the branched short chain alkyl sulfate is a hexyl sulfate, preferably 2-ethyl hexyl sulfate.
5. A product according to any of the preceding claims wherein the surfactant system comprises a non-sulphated branched short chain alcohol.
6. A product according to any of the preceding claims wherein the co-surfactant is an amphoteric surfactant comprising amine oxide surfactant.
7. A product according to any of the preceding claims wherein the branched short chain alkyl sulfate and the co-surfactant are present in a weight ratio of about 4:1 to about 1:1.
8. A product according to any of the preceding claims wherein the composition comprises from about 1% to about 7% by weight of the composition of the glycol ether solvent.
9. A product according to any of the preceding claims wherein the glycol ether solvent is selected from the group consisting of comprises dipropylene glycol n-butyl ether, propyleneglycol n-butyl ether and mixtures thereof.
10. A product according to any of the preceding claims wherein the composition has a pH greater than 8, preferably from 10.5 to 11.5 as measured at 10% solution in distilled

water at 20°C and a reserve alkalinity of from about 0.1 to about 1 expressed as g NaOH/ 100ml of composition at a pH of 10.

11. A product according to any of the preceding claims wherein the composition has a reserve alkalinity of from about 0.1 to about 0.5 expressed as g NaOH/ 100ml of composition at a pH of 10.
12. A product according to any of the preceding claims wherein the composition has a pH of from 10 to 11.5 as measured in a 10% solution in distilled water at 20°C, a reserve alkalinity of from 0.1 to 0.3, expressed as g NaOH/ 100ml of composition at a pH of 10, the composition comprising:
 - i) 4 to 10% by weight of the composition of a branched short chain sulfate, preferably 2-ethyl hexyl sulfate,
 - ii) 1 to 5% by weight of the composition of amine oxide surfactant; and
 - iii) 3% to 8% by weight of the composition of glycol ether solvent, preferably dipropylene glycol n-butyl ether.
13. A product according to any of the preceding claims wherein the composition further comprises a chelant, preferably an aminocarboxylate chelant, more preferably a salt of glutamic-N,N- diacetic acid.
14. A product according to any of the preceding claims wherein the composition further comprises a builder, preferably citrate.
15. A product according to any of the preceding claims wherein the composition further comprises bicarbonate.
16. A product according to any of the preceding claims wherein the composition further comprises an alkanol amine, preferably monoethanol amine.
17. A product according to any of the preceding claims wherein the composition further comprises a further solvent selected from the group consisting of C2-C4 alcohols, C2-C4 polyols, poly alkylene glycol and mixtures thereof.
18. A product according to any of the preceding claims wherein the composition has a high shear viscosity (at 10,000 s⁻¹) of from about 1 to about 20 mPa s at 20°C as measured using the method defined herein.
19. A product according to the preceding claim wherein the composition has a low shear (100 s⁻¹) to high shear viscosity ratio of from about 10:1 to about 1.5:1 at 20°C as measured using the method defined herein.
20. A product according to any of the preceding claims wherein the composition comprises xanthan gum.

21. A method of cleaning soiled dishware using the product according to any of the preceding claims comprising the steps of:
- a) optionally pre-wetting the soiled dishware;
 - b) spraying the cleaning composition onto the soiled dishware;
 - c) optionally adding water to the soiled dishware during a period of time;
 - d) optionally scrubbing the dishware; and
 - e) rinsing the dishware.

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2016/040269

A. CLASSIFICATION OF SUBJECT MATTER

INV. C11D1/75 C11D1/83 C11D1/94 C11D3/20 C11D3/43
C11D17/04

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 2 431 455 A1 (PROCTER & GAMBLE) 21 March 2012 (2012-03-21) paragraphs [0001], [0062], [0071], [0139], [0124]; claims -----	1-21
X	WO 99/19441 A1 (PROCTER & GAMBLE) 22 April 1999 (1999-04-22) page 7, line 18 - page 7, line 35; claims; examples -----	1-21
X	EP 0 839 907 A1 (PROCTER & GAMBLE) 6 May 1998 (1998-05-06) page 8, line 20 - line 44; examples -----	1-21
X	EP 0 805 197 A1 (PROCTER & GAMBLE) 5 November 1997 (1997-11-05) page 5, line 25 - line 43; claims; examples ----- -/-	1-21

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

8 September 2016

Date of mailing of the international search report

16/09/2016

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Hillebrecht, Dieter

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2016/040269

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 99/43778 A1 (RECKITT & COLMAN INC) 2 September 1999 (1999-09-02) page 15, line 12 - line 23; claims; examples -----	1-21
X	WO 91/15565 A1 (BUCKEYE INT) 17 October 1991 (1991-10-17) examples 4,10 -----	1-21

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/040269

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 2431455	A1	21-03-2012	EP 2431455 A1 21-03-2012
		JP 5864584 B2	17-02-2016
		JP 2013545827 A	26-12-2013
		US 2012071379 A1	22-03-2012
		WO 2012040141 A1	29-03-2012
WO 9919441	A1	22-04-1999	AT 234910 T 15-04-2003
		CA 2306469 A1	22-04-1999
		DE 69812396 D1	24-04-2003
		DE 69812396 T2	19-02-2004
		EP 0916718 A1	19-05-1999
		EP 1023427 A1	02-08-2000
		ES 2191965 T3	16-09-2003
		US 6537955 B1	25-03-2003
		WO 9919441 A1	22-04-1999
EP 0839907	A1	06-05-1998	CA 2219653 A1 29-04-1998
		EP 0839907 A1	06-05-1998
		US 6211124 B1	03-04-2001
EP 0805197	A1	05-11-1997	AR 006940 A1 29-09-1999
		AU 2815997 A	26-11-1997
		BR 9709584 A	02-05-2000
		CA 2252716 A1	13-11-1997
		CN 1232488 A	20-10-1999
		CZ 9803514 A3	14-04-1999
		EG 20926 A	28-06-2000
		EP 0805197 A1	05-11-1997
		HU 0002498 A2	28-11-2000
		JP 2000514847 A	07-11-2000
		TR 9802215 T2	21-06-2001
		WO 9742278 A1	13-11-1997
		ZA 9703710 B	25-11-1997
WO 9943778	A1	02-09-1999	AR 018566 A1 28-11-2001
		AU 750018 B2	11-07-2002
		AU 2574399 A	15-09-1999
		CA 2319491 A1	02-09-1999
		DE 69903611 D1	28-11-2002
		DE 69903611 T2	26-06-2003
		EP 1056822 A1	06-12-2000
		ES 2181393 T3	16-02-2003
		GB 2334721 A	01-09-1999
		MY 133521 A	30-11-2007
		US 6022840 A	08-02-2000
		WO 9943778 A1	02-09-1999
		ZA 9901467 B	22-03-2000
WO 9115565	A1	17-10-1991	AU 7694991 A 30-10-1991
		CA 2080352 A1	11-10-1991
		DE 69131928 D1	24-02-2000
		DE 69131928 T2	17-08-2000
		EP 0525032 A1	03-02-1993
		JP 2528053 B2	28-08-1996
		JP H05507300 A	21-10-1993
		US 5080822 A	14-01-1992
		WO 9115565 A1	17-10-1991